AutoSave Off PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only Proprietary* • Last Modified: 12 February Search
File Home Insert Draw Page Layout Formulas Data Review View Automate Help Comments Share
Paste Cut Copy Format Painter Clipboard Arial 11 Font Wrap Text Merge & Center Alignment General Number Conditional Formatting Format as Table Cell Styles Styles Insert Delete Format Cells AutoSum Fill Clear Sort & Filter Find & Select Editing Sensitivity Sensitivity Add-ins Add-ins Copilot

E33 If LOTN>=5, then assign LOT5SD= INIT + line_of_therapy/line_of_therapy_start_timedelta where line_of_therapy/line_of_therapy=5;

	A	B	C	D	E	F
1	Time Period	Variable	Label	Values	Definition	Additional Notes
23	FU	LOT3CAT	LOT3 Treatments - CAT			Single value per patient. For each patient, copy the variable to all cohorts they belong to.
24	FU	LOT3CATN	LOT3 Treatments - CAT (N)		Numeric version of LOT3CAT	Single value per patient. For each patient, copy the variable to all cohorts they belong to.
25	FU	LOT3REGN	Number of treatment regimens in LOT3	numeric	If LOTN>=3, then LOT3REGN is the number of rows in regimen table where regimen/line_of_therapy=3 for that patient; else if LOTN<3, then assign LOT3REGN=. (missing).	Single value per patient. For each patient, copy the variable to all cohorts they belong to.
26	FU	LOT4SD	LOT4 Start Date	date	If LOTN>=4, then assign LOT4SD = INIT + line_of_therapy/line_of_therapy_start_timedelta where line_of_therapy/line_of_therapy = 4; else if LOTN<4, then assign LOT4SD=. (missing).	Single value per patient. For each patient, copy the variable to all cohorts they belong to. Specs note: Linked from variable LOT4SD in 4.StudyPop
27	FU	LOT4ED	LOT4 End Date	date	If LOTN>=4, then assign LOT4ED= INIT + line_of_therapy/line_of_therapy_end_timedelta where line_of_therapy/line_of_therapy=4; else if LOTN<4, then assign LOT4ED=. (missing).	Single value per patient. For each patient, copy the variable to all cohorts they belong to.
28	FU	LOT4	LOT4 drug names, grouped by regimen	character	If LOTN>=4, then assign LOT4=line_of_therapy/line_of_therapy_name where line_of_therapy/line_of_therapy=4; else if LOTN<4, then assign LOT4=. (missing).	Single value per patient. For each patient, copy the variable to all cohorts they belong to.
29	FU	LOT4NAME	LOT4 regimen names, grouped by regimen	character	If LOT4 is not missing, then assign LOT4NAME by mapping the drug names to the corresponding regimen name. The mapping is avaialble with regimen/regimen_name and regimen/regiment_drugs else if LOT4=., then assign LOT4NAME=. (missing).	Single value of LOT4NAME per patient. For each patient, copy the variable to all cohorts they belong to: For example, if patient has LOT4=[Cyclophosphamide, Doxorubicin, Prednisone, Rituximab, Vincristine][Bendamustine], then LOT4NAME=[R-CHOP][Bendamustine monotherapy]
30	FU	LOT4CAT	LOT4 Treatments - CAT			Single value per patient. For each patient, copy the variable to all cohorts they belong to.
31	FU	LOT4CATN	LOT4 Treatments - CAT (N)		Numeric version of LOT4CAT	Single value per patient. For each patient, copy the variable to all cohorts they belong to.
32	FU	LOT4REGN	Number of treatment regimens in LOT4	numeric	If LOTN>=4, then LOT4REGN is the number of rows in regimen table where regimen/line_of_therapy=4 for that patient; else if LOTN<4, then assign LOT4REGN=. (missing).	Single value per patient. For each patient, copy the variable to all cohorts they belong to.
33	FU	LOT5SD	LOT5 Start Date	date	If LOTN>=5, then assign LOT5SD= INIT + line_of_therapy/line_of_therapy_start_timedelta where line_of_therapy/line_of_therapy=5; else if LOTN<5, then assign LOT5SD=. (missing).	Single value per patient. For each patient, copy the variable to all cohorts they belong to. Note: needed to define outcomes time to next and 2nd next treatment.
34	FU	LOT6SD	LOT6 Start Date	date	If LOTN>=6, then assign LOT6SD= INIT + line_of_therapy/line_of_therapy_start_timedelta where line_of_therapy/line_of_therapy=6; else if LOTN<6, then assign LOT6SD=. (missing).	Single value per patient. For each patient, copy the variable to all cohorts they belong to. Note: needed to define outcomes time to next and 2nd next treatment.
	INDEX for treated cohort FU for overall/untreated	*CSD*	*Presence of Clinical Study Drug*		*Regimen is 'Clinical Study Drug' in the DrugEpisode table where the line of therapy (and maintenancetherapy flag) match the index line then=1; else 0* *If COHORT="Overall advNSCLC" then index(Linename "CSD") then 1 else 0*	

1.Cover 2.QC Review 3.Data Prep 4.StudyPop 5A. Demos 5B.ClinChars 5C.BioVars 5D.LabVars 6.TreatVars 7.Outcomes
Ready Accessibility: Investigate Display Settings 90%

AutoSave Off PROG_SPEC_RWDAP_DLBCL_DRAFT_Jan2026.xlsm - Read-Only Proprietary* • Last Modified: 12 February Search
Comments Share
File Home Insert Draw Page Layout Formulas Data Review View Automate Help
Paste Cut Copy Format Painter Clipboard Arial 11 Font Wrap Text Merge & Center Alignment General Number Conditional Formatting Format as Table Cell Styles Styles Insert Delete Format Cells AutoSum Fill Clear Sort & Filter Find & Select Editing Sensitivity Add-ins Copilot

E45 If LOTN>=5, then assign LOT5SD= INIT + line_of_therapy/line_of_therapy_start_timedelta where line_of_therapy/line_of_therapy=5;

Time Period	Variable	Label	Values	Definition	Additional Notes

INDEX for treated cohort
FU for overall/untreated
	CSD	Presence of Clinical Study Drug	1 = Yes, 0 = No	Regimen is 'Clinical Study Drug' in the DrugEpisode table where the line of therapy (and maintenancetherapy flag) match the index line then=1, else 0
				
				If COHORT="Overall advNSCLC" then index(Linename,"CSD") then 1 else 0;
				if COHORT="L1+ treated advNSCLC" then index(LOT1,"CSD") then 1 else 0;
				if COHORT="L1m+ treated advNSCLC" then index(LOT1m,"CSD") then 1 else 0;
				if COHORT="L2+ treated advNSCLC" then index(LOT2,"CSD") then 1 else 0;
				if COHORT="L3+ treated advNSCLC" then index(LOT3,"CSD") then 1 else 0;	

PRE_INIT/FU Cohort dependent	LOT1MSD	LOT1 Maintenance Start Date	date	t_&cohort_lineoftherapy_&date where enhancedcohort='AdvancedNSCLC' and linenumber=1 and upper(ismaintenancetherapy)='TRUE' value of STARTDATE_SASDT	
PRE_INIT/FU Cohort dependant	LOT1MED	LOT1 Maintenance End Date (Derived)	DATE	from t_nsc_drugepisode where linenumber=1 and upper(ismaintenancetherapy)='TRUE' , max value of EPISODEDATE_SASDT	
PRE_INIT/FU Cohort dependant	LOT1M	LOT1 Maintenance Treatments	character	t_&cohort_lineoftherapy_&date where enhancedcohort='AdvancedNSCLC' and linenumber=1 and upper(ismaintenancetherapy)='TRUE' value of LINENAME ADD 'No Maintenance' for people without maintenance	

1.Cover 2.QC Review 3.Data Prep 4.StudyPop 5A. Demos 5B.ClinChars 5C.BioVars 5D.LabVars 6.TreatVars 7.Outcomes
Ready Accessibility: Investigate Display Settings 90%