



البرمجة بلغة ++C

جنى الخطاب

Q1) What is the output of the following code?

```
#include<iostream>
using namespace std;
int main()
{
    int x = 2, y = 2;
    if (x * y != y + y)
        cout << "A";
    if (y * y <= x)
        cout << "B";
    else
        cout << "A";
    cout << "B" endl;
    return 0;
}
```

- A) BA
- B) AAB
- C) BB
- D) BAB
- E) AB

Q2)

What is the output of the following code?

```
#include<iostream>
using namespace std;
int main()
{
    int x = 3, y=4;
    if(x >= y--)
```

```
cout<< x++;  
else  
/*x += 2;  
cout<< x;*/
```

```
cout<< ++x;  
cout<<y;  
return 0;  
}
```

- A)44
- B)353
- C)33
- D)43
- E)Error

Q3)

What is the output of the following code ?

```
#include <iostream>  
using namespace std;
```

```
int main()
```

```
{
```

```
int y = 1;
```

```
int x = ++y;
```

```
if (x != y && x == 1)
```

```
x = y + 1;
```

```
if(y >= x);
```

```
x = x*2;
```

```
if(x + y >= 0 || false)
x++;
cout<< x <<" "<<y;
return 0;
}
```

A) 3 2

B) 5 2

C) 1 2

D) 4 2

E) 3 1

Q4) Which of the following expressions evaluates to false ?

Note that ASCII value for :

'A' = 65, 'B' = 66, 'C' = 67, 'D' = 68, 'E' = 69 'a' = 97, 'b' = 98, 'c' = 99, 'd' = 100, 'e' = 101

A) ("REDApplE" <="REDBan")

B) (12 - 5 % 2 < 4 || 'e'>='E')

C) ('e'== 99+1 && 5+2)

D) (3.5< 5 +3.2)

Q5)What is the output?

```
#include <iostream>
```

```
using namespace std;
```

```
int main()
```

```
{
```

```
double ch;
```

```
cout<<"enter a value between 1 to 2:";
```

```
cin>>ch;
```

```
switch (ch)
```

```
{  
case 1:  
cout<<"1";  
break;  
case 2:  
cout<<"2";  
break;  
}  
return o;  
}
```

- A)Varies
- B)Compile time error
- C)2
- D)1

Q6) What is the output of the following code?

```
int myNum = 10;  
int yourNum = 30;  
if (yourNum % myNum == 3)  
{  
yourNum = 3;  
myNum = 1;  
}  
else if (yourNum % myNum == 2)  
{  
yourNum = 2;  
myNum = 2;  
}
```

```
else
{
yourNum = 1;
myNum = 3;
}
cout << myNum << " " << yourNum << endl;
```

- A) 2 2
- B) 10 30
- C) 3 1
- D) 1 3

Q7) Suppose the input is 5. What is the value of alpha after the following C++ code executes?

```
int alpha;
cin >> alpha;
switch (alpha)
{
case 1:
case 2:
    alpha = alpha + 2;
break;
case 4:
    alpha++;
case 5:
    alpha = 2 * alpha;
case 6:
    alpha = alpha + 5;
break;
default:
```

```
alpha--;
```

```
}
```

```
cout <<endl<<alpha;
```

A)10

B)5

C)14

E)15

Answer Key:

1) E

2) D

3) B

4) C

5) A

6) C

7) E

DONE BY:Jana Khattb.