

X

NPTEL

singh.santosh2702@gmail.com ▼

Courses » Problem Solving through Programming in C[Announcements](#) [Course](#) [Ask a Question](#) [Progress](#) [Mentor](#) [FAQ](#)

Unit 4 - Week 3

Course outline

How to access the portal

Week 1

Week 2

Week 3

- ☐ Lecture 11 :
Assignment
Statement and
Operators in C
- ☐ Lecture 12 :
Arithmetic
Expressions
and Relational
Expressions
- ☐ Lecture 13 :
Logical
Operators and
Change in
Control Flow
- ☐ Lecture 14 :
Use of Logical
Operators in
Branching
- ☐ Lecture 15 :
Branching : IF
- ELSE
Statement
- ☒ Quiz :
Assignment 3
- ☐ Practice
Problem-1

Assignment 3

Due date for this assignment: 2018-09-06, 23:59 IST.

- 1) The precedence of arithmetic operators is (from highest to lowest) 1 point
- ☒ %, *, /, +, -
 - ☐ %, +, /, *, -
 - ☐ +, -, %, *, /
 - ☐ %, +, -, *, /
- 2) Which of the following operator takes only integer operands? 1 point
- ☐ +
 - ☐ /
 - ☐ *
 - ☐ %
- 3) Which of the following method are accepted for assignment? 1 point
- ☐ 8=x=y=z
 - ☐ x=8=y=z
 - ☐ x=y=z=8
 - ☐ None
- 4) Which of the following statement is correct? 1 point
- ☐ Operator precedence determines which operator is performed first in an expression with more than one operator with different precedence. Associativity is used when two operators of same precedence appear in an expression
 - ☐ Operator associativity determines which operator is performed first in an expression with more than one operator with different associativity. Precedence is used when two operators of same precedence appear in an expression.
 - ☐ Operator precedence and associativity are same.
 - ☐ None of the above.

☐ Practice
Problem-2

☐ Practice
Problem-3

☐ Practice
Problem-4

☐ Feedback for
Week 3

Week 4

Download Videos

Assignment Solution

5) What is the output of the following program?

1 point

```
#include <stdio.h>
main()
{
    float i = -3.0;
    int k = i % 2;
    printf("%d", k);
}
```

- ☐ -1
☐ 1
☐ 0
☐ Compilation error

6) Compute the value of x of the C program given below

1 point

```
#include <stdio.h>
main()
{
    int x = 5 * 5 / 3 + 9;
}
```

- ☐ 17.33
☐ 14
☐ 17
☐ Depends on compiler

7) What is the output of the following program?

1 point

```
#include<stdio.h>
main()
{
    int a=10, b=3, c;
    float d;
    c=a%b;
    d=a/b;
    printf("Value of c and d are %d and %f respectively",c, d);
}
```

- ☐ Value of c and d are 1 and 3 respectively
☐ Value of c and d are 1 and 3.333333 respectively
☐ Value of c and d are 1.000000 and 3.000000 respectively
☒ Value of c and d are 1 and 3.000000 respectively

8) Find the output of the following C code

1 point

```
#include<stdio.h>
main()
{
    int a=10, b=3, c=2, d=4, result;
    result=a+a*-b/c%d+c*d;
    printf("%d", result);
}
```

- ☐ -42

- ☐ 24
- ☐ 15
- ☐ -34

9) What is the output of the following C code?

1 point

```
#include <stdio.h>
main()
{
    int y = 2;
    int z = y +(y == 10);
    printf("%d\n", z);
}
```

- ☐ 12
- ☐ 2
- ☐ 20
- ☐ Compiler error

10. The output of the following program will be

1 point

```
#include<stdio.h>
main()
{
    int a=0,b=1,c=-1;
    if(a)
        printf("IITKGP \n");
    if(b)
        printf("IITM \n");
    if(c)
        printf("IITR \n");
}
```

- ☐ IITKGP
- ☐ IITM IITR
- ☐ IITM
- ☐ IITR
- ☐ IITKGP
- ☐ IITR

11 What is the output of the following program?

1 point

```
#include<stdio.h>
int main()
{
    int i;
    if(i=0,2,3)
        printf("NPTEL ");
    else
        printf("Programming on C ");
    printf("%d\n",i);
}
```

- ☐ Programming on C 0
- ☐ NPTEL 0

- ☐ NPTEL 3
- ☐ Compilation error

12 Find the output of the following program.

1 point

```
#include <stdio.h>
main()
{
    int x = 5;
    if (x>=6);
    printf("hello");
}
```

- ☐ It will display hello
- ☐ It will throw an error
- ☐ Nothing will be displayed
- ☐ Compiler dependent

13 What will be the output?

1 point

```
#include<stdio.h>
int main()
{
    int a;
    a = 10, 20, 30;
    printf("%d", a);
    return 0;
}
```

- ☐ 10
- ☐ 20
- ☐ 30
- ☐ Compilation error

14 What will be the output?

1 point

```
#include <stdio.h>
int main()
{
    int a = 100, b = 200, c = 300;
    if (c > b > a)
        printf("TRUE");
    else
        printf("FALSE");
    return 0;
}
```

- ☐ TRUE
- ☐ FALSE
- ☐ Syntax Error
- ☐ Compilation Error

1 point

15. What will be the output?

```
#include<stdio.h>
int main()
{
    int x;
    x= 5>7+3 && 8;
    printf("%d", x);
    return 0;
}
```

- ☐ 0
- ☐ 1
- ☐ 9
- ☐ Compilation error

1 point

16. What will be the output?

```
#include<stdio.h>
int main()
{
    int x;
    x= 10==20!=30;
    printf("%d", x);
    return 0;
}
```

- ☐ 0
- ☐ 1
- ☐ 10
- ☐ 30

1 point

17. What will be the output?

```
#include <stdio.h>
int main()
{
    int x=2;
    if(x=1)
        printf("TRUE");
    else
        printf("FALSE");
    return 0;
}
```

- ☐ TRUE
- ☐ FALSE
- ☐ Compilation Error
- ☐ Compiler Dependent

1 point

18 What will be the output?

```
#include <stdio.h>
int main()
{
    if( (-10 && 10)|| (20 && -20) )
        printf("Condition is true.");
    else
        printf("Condition is false.");
    return 0;
}
```

- ☐ Condition is true
- ☐ Condition is false
- ☐ Error
- ☐ No output possible

1 point

19 What will be the output?

```
#include <stdio.h>
#define TRUE 1
int main()
{
    if(TRUE)
        printf("1");
        printf("2");
    else
        printf("3");
        printf("4");
    return 0;
}
```

- ☐ 1 2 3 4
- ☐ 1 2
- ☐ Compilation error
- ☐ 3 4

1 point

20 Which of the following are incorrect statements? If int a=7.

- 1) if(a==7) printf("IncludeHelp");
- 2) if(7==a) printf("IncludeHelp");
- 3) if(a=7) printf("IncludeHelp");
- 4) if(7=a) printf("IncludeHelp");

- ☐ 1 and 2.
- ☐ 3 only.
- ☐ 4 only.
- ☐ 2,3 and 4.

You may submit any number of times before the due date. The final submission will be considered for grading.

[Submit Answers](#)

[Previous Page](#)[End](#)

© 2014 NPTEL - Privacy & Terms - Honor Code - FAQs -



A project of



In association with



Funded by

Government of India
Ministry of Human Resource Development

Powered by

