Cheatsheets: Claude Code Workflow Cheatsheet (2026 Edition)

References & Companions, Chapter 3/4 — Revision & Viva-Prep Cheatsheet (English + Roman Urdu)
Source: agentfactory.panaversity.org/docs/cheatsheets

EN: 16 dense reference panels, not prose -- install, CLAUDE.md memory, skills/hooks/permissions, architecture, models, CI/CD, MCP, multi-agent work, git/PR, and cost management.
Roman Urdu: 16 dense reference panels, prose nahi -- install, CLAUDE.md memory, skills/hooks/permissions, architecture, models, CI/CD, MCP, multi-agent work, git/PR, aur cost management.

1. CLAUDE.md Memory + Skills/Hooks/Permissions

- **Memory hierarchy:** ~/.claude/CLAUDE.md (global) -> CLAUDE.md (project) -> .claude/CLAUDE.md (project alt) -> ./src/CLAUDE.md (subfolder, APPENDS, never overwrites). Keep under 200 lines.
- Skills: .claude/skills/name/SKILL.md -- the description field is CRITICAL for auto-activation. Hooks: PreToolUse/PostToolUse/Notification -- exit code 0=allow, 2=block.

2. Architecture + Daily Workflow

- **4-Layer Architecture:** L1 CLAUDE.md -> L2 Skills -> L3 Hooks -> L4 Agents.
- **Daily 8-step pattern:** cd+claude -> Plan Mode (Shift+Tab) -> describe intent -> Auto Accept -> !git status -> /compact -> Ctrl+B (background) -> Esc Esc (rewind).

3. Models, CI/CD, MCP + Multi-Agent

- Models: claude-opus (deep reasoning), claude-sonnet (balanced daily), claude-haiku (fastest/cheapest). Context up to 1M tokens, auto-compression.
- Non-interactive: claude -p '...' --output-format json --allowedTools Read,Grep, auth via ANTHROPIC_API_KEY.
- Subagents (isolated parallel workers) vs Agent Teams (team lead + shared task list + mailbox). /loop 5m repeats on interval. Git: secret scanning BLOCKS commits containing API keys/tokens.

4. Cost Management

- Try /compact first, /clear only if still off-track. /cost checks spend. Start fresh sessions roughly every ~20 turns.

Key Terms Cheatsheet

One line each — English + Roman Urdu.

Term	English	Roman Urdu
Memory hierarchy	Global -> project -> project-alt -> subfolder CLAUDE.md, each appending not overwriting.	Global -> project -> project-alt -> subfolder CLAUDE.md, har ek append karta, overwrite nahi.
Hook exit codes	0 = allow, 2 = block.	0 = allow, 2 = block.
4-Layer Architecture	L1 CLAUDE.md, L2 Skills, L3 Hooks, L4 Agents.	L1 CLAUDE.md, L2 Skills, L3 Hooks, L4 Agents.
Subagents vs Agent Teams	Isolated parallel workers vs a team lead + shared task list + mailbox.	Isolated parallel workers vs team lead + shared task list + mailbox.
Secret scanning	Blocks commits containing API keys/tokens automatically.	API keys/tokens wale commits automatically block karta.

Quick Self-Check

Question	Answer
What's the correct order for the CLAUDE.md memory hierarchy, and how do lower levels interact with higher ones?	Global -> project -> project-alt -> subfolder, and each level APPENDS to the ones above it rather than overwriting.
What do hook exit codes 0 and 2 mean?	0 = allow the action to proceed; 2 = block it.
What's the 4-Layer Architecture, in order?	L1 CLAUDE.md -> L2 Skills -> L3 Hooks -> L4 Agents.
What's the difference between Subagents and Agent Teams?	Subagents are isolated parallel workers; Agent Teams have a team lead plus a shared task list and mailbox for coordination.
What should you try before /clear when a session goes off-track?	/compact first -- /clear is the fallback only if compacting doesn't fix it.

Where This Leads / Sources

Pure reference card, no further chapter dependency. Full 15-Q quiz in 06-test-your-understanding.

Source: docs/cheatsheets/ (this repo), content originally via Zia Tutor AI connector.