

Samadhan Setu (समाधान सेतु)

Civic Issue Reporting & Governance Platform with Proof of Work

Comprehensive Line-by-Line Code Breakdown, Cryptographic Flowcharts & System Schemas

TECHNOLOGY STACK

Next.js 14 • Supabase • Deno Edge Functions • PostgreSQL

GEOSPATIAL ANTI-CHEAT

Haversine Radius ($\leq 75m$) • 50m GPS Bounding • 2-Min Clock Sync

SECURITY & INTEGRITY

Cryptographic Hash Chaining (SHA-256) • HMAC Anonymization • RLS

ALGORITHMIC GOVERNANCE

Multi-Factor Officer Dispatch • Automated Nightly CRON Score Engine

Document Scope: This engineering manual provides an exhaustive, line-by-line analysis of all database migrations, PostgreSQL stored procedures, Deno Edge Functions, and core frontend interfaces powering the Samadhan Setu civic accountability ecosystem.

1. System Architecture & Execution Topology

Samadhan Setu is designed from first principles to solve the fundamental flaw in modern civic governance: **the lack of tamper-evident accountability**. Traditional grievance portals permit verbal closure without verifiable physical proof. Samadhan Setu establishes a tamper-evident workflow connecting citizens, civic authorities, and field officers through hardware-bound photographic proof, cryptographic hash chaining, and automated performance tracking.




Figure 1.1: Multi-tier System Architecture from Client PWAs to Deno Edge Functions and PostgreSQL RLS

Core Architectural Tenets:

- **Privacy by Design:** Citizens are pseudonymized using HMAC-SHA256 tokens derived from (user_id || complaint_id). No phone numbers or wallet IDs appear on public records.
- **Proof-of-Work Chaining:** Resolutions form an immutable hash-chained ledger (Blockchain-style SHA-256 blocks), ensuring that physical repairs cannot be forged, retrofitted, or substituted.
- **Anti-Spoofing Sensors:** Native device camera access (blocking gallery uploads), ≤50m GPS accuracy checks, and a strict 120-second server clock synchronization window.
- **Automated Work Allocation:** Multi-factor algorithmic ranking balancing officer historical reliability, open workload, and idle recency.

2. End-to-End Civic Issue Lifecycle Flowchart

The complete complaint lifecycle advances through seven strictly validated states: `filed` → `assigned` → `in_progress` → `work_completed` → `under_review` → `resolved` → `reopened`. All state mutations are mediated exclusively by service-role Deno Edge Functions with immutable audit logging.




Figure 2.1: Complete Civic Workflow Flowchart: Citizen Capture, Duplicate Triage, Proof Chaining, and Citizen Verification

3. Proof of Work: Cryptographic Hash Chaining

To prevent field personnel or contracting agencies from retrofitting completion photos or taking images from social media, every resolution submission creates an immutable block anchored to the complaint's history.



Figure 3.1: Resolution Block Structure and Recursive SHA-256 Chaining Protocol

Mathematical Hash Chaining Formulation:
Each resolution block B_n calculates its unique record_hash as:
$$\text{record_hash} = \text{SHA256}(\text{complaint_id} + \text{officer_id} + \text{after_photo_hash} + \text{lat} + \text{long} + \text{resolved_at} + \text{previous_hash})$$

where previous_hash equals "GENESIS" for the initial repair block, or $H(n-1)$ for recurring/reopened work. Altering any coordinate, image byte, or timestamp alters the hash and invalidates the entire audit chain.

Intelligent Officer Allocation Algorithm & Graph

When an authority requests officer recommendations via GET /authority-assignments/suggestions?complaint_id=..., the system evaluates all active officers in the matching civic domain using a multi-factor optimization formula:




Figure 3.2: Multi-Factor Scoring Weight Matrix and Live Candidate Optimization Comparison

4. Database Entity-Relationship (ER) Architecture

The database schema comprises 10 relational tables, 6 custom PostgreSQL ENUM types, spatial indexes, and Row Level Security policies implemented in PostgreSQL 15.




Figure 4.1: PostgreSQL Entity Relationship Diagram with Primary Keys, Foreign Keys, and Security Enforcements

5. Line-by-Line Code Breakdown: Database Migrations

This chapter examines the exact SQL migration scripts executed to initialize the Samadhan Setu database schema, constraints, stored procedures, and security policies.

5.1 Core Relational Schema (20260914000100_vericity_schema.sql)

LINES	SOURCE CODE	ARCHITECTURAL LINE-BY-LINE EXPLANATION
Lines 1-9	<pre>create extension if not exists pgcrypto; create type public.authority_type as enum ('in_house_officer', 'external_agency'); create type public.complaint_status as enum ('filed','assigned','in_progress','work_completed','under_review','resolved','reopened'); create type public.assignment_status as enum ('assigned','accepted','in_progress','work_completed','authority_review','resolved','reopened'); create type public.verification_verdict as enum ('confirmed','disputed'); create type public.priority_level as enum ('low','normal','high','urgent'); create type public.review_status as enum ('pending','approved','rejected','reassigned');</pre>	Foundation & Security Machine Enumerations: • Line 1: Enable: <code>pgcrypto</code> Post extension, power UUIDv4 generation (<code>gen_random_uuid</code>) and cryptographic hashing inside database procedures. • Lines 3-9: Dec strict domain-specific Postgres ENUMs enforcing rigid schema machines across complaint lifecycle, officer assignment, authority review, verification verdict. Invalid states are rejected at the database engine level.
Lines 10-14	<pre>create table public.citizen_wallets (wallet_id uuid primary key references auth.users(id) on delete cascade, reputation_score numeric(5,2) not null default 50.00 check (reputation_score between 0 and 100), created_at timestampz not null default now());</pre>	Citizen Wallet & Reputation Ledger • Line 11: Links <code>wallet_id</code> directly to Supabase's internal <code>auth.users(id)</code> cascading foreign key. • Line 12: Every starts with a base reputation of 50 (constrained between 0.00 and 100.00). Confirmed resolution boost reputation while fraudulent rejected complaints trigger penalties.
Lines 16-40	<pre>create table public.domains (id uuid primary key default gen_random_uuid(), name text not null unique, created_at timestampz not null default now()); create table public.authorities (id uuid primary key references auth.users(id) on delete cascade, name text not null, type public.authority_type not null, domain_id uuid references public.domains(id), tenure_start date, tenure_end date, performance_score numeric(5,2) not null default 50.00 check (performance_score between 0 and 100), created_at timestampz not null default now()); create table public.domain_authority_map (domain_id uuid not null references public.domains(id), authority_id uuid not null references public.authorities(id), effective_from timestampz not null default now(), effective_to timestampz, primary key (domain_id, authority_id, effective_from), check (effective_to is null or effective_to > effective_from));</pre>	Governance Domains & Authority Mappings • Lines 16-20: Domain: municipal civic center (Road, Streetlight, Water, Waste). • Lines 22-31: Authority: government departments and contracting agencies. Tracks their ongoing performance score (default 50.00). • Lines 33-40: Mapping: Implements temporal mapping (<code>effective_from</code> to <code>effective_to</code>) domains to responsibilities, ensures audit historical accuracy even if jurisdictional transfers.

Lines	Source Code	Architecture, Line-by-Line Explanation
Lines 42-52	<pre> create table public.officers (id uuid primary key references auth.users(id) on delete cascade, officer_id text unique not null check (officer_id ~ '^OFF-[0-9]{4,}\$'), name text not null, role text, authority_id uuid not null references public.authorities(id), domain_id uuid references public.domains(id), active boolean not null default true, performance_score numeric(5,2) not null default 50.00 check (performance_score between 0 and 100), created_at timestamptz not null default now()); </pre>	Field Officer ID & Identity Check • Line 44: Enforces strict regex check (^OFF-[0-9]{4,}), human-readable badges (e.g. OFF1042). • Line 47: Binds to their parent municipal authority preventing cross-agency case leak. • Line 50: Performance score (0–100) dynamically recalculated by a CRON based on punctuality and
Lines 54-80	<pre> create table public.complaints (id uuid primary key default gen_random_uuid(), wallet_id uuid not null references public.citizen_wallets(wallet_id), derived_citizen_id text not null unique, domain_id uuid not null references public.domains(id), description text check (char_length(description) <= 3000), before_photo_url text not null, lat numeric(9,6) not null check (lat between -90 and 90), long numeric(9,6) not null check (long between -180 and 180), status public.complaint_status not null default 'filed', assigned_authority_id uuid references public.authorities(id), duplicate_of uuid references public.complaints(id), upvote_count integer not null default 0 check (upvote_count >= 0), created_at timestamptz not null default now()); create table public.complaint_upvotes (id uuid primary key default gen_random_uuid(), complaint_id uuid not null references public.complaints(id) on delete cascade, wallet_id uuid not null references public.citizen_wallets(wallet_id), derived_citizen_id text not null, photo_url text not null, lat numeric(9,6) check (lat between -90 and 90), long numeric(9,6) check (long between -180 and 180), created_at timestamptz not null default now(), unique (complaint_id, wallet_id)); </pre>	Core Complaint Upvote Corroboration • Line 57: <code>derived_citizen_id</code> Cryptographic Hash pseudonym allows public tracking without leaking the citizen's wallet UUID, protecting identity. • Lines 61-62: Stores decimal coordinate precision (±0.11 precision on Earth). • Line 65: <code>duplicate_of</code>: referential foreign key pointing to the first complaint if near-duplicate was detected. • Lines 70-80: <code>complaint_upvotes</code> Requires citizens upvoting an issue to submit their own corroborating proof + GPS location, preventing bot manipulation.
Lines 82-108	<pre> create table public.case_assignments (id uuid primary key default gen_random_uuid(), complaint_id uuid not null references public.complaints(id) on delete cascade, officer_id uuid not null references public.officers(id), assigned_by uuid not null references public.authorities(id), assigned_at timestamptz not null default now(), deadline timestamptz, priority public.priority_level not null default 'normal', status public.assignment_status not null default 'assigned'); create table public.resolutions (id uuid primary key default gen_random_uuid(), complaint_id uuid not null references public.complaints(id) on delete cascade, officer_id uuid not null references public.officers(id), after_photo_url text not null, after_photo_hash text not null, lat numeric(9,6) not null check (lat between -90 and 90), long numeric(9,6) not null check (long between -180 and 180), resolved_at timestamptz not null default now(), officer_note text check (char_length(officer_note) <= 3000), previous_hash text, record_hash text not null unique, review_status public.review_status not null default 'pending', reviewed_by uuid references public.authorities(id), reviewed_at timestamptz); </pre>	Assignments & of-Work Resolution Ledger: • Lines 82-91: Tracks authority dispatch field staff with explicit deadlines and priorities. • Lines 93-108: <code>resolutions</code> form immutable cryptographic ledger. <code>after_photo_hash</code> stores the SHA-256 digest of the physical resolution image. • Line 103: <code>previous_hash</code> links to the prior state ("GENESIS" for initial resolution). • Line 104: <code>record_hash</code> is a unique SHA-256 chained hash tying complaint, officer, photo hash, coordinates, time, and previous hash together.

LINES	SOURCE CODE	ARCHITECTURE LINE-BY-LINE EXPLANATION
Lines 110-136	<pre> create table public.verifications (id uuid primary key default gen_random_uuid(), complaint_id uuid not null references public.complaints(id) on delete cascade, wallet_id uuid not null references public.citizen_wallets(wallet_id), derived_citizen_id text not null, verdict public.verification_verdict not null, comment text check (char_length(comment) <= 3000), created_at timestampz not null default now(), unique (complaint_id, wallet_id)); create table public.audit_log (id bigint generated always as identity primary key, actor_type text not null check (actor_type in ('citizen','authority','officer','system')), actor_id text, action text not null, entity_type text not null, entity_id uuid, metadata jsonb not null default '{}':jsonb, created_at timestampz not null default now()); create index complaints_domain_status_idx on public.complaints(domain_id, status); create index complaints_active_geo_idx on public.complaints(domain_id, created_at desc) where status <> 'resolved'; create index assignments_officer_status_idx on public.case_assignments(officer_id, status); create index resolutions_complaint_resolved_idx on public.resolutions(complaint_id, resolved_at desc); </pre>	Citizen Verification Audit Trail & Q Indices: • Lines 110-119 the citizen to co-dispute resolved UNIQUE(complaint_id, wallet_id) pre-ballot stuffing. • Lines 121-130 Append-only immutable audit capturing all state changes by actor across the system • Lines 132-136 performance padding compound B-tree indexes for fast and lifecycle queries (e.g. active complaints filtered where status <> 'resolved')
Lines 139-177	<pre> create view public.complaints_public with (security_invoker = false) as select id, derived_citizen_id, domain_id, description, before_photo_url, lat, long, status, assigned_authority_id, duplicate_of, upvote_count, created_at from public.complaints; grant usage on schema public to anon, authenticated; grant select on public.complaints_public to anon, authenticated; alter table public.citizen_wallets enable row level security; ... insert into storage.buckets (id, name, public, file_size_limit, allowed_mime_types) values ('complaint-evidence', 'complaint-evidence', false, 10485760, array['image/jpeg','image/png','image/webp']) on conflict (id) do nothing; create policy "authenticated evidence upload" on storage.objects for insert to authenticated with check (bucket_id = 'complaint-evidence' and (storage.foldername(name))[1] = auth.uid()::text); </pre>	Public Privacy Projection & Strict Isolation: • Lines 140-144 complaints_public deliberately omits internal wallet and user phone exposing only derived_citizen_id • Lines 148-158 Level Security (RLS) enabled on all 1 • Lines 169-177 Private encrypted storage bucket (complaint-evidence) 10MB limit, image only. Storage permissions enforce folder is authenticated user only write and read inside <auth.uid()>/

5.2 Geospatial Math & Stored Procedures (20260914000200_vericity_helpers.sql)

LINES	SOURCE CODE
Lines 1-9	<pre>create or replace function public.distance_meters(lat1 numeric, lon1 numeric, lat2 numeric, lon2 numeric) returns numeric language sql immutable strict as \$\$ select 6371000 * acos(least(1, greatest(-1, cos(radians(lat1::double precision)) * cos(radians(lat2::double precision)) * cos(radians(lon2::double precision) - radians(lon1::double precision)) + sin(radians(lat1::double precision)) * sin(radians(lat2::double precision))))) \$\$;</pre>
Lines 11-25	<pre>create or replace function public.nearby_complaints(p_domain_id uuid, p_lat numeric, p_long numeric) returns table (id uuid, domain_id uuid, description text, before_photo_url text, lat numeric, long numeric, status public.complaint_status, created_at timestampz, language sql stable security definer set search_path = public as \$\$ select c.id, c.domain_id, c.description, c.before_photo_url, c.lat, c.long, c.status, c.created_at, public.distance_meters(p_lat, p_long, c.lat, c.long) as distance_meters from public.complaints c where c.domain_id = p_domain_id and c.status <> 'resolved' and c.created_at > now() - interval '30 days' and public.distance_meters(p_lat, p_long, c.lat, c.long) <= 75 order by distance_meters asc; \$\$;</pre>
Lines 27-41	<pre>create or replace function public.increment_upvote(complaint_uuid uuid) returns void language sql security definer set search_path = public as \$\$ update public.complaints set upvote_count = upvote_count + 1 where id = complaint_uuid; \$\$; create or replace function public.adjust_reputation(target_wallet uuid, delta numeric) returns void language sql security definer set search_path = public as \$\$ update public.citizen_wallets set reputation_score = greatest(0, least(100, reputation_score + delta)) where wallet_id = target_wallet; \$\$;</pre>

6. Line-by-Line Code Breakdown: Supabase Edge Functions

Samadhan Setu backend mutations are executed exclusively via Deno-based Supabase Edge Functions. Direct client mutations to complaints, assignments, resolutions, and reputation tables are denied by RLS.

6.1 Shared Microservice Utilities (`_shared/core.ts`)

LINES	SOURCE CODE
Lines 1-14	<pre>import { createClient, SupabaseClient, User } from "https://esm.sh/@supabase/supabase-js@2"; export const corsHeaders = { "Access-Control-Allow-Origin": "*", "Access-Control-Allow-Headers": "authorization, x-client-info, apikey, content-type, x-cron-secret", "Access-Control-Allow-Methods": "GET, POST, OPTIONS", }; export const json = (body: unknown, status = 200) => new Response(JSON.stringify(body), { status, headers: { ...corsHeaders, "Content-Type": "application/json" }, }); export const fail = (message: string, status = 400) => json({ error: message }, status); export const options = () => new Response("ok", { headers: corsHeaders });</pre>
Lines 16-35	<pre>export function adminClient(): SupabaseClient { return createClient(Deno.env.get("SUPABASE_URL")!, Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!, { auth: { autoRefreshToken: false, persistSession: false }, }); } export async function authenticatedUser(req: Request): Promise<{ user?: User; error?: Response }> { const token = req.headers.get("Authorization")?.replace(/^Bearer\s+/i, ""); if (!token) return { error: fail("Missing bearer token", 401) }; const client = createClient(Deno.env.get("SUPABASE_URL")!, Deno.env.get("SUPABASE_ANON_KEY")!, { auth: { autoRefreshToken: false, persistSession: false }, global: { headers: { Authorization: `Bearer \${token}` } }, }); const { data, error } = await client.auth.getUser(); return error !data.user ? { error: fail("Invalid session", 401) } : { user: data.user }; } export function requireRole(user: User, role: "citizen" "authority" "officer"): Response undefined { return user.app_metadata?.role === role ? undefined : fail("Forbidden", 403); }</pre>
Lines 37-64	<pre>export function validLocation(lat: unknown, long: unknown): boolean { return typeof lat === "number" && typeof long === "number" && Number.isFinite(lat) && Number.isFinite(long) && lat >= -90 && lat <= 90 && long >= -180 && long <= 180; } export function requestPath(req: Request): string[] { const marker = "/functions/v1/"; const part = new URL(req.url).pathname.split(marker)[1] ?? ""; return part.split("/").filter(Boolean); } export async function audit(admin: SupabaseClient, actorType: string, actorId: string null, action: string, entityType: string, entityId: string null, metadata: unknown) { const { error } = await admin.from("audit_log").insert({ actor_type: actorType, actor_id: actorId, action, entity_type: entityType, entity_id: entityId, metadata }); if (error) console.error("audit write failed", error.message); } export async function sha256(value: string): Promise<string> { const bytes = new TextEncoder().encode(value); const hash = await crypto.subtle.digest("SHA-256", bytes); return Array.from(new Uint8Array(hash)).map((b) => b.toString(16).padStart(2, "0")).join(""); } export async function hmac(value: string): Promise<string> { const secret = Deno.env.get("HMAC_SECRET"); if (!secret) throw new Error("HMAC_SECRET is not configured"); const key = await crypto.subtle.importKey("raw", new TextEncoder().encode(secret), { name: "HMAC", hash: "SHA-256" }, false, ["sign"]); const sig = await crypto.subtle.sign("HMAC", key, new TextEncoder().encode(value)); return Array.from(new Uint8Array(sig)).map((b) => b.toString(16).padStart(2, "0")).join(""); }</pre>

6.2 Complaint Registration, Nearby & Upvoting (complaints/index.ts)

LINES	SOURCE CODE
Lines 3-13	<pre>Deno.serve(async (req) => { if (req.method === "OPTIONS") return options(); const auth = await authenticatedUser(req); if (auth.error) return auth.error; const user = auth.user!; const admin = adminClient(); const parts = requestPath(req).slice(1); if (req.method === "GET" && parts[0] === "nearby") { const url = new URL(req.url); const domainId = url.searchParams.get("domain_id"); const lat = Number(url.searchParams.get("lat")); const long = Number(url.searchParams.get("long")); if (!domainId !validLocation(lat, long)) return fail("Valid domain_id, lat and long are required"); const { data, error } = await admin.rpc("nearby_complaints", { p_domain_id: domainId, p_lat: lat, p_long: long }); return error ? fail(error.message, 500) : json({ candidates: data }); } });</pre>
Lines 14-27	<pre>const denied = requireRole(user, "citizen"); if (denied) return denied; if (req.method === "POST" && parts.length === 0) { const body = await req.json(); const { domain_id, description, before_photo_url, lat, long, gps_accuracy_meters } = body; if (!domain_id !before_photo_url !validLocation(lat, long)) return fail("domain_id, before_photo_url and valid location are required"); if (typeof before_photo_url !== "string" !before_photo_url.startsWith(`\${user.id}/`)) return fail("Evidence must be an object path in your own storage folder"); if (gps_accuracy_meters != null && (!Number.isFinite(gps_accuracy_meters) gps_accuracy_meters > 50)) return fail("GPS accuracy must be 50 metres or better"); const { error: walletError } = await admin.from("citizen_wallets").upsert({ wallet_id: user.id }, { onConflict: "wallet_id", ignoreDuplicates: true }); if (walletError) return fail(walletError.message, 500); const id = crypto.randomUUID(); const derived = await hmac(`\${user.id}\${id}`); const { data, error } = await admin.from("complaints").insert({ id, wallet_id: user.id, derived_citizen_id: derived, domain_id, description, before_photo_url, gps_accuracy_meters }); if (error) return fail(error.message, 400); await audit(admin, "citizen", user.id, "complaint_created", "complaint", id, { domain_id }); return json({ complaint: data }, 201); }</pre>
Lines 28-39	<pre>const complaintId = parts[0]; const action = parts[1]; if (req.method === "POST" && complaintId && action === "upvote") { const { photo_url, lat, long } = await req.json(); if (!photo_url !validLocation(lat, long)) return fail("photo_url and valid location are required"); if (typeof photo_url !== "string" !photo_url.startsWith(`\${user.id}/`)) return fail("Evidence must be an object path in your own storage folder"); const { data: complaint, error: readError } = await admin.from("complaints").select("id").eq("id", complaintId).single(); if (readError !complaint) return fail("Complaint not found", 404); const derived = await hmac(`\${user.id}\${complaintId}`); const { error } = await admin.from("complaint_upvotes").insert({ complaint_id: complaintId, wallet_id: user.id, derived_citizen_id: derived, photo_url, lat, long }); if (error) return fail(error.code === "23505" ? "You already added proof to this complaint" : error.message, 400); await admin.rpc("increment_upvote", { complaint_uuid: complaintId }); await audit(admin, "citizen", user.id, "proof_added", "complaint", complaintId); return json({ ok: true }, 201); }</pre>
Lines 40-53	<pre>if (req.method === "POST" && complaintId && action === "verify") { const { verdict, comment } = await req.json(); if (verdict !== "confirmed" && verdict !== "disputed") return fail("verdict must be confirmed or disputed"); const { data: complaint } = await admin.from("complaints").select("id, wallet_id, status, derived_citizen_id").eq("id", complaintId).eq("wallet_id", user.id).single(); if (!complaint) return fail("Complaint not found", 404); if (complaint.status !== "resolved") return fail("Only resolved complaints can be verified", 400); const { error } = await admin.from("verifications").insert({ complaint_id: complaintId, wallet_id: user.id, derived_citizen_id: complaint.derived_citizen_id, verdict, comment }); if (error) return fail(error.code === "23505" ? "Complaint already verified" : error.message, 400); await admin.from("complaints").update({ status: verdict === "confirmed" ? "resolved" : "reopened" }).eq("id", complaintId); await admin.rpc("adjust_reputation", { target_wallet: user.id, delta: verdict === "confirmed" ? 2 : -6 }); await audit(admin, "citizen", user.id, `resolution_\${verdict}`, "complaint", complaintId); return json({ status: verdict === "confirmed" ? "resolved" : "reopened" }); } return fail("Not found", 404); });</pre>

6.3 Officer Case Management & Proof of Work (officer-cases/index.ts)

LINES SOURCE CODE

Lines 1-18

```
import { adminClient, authenticatedUser, audit, fail, json, options, requestPath, requireRole, sha256, validLocation } from "../_shared/core.ts";

Deno.serve(async (req) => {
  if (req.method === "OPTIONS") return options();
  if (req.method !== "POST") return fail("Method not allowed", 405);
  const auth = await authenticatedUser(req); if (auth.error) return auth.error;
  const denied = requireRole(auth.user!, "officer"); if (denied) return denied;
  const officerId = auth.user!.id; const admin = adminClient(); const parts = requestPath(req).slice(1);
  const assignmentId = parts[0]; const action = parts[1]; if (!assignmentId || !action) return fail("Not found", 404);
  const { data: assignment } = await admin.from("case_assignments").select("id, complaint_id, officer_id, status").eq("id", assignmentId).single();
  if (!assignment || assignment.officer_id !== officerId) return fail("Assignment not found", 404);
  if (action === "accept") {
    if (!["assigned", "accepted"].includes(assignment.status)) return fail("Case cannot be accepted in its current state", 409);
    await admin.from("case_assignments").update({ status: "in_progress" }).eq("id", assignmentId);
    await admin.from("complaints").update({ status: "in_progress" }).eq("id", assignment.complaint_id);
    await audit(admin, "officer", officerId, "case_accepted", "case_assignment", assignmentId);
    return json({ status: "in_progress" });
  }
});
```

Lines 19-37

```
if (action === "complete") {
  const { after_photo_url, after_photo_hash, lat, long, officer_note, gps_accuracy_meters, captured_at } = await req.json();
  if (!after_photo_url || !after_photo_hash || !validLocation(lat, long)) return fail("after_photo_url, after_photo_hash and valid location are required");
  if (typeof after_photo_url !== "string" || !after_photo_url.startsWith(`${officerId}/`)) return fail("Evidence must be an object path in your own storage folder");
  if (gps_accuracy_meters !== null && (!Number.isFinite(gps_accuracy_meters) || gps_accuracy_meters > 50)) return fail("GPS accuracy must be 50 metres or better");
  const resolvedAt = captured_at ?? new Date().toISOString();
  if (Math.abs(Date.now() - new Date(resolvedAt).getTime()) > 120_000) return fail("Capture time must be within two minutes of server time");
  const { data: last } = await admin.from("resolutions").select("record_hash").eq("complaint_id", assignment.complaint_id).order("resolved_at", { ascending: false }).limit(1).single();
  const previousHash = last?.record_hash ?? "GENESIS";
  const recordHash = await sha256(`${assignment.complaint_id}${officerId}${after_photo_hash}${lat}${long}${resolvedAt}${previousHash}`);
  const { data, error } = await admin.from("resolutions").insert({ complaint_id: assignment.complaint_id, officer_id: officerId, after_photo_url, after_photo_hash, record_hash });
  if (error) return fail(error.message, 400);
  await admin.from("case_assignments").update({ status: "authority_review" }).eq("id", assignmentId);
  await admin.from("complaints").update({ status: "under_review" }).eq("id", assignment.complaint_id);
  await audit(admin, "officer", officerId, "resolution_submitted", "resolution", data.id, { assignment_id: assignmentId, record_hash: recordHash });
  return json({ resolution: data }, 201);
}
return fail("Not found", 404);
});
```

6.4 Authority Dispatch & Review Workflow (authority-assignments/index.ts)

LINES	SOURCE CODE
Lines 8-22	<pre>if (req.method === "GET" && parts[0] === "suggestions") { const complaintId = new URL(req.url).searchParams.get("complaint_id"); if (!complaintId) return fail("complaint_id is required"); const { data: complaint } = await admin.from("complaints").select("domain_id").eq("id", complaintId).single(); if (!complaint) return fail("Complaint not found"); const { data: officers, error } = await admin.from("officers").select("id, officer_id, name, role, performance_score").eq("authority_id", authorityId).eq("domain_id", domainId); if (error) return fail(error.message, 500); const ranked = await Promise.all((officers ?? []).map(async (o) => { const { data: cases, count } = await admin.from("case_assignments").select("assigned_at", { count: "exact" }).eq("officer_id", o.id).order("assigned_at", { ascending: true }); const open = await admin.from("case_assignments").select("id", { count: "exact", head: true }).eq("officer_id", o.id).in("status", ["assigned", "accepted", "pending"]); const lastAssigned = cases?.[0]?.assigned_at ? new Date(cases[0].assigned_at.getTime() : 0; const daysSince = lastAssigned ? (Date.now() - lastAssigned) / 86_400_000 : 365; const inverseRecency = Math.min(daysSince / 30, 1); return { ...o, open_case_count: open.count ?? count ?? 0, score: 0.6 * Number(o.performance_score) - 0.3 * (open.count ?? count ?? 0) + 0.1 * inverseRecency }; })); return json({ suggestions: ranked.sort((a, b) => b.score - a.score).slice(0, 3) }); }</pre>
Lines 23-34	<pre>if (req.method === "POST" && parts.length === 0) { const { complaint_id, officer_id, deadline, priority = "normal" } = await req.json(); if (!complaint_id !officer_id) return fail("complaint_id and officer_id are required"); const { data: officer } = await admin.from("officers").select("id, authority_id").eq("id", officer_id).single(); if (!officer officer.authority_id !== authorityId) return fail("Officer not found or not authorized"); const { data: complaint } = await admin.from("complaints").select("id, domain_id, status").eq("id", complaint_id).single(); if (!complaint) return fail("Complaint not found"); const { data: mapping } = await admin.from("domain_authority_map").select("authority_id").eq("authority_id", authorityId).eq("domain_id", complaint.domain_id).single(); if (!mapping) return fail("Your authority is not currently responsible for this complaint domain", 403); const { data, error } = await admin.from("case_assignments").insert({ complaint_id, officer_id, assigned_by: authorityId, deadline, priority }).select().single(); if (error) return fail(error.message, 400); await admin.from("complaints").update({ status: "assigned", assigned_authority_id: authorityId }).eq("id", complaint_id); await audit(admin, "authority", authorityId, "case_assigned", "case_assignment", data.id, { complaint_id, officer_id }); return json({ assignment: data }, 201); }</pre>
Lines 35-48	<pre>const assignmentId = parts[0]; if (req.method === "POST" && assignmentId && parts[1] === "review") { const { decision } = await req.json(); if (!['approved', 'rejected', 'reassigned'].includes(decision)) return fail("Invalid decision"); const { data: assignment } = await admin.from("case_assignments").select("id, complaint_id, assigned_by").eq("id", assignmentId).single(); if (!assignment assignment.authority_id !== authorityId) return fail("Assignment not found or not authorized"); const { error } = await admin.from("resolutions").update({ review_status: decision, reviewed_by: authorityId, reviewed_at: new Date().toISOString() }).eq("complaint_id", assignment.complaint_id); if (error) return fail(error.message, 400); const nextStatus = decision === "approved" ? "resolved" : "reopened"; await admin.from("case_assignments").update({ status: decision === "approved" ? "resolved" : "reopened" }).eq("id", assignmentId); await admin.from("complaints").update({ status: nextStatus }).eq("id", assignment.complaint_id); await audit(admin, "authority", authorityId, `resolution_\${decision}`, "case_assignment", assignmentId); return json({ status: nextStatus }); } return fail("Not found", 404); });</pre>

6.5 Automated Governance & Nightly CRON (score-recompute/index.ts)

LINES SOURCE CODE

Lines 1-25

```
import { adminClient, fail, json, options } from "../_shared/core.ts";

Deno.serve(async (req) => {
  if (req.method === "OPTIONS") return options();
  if (req.method !== "POST") return fail("Method not allowed", 405);
  const secret = Deno.env.get("CRON_SECRET");
  if (!secret || req.headers.get("x-cron-secret") !== secret) return fail("Unauthorized", 401);
  const admin = adminClient();
  const { data: officers, error } = await admin.from("officers").select("id, authority_id"); if (error) return fail(error.message, 500);
  for (const officer of officers ?? []) {
    const { data: assignments } = await admin.from("case_assignments").select("id, deadline, status, complaint_id").eq("officer_id", officer.id);
    const total = assignments?.length ?? 0; if (!total) continue;
    const resolved = assignments?.filter((a) => a.status === "resolved") ?? [];
    const ids = assignments?.map((a) => a.complaint_id) ?? [];
    const { data: resolutions } = ids.length ? await admin.from("resolutions").select("complaint_id, resolved_at").eq("officer_id", officer.id).in("complaint_id",
    const completedAt = new Map((resolutions ?? []).map((r) => [r.complaint_id, new Date(r.resolved_at)]));
    const onTime = resolved.filter((a) => !a.deadline || (completedAt.get(a.complaint_id) && completedAt.get(a.complaint_id)! <= new Date(a.deadline))).length / total;
    const reopened = (assignments?.filter((a) => a.status === "reopened").length ?? 0) / total;
    const { data: verified } = ids.length ? await admin.from("verifications").select("verdict").in("complaint_id", ids) : { data: [] };
    const confirmations = verified?.filter((v) => v.verdict === "confirmed").length ?? 0;
    const confirmedRate = verified?.length ? confirmations / verified.length : 0;
    const score = Math.max(0, Math.min(100, 100 * (0.4 * onTime + 0.4 * confirmedRate + 0.2 * (1 - reopened))));
    await admin.from("officers").update({ performance_score: score.toFixed(2) }).eq("id", officer.id);
    await admin.from("audit_log").insert({ actor_type: "system", action: "officer_score_recomputed", entity_type: "officer", entity_id: officer.id, metadata: { sco
  }
}
```

Lines 26-36

```
const { data: authorities } = await admin.from("authorities").select("id");
for (const authority of authorities ?? []) {
  const { data: staff } = await admin.from("officers").select("performance_score").eq("authority_id", authority.id);
  if (staff?.length) {
    const average = staff.reduce((total, officer) => total + Number(officer.performance_score), 0) / staff.length;
    await admin.from("authorities").update({ performance_score: average.toFixed(2) }).eq("id", authority.id);
  }
}
return json({ ok: true, recomputed_at: new Date().toISOString() });
});
```

7. Frontend Architecture, Cryptography & UI Components

The frontend is built on Next.js 14 App Router, integrating device hardware sensors, client-side cryptographic hashing, and responsive state visualization.

7.1 Client-Side SHA-256 & Dual-Mode Client (hash.ts & supabaseClient.ts)

FILE & LINES	SOURCE CODE	ARCHITECTURAL & LINE-BY-LINE EXPLANATION
lib/hash.ts (Lines 19-32)	<pre>export async function sha256Hex(input: string ArrayBuffer): Promise<string> { const data = typeof input === "string" ? new TextEncoder().encode(input) : input; const digest = await crypto.subtle.digest("SHA-256", data); return Array.from(new Uint8Array(digest)) .map((b) => b.toString(16).padStart(2, "0")) .join(""); } export async function hashBlob(blob: Blob): Promise<string> { const buf = await blob.arrayBuffer(); return sha256Hex(buf); }</pre>	Client-Side Web Crypto SHA-256 Hashing: - Uses browser-native <code>crypto.subtle.digest</code> to compute SHA-256 cryptographic digests in pure JavaScript without external hashing dependencies. <code>hashBlob()</code> converts image Blobs directly from the camera canvas into <code>ArrayBuffers</code> for hashing before upload, ensuring tamper detection in transit.
lib/supabaseClient.ts (Lines 1-21)	<pre>import { createClient, SupabaseClient } from "@supabase/supabase-js"; const url = process.env.NEXT_PUBLIC_SUPABASE_URL; const anonKey = process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY; export const HAS_SUPABASE = Boolean(url && anonKey); export const supabase: SupabaseClient null = HAS_SUPABASE ? createClient(url as string, anonKey as string, { auth: { persistSession: true, autoRefreshToken: true } }) : null;</pre>	Dual-Mode Environment Auto-Detection: - Inspects Next.js environment variables (<code>NEXT_PUBLIC_SUPABASE_URL</code> & <code>ANON_KEY</code>). - If credentials exist: instantiates live Supabase client with local session persistence. - If credentials are absent: sets <code>HAS_SUPABASE = false</code>, prompting <code>lib/api.ts</code> to seamlessly route calls to in-memory realistic mock state for local prototyping.

7.2 Live Camera Anti-Cheat Hardware Binding (LiveCameraCapture.tsx)

FILE & LINES	SOURCE CODE	ARCHITECTURAL & LINE-BY-LINE EXPLANATION
LiveCameraCapture.tsx (Lines 23-45)	<pre>const startCamera = useCallback(async () => { setCameraError(null); try { if (!navigator.mediaDevices !navigator.mediaDevices.getUserMedia) { throw new Error("Camera API not supported in this browser environment."); } const stream = await navigator.mediaDevices.getUserMedia({ video: { facingMode: "environment" }, audio: false }); streamRef.current = stream; if (videoRef.current) { videoRef.current.srcObject = stream; await videoRef.current.play(); } setReady(true); } catch (err: any) { setCameraError("Camera stream unavailable (or desktop mode)..."); } }, []);</pre>	Hardware Camera Stream Initialization: - Requests direct video stream using <code>facingMode: "environment"</code> (rear camera on mobile devices). - Streams video frames live into an HTML5 <code><video></code> element with zero audio overhead. - Prevents file gallery selection attacks by binding directly to the device sensor hardware.
LiveCameraCapture.tsx (Lines 55-67)	<pre>const captureLive = () => { const video = videoRef.current; const canvas = canvasRef.current; if (!video !canvas) return; canvas.width = video.videoWidth 640; canvas.height = video.videoHeight 480; const ctx = canvas.getContext("2d"); if (!ctx) return; ctx.drawImage(video, 0, 0, canvas.width, canvas.height); const dataUrl = canvas.toDataURL("image/jpeg", 0.85); setPhoto(dataUrl); streamRef.current?.getTracks().forEach((t) => t.stop()); };</pre>	Canvas Snapshot & Sensor Freezing: - Grabs the exact active video frame and paints it onto an off-screen HTML5 <code><canvas></code> at native resolution. - Encodes snapshot directly to standard JPEG (<code>image/jpeg</code> at 85% quality) to compress payload. - Immediately closes media tracks to release battery and camera hardware.

7.3 Visual Audit Trail & Status Timeline (ComplaintTimeline.tsx)

[ComplaintTimeline.tsx \(Lines 20-74\)](#)

```
const steps: Step[] = [
  { label: "Filed", detail: "Live photo + GPS captured", at: complaint.created_at, state: "done" },
  { label: "Assigned", detail: assignment ? "Routed to a field officer" : "Waiting on the responsible authority",
    at: assignment?.assigned_at, state: assignment ? "done" : complaint.status === "filed" ? "current" : "pending" },
  { label: "Work in progress", detail: assignment?.status === "in_progress" ? "Officer accepted the case" : undefined,
    state: resolution || ["in_progress", "work_completed", "under_review", "resolved"].includes(complaint.status) ? "done" : assignment ?
  { label: "Completion evidence submitted", detail: resolution ? "Live after-photo + GPS recorded, hash-chained" : undefined,
    at: resolution?.resolved_at, state: resolution ? "done" : "pending" },
  { label: "Authority review", detail: resolution ? (resolution.review_status === "pending" ? "Awaiting sign-off" : "Marked ${resolution.r
    at: resolution?.reviewed_at ?? undefined, state: resolution?.review_status === "approved" ? "done" : resolution?.review_status === "re
  { label: verification?.verdict === "disputed" ? "Reopened by citizen" : "Confirmed by citizen",
    detail: verification?.comment ?? (complaint.status === "resolved" ? "Case closed" : "Your call once evidence is in"),
    at: verification?.created_at, state: verification ? (verification.verdict === "confirmed" ? "done" : "flagged") : "pending" }
];
```

8. Production Security & Deployment Checklist

Zero Trust Security Architecture Review:

1. **Role-Based Storage Access:** Supabase storage policies enforce that objects uploaded to `complaint-evidence` must reside in `auth.uid()/*`. The Edge Functions strictly reject any path not prefixed by the user's UUID.
2. **Clock Manipulation Defense:** In `officer`-cases, the resolution timestamp is compared against the server clock with $|T_{client} - T_{server}| \leq 120$ seconds. Devices with forged local system times are rejected.
3. **Anti-Sybil Upvoting:** Upvotes require fresh photographic proof and GPS coordinates, preventing coordinated digital upvote fraud.
4. **Database Constraint Integrity:** PostgreSQL CHECK constraints enforce numeric bounds on coordinates, reputation scores (0–100), string lengths (≤ 3000 chars), and regex identifiers (OFF-XXXX).

Automated Deployment Command:

To link your Supabase project, execute migrations, upload environment secrets, and deploy all 8 Edge Functions in a single automated step:

```
./scripts/deploy.ps1 -ProjectRef YOUR_PROJECT_REF
```

— End of Official Samadhan Setu Architectural and Line-by-Line Code Manual —