

## Advanced Programming Exam - Binary Search Tree

Generated by Doxygen 1.8.13



# Contents

<b>1</b>	<b>Hierarchical Index</b>	<b>1</b>
1.1	Class Hierarchy . . . . .	1
<b>2</b>	<b>Class Index</b>	<b>3</b>
2.1	Class List . . . . .	3
<b>3</b>	<b>File Index</b>	<b>5</b>
3.1	File List . . . . .	5
<b>4</b>	<b>Class Documentation</b>	<b>7</b>
4.1	NodeNamespace::BSTNode< K, T > Class Template Reference . . . . .	7
4.1.1	Member Function Documentation . . . . .	8
4.1.1.1	get_next() . . . . .	8
4.1.1.2	hasLChild() . . . . .	8
4.1.1.3	hasRChild() . . . . .	8
4.2	BSTree< K, T, C > Class Template Reference . . . . .	9
4.2.1	Detailed Description . . . . .	10
4.2.2	Constructor & Destructor Documentation . . . . .	10
4.2.2.1	BSTree() . . . . .	10
4.2.3	Member Function Documentation . . . . .	11
4.2.3.1	balance() . . . . .	11
4.2.3.2	begin() . . . . .	11
4.2.3.3	cbegin() . . . . .	11
4.2.3.4	cend() . . . . .	12
4.2.3.5	clear() . . . . .	12

4.2.3.6	<a href="#">end()</a>	12
4.2.3.7	<a href="#">find()</a>	12
4.2.3.8	<a href="#">get_root()</a>	13
4.2.3.9	<a href="#">insert()</a> [1/2]	13
4.2.3.10	<a href="#">insert()</a> [2/2]	14
4.2.3.11	<a href="#">is_empty()</a>	14
4.2.3.12	<a href="#">operator=()</a>	14
4.2.3.13	<a href="#">operator[]()</a>	15
4.2.3.14	<a href="#">print()</a>	15
4.2.3.15	<a href="#">size_of()</a>	15
4.2.3.16	<a href="#">square_bracket_test()</a>	16
4.3	<a href="#">compareh Struct Reference</a>	16
4.4	<a href="#">BSTree&lt; K, T, C &gt;::ConstIterator Class Reference</a>	17
4.5	<a href="#">error Struct Reference</a>	18
4.6	<a href="#">BSTree&lt; K, T, C &gt;::Iterator Class Reference</a>	18
4.7	<a href="#">RandomKey Struct Reference</a>	19
4.8	<a href="#">RandomKey_explicit Struct Reference</a>	19
<b>5</b>	<b>File Documentation</b>	<b>21</b>
5.1	<a href="#">/home/w-wilson/DSSC/first_year/exam_advanced/test/include/BST.h File Reference</a>	21
5.1.1	<a href="#">Detailed Description</a>	22
5.2	<a href="#">/home/w-wilson/DSSC/first_year/exam_advanced/test/src/main.cc File Reference</a>	23
5.2.1	<a href="#">Detailed Description</a>	23
<b>Index</b>		<b>25</b>

# Chapter 1

## Hierarchical Index

### 1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

NodeNamespace::BSTNode< K, T > . . . . .	7
BSTree< K, T, C > . . . . .	9
compareh . . . . .	16
error . . . . .	18
BSTree< K, T, C >::iterator . . . . .	18
BSTree< K, T, C >::ConstIterator . . . . .	17
RandomKey . . . . .	19
RandomKey_explicit . . . . .	19



## Chapter 2

# Class Index

### 2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">NodeNamespace::BSTNode&lt; K, T &gt;</a>	<a href="#">7</a>
<a href="#">BSTree&lt; K, T, C &gt;</a>	<a href="#">9</a>
<a href="#">compareh</a>	<a href="#">16</a>
<a href="#">BSTree&lt; K, T, C &gt;::ConstIterator</a>	<a href="#">17</a>
<a href="#">error</a>	<a href="#">18</a>
<a href="#">BSTree&lt; K, T, C &gt;::Iterator</a>	<a href="#">18</a>
<a href="#">RandomKey</a>	<a href="#">19</a>
<a href="#">RandomKey_explicit</a>	<a href="#">19</a>





## Chapter 3

# File Index

### 3.1 File List

Here is a list of all documented files with brief descriptions:

/home/w-wilson/DSSC/first_year/exam_advanced/test/include/ <a href="#">BST.h</a>	
BST header file . . . . .	<a href="#">21</a>
/home/w-wilson/DSSC/first_year/exam_advanced/test/src/ <b>BST.hpp</b> . . . . .	<b>??</b>
/home/w-wilson/DSSC/first_year/exam_advanced/test/src/ <a href="#">main.cc</a>	
Main file for the exam . . . . .	<a href="#">23</a>




## Chapter 4

# Class Documentation

### 4.1 NodeNamespace::BSTNode< K, T > Class Template Reference

Collaboration diagram for NodeNamespace::BSTNode< K, T >:



#### Public Member Functions

- `BSTNode ()`=default  
*BSTNode default constructor.*
- `BSTNode (const std::pair< const K, T > &data)`  
*BSTNode constructor accepting a std::pair<K,T> as input.*
- `BSTNode (const std::pair< const K, T > &data, BSTNode *_parent)`  
*BSTNode constructor accepting a std::pair<K,T> and a pointer to the parent node as input.*
- `~BSTNode ()` noexcept=default  
*Sefault BSTNode destructor.*
- `bool hasLChild ()` const noexcept  
*Checks if the node has a left child.*
- `bool hasRChild ()` const noexcept  
*Checks if the node has a right child.*
- `BSTNode * get_next ()` noexcept  
*Returns a pointer to the next node, according to key order.*

## Public Attributes

- `std::pair< const K, T >` **content**
- `std::unique_ptr< BSTNode >` **left**
- `std::unique_ptr< BSTNode >` **right**
- `BSTNode *` **parent**

### 4.1.1 Member Function Documentation

#### 4.1.1.1 `get_next()`

```
template<typename K , typename T >
NodeNamespace::BSTNode< K, T > * NodeNamespace::BSTNode< K, T >::get_next ( ) [noexcept]
```

Returns a pointer to the next node, according to key order.

#### Parameters

<i>none</i>	
-------------	--

#### Returns

Pointer to the next node.

#### 4.1.1.2 `hasLChild()`

```
template<typename K, typename T>
bool NodeNamespace::BSTNode< K, T >::hasLChild ( ) const [inline], [noexcept]
```

Checks if the node has a left child.

#### Parameters

<i>none</i>	
-------------	--

#### Returns

True if the node has a left child, False otherwise.

#### 4.1.1.3 `hasRChild()`

```
template<typename K, typename T>
bool NodeNamespace::BSTNode< K, T >::hasRChild ( ) const [inline], [noexcept]
```

Checks if the node has a right child.

#### Parameters

<i>none</i>	
-------------	--

#### Returns

True if the node has a right child, False otherwise.

The documentation for this class was generated from the following files:

- /home/w-wilson/DSSC/first\_year/exam\_advanced/test/include/BST.h
- /home/w-wilson/DSSC/first\_year/exam\_advanced/test/src/BST.hpp

## 4.2 BSTree< K, T, C > Class Template Reference

```
#include <BST.h>
```

### Classes

- class [ConstIterator](#)
- class [Iterator](#)

### Public Member Functions

- const int & [size\\_of](#) () const noexcept  
*Returns the number of elements of the tree.*
- bool [is\\_empty](#) () const noexcept  
*Check if the tree is empty.*
- const [BSTNode](#)< K, T > \* [get\\_root](#) () const  
*Returns a pointer to the root node.*
- [BSTree](#) ()=default  
*Default [BSTree](#) constructor.*
- [BSTree](#) (const K &key, const T &value, C comp=C{})  
*[BSTree](#) constructor accepting a key and a value, inserted as root.*
- [BSTree](#) (const std::pair< const K, T > &data, C comp=C{})  
*[BSTree](#) constructor accepting a std::pair<key,value> inserted as root.*
- [~BSTree](#) () noexcept=default  
*Default [BSTree](#) destructor.*
- [BSTree](#) (const [BSTree](#) &t)  
*Copy constructor for a [BSTree](#). Calls the auxiliary function [copy\\_tree\(\)](#) which performs a deep copy of the tree.*
- [BSTree](#) & [operator=](#) (const [BSTree](#) &t)  
*Copy assignment of a [BSTree](#).*
- [BSTree](#) ([BSTree](#)< K, T, C > &&) noexcept=default  
*Default move constructor for a [BSTree](#).*
- [BSTree](#)< K, T, C > & [operator=](#) ([BSTree](#)< K, T, C > &&) noexcept=default

- Default move assignment for a [BSTree](#).*
- [Iterator begin](#) ()  
*first element for iterating a [BSTree](#).*
- [Iterator end](#) ()  
*last element for iterating a [BSTree](#)*
- [ConstIterator cbegin](#) () const  
*first element for iterating a [BSTree](#).*
- [ConstIterator cend](#) () const  
*last element for iterating a [BSTree](#)*
- bool [insert](#) (const std::pair< const K, T > &data)  
*Inserts a [BSTNode](#) passing a std::pair<key,value>. Calls position\_of(key) to find where the node should be appended. If the key is already present, does nothing. Otherwise a new node is created.*
- bool [insert](#) (const K &key, const T &value)  
*Inserts a node passing a key and a value separately.*
- [Iterator find](#) (const K &key) const  
*Returns, if found, an iterator to the node labelled by key.*
- void [clear](#) () noexcept  
*Wipes out the tree. Resets the root to nullptr, causing all the other nodes to be deleted. The tree is left uninitialized, but still usable.*
- void [print](#) () const  
*Prints the value in all the nodes, traversing the tree in order.*
- void [balance](#) ()  
*Balances the tree.*
- T & [operator\[\]](#) (const K &k)  
*Operator [] to access/insert a [BSTNode](#). Returns the value associated with key if found. Otherwise, appends a node with the desired key and the default value.*
- const T & [operator\[\]](#) (const K &k) const
- const T & [square\\_bracket\\_test](#) (const K &key) const  
*Operator << to print a [BSTree](#).*

## Public Attributes

- C [compare\\_f](#)

### 4.2.1 Detailed Description

```
template<typename K, typename T, typename C = std::less<K>>
class BSTree< K, T, C >
```

Binary Search Tree implementation.

Implementation of a Binary Search Tree. The tree is made of nodes which store a key/value pair. It requires a compare structure to order keys. If none is provided, it uses std::less<K>, where K is the key type.

### 4.2.2 Constructor & Destructor Documentation

#### 4.2.2.1 BSTree()

```
template<typename K, typename T, typename C = std::less<K>>
BSTree< K, T, C >::BSTree (
    const BSTree< K, T, C > & t ) [inline]
```

Copy constructor for a [BSTree](#). Calls the auxiliary function copy\_tree() which performs a deep copy of the tree.

## Parameters

<i>t</i>	BSTree to be copied, passed by const reference.
----------	---

## 4.2.3 Member Function Documentation

## 4.2.3.1 balance()

```
template<typename K , typename T , typename C >
void BSTree< K, T, C >::balance ( )
```

Balances the tree.

The tree is linearized into a vector of `std::pair<key,value>`. Then calls `clear()` and the auxiliary function `balance(vector, begin, end)`.

## Parameters

<i>none</i>	
-------------	--

## Returns

*none*

## 4.2.3.2 begin()

```
template<typename K, typename T, typename C = std::less<K>>
Iterator BSTree< K, T, C >::begin ( ) [inline]
```

first element for iterating a BSTree.

## Returns

iterator to the leftmost node.

## 4.2.3.3 cbegin()

```
template<typename K, typename T, typename C = std::less<K>>
ConstIterator BSTree< K, T, C >::cbegin ( ) const [inline]
```

first element for iterating a BSTree.

## Returns

constiterator to the leftmost node.

#### 4.2.3.4 cend()

```
template<typename K, typename T, typename C = std::less<K>>
ConstIterator BSTree< K, T, C >::cend ( ) const [inline]
```

last element for iterating a [BSTree](#)

##### Returns

cosntiterator to nullptr.

#### 4.2.3.5 clear()

```
template<typename K , typename T , typename C >
void BSTree< K, T, C >::clear ( ) [noexcept]
```

Wipes out the tree. Resets the root to nullptr, causing all the other nodes to be deleted. The tree is left uninitialized, but still usable.

##### Parameters

<i>none</i>	
-------------	--

##### Returns

none

#### 4.2.3.6 end()

```
template<typename K, typename T, typename C = std::less<K>>
Iterator BSTree< K, T, C >::end ( ) [inline]
```

last element for iterating a [BSTree](#)

##### Returns

iterator to nullptr.

#### 4.2.3.7 find()

```
template<typename K , typename T , typename C >
BSTree< K, T, C >::Iterator BSTree< K, T, C >::find (
    const K & key ) const
```

Returns, if found, an iterator to the node labelled by key.

Calls the auxiliary function `position_of(key)` which returns, if key is found, an iterator pointing to the node that contains key. If the key is not found or the [BSTree](#) is empty, returns a [ConstIterator](#) to nullptr.



## Parameters

<i>key</i>	Key to be found.
------------	------------------

## Returns

[Iterator](#) to the node containing the requested key or to nullptr.

4.2.3.8 `get_root()`

```
template<typename K, typename T, typename C = std::less<K>>
const BSTNode<K,T>* BSTree< K, T, C >::get_root ( ) const [inline]
```

Returns a pointer to the root node.

## Parameters

<i>none</i>	
-------------	--

## Returns

Pointer to root BSTNode.

4.2.3.9 `insert()` [1/2]

```
template<typename K , typename T , typename C >
bool BSTree< K, T, C >::insert (
    const std::pair< const K, T > & data )
```

Inserts a BSTNode passing a `std::pair<key,value>`. Calls `position_of(key)` to find where the node should be appended. If the key is already present, does nothing. Otherwise a new node is created.

## Parameters

<i>data</i>	Pair of key-value.
-------------	--------------------

## Returns

bool Boolean which is true if a new node was inserted, false if the key was already present.

**4.2.3.10 insert()** [2/2]

```
template<typename K , typename T , typename C >
bool BSTree< K, T, C >::insert (
    const K & key,
    const T & value )
```

Inserts a node passing a key and a value separately.

Key and value are grouped in an `std::pair<key, value>`, **insert()** is then called passing the `std::pair<key,value>`.

**Parameters**

<i>key</i>	key entry of the node.
<i>value</i>	content associated to key.

**Returns**

`bool`

**4.2.3.11 is\_empty()**

```
template<typename K, typename T, typename C = std::less<K>>
bool BSTree< K, T, C >::is_empty ( ) const [inline], [noexcept]
```

Check if the tree is empty.

**Parameters**

<i>none</i>	
-------------	--

**Returns**

True if the tree is empty, false otherwise.

**4.2.3.12 operator=()**

```
template<typename K , typename T , typename C >
BSTree< K, T, C > & BSTree< K, T, C >::operator= (
    const BSTree< K, T, C > & t )
```

Copy assignment of a **BSTree**.

**Parameters**

<i>t</i>	the <b>BSTree</b> to be copied.
----------	---------------------------------

**Returns**

The newly copied [BSTree](#).

**4.2.3.13 operator[]()**

```
template<typename K , typename T , typename C >
T & BSTree< K, T, C >::operator[] (
    const K & k )
```

Operator [] to access/insert a BSTNode. Returns the value associated with key if found. Otherwise, appends a node with the desired key and the default value.

**Parameters**

<i>k</i>	key to be found/inserted.
----------	---------------------------

**Returns**

the value associated with the key *k*.

**4.2.3.14 print()**

```
template<typename K , typename T , typename C >
void BSTree< K, T, C >::print ( ) const
```

Prints the value in all the nodes, traversing the tree in order.

**Parameters**

<i>none</i>	
-------------	--

**Returns**

none

**4.2.3.15 size\_of()**

```
template<typename K, typename T, typename C = std::less<K>>
const int& BSTree< K, T, C >::size_of ( ) const [inline], [noexcept]
```

Returns the number of elements of the tree.

**Parameters**

<i>none</i>	
-------------	--

**Returns**

const int& Number of elements of the tree.

**4.2.3.16 square\_bracket\_test()**

```
template<typename K , typename T , typename C >
const T & BSTree< K, T, C >::square_bracket_test (
    const K & key ) const
```

Operator << to print a [BSTree](#).

Iterates the tree using const iterators and prints "key: value" for each node.

**Parameters**

<i>os</i>	OutputStream, where the content of the <a href="#">BSTree</a> should be printed.
<i>t</i>	Const reference to the <a href="#">BSTree</a> to be printed.

**Returns**

Reference to the OutputStream.

Test function for const[] operator

Trivial function declared as const which calls the const[] operator

**Parameters**

<i>key</i>	key to be searched
------------	--------------------

The documentation for this class was generated from the following files:

- [/home/w-wilson/DSSC/first\\_year/exam\\_advanced/test/include/BST.h](#)
- [/home/w-wilson/DSSC/first\\_year/exam\\_advanced/test/src/BST.hpp](#)
- [/home/w-wilson/DSSC/first\\_year/exam\\_advanced/test/src/main.cc](#)

**4.3 compareh Struct Reference****Public Member Functions**


- **bool operator()** ([RandomKey\\_explicit](#) bingo, [RandomKey\\_explicit](#) bango) const

The documentation for this struct was generated from the following file:


- [/home/w-wilson/DSSC/first\\_year/exam\\_advanced/test/src/main.cc](#)

## 4.4 BSTree< K, T, C >::ConstIterator Class Reference

Inheritance diagram for BSTree< K, T, C >::ConstIterator:



Collaboration diagram for BSTree< K, T, C >::ConstIterator:



### Public Types

- using **parent** = [BSTree< K, T, C >::Iterator](#)

### Public Member Functions

- const std::pair< const K, T > & **operator\*** () const

The documentation for this class was generated from the following file:

- [/home/w-wilson/DSSC/first\\_year/exam\\_advanced/test/src/BST.hpp](#)

## 4.5 error Struct Reference

### Public Member Functions

- **error** (const std::string &s) noexcept

### Public Attributes


- std::string **message**

The documentation for this struct was generated from the following file:

- /home/w-wilson/DSSC/first\_year/exam\_advanced/test/src/BST.hpp

## 4.6 BSTree< K, T, C >::Iterator Class Reference

Inheritance diagram for BSTree< K, T, C >::Iterator:



### Public Member Functions

- **Iterator** (BSTNode< K, T > \*n)
- std::pair< const K, T > & **operator\*** () const
- BSTNode< K, T > \* **get** ()
- **Iterator** & **operator++** () noexcept
- bool **operator==** (const **Iterator** &other) const noexcept
- bool **operator!=** (const **Iterator** &other) const noexcept

The documentation for this class was generated from the following file:

- /home/w-wilson/DSSC/first\_year/exam\_advanced/test/src/BST.hpp

## 4.7 RandomKey Struct Reference

### Public Member Functions

- bool **operator**< ([RandomKey](#) other) const

### Public Attributes

- int **one**
- int **two**
- int **three**

The documentation for this struct was generated from the following file:

- /home/w-wilson/DSSC/first\_year/exam\_advanced/test/src/[main.cc](#)

## 4.8 RandomKey\_explicit Struct Reference

### Public Attributes

- int **one**
- int **two**
- int **three**

The documentation for this struct was generated from the following file:

- /home/w-wilson/DSSC/first\_year/exam\_advanced/test/src/[main.cc](#)






## Chapter 5

# File Documentation


### 5.1 /home/w-wilson/DSSC/first\_year/exam\_advanced/test/include/BST.h File Reference

BST header file.

```
#include <memory>
#include <utility>
#include <iostream>
#include <vector>
#include "../src/BST.hpp"
Include dependency graph for BST.h:
```



This graph shows which files directly or indirectly include this file:



## Classes

- class [NodeNamespace::BSTNode< K, T >](#)
- class [BSTree< K, T, C >](#)

## Typedefs

- `template<typename K , typename T >`  
using **BSTNode** = [NodeNamespace::BSTNode< K, T >](#)

### 5.1.1 Detailed Description

BST header file.

#### Author

Amadio Simone, Indri Patrick

#### Date

25/01/19


## 5.2 /home/w-wilson/DSSC/first\_year/exam\_advanced/test/src/main.cc File Reference

main file for the exam

```
#include <memory>
```

```
#include "BST.h"
```

Include dependency graph for main.cc:



### Classes

- struct [RandomKey\\_explicit](#)
- struct [compareh](#)
- struct [RandomKey](#)

### Functions

- `std::ostream & operator<< (std::ostream &os, const RandomKey &k)`
- `int main ()`

#### 5.2.1 Detailed Description

main file for the exam

#### Author

William Wilson

#### Date

1/2/23



# Index

/home/w-wilson/DSSC/first\_year/exam\_advanced/test/include/NodeNamespace::BSTNode, 8  
BST.h, 21 hasRChild

/home/w-wilson/DSSC/first\_year/exam\_advanced/test/src/main.NodeNamespace::BSTNode, 8  
cc, 23

## BSTree

BSTree, 10  
balance, 11  
begin, 11  
cbegin, 11  
cend, 11  
clear, 12  
end, 12  
find, 12  
get\_root, 13  
insert, 13  
is\_empty, 14  
operator=, 14  
operator[], 15  
print, 15  
size\_of, 15  
square\_bracket\_test, 16

BSTree< K, T, C >, 9

BSTree< K, T, C >::ConstIterator, 17

BSTree< K, T, C >::Iterator, 18

## balance

BSTree, 11

## begin

BSTree, 11

## cbegin

BSTree, 11

## cend

BSTree, 11

## clear

BSTree, 12

## compareh, 16

## end

BSTree, 12

## error, 18

## find

BSTree, 12

## get\_next

NodeNamespace::BSTNode, 8

## get\_root

BSTree, 13

## hasLChild

## insert

BSTree, 13

## is\_empty

BSTree, 14

## NodeNamespace::BSTNode

get\_next, 8

hasLChild, 8

hasRChild, 8

## NodeNamespace::BSTNode< K, T >, 7

## operator=

BSTree, 14

## operator[]

BSTree, 15

## print

BSTree, 15

## RandomKey, 19

## RandomKey\_explicit, 19

## size\_of

BSTree, 15

## square\_bracket\_test

BSTree, 16