Computer Technology I

Lab. 1 : How to use the PORTs, Digital input/output, Subroutine call

Author:
Supervisor:
Semester: Autumn 2019
Area: Computer Science
Course code: 1DT301

Contents

1 Task 1

For the first task the goal was to get a light blinking. This was done by setting the data direction register to output, and after that setting the LED port low.

```
;>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>
;       1DT301, Computer Technology 1
;       Date: 09-09-2019
;       Authors:
;               Roel de Vries
;               Student name 2
;
;       Lab number 1
;       Title:  How to use the PORTS, digital IO, subroutine call
;
;       Hardware: STK600, CPU ATmega 2560
;
;       Function: Turn on Led 3
;
;       Input ports: None
;
;       Output ports: PORTB, used for LEDS
;
;       Subroutines: None
;       Included files: m2560def.inc
;
;       Other information: None
;
;       Changes in program:
;               09-09-2019 > file created
;<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<
.include "m2560def.inc"

main:
        SBI DDRB, 2
        CBI PORTB, 2
```

2 Task 2

3 Task 3

In task 3 the goal was to turn on led 0, only if switch 5 was pressed. by checking if the bit for switch 5 is high we are able to turn the led on at the right moment

```
;>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>
;       1DT301, Computer Technology 1
;       Date: 09-09-2019
;       Authors:
;               Roel de Vries
;               Student name 2
;
;       Lab number 1
;       Title:  How to use the PORTS, digital IO, subroutine call
;
;       Hardware: STK600, CPU ATmega 2560
;
```

```
;       Function: Turn on Led 0 when you press led 5
;
;       Input ports: PORTA, used for the switches
;
;       Output ports: PORTB, used for LEDS
;
;       Subroutines: None
;       Included files: m2560def.inc
;
;       Other information: None
;
;       Changes in program:
;               09-09-2019 > file created
;<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<
.include "m2560def.inc"

main:
        SBI DDRB, 0 ; set output
        CBI DDRA, 5 ; set input

lightloop:

        SBIS PINA, 5
        CBI PORTB, 0
        SBIC PINA, 5
        SBI PORTB, 0
```

4 Task 4

In task 4 we needed to run the task 3 code in the simulator, as seen in the screenshots below, this worked.

TBD

5 Task 5

For task 5 we needed to create a ring counter. This was done by creating a loop which constantly shifts the PORTB register one sideways with a delay.

```
;>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>
;       1DT301, Computer Technology 1
;       Date: 09-09-2019
;       Authors:
;               Roel de Vries
;               Student name 2
;
;       Lab number 1
;       Title:  How to use the PORTS, digital IO, subroutine call
;
;       Hardware: STK600, CPU ATmega 2560
;
;       Function: Creates a ring counter, updates every 0.5 seconds
;
;       Input ports: None
;
```

```
;       Output ports: PORTB, used for LEDS
;
;       Subroutines: Timer
;       Included files: m2560def.inc
;
;       Other information: None
;
;       Changes in program:
;               09-09-2019 > file created
;<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<
.include "m2560def.inc"

main:
        ; Initialize SP, Stack Pointer
        ldi r20, HIGH(RAMEND) ; R20 = high part of RAMEND address
        out SPH,R20 ; SPH = high part of RAMEND address
        ldi R20, low(RAMEND) ; R20 = low part of RAMEND address
        out SPL,R20 ; SPL = low part of RAMEND address

        LDI r20, 0xFF
        OUT DDRB, r20
        CBR r20, 1 ; set output
        OUT PORTB, r20
        call timer

lightloop:
        LSL r20
        BRCS setbit
lightloopcont:
        OUT PORTB, r20
        call timer
        call lightloop

setbit:
        SBR r20, 1
        CLC
        call lightloopcont

timer:
; Generated by delay loop calculator
; at http://www.bretmulvey.com/avrdelay.html
        ldi  r17, 5
    ldi  r18, 20
    ldi  r19, 175
L1: dec  r19
    brne L1
    dec  r18
    brne L1
    dec  r17
    brne L1
        ret
```

6 Task 6

The Johnson counter was created by using two smaller loops who constantly call eachother. the first which increases the amount of leds on, and a second which decreases

the amount of leds on.

```
;>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>
;       1DT301, Computer Technology 1
;       Date: 09-09-2019
;       Authors:
;               Roel de Vries
;               Student name 2
;
;       Lab number 1
;       Title:  How to use the PORTS, digital IO, subroutine call
;
;       Hardware: STK600, CPU ATmega 2560
;
;       Function: Creates a johnson counter, updates every 0.5 seconds
;
;       Input ports: None
;
;       Output ports: PORTB, used for LEDS
;
;       Subroutines: Timer
;       Included files: m2560def.inc
;
;       Other information: None
;
;       Changes in program:
;               09-09-2019 > file created
;<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<<
.include "m2560def.inc"

main:
        ; Initialize SP, Stack Pointer
        ldi r21, HIGH(RAMEND) ; R20 = high part of RAMEND address
        out SPH,R21 ; SPH = high part of RAMEND address
        ldi R21, low(RAMEND) ; R20 = low part of RAMEND address
        out SPL,R21 ; SPL = low part of RAMEND address

        CBR r16, 0; counter
        SBR r17, 255; light state
        OUT DDRB, r17
        ldi r16, 8

incloop:
        LSL r17
        OUT PORTB, r17
        call timer
        dec r16
    brne incloop
        ldi r16, 8
        call decloop

decloop:
        LSR r17
        SBR r17, 128
        OUT PORTB, r17
        call timer
        dec r16
    brne decloop
        ldi r16, 8
        call incloop
```

```
timer:
; Generated by delay loop calculator
; at http://www.bretmulvey.com/avrdelay.html
        ldi  r18, 5
    ldi  r19, 20
    ldi  r20, 175
L1: dec  r20
    brne L1
    dec  r19
    brne L1
    dec  r18
    brne L1
    rjmp PC+1
        ret
```