P802.1ASds/D1.0
July 25, 2024
(Amendment to IEEE Std 802.1AS™-202x)

Draft Standard for Local and metropolitan area networks—

Timing and Synchronization for Time-Sensitive Applications

Amendment: Support for the IEEE Std 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex

Sponsor

LAN/MAN Standards Committee
of the
IEEE Computer Society

Time-Sensitive Networking (TSN) Task Group of IEEE 802.1

All participants in IEEE standards development have responsibilities under the IEEE patent policy and should familiarize themselves with that policy, see http://standards.ieee.org/about/sasb/patcom/materials.html

As part of our IEEE 802® process, the text of the PAR (Project Authorization Request) and CSD (Criteria for Standards Development) is reviewed regularly to ensure their continued validity. A vote of “Approve” on this draft is also an affirmation that the PAR is still valid. It is included in these cover pages.

The text proper of this draft begins with the title page (1). The cover pages (a), (b), (c) etc. are for 802.1 WG information, and will be removed prior to Sponsor Ballot.

Important Notice

This document is an unapproved draft of a proposed IEEE Standard. IEEE hereby grants the named IEEE SA Working Group or Standards Committee Chair permission to distribute this document to participants in the receiving IEEE SA Working Group or Standards Committee, for purposes of review for IEEE standardization activities. No further use, reproduction, or distribution of this document is permitted without the express written permission of IEEE Standards Association (IEEE SA). Prior to any review or use of this draft standard, in part or in whole, by another standards development organization, permission must first be obtained from IEEE SA (stds-copyright@ieee.org). This page is included as the cover of this draft, and shall not be modified or deleted.

IEEE Standards Association
445 Hoes Lane
Piscataway, NJ 08854, USA

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards Draft, subject to change.

Editors' Foreword

This draft standard is an amendment. The scope of changes to the base standard is thus strictly limited, as detailed in the PAR.

Information on participation in this project, and in the IEEE 802.1 Working Group can be found here.

Participation in 802.1 standards development

Comments on this draft are encouraged. **NOTE: All issues related to IEEE standards presentation style, formatting, spelling, etc. are routinely handled between the 802.1 Editor and the IEEE Staff Editors prior to publication, after balloting and the process of achieving agreement on the technical content of the standard is complete.** Readers are urged to devote their valuable time and energy only to comments that materially affect either the technical content of the document or the clarity of that technical content. Comments should not simply state what is wrong, but also what might be done to fix the problem.

Full participation in the work of IEEE 802.1 requires attendance at IEEE 802 meetings. Information on 802.1 activities, working papers, and email distribution lists etc. can be found on the 802.1 Website:

http://ieee802.org/1/

Use of the email distribution list is not presently restricted to 802.1 members, and the working group has a policy of considering ballot comments from all who are interested and willing to contribute to the development of the draft. Individuals not attending meetings have helped to identify sources of misunderstanding and ambiguity in past projects. The email lists exist primarily to allow the members of the working group to develop standards, and are not a general forum. All contributors to the work of 802.1 should familiarize themselves with the IEEE patent policy and anyone using the mail distribution will be assumed to have done so. Information can be found at http://standards.ieee.org/about/sasb/patcom/materials.html/

Comments on this document may be sent to the 802.1 email exploder, to the Editor, or to the Chair of the 802.1 Working Group.

Silvana Rodrigues	Glenn Parsons
Editor, P802.1ASds	Chair, 802.1 Working Group
Email:silvana.rodrigues@huawei.com	Email: glenn.parsons@ericsson.com

NOTE: Comments whose distribution is restricted in any way cannot be considered, and may not be acknowledged.

All participants in IEEE standards development have responsibilities under the IEEE patent policy and should familiarize themselves with that policy, see http://standards.ieee.org/about/sasb/patcom/materials.html

As part of our IEEE 802 process, the text of the PAR and CSD (Criteria for Standards Development, formerly referred to as the 5 Criteria or 5C's) is reviewed on a regular basis in order to ensure their continued validity. A vote of "Approve" on this draft is also an affirmation by the balloter that the PAR is still valid.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Project Authorization Request, Scope, Purpose, and Criteria for Standards Development (CSD)

The complete amendment PAR, as approved by IEEE NesCom 23 February 2022, can be found at:

https://development.standards.ieee.org/myproject-web/public/view.html#pardetail/9522

The ‘Scope of the Proposed changes’ and the ‘Need for the Project’ specify the changes to be made by this amendment (see below).

Scope of the Proposed changes:

This amendment specifies protocols, procedures, and managed objects that support IEEE Std 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex while retaining existing functionality and backward compatibility, and remaining a profile of IEEE Std 1588™-2019.
This amendment addresses errors and omissions in the description of existing functionality.

Need for the Project:

Support is needed in applications such as automotive in-vehicle networks and industrial automation networks for the IEEE Std 802.3 Clause 4 MAC operating in half-duplex, including those using links with the 10BASE-T1S PHY in either point-to-point or multidrop half-duplex mode recently introduced by IEEE Std 802.3cg-2019.

Criteria for Standards Development:

The complete Criteria for Standards Development (CSD) can be found at:

https://mentor.ieee.org/802-ec/dcn/21/ec-21-0308-00-ACSD-p802-1asds.pdf

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Draft IEEE Standard for Local and metropolitan area networks—

Timing and Synchronization for Time-Sensitive Applications

Amendment: Support for the IEEE Std 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex

[This amendment is based on IEEE Std 802.1AS™-20xx (IEEE Std 802.1AS™-2020 Revision).

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strikethrough~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.[1]

[1]Notes in text, tables, and figures are given for information only, and do not contain requirements needed to implement the standard.

Copyright © 20XX IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

P802.1ASds/D1.0
July 25, 2024
(Amendment to IEEE Std 802.1AS™-202x)

Draft IEEE Standard for Local and metropolitan area networks—

Timing and Synchronization for Time-Sensitive Applications

Amendment: Support for the IEEE Std 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex

Prepared by the
Time-Sensitive Networking (TSN)Task Group of IEEE 802.1

Sponsor
LAN/MAN Standards Committee
of the
IEEE Computer Society

Copyright 2024 by the IEEE.
Three Park Avenue
New York, New York 10016-5997, USA
All rights reserved.

This document is an unapproved draft of a proposed IEEE Standard. As such, this document is subject to change. USE AT YOUR OWN RISK! IEEE copyright statements SHALL NOT BE REMOVED from draft or approved IEEE standards, or modified in any way. Because this is an unapproved draft, this document must not be utilized for any conformance/compliance purposes. Permission is hereby granted for officers from each IEEE Standards Working Group or Committee to reproduce the draft document developed by that Working Group for purposes of international standardization consideration. IEEE Standards Department must be informed of the submission for consideration prior to any reproduction for international standardization consideration (stds.ipr@ieee.org). Prior to adoption of this document, in whole or in part, by another standards development organization, permission must first be obtained from the IEEE Standards Department (stds.ipr@ieee.org). When requesting permission, IEEE Standards Department will require a copy of the standard development organization's document highlighting the use of IEEE content. Other entities seeking permission to reproduce this document, in whole or in part, must also obtain permission from the IEEE Standards Department.

IEEE Standards Activities Department
445 Hoes Lane
Piscataway, NJ 08854, USA

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Abstract: This amendment to IEEE Std 802.1AS™-2020 specifies protocols, procedures, and managed objects that support IEEE Std 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex while retaining existing functionality and backward compatibility, and remaining a profile of IEEE Std 1588™-2019.

This amendment addresses errors and omissions in the description of existing functionality.

Keywords: best timeTransmitter, frequency offset, Grandmaster Clock, Grandmaster PTP Instance, PTP End Instance, PTP Relay Instance, IEEE 802.1AS™, phase offset, synchronization, syntonization, time-aware system

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2024 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published xx Month xxxx. Printed in the United States of America.

MoCA is a registered trademark of the Multimedia over Coax Alliance.

POSIX is a registered trademark of The Institute of Electrical and Electronics Engineers, Incorporated.

IEEE and IEEE 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-X-XXX-XXX-X STDXXXXX
Print: ISBN 978-X-XXX-XXX-X STDPDXXXXX

IEEE prohibits discrimination, harassment and bullying.

For more information, visit https://www.ieee.org/about/corporate/governance/p9-26.html.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading "Important Notices and Disclaimers Concerning IEEE Standards Documents." They can also be obtained on request from IEEE or viewed at http://standards.ieee.org/ipr/disclaimers.html.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association ("IEEE-SA") Standards Board. IEEE ("the Institute") develops its standards through a consensus development process, approved by the American National Standards Institute ("ANSI"), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied "AS IS" and "WITH ALL FAULTS."

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at https://ieeexplore.ieee.org or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE-SA Website at https://standards.ieee.org.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: https://standards.ieee.org/standard/index.html. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at https://standards.ieee.org/about/sasb/patcom/patents.html. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Participants

<<The following lists will be updated in the usual way prior to publication>>

At the time this standard was completed, the IEEE 802.1 working group had the following membership:

Glenn Parsons, *Chair*
Jessy Rouyer, *Vice Chair*
János Farkas, *TSN Task Group Chair*
Silvana Rodrigues, *Editor IEEE Std 802.1AS*
Silvana Rodrigues, *Editor P802.1ASds*

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

<<The above lists will be updated in the usual way prior to publication>>

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

When the IEEE-SA Standards Board approved this standard on <dd> <month> <year>, it had the following membership:

Jean-Philippe Faure, *Chair*
Vacant Position, *Vice-Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Chuck Adams	Michael Janezic	Robby Robson
Masayuki Ariyoshi	Thomas Koshy	Dorothy Stanley
Ted Burse	Joseph L. Koepfinger1	Adrian Stephens
Stephen Dukes	Kevin Lu	Mehmet Ulema
Doug Edwards	Daleep Mohla	Phil Wennblom
J. Travis Griffith	Damir Novosel	Howard Wolfman
Gary Hoffman	Ronald C. Petersen	Yu Yuan
	Annette D. Reilly	

*Member Emeritus

<<The above lists will be updated in the usual way prior to publication>>

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Introduction

This introduction is not part of IEEE Std 802.1ASds™-20xx, IEEE Standard for Local and metropolitan area networks—Timing and Synchronization for Time-Sensitive Applications—Amendment: Support for the IEEE Std 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex

The first edition of IEEE Std 802.1AS was published in 2011. A first corrigendum, IEEE Std 802.1AS™-2011/Cor1-2013, provided technical and editorial corrections. A second corrigendum, IEEE Std 802.1AS™-2011/Cor2-2015 provided additional technical and editorial corrections.

The second edition, IEEE Std 802.1AS-2020, added support for multiple gPTP domains, Common Mean Link Delay Service, external port configuration, and Fine Timing Measurement for 802.11 transport. Backward compatibility with IEEE Std 802.1AS-2011 was maintained. A corrigendum, IEEE Std 802.1AS™-2020/Cor1-2021, provides technical and editorial corrections.

The third edition, IEEE Std 802.1AS-202x is a roll-up of IEEE Std 802.1AS-2020 with the corrigendum IEEE Std 802.1AS-2020/Cor1, and its amendments: IEEE Std 802.1ASdr, IEEE Std 802.1ASdn, and IEEE Std 802.1ASdm.

This amendment to IEEE Std 802.1AS-202x specifies protocols, procedures, and managed objects that support IEEE Std 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex while retaining existing functionality and backward compatibility, and remaining a profile of IEEE Std 1588™-2019.

This amendment addresses errors and omissions in the description of existing functionality

<<Editor's note: P802.1ASds is an amendment to 802.1AS-2020-Rev>>

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Contents

Copyright © 2024 IEEE. All rights reserved.

Copyright © 2024 IEEE. All rights reserved.

List of figures

Copyright © 2024 IEEE. All rights reserved.

List of tables

Copyright © 2024 IEEE. All rights reserved.

IEEE Standard for Local and Metropolitan Area Networks — Timing and Synchronization for Time-Sensitive Applications

Amendment: Support for the IEEE Std 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex

1. Overview

1.1 Scope

This standard specifies protocols, procedures, and managed objects used to ensure that the synchronization requirements are met for time-sensitive applications, such as audio, video, and time-sensitive control, across networks, for example, IEEE 802 and similar media. This includes the maintenance of synchronized time during normal operation and following addition, removal, or failure of network components and network reconfiguration. It specifies the use of IEEE Std 1588™ specifications where applicable in the context of IEEE Std 802.1Q™-2018. Synchronization to an externally provided timing signal [e.g., a recognized timing standard such as Coordinated Universal Time (UTC) or International Atomic Time (TAI)] is not part of this standard but is not precluded.

1.2 Purpose

This standard enables systems to meet the respective jitter, wander, and time-synchronization requirements for time-sensitive applications, including those that involve multiple streams delivered to multiple end stations. To facilitate the widespread use of packet networks for these applications, synchronization information is one of the components needed at each network element where time-sensitive application data are mapped or demapped or a time-sensitive function is performed. This standard leverages the work of the IEEE 1588 Working Group by developing the additional specifications needed to address these requirements

Copyright © 20XX IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

1.3 Word usage

The word *shall* indicates mandatory requirements strictly to be followed in order to conform to the standard and from which no deviation is permitted (*shall* equals *is required to*).[1,2]

The word *should* indicates that among several possibilities one is recommended as particularly suitable, without mentioning or excluding others; or that a certain course of action is preferred but not necessarily required (*should* equals *is recommended that*).

The word *may* is used to indicate a course of action permissible within the limits of the standard (*may* equals *is permitted to*).

The word *can* is used for statements of possibility and capability, whether material, physical, or causal (*can* equals is *able to*).

[1] The use of the word *must* is deprecated and cannot be used when stating mandatory requirements; *must* is used only to describe unavoidable situations.

[2] The use of *will* is deprecated and cannot be used when stating mandatory requirements; *will* is only used in statements of fact.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

3. Definitions

Insert the following definitions in Clause 3, and renumber the definitions as appropriate:

3.17 Half-duplex Ethernet: An Ethernet whose physical ports use the IEEE Std 802.3™ Clause 4 MAC in half-duplex mode, independent of the physical medium access method and independent of the physical topology of the shared medium connected.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

4. Acronyms and abbreviations

Insert the following acronym in clause 4 as follows:

HDE	Half-duplex Ethernet

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

5. Conformance

Insert 5.9 as follows:

5.9 MAC-specific timing and synchronization methods for HDE links

An implementation of a time-aware system with IEEE 802.3 media access control (MAC) services to physical ports shall:

a) Support half-duplex operation, as specified in Clause 4 of IEEE Std 802.3-2022.
b) Support the requirements as specified in Clause 19.

Copyright © 2024 IEEE. All rights reserved.

7. Time-synchronization model for a packet network

7.2 Architecture of a time-aware network

7.2.1 General

Add item g) after item f) in the lettered list in 7.2.1 as follows:

g) IEEE 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex (Clause 19)

7.3 Time synchronization

7.3.2 Delay measurement

Add item e) after item d) in the lettered list in 7.3.2 as follows:

e) HDE links use the same mechanism as full-duplex Ethernet

7.4 PTP Instance architecture

Change the last paragraph of 7.4 as follows:

For EPON, timing information is communicated using a “slow protocol” as defined in Clause 13. CSNs and HDE links use the same communication system used by full-duplex Ethernet, as defined in Clause 16 and Clause 19, respectively.

7.5 Differences between gPTP (IEEE Std 802.1AS) and PTP (IEEE Std 1588-2019)

Change item e) and item f) in 7.5 as follows:

e) For full-duplex Ethernet and HDE links, gPTP requires the use of the peer-to-peer delay mechanism, while IEEE Std 1588-2019 also allows the use of end-to-end delay measurement.

f) For full-duplex Ethernet and HDE links, gPTP requires the use of two-step processing (use of Follow_Up and Pdelay_Resp_Follow_Up messages to communicate timestamps), with an optional one-step processing mode for full-duplex Ethernet that embeds timestamps in the Sync “on the fly” as they are being transmitted (gPTP does not specify one-step processing for peer delay messages). IEEE Std 1588-2019 allows either two-step or one-step processing to be required (for both Sync and peer delay messages) depending on a specific profile.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

8. IEEE 802.1AS concepts and terminology

8.5 Ports

8.5.1 General

Change 8.5.1 as follows:

The PTP Instances in a gPTP domain interface with the network media via physical ports. gPTP defines a logical port, i.e., a PTP Port, in such a way that communication between PTP Instances is point-to-point or, in the case of an HDE link (see Clause 19), point-to-multipoint. A logical port consists of one PortSync entity and one media-dependent (MD) entity. Multiple PTP Ports can be associated with a single physical port. ~~even over physical ports that are attached to shared media. One~~ For shared media, there are multiple possibilities:

a) one logical port~~, consisting of one PortSync entity and one media-dependent (MD) entity, is~~ can be instantiated for each PTP Instance with which the PTP Instance communicates, i.e., the PTP communication paths are physically point-to-point even though the physical port is attached to a shared medium, e.g., CSN (see 16); or

b) the PTP communication path can be physically point-to-multipoint, e.g., for an HDE link (see 19). ~~For shared media, multiple logical ports can be associated with a single physical port.~~

Unless otherwise qualified, each instance of the term *port* refers to a *logical port*.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

10. Media-independent layer specification

10.7 Protocol timing characterization

10.7.2 Message transmission intervals

10.7.2.1 General interval specification

Change the second paragraph in 10.7.2.1 as follows:

The mean time interval between the sending of successive time-synchronization event messages for full-duplex point-to-point, IEEE 802.11, ~~and~~ CSN, and HDE links, and successive general messages containing time-synchronization information for IEEE 802.3 EPON links, is known as the *sync interval*. The sync interval shall be as specified in 10.7.2.3.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

11. Media-dependent layer specification for full-duplex point-to-point links

11.1 Overview

11.1.1 General

Add a NOTE at the end of 11.1.1 as follows:

NOTE—PTP links using the IEEE 802.3 Clause 4 MAC operating in half-duplex mode are specified in Clause 19.

11.2 State machines for MD entity specific to full-duplex point-to-point links

11.2.2 Determination of asCapable and asCapableAcrossDomains

Change 11.2.2 as follows:

There is one instance of the global variable asCapable (see 10.2.5.1) per PTP Port, per domain. There is one instance of the global variable asCapableAcrossDomains (see 11.2.13.12), per port, that is common across, and accessible by, all the domains.

The per-PTP Port global variable asCapable (see 10.2.5.1) indicates whether the IEEE 802.1AS protocol is operating, in this domain, on the PTP Link attached to this PTP Port, and can provide the required time-synchronization performance ~~described in B.3~~. asCapable is used by the PortSync entity, which is media-independent; however, the determination of asCapable is media-dependent.

The per-port global variable asCapableAcrossDomains is set by the MDPdelayReq state machine (see 11.2.19 and Figure 11-9). For a port attached to a full-duplex point-to-point PTP Link or to an HDE link, asCapableAcrossDomains shall be set to TRUE if and only if either:

a) I~~i~~t is determined, via the transport-specific peer-to-peer delay mechanism or CMLDS, that the following conditions hold for the port:
   1) ~~a)~~The port is exchanging peer delay messages with its neighbor,
   2) ~~b)~~The measured delay does not exceed meanLinkDelayThresh,
   3) ~~c)~~The port does not receive multiple Pdelay_Resp or Pdelay_Resp_Follow_Up messages in response to a single Pdelay_Req message, and
   4) ~~d)~~The port does not receive a response from itself or another PTP Port of the same PTP Instance.

or:

b) pdelayReqSendDisabled is set to TRUE

NOTE 1—If a PTP Instance implements only domain 0 and the MDPdelayReq and MDPdelayResp state machines are invoked on domain 0 (see 11.2.19), asCapableAcrossDomains is still set by the MDPdelayReq state machine.

The default value of meanLinkDelayThresh shall be set as specified in Table 11-1.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Table 11-1—Value of meanLinkDelayThresh for various links

Link	Value of meanLinkDelayThresh (ns) (see NOTE)
100BASE-TX, 1000BASE-T	800_{10}
100BASE-FX, 1000BASE-X, HDE	FFFF FFFF FFFF FFFF FFFF FFFF$_{16}$
NOTE—The actual propagation delay for 100BASE-TX and 1000BASE-T links is expected to be smaller than the above respective threshold. If the measured mean propagation delay (i.e., meanLinkDelay; see 10.2.5.8) exceeds this threshold, it is assumed that this is due to the presence of equipment that does not implement gPTP. For 100BASE-FX, ~~and~~ 1000BASE-X, and HDE links, the actual propagation delay can be on the order of, or larger than, the delay produced by equipment that does not implement gPTP; therefore, such equipment cannot be detected by comparing measured propagation delay with a threshold. In this case, meanLinkDelayThresh is set to the largest possible value (i.e., all 1s).	

<<Editor's note: Table 11-1 may need to be generalized.>>

The per-PTP Port, per-domain global variable asCapable shall be set to TRUE if and only if the following conditions hold:

c) ~~c)~~The value of asCapableAcrossDomains is TRUE, and

d) ~~f)~~One of the following conditions holds:

1) The value of neighborGptpCapable for this PTP Port is TRUE, or

2) The value of domainNumber is zero, and the value of sdoId for peer delay messages received on this PTP Port is 0x100.

NOTE 2—Condition ~~f)~~d) 2) ensures backward compatibility with the 2011 edition of this standard. A PTP Instance compliant with the current edition of this standard that is attached, via a full-duplex point-to-point PTP Link, to a PTP Instance compliant with the 2011 edition of this standard will not receive Signaling messages that contain the gPTP capable TLV and will not set neighborGptpCapable to TRUE. However, condition ~~f)~~d) 2) ensures that asCapable for this PTP Port and domain (i.e., domain 0) will still be set to TRUE if condition c) holds because the peer delay messages received from the time-aware system compliant with the 2011 edition of this standard will have sdoId set to 0x100.

11.2.13 MD entity global variables

Change 11.2.13.12 as follows:

11.2.13.12 asCapableAcrossDomains: A Boolean that is TRUE if and only if either: a) conditions 1~~a~~) through 4~~d~~) of 11.2.2 are satisfied, or b) condition b) of 11.2.2 is satisfied. ~~This Boolean~~ asCapableAcrossDomains is set by the MDPdelayReq state machine and is used in determining asCapable for a port (see 11.2.2). There is one instance of this variable for all the domains (per port) for full-duplex point-to-point links. ~~T~~and the variable is accessible by all the domains. There is one instance of this variable per PTP Instance (i.e., per domain) for HDE links (see 19.2.2). When only one domain is active, asCapableAcrossDomains is equivalent to the variable asCapable (see 10.2.5.1).

11.2.19 MDPdelayReq state machine

11.2.19.2 State machine variables

Change 11.2.19.2.2 as follows:

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

11.2.19.2.2 rcvdPdelayResp: A Boolean variable that notifies the current state machine when a Pdelay_Resp message is received and its requestingPortIdentity.clockIdentity is equal to the clockIdentity of the current PTP Instance. This variable is reset by the current state machine.

Change 11.2.19.2.4 as follows:

11.2.19.2.4 rcvdPdelayRespFollowUp: A Boolean variable that notifies the current state machine when a Pdelay_Resp_Follow_Up message is received and its requestingPortIdentity.clockIdentity is equal to the clockIdentity of the current PTP instance. This variable is reset by the current state machine.

Insert a new variable after 11.2.19.2.13 as follows:

11.2.19.2.14 pdelayReqSendDisabled: A boolean that is administratively set to TRUE if Pdelay_Req messages are not transmitted by this port. The default value for this variable shall be FALSE.

11.2.19.4 State diagram

Replace Figure 11-9 with the following:.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Figure 11-9—MDPdelayReq state machine

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Add a NOTE after Figure 11-9 as follows:

NOTE—A change in the value of the variable pdelayReqSendDisabled takes effect only when portEnabled0 (see 11.2.19.2.12) is FALSE.

11.2.20 MDPdelayResp state machine

11.2.20.2 State machine variables

Insert a new variable after 11.2.20.2.5 as follows:

11.2.20.2.6 pdelayRespSendDisabled: A boolean that is administratively set to TRUE if Pdelay_Resp messages are not transmitted by this port. The default value for this variable shall be FALSE.

11.2.20.4 State diagram

Replace Figure 11-10 with the following:



Figure 11-10—MDPdelayResp state machine

Add a NOTE after Figure 11-10 as follows:

NOTE—A change in the value of the variable pdelayRespSendDisabled takes effect only when portEnabled1 (see 11.2.20.2.5) is FALSE.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

12. Media-dependent layer specification for IEEE 802.11 links

12.1 Overview

12.1.2 IEEE 802.11 Timing Measurement and Fine Timing Measurement procedures

12.1.2.2 Detailed description of Fine Timing Measurement (FTM)

Change the last paragraph in 12.1.2.2 as follows:

With the above procedure for FTM, the slave controls the rate at which time synchronization information is sent from the master. This is different from TM, full-duplex IEEE 802.3, IEEE 802.3 EPON, ~~and~~ CSN, and HDE transports. In those cases, the sending of time synchronization information from the master to the slave is controlled by the master; this is true for syncLocked (see 10.2.5.15) TRUE, in which case the information is sent as soon as it is received from further upstream, and syncLocked FALSE, in which case it is sent independently of information received from further upstream. For FTM, the slave requests time synchronization information from the master at an average rate equal to the inverse of the current synchronization message interval currentLogSyncInterval (see 12.8 and 14.8.18). In addition, the actual intervals between successive requests by the slave for time synchronization information meet the requirements of 10.7.2.3. Also, the value of syncLocked at the master port will not affect the sending of time synchronization information from the master to the slave; the requests for time synchronization information from the slave are asynchronous to the receipt of time synchronization information from upstream at the node that contains the master port.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

14. Timing and synchronization management

14.8 Port Parameter Data Set (portDS)

14.8.23 InitialLogPdelayReqInterval

Change the first paragraph in 14.8.23 as follows:

For full-duplex and HDE IEEE 802.3 media, and for CSN media, that use the peer-to-peer delay mechanism to measure path delay (see 16.4.3.2), the value is the logarithm to base 2 of the Pdelay_Req message transmission interval used when:

14.8.24 currentLogPdelayReqInterval

Change the first paragraph in 14.8.24 as follows:

For full-duplex and HDE IEEE 802.3 media, and for CSN media, that use the peer-to-peer delay mechanism to measure path delay (see 16.4.3.2), the value is the logarithm to the base 2 of the current Pdelay_Req message transmission interval (see 11.5.2.2).

14.8.32 currentComputeNeighborRateRatio

Change the first paragraph in 14.8.32 as follows:

For full-duplex and HDE IEEE 802.3 media, and for CSN media, that use the peer-to-peer delay mechanism to measure path delay (see 16.4.3.2), the value is the current value of computeNeighborRateRatio.

14.8.36 currentComputeMeanLinkDelay

Change the first paragraph in 14.8.36 as follows:

For full-duplex and HDE IEEE 802.3 media, and for CSN media, that use the peer-to-peer delay mechanism to measure path delay (see 16.4.3.2), the value is the current value of computeMeanLinkDelay.

14.8.53 pdelayTruncatedTimestampsArray

Change the first paragraph in 14.8.53 as follows:

For full-duplex and HDE IEEE 802.3 media, and for CSN media, that use the peer-to-peer delay mechanism to measure path delay (see 16.4.3.2), the values of the four elements of this array are as described in Table 14-9. For all other media, the values are zero. Array elements 0, 1, 2, and 3 correspond to the timestamps t1, t2, t3, and t4, respectively, in Figure 11-1 and are expressed in units of 2–16 ns (i.e., the value of each array element is equal to the remainder obtained upon dividing the respective timestamp, expressed in units of 2–16 ns, by 248). At any given time, the timestamp values stored in the array are for the same, and most recently completed, peer delay message exchange.

14.8.55 portDS table

Insert the following items after the final item of Table 14-10:

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Table 14-10—portDS table

Name	Data type	Operations supported[a]	References
pdelayReqSendDisabled	Boolean	RW	14.8.60
pdelayRespSendDisabled	Boolean	RW	14.8.61

[a] R = Read only access; RW = Read/write access.

Insert 14.8.60 and 14.8.61 as follows:

14.8.60 pdelayReqSendDisabled

The value is equal to the value of the per-PTP Port global variable pdelayReqSendDisabled (see 11.2.19.2.14). If its value is TRUE, Pdelay_Req messages are not transmitted by the PTP Port. The default value for this variable shall be FALSE.

14.8.61 pdelayRespSendDisabled

The value is equal to the value of the per-PTP Port global variable pdelayRespSendDisabled (see 11.2.20.2.6). If its value is TRUE, Pdelay_Resp messages are not transmitted by the PTP Port. The default value for this variable shall be FALSE.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

17. YANG Data Model

<<Editor's note: P802.1ASds is an amendment to P802.1AS-2020-Rev, therefore this clause may need to be aligned once 802.1ASdn and 802.1ASdm are roll up into the revision of IEEE 802.1AS-2020.>>

17.1 YANG framework

Change 17.1.1 as follows:

17.1.1 Relationship to the IEEE Std 1588 data model

Change the first paragraph in 17.1.1 as follows:

The YANG data models specified in this standard are based on, and augment, those specified in IEEE Std 1588. In particular the ieee802-dot1as-gptp.yang module imports the ieee1588-ptp-tt module as a whole, augmenting that module as necessary to meet the requirements of this standard. In addition, the ieee802-dot1as-hs.yang module imports the ieee1588-ptp-tt and ieee802-dot1as-gptp modules as a whole, augmenting those modules as necessary to meet the requirements of this standard. Also, the ieee802-dot1as-hd.yang module imports the ieee1588-ptp-tt, the ieee802-dot1as-gpt, and the ieee802-dot1as-hs modulesas a whole, augmenting those modules as necessary to meet the requirements of this standard.

Change the fourth paragraph in 17.1.1 as follows:

The YANG modules of this clause (ieee802-dot1as-gptp.yang, ~~and~~ ieee802-dot1as-hs.yang, and ieee802-dot1as-hd.yang) use the YANG "import" statement to import the YANG module of IEEE Std 1588e. This effectively uses the IEEE Std 1588 YANG tree as the foundation of the IEEE Std 802.1AS YANG tree. By importing the tree and its data set containers, all members from Clause 14 that are derived from IEEE Std 1588 are also imported.

17.2 IEEE 802.1AS YANG models

Replace Figure 17-3 with the following:

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.



NOTE 3—This figure differs from the 202x edition of this standard in that managed objects needed for the HDE are added.

Figure 17-3—PTP Port detail

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

17.3 Structure of YANG models

Change Table 17-1 as follows:.

Table 17-1—Summary of the YANG modules

Module	Managed functionality	YANG specification notes
ietf-yang-types	Type definitions	IETF RFC 6991 - Common YANG Data Types.
ieee1588-ptp-tt	Clause 14	IEEE Std 1588e - MIB and YANG Data Models. IEEE Std 802.1ASdn imports this YANG module as its foundational tree, including a subset of members from Clause 14.
ieee802-dot1as-gptp	Clause 14	IEEE Std 802.1ASdn - YANG Data Model. The YANG module of this clause uses YANG augments to add members from Clause 14 that are unique to IEEE Std 802.1AS.
ieee802-dot1as-hs	Clause 14	IEEE Std 802.1ASdm - YANG Data Model. The YANG module of this clause uses YANG augments to add members from Clause 14 that are unique to IEEE Std 802.1ASdm.
ieee802-dot1as-hd	Clause 14	IEEE Std 802.1ASds - YANG Data Model. The YANG module of this clause uses YANG augments to add members from Clause 14 that are unique to IEEE Std 802.1ASds

17.5 YANG schema tree definitions

Insert 17.5.3 and renumber subsequent subclauses as appropriate:

17.5.3 Tree diagram for ieee802-dot1as-hd.yang

```
module: ieee802-dot1as-hd

      augment   /ptp-tt:ptp/ptp-tt:instances/ptp-tt:instance/ptp-tt:ports/ptp-tt:port/ptp-
tt:port-ds:
    +--rw pdelay-req-send-disabled?    boolean
    +--rw pdelay-resp-send-disabled?   boolean
```

17.6 YANG modules[1] [2]

Insert 17.6.3 and renumber subsequent subclauses as appropriate:

17.6.3 Module ieee802-dot1as-hd.yang

```
module ieee802-dot1as-hd {
  yang-version 1.1;
```

[1]Copyright release for YANG modules: Users of this standard may freely reproduce the YANG modules contained in this subclause so that they can be used for their intended purpose.

[2]An ASCII version of the YANG modules are attached to the PDF version of this standard, and can be obtained by Web browser from the IEEE 802.1 Website at https://1.ieee802.org/yang-modules/.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

```
namespace “urn:ieee:std:802.1AS:yang:ieee802-dot1as-hd”;
prefix dot1as-hd;

import ieee1588-ptp-tt {
  prefix ptp-tt;
}
import ieee802-dot1as-gptp {
  prefix dot1as-gptp;
}
import ieee802-dot1as-hs {
  prefix dot1as-hs;
}

organization
  “IEEE 802.1 Working Group”;
contact
  “WG-URL: http://ieee802.org/1/
   WG-EMail: stds-802-1-l@ieee.org

   Contact: IEEE 802.1 Working Group Chair
            Postal: C/O IEEE 802.1 Working Group
            IEEE Standards Association
            445 Hoes Lane
            Piscataway, NJ 08854
            USA

   E-mail: stds-802-1-chairs@ieee.org”;
description
  “Management objects that control MAC operating in half-duplex as
   specified in IEEE Std 802.1ASds.

   References in this YANG module to IEEE Std 802.1AS are to
   IEEE Std 802.1AS-2020 as modified by
   IEEE Std 802.1AS-2020/Cor-1-2021, and amended by
   IEEE Std 802.1ASdr, IEEE Std 802.1ASdn,
   IEEE Std 802.1ASdm, and IEEE Std 802.1ASds.

   Copyright (C) IEEE (2024).
   This version of this YANG module is part of IEEE Std 802.1AS;
   see the standard itself for full legal notices.”;

revision 2024-07-25 {
  description
    “Published as part of IEEE Std 802.1ASds-2024.
     Initial version.”;
  reference
    “IEEE Std 802.1AS - YANG Data Model”;
}

augment “/ptp-tt:ptp/ptp-tt:instances/ptp-tt:instance”
      + “/ptp-tt:ports/ptp-tt:port/ptp-tt:port-ds” {
  description
    “Augment IEEE Std 1588 portDS.”;
  leaf pdelay-req-send-disabled {
    type boolean;
    description
      “A boolean that is administratively set to TRUE
       if Pdelay_Req messages are not transmitted by this port.
       The default value for this variable shall be FALSE.”;
    reference
      “11.2.19.2.14 of IEEE Std 802.1ASds”;
  }
  leaf pdelay-resp-send-disabled {
    type boolean;
    description
```


Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

```
        "A boolean that is administratively set to TRUE
         if Pdelay_Resp messages are not transmitted by this port.
         The default value for this variable shall be FALSE.";
      reference
        "11.2.20.2.6 of IEEE Std 802.1ASds";
    }
  }
}
```


Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Insert the following new Clause 19:

19. Media-dependent layer specification for IEEE 802.3 Clause 4 Media Access Control (MAC) operating in half-duplex

19.1 Overiew

19.1.1 General

Accurate synchronized time is distributed throughout a gPTP domain through time measurements between adjacent PTP Relay Instances or PTP End Instances in a packet network. Time is communicated from the root of the clock spanning tree (i.e., the Grandmaster PTP Instance) toward the leaves of the tree (i.e., from leaf-facing timeTransmitter ports to root-facing timeReceiver ports) through measurements made across the links connecting the PTP Instances. While the semantics of time transfer are consistent across the time-aware packet network, the method for communicating synchronized time from a timeTransmitter port to its immediate downstream link partner(s) varies depending on the type of link interconnecting the two or more PTP Instances. This clause specifies the protocol that provides accurate synchronized time across links that use IEEE 802.3 (Ethernet) Clause 4 MACs operating in half-duplex mode as part of a packet network.

19.1.1.1 Half-duplex Ethernet (HDE) characteristics

The Ethernet IEEE 802.3 Clause 4 MAC can operate in either full-duplex or half-duplex mode. When this MAC is operating in full-duplex, its media-dependent specification for gPTP is covered in Clause 11 of this standard. The present clause is used when the 802.3 Clause 4 MAC is operating in half-duplex.This mode necessitates additional managed object settings and frame processing due to the effects of the shared media this mode supports, which are described in this clause.

NOTE—Shared media allow multiple devices to be connected to the same physical wire without the need of bridges or PTP Relay Instances between them, as shown in Figure 19-1.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.



Note 1: The "bridge" in this figure is an example of a time-aware system that contains a PTP Relay Instance, and the end stations with clock targets are examples of time-aware systems that contain PTP End Instances.
Note 2: GM denotes Grandmaster PTP Instance

Figure 19-1— Time-aware network example where the four end stations near the bottom of the figure are connected to the bridge via an HDE link

When using HDE links, the use of "neighbor" refers to a device or to devices (end station or bridge) that is/are the intended recipient(s) of a transmitted PTP message. The intended recipient need not be the next physically closest device that is attached to the shared medium..

19.1.1.2 Half-duplex Ethernet (HDE) using PLCA (10BASE-T1S) PHYs

IEEE 802.3 PHYs that support Physical Layer Collision Avoidance (PLCA) form deterministic links by avoiding the MAC's random back-off caused by collisions (see Clause 148 of IEEE Std 802.3-2022). Simply stated, collisions are avoided by assigning local_nodeIDs, each of which represents a device's transmit opportunity number. One of the devices on the link sends out a BEACON, which starts the transmit opportunity cycle. Following each BEACON, the lowest local_nodeID gets to transmit first (assuming it has a frame ready to transmit) followed by the next higher local_nodeID, etc., until all the link's local_nodeIDs have been given a transmit opportunity. Then the process is repeated with another BEACON.

NOTE 1—In IEEE Std 802.3-2022, the only PHY that supports PLCA is 10BASE-T1S, which is specified in Clause 147 of IEEE Std 802.3-2022.

NOTE 2—Configuration of PLCA local_nodeID numbers, etc., are out of scope of this standard.

19.1.1.3 Overview of the major differences and restrictions of using HDE

The present clause uses Clause 11 in its entirety with the following major differences and restrictions (complete details follow starting in 19.1.2):

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

a) The peer delay initiator is restricted to timeReceivers only (see 19.1.2).
b) One-step time transport is not supported (see 19.1.3 and 19.2.16)
c) CMLDS is not supported (see 19.2.17)
d) External port configuration mode is the only mode supported (see 19.8)
e) The use of Signaling messages is not specified (see 19.8)
f) Hot Standby is not supported (see 19.8)

19.1.2 Propagation delay measurement over links

The measurement of propagation delay on an HDE PTP Link using the peer-to-peer delay mechanism is illustrated in Figure 11-1 and is described in 11.1.2, with the exception that the peer delay initiator is restricted to each timeReceiver port (i.e., an end station, or a timeReceiver port on a PTP Relay Instance)) and the timeTransmitter port does not initiate the peer-to-peer delay mechanism. Therefore, pdelayReqSendDisabled and pdelayRespSendDisabled are set as follows:

a) pdelayReqSendDisabled shall be set to TRUE for a timeTransmitter port or a PassivePort.
b) pdelayRespSendDisabled shall be set to TRUE for a timeReceiver port or a PassivePort.

19.1.3 Transport of time-synchronization information

The transport of time-synchronization information by a PTP Instance, using Sync and Follow_Up messages, is illustrated in Figure 11-2.

HDE links shall use two-step time transport as described in clause 11.1.3.

19.1.4 Model of operation

A PTP Instance contains one MD entity per PTP Instance, per PTP Port. This entity contains functions generic to all media, which are described in Clause 10, and functions specific to the respective medium for the PTP Link. Functions specific to HDE links are described in the current clause.

The model for a PTP Instance of a time-aware system with full-duplex point-to-point links is shown in Figure 11-3. This (HDE) Clause reuses Figure 11-3 (as its structure is unchanged for this clause), where all references to clause 11 in Figure 11-3 are to be replaced by references to clause 19 (this clause). The presence of one HDE MD entity per PTP Port is assumed. The media-independent entities shown in Figure 11-3 are described in 10.1.2.

A general, media-independent description of the generation of timestamps is given in 8.4.3. A more specific description for PTP event messages is given in 11.3.2.1. A PTP event message is timestamped relative to the LocalClock entity when the message timestamp point (see 3.17) crosses the timestamp measurement plane (see 3.33). The timestamp is corrected for any ingressLatency or egressLatency (see 8.4.3) to produce a timestamp relative to the reference plane (see 3.26). The corrected timestamp value is provided to the MD entity.

The MD entity behavior and detailed state machines specific to full-duplex point-to-point links, which are described in 11.2, are reused for HDE links subject to the conditions defined in 19.2. The behavior of the MD entity that is generic to all media is described in Clause 10.

19.2 State machines for HDE links

<<**Editor's note: Need to check the changes made in P802.1ASdm to clause 11.2 and its subclauses whether or not they have any implications for HDE.**>>

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

19.2.1 General

The state machines for HDE links are described in 11.2.1.

19.2.2 Determination of asCapable and asCapableAcrossDomains

Determination of asCapableAcrossDomains shall be as specified in 11.2.13.12.

NOTE: For full-duplex point-to-point links, asCapableAcrossDomains is a global variable for all domains per linkport. For HDE links, asCapableAcrossDomains is a global variable per PTP Instance (i.e., per domain), the name asCapableAcrossDomains has been kept for backwards compatibility with existing implementations.

19.2.3 Use of MAC Control PAUSE operation

This is not applicable when the IEEE 802.3 Clause 4 MAC is in half-duplex mode (see Clause 1.4.458 in Annex 31B of IEEE Std 802.3-2022).

19.2.4 Use of priority-based flow control

This is not applicable when the IEEE 802.3 Clause 4 MAC is in half-duplex mode (see Clause 1.4.489 of IEEE Std 802.3-2022).

19.2.5 Use of link aggregation

This is not applicable when the IEEE 802.3 Clause 4 MAC is in half-duplex mode (see Introduction in IEEE Std 802.1AX-2020).

19.2.6 Service interface primitives and data structures communicated between state machines

The following subclauses describe the service primitives and data structures communicated between the time-synchronization state machines of the MD entity. First the service primitives are described, followed by the data structures.

19.2.7 DL-UNITDATA.request

This service primitive is described in 2.2.1.1.1 of ISO/IEC 8802-2:1998 [B16].

19.2.8 DL-UNITDATA.indication

This service primitive is described in 2.2.1.1.1 of ISO/IEC 8802-2:1998 [B16].

19.2.9 MDTimestampReceive

This structure shall be as specified in in 11.2.9.

19.2.10 MDSyncReceive

This structure shall be as specified in 10.2.2.2.

19.2.11 MDSyncSend

This structure shall be as specified in 10.2.2.1.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

19.2.12 Overview of MD entity global variables

The overview of MD entity global variables is given in 11.2.12.

19.2.13 MD entity global variables

19.2.13.1 currentLogPdelayReqInterval: This variable shall be as specified in 11.2.13.1.

19.2.13.2 initialLogPdelayReqInterval: This variable shall be as specified in 11.2.13.2.

19.2.13.3 pdelayReqInterval: This variable shall be as specified in 11.2.13.3.

19.2.13.4 allowedLostResponses: This variable shall be as specified in 11.2.13.4.

19.2.13.5 allowedFaults: This variable shall be as specified in 11.2.13.5.

19.2.13.6 isMeasuringDelay: This variable shall be as specified in 11.2.13.6.

19.2.13.7 meanLinkDelayThresh: This variable shall be as specified in 11.2.13.7.

19.2.13.8 syncSequenceId: This variable shall be as specified in 11.2.13.8.

19.2.13.9 oneStepReceive: This variable shall be as specified in 11.2.13.9. It shall be set to FALSE for HDE.

19.2.13.10 oneStepTransmit: This variable shall be as specified in 11.2.13.10. It shall be set to FALSE for HDE.

19.2.13.11 oneStepTxOper: This variable shall be as specified in 11.2.13.11. It shall be set to FALSE for HDE.

19.2.13.12 asCapableAcrossDomains: This variable shall be as specified in 11.2.13.12.

19.2.13.13 nrrPdelay: This variable shall be as specified in 11.2.13.13.

19.2.13.14 nrrSync: This variable shall be as specified in 11.2.13.14.

19.2.13.15 nrrCompMethod: This variable shall be as specified in 11.2.13.15.

19.2.14 MDSyncReceiveSM state machine

The MDSyncReceiveSM state machine shall be as specified in 11.2.14.

19.2.15 MDSyncSendSM state machine

The MDSyncSendSM state machine shall be as specified in 11.2.15.

19.2.16 OneStepTxOperSetting state machine

This state machine is not used for HDE.

19.2.17 Common Mean Link Delay Service (CMLDS)

The Common Mean Link Delay Service (CMLDS) shall not be used for HDE.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

HDE uses the transport-specific peer-to-peer delay mechanism for all domains. Therefore, if the time-aware system implements multiple domains on an HDE link, all the domains use the transport-specific peer-to-peer delay mechanism on that link regardless of the domain numbers. However, if the time-aware system implements other PTP Ports that are full-duplex, point-to-point, those PTP Ports can use the transport-specific peer-to-peer delay mechanism or CMLDS as allowed by Clause 11.

If multiple TimeTransmitter ports are present on an HDE link, they are in different gPTP domains. CMLDS cannot be used because, in general, the TimeTransmitter ports can be on physical ports of different time-aware systems (i.e., different bridges). In this case, both meanLinkDelay and neighborRateRatio between a PTP End Instance in one of the domains and the TimeTransmitter it is communicating with can be different from meanLinkDelay and neighborRateRatio between a PTP End Instance in another domain on the same end station and the TimeTransmitter that PTP End Instance is communicating with.

19.2.18 Common Mean Link Delay Service (CMLDS) global variables

The Common Mean Link Delay Service (CMLDS) global variables are not used for HDE links.

19.2.19 MDPdelayReq state machine

The MDPdelayReq state machine shall be as specified in 11.2.19.

The variable pdelayReqSendDisabled is set per 19.1.2.

19.2.20 MDPdelayResp state machine

The MDPdelayResp state machine shall be as specified in 11.2.20.

The variable pdelayRespSendDisabled is set per 19.1.2.

19.2.21 LinkDelayIntervalSetting state machine

This state machine is not used for HDE.

19.3 Message attributes

Message attributes shall be as specified in 11.3.

19.4 Message formats

Message formats shall be as specified in 11.4, except for 11.4.2.4, where the domainNumber for Pdelay_Req, Pdelay_Resp, and Pdelay_Resp_Follow_Up messages shall be the domain number of the HDE gPTP domain used by the transport-specific peer delay mechanism. The domainNumber for all other PTP messages is as specified in 10.6.2.2.6.

19.5 Protocol timing characterization

19.5.1 General

This subclause specifies timing attributes for the media-dependent sublayer specified in this clause.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

19.5.2 Message transmission intervals

19.5.2.1 General interval specification

The mean time interval between successive Pdelay_Req messages is represented as the logarithm to the base 2 of this time interval measured in seconds. The value of this logarithmic attribute shall be as specified in 19.5.2.2.

The mean time interval between successive Sync messages shall be as specified in 10.7.2.1, 10.7.2.3, and 19.5.2.3.

19.5.2.2 Pdelay_Req message transmission interval

Pdelay_Req message transmission interval is specified in 11.5.2.2. The variable useMgtSettableLogPdelayReqInterval shall be set to TRUE.

19.5.2.3 Sync message transmission interval default value

The Sync message transmission interval default value shall be as specified in 11.5.2.3.

In the case of non-deterministic behavior (see IEEE Std 802.3) in an HDE link, the nondeterministic behavior needs to be considered in determining whether the requirements of 10.7.2.3 for the Sync message transmission interval are met.

19.5.3 allowedLostResponses

The variable allowedLostResponses shall be as specified in 11.5.3.

19.5.4 allowedFaults

The variable allowedFaults shall be as specified in 11.5.4.

19.6 Control of computation of neighborRateRatio

The control of computation of neighborRateRatio shall be as specified in 11.6.

19.7 Control of computation of meanLinkDelay

The control of computation of meanLinkDelay shall be as specified in 11.7.

19.8 HDE settings and configuration

This clause provides settings and configurations that are specific for HDE.

The per PTP Instance global variable externalPortConfigurationEnabled shall be set to TRUE for HDE.

Both GptpCapableTransmit and GptpCapableReceive state machines shall be disabled for HDE, and therefore gptpCapableStateMachinesEnabled shall be set to FALSE (see 10.4.1). According to 10.4.1, if the managed object gptpCapableStateMachinesEnabled is FALSE, the global variable neighborGptpCapable for the port (see 10.2.5.16) is set to TRUE.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

<<**Editor's note: The ability to disable GptpCapableTransmit and GptpCapableReceive state machines are specified in clause 10.4.1 in P802.1ASdm, however P802.1ASds is an amendment of IEEE 802.1AS-2020-Rev then P802.1ASdm is not mentioned in the paragraph above, as it will be rolled up in IEEE 802.1AS-2020-Rev>>**

The use of Signaling messages on HDE links is not specified by this standard.

Hot Standby (see Clause 18) is not supported on HDE links.

The SyncIntervalSetting and the AnnounceIntervalSetting state machines are not used for HDE. The variables useMgtSettableLogSyncInterval and useMgtSettableLogAnnounceInterval shall be set to TRUE.

Copyright © 2024 IEEE. All rights reserved.
This is an unapproved IEEE Standards draft, subject to change.

Annex A

(normative)

Protocol Implementation Conformance Statement (PICS) proforma[3]

Add a row at the end of Table A.5 as follows:

A.5 Major Capabilities

Item	Feature	Status	References	Support
MDHDE	Does the PTP Instance support media-dependent HDE link functionality on one or more PTP Ports?	O.1	5.9, 11, 19, A.6, A.22	Yes [ ] No [ ]

Change A.6 as follows:

A.6 Media access control methods

Item	Feature	Status	References	Support
MAC-IEEE-802.3 MAC-IEEE-802.11	Which MAC methods are implemented in conformance with the relevant MAC standards?	O:2 O:2	11.1 19.1 12.1	Yes [ ] No [ ] Yes [ ] No [ ] Yes [ ] No [ ]
MAC-1	Has a PICS been completed for each of the MAC methods implemented as required by the relevant MAC Standards?	M		Yes [ ]
MAC-2	Do all the MAC methods implemented support the MAC Timing aware Service as specified?	M	Clause 11 Clause 12 Clause 13 Clause 19	Yes [ ]

[3] *Copyright release for PICS proformas:* Users of this standard may freely reproduce the PICS proforma in this annex so that it can be used for its intended purpose and may further publish the completed PICS.

Copyright © 2024 IEEE. All rights reserved.

Change A.21 as follows:

A.21 External port configuration

Item	Feature	Status	References	Support
	If item EXT is not supported, mark N/A.			NA[ ]
EXT-1	Does the PTP Instance support the specifications for externalPortConfigurationEnabled value of true?	EXT:M	10.3.1 19.8	Yes [ ]
EXT-2	Does the PTP Instance support the PortAnnounceInformationExt state machine?	EXT:M	10.3.14	Yes [ ]
EXT-3	Does the PTP Instance support the PortStateSettingExt state machine?	EXT:M	10.3.15	Yes [ ]

<<Editor's note: Table A.22 is based on Table A.13 for full-duplex point-to-point link. Please, check.>

Insert Table A.22 as follows:

A.22 Media-dependent, HDE link

Item	Feature	Status	References	Support
MDHDE-1	Does this PTP Port implement the functionality of the MDSyncReceiveSM state machine in compliance with the requirements of 19.2.14, 11.2.14 and Figure 11-6?	MDHDE:M	19.2.14, 11.2.14	Yes [ ]
MDHDE-2	Does this PTP Port implement the functionality of the MDSyncSendSM state machine in compliance with the requirements of 19.2.15, 11.2.15 and Figure 11-7?	MIMSTR and MDHDE:M	19.2.15, 11.2.15	Yes [ ]
MDHDE-3	Does this port implement the functionality of the MDPdelayRequest state machine in compliance with the requirements of 19.1.2, 19.2.19, 11.2.19 and Figure 11-9?	MDHDE:M	19.1.2, 19.2.19, 11.2.19	Yes [ ]
MDHDE-4	Does this port implement the functionality of the MDPdelayResponse state machine in compliance with the requirements of 19.1.2, 19.2.20, 11.2.20 and Figure 11-10?	MDHDE:M,	19.2.20 19.1.2 11.2.20	Yes [ ]
MDHDE-5	Does this PTP Port timestamp Sync messages on ingress with respect to the LocalClock in compliance with 19.3, 11.3.2.1 and 11.3.9?	MDHDE:M	19.3, 11.3.2.1	Yes [ ]
MDHDE-6	Does this PTP Port timestamp Sync messages on egress with respect to the LocalClock in compliance with the requirements of 19.3, 11.3.2.1 and 11.3.9?	MIMSTR and MDHDE:M	19.3 11.3.2.1	Yes [ ]
MDHDE-7	Does this port timestamp Pdelay_Req messages on ingress and egress with respect to the LocalClock in compliance with the requirements of 19.3, 11.3.2.1 and 11.3.9?	MDHDE:M	19.3, 11.3.2.1	Yes [ ]

Copyright © 2024 IEEE. All rights reserved.

A.22 Media-dependent, HDE link *(continued)*

Item	Feature	Status	References	Support
MDHDE-8	Does this port timestamp Pdelay_Resp messages on ingress and egress with respect to the LocalClock in compliance with the requirements of 19.3, 11.3.2.1 and 11.3.9?	MDHDE:M	19.3, 11.3.2.1	Yes [ ]
MDHDE-9	Are all IEEE 802.1AS messages on this port sent without a Q-tag in compliance with the requirements of 19.3, 11.3.3?	MDHDE:M	19.3, 11.3.3	Yes [ ]
MDHDE-10	Do all media-dependent messages transmitted on this port use a destination MAC address taken from Table 11-3 in compliance with the requirements of 19.3 and 11.3.4 [01-80-C2-00-00-0E]?	MDHDE:M	19.3, 11.3.4	Yes [ ]
MDHDE-11	Do all media-dependent messages transmitted on this port use a source MAC address that is assigned to that port in compliance with the requirements of 19.3 and 11.3.4?	MDHDE:M	19.3, 11.3.4	Yes [ ]
MDHDE-12	Do all media-dependent message tranmitted on this port us an EtherType specified in Table 11-4 [88-F7]?	MDHDE:M	19.3, 11.3.5	Yes [ ]
MDHDE-13	Does the header of all the media-dependent messages on this port comply with the requirements of 19.4, 11.4.2 and Table 10-7?	MDHDE:M	19.4, 11.4.2	Yes [ ] N/A [ ]
MDHDE-14	Does the body of Sync messages sent on this PTP Port comply with the requirements of 19.4, 11.4.3, Table 11-8, and Table 11-9?	MDHDE:M	19.4, 11.4.3	Yes [ ]
MDHDE-15	Does the body of Follow_Up messages sent on this PTP Port comply with the requirements of 19.4, 11.4.4, 6.4.3.3 (lastGmPhaseChange), and Table 11-10?	MDHDE:M	19.4, 11.4.4, 6.4.3.3	Yes [ ]
MDHDE-16	Does the body of Pdelay_Req messages sent on this port comply with the requirements of 19.4, 11.4.5 and Table 11-12?	MDHDE:M	19.4, 11.4.5	Yes [ ]
MDHDE-17	Does the body of Pdelay_Resp messages sent on this port comply with the requirements of 19.4, 11.4.6 and Table 11-13?	MDHDE:M	19.4, 11.4.6	Yes [ ]
MDHDE-18	Does the body of Pdelay_Resp_Follow_Up messages sent on this port comply with the requirements of 19.4, 11.4.7 and Table 11-14?	MDHDE:M	19.4, 11.4.7	Yes [ ]
MDHDE-19	Are all reserved fields in media-dependent messages sent on this port set to 0 in compliance with the requirements of 19.4, 11.4.1?	MDHDE:M	19.4, 11.4.1	Yes [ ]
MDHDE-20	Do the Sync message sequence numbers comply with the requirements of 19.3, 11.3.8?	MIMSTR and MDHDE:M	19.3, 11.3.8	Yes [ ] N/A [ ]

Copyright © 2024 IEEE. All rights reserved.

A.22 Media-dependent, HDE link *(continued)*

Item	Feature	Status	References	Support
MDHDE-21	Do the Pdelay_Req message sequence numbers comply with the requirements of 19.3 and 11.3.8?	MDHDE:M	19.3, 11.3.8	Yes [ ]
MDHDE-22	Does the Pdelay mean request transmission interval comply with the requirements of 19.5.2.2 and 11.5.2.2?	MDHDE:M	19.5.2.2, 11.5.2.2	Yes [ ]
MDHDE-23	Does the Sync mean transmission interval comply with the requirements of 19.5.2.3 and 11.5.2.3?	MDHDE:M	19.5.2.3, 11.5.2.3	Yes [ ]
MDHDE-24	Does the HDE media-dependent layer set the asCapable global variable in the media-independent PortSync entity in compliance with the requirements of 19.2.2 and 11.2.2?	MDHDE:M	19.2.2, 11.2.2	Yes [ ]
MDHDE-25	Does the PTP Instance consider the PTP Port or Link Port, respectively, to not be exchanging Pdelay messages when a valid response is not received in compliance with the requirements of 19.5.3 and 11.5.3?	MDHDE:M	19.5.3, 11.5.3	Yes [ ]
MDHDE-26	Does the PTP Instance ignore TLVs, of PTP messages, that it cannot parse and attempt to parse the next TLV, in compliance with the requirements of 19.4 and 11.4.1?	MDHDE:M	19.4, 11.4.1	Yes [ ]
MDHDE-27	Does the time-aware system initialize meanLinkDelayThresh as specified in 19.2.2 and 11.2.2?	MDHDE:M	19.2.2, 11.2.2	Yes [ ]
MDHDE-28	Does this port support propagation delay averaging?	MDHDE:O	19.2.19, 11.2.19.3.4	Yes [ ] No [ ]
MDHDE-29	Does this port support two-step capability on receive?	MDHDE:M	19.2.14, 11.2.14, item d) of 5.5	Yes [ ]
MDHDE-30	Does this port support two-step capability on transmit?	MDHDE:M	19.2.15, 11.2.15, item e) of 5.5	Yes [ ]
MDHDE-31	Is the transport-specific peer-to-peer delay mechanism supported?	MDHDE:M	19.2.17	Yes [ ]

Copyright © 2024 IEEE. All rights reserved.

Annex F

(informative)

PTP profile included in this standard

F.1 General

Change the paragraph in F.1 as follows:

The specification in this standard of synchronized time transport over a full-duplex point-to-point link includes a PTP profile. The information contained in a PTP profile is described in 20.3 of IEEE Std 1588-2019. This annex summarizes the PTP profile for transport of timing over full-duplex point-to-point links. This PTP profile is also used in the transport of timing over HDE (see Clause 19), and in the transport of timing over CSN when a CSN clock reference is not present (see Clause 16). This PTP profile is not used in the transport of timing over IEEE 802.11 links and IEEE 802.3 EPON links; both these transports use native timing mechanisms to assist in the synchronized time transport.

Copyright © 2024 IEEE. All rights reserved.