

Draft Standard for Local and metropolitan area networks—

Link-local Registration Protocol

Corrigendum 1: Corrections to Management Modules and Protocol Encoding

Unapproved draft, prepared by the
Time-Sensitive Networking (TSN) Task Group of IEEE 802.1

Sponsored by the
LAN/MAN Standards Committee
of IEEE Computer Society the

This page and the following cover pages are not part of the draft. They provide revision and other information for IEEE 802.1 Working Group members and participants in the IEEE Standards Association ballot process, and will be updated as convenient. Blank pages allow for the future addition of cross-references to changed text without forcing renumbering of all pages in the draft. Pages are numbered from 1 (including cover pages) for the convenience of reviewers whose PDF viewers do not easily accommodate different numbering sequences. Pages will of course be renumbered prior to publication as a standard.

The text proper of this draft begins with the [Title page](#).

Important Notice

This document is an unapproved draft of a proposed IEEE Standard. IEEE hereby grants the named IEEE SA Working Group or Standards Committee Chair permission to distribute this document to participants in the receiving IEEE SA Working Group or Standards Committee, for purposes of review for IEEE standardization activities. No further use, reproduction, or distribution of this document is permitted without the express written permission of IEEE Standards Association (IEEE SA). Prior to any review or use of this draft standard, in part or in whole, by another standards development organization, permission must first be obtained from IEEE SA (stds-copyright@ieee.org). This page is included as the cover of this draft, and shall not be modified or deleted.

IEEE Standards Association
445 Hoes Lane
Piscataway, NJ 08854, USA

1 **Draft status**

2 This draft P802.1CS-2020/Cor1/D2.1 is being issued for initial Standards Association ballot. The 802.1
3 Working Group ballot that preceded this Standards Association ballot closed with no Disapprove ballots and
4 no comments. The text of the draft (including page numbering) is unchanged from the balloted draft, with
5 the exception of updates to these cover pages (not part of this draft) and the consequent update of the date
6 shown in the header of most pages.

7 Information in the cover letter for this ballot is repeated below.

8 **Editorial suggestions**

9 Please note, that professional editing takes place once the document is approved, and as such, required
10 editorial changes will be reviewed/made then (e.g., punctuation, grammar, formatting, style consistency).
11 The following editorial suggestions will also be considered as part of this initial ballot: << >>.

12 **MIB and YANG modules**

13 The YANG module is attached in plain text (UTF-8) format to the draft pdf. Also included is a txt file
14 showing the differences between the YANG module in the base document IEEE Std 802.1CS-2020, and the
15 replacement YANG module specified in this corrigendum draft.

¹ This page intentionally left blank.

¹ This page intentionally left blank.

¹ This page intentionally left blank.

¹ This page intentionally left blank.

¹ This page intentionally left blank.

2

Draft Standard for Local and metropolitan area networks— Link-local Registration Protocol

Corrigendum 1: Corrections to Management Modules and Protocol Encoding

Unapproved draft, prepared by the
Time-Sensitive Networking (TSN) Task Group of IEEE 802.1

Sponsored by the
LAN/MAN Standards Committee
of the
IEEE Computer Society

Copyright ©2023 by the IEEE.
3 Park Avenue
New York, NY 10016-5997
USA

All rights reserved.

This document is an unapproved draft of a proposed IEEE Standard. As such, this document is subject to change. USE AT YOUR OWN RISK! IEEE copyright statements SHALL NOT BE REMOVED from draft or approved IEEE standards, or modified in any way. Because this is an unapproved draft, this document must not be utilized for any conformance/compliance purposes. Permission is hereby granted for officers from each IEEE Standards Working Group or Committee to reproduce the draft document developed by that Working Group for purposes of international standardization consideration. IEEE Standards Department must be informed of the submission for consideration prior to any reproduction for international standardization consideration (stds.ipr@ieee.org). Prior to adoption of this document, in whole or in part, by another standards development organization, permission must first be obtained from the IEEE Standards Department (stds.ipr@ieee.org). When requesting permission, IEEE Standards Department will require a copy of the standard development organization's document highlighting the use of IEEE content. Other entities seeking permission to reproduce this document, in whole or in part, must also obtain permission from the IEEE Standards Department.

IEEE Standards Activities Department
445 Hoes Lane
Piscataway, NJ 08854, USA

¹ **Abstract:** Corrects errors in the YANG module, SNMP MIB and TLV encoding in IEEE Std
² 802.1CS-2020.

³ **Keywords:** Bridged Local Area Networks, bridges, bridging, IEEE 802®, IEEE 802.1CS™, IEEE
⁴ 802.1Q™, Link-local Registration Protocol, local area networks (LANs), LRP, MAC Bridges, Time-
⁵ Sensitive Networking, TSN, Virtual Bridged Local Area Networks (virtual LANs).

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2023 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published dd month year. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

Print: ISBN 978-X-XXX-XXX-X STDXXXXX
PDF: ISBN 978-X-XXX-XXX-X STDPDXXXXX

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

1 Important Notices and Disclaimers Concerning IEEE Standards Documents

2 IEEE Standards documents are made available for use subject to important notices and legal disclaimers.
3 These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>),
4 appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning
5 IEEE Standards Documents.”

6 Notice and Disclaimer of Liability Concerning the Use of IEEE Standards 7 Documents

8 IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating
9 Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards
10 through an accredited consensus development process, which brings together volunteers representing varied
11 viewpoints and interests to achieve the final product. IEEE Standards are documents developed by
12 volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers
13 are not necessarily members of IEEE or IEEE SA, and participate without compensation from IEEE. While
14 IEEE administers the process and establishes rules to promote fairness in the consensus development
15 process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the
16 soundness of any judgments contained in its standards.

17 IEEE makes no warranties or representations concerning its standards, and expressly disclaims all
18 warranties, express or implied, concerning this standard, including but not limited to the warranties of
19 merchantability, fitness for a particular purpose and non-infringement. In addition, IEEE does not warrant
20 or represent that the use of the material contained in its standards is free from patent infringement. IEEE
21 standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

22 Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there
23 are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to
24 the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and
25 issued is subject to change brought about through developments in the state of the art and comments
26 received from users of the standard.

27 In publishing and making its standards available, IEEE is not suggesting or rendering professional or other
28 services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any
29 other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his
30 or her own independent judgment in the exercise of reasonable care in any given circumstances or, as
31 appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE
32 standard.

33 IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
34 EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE
35 NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
36 BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
37 WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
38 OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON
39 ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND
40 REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

1 Translations

2 The IEEE consensus development process involves the review of documents in English only. In the event
3 that an IEEE standard is translated, only the English version published by IEEE is the approved IEEE
4 standard.

5 Official statements

6 A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board
7 Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its
8 committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures,
9 symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall
10 make it clear that the presenter's views should be considered the personal views of that individual rather than
11 the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group.

12 Comments on standards

13 Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of
14 membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations,**
15 **consulting information, or advice pertaining to IEEE Standards documents.**

16 Suggestions for changes in documents should be in the form of a proposed change of text, together with
17 appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is
18 important that any responses to comments and questions also receive the concurrence of a balance of
19 interests. For this reason, IEEE and the members of its Societies and Standards Coordinating Committees
20 are not able to provide an instant response to comments, or questions except in those cases where the matter
21 has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any
22 person who would like to participate in evaluating comments or in revisions to an IEEE standard is welcome
23 to join the relevant IEEE working group. You can indicate interest in a working group using the Interests tab
24 in the Manage Profile & Interests area of the [IEEE SA myProject system](#).¹ An IEEE Account is needed to
25 access the application.

26 Comments on standards should be submitted using the [Contact Us](#) form.²

27 Laws and regulations

28 Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the
29 provisions of any IEEE Standards document does not imply compliance to any applicable regulatory
30 requirements. Implementers of the standard are responsible for observing or referring to the applicable
31 regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not
32 in compliance with applicable laws, and these documents may not be construed as doing so.

33 Data privacy

34 Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and
35 data ownership in the context of assessing and using the standards in compliance with applicable laws and
36 regulations.

1. Available at: <https://development.standards.ieee.org/myproject-web/public/view.html#landing>.

2. Available at: <https://standards.ieee.org/content/ieee-standards/en/about/contact/index.html>.

1 Copyrights

2 IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws.
3 They are made available by IEEE and are adopted for a wide variety of both public and private uses. These
4 include both use, by reference, in laws and regulations, and use in private self-regulation, standardization,
5 and the promotion of engineering practices and methods. By making these documents available for use and
6 adoption by public authorities and private users, IEEE does not waive any rights in copyright to the
7 documents.

8 Photocopies

9 Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to
10 photocopy portions of any individual standard for company or organizational internal use or individual, non-
11 commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center,
12 Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to
13 photocopy portions of any individual standard for educational classroom use can also be obtained through
14 the Copyright Clearance Center.

15 Updating of IEEE Standards documents

16 Users of IEEE Standards documents should be aware that these documents may be superseded at any time
17 by the issuance of new editions or may be amended from time to time through the issuance of amendments,
18 corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the
19 document together with any amendments, corrigenda, or errata then in effect.

20 Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years
21 old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of
22 some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that
23 they have the latest edition of any IEEE standard.

24 In order to determine whether a given document is the current edition and whether it has been amended
25 through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#).³ For more
26 information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

27 Errata

28 Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#).⁴ Search for standard number
29 and year of approval to access the web page of the published standard. Errata links are located under the
30 Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to
31 periodically check for errata.

32 Patents

33 IEEE Standards are developed in compliance with the [IEEE SA Patent Policy](#).⁵

34 Attention is called to the possibility that implementation of this standard may require use of subject matter
35 covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the
36 existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has
37 filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the

3. Available at: <https://ieeexplore.ieee.org/browse/standards/collection/ieee>.

4. Available at: <https://standards.ieee.org/standard/index.html>.

5. Available at: <https://standards.ieee.org/about/sasb/patcom/materials.html>.

1 IEEE SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may
2 indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without
3 compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of
4 any unfair discrimination to applicants desiring to obtain such licenses.

5 Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not
6 responsible for identifying Essential Patent Claims for which a license may be required, for conducting
7 inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or
8 conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing
9 agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that
10 determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their
11 own responsibility. Further information may be obtained from the IEEE Standards Association.

12 **IMPORTANT NOTICE**

13 IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure
14 against interference with or from other devices or networks. IEEE Standards development activities consider
15 research and information presented to the standards development group in developing any safety
16 recommendations. Other information about safety practices, changes in technology or technology
17 implementation, or impact by peripheral systems also may be pertinent to safety considerations during
18 implementation of the standard. Implementers and users of IEEE Standards documents are responsible for
19 determining and complying with all appropriate safety, security, environmental, health, and interference
20 protection practices and all applicable laws and regulations.

1 Participants

2 <<The following lists will be updated in the usual way prior to publication>>

3 At the time this standard was completed, the IEEE 802.1 working group had the following membership:

4 **Glenn Parsons, *Chair***
5 **Jessy Rouyer, *Vice Chair***
6 **János Farkas, *TSN Task Group Chair***
7 **Norman Finn, *Editor***
8

9 The following members of the individual balloting committee voted on this standard. Balloters may have
10 voted for approval, disapproval, or abstention.

A.N. Other

11 <<The above lists will be updated in the usual way prior to publication>>

12

1

2 When the IEEE-SA Standards Board approved this standard on <dd> <month> <year>, it had the following
3 membership:

4

Chair

5

Vice-Chair

6

Past Chair

7

Secretary

8

*Member Emeritus

9

<<The above lists will be updated in the usual way prior to publication>>

10

1 Introduction

2

This introduction is not part of IEEE Std 802.1CS-2020/Cor1, IEEE Standard for Local and metropolitan area networks—Bridges and Bridged Networks—Corrigendum 1: Corrections to Management Modules and Protocol Encoding

3 This corrigendum to IEEE Std 802.1CS-2020 corrects errors in the YANG module, SNMP MIB and TLV
4 encoding.

5

Contents

1	2	1.	Overview.....	20
3		1.1	Scope.....	20
4	6.		Link-local Registration Protocol.....	21
5	6.3		Objectives and non-objectives	21
6	6.3.1		Objectives of LRP	21
7	12.		YANG models for LRP	22
8	12.2		The YANG framework	22
9	12.6		Definition of LRP YANG module.....	22
10	13.		MIB modules for LRP	30
11	13.5		MIB modules	30
12	13.5.1		LRP Textual conventions MIB	30
13	13.5.2		LRP MIB	32
14	13.5.3		LLDPv2 LRP extension MIB	44
15	Annex C	(normative)	IEEE 802.1 Organizationally Specific TLVs for LLDP.....	62
16	C.2		Organizationally Specific TLV definitions.....	62
17	C.2.2		LRP TCP Discovery TLV	62

¹ **Tables**

²	Table C-1	Allowed address information encodings and lengths	62
--------------	-----------	---	----

1

2

3 **Draft Standard for** 4 **Local and Metropolitan Networks —**

5 **Link-local Registration Protocol**

6 **Corrigendum 1: Corrections to Management** 7 **Modules and Protocol Encoding**

8 (Corrigendum to IEEE Std 802.1CS™–2020)

9 NOTE—The editing instructions contained in this corrigendum define how to merge the material contained therein into
10 the existing base standard and its amendments to form the comprehensive standard.

11 The editing instructions are shown in ***bold italics***. Four editing instructions are used: change, delete, insert,
12 and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies
13 the location of the change and describes what is being changed by using ~~striketrough~~ (to remove old
14 material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material
15 without disturbing the existing material. Deletions and insertions may require renumbering. If so,
16 renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or
17 equations by removing the existing figure or equation and replacing it with a new one. Editing instructions,
18 change markings, and this note will not be carried over into future editions because the changes will be
19 incorporated into the base standard.

1 *Change ABSTRACT as follows:*

2 **Abstract:** This standard specifies protocols, procedures, and managed objects for a Link-local
3 Registration Protocol (LRP) to replicate a registration database from one end to the other of a
4 point-to-point link and to replicate changes to parts of that database. A facility is provided to purge
5 the replicated database if the source becomes unresponsive. LRP is optimized for databases on
6 the order of ~~1-Mbyte~~[a million bytes](#).

7 **1. Overview**

8 **1.1 Scope**

9 *Change 1.1 as follows:*

10 This standard specifies protocols, procedures, and managed objects for a Link-local Registration Protocol
11 (LRP) to replicate a registration database from one end to the other of a point-to-point link and to replicate
12 changes to parts of that database. A facility is provided to purge the replicated database if the source
13 becomes unresponsive. Provision is made for a proxy system to operate LRP on behalf of a controlled
14 system. LRP is optimized for databases on the order of ~~1-Mbyte~~[a million bytes](#).

6. Link-local Registration Protocol

6.3 Objectives and non-objectives

6.3.1 Objectives of LRP

Change 6.3.1 as follows:

The objectives of LRP are to:

- a) Serve application instances as described in 6.2.
- b) Remain independent of the syntax and semantics of the LRP application data contained in the applicant and registrar databases.
- c) Provide a facility for an application instance to discover its peers, and to make and break associations between application instances.
- d) Support multiple options for the transport mechanisms used to carry LRPDUs, in order to provide a range of capability/complexity trade-offs.
- e) Transfer the application instances' data quickly, reliably, and efficiently with respect to bandwidth.
- f) Efficiently transfer changes to parts of a database, without retransmitting the whole database.
- g) Serve applicant and registrar databases whose size, per port, is on the order of magnitude of ~~1-Mbyte~~ [a million bytes](#).
- h) Support only point-to-point associations between application instances.
- i) Support multiple point-to-point associations on one port.
- j) By the use of TCP as an LRP-DT transport mechanism, provide for placing the application instance and Portal in a separate Proxy system from its target port, in order to facilitate central control of a network.
- k) Support proxying for a Controlled system without requiring any new behaviors of the Controlled system, in order to make it possible to deploy a new LRP application without implementing an application instance in every system.
- l) Make efficient use of TCP connections.
- m) Support resource-constrained end systems.

12. YANG models for LRP

12.2 The YANG framework

Change 12.2 as follows:

This clause has been developed according to the YANG guidelines published in RFC6087 ([D12]) as applicable to IEEE standards. The YANG framework applies hierarchy in the following areas:

- 1) The uniform resource name (URN), as specified in IEEE Std 802d. ~~The structure of the URN is such that “ieee” is the root (i.e., name-space identifier), followed by the standard, then the working group developing the standard.~~
- 2) The YANG objects form a hierarchy of configuration and operational data structures that define the YANG model. These hierarchical relationships are described in 11.2 and 12.5.

12.6 Definition of LRP YANG module

Delete the YANG module in 12.6:

Insert the following YANG module in 12.6:

```
module ieee802-dot1cs-lrp {
  yang-version 1.1;

  namespace "urn:ieee:std:802.1CS:yang:ieee802-dot1cs-lrp";
  prefix "dot1cs";

  import ietf-system { prefix "sys"; }
  import ietf-yang-types { prefix "yang"; }
  import ietf-interfaces { prefix if; }
  import ieee802-types { prefix ieee; }
  import ietf-inet-types { prefix inet; }

  organization
    "Institute of Electrical and Electronics Engineers";
  contact
    "WG-URL: http://ieee802.org/1/
    WG-EMail: stds-802-1-l@ieee.org
    Contact: IEEE 802.1 Working Group Chair
    Postal: C/O IEEE 802.1 Working Group
    IEEE Standards Association
    445 Hoes Lane
    Piscataway
    NJ 08854
    USA

    E-mail: stds-802-1-chairs@ieee.org";

  description
    "This module provides management of systems that support the
    Link-local Registration Protocol (LRP).

    Copyright (C) IEEE (2023).

    This version of this YANG module is part of IEEE Std 802.1CS-2020/Cor1;
    see the standard itself for full legal notices.";

  revision 2023-11-16 {
    description
      "Published as part of IEEE Std 802.1CS-2020/Cor1.

      The following reference statement identifies each referenced
      IEEE Standard as updated by applicable amendments.";

    reference
      "IEEE Std 802.1CS:
```

```
1 IEEE Std 802.1CS-2020 Link-local Registration Protocol,
2 IEEE Std 802.1CS-2020 Corrigendum 1: Corrections to
3 Management Modules and Protocol Encoding.";
4 }
5
6 revision 2020-12-03 {
7   description
8     "First defined in IEEE P802.1CS-2020";
9   reference
10    "IEEE Std 802.1CS-2020.";
11 }
12 /*-----*/
13 /* Feature */
14 /*-----*/
15
16 feature lrp {
17   description
18     "Feature Link-local Registration Protocol";
19 }
20
21 /*-----*/
22 /* Type Definitions */
23 /*-----*/
24 typedef lrp-dt-address-union {
25   type union {
26     type ieee:mac-address;
27     type inet:ipv4-address;
28     type inet:ipv6-address;
29   }
30 }
31
32 /*-----*/
33 /* Configuration Data */
34 /*-----*/
35 /*
36   Link-local Registration Protocol
37 */
38 augment "/sys:system" {
39   description "Link-local Registration Protocol";
40   container lrp {
41     if-feature lrp;
42     description
43       "Configure the Link-local Registration Protocol";
44     leaf lrp-ack-timer-init {
45       type uint32;
46       units "milliseconds";
47       config false;
48       description
49         "A read-only integer n specifying the number of milliseconds for
50         ackTimerInit (D.2.12.6 of IEEE Std 802.1Q-2018)";
51       reference
52         "11.3.1 of IEEE Std 802.1CS";
53     }
54     leaf lrp-reconnect-max {
55       type uint16;
56       units "seconds";
57       description
58         "An integer number of seconds which is the maximum value for
59         instReconnectReset.";
60       reference
61         "11.3.2 of IEEE Std 802.1CS";
62     }
63     list portal {
64       key "portal-id";
65       config false;
66       leaf portal-id {
67         type uint32;
68         config false;
69         description
70           "Local Identifier of portal";
71         reference
72           "Clause 10 of IEEE Std 802.1CS";
```

```
1     }
2     leaf target-port-interface-ref {
3         type if:interface-ref;
4         config false;
5         description
6             "The interface reference identifying the target
7             port to which this portal is attached.";
8         reference
9             "8.2.1 of IEEE Std 802.1CS";
10    }
11    leaf lrp-dt-instance-id {
12        type leafref {
13            path "/sys:system/dot1cs:lrp/dot1cs:lrp-dt-instance/dot1cs:instance-id";
14        }
15        config false;
16        description
17            "The LRP-DT instance id that this portal is
18            attached to.";
19        reference
20            "8.2.1 of IEEE Std 802.1CS";
21    }
22    leaf application-id {
23        type string;
24        config false;
25        description
26            "The value transmitted in, and expected to be received in, the
27            appId field of Hello LRPDU's.";
28        reference
29            "8.2.2.1 of IEEE Std 802.1CS";
30    }
31    leaf my-chassis-id {
32        type ieee:chassis-id-type ;
33        config false;
34        description
35            "The value transmitted in the My Chassis ID TLV, and expected to be
36            received in the Neighbor Chassis ID TLV, of Hello LRPDU's";
37        reference
38            "8.2.2.2 of IEEE Std 802.1CS";
39    }
40    leaf my-port-id {
41        type ieee:port-id-type ;
42        config false;
43        description
44            "The value transmitted in the My Port ID TLV, and expected to be
45            received in the Neighbor Port ID TLV, of Hello LRPDU's.";
46        reference
47            "8.2.2.3 of IEEE Std 802.1CS";
48    }
49    leaf neighbor-chassis-id {
50        type ieee:chassis-id-type ;
51        config false;
52        description
53            "The value transmitted in the Neighbor Chassis ID TLV, and expected
54            to be received in the My Chassis ID TLV, of Hello LRPDU's.";
55        reference
56            "8.2.2.4 of IEEE Std 802.1CS";
57    }
58    leaf neighbor-port-id {
59        type ieee:port-id-type ;
60        config false;
61        description
62            "The value transmitted in the Neighbor Port ID TLV, and expected to
63            be received in the My Port ID TLV, of Hello LRPDU's.";
64        reference
65            "8.2.2.5 of IEEE Std 802.1CS";
66    }
67    leaf my-hello-status {
68        type enumeration {
69            enum hs-looking {
70                value 1;
71                description
72                    "This Portal has not yet received a successful Associate Portal
```



```
1         request.";
2     }
3     enum hs-connecting {
4         value 2;
5         description
6             "This Portal has received a successful Associate Portal
7             request, and a Hello LRPDU with the hsLooking status. The
8             Portal is ready to receive all LRPDUs.";
9     }
10    enum hs-connected {
11        value 3;
12        description
13            "This Portal is up and ready to transfer LRP application data.
14            The Portal is allowed to transmit all LRPDUs.";
15    }
16    }
17    config false;
18    description
19        "An enumerated value to be transmitted in the Hello status field
20        of any Hello LRPDU.";
21    reference
22        "8.2.2.8 of IEEE Std 802.1CS";
23    }
24    leaf local-overflow {
25        type boolean;
26        config false;
27        description
28            "Contains the last Boolean input from the Database overflow
29            request. A value of TRUE indicates that the partner applicant
30            database has exceeded the capacity of the local registrar LRP
31            application.";
32        reference
33            "8.2.2.10 of IEEE Std 802.1CS";
34    }
35    leaf neighbor-overflow {
36        type boolean;
37        config false;
38        description
39            "A Boolean copied from the last-received database overflow bit [bit
40            8] in the Error status field of the last-received Hello LRPDU.";
41        reference
42            "8.2.2.11 of IEEE Std 802.1CS";
43    }
44    leaf neighbor-acknowledged {
45        type boolean;
46        config false;
47        description
48            "A Boolean, equal to the AND of all of the actAcknowledged
49            variables for all of the Applicant state machines (records) on this
50            Portal.";
51        reference
52            "8.2.2.12 of IEEE Std 802.1CS";
53    }
54    leaf my-app-hello-info {
55        type string;
56        config false;
57        description
58            "Value to put in the Application Information TLV of a
59            transmitted Hello LRPDU.";
60        reference
61            "8.2.2.16 of IEEE Std 802.1CS";
62    }
63    leaf last-received-status {
64        type string;
65        config false;
66        description
67            "Used by the Receive Hello state machine to record the
68            Hello status field of a Hello LRPDU received from the
69            neighbor Portal.";
70        reference
71            "8.2.2.22 of IEEE Std 802.1CS";
72    }
```

```
1 leaf applicant-active-records {
2     type uint32;
3     config false;
4     description
5         "An integer reporting the number of records in the applicant
6         database.";
7     reference
8         "11.5.1 of IEEE Std 802.1CS";
9 }
10 leaf registrar-active-records {
11     type uint32;
12     config false;
13     description
14         "An integer reporting the number of records in the registrar
15         database.";
16     reference
17         "11.5.2 of IEEE Std 802.1CS";
18 }
19 leaf sent-hellos {
20     type yang:counter64;
21     config false;
22     description
23         "The number of Hello LRPDU's transmitted by the Send Hello state machines.";
24     reference
25         "11.5.3 of IEEE Std 802.1CS";
26 }
27 leaf accepted-hellos {
28     type yang:counter64;
29     config false;
30     description
31         "The number of valid Hello LRPDU's received by the Receive Hello
32         state machine.";
33     reference
34         "11.5.4 of IEEE Std 802.1CS";
35 }
36 leaf discarded-hellos {
37     type yang:counter64;
38     config false;
39     description
40         "The number of invalid Hello LRPDU's discarded by the Receive Hello
41         state machine.";
42     reference
43         "11.5.5 of IEEE Std 802.1CS";
44 }
45 leaf sent-records {
46     type yang:counter64;
47     config false;
48     description
49         "The number of Record LRPDU's transmitted by the Applicant state
50         machine.";
51     reference
52         "11.5.6 of IEEE Std 802.1CS";
53 }
54 leaf accepted-records {
55     type yang:counter64;
56     config false;
57     description
58         "The number of valid Record LRPDU's received by the Partial list
59         state machine.";
60     reference
61         "11.5.7 of IEEE Std 802.1CS";
62 }
63 leaf discarded-records {
64     type yang:counter64;
65     config false;
66     description
67         "The number of invalid Record LRPDU's discarded by the Partial list
68         state machine.";
69     reference
70         "11.5.8 of IEEE Std 802.1CS";
71 }
72 leaf record-errors {
```

```
1      type yang:counter64;
2      config false;
3      description
4          "The number of records discarded from otherwise-valid Record LRPDU
5          by regReceiveWriteRecord due to inconsistencies between the
6          Checksum, Application data, and Data length fields.";
7      reference
8          "11.5.9 of IEEE Std 802.1CS";
9  }
10 leaf sent-partials {
11     type yang:counter64;
12     config false;
13     description
14         "The number of Partial List LRPDU transmitted by the Applicant
15         state machine.";
16     reference
17         "11.5.10 of IEEE Std 802.1CS";
18 }
19 leaf accepted-partials {
20     type yang:counter64;
21     config false;
22     description
23         "The number of valid Partial List LRPDU received by the Applicant
24         state machine.";
25     reference
26         "11.5.11 of IEEE Std 802.1CS";
27 }
28 leaf discarded-partials {
29     type yang:counter64;
30     config false;
31     description
32         "The number of invalid Partial List LRPDU discarded by the
33         Applicant state machine.";
34     reference
35         "11.5.12 of IEEE Std 802.1CS";
36 }
37 leaf sent-complete {
38     type yang:counter64;
39     config false;
40     description
41         "The number of Complete List LRPDU transmitted by the Applicant
42         state machine.";
43     reference
44         "11.5.13 of IEEE Std 802.1CS";
45 }
46 leaf accepted-completes {
47     type yang:counter64;
48     config false;
49     description
50         "The number of valid Complete List LRPDU received by the Applicant
51         state machine.";
52     reference
53         "11.5.14 of IEEE Std 802.1CS";
54 }
55 leaf discarded-completes {
56     type yang:counter64;
57     config false;
58     description
59         "The number of invalid Complete List LRPDU discarded by the
60         Applicant state machine.";
61     reference
62         "11.5.15 of IEEE Std 802.1CS";
63 }
64 leaf discarded-unknowns {
65     type yang:counter64;
66     config false;
67     description
68         "The number of LRPDU of unknown type discarded by the Applicant
69         state machine or Partial list state machine.";
70     reference
71         "11.5.16 of IEEE Std 802.1CS";
72 }
```

```
1 } // end portal
2 list lrp-dt-instance {
3   key "instance-id";
4   config false;
5   leaf instance-id {
6     type uint32;
7     config false;
8     description
9       "Local data transport instance";
10    reference
11      "Clause 7 of IEEE Std 802.1CS";
12  }
13  leaf active-tcp-open {
14    type boolean;
15    config false;
16    description
17      "A Boolean value that is TRUE if and only if instMyAddress and
18      instNeighborAddress are TCP addresses and this LRP-DT instance is
19      using the active , not the passive , form of TCP OPEN";
20    reference
21      "7.3.2.1 of IEEE Std 802.1CS";
22  }
23  leaf my-dt-address {
24    type lrp-dt-address-union;
25    config false;
26    description
27      "The address of the local system for this LRP-DT instance; the
28      address used as a destination address by the neighbor LRP-DT
29      instance. The address includes a type (MAC, IPv4, or IPv6) and an
30      address of that type.";
31    reference
32      "7.3.2.2 of IEEE Std 802.1CS";
33  }
34  leaf my-tcp-port{
35    type inet:port-number;
36    config false;
37    description
38      "The local port number for this TCP connection, or 0, if this
39      connection uses ECP, instead of TCP.";
40    reference
41      "7.3.2.3 of IEEE Std 802.1CS";
42  }
43  leaf neighbor-dt-address {
44    type lrp-dt-address-union;
45    config false;
46    description
47      "The address of the neighbor LRP-DT instance; the address used as a
48      destination address by this LRP-DT instance. The address includes a
49      type (MAC, IPv4, or IPv6) and an address of that type.";
50    reference
51      "7.3.2.4 of IEEE Std 802.1CS";
52  }
53  leaf neighbor-tcp-port {
54    type inet:port-number;
55    config false;
56    description
57      "The remote port number for this TCP connection, or 0, if this
58      connection uses ECP, instead of TCP.";
59    reference
60      "7.3.2.5 of IEEE Std 802.1CS";
61  }
62  leaf discarded-lrpdus {
63    type yang:counter64;
64    config false;
65    description
66      "A counter indicating the number of LRPDUs discarded by the LRP-DT
67      instance that cannot be assigned to a Portal for processing.";
68    reference
69      "11.4.1 of IEEE Std 802.1CS";
70  }
71 } // end lrp-dt-instance
72 } // end lrp
```

```
1 } // end augment system
2 } // end ieee802-dot1cs-lrp
3
```

1 13. MIB modules for LRP¹

2 13.5 MIB modules²

3 13.5.1 LRP Textual conventions MIB

4 *Change the MIB module in 13.5.1 with as follows:*

```
5 LRP-TC-MIB DEFINITIONS ::= BEGIN
6
7 IMPORTS
8     MODULE-IDENTITY,
9     Unsigned32
10    FROM SNMPv2-SMI
11    ieee802dot1mibs
12    FROM IEEE8021-TC-MIB
13    TEXTUAL-CONVENTION
14    FROM SNMPv2-TC;
15
16
17
18
19
20 ieee8021LrpTcMIB MODULE-IDENTITY
21 LAST-UPDATED "202012030000Z" -- December 3, 2020
22 LAST-UPDATED "202303140000Z" -- March 14, 2023
23 ORGANIZATION "IEEE 802.1 Working Group"
24 CONTACT-INFO
25     "WG-URL:      http://1.ieee802.org
26      WG-EMail:    stds-802-1-l@ieee.org
27
28      Contact:     IEEE 802.1 Working Group Chair
29      Postal:      C/O IEEE 802.1 Working Group
30                  IEEE Standards Association
31                  445 Hoes Lane
32                  Piscataway
33                  NJ 08854
34                  USA
35      E-mail:      stds-802-1-chairs@ieee.org"
36
37
38 DESCRIPTION
39     "Textual conventions used throughout IEEE Std 802.1CS.
40
41     Unless otherwise indicated, the references in this
42     MIB module are to IEEE Std 802.1CS-2020.
43
44 Copyright (C) IEEE (2021). This version of this MIB module
45 is included in clause 13 of IEEE Std 802.1CS-2020;
46 Copyright (C) IEEE (2023). This version of this MIB module
47 is included in clause 13 of IEEE Std 802.1CS-2020/Cor1-2023;
48     see the standard itself for full legal notices."
49
50 REVISION      "202303140000Z" -- March 14, 2023
51 DESCRIPTION   "OID changed to avoid conflict with a MIB defined in
52               IEEE Std 802.1CBcv-2021."
53
54 REVISION      "202012030000Z" -- December 3, 2020
55 DESCRIPTION   "This MIB module included in IEEE Std 802.1CS-2020.
56               "
57
58 ::= { ieee802dot1mibs 34 }
59 ::= { ieee802dot1mibs 38 }
```

¹An ASCII version of this MIB module can be obtained by Web browser from the IEEE 802.1 Website at <http://www.ieee802.org/1/pages/MIBS.html>.

²Copyright release for MIBs: Users of this standard may freely reproduce the MIBs contained in this subclause so that they can be used for their intended purpose.

```
1
2 --
3 -- *****
4 -- Textual Conventions
5 -- *****
6
7 LrpHelloStatus ::= TEXTUAL-CONVENTION
8     STATUS current
9     DESCRIPTION
10         "This specifies the current state of the Hello Receive State
11         Machine. It can take the following values:
12
13         hsLooking(1) This Portal has not yet received a successful
14         Complete Portal create request.
15         hsConnecting(2) This Portal has received a successful
16         Complete Portal create request (10.2.4), and a
17         Hello LRPDU with the hsLooking status.
18         The Portal is ready to receive all LRPDU's.
19         hsConnected(3) This Portal is up and ready to transfer
20         LRP application data. The Portal is allowed to
21         transmit all LRPDU's
22
23         "
24     REFERENCE
25         "8.2.2.8"
26     SYNTAX INTEGER {
27         hsLooking (1),
28         hsConnecting (2),
29         hsConnected (3)
30     }
31
32 LrpAppId ::= TEXTUAL-CONVENTION
33     DISPLAY-HINT "x"
34     STATUS current
35     DESCRIPTION
36         "Identifies an LRP application type.
37         A 32 bit number. The most-significant 24 bits of the integer are
38         an OUI or CID (obtainable from the IEEE Registration Authority),
39         and the least-significant 8 bits are assigned by the owner of
40         the OUI or CID. This creates a world-wide unique identity for
41         the LRP application type.
42
43         "
44     REFERENCE "9.2"
45     SYNTAX Unsigned32
46
47 LrpInetAddressInfo ::= TEXTUAL-CONVENTION
48     STATUS current
49     DESCRIPTION
50         "An LRP TCP Discovery TLV has some number of
51         Application descriptors, each of which can have either one or
52         two Address info fields. The Address info field tells whether
53         the following Address field is present or not, and if present,
54         whether it contains an IPv4 or an IPv6 address.
55         LrpInetAddressInfo can take the following values:
56
57         noAddress(0), Address info present, Address field not present
58         addrIPv4(1), Address info present, Address field has IPv4
59         addrIPv6(2), Address info present, Address field has IPv6
60         notPresent(256) Address info not present
61
62         "
63     REFERENCE "C.2.2.6.2"
64     SYNTAX INTEGER {
65         noAddress(0),
66         addrIPv4(1),
67         addrIPv6(2),
68         notPresent(256)
```

```
1      }  
2  
3 END
```

4 13.5.2 LRP MIB

5 *Change the MIB module in 13.5.2 with as follows:*

```
6 LRP-MIB DEFINITIONS ::= BEGIN  
8 IMPORTS  
9     MODULE-IDENTITY,  
10    OBJECT-TYPE,  
11    Unsigned32,  
12    Counter64  
13    FROM SNMPv2-SMI  
14    TruthValue  
15    FROM SNMPv2-TC  
16    MODULE-COMPLIANCE,  
17    OBJECT-GROUP  
18    FROM SNMPv2-CONF  
19    AddressFamilyNumbers  
20    FROM IANA-ADDRESS-FAMILY-NUMBERS-MIB  
21    InetPortNumber  
22    FROM INET-ADDRESS-MIB  
23    InterfaceIndex  
24    FROM IF-MIB  
25    LldpV2ChassisIdSubtype,  
26    LldpV2ChassisId,  
27    LldpV2PortIdSubtype,  
28    LldpV2PortId,  
29    LldpV2ManAddress  
30    FROM LLDP-V2-TC-MIB  
31    ieee802dot1mibs  
32    FROM IEEE8021-TC-MIB  
33    LrpAppId  
34    FROM LRP-TC-MIB;  
35  
36 ieee8021LrpMIB MODULE-IDENTITY  
37 LAST-UPDATED "202012030000Z" -- December 3, 2020  
38 LAST-UPDATED "202311160000Z" -- November 16, 2023  
39 ORGANIZATION "IEEE 802.1 Working Group"  
40 CONTACT-INFO  
41     "WG-URL:    http://1.ieee802.org  
42      WG-EMail:  stds-802-1-l@ieee.org  
43  
44      Contact:   IEEE 802.1 Working Group Chair  
45      Postal:    C/O IEEE 802.1 Working Group  
46                IEEE Standards Association  
47                445 Hoes Lane  
48                Piscataway  
49                NJ 08854  
50                USA  
51      E-mail:    stds-802-1-chairs@ieee.org"  
52 DESCRIPTION  
53     "Management Information Base module for configuration of the  
54     Link-local Registration Protocol.  
55  
56     This MIB module supports the managed objects described in  
57     clause 11.  
58  
59     Unless otherwise indicated, the references in this  
60     MIB module are to IEEE Std 802.1CS-2020.  
61  
62 Copyright (C) IEEE (2021). This version of this MIB module  
63 is included in clause 13 of IEEE Std 802.1CS-2020;
```



```
1      Copyright (C) IEEE (2023). This version of this MIB module
2      is included in clause 13 of IEEE Std 802.1CS-2020/Cor1-2023;
3      see the standard itself for full legal notices."
4
5      REVISION      "202311160000Z" -- November 16, 2023
6      DESCRIPTION   "OID changed to avoid conflict with a MIB defined in
7      IEEE Std 802.1CBcv-2021.
8      "
9      REVISION      "202012030000Z" -- December 3, 2020
10     DESCRIPTION   "This MIB module included in IEEE Std 802.1CS-2020.
11     "
12
13  ::= { ieee802dot1mibs 35 }
14 ::= { ieee802dot1mibs 39 }
15
16 lrpObjects          OBJECT IDENTIFIER ::= { ieee8021LrpMIB 1 }
18 lrpConformance      OBJECT IDENTIFIER ::= { ieee8021LrpMIB 2 }
19
20
21 --
22 -- LRP MIB Objects
23 --
24
25 lrpConfiguration    OBJECT IDENTIFIER ::= { lrpObjects 1 }
27 lrpStatistics        OBJECT IDENTIFIER ::= { lrpObjects 2 }
28
29
30
31 -- *****
32 --               L R P       C O N F I G
33 -- *****
34
35
36 -- *****
37 -- The table containing information about each LRP-DT instance.
38 -- *****
39
40 lrpDtInstanceTable  OBJECT-TYPE
42     SYNTAX          SEQUENCE OF LrpDtInstanceEntry
43     MAX-ACCESS      not-accessible
44     STATUS          current
45     DESCRIPTION
46         "A table presenting basic information about each LRP-DT instance
47         in the system.
48         "
49     REFERENCE
50         "11.4"
51     ::= { lrpConfiguration 1 }
52
53 lrpDtInstanceEntry  OBJECT-TYPE
55     SYNTAX          LrpDtInstanceEntry
56     MAX-ACCESS      not-accessible
57     STATUS          current
58     DESCRIPTION
59         "A list of basic information about one LRP-DT instance.
60         "
61     INDEX { lrpDtInstNumber }
62     ::= { lrpDtInstanceTable 1 }
63
64 LrpDtInstanceEntry ::= SEQUENCE {
66     lrpDtInstNumber      Unsigned32,
67     lrpDtInstActiveTcp    TruthValue,
68     lrpDtInstAddressTypes AddressFamilyNumbers,
69     lrpDtInstMyAddress    LldpV2ManAddress,
70     lrpDtInstMyTcpPort    InetPortNumber,
71     lrpDtInstNeighborAddress LldpV2ManAddress,
72     lrpDtInstNeighborTcpPort InetPortNumber
```

```
1      }
2
3 lrpDtInstNumber OBJECT-TYPE
4     SYNTAX      Unsigned32(1..4294967295)
5     MAX-ACCESS   not-accessible
6     STATUS      current
7     DESCRIPTION
8         "A small integer identifying an LRP-DT instance. Each
9         LRP-DT instance in a system has a unique lrpDtInstNumber.
10
11         This object SHALL NOT contain the value 0.
12
13         "
14     REFERENCE
15         "11.2"
16     ::= { lrpDtInstanceEntry 1 }
17
18 lrpDtInstActiveTcp OBJECT-TYPE
19     SYNTAX      TruthValue
20     MAX-ACCESS   read-only
21     STATUS      current
22     DESCRIPTION
23         "TRUE if and only if lrpDtInstAddressTypes indicates an IPv4
24         or IPv6 address, and this LRP-DT instance uses an active TCP
25         OPEN, as opposed to a passive TCP OPEN, to initiate the TCP
26         connection.
27
28         "
29     REFERENCE
30         "11.4, 7.3.2.1"
31     ::= { lrpDtInstanceEntry 2 }
32
33 lrpDtInstAddressTypes OBJECT-TYPE
34     SYNTAX      AddressFamilyNumbers
35     MAX-ACCESS   read-only
36     STATUS      current
37     DESCRIPTION
38         "An enumerated value specifying the format of the addresses
39         in lrpDtInstMyAddress and lrpDtInstNeighborAddress.
40
41         If lrpDtInstAddressTypes has a value indicating a type of
42         Internet Protocol address, then this LRP-DT instance uses TCP.
43         Otherwise, it uses ECP.
44
45         "
46     REFERENCE
47         "11.4, 7.3.2.2, 7.3.2.4"
48     ::= { lrpDtInstanceEntry 3 }
49
50 lrpDtInstMyAddress OBJECT-TYPE
51     SYNTAX      LldpV2ManAddress
52     MAX-ACCESS   read-only
53     STATUS      current
54     DESCRIPTION
55         "The address used by the local end of the LRP-DT instance. The
56         format of the address is determined by lrpDtInstAddressTypes.
57
58         "
59     REFERENCE
60         "11.4, 7.3.2.2"
61     ::= { lrpDtInstanceEntry 4 }
62
63 lrpDtInstMyTcpPort OBJECT-TYPE
64     SYNTAX      InetPortNumber
65     MAX-ACCESS   read-only
66     STATUS      current
67     DESCRIPTION
68         "The local TCP port number used for the TCP connection, or 0,
69         if this connection uses ECP, instead of TCP.
70
```

```
1      "
2  REFERENCE
3      "11.4, 7.3.2.3"
4      ::= { lrpDtInstanceEntry 5 }
5
6  lrpDtInstNeighborAddress OBJECT-TYPE
7      SYNTAX      LldpV2ManAddress
8      MAX-ACCESS  read-only
9      STATUS      current
10     DESCRIPTION
11         "The address used by the partner end of the LRP-DT instance, if
12         lrpDtInstActiveTcp is TRUE or lrpDtInstAddressTypes indicates
13         a MAC address. Otherwise (this LRP-DT instance was created
14         from a passive TCP OPEN), lrpDtInstNeighborAddress contains a
15         zero-length string. The format of the address is determined by
16         lrpDtInstAddressTypes.
17         "
18     REFERENCE
19         "11.4, 7.3.2.4"
20     ::= { lrpDtInstanceEntry 6 }
21
22
23  lrpDtInstNeighborTcpPort OBJECT-TYPE
24      SYNTAX      InetPortNumber
25      MAX-ACCESS  read-only
26      STATUS      current
27      DESCRIPTION
28         "The remote TCP port number used for the TCP connection, or 0,
29         if this connection uses ECP, instead of TCP.
30         "
31     REFERENCE
32         "11.4, 7.3.2.5"
33     ::= { lrpDtInstanceEntry 7 }
34
35
36
37 -- *****
38 -- The table containing information about each LRP-DS Portal.
39 -- *****
40
41  lrpPortalTable OBJECT-TYPE
42      SYNTAX      SEQUENCE OF LrpPortalEntry
43      MAX-ACCESS  not-accessible
44      STATUS      current
45      DESCRIPTION
46         "A table containing the per-portal set of counters that record
47         LRP events. There is an entry in the table for every portal in
48         a system.
49         "
50     REFERENCE
51         "8.2.2"
52     ::= { lrpConfiguration 2 }
53
54
55  lrpPortalEntry OBJECT-TYPE
56      SYNTAX      LrpPortalEntry
57      MAX-ACCESS  not-accessible
58      STATUS      current
59      DESCRIPTION
60         "A list of counters for events occurring on one Portal.
61         "
62     INDEX { lrpPortalNumber }
63     ::= { lrpPortalTable 1 }
64
65
66  LrpPortalEntry ::= SEQUENCE {
67      lrpPortalNumber      Unsigned32,
68      lrpPortalIfIndex      InterfaceIndex,
69      lrpPortalDtInstanceIndex  Unsigned32,
```

```
1      lrpPortalAppId          LrpAppId,
2      lrpPortalMyChassisIdType LdpV2ChassisIdSubtype,
3      lrpPortalMyChassisId     LdpV2ChassisId,
4      lrpPortalMyPortIdType    LdpV2PortIdSubtype,
5      lrpPortalMyPortId        LdpV2PortId,
6      lrpPortalNbrChassisIdType LdpV2ChassisIdSubtype,
7      lrpPortalNbrChassisId    LdpV2ChassisId,
8      lrpPortalNbrPortIdType   LdpV2PortIdSubtype,
9      lrpPortalNbrPortId       LdpV2PortId,
10     lrpPortalLocalOverflow    TruthValue
11   }
12
13 lrpPortalNumber OBJECT-TYPE
14     SYNTAX      Unsigned32
15     MAX-ACCESS  not-accessible
16     STATUS      current
17     DESCRIPTION
18       "A small integer identifying a portal. Each portal in a system
19       has a unique lrpPortalNumber.
20
21       This object SHALL NOT contain the value 0.
22       "
23     ::= { lrpPortalEntry 1 }
24
25 lrpPortalIfIndex OBJECT-TYPE
26     SYNTAX      InterfaceIndex
27     MAX-ACCESS  read-only
28     STATUS      current
29     DESCRIPTION
30       "The interface index identifying the target port to which this
31       portal is attached. The value is 0, if there is none.
32       "
33     ::= { lrpPortalEntry 2 }
34
35 lrpPortalDtInstanceIndex OBJECT-TYPE
36     SYNTAX      Unsigned32
37     MAX-ACCESS  read-only
38     STATUS      current
39     DESCRIPTION
40       "The same value as the lrpDtInstNumber object of the
41       lrpDtInstanceEntry describing the LRP-DT instance to which this
42       Portal is attached.
43       "
44     REFERENCE
45       "8.2.2.1"
46       "8.2.1"
47     ::= { lrpPortalEntry 3 }
48
49 lrpPortalAppId OBJECT-TYPE
50     SYNTAX      LrpAppId
51     MAX-ACCESS  read-only
52     STATUS      current
53     DESCRIPTION
54       "The application ID used for this Portal.
55       "
56     REFERENCE
57       "8.2.2.1"
58     ::= { lrpPortalEntry 4 }
59
60 lrpPortalMyChassisIdType OBJECT-TYPE
61     SYNTAX      LdpV2ChassisIdSubtype
62     MAX-ACCESS  read-only
63     STATUS      current
64     DESCRIPTION
65       "The My Chassis ID TLV type field used for this Portal.
```

```
1      "
2      REFERENCE
3      "8.2.2.2"
4      ::= { lrpPortalEntry 5 }
5
6 lrpPortalMyChassisId OBJECT-TYPE
7     SYNTAX      LldpV2ChassisId
8     MAX-ACCESS  read-only
9     STATUS      current
10    DESCRIPTION
11        "The My Chassis ID TLV Chassis ID field used for this Portal."
12    "
13    REFERENCE
14        "8.2.2.2"
15    ::= { lrpPortalEntry 6 }
16
17
18 lrpPortalMyPortIdType OBJECT-TYPE
19    SYNTAX      LldpV2PortIdSubtype
20    MAX-ACCESS  read-only
21    STATUS      current
22    DESCRIPTION
23        "The My Port ID TLV type field used for this Portal."
24    "
25    REFERENCE
26        "8.2.2.3"
27    ::= { lrpPortalEntry 7 }
28
29
30 lrpPortalMyPortId OBJECT-TYPE
31    SYNTAX      LldpV2PortId
32    MAX-ACCESS  read-only
33    STATUS      current
34    DESCRIPTION
35        "The My Port ID TLV Port ID field used for this Portal."
36    "
37    REFERENCE
38        "8.2.2.3"
39    ::= { lrpPortalEntry 8 }
40
41
42 lrpPortalNbrChassisIdType OBJECT-TYPE
43    SYNTAX      LldpV2ChassisIdSubtype
44    MAX-ACCESS  read-only
45    STATUS      current
46    DESCRIPTION
47        "The Neighbor Chassis ID TLV type field used for this Portal."
48    "
49    REFERENCE
50        "8.2.2.2"
51    ::= { lrpPortalEntry 9 }
52
53
54 lrpPortalNbrChassisId OBJECT-TYPE
55    SYNTAX      LldpV2ChassisId
56    MAX-ACCESS  read-only
57    STATUS      current
58    DESCRIPTION
59        "The Neighbor Chassis ID TLV Chassis ID field used for this
60        Portal."
61    "
62    REFERENCE
63        "8.2.2.2"
64    ::= { lrpPortalEntry 10 }
65
66
67 lrpPortalNbrPortIdType OBJECT-TYPE
68    SYNTAX      LldpV2PortIdSubtype
69    MAX-ACCESS  read-only
70    STATUS      current
```

```
1 DESCRIPTION
2     "The Neighbor Port ID TLV type field used for this Portal.
3     "
4 REFERENCE
5     "8.2.2.3"
6     ::= { lrpPortalEntry 11 }
7
8 lrpPortalNbrPortId OBJECT-TYPE
9     SYNTAX      LldpV2PortId
10    MAX-ACCESS  read-only
11    STATUS      current
12    DESCRIPTION
13        "The Neighbor Port ID TLV Port ID field used for this Portal.
14        "
15    REFERENCE
16        "8.2.2.3"
17    ::= { lrpPortalEntry 12 }
18
19
20 lrpPortalLocalOverflow OBJECT-TYPE
21     SYNTAX      TruthValue
22     MAX-ACCESS  read-only
23     STATUS      current
24     DESCRIPTION
25         "A Boolean indicating whether or not the local registrar
26         database has overflowed its allotted memory.
27         "
28     REFERENCE
29         "8.2.2.10"
30     ::= { lrpPortalEntry 13 }
31
32
33 -- *****
34 --             P O R T A L       S T A T I S T I C S
35 -- *****
36
37 lrpPortalCountersTable OBJECT-TYPE
38     SYNTAX      SEQUENCE OF LrpPortalCountersEntry
39     MAX-ACCESS  not-accessible
40     STATUS      current
41     DESCRIPTION
42         "A table containing the per-portal set of counters that record
43         LRP events.  There is an entry in the table for every portal in
44         a system.
45         "
46     REFERENCE
47         "11.5"
48     ::= { lrpStatistics 1 }
49
50
51 lrpPortalCountersEntry OBJECT-TYPE
52     SYNTAX      LrpPortalCountersEntry
53     MAX-ACCESS  not-accessible
54     STATUS      current
55     DESCRIPTION
56         "A list of counters for events occurring on one Portal.
57         "
58     INDEX { lrpPortalNumber }
59     ::= { lrpPortalCountersTable 1 }
60
61
62 LrpPortalCountersEntry ::= SEQUENCE {
63     lrpPortalApplicantActiveRecords Unsigned32,
64     lrpPptCtRegistrarActiveRecords Unsigned32,
65     lrpPptCtSentHellos              Counter64,
66     lrpPptCtAcceptedHellos          Counter64,
67     lrpPptCtDiscardedHellos         Counter64,
68     lrpPptCtSentRecords             Counter64,
69     lrpPptCtAcceptedRecords         Counter64,
```

```
1         lrpPptCtDiscardedRecords          Counter64,
2         lrpPptCtRecordErrors               Counter64,
3         lrpPptCtSentPartials               Counter64,
4         lrpPptCtAcceptedPartials           Counter64,
5         lrpPptCtDiscardedPartials           Counter64,
6         lrpPptCtSentCompletes               Counter64,
7         lrpPptCtAcceptedCompletes           Counter64,
8         lrpPptCtDiscardedCompletes          Counter64,
9         lrpPptCtDiscardedUnknowns          Counter64
10    }
11
12 lrpPortalApplicantActiveRecords OBJECT-TYPE
13     SYNTAX      Unsigned32
14     MAX-ACCESS  read-only
15     STATUS      current
16     DESCRIPTION
17         "The number of records in the applicant database."
18         "
19     REFERENCE
20         "11.5.1"
21     ::= { lrpPortalCountersEntry 1 }
22
23
24 lrpPptCtRegistrarActiveRecords OBJECT-TYPE
25     SYNTAX      Unsigned32
26     MAX-ACCESS  read-only
27     STATUS      current
28     DESCRIPTION
29         "The number of records in the registrar database."
30         "
31     REFERENCE
32         "11.5.2"
33     ::= { lrpPortalCountersEntry 2 }
34
35
36 lrpPptCtSentHellos OBJECT-TYPE
37     SYNTAX      Counter64
38     MAX-ACCESS  read-only
39     STATUS      current
40     DESCRIPTION
41         "Incremented once for each Hello LRPDU transmitted by the
42         Send Hello state machines."
43         "
44     REFERENCE
45         "11.5.3"
46     ::= { lrpPortalCountersEntry 3 }
47
48
49 lrpPptCtAcceptedHellos OBJECT-TYPE
50     SYNTAX      Counter64
51     MAX-ACCESS  read-only
52     STATUS      current
53     DESCRIPTION
54         "Incremented once for each Hello LRPDU received by the
55         Receive Hello state machine."
56         "
57     REFERENCE
58         "11.5.4"
59     ::= { lrpPortalCountersEntry 4 }
60
61
62 lrpPptCtDiscardedHellos OBJECT-TYPE
63     SYNTAX      Counter64
64     MAX-ACCESS  read-only
65     STATUS      current
66     DESCRIPTION
67         "Incremented once for each invalid Hello LRPDU discarded by the
68         Receive Hello state machine"
69         "
70
```

```
1  REFERENCE
2  "11.5.5"
3  ::= { lrpPortalCountersEntry 5 }
4
5 lrpPptCtSentRecords OBJECT-TYPE
6
7  SYNTAX      Counter64
8  MAX-ACCESS  read-only
9  STATUS      current
10 DESCRIPTION
11   "Incremented once for each Record LRPDU transmitted by the
12   Applicant state machine.
13   "
14 REFERENCE
15   "11.5.6"
16 ::= { lrpPortalCountersEntry 6 }
17
18 lrpPptCtAcceptedRecords OBJECT-TYPE
19
20 SYNTAX      Counter64
21 MAX-ACCESS  read-only
22 STATUS      current
23 DESCRIPTION
24   "Incremented once for each valid Record LRPDU received by the
25   Partial list state machine.
26   "
27 REFERENCE
28   "11.5.7"
29 ::= { lrpPortalCountersEntry 7 }
30
31 lrpPptCtDiscardedRecords OBJECT-TYPE
32
33 SYNTAX      Counter64
34 MAX-ACCESS  read-only
35 STATUS      current
36 DESCRIPTION
37   "Incremented once for each invalid Record LRPDU discarded by the
38   Partial list state machine.
39   "
40 REFERENCE
41   "11.5.8"
42 ::= { lrpPortalCountersEntry 8 }
43
44 lrpPptCtRecordErrors OBJECT-TYPE
45
46 SYNTAX      Counter64
47 MAX-ACCESS  read-only
48 STATUS      current
49 DESCRIPTION
50   "Incremented once for each record discarded from a Record LRPDU
51   because of inconsistencies among the Checksum, Application data,
52   and Data length fields.
53   "
54 REFERENCE
55   "11.5.9"
56 ::= { lrpPortalCountersEntry 9 }
57
58 lrpPptCtSentPartials OBJECT-TYPE
59
60 SYNTAX      Counter64
61 MAX-ACCESS  read-only
62 STATUS      current
63 DESCRIPTION
64   "Incremented once for each Partial List LRPDU transmitted by the
65   Applicant state machine.
66   "
67 REFERENCE
68   "11.5.10"
69 ::= { lrpPortalCountersEntry 10 }
70
```



```
1 lrpPptCtAcceptedPartials OBJECT-TYPE
3     SYNTAX      Counter64
4     MAX-ACCESS  read-only
5     STATUS      current
6     DESCRIPTION
7         "Incremented once for each valid Partial List LRPDU received by
8         the Applicant state machine.
9     "
10    REFERENCE
11        "11.5.11"
12    ::= { lrpPortalCountersEntry 11 }
13
14 lrpPptCtDiscardedPartials OBJECT-TYPE
16     SYNTAX      Counter64
17     MAX-ACCESS  read-only
18     STATUS      current
19     DESCRIPTION
20         "Incremented once for each invalid Partial List LRPDU discarded
21         by the Applicant state machine.
22     "
23    REFERENCE
24        "11.5.12"
25    ::= { lrpPortalCountersEntry 12 }
26
27 lrpPptCtSentCompletes OBJECT-TYPE
29     SYNTAX      Counter64
30     MAX-ACCESS  read-only
31     STATUS      current
32     DESCRIPTION
33         "Incremented once for each Complete List LRPDU transmitted by
34         the Applicant state machine.
35     "
36    REFERENCE
37        "11.5.13"
38    ::= { lrpPortalCountersEntry 13 }
39
40 lrpPptCtAcceptedCompletes OBJECT-TYPE
42     SYNTAX      Counter64
43     MAX-ACCESS  read-only
44     STATUS      current
45     DESCRIPTION
46         "Incremented once for each valid Complete List LRPDU received
47         by the Applicant state machine.
48     "
49    REFERENCE
50        "11.5.14"
51    ::= { lrpPortalCountersEntry 14 }
52
53 lrpPptCtDiscardedCompletes OBJECT-TYPE
55     SYNTAX      Counter64
56     MAX-ACCESS  read-only
57     STATUS      current
58     DESCRIPTION
59         "Incremented once for each invalid Complete List LRPDU discarded
60         by the Applicant state machine.
61     "
62    REFERENCE
63        "11.5.15"
64    ::= { lrpPortalCountersEntry 15 }
65
66 lrpPptCtDiscardedUnknowns OBJECT-TYPE
68     SYNTAX      Counter64
69     MAX-ACCESS  read-only
70     STATUS      current
71     DESCRIPTION
```

```
1      "Incremented once for each LRPDU of unknown type discarded by
2      the Applicant state machine or Partial list state machine.
3      "
4  REFERENCE
5      "11.5.16"
6      ::= { lrpPortalCountersEntry 16 }
7
8
9  -- *****
10 --      L R P - D T   I N S T A N C E   S T A T I S T I C S
11 -- *****
12
13 lrpDtInstanceCountersTable OBJECT-TYPE
14     SYNTAX      SEQUENCE OF LrpDtInstanceCountersEntry
15     MAX-ACCESS  not-accessible
16     STATUS      current
17     DESCRIPTION
18         "A table containing the per-LRP-DT instance set of counters that
19         record LRP events. There is an entry in the table for every
20         LRP-DT instance in a system.
21         "
22     REFERENCE
23         "11.4"
24     ::= { lrpStatistics 2 }
25
26
27 lrpDtInstanceCountersEntry OBJECT-TYPE
28     SYNTAX      LrpDtInstanceCountersEntry
29     MAX-ACCESS  not-accessible
30     STATUS      current
31     DESCRIPTION
32         "A list of statistics about one LRP-DT instance.
33         "
34     INDEX { lrpDtInstNumber }
35     ::= { lrpDtInstanceCountersTable 1 }
36
37
38 LrpDtInstanceCountersEntry ::= SEQUENCE {
39     lrpDtInstDiscardedLrpdus Counter64
40 }
41
42
43 lrpDtInstDiscardedLrpdus OBJECT-TYPE
44     SYNTAX      Counter64
45     MAX-ACCESS  read-only
46     STATUS      current
47     DESCRIPTION
48         "The number of received Link-local Registration Protocol Data
49         Units discarded by the LRP-DT instance because it could not
50         determine to which Portal it should be given.
51         "
52     REFERENCE
53         "11.4, 11.4.1"
54     ::= { lrpDtInstanceCountersEntry 1 }
55
56
57
58 --
59 -- *****
60 --      L R P   M I B   C O N F O R M A N C E
61 -- *****
62 --
63
64 lrpCompliances OBJECT IDENTIFIER ::= { lrpConformance 1 }
65 lrpGroups      OBJECT IDENTIFIER ::= { lrpConformance 2 }
66
67
68
69 -- compliance statements
70
71 lrpCompliance MODULE-COMPLIANCE
```

```
1  STATUS  current
2  DESCRIPTION
3      "A compliance statement for all SNMP entities that
4      implement the LRP MIB.
5
6      This version defines compliance requirements for
7      LRP MIB module.
8      "
9  MODULE  -- this module
10     MANDATORY-GROUPS {
11         lrpDsDtGroup
12     }
13
14     ::= { lrpCompliances 1 }
15
16 -- MIB groupings
17
18 lrpDsDtGroup  OBJECT-GROUP
19     OBJECTS {
20         lrpDtInstActiveTcp,
21         lrpDtInstAddressTypes,
22         lrpDtInstMyAddress,
23         lrpDtInstMyTcpPort,
24         lrpDtInstNeighborAddress,
25         lrpDtInstNeighborTcpPort,
26         lrpPortalIfIndex,
27         lrpPortalDtInstanceIndex,
28         lrpPortalAppId,
29         lrpPortalMyChassisIdType,
30         lrpPortalMyChassisId,
31         lrpPortalMyPortIdType,
32         lrpPortalMyPortId,
33         lrpPortalNbrChassisIdType,
34         lrpPortalNbrChassisId,
35         lrpPortalNbrPortIdType,
36         lrpPortalNbrPortId,
37         lrpPortalLocalOverflow,
38         lrpPortalApplicantActiveRecords,
39         lrpPptCtRegistrarActiveRecords,
40         lrpPptCtSentHellos,
41         lrpPptCtAcceptedHellos,
42         lrpPptCtDiscardedHellos,
43         lrpPptCtSentRecords,
44         lrpPptCtAcceptedRecords,
45         lrpPptCtDiscardedRecords,
46         lrpPptCtRecordErrors,
47         lrpPptCtSentPartials,
48         lrpPptCtAcceptedPartials,
49         lrpPptCtDiscardedPartials,
50         lrpPptCtSentCompletes,
51         lrpPptCtAcceptedCompletes,
52         lrpPptCtDiscardedCompletes,
53         lrpPptCtDiscardedUnknowns,
54         lrpDtInstDiscardedLrpdus
55     }
56
57 STATUS  current
58 DESCRIPTION
59     "The collection of objects which are used to monitor the
60     status of LRP-DS and LRP-DT.
61     "
62     ::= { lrpGroups 1 }
63
64 END
```

1 13.5.3 LLDPv2 LRP extension MIB

2 *Change the MIB module in 13.5.3 with as follows:*

```
3 LLDP-V2-LRP-EXT-MIB DEFINITIONS ::= BEGIN
5
6 IMPORTS
7     MODULE-IDENTITY,
9     OBJECT-TYPE,
11    Unsigned32
13        FROM SNMPv2-SMI
14    TruthValue
16        FROM SNMPv2-TC
17    MODULE-COMPLIANCE,
19    OBJECT-GROUP
21        FROM SNMPv2-CONF
22    TimeFilter
24        FROM RMON2-MIB
25    InterfaceIndex
27        FROM IF-MIB
28    InetAddress,
30    InetAddressIPv4,
32    InetAddressIPv6,
34    InetPortNumber
36        FROM INET-ADDRESS-MIB
37    LldpV2DestAddressTableIndex
39        FROM LLDP-V2-TC-MIB
40    lldpXdot1StandAloneExtensions
42        FROM LLDP-EXT-DOT1-EVB-EXTENSIONS-MIB
43    LrpAppId,
45    LrpInetAddressInfo
47        FROM LRP-TC-MIB;
48
49 lldpXdot1LrpExtensions MODULE-IDENTITY
51 LAST-UPDATED "202012030000Z" -- December 3, 2020
52 LAST-UPDATED "202303140000Z" -- March 14, 2023
53 ORGANIZATION "IEEE 802.1 Working Group"
54 CONTACT-INFO
55     "WG-URL: http://www.ieee802.org/1/
56     WG-EMail: stds-802-1-1@ieee.org
57
58     Contact: IEEE 802.1 Working Group Chair
59     Postal: C/O IEEE 802.1 Working Group
60             IEEE Standards Association
61             445 Hoes Lane
62             Piscataway
63             NJ 08854
64             USA
65     E-mail: stds-802-1-chairs@ieee.org"
66 DESCRIPTION
67     "The LLDP Management Information Base extension module for IEEE
68     802.1 organizationally-defined discovery information, as
69     specified in IEEE Std 802.1CS, Link-local Registration Protocol
70     (LRP).
71
72     The Link-Layer Discovery Protocol (LLDP) is defined in
73     IEEE Std 802.1AB.
74
75     lldpXdot1StandAloneExtensions is the OUI for LLDP-EXT-DOT1-EVB-EXTENSIONS-MIB.
76     which defines managed objects for IEEE 802.1-defined
77     organizationally-specified LLDP Type-Length Value (TLV)
78     discovery information. lldpXdot1StandAloneExtensions is branched
79     from lldpV2Extensions (defined in LLDP-V2-MIB) using the
80     Organizationally Unique Identifier (OUI) value 00-80-C1, which
81     belongs to IEEE 802.1. An OUI is a 24 bit globally-unique number
```

```
1      assigned by the IEEE Registration Authority -- see:
2
3      http://standards.ieee.org/develop/regauth/oui/index.html
4
5      In turn, lldpXdot1LrpExtensions and lldpV2ExtLrpConformance are
6      branched from lldpXdot1StandAloneExtensions, and thus are also
7      extensions from the IEEE 802.1 OUI.
8
9      Unless otherwise indicated, the references in this MIB module
10     are to IEEE Std 802.1CS-2020.
11
12     Copyright (C) IEEE (2020). This version of this MIB module is
13     included in clause 13 of IEEE Std 802.1CS-2020; see the
14     Copyright (C) IEEE (2023). This version of this MIB module is
15     included in clause 13 of IEEE Std 802.1CS-2020/Cor1-2023; see the
16     standard itself for full legal notices."
17
18     REVISION "202303140000Z" -- March 14, 2023
19     DESCRIPTION
20     "Description of lldpV2LocLrpTcpAddress1 corrected.
21     "
22     REVISION "202012030000Z" -- December 3, 2020
23     DESCRIPTION
24         "This MIB module included in IEEE Std 802.1CS-2020.
25         "
26
27     ::= { lldpXdot1StandAloneExtensions 3 }
28
29     -----
30     -----
31     --
32     -- Organizationally Defined Information Extension - IEEE 802.1
33     -- Definitions to support the IEEE Std 802.1AB LLDP TLVs defined in
34     -- IEEE Std 802.1CS Link-local Registration Protocol (LRP)
35     --
36     -----
37     -----
38
39     lldpV2ExtLrpObjects      OBJECT IDENTIFIER ::= { lldpXdot1LrpExtensions 1 }
40
41
42     -- LLDP IEEE 802.1CS extension MIB groups
43
44     lldpV2ExtConfigLrp      OBJECT IDENTIFIER ::= { lldpV2ExtLrpObjects 1 }
45     lldpV2ExtLrpLocalData   OBJECT IDENTIFIER ::= { lldpV2ExtLrpObjects 2 }
46     lldpV2ExtLrpRemoteData  OBJECT IDENTIFIER ::= { lldpV2ExtLrpObjects 3 }
47
48
49     -----
50     -- IEEE 802.1 - Configuration for the LRP TLV set
51     -----
52     --
53     --
54     -- The table specifying, for each LRP application, what IP
55     -- addresses to advertise in LRP TCP Discovery TLVs in a
56     -- Controlled system.
57     --
58
59
60
61     lldpV2ConfigLrpTcpControlledTable OBJECT-TYPE
62     SYNTAX      SEQUENCE OF LldpV2LrpConfigTcpControlledEntry
63     MAX-ACCESS  not-accessible
64     STATUS      current
65     DESCRIPTION
66         "A table specifying what IP addresses are to be advertised as
67         the address of the Proxy system controlling this Controlled
68         system, for each particular LRP application. These IP addresses
69         and application identifiers can be transmitted in
```

```
1      LRP TCP Discovery TLVs.
2      "
3      REFERENCE
4      "11.6.1.1"
5      ::= { lldpV2ExtConfigLrp 1 }
6
7 lldpV2ConfigLrpTcpControlledEntry OBJECT-TYPE
9     SYNTAX      LldpV2LrpConfigTcpControlledEntry
10    MAX-ACCESS   not-accessible
11    STATUS       current
12    DESCRIPTION
13        "A table specifying what IP addresses are to be advertised as
14        the address of the Proxy system controlling this Controlled
15        system, for a particular LRP application. These IP addresses
16        and application identifiers can be transmitted in
17        LRP TCP Discovery TLVs.
18        "
19    INDEX { lldpV2ConfigLrpTcpControlledApplicationId }
20    ::= { lldpV2ConfigLrpTcpControlledTable 1 }
21
22 lldpV2LrpConfigTcpControlledEntry ::= SEQUENCE {
24     lldpV2ConfigLrpTcpControlledApplicationId  LrpAppId,
25     lldpV2ConfigLrpTcpControlledTcpPortNumber  InetPortNumber,
26     lldpV2ConfigLrpTcpControlledIPv4Enable     TruthValue,
27     lldpV2ConfigLrpTcpControlledIPv4Address    InetAddressIPv4,
28     lldpV2ConfigLrpTcpControlledIPv6Enable     TruthValue,
29     lldpV2ConfigLrpTcpControlledIPv6Address    InetAddressIPv6
30 }
31
32
33 lldpV2ConfigLrpTcpControlledApplicationId OBJECT-TYPE
35     SYNTAX      LrpAppId
36     MAX-ACCESS   not-accessible
37     STATUS       current
38     DESCRIPTION
39         "The application identifier to which the rest of the
40         lldpV2ConfigLrpTcpControlledEntry applies.
41         "
42     REFERENCE
43     "9.2"
44     ::= { lldpV2ConfigLrpTcpControlledEntry 1 }
45
46 lldpV2ConfigLrpTcpControlledTcpPortNumber OBJECT-TYPE
48     SYNTAX      InetPortNumber
49     MAX-ACCESS   read-write
50     STATUS       current
51     DESCRIPTION
52         "The destination TCP Port number to which TCP connections for
53         LRP to the addresses in lldpV2ConfigLrpTcpControlledIPv4Address
54         or lldpV2ConfigLrpTcpControlledIPv6Address, for the
55         application in lldpV2ConfigLrpTcpControlledApplicationId, are
56         to be made.
57
58         If this object contains the value 0, then no
59         Application descriptor with the indexed application ID is
60         transmitted.
61
62         The value of this object is restored from non-volatile
63         storage after a re-initialization of the management system.
64         "
65     REFERENCE
66     "C.2.2.6.1"
67     ::= { lldpV2ConfigLrpTcpControlledEntry 2 }
68
69 lldpV2ConfigLrpTcpControlledIPv4Enable OBJECT-TYPE
```

```
1 SYNTAX      TruthValue
2 MAX-ACCESS  read-write
3 STATUS      current
4 DESCRIPTION
5     "Specifies whether or not the indexed LRP application is
6     available through the LRP-DT TCP mechanism using TCP over IPv4.
7     It thus controls whether the LRP TCP Discovery TLVs transmitted
8     from this Controlled system include the IPv4 address in
9     lldpV2ConfigLrpTcpControlledIPv4Address in an
10    Application descriptor containing the indexed application ID.
11
12    If lldpV2ConfigLrpTcpControlledIPv4Enable and
13    lldpV2ConfigLrpTcpControlledIPv4Enable are both false(2), then
14    no Application descriptor with the indexed application ID is
15    transmitted.
16
17    The value of this object is restored from non-volatile
18    storage after a re-initialization of the management system.
19    "
20 REFERENCE
21     "C.2.2.6.2"
22 ::= { lldpV2ConfigLrpTcpControlledEntry 3 }
23
24 lldpV2ConfigLrpTcpControlledIPv4Address OBJECT-TYPE
25 SYNTAX      InetAddressIPv4
26 MAX-ACCESS  read-write
27 STATUS      current
28 DESCRIPTION
29     "Specifies an IPv4 address to be advertised in all of the
30     LRP TCP Discovery TLVs that carry the indexed application ID
31     that are transmitted by this Controlled system.
32
33     The value of this object is restored from non-volatile
34     storage after a re-initialization of the management system.
35     "
36 REFERENCE
37     "C.2.2.6.3"
38 ::= { lldpV2ConfigLrpTcpControlledEntry 4 }
39
40
41 lldpV2ConfigLrpTcpControlledIPv6Enable OBJECT-TYPE
42 SYNTAX      TruthValue
43 MAX-ACCESS  read-write
44 STATUS      current
45 DESCRIPTION
46     "Specifies whether or not the indexed LRP application is
47     available through the LRP-DT TCP mechanism using TCP over IPv6.
48     It thus controls whether the LRP TCP Discovery TLVs transmitted
49     from this Controlled system include the IPv6 address in
50     lldpV2ConfigLrpTcpControlledIPv6Address in an
51     Application descriptor containing the indexed application ID.
52
53     If lldpV2ConfigLrpTcpControlledIPv4Enable and
54     lldpV2ConfigLrpTcpControlledIPv4Enable are both false(2), then
55     no Application descriptor with the indexed application ID is
56     transmitted.
57
58     The value of this object is restored from non-volatile
59     storage after a re-initialization of the management system.
60     "
61 REFERENCE
62     "C.2.2.6.2"
63 ::= { lldpV2ConfigLrpTcpControlledEntry 5 }
64
65
66 lldpV2ConfigLrpTcpControlledIPv6Address OBJECT-TYPE
67 SYNTAX      InetAddressIPv6
```

```
1  MAX-ACCESS  read-write
2  STATUS      current
3  DESCRIPTION
4      "Specifies an IPv6 address to be advertised in all of the
5      LRP TCP Discovery TLVs that carry the indexed application ID
6      that are transmitted by this Controlled system.
7
8      The value of this object is restored from non-volatile
9      storage after a re-initialization of the management system.
10     "
11  REFERENCE
12      "C.2.2.6.3"
13      ::= { lldpV2ConfigLrpTcpControlledEntry 6 }
14
15 --
16 -- lldpV2ConfigLrpEcpTxTable: configure the transmission of the
17 --      LRP ECP Discovery TLVs on a set of ports.
18 --
19
20 lldpV2ConfigLrpEcpTxTable OBJECT-TYPE
21     SYNTAX      SEQUENCE OF LldpV2ConfigLrpEcpTxEntry
22     MAX-ACCESS  not-accessible
23     STATUS      current
24     DESCRIPTION
25         "This table contains one or more rows per physical network
26         connection known to this agent. The agent may wish to
27         ensure that only one lldpV2ConfigLrpEcpTxEntry is present for
28         each local port, or it may choose to maintain multiple
29         entries for the same local port."
31     REFERENCE
32         "11.6.2.1"
33     ::= { lldpV2ExtLrpLocalData 1 }
34
35 lldpV2ConfigLrpEcpTxEntry OBJECT-TYPE
36     SYNTAX      LldpV2ConfigLrpEcpTxEntry
37     MAX-ACCESS  not-accessible
38     STATUS      current
39     DESCRIPTION
40         "Information about a particular port component."
41     INDEX      { lldpV2ConfigLrpEcpTxLocalIfIndex,
42                  lldpV2ConfigLrpEcpTxLocalDestMACAddress }
43     ::= { lldpV2ConfigLrpEcpTxTable 1 }
44
45
46 LldpV2ConfigLrpEcpTxEntry ::= SEQUENCE {
47     lldpV2ConfigLrpEcpTxLocalIfIndex      InterfaceIndex,
48     lldpV2ConfigLrpEcpTxLocalDestMACAddress LldpV2DestAddressTableIndex,
49     lldpV2ConfigLrpEcpTxEnable            TruthValue
50 }
51
52
53 lldpV2ConfigLrpEcpTxLocalIfIndex OBJECT-TYPE
54     SYNTAX      InterfaceIndex
55     MAX-ACCESS  not-accessible
56     STATUS      current
57     DESCRIPTION
58         "The interface index value used to identify the port
59         associated with this entry. Its value is an index
60         into the interfaces MIB
61
62         The value of this object is used as an index to the
63         lldpV2ConfigLrpEcpTxTable.
64     "
65     ::= { lldpV2ConfigLrpEcpTxEntry 1 }
66
67
68 lldpV2ConfigLrpEcpTxLocalDestMACAddress OBJECT-TYPE
69     SYNTAX      LldpV2DestAddressTableIndex
```



```
1  MAX-ACCESS  not-accessible
2  STATUS      current
3  DESCRIPTION
4      "The index value used to identify the LLDPDU frame destination
5      MAC address associated with this entry. Its value identifies
6      the row in the lldpV2DestAddressTable where the MAC address
7      can be found.
8
9      The value of this object is used as an index to the
10     lldpV2ConfigLrpEcpTxTable.
11     "
12     ::= { lldpV2ConfigLrpEcpTxEntry 2 }
13
14 lldpV2ConfigLrpEcpTxEnable OBJECT-TYPE
15     SYNTAX      TruthValue
16     MAX-ACCESS  read-write
17     STATUS      current
18     DESCRIPTION
19         "The lldpV2ConfigLrpEcpTxEnable, which is defined
20         as a truth value and configured by the network management,
21         determines whether the IEEE 802.1 organizationally defined
22         LRP ECP Discovery TLV transmission is allowed on a given
23         LLDP transmission-capable port component.
24
25         The value of this object is restored from non-volatile
26         storage after a re-initialization of the management system."
27     DEFVAL { false }
28     ::= { lldpV2ConfigLrpEcpTxEntry 3 }
29
30
31
32 --
33 -- lldpV2ConfigLrpTcpTxTable: configure the transmission of the
34 --     LRP TCP Discovery TLVs on a set of ports.
35 --
36
37 lldpV2ConfigLrpTcpTxTable OBJECT-TYPE
38     SYNTAX      SEQUENCE OF LldpV2ConfigLrpTcpTxEntry
39     MAX-ACCESS  not-accessible
40     STATUS      current
41     DESCRIPTION
42         "This table contains one or more rows per physical network
43         connection known to this agent. The agent may wish to
44         ensure that only one lldpV2ConfigLrpTcpTxEntry is present for
45         each local port, or it may choose to maintain multiple
46         entries for the same local port."
47     ::= { lldpV2ExtLrpLocalData 2 }
48
49
50 lldpV2ConfigLrpTcpTxEntry OBJECT-TYPE
51     SYNTAX      LldpV2ConfigLrpTcpTxEntry
52     MAX-ACCESS  not-accessible
53     STATUS      current
54     DESCRIPTION
55         "Information about a particular port component."
56     INDEX      { lldpV2ConfigLrpTcpTxLocalIfIndex,
57                 lldpV2ConfigLrpTcpTxLocalDestMACAddress }
58     ::= { lldpV2ConfigLrpTcpTxTable 1 }
59
60
61 lldpV2ConfigLrpTcpTxEntry ::= SEQUENCE {
62     lldpV2ConfigLrpTcpTxLocalIfIndex      InterfaceIndex,
63     lldpV2ConfigLrpTcpTxLocalDestMACAddress LldpV2DestAddressTableIndex,
64     lldpV2ConfigLrpTcpTxEnable            TruthValue
65 }
66
67
68 lldpV2ConfigLrpTcpTxLocalIfIndex OBJECT-TYPE
69     SYNTAX      InterfaceIndex
```

```
1  MAX-ACCESS  not-accessible
2  STATUS      current
3  DESCRIPTION
4      "The interface index value used to identify the port
5      associated with this entry. Its value is an index
6      into the interfaces MIB
7
8      The value of this object is used as an index to the
9      lldpV2ConfigLrpTcpTxTable.
10     "
11     ::= { lldpV2ConfigLrpTcpTxEntry 1 }
12
13 lldpV2ConfigLrpTcpTxLocalDestMACAddress OBJECT-TYPE
14     SYNTAX      LldpV2DestAddressTableIndex
15     MAX-ACCESS  not-accessible
16     STATUS      current
17     DESCRIPTION
18         "The index value used to identify the LLDPDU frame destination
19         MAC address associated with this entry. Its value identifies
20         the row in the lldpV2DestAddressTable where the MAC address
21         can be found.
22
23         The value of this object is used as an index to the
24         lldpV2ConfigLrpTcpTxTable.
25         "
26     ::= { lldpV2ConfigLrpTcpTxEntry 2 }
27
28
29 lldpV2ConfigLrpTcpTxEnable OBJECT-TYPE
30     SYNTAX      TruthValue
31     MAX-ACCESS  read-write
32     STATUS      current
33     DESCRIPTION
34         "The lldpV2ConfigLrpTcpTxEnable, which is defined
35         as a truth value and configured by the network management,
36         determines whether the IEEE 802.1 organizationally defined
37         LRP TCP Discovery TLV transmission is allowed on a given
38         LLDP transmission-capable port component.
39
40         The value of this object is restored from non-volatile
41         storage after a re-initialization of the management system."
42     REFERENCE
43         "9.1.2.1 of IEEE Std 802.1AB-2016"
44     DEFVAL { false }
45     ::= { lldpV2ConfigLrpTcpTxEntry 3 }
46
47
48 -----
49 -- IEEE 802.1CS LRP LLDP TLVs - Local System Information
50 -----
51
52 --
53 -- lldpV2LocLrpEcpTable
54 --
55
56 lldpV2LocLrpEcpTable OBJECT-TYPE
57     SYNTAX      SEQUENCE OF LldpV2LocLrpEcpEntry
58     MAX-ACCESS  not-accessible
59     STATUS      current
60     DESCRIPTION
61         "This table contains one or more rows per physical network
62         connection known to this agent. The agent may wish to
63         ensure that only one lldpV2ExtLrpLocEntry is present for
64         each local port, or it may choose to maintain multiple
65         lldpV2ExtLrpLocEntries for the same local port.
66         "
67     REFERENCE
```

```
1      "11.6.2.2"
2      ::= { lldpV2ExtLrpLocalData 3 }
3
4 lldpV2LocLrpEcpEntry OBJECT-TYPE
5     SYNTAX      LldpV2LocLrpEcpEntry
6     MAX-ACCESS  not-accessible
7     STATUS      current
8     DESCRIPTION
9         "Information about the C.2.1LRP ECP Discovery TLV that can
10        be transmitted from a particular LLDP port component.
11        Note that this MIB supports the transmission of only one
12        LRP ECP Discovery TLV per port component.
13        "
14     INDEX      { lldpV2LocLrpEcpLocalIfIndex,
15                  lldpV2LocLrpEcpLocalDestMACAddress,
16                  lldpV2LocLrpEcpApplicationIndex }
17     ::= { lldpV2LocLrpEcpTable 1 }
18
19
20 LldpV2LocLrpEcpEntry ::= SEQUENCE {
21     lldpV2LocLrpEcpLocalIfIndex      InterfaceIndex,
22     lldpV2LocLrpEcpLocalDestMACAddress LldpV2DestAddressTableIndex,
23     lldpV2LocLrpEcpApplicationIndex   Unsigned32,
24     lldpV2LocLrpEcpApplicationId      LrpAppId
25 }
26
27
28 lldpV2LocLrpEcpLocalIfIndex OBJECT-TYPE
29     SYNTAX      InterfaceIndex
30     MAX-ACCESS  not-accessible
31     STATUS      current
32     DESCRIPTION
33         "The interface index value used to identify the port
34         associated with this entry. Its value is an index
35         into the interfaces MIB
36
37         The value of this object is used as an index to the
38         lldpV2LocLrpEcpTable.
39         "
40     ::= { lldpV2LocLrpEcpEntry 1 }
41
42
43 lldpV2LocLrpEcpLocalDestMACAddress OBJECT-TYPE
44     SYNTAX      LldpV2DestAddressTableIndex
45     MAX-ACCESS  not-accessible
46     STATUS      current
47     DESCRIPTION
48         "The index value used to identify the LLDPDU frame destination
49         MAC address associated with this entry. Its value identifies
50         the row in the lldpV2DestAddressTable where the MAC address
51         can be found.
52
53         The value of this object is used as an index to the
54         lldpV2LocLrpEcpTable.
55         "
56     ::= { lldpV2LocLrpEcpEntry 2 }
57
58
59 lldpV2LocLrpEcpApplicationIndex OBJECT-TYPE
60     SYNTAX      Unsigned32 (0..255)
61     MAX-ACCESS  not-accessible
62     STATUS      current
63     DESCRIPTION
64         "A small integer that selects one entry in the
65         lldpV2LocLrpEcpTable. For every entry in lldpV2LocLrpEcpEntry,
66         there is one Application descriptor in the transmitted
67         LRP ECP Discovery TLV.
68
69         The value of the transmitted Application count field in the
```

```
1      LRP ECP Discovery TLV is equal to the number of different values
2      of lldpV2LocLrpEcpApplicationIndex for this port component.
3      "
4      REFERENCE "C.2.1.5, C.2.1.6"
5      ::= { lldpV2LocLrpEcpEntry 3 }
6
7 lldpV2LocLrpEcpApplicationId OBJECT-TYPE
9     SYNTAX      LrpAppId
10    MAX-ACCESS   read-only
11    STATUS       current
12    DESCRIPTION
13        "The AppId in one Application descriptor in the transmitted
14        LRP ECP Discovery TLV.
15        "
16    REFERENCE "C.2.1.5, C.2.1.6"
17    ::= { lldpV2LocLrpEcpEntry 4 }
18
19 --
20 -- lldpV2LocLrpTcpTable - indexed by ifIndex.
21 --
22
23 lldpV2LocLrpTcpTable OBJECT-TYPE
25    SYNTAX      SEQUENCE OF LldpV2LocLrpTcpEntry
26    MAX-ACCESS   not-accessible
27    STATUS       current
28    DESCRIPTION
29        "This table contains one or more rows per physical network
30        connection known to this agent, one for each port component.
31        "
32    ::= { lldpV2ExtLrpLocalData 4 }
33
34 lldpV2LocLrpTcpEntry OBJECT-TYPE
36    SYNTAX      LldpV2LocLrpTcpEntry
37    MAX-ACCESS   not-accessible
38    STATUS       current
39    DESCRIPTION
40        "Information about a particular LLDP port component's transmitted
41        LRP TCP Discovery TLV. Note that this MIB supports the
42        transmission of only one LRP TCP Discovery TLV per port
43        component.
44        "
45    INDEX      { lldpV2LocLrpTcpLocalIfIndex,
46                lldpV2LocLrpTcpLocalDestMACAddress,
47                lldpV2LocLrpTcpApplicationIndex }
48    ::= { lldpV2LocLrpTcpTable 1 }
49
50 lldpV2LocLrpTcpEntry ::= SEQUENCE {
52     lldpV2LocLrpTcpLocalIfIndex      InterfaceIndex,
53     lldpV2LocLrpTcpLocalDestMACAddress LldpV2DestAddressTableIndex,
54     lldpV2LocLrpTcpApplicationIndex  Unsigned32,
55     lldpV2LocLrpTcpApplicationId     LrpAppId,
56     lldpV2LocLrpTcpPortNumber        InetPortNumber,
57     lldpV2LocLrpTcpAddressInfo1      LrpInetAddressInfo,
58     lldpV2LocLrpTcpAddress1          InetAddress,
59     lldpV2LocLrpTcpAddressInfo2      LrpInetAddressInfo,
60     lldpV2LocLrpTcpAddress2          InetAddress
61 }
62
63 lldpV2LocLrpTcpLocalIfIndex OBJECT-TYPE
65    SYNTAX      InterfaceIndex
66    MAX-ACCESS   not-accessible
67    STATUS       current
68    DESCRIPTION
69        "The interface index value used to identify the port
70        associated with this entry. Its value is an index
```

```
1      into the interfaces MIB
2
3      The value of this object is used as an index to the
4      lldpV2LocLrpTcpTable.
5      "
6      ::= { lldpV2LocLrpTcpEntry 1 }
7
8 lldpV2LocLrpTcpLocalDestMACAddress OBJECT-TYPE
9     SYNTAX      LldpV2DestAddressTableIndex
10    MAX-ACCESS   not-accessible
11    STATUS       current
12    DESCRIPTION
13        "The index value used to identify the destination
14        MAC address associated with this entry. Its value identifies
15        the row in the lldpV2DestAddressTable where the MAC address
16        can be found.
17
18        The value of this object is used as an index to the
19        lldpV2LocLrpTcpTable.
20        "
21    ::= { lldpV2LocLrpTcpEntry 2 }
22
23 lldpV2LocLrpTcpApplicationIndex OBJECT-TYPE
24     SYNTAX      Unsigned32 (0..255)
25     MAX-ACCESS   not-accessible
26     STATUS       current
27     DESCRIPTION
28         "A small integer that selects one entry in the
29         lldpV2LocLrpTcpTable. For every entry in lldpV2LocLrpTcpEntry,
30         there is one Application descriptor in the transmitted
31         LRP TCP Discovery TLV.
32
33         The value of the transmitted Application count field in the
34         LRP TCP Discovery TLV is equal to the number of different values
35         of lldpV2LocLrpTcpApplicationIndex for this port component.
36         "
37     REFERENCE "C.2.2.5, C.2.2.6"
38     ::= { lldpV2LocLrpTcpEntry 3 }
39
40 lldpV2LocLrpTcpApplicationId OBJECT-TYPE
41     SYNTAX      LrpAppId
42     MAX-ACCESS   read-only
43     STATUS       current
44     DESCRIPTION
45         "The AppId in one Application descriptor in the transmitted
46         LRP TCP Discovery TLV.
47         "
48     REFERENCE "C.2.2.6"
49     ::= { lldpV2LocLrpTcpEntry 4 }
50
51 lldpV2LocLrpTcpPortNumber OBJECT-TYPE
52     SYNTAX      InetPortNumber
53     MAX-ACCESS   read-only
54     STATUS       current
55     DESCRIPTION
56         "The contents of the TCP Port number field in the transmitted
57         LRP TCP Discovery TLV. lldpV2LocLrpTcpPortNumber SHALL NOT
58         contain the value 0.
59         "
60     REFERENCE "C.2.2.6"
61     ::= { lldpV2LocLrpTcpEntry 5 }
62
63 lldpV2LocLrpTcpAddressInfo1 OBJECT-TYPE
64     SYNTAX      LrpInetAddressInfo
65     MAX-ACCESS   read-only
```

```
1 STATUS current
2 DESCRIPTION
3 "The contents of the first Address info field in the transmitted
4 Application descriptor. lldpV2LocLrpTcpAddressInfo1 SHALL NOT
5 contain the value, notPresent(256).
6 "
7 REFERENCE "C.2.2.6"
8 ::= { lldpV2LocLrpTcpEntry 6 }
9
10 lldpV2LocLrpTcpAddress1 OBJECT-TYPE
11 SYNTAX InetAddress
12 MAX-ACCESS read-only
13 STATUS current
14 DESCRIPTION
15 "The contents of the first Address field in the transmitted
16 Application descriptor. If lldpV2LocLrpTcpAddressInfo1 has the
17 value notPresent(256) or noAddress(0), lldpV2LocLrpTcpAddress1
18 SHALL contain a zero-length octet string. Otherwise,
19 lldpV2LocLrpTcpAddress1 SHALL contain an IPv4 or IPv6 address,
20 as specified by lldpV2LocLrpTcpAddressInfo1.
21 "
22 REFERENCE "C.2.2.6"
23 ::= { lldpV2LocLrpTcpEntry 7 }
24
25
26 lldpV2LocLrpTcpAddressInfo2 OBJECT-TYPE
27 SYNTAX LrpInetAddressInfo
28 MAX-ACCESS read-only
29 STATUS current
30 DESCRIPTION
31 "The contents of the second Address info field in the transmitted
32 Application descriptor. lldpV2LocLrpTcpAddressInfo2 has the
33 value notPresent(256) if there is no second Address info field
34 in the Application descriptor.
35 "
36 REFERENCE "C.2.2.6"
37 ::= { lldpV2LocLrpTcpEntry 8 }
38
39
40 lldpV2LocLrpTcpAddress2 OBJECT-TYPE
41 SYNTAX InetAddress
42 MAX-ACCESS read-only
43 STATUS current
44 DESCRIPTION
45 "The contents of the second Address field in the transmitted
46 Application descriptor. If lldpV2LocLrpTcpAddressInfo2 has the
47 value notPresent(256) or noAddress(0), lldpV2LocLrpTcpAddress2
48 SHALL contain a zero-length octet string. Otherwise,
49 lldpV2LocLrpTcpAddress2 SHALL contain an IPv4 or IPv6 address,
50 as specified by lldpV2LocLrpTcpAddressInfo2.
51 "
52 REFERENCE "C.2.2.6"
53 ::= { lldpV2LocLrpTcpEntry 9 }
54
55
56 -----
57 -- IEEE 802.1CS LRP LLDP TLVs - Remote (Neighbor) System Information
58 -----
59
60 --
61 -- lldpV2RemLrpEcpTable
62 --
63
64 lldpV2RemLrpEcpTable OBJECT-TYPE
65 SYNTAX SEQUENCE OF LldpV2RemLrpEcpEntry
66 MAX-ACCESS not-accessible
67 STATUS current
68 DESCRIPTION
69
```

```
1         "This table contains one or more rows per physical network
2         connection known to this agent. The agent may wish to
3         ensure that only one lldpV2ExtLrpRemEntry is present for
4         each local port, or it may choose to maintain multiple
5         lldpV2ExtLrpRemEntries for the same local port."
6     REFERENCE
7         "11.6.2.3"
8     ::= { lldpV2ExtLrpRemoteData 1 }
9
10 lldpV2RemLrpEcpEntry OBJECT-TYPE
11     SYNTAX      LldpV2RemLrpEcpEntry
12     MAX-ACCESS  not-accessible
13     STATUS      current
14     DESCRIPTION
15         "Information about a particular port component."
16     INDEX       { lldpV2RemLrpEcpTimeMark,
17                  lldpV2RemLrpEcpLocalIfIndex,
18                  lldpV2RemLrpEcpLocalDestMACAddress,
19                  lldpV2RemLrpEcpIndex,
20                  lldpV2RemLrpEcpApplicationIndex }
21     ::= { lldpV2RemLrpEcpTable 1 }
22
23
24 lldpV2RemLrpEcpEntry ::= SEQUENCE {
25     lldpV2RemLrpEcpTimeMark      TimeFilter,
26     lldpV2RemLrpEcpLocalIfIndex  InterfaceIndex,
27     lldpV2RemLrpEcpLocalDestMACAddress LldpV2DestAddressTableIndex,
28     lldpV2RemLrpEcpIndex         Unsigned32,
29     lldpV2RemLrpEcpApplicationIndex Unsigned32,
30     lldpV2RemLrpEcpApplicationId LrpAppId
31 }
32
33
34 lldpV2RemLrpEcpTimeMark OBJECT-TYPE
35     SYNTAX      TimeFilter
36     MAX-ACCESS  not-accessible
37     STATUS      current
38     DESCRIPTION
39         "A TimeFilter for this entry. See the TimeFilter textual
40         convention in IETF RFC 4502 to see how TimeFilter works."
41     "
42     REFERENCE
43         "IETF RFC 4502 section 6"
44     ::= { lldpV2RemLrpEcpEntry 1 }
45
46
47
48 lldpV2RemLrpEcpLocalIfIndex OBJECT-TYPE
49     SYNTAX      InterfaceIndex
50     MAX-ACCESS  not-accessible
51     STATUS      current
52     DESCRIPTION
53         "The interface index value used to identify the port
54         associated with this entry. Its value is an index
55         into the interfaces MIB
56
57         The value of this object is used as an index to the
58         lldpV2RemLrpEcpTable.
59     "
60     ::= { lldpV2RemLrpEcpEntry 2 }
61
62
63 lldpV2RemLrpEcpLocalDestMACAddress OBJECT-TYPE
64     SYNTAX      LldpV2DestAddressTableIndex
65     MAX-ACCESS  not-accessible
66     STATUS      current
67     DESCRIPTION
68         "The index value used to identify the LLDPDU frame destination
69         MAC address associated with this entry. Its value identifies
```

```
1         the row in the lldpV2DestAddressTable where the MAC address
2         can be found.
3
4         The value of this object is used as an index to the
5         lldpV2RemLrpTcpTable.
6         "
7         ::= { lldpV2RemLrpEcpEntry 3 }
8
9
10 lldpV2RemLrpEcpIndex OBJECT-TYPE
11     SYNTAX      Unsigned32(1..2147483647)
12     MAX-ACCESS  not-accessible
13     STATUS      current
14     DESCRIPTION
15         "This object represents an arbitrary local integer value used
16         by this agent to identify a particular connection instance,
17         unique only for the indicated remote system.
18
19         An agent is encouraged to assign monotonically increasing
20         index values to new entries, starting with one, after each
21         reboot. It is considered unlikely that the
22         lldpV2RemLrpEcpIndex can wrap between reboots.
23         "
24     ::= { lldpV2RemLrpEcpEntry 4 }
25
26
27 lldpV2RemLrpEcpApplicationIndex OBJECT-TYPE
28     SYNTAX      Unsigned32 (0..255)
29     MAX-ACCESS  not-accessible
30     STATUS      current
31     DESCRIPTION
32         "A small integer that selects one entry in the
33         lldpV2RemLrpEcpTable. For every entry in lldpV2RemLrpEcpEntry,
34         there is one Application descriptor in the received
35         LRP ECP Discovery TLV.
36
37         The value of the received Application count field in the
38         LRP ECP Discovery TLV is equal to the number of different values
39         of lldpV2RemLrpEcpApplicationIndex for this connection instance.
40         "
41     REFERENCE "C.2.1.5, C.2.1.6"
42     ::= { lldpV2RemLrpEcpEntry 5 }
43
44
45 lldpV2RemLrpEcpApplicationId OBJECT-TYPE
46     SYNTAX      LrpAppId
47     MAX-ACCESS  read-only
48     STATUS      current
49     DESCRIPTION
50         "The AppId in one Application descriptor in the received
51         LRP ECP Discovery TLV.
52         "
53     REFERENCE "C.2.1.5, C.2.1.6"
54     ::= { lldpV2RemLrpEcpEntry 6 }
55
56
57 --
58 -- lldpV2RemLrpTcpTable
59 --
60
61 lldpV2RemLrpTcpTable OBJECT-TYPE
62     SYNTAX      SEQUENCE OF LldpV2RemLrpTcpEntry
63     MAX-ACCESS  not-accessible
64     STATUS      current
65     DESCRIPTION
66         "This table contains one or more rows per physical network
67         connection known to this agent. The agent may wish to
68         ensure that only one lldpV2ExtLrpRemEntry is present for
```



```
1         each local port, or it may choose to maintain multiple
2         lldpV2ExtLrpRemEntries for the same local port."
3 ::= { lldpV2ExtLrpRemoteData 2 }
4
5 lldpV2RemLrpTcpEntry OBJECT-TYPE
6     SYNTAX      LldpV2RemLrpTcpEntry
7     MAX-ACCESS  not-accessible
8     STATUS      current
9     DESCRIPTION
10        "Information about a particular port component."
11     INDEX      { lldpV2RemLrpTcpTimeMark,
12                 lldpV2RemLrpTcpLocalIfIndex,
13                 lldpV2RemLrpTcpLocalDestMACAddress,
14                 lldpV2RemLrpTcpIndex,
15                 lldpV2RemLrpTcpApplicationIndex }
16 ::= { lldpV2RemLrpTcpTable 1 }
17
18
19 LldpV2RemLrpTcpEntry ::= SEQUENCE {
20     lldpV2RemLrpTcpTimeMark      TimeFilter,
21     lldpV2RemLrpTcpLocalIfIndex  InterfaceIndex,
22     lldpV2RemLrpTcpLocalDestMACAddress  LldpV2DestAddressTableIndex,
23     lldpV2RemLrpTcpIndex         Unsigned32,
24     lldpV2RemLrpTcpApplicationIndex  Unsigned32,
25     lldpV2RemLrpTcpApplicationId  LrpAppId,
26     lldpV2RemLrpTcpPortNumber    InetPortNumber,
27     lldpV2RemLrpTcpAddressInfo1  LrpInetAddressInfo,
28     lldpV2RemLrpTcpAddress1     InetAddress,
29     lldpV2RemLrpTcpAddressInfo2  LrpInetAddressInfo,
30     lldpV2RemLrpTcpAddress2     InetAddress
31 }
32
33
34 lldpV2RemLrpTcpTimeMark OBJECT-TYPE
35     SYNTAX      TimeFilter
36     MAX-ACCESS  not-accessible
37     STATUS      current
38     DESCRIPTION
39        "A TimeFilter for this entry. See the TimeFilter textual
40        convention in IETF RFC 4502 to see how TimeFilter works."
41
42     REFERENCE
43        "IETF RFC 4502 section 6"
44 ::= { lldpV2RemLrpTcpEntry 1 }
45
46
47
48 lldpV2RemLrpTcpLocalIfIndex OBJECT-TYPE
49     SYNTAX      InterfaceIndex
50     MAX-ACCESS  not-accessible
51     STATUS      current
52     DESCRIPTION
53        "The interface index value used to identify the port
54        associated with this entry. Its value is an index
55        into the interfaces MIB
56
57        The value of this object is used as an index to the
58        lldpV2RemLrpTcpTable.
59
60 ::= { lldpV2RemLrpTcpEntry 2 }
61
62
63 lldpV2RemLrpTcpLocalDestMACAddress OBJECT-TYPE
64     SYNTAX      LldpV2DestAddressTableIndex
65     MAX-ACCESS  not-accessible
66     STATUS      current
67     DESCRIPTION
68        "The index value used to identify the destination
69        MAC address associated with this entry. Its value identifies
```

```
1         the row in the lldpV2DestAddressTable where the MAC address
2         can be found.
3
4         The value of this object is used as an index to the
5         lldpV2RemLrpTcpTable.
6         "
7         ::= { lldpV2RemLrpTcpEntry 3 }
8
9
10 lldpV2RemLrpTcpIndex OBJECT-TYPE
11     SYNTAX      Unsigned32(1..2147483647)
12     MAX-ACCESS  not-accessible
13     STATUS      current
14     DESCRIPTION
15         "This object represents an arbitrary local integer value used
16         by this agent to identify a particular connection instance,
17         unique only for the indicated remote system.
18
19         An agent is encouraged to assign monotonically increasing
20         index values to new entries, starting with one, after each
21         reboot. It is considered unlikely that the
22         lldpV2RemLrpTcpIndex can wrap between reboots.
23         "
24     ::= { lldpV2RemLrpTcpEntry 4 }
25
26
27 lldpV2RemLrpTcpApplicationIndex OBJECT-TYPE
28     SYNTAX      Unsigned32 (0..255)
29     MAX-ACCESS  not-accessible
30     STATUS      current
31     DESCRIPTION
32         "A small integer that selects one entry in the
33         lldpV2RemLrpTcpTable. For every entry in lldpV2RemLrpTcpEntry,
34         there is one Application descriptor in the received
35         LRP TCP Discovery TLV.
36
37         The value of the received Application count field in the
38         LRP TCP Discovery TLV is equal to the number of different values
39         of lldpV2RemLrpTcpApplicationIndex for this connection instance.
40         "
41     REFERENCE "C.2.2.5, C.2.2.6"
42     ::= { lldpV2RemLrpTcpEntry 5 }
43
44
45 lldpV2RemLrpTcpApplicationId OBJECT-TYPE
46     SYNTAX      LrpAppId
47     MAX-ACCESS  read-only
48     STATUS      current
49     DESCRIPTION
50         "The AppId in one Application descriptor in the received
51         LRP TCP Discovery TLV.
52         "
53     REFERENCE "C.2.2.6"
54     ::= { lldpV2RemLrpTcpEntry 6 }
55
56
57 lldpV2RemLrpTcpPortNumber OBJECT-TYPE
58     SYNTAX      InetPortNumber
59     MAX-ACCESS  read-only
60     STATUS      current
61     DESCRIPTION
62         "The contents of the TCP Port number field in the received
63         Application descriptor. lldpV2RemLrpTcpPortNumber SHALL NOT
64         contain the value 0.
65         "
66     REFERENCE "C.2.2.6"
67     ::= { lldpV2RemLrpTcpEntry 7 }
68
69
```

```
1 lldpV2RemLrpTcpAddressInfo1 OBJECT-TYPE
3   SYNTAX      LrpInetAddressInfo
4   MAX-ACCESS  read-only
5   STATUS      current
6   DESCRIPTION
7       "The contents of the first Address info field in the received
8       Application descriptor. lldpV2RemLrpTcpAddressInfo1 SHALL NOT
9 contain the value, notPresent(256).
10      "
11   REFERENCE "C.2.2.6"
12   ::= { lldpV2RemLrpTcpEntry 8 }
13
14 lldpV2RemLrpTcpAddress1 OBJECT-TYPE
16   SYNTAX      InetAddress
17   MAX-ACCESS  read-only
18   STATUS      current
19   DESCRIPTION
20       "The contents of the first Address field in the received
21       Application descriptor. If lldpV2RemLrpTcpAddressInfo1 has the
22       value notPresent(256) or noAddress(0), lldpV2RemLrpTcpAddress1
23       SHALL contain a zero-length octet string. Otherwise,
24       lldpV2RemLrpTcpAddress1 SHALL contain an IPv4 or IPv6 address,
25       as specified by lldpV2RemLrpTcpAddressInfo1.
26      "
27   REFERENCE "C.2.2.6"
28   ::= { lldpV2RemLrpTcpEntry 9 }
29
30 lldpV2RemLrpTcpAddressInfo2 OBJECT-TYPE
32   SYNTAX      LrpInetAddressInfo
33   MAX-ACCESS  read-only
34   STATUS      current
35   DESCRIPTION
36       "The contents of the second Address info field in the received
37       Application descriptor. lldpV2RemLrpTcpAddressInfo2 has the
38       value notPresent(256) if there is no second Address info field
39       in the Application descriptor.
40      "
41   REFERENCE "C.2.2.6"
42   ::= { lldpV2RemLrpTcpEntry 10 }
43
44 lldpV2RemLrpTcpAddress2 OBJECT-TYPE
46   SYNTAX      InetAddress
47   MAX-ACCESS  read-only
48   STATUS      current
49   DESCRIPTION
50       "The contents of the second Address field in the received
51       Application descriptor. If lldpV2RemLrpTcpAddressInfo2 has the
52       value notPresent(256) or noAddress(0), lldpV2RemLrpTcpAddress2
53       SHALL contain a zero-length octet string. Otherwise,
54       lldpV2RemLrpTcpAddress2 SHALL contain an IPv4 or IPv6 address,
55       as specified by lldpV2RemLrpTcpAddressInfo2.
56      "
57   REFERENCE "C.2.2.6"
58   ::= { lldpV2RemLrpTcpEntry 11 }
59
60 -----
61 -- Conformance Information for the basicSet TLV set
62 -----
63
64 lldpV2ExtLrpConformance
66   OBJECT IDENTIFIER ::= { lldpXdot1StandAloneExtensions 9 }
67 lldpV2ExtLrpCompliances
69   OBJECT IDENTIFIER ::= { lldpV2ExtLrpConformance 1 }
70 lldpV2ExtLrpGroups
72   OBJECT IDENTIFIER ::= { lldpV2ExtLrpConformance 2 }
```

```
1
2 -- compliance statements
3
4
5 lldpV2ExtLrpTxRxCompliance MODULE-COMPLIANCE
6
7     STATUS current
8     DESCRIPTION
9         "A compliance statement for SNMP entities that implement
10         the IEEE 802.1 organizationally defined LLDP extension MIB.
11
12         This group is mandatory for all agents that implement the
13         LLDP 802.1 organizational extension in TX and/or RX mode
14         for the basicSet TLV set.
15
16         This version defines compliance requirements for
17         V2 of the LLDP MIB."
18     MODULE -- this module
19     ::= { lldpV2ExtLrpCompliances 1 }
20
21
22
23 -- MIB groupings for the basicSet TLV set
24
25 lldpV2ExtLrpControlledTcpControlGroup OBJECT-GROUP
26
27     OBJECTS {
28         lldpV2ConfigLrpTcpControlledTcpPortNumber,
29         lldpV2ConfigLrpTcpControlledIPv4Enable,
30         lldpV2ConfigLrpTcpControlledIPv4Address,
31         lldpV2ConfigLrpTcpControlledIPv6Enable,
32         lldpV2ConfigLrpTcpControlledIPv6Address
33     }
34     STATUS current
35     DESCRIPTION
36         "The optional collection of objects which are required of a
37         Controlled system so that a Proxy system SNMP client can
38         configure the LRP TCP Discovery TLVs to be transmitted by the
39         Controlled system.
40         "
41     REFERENCE "5.10:b"
42     ::= { lldpV2ExtLrpGroups 1 }
43
44 lldpV2ExtLrpEcpTlvGroup OBJECT-GROUP
45
46     OBJECTS {
47         lldpV2ConfigLrpEcpTxEnable,
48         lldpV2LocLrpEcpApplicationId,
49         lldpV2RemLrpEcpApplicationId
50     }
51     STATUS current
52     DESCRIPTION
53         "The optional collection of objects which are required of any
54         system implementing the LRP-DT ECP mechanism so that an SNMP
55         client can observe the LRP ECP Discovery TLVs transmitted and
56         received by the system."
57     REFERENCE "Clause 5"
58     ::= { lldpV2ExtLrpGroups 2 }
59
60 lldpV2ExtLrpTcpTlvGroup OBJECT-GROUP
61
62     OBJECTS {
63         lldpV2ConfigLrpTcpTxEnable,
64         lldpV2LocLrpTcpApplicationId,
65         lldpV2LocLrpTcpPortNumber,
66         lldpV2LocLrpTcpAddressInfo1,
67         lldpV2LocLrpTcpAddress1,
68         lldpV2LocLrpTcpAddressInfo2,
69         lldpV2LocLrpTcpAddress2,
```

```
1      lldpV2RemLrpTcpApplicationId,  
2      lldpV2RemLrpTcpPortNumber,  
3      lldpV2RemLrpTcpAddressInfo1,  
4      lldpV2RemLrpTcpAddress1,  
5      lldpV2RemLrpTcpAddressInfo2,  
6      lldpV2RemLrpTcpAddress2  
7  }  
8  STATUS current  
9  DESCRIPTION  
10     "The optional collection of objects which are required of any  
11     system implementing the LRP-DT TCP mechanism so that an SNMP  
12     client can observe the LRP TCP Discovery TLVs transmitted and  
13     received by the system."  
14  REFERENCE "Clause 5"  
15  ::= { lldpV2ExtLrpGroups 3 }  
16  
17 END  
18
```

Annex C

(normative)

IEEE 802.1 Organizationally Specific TLVs for LLDP

C.2 Organizationally Specific TLV definitions

C.2.2 LRP TCP Discovery TLV

C.2.2.6 Application descriptor

Change C.2.2.6 as follows:

An Application descriptor for the LRP TCP Discovery TLV contains four octets with an AppId, followed by one or two addresses to use to make the TCP association, as shown in Figure C-1. The first three octets contain the OUI or CID of the organization assigning the AppId, and the fourth octet identifies a specific LRP application that connects using TCP. Following these four octets is a two-octet TCP port number, followed in turn by the descriptions of one or two IP addresses, as shown in Table C-1.

Offset	0	3	4	6	7	varies	varies
	OUI or CID for AppId (3 octets)	AppId subtype (1 octet)	TCP port number (2 octets)	Address info 1 (1 octet)	Address 1 (0, 4, or 16 octets)	Address info 2 (1 octet)	Address 2 (0, 4, or 16 octets)

Figure C-1—LRP TCP Discovery TLV application descriptor format

Table C-1—Allowed address information encodings and lengths

Address info 1	Address 1 length	Address info 2	Address 2 length	Total length of address information
noAddress	0	addrIPv4	4	6
		addrIPv6	16	18
addrIPv4	4	not present ^a	0	5
		noAddress	0	6
		addrIPv6	16	22
addrIPv6	16	not present ^a	0	17
		noAddress	0	18
		addrIPv4	4	22

^a [Allowed only at the end of the TLV. See C.2.2.7.](#)

1 **C.2.2.7 LRP TCP Discovery TLV usage rules**

2 *Change section C.2.2.7 as follows:*

3 The LRP TCP Discovery TLV is used to establish TCP associations among the Portals on a physical link. A
4 Native or Controlled system should transmit this TLV if and only if the information transmitted in the
5 LLDPDU matches the information in an entry in the imTargetPortList (7.2.2.1) in the Native system or the
6 Controlled's Proxy system.

7 A system shall not transmit the same AppId value in more than one Application descriptor of the same LRP
8 TCP Discovery TLV. A system can transmit more than one LRP TCP Discovery TLV for different sets of
9 AppId values, but the same AppId value shall not appear in more than one LRP TCP Discovery TLV in the
10 same LLDPDU. At least one IP address shall be included in an LRP TCP Discovery TLV. If two addresses
11 are included, they shall be of different types (addrIPv4 vs. addrIPv6). The second AddressInfo field can be
12 omitted from an application descriptor (be not present in Table C-2) only if it would be the last octet of the
13 LRP TCP Discovery TLV.

14 NOTE—The provision for sending or receiving multiple LRP TCP Discovery TLVs is made to facilitate control of these
15 LLDP TLVs by more than one LRP application.

16 This standard does not specify the actions to be taken if a received LRP TCP Discovery TLV violates these
17 usage rules.

18 As explained in 9.2.7.7.2 of IEEE Std 802.1AB-2016, a received LRP TCP Discovery TLV is not invalid if
19 the value of the TLV information string length field is larger than the total amount of information indicated
20 by the Application count and Application descriptors. A system receiving such a TLV shall interpret the
21 TLV as described in this standard, and ignore any information following the Application descriptor.

22