IEEE P802.3.1b™/D0.1

Draft Standard for Ethernet Structure of Management Information version 2 (SMIv2) Data Model Definitions

Sponsor

LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved XX XXXX 202X

IEEE-SA Standards Board

Prepared by the

LAN/MAN Standards Committee
of the
IEEE Computer Society

This draft is a revision of IEEE Std 802.3.1-2013. Draft D0.1 is prepared for the Task Force review. This draft expires 6 months after the date of publication or when the next version is published, whichever comes first.

IEEE Standards Department
445 Hoes Lane
Piscataway, NJ 08854, USA

Permissions have been granted as follows[a]:

> ***Editor's Note (to be removed prior to publication):***
>
> Confirm permissions are still applicable.

Portions of this standard reprinted with permission from Avaya, IETF RFC 2108 Definitions of Managed Objects for IEEE 802.3 Repeater Devices using SMIv2, © 1997.

Portions of this standard reprinted with permission from Microsemi Corporation, IETF RFC 3621 Definitions Power Ethernet MIB, © 2003.

Portions of this standard reprinted with permission from Avaya, IETF RFC 3621 Definitions Power Ethernet MIB, © 2003.

Portions of this standard reprinted with permission from the Hewlett-Packard Company, IETF RFC 3635 Definitions of Managed Objects for the Ethernet-like Interface Types, © 2003.

Material from IETF RFC 4836 Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs) reprinted with permission from the IETF Trust and the persons identified as the document authors, © 2007.

Portions of this standard reprinted with permission from Edward Beili, IETF RFC 4836 Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs), © 2007.

Material from IETF RFC 4837 Managed Objects of Ethernet Passive Optical Networks (EPON) reprinted with permission from the IETF Trust and the persons identified as the document authors, © 2007.

Portions of this standard reprinted with permission from PMC-Sierra, IETF RFC 4837 Managed Objects of Ethernet Passive Optical Networks (EPON), © 2007.

Material from IETF RFC 4878 Definitions and Managed Objects for Operations, Administration, and Maintenance (OAM) Functions on Ethernet-Like Interfaces reprinted with permission from the IETF Trust and the persons identified as the document authors, © 2007.

Material from IETF RFC 5066 Ethernet in the First Mile Copper (EFMCu) Interfaces MIB reprinted with permission from the IETF Trust and the persons identified as the document authors.

Portions of this standard reprinted with permission from Edward Beili, IETF RFC 5066 Ethernet in the First Mile Copper (EFMCu) Interfaces MIB, © 2007.

[a]Every effort has been made to secure permission to reprint borrowed material contained in this document. If omissions have been made, please bring them to the attention of the IEEE P802.3.1 working group.

Abstract: This standard defines Structure of Management Information version 2 (SMIv2) MIB module specifications for IEEE Std 802.3 Ethernet and associated managed object branch and leaf assignments used in the variable descriptors in IEEE Std 802.3 Variable Request operations, administration, and maintenance protocol data unit (OAMPUD).

Keywords: Ethernet, IEEE 802.3.1™, Management Information Base (MIB), network management, Simple Network Management Protocol (SNMP), Structure of Management Information Version 2 (SMIv2)

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

PDF: ISBN 978-0-7381-8432-6 STD98241
Print: ISBN 978-0-7381-8433-3 STDPD98241

Editor's Note (to be removed prior to publication):

This front matter is provided for comment only. Front matter is not part of a published standard and is therefore, not part of the draft standard. You are invited to review and comment on it as it will be included in the published standard after approval.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE Standards documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page (https://standards.ieee.org/ipr/disclaimers.html), appear in all standards and may be found under the heading "Important Notices and Disclaimers Concerning IEEE Standards Documents."

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents are developed within IEEE Societies and subcommittees of IEEE Standards Association (IEEE SA) Board of Governors. IEEE develops its standards through an accredited consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed by volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers are not necessarily members of IEEE or IEEE SA and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE makes no warranties or representations concerning its standards, and expressly disclaims all warranties, express or implied, concerning this standard, including but not limited to the warranties of merchantability, fitness for a particular purpose and non-infringement. In addition, IEEE does not warrant or represent that the use of the material contained in its standards is free from patent infringement. IEEE standards documents are supplied "AS IS" and "WITH ALL FAULTS."

Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,

WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE is the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that the presenter's views should be considered the personal views of that individual rather than the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group. Statements made by volunteers may not represent the formal position of their employer(s) or affiliation(s).

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations, consulting information, or advice pertaining to IEEE Standards documents**.

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its Societies and subcommittees of the IEEE SA Board of Governors are not able to provide an instant response to comments, or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in evaluating comments or in revisions to an IEEE standard is welcome to join the relevant IEEE working group. You can indicate interest in a working group using the Interests tab in the Manage Profile & Interests area of the IEEE SA myProject system.[b] An IEEE Account is needed to access the application.

Comments on standards should be submitted using the Contact Us form.[c]

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not constitute compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

---

[b] Available at: https://development.standards.ieee.org/myproject-web/public/view.html#landing.

[c] Available at: https://standards.ieee.org/content/ieee-standards/en/about/contact/index.html.

Data privacy

Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and data ownership in the context of assessing and using the standards in compliance with applicable laws and regulations.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, neither IEEE nor its licensors waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate licensing fees, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400; https://www.copyright.com/. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit IEEE Xplore or contact IEEE.[d] For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE SA Website.[e] Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in IEEE Xplore. Users are encouraged to periodically check for errata.

[d] Available at: https://ieeexplore.ieee.org/browse/standards/collection/ieee.

[e] Available at: https://standards.ieee.org/standard/index.html.

Patents

IEEE Standards are developed in compliance with the IEEE SA Patent Policy.[f]

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at https://standards.ieee.org/about/sasb/patcom/patents.html. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

IMPORTANT NOTICE

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. IEEE Standards development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

[f] Available at: https://standards.ieee.org/about/sasb/patcom/materials.html.

Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3.2a Working Group ballot.

David J. Law, *IEEE 802.3 Working Group Chair*
Adam Healey, *IEEE 802.3 Working Group Vice-Chair*
Jon Lewis, *IEEE 802.3 Working Group Secretary*
Steven B. Carlson, *IEEE 802.3 Working Group Executive Secretary*
Valerie Maguire, *IEEE 802.3 Working Group Treasurer*

Marek Hajduczenia, *IEEE P802.3.2a Task Force Chair and Editor*

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

When the IEEE-SA Standards Board approved this standard on XX Month 202X, it had the following membership:

FirstName SecondName, *Chair*
FirstName SecondName, *Vice Chair*
FirstName SecondName, *Past Chair*
Konstantinos Karachalios, *Secretary*

[to be supplied at publication]

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.3.1b-202x, Standard for Ethernet Structure of Management Information version 2 (SMIv2) Data Model Definitions.

The initial version of this standard was based on the managed object definitions provided in IEEE Std 802.3™-2008, which subsumed and superseded IEEE Std 802.3an™-2006, IEEE Std 802.3ap™-2007, IEEE Std 802.3aq™-2006, and IEEE Std 802.3as™-2006. It also includes the Logical Link Discovery Protocol Ethernet extensions provided in Annex F of IEEE Std 802.1AB™-2009.[g] In addition, the initial version of this standard incorporated and updated the MIB module definitions formerly defined in IETF RFC 2108 [B20],[h] IETF RFC 3621 [B27], IETF RFC 3635 [B29], IETF RFC 3637 [B30], IETF RFC 4836 [B35], IETF RFC 4837 [B36], IETF RFC 4878 [B37], and IETF RFC 5066 [B38].

The first revision of this standard updated the MIB module definitions to reflect the managed object definitions provided in IEEE Std 802.3-2012, which subsumed and superseded IEEE Std 802.3-2008, IEEE Std 802.3at™, IEEE Std 802.3av™, IEEE Std 802.3az™, IEEE Std 802.3ba™, IEEE Std 802.3bc™, IEEE Std 802.3bd™, IEEE Std 802.3bf™, and IEEE Std 802.3bg™.

The second revision of this standard ... <<<TBD>>>

---

[g] Information on references can be found in Clause 2.

[h] The numbers in brackets correspond to those of the bibliography in Annex A.

Contents

Standard for Ethernet Structure of Management Information version 2 (SMIv2) Data Model Definitions

IMPORTANT NOTICE: IEEE Standards documents are not intended to ensure safety, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading "Important Notice" or "Important Notices and Disclaimers Concerning IEEE Documents." They can also be obtained on request from IEEE or viewed at http://standards.ieee.org/IPR/disclaimers.html.

1. Overview

> ***Editor's Note (to be removed prior to publication):***
>
> Text of the Overview will need to be aligned with the new scope of the project and perhaps keep the original Overview in historic description of the project. A new scope aligned with PAR scope needs to be provided.

This document supersedes and makes obsolete Annex 30A and Annex 30B of IEEE Std 802.3™-2008, Annex F of IEEE Std 802.1AB™-2009,[1] IETF RFC 2108 [B20],[2] IETF RFC 3621 [B27], IETF RFC 3635 [B29], IETF RFC 3637 [B30], IETF RFC 4836 [B35], IETF RFC 4837 [B36], IETF RFC 4878 [B37], and IETF RFC 5066 [B38].

---

[1]Information on references can be found in Clause 2.

[2]The numbers in brackets correspond to those of the bibliography in Annex A.

Ethernet technology, as defined by the IEEE 802.3 Working Group, continues to evolve, with scalable increases in speed, new types of cabling and interfaces, and new features. This evolution may require changes in the managed objects in order to reflect this new functionality. This document, as with other documents issued by this working group, reflects a certain stage in the evolution of Ethernet technology. In the future, this document might be revised, or new documents might be issued, in order to reflect the evolution of Ethernet technology.

The term “Ethernet-like interfaces” was historically used because the interfaces defined by the IEEE 802.3 Working Group were not considered “Ethernet” per se, but “Ethernet-like,” because “Ethernet” was taken to mean “Ethernet version 2” according to the (DEC, Intel, Xerox) DIX “blue book.” Today and in the context of SNMP management and SMIv2 MIB modules, “Ethernet,” “Ethernet-like,” and “IEEE 802.3” are synonymous and interchangeable in the marketplace. The term “Ethernet-like” is retained in this document because of its common usage in the SNMP-based network management community.

1.1 Scope

This standard contains the Management Information Base (MIB) module specifications for IEEE Std 802.3, also known as Ethernet. It includes the Structure of Management Information Version 2 (SMIv2) MIB module specifications formerly produced and published by the Internet Engineering Task Force (IETF), and the managed object branch and leaf assignments provided in the Guidelines for the Definition of Managed Objects (GDMO) MIB modules formerly specified within IEEE Std 802.3, as well as extensions resulting from recent amendments to IEEE Std 802.3. The SMIv2 MIB modules are intended for use with the Simple Network Management Protocol (SNMP), commonly used to manage Ethernet.

1.2 Purpose

The purpose of the standard is to publish the SMIv2 MIB module specifications in a single document that is separate from IEEE Std 802.3, and that can be published in a machine-readable format. Future amendments and revisions to IEEE Std 802.3.1 will be performed to update the MIB specifications as required to track future amendments and revisions to IEEE Std 802.3.

1.3 Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of IETF RFC 3410.

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the SNMP.

Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This standard specifies MIB modules that are compliant to the SMIv2, which is described in IETF STD 58 (RFC 2578), IETF STD 58 (RFC 2579), and IETF STD 58 (RFC 2580).

1.4 Security considerations

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in a MIB module.

Implementers should consider the security features as provided by the SNMPv3 framework (see section 8 of IETF RFC 3410), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

SNMPv3 should be deployed, rather than previous versions of SNMP, and cryptographic security should be enabled. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

Throughout this standard, there are a number of accessible management objects that may be considered sensitive or vulnerable in some network environments. The support for some operations in a non-secure environment without proper protection can have a negative effect on network operations. Such management objects are detailed in the clauses that define them.

The user of these MIB modules should therefore be aware that support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

The readable objects in these MIB modules (i.e., those with MAX-ACCESS other than not-accessible) may be considered sensitive in some environments since, collectively, they provide information about the performance of network interfaces and can reveal some aspects of their configuration. In such environments, it is important to control GET and NOTIFY access to these objects and possibly encrypt their values when sending them over the network via SNMP.

1.5 Conformance

Specific conformance statements and compliance statements, written in accordance with IETF STD 58, RFC 2580, are included in each MIB module. They can be found by searching for the text strings “Conformance statements” and “Compliance statements.”

2. Normative references

The following referenced documents are indispensable for the application of this document (i.e., they must be understood and used, so each referenced document is cited in text and its relationship to this document is explained). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments or corrigenda) applies.

ANSI T1.231-1997, Layer 1 In-Service Digital Transmission Performance Monitoring.[3]

ANSI T1.424-2004, Interface Between Networks and Customer Installation—Very-high-bit-rate Digital Subscriber Lines (VDSL) Metallic Interface (DMT Based).

ETSI TS1 101 270-1~~,~~ (1999), Transmission and Multiplexing (TM); Access transmission systems on metallic access cables; Very high speed Digital Subscriber Line (VDSL); Part 1: Functional requirements.[4]

IEEE Std 802®, IEEE Standard for Local and Metropolitan Area Networks—Architecture and Overview.[5, 6]

Editor's Note (to be removed prior to publication):
Reference to IEEE Std 802.1D was replaced with IEEE Std 802.1Q per Maintenance Request 1383 (see https://www.ieee802.org/3/maint/requests/maint_1383.pdf)

IEEE Std 802.1Q™, Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks.

IEEE Std 802.1AB™-2009, IEEE Standard for Local and Metropolitan Area Networks—Station and Media Access Control Discovery.

IEEE Std 802.3™, IEEE Standard for Ethernet.

IEEE Std 802.9a™-1995, IEEE Standards for Local and Metropolitan Area Networks~~: –~~—Supplement to Integrated Services (IS) LAN Interface at the Medium Access Control (MAC) and Physical (PHY) Layers—~~:~~ Specification of IsLAN16-T.

IETF RFC 1213, Management Information Base for Network Management of TCP/IP-based internets: MIB-II, McCloghrie, K., and ~~M.~~ Rose, M., Mar~~ch~~. 1991.[7]

IETF RFC 1516, Definitions of Managed Objects for IEEE 802.3 Repeater Devices, McMaster, D., and ~~K.~~ McCloghrie, K., Sept~~ember~~. 1993.

IETF RFC 2119, Keywords for use in RFCs to Indicate Requirement Levels, Bradner, S., Mar~~ch~~. 1997.

IETF RFC 2434, Guidelines for Writing an IANA Considerations Section in RFCs, Narten, T. and ~~H.~~ Alvestrand, H., Oct~~ober~~, 1998.

---

[3]~~ANSI publications are available from the Sales Department, American National Standards Institute, 25 West 43rd Street, 4th Floor, New York, NY 10036, USA (http://www.ansi.org/).~~ANSI publications are available from the American National Standards Institute (http://www.ansi.org/).

[4]~~ETSI standards are available from the European Telecommunications Standards Institute at 650, Route des Lucioles, 06921 Sophia-Antipolis Cedex, France (http://www.etsi.org/)~~ETSI publications are available from the European Telecommunications Standards Institute (http://www.etsi.org/).

[5]~~IEEE publications are available from the Institute of Electrical and Electronics Engineers, Inc., 445 Hoes Lane, Piscataway, NJ 08854, USA (http://standards.ieee.org/).~~IEEE publications are available from The Institute of Electrical and Electronics Engineers (http://standards.ieee.org/).

[6]The IEEE standards or products referred to in this clause are trademarks of T~~t~~he Institute of Electrical and Electronics Engineers, Inc.

[7]~~IETF RFCs are available from the Internet Engineering Task Force website at http://www.ietf.org/rfc.html.~~IETF documents (i.e., RFCs) are available for download at http://www.rfc-archive.org/.

IETF STD 58 (RFC 2578), Structure of Management Information Version 2 (SMIv2), McCloghrie, K., ~~D.,~~ Perkins, D., and ~~J.~~ Schoenwaelder, J., Apr.~~il~~ 1999.

IETF STD 58 (RFC 2579), Textual Conventions for SMIv2, McCloghrie, K., ~~D.~~ Perkins, D., and ~~J.~~ Schoenwaelder, J., Apr.~~il~~ 1999.

IETF STD 58 (RFC 2580), Conformance Statements for SMIv2, McCloghrie, K., Perkins, D., and ~~J.~~ Schoenwaelder, J., Apr.~~il~~ 1999.

IETF RFC 2856, Textual Conventions for Additional High Capacity Data Types, Bierman, A., McCloghrie, K., and ~~R.~~ Presuhn, -R., June 2000.

IETF RFC 2863, -The Interfaces Group MIB, McCloghrie, K., and ~~F.~~ Kastenholz, F., June 2000.

IETF RFC 2864, The Inverted Stack Table Extension to the Interfaces Group MIB, McCloghrie, K., and ~~G.~~ Hanson, G., June 2000.

IETF RFC 3410, Introduction and Applicability Statements for Internet Standard Management Framework, Case, J., Mundy R., Partain, D., and ~~B.~~ Stewart, B., Dec.~~ember~~ 2002.

IETF RFC 3411, An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks, Harrington, D., Presuhn, R., and ~~B.~~ Wijnen, B., Dec~~ember~~. 2002.

IETF RFC 3592, Definitions of Managed Objects for the Synchronous Optical Network/Synchronous Digital Hierarchy (SONET/SDH) Interface Type, Tesink, K., Sept~~ember~~. 2003.

ITU-T Recommendation G.983.1, 1998—Optical line systems for local and access networks—Broadband optical access systems based on Passive Optical Networks (PON).[8]

ITU-T Recommendation G.991.2, 2003—Single-pair High-speed Digital Subscriber Line (SHDSL) transceivers.

ITU-T Recommendation G.993.1, 2004—Very high speed digital subscriber line transceivers.

[8]~~ITU-T publications are available from the International Telecommunications Union, Place des Nations, CH-1211, Geneva 20, Switzerland/Suisse (http://www.itu.int/)~~ITU-T publications are available from the International Telecommunications Union (http://www.itu.int/).

3. Definitions

For the purposes of this document, the following terms and definitions apply. *The IEEE Standards Dictionary Online* should be consulted for terms not defined in this clause.[9]

agent: An entity, typically implemented in software, which provides remote access to management instrumentation, via the Simple Network Management Protocol (SNMP).

group: Within the context of the repeater management ~~MIB~~Management Information Base (MIB) module defined in Clause 7 of IEEE Std 802.3.1-2013: A recommended, but optional, entity defined in Clause 30 of IEEE Std 802.3, ~~Clause 30,~~ in order to support a modular numbering scheme. The classic~~al~~ example allows an implementor to represent field-replaceable units as groups of ports, with the port numbering matching the modular hardware implementation.

jack type: The jack connector type, as it appears on the outside of the system. The type of mechanical interface to the transmission medium.

Loss of Codegroup Delineation: *See* 50.3.5.3 of IEEE Std 802.3~~ 50.3.5.3~~.

managed object: ~~a~~An abstract representation of network resources that are managed. A managed object is defined according to the *Structure of Management Information version 2* (SMIv2) defined in IETF STD 58, RFC 2578.

managed repeater: A repeater as defined by IEEE Std 802.3 incorporating a management entity that complies with the ~~MIB~~Management Information Base (MIB) module definition contained in Clause 7 of ~~this document~~IEEE Std 802.3.1-2013.

module: A building block in a modular system. In the context of the MIB definitions, a specification of management capabilities related to the system. In the context of a chassis, it typically maps into one “~~"~~slot”~~"~~; however, the range of configurations may be very large, with several modules entering one slot, or one module covering several slots.

non-trivial repeater: A repeater as defined by IEEE Std 802.3 having multiple ports.

Path Coding violations: In IEEE Std 802.3, the path layer coding violations count is based on block errors and not on BIP-8 errors;~~,~~ i.e., it is incremented only once for each B3 byte that indicates incorrect parity, regardless of the number of bits in error. Note that Section 8.4.5.1 of ANSI T1.231-1997 allows either path BIP-8 errors or path block errors to be used for the path layer error count.

repeater system: A managed entity compliant with this standard~~,~~ and incorporating at least one managed IEEE ~~Std~~ 802.3 repeater.

repeater-unit: The portion of a repeater that is inboard of its Physical Medium Attachment (PMA)/Physical Signaling Sublayer (PLS)~~,~~ or PMA/Physical Coding Sublayer (PCS).

Signal Label Mismatch: This defect is called Payload Label Mismatch (PLM) in IEEE Std 802.3. It is reported by setting both the sonetPathSignalLabelMismatch bit in the appropriate instance of sonetPathCurrentStatus (defined in IETF RFC 3592) and the etherWisPathPLM bit in the corresponding instance of etherWisPathCurrentStatus.

stack: A scalable system in which modularity is achieved by interconnecting a number of different systems.

[9] *The IEEE Standards Dictionary Online* subscription is available at http://www.ieee.org/portal/innovate/products/standard/standards_-dictionary.html.

STS-Path Remote Defect Indication: IEEE Std 802.3 mandates the use of ERDI-P (Enhanced Remote Defect Indication-Path) defined in ANSI T1.231-1997 to signal remote server defects (triggered by path AIS or path LOP) and remote payload defects (triggered by Payload Label Mismatch or Loss of Codegroup Delineation). IETF RFC 3592 defines the one-bit RDI-P (Remote Defect Indication-Path), which s~~ s~~ignals remote server detects (i.e., path AIS and path LOP) only. An implementation of the MIB module defined in ~~Clause 12~~Clause 12 of IEEE Std 802.3.1-2013 sets the sonetPathSTSRDI bit in the appropriate instance of sonetPathCurrentStatus when it receives an ERDI-P server defect indication from the remote end. Both ERDI-P payload defects and ERDI-P server defects are reported in the object etherWisFarEndPathCurrentStatus.

system: An entity compliant with one or more ~~MIB~~Management Information Base (MIB) modules of this standard.

system interconnect segment: An internal segment allowing interconnection of ports belonging to different physical entities into the same logical managed repeater, bridge, or other system. Examples of implementation might be backplane busses in modular hubs, or chaining cables in stacks of bridges/switches. It is not uncommon for such segments to be a proprietary implementation.

trivial repeater-unit: An isolated port that can gather statistics.

4. Abbreviations

ACK	acknowledge
AIS	Alarm Indication Signal
ARP	address resolution protocol
ASCII	American Standard Code for Information Interchange
Atn	attenuation
BER	bit error ratio
BIP	bit interleaved parity
BW	bandwidth
CO	central office
CPE	customer premises equipment
CRC	cyclic redundancy check
DTE	data terminal equipment
EFM	Ethernet in the First Mile
EFMCu	EFM copper
ELTE	Ethernet line termination equipment
EPON	Ethernet passive optical network
ERDI-P	enhanced remote defect indication—path
FCS	frame check sequence
FEC	forward error correction
GDMO	Guidelines for Definition of Managed Objects
GMII	gigabit media independent interface
IANA	Internet Assigned Numbers Authority
IETF	Internet Engineering Task Force
IFG	inter-frame gap
ITU	International Telecommunication Union
LAN	local area network
LCD	Loss of Codegroup Deliniation
LLC	logical link control
LLDP	logical link discovery protocol
LLDPDU	logical link discovery protocol data unit
LLID	logical link identifier
LOP	Loss of Pointer
LTE	line termination equipment
MAC	media access control
MAU	medium attachment unit
Mb/s	megabit per second
MDI	medium dependent interface
MDIO	management data input/output
MII	media independent interface
MP2PE	multipoint-to-point emulation
MPCP	multipoint control protocol
MPCPDU	multipoint control protocol data unit
MTU	maximum transmission unit
NMS	network management system

OAM	operations, administration, and maintenance
OAMPDU	operations, administration, and maintenance protocol data unit
OID	object identifier
OLT	optical line terminal
OMP	optical multipoint
ONU	optical network unit
OSI	Open Systems Interconnection
P2MP	point-to-multipoint
P2PE	point-to-point emulation
PAF	PME aggregation function
PBO	power back-off
PCS	physical coding sublayer
PD	powered device
PDU	protocol data unit
PHY	Physical Layer entity
PLM	Payload Label Mismatch
PMA	physical medium attachment
PMD	physical medium dependent
PME	physical medium entity
PON	passive optical network
PSD	power spectral density
PSE	power sourcing equipment
RFC	Request for Comments
ROM	read-only-memory
RS	reconciliation sublayer
RTT	round-trip time
SDH	Synchronous Digital Hierarchy
SLA	service level agreement
SLD	start of LLID delimiter
SMIv2	structure of management information version 2
SNMP	simple network management protocol
SNR	signal-to-noise ratio
SONET	Synchronous Optical Network
TCPAM	trellis coded pulse amplitude modulation
TDM	time division multiplexing
TDMA	time division multiple access
TLV	type/length/value
TQ	time quanta
WAN	wide area network
WDM	wavelength division multiplexing
WIS	WAN interface sublayer

5. Ethernet logical link discovery protocol (LLDP) extension MIB module

The logical link discovery protocol (LLDP) is defined in IEEE Std 802.1AB-2009, Station and Media Access Control Discovery. Extensions to this protocol for Ethernet are defined in Clause 79 of IEEE Std 802.3.

5.1 Structure of the IEEE 802.3 LLDP extension MIB

Table 5-1 summarizes the particular object groups that are required for each operating mode. The implemented MIB shall comply with the MIB conformance section for the particular operating mode being supported.

Table 5-1—IEEE 802.3 LLDP extension MIB object group conformance requirements

MIB group	Rx mode	Tx mode	Tx/Rx mode
lldpV2Xdot3ConfigGroup	M[a]	M	M
lldpV2Xdot1LocSysGroup	M	—	M
lldpV2Xdot1RemSysGroup	—	M	M
ifGeneralInformationGroup	M	M	M

[a]M = Mandatory.

Table 5-2 shows the structure of the MIB and the relationship of the MIB objects to the LLDP operational status/control variables, LLDP statistics variables, and TLV variables.

5.2 Relationship to other MIBs

Version 1 of the IEEE 802.3 LLDP extension MIB module is deprecated.

Table 5-2—IEEE 802.3/LLDP extension MIB cross reference

MIB table	MIB object	LLDP reference
Configuration group		
lldpV2Xdot3PortConfigTable		Augments lldpV2PortConfigEntry
	lldpV2Xdot3PortConfigTLVsTxEnable	Normal LLDPDUs
Local devices information group		
lldpV2Xdot3LocPortTable		
	lldpV2LocPortIfIndex	(Table index)
	lldpV2Xdot3LocPortAutoNegSupported	Auto-Negotiation support/status
	lldpV2Xdot3LocPortAutoNegEnabled	Auto-Negotiation support/status
	lldpV2Xdot3LocPortAutoNegAdvertisedCap	Auto-Negotiation advertised
	lldpV2Xdot3LocPortOperMauType	Operational MAU type
lldpV2Xdot3LocPowerTable		
	lldpV2LocPortIfIndex	(Table index)
	lldpV2Xdot3LocPowerPortClass	MDI power support
	lldpV2Xdot3LocPowerMDISupported	MDI power support
	lldpV2Xdot3LocPowerMDIEnabled	MDI power support
	lldpV2Xdot3LocPowerPairControlable	MDI power support
	lldpV2Xdot3LocPowerPairs	PSE power pair
	lldpV2Xdot3LocPowerClass	Power class
lldpV2Xdot3LocMaxFrameSizeTable		
	lldpV2LocPortIfIndex	(Table index)
	lldpV2Xdot3LocMaxFrameSize	Maximum frame size
Remote devices information group		
lldpV2Xdot3RemPortTable		
	lldpV2RemTimeMark	(Table index)
	lldpV2RemLocalIfIndex	(Table index)
	lldpV2RemLocalDestMACAddress	(Table index)
	lldpV2RemIndex	(Table index)
	lldpV2Xdot3RemPortAutoNegSupported	Auto-Negotiation support/status
	lldpV2Xdot3RemPortAutoNegEnabled	Auto-Negotiation support/status
	lldpV2Xdot3RemPortAutoNegAdvertisedCap	Auto-Negotiation advertised
	lldpV2Xdot3RemPortOperMauType	Operational MAU type

Table 5-2—IEEE 802.3/LLDP extension MIB cross reference *(continued)*

MIB table	MIB object	LLDP reference
lldpV2Xdot3RemPowerTable		
	lldpV2RemTimeMark	(Table index)
	lldpV2RemLocalIfIndex	(Table index)
	lldpV2RemLocalDestMACAddress	(Table index)
	lldpV2RemIndex	(Table index)
	lldpV2Xdot3RemPowerPortClass	MDI power support
	lldpV2Xdot3RemPowerMDISupported	MDI power support
	lldpV2Xdot3RemPowerMDIEnabled	MDI power support
	lldpV2Xdot3RemPowerPairControlable	MDI power support
	lldpV2Xdot3RemPowerPairs	PSE power pair
	lldpV2Xdot3RemPowerClass	Power class
lldpV2Xdot3RemMaxFrameSizeTable		
	lldpV2RemTimeMark	(Table index)
	lldpV2RemLocalIfIndex	(Table index)
	lldpV2RemLocalDestMACAddress	(Table index)
	lldpV2RemIndex	(Table index)
	lldpV2Xdot3RemMaxFrameSize	Maximum frame size

5.3 Security considerations for IEEE 802.3 LLDP extension MIB module

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write.[10] Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

Setting the object, lldpXdot3PortConfigTLVsTxEnable, to incorrect values can result in improper operation of LLDP.

The following readable objects in this MIB module may be considered to be sensitive or vulnerable in some network environments:

a) Objects that are associated with the transmit mode are as follows:
   1) lldpV2Xdot3LocPortAutoNegSupported
   2) lldpV2Xdot3LocPortAutoNegEnabled
   3) lldpV2Xdot3LocPortAutoNegAdvertisedCap
   4) lldpV2Xdot3LocPortOperMauType
   5) lldpV2Xdot3LocPowerPortClass
   6) lldpV2Xdot3LocPowerMDISupported
   7) lldpV2Xdot3LocPowerMDIEnabled
   8) lldpV2Xdot3LocPowerPairControlable
   9) lldpV2Xdot3LocPowerPairs
   10) lldpV2Xdot3LocPowerClass
   11) lldpV2Xdot3LocMaxFrameSize
b) Objects that are associated with the receive mode are as follows:
   1) lldpV2Xdot3RemPortAutoNegSupported
   2) lldpV2Xdot3RemPortAutoNegEnabled
   3) lldpV2Xdot3RemPortAutoNegAdvertisedCap
   4) lldpV2Xdot3RemPortOperMauType
   5) lldpV2Xdot3RemPowerPortClass
   6) lldpV2Xdot3RemPowerMDISupported
   7) lldpV2Xdot3RemPowerMDIEnabled
   8) lldpV2Xdot3RemPowerPairControlable
   9) lldpV2Xdot3RemPowerPairs
   10) lldpV2Xdot3RemPowerClass
   11) lldpV2Xdot3RemMaxFrameSize

This concern applies both objects that describe the configuration of the local host, as well as objects that describe information from the remote hosts, acquired via LLDP and displayed by the objects in this MIB module. It is thus also important to control GET and/or NOTIFY access to these objects and possibly to encrypt the values of these objects when sending them over the network via SNMP.

[10]In IETF MIB definitions, the MAX-ACCESS clause defines the type of access that is allowed for particular data elements in the MIB. An explanation of the MAX-ACCESS mapping is given in section 7.3 of IETF STD 58, RFC 2578.

5.4 MIB module definition

In the following MIB definition, should any discrepancy between the DESCRIPTION text and the corresponding definition in 5.2 through 5.3 of this clause occur, the definitions in 5.2 through 5.3 shall take precedence.

An ASCII text version of the MIB definition can be found at the following URL[11]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C5mib.txt

Two additional modules must be imported when compiling the IEEE 802.3 LLDP extension MIB module, and they can be found at the following URLs:

http://www.ieee802.org/1/files/public/MIBs/LLDP-V2-MIB-200906080000Z.txt

http://www.ieee802.org/1/files/public/MIBs/LLDP-V2-TC-MIB-200906080000Z.txt

[11]Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.

```
IEEE8023-DOT3-LLDP-EXT-V2-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Unsigned32,
    Integer32,
    org
        FROM SNMPv2-SMI
    TruthValue
        FROM SNMPv2-TC
    MODULE-COMPLIANCE,
    OBJECT-GROUP
        FROM SNMPv2-CONF
    ifGeneralInformationGroup
        FROM IF-MIB
    lldpV2LocPortIfIndex,
    lldpV2RemLocalIfIndex,
    lldpV2RemTimeMark,
    lldpV2RemLocalDestMACAddress,
    lldpV2RemIndex,
    lldpV2PortConfigEntry
        FROM LLDP-V2-MIB
 -- http://www.ieee802.org/1/files/public/MIBs/LLDP-V2-MIB-200906080000Z.txt
    LldpV2PowerPortClass
        FROM LLDP-V2-TC-MIB
 -- http://www.ieee802.org/1/files/public/MIBs/LLDP-V2-TC-MIB-200906080000Z.txt
;

ieee8023lldpV2Xdot3MIB MODULE-IDENTITY
    LAST-UPDATED "201304110000Z" -- April 11, 2013
    ORGANIZATION "IEEE 802.3 Working Group"
    CONTACT-INFO
            "WG-URL: http://www.ieee802.org/3/index.html
            WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

            Contact: Howard Frazier
            Postal:  3151 Zanker Road
                     San Jose, CA 95134
                     USA
            Tel:     +1.408.922.8164
            E-mail:  hfrazier@broadcom.com"
    DESCRIPTION
            "The LLDP Management Information Base extension module for
            IEEE 802.3 organizationally defined discovery information."

       REVISION    "201304110000Z" -- April 11, 2013
       DESCRIPTION
           "Revision, based on an earlier version in IEEE Std 802.3.1-2011."


       REVISION "201102020000Z" -- February 2, 2011
       DESCRIPTION
            "This revision incorporated changes to the MIB module to
            add objects to support management of Energy Efficient
            Ethernet (EEE) and Enhanced DTE Power via the MDI (PoE+)."
```

```
   ::= { org ieee(111)
         standards-association-numbers-series-standards(2)
         lan-man-stds(802)ieee802dot3(3) ieee802dot3dot1mibs(1) 5 }

------------------------------------------------------------------------------
------------------------------------------------------------------------------
--
-- Organizationally Defined Information Extension - IEEE 802.3
--
------------------------------------------------------------------------------
------------------------------------------------------------------------------

lldpV2Xdot3Objects    OBJECT IDENTIFIER ::= { ieee8023lldpV2Xdot3MIB 1 }

-- LLDP IEEE 802.3 extension MIB groups
lldpV2Xdot3Config     OBJECT IDENTIFIER ::= { lldpV2Xdot3Objects 1 }
lldpV2Xdot3LocalData  OBJECT IDENTIFIER ::= { lldpV2Xdot3Objects 2 }
lldpV2Xdot3RemoteData OBJECT IDENTIFIER ::= { lldpV2Xdot3Objects 3 }



------------------------------------------------------------------------------
-- IEEE 802.3 - Configuration
------------------------------------------------------------------------------



--
-- Version 2 of lldpV2Xdot3PortConfigTable
-- supports use of multiple destination MAC addresses
--


lldpV2Xdot3PortConfigTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3PortConfigEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "A table that controls selection of LLDP TLVs to be transmitted
            on individual ports."
    ::= { lldpV2Xdot3Config 1 }

lldpV2Xdot3PortConfigEntry  OBJECT-TYPE
    SYNTAX      LldpV2Xdot3PortConfigEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "LLDP configuration information that controls the
            transmission of IEEE 802.3 organizationally defined TLVs on
            LLDP transmission capable ports.

            This configuration object augments the lldpV2PortConfigEntry of
            the LLDP-MIB, therefore it is only present along with the port
            configuration defined by the associated lldpV2PortConfigEntry
            entry.

            Each active lldpV2Xdot3PortConfigEntry is restored from non-volatile
            storage (along with the corresponding lldpV2PortConfigEntry)
            after a re-initialization of the management system."
    AUGMENTS { lldpV2PortConfigEntry }
```

```
    ::= { lldpV2Xdot3PortConfigTable 1 }

LldpV2Xdot3PortConfigEntry ::= SEQUENCE {
      lldpV2Xdot3PortConfigTLVsTxEnable  BITS
}

lldpV2Xdot3PortConfigTLVsTxEnable  OBJECT-TYPE
    SYNTAX      BITS {
            macPhyConfigStatus(0),
            powerViaMDI(1),
            unused(2), --avoids re-use of the old link agg bit number
            maxFrameSize(3)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
            "The lldpV2Xdot3PortConfigTLVsTxEnable, defined as a bitmap,
            includes the IEEE 802.3 organizationally defined set of LLDP
            TLVs whose transmission is allowed by the local LLDP agent by
            the network management. Each bit in the bitmap corresponds
            to an IEEE 802.3 subtype associated with a specific IEEE
            802.3 optional TLV.

            The bit 'macPhyConfigStatus(0)' indicates that the LLDP agent
            should transmit 'MAC/PHY configuration/status TLV'.

            The bit 'powerViaMDI(1)' indicates that the LLDP agent should
            transmit 'Power via MDI TLV'.

            The bit 'unused(2)' is no longer used; this was used for
            the 'Link Aggregation TLV' in the previous version.

            The bit 'maxFrameSize(3)' indicates that the LLDP agent should
            transmit 'Maximum-frame-size TLV'.

            The default value for lldpV2Xdot3PortConfigTLVsTxEnable object
            is an empty set, which means no enumerated values are set.

            The value of this object is restored from non-volatile
            storage after a re-initialization of the management system."
    REFERENCE
            "IEEE Std 802.3 30.12.1.1.1"
    DEFVAL  { { } }
    ::= { lldpV2Xdot3PortConfigEntry  1 }



------------------------------------------------------------------------------
-- IEEE 802.3 - Local Device Information
------------------------------------------------------------------------------

---
--- lldpV2Xdot3LocPortTable: Ethernet Port AutoNeg/Speed/Duplex
---                        Information Table
--- V2 modified to be indexed by ifIndex.
---

lldpV2Xdot3LocPortTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3LocPortEntry
```

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "This table contains one row per port of Ethernet port
            information (as a part of the LLDP 802.3 organizational
            extension) on the local system known to this agent."
    ::= { lldpV2Xdot3LocalData 1 }

lldpV2Xdot3LocPortEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3LocPortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "Information about a particular port component."
    INDEX   { lldpV2LocPortIfIndex }
    ::= { lldpV2Xdot3LocPortTable 1 }

LldpV2Xdot3LocPortEntry ::= SEQUENCE {
         lldpV2Xdot3LocPortAutoNegSupported     TruthValue,
         lldpV2Xdot3LocPortAutoNegEnabled       TruthValue,
         lldpV2Xdot3LocPortAutoNegAdvertisedCap OCTET STRING,
         lldpV2Xdot3LocPortOperMauType          Unsigned32
}

lldpV2Xdot3LocPortAutoNegSupported OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to indicate whether the given port
            (associated with the local system) supports Auto-negotiation."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.1"
    ::= { lldpV2Xdot3LocPortEntry 1 }

lldpV2Xdot3LocPortAutoNegEnabled  OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to indicate whether port
            Auto-negotiation is enabled on the given port associated
            with the local system."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.2"
    ::= { lldpV2Xdot3LocPortEntry 2 }

lldpV2Xdot3LocPortAutoNegAdvertisedCap OBJECT-TYPE
    SYNTAX      OCTET STRING(SIZE(2))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "This object contains the value (bitmap) of the
            ifMauAutoNegCapAdvertisedBits object (defined in IETF RFC
            3636) which is associated with the given port on the
            local system."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.3"
    ::= { lldpV2Xdot3LocPortEntry 3 }
```

```
lldpV2Xdot3LocPortOperMauType  OBJECT-TYPE
    SYNTAX      Unsigned32(0..2147483647)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "An integer value that indicates the operational MAU type
            of the given port on the local system.

            This object contains the integer value derived from the
            list position of the corresponding dot3MauType as listed
            in Clause 13 and is equal to the last number in the
            respective dot3MauType OID.

            For example, if the ifMauType object is dot3MauType1000BaseTHD
            which corresponds to {dot3MauType 29}, the numerical value of
            this field is 29. For MAU types not listed in Clause 13,
            the value of this field shall be set to zero."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.4"
    ::= { lldpV2Xdot3LocPortEntry 4 }



---
---
--- lldpV2Xdot3LocPowerTable: Power Ethernet Information Table
--- V2 modified to be indexed by ifIndex.
---
---

lldpV2Xdot3LocPowerTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3LocPowerEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "This table contains one row per port of power Ethernet
            information (as a part of the LLDP IEEE 802.3 organizational
            extension) on the local system known to this agent."
    ::= { lldpV2Xdot3LocalData 2 }

lldpV2Xdot3LocPowerEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3LocPowerEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "Information about a particular port component."
    INDEX   { lldpV2LocPortIfIndex }
    ::= { lldpV2Xdot3LocPowerTable 1 }

LldpV2Xdot3LocPowerEntry ::= SEQUENCE {
         lldpV2Xdot3LocPowerPortClass           LldpV2PowerPortClass,
         lldpV2Xdot3LocPowerMDISupported        TruthValue,
         lldpV2Xdot3LocPowerMDIEnabled          TruthValue,
         lldpV2Xdot3LocPowerPairControlable     TruthValue,
         lldpV2Xdot3LocPowerPairs               Unsigned32,
         lldpV2Xdot3LocPowerClass               Unsigned32,
         lldpV2Xdot3LocPowerType                INTEGER,
         lldpV2Xdot3LocPowerSource              INTEGER,
```

```
        lldpV2Xdot3LocPowerPriority            INTEGER,
        lldpV2Xdot3LocPDRequestedPowerValue    Integer32,
        lldpV2Xdot3LocPSEAllocatedPowerValue   Integer32,
        lldpV2Xdot3LocResponseTime             Integer32,
        lldpV2Xdot3LocReady                    TruthValue,
        lldpV2Xdot3LocReducedOperationPowerValue  Integer32
}


lldpV2Xdot3LocPowerPortClass  OBJECT-TYPE
    SYNTAX      LldpV2PowerPortClass
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The value that identifies the port Class of the given port
            associated with the local system."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.5"
    ::= { lldpV2Xdot3LocPowerEntry 1 }

lldpV2Xdot3LocPowerMDISupported  OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to indicate whether the MDI power is
            supported on the given port associated with the local system."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.6"
    ::= { lldpV2Xdot3LocPowerEntry 2 }

lldpV2Xdot3LocPowerMDIEnabled  OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to identify whether MDI power is
            enabled on the given port associated with the local system."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.7"
    ::= { lldpV2Xdot3LocPowerEntry 3 }

lldpV2Xdot3LocPowerPairControlable  OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value is derived from the value of
            pethPsePortPowerPairsControlAbility object (defined in
            Clause 8) and is used to indicate whether the pair selection
            can be controlled on the given port associated with the
            local system."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.8"
    ::= { lldpV2Xdot3LocPowerEntry 4 }

lldpV2Xdot3LocPowerPairs  OBJECT-TYPE
    SYNTAX      Unsigned32(1|2)
    MAX-ACCESS  read-only
```

```
    STATUS      current
    DESCRIPTION
            "This object contains the value of the pethPsePortPowerPairs
            object (defined in Clause 8) which is associated with
            the given port on the local system."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.9"
    ::= { lldpV2Xdot3LocPowerEntry 5 }

lldpV2Xdot3LocPowerClass  OBJECT-TYPE
    SYNTAX      Unsigned32(1|2|3|4|5)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "This object contains the value of the
            pethPsePortPowerClassifications object (defined in
            Clause 8) which is associated with the given port on the
            local system."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.10"
    ::= { lldpV2Xdot3LocPowerEntry 6 }

lldpV2Xdot3LocPowerType  OBJECT-TYPE
    SYNTAX      INTEGER {
                    psetype1(0),
                    psetype2(1),
                    pdtype(2),
                    pdtype2(3)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns an integer indicating whether the local
             system is a PSE or a PD and whether it is Type 1 or Type 2."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.14"
    ::= { lldpV2Xdot3LocPowerEntry 7 }

lldpV2Xdot3LocPowerSource  OBJECT-TYPE
    SYNTAX      INTEGER {
                    pseprimary(0),
                    psebackup(1),
                    pseunknown(2),
                    pdpseandlocal(3),
                    pdpseonly(4),
                    pdunknown(5)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns an integer indicating the power sources of the
            local system. A PSE indicates whether it is being powered by
            a primary power source; a backup power source; or unknown. A PD
            indicates whether it is being powered by a PSE and locally;
            by a PSE only; or unknown."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.15"
    ::= { lldpV2Xdot3LocPowerEntry 8 }
```

```
lldpV2Xdot3LocPowerPriority  OBJECT-TYPE
    SYNTAX      INTEGER {
                    low(0),
                    high(1),
                    critical(2),
                    unknown(3)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
            "A GET returns the priority of a PD system. For a PSE, this
            is the priority that the PSE assigns to the PD. For a PD, this
            is the priority that the PD requests from the PSE. A SET
            operation changes the priority of the PD system to the indicated
            value."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.16"
    ::= { lldpV2Xdot3LocPowerEntry 9 }

lldpV2Xdot3LocPDRequestedPowerValue  OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the PD requested power value.
            For a PD, it is the power value that the PD has currently
            requested from the remote system. PD requested power value
            is the maximum input average power the PD ever draws under
            this power allocation if accepted. For a PSE, it is the power
            value that the PSE mirrors back to the remote system. This is
            the PD requested power value that was used by the PSE to compute
            the power it has currently allocated to the remote system.
            The PD requested power value is encoded according to
            IEEE Std 802.3 Equation (79–1), where X is the decimal value of
            aLldpXdot3LocPDRequestedPowerValue."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.17"
    ::= { lldpV2Xdot3LocPowerEntry 10 }

lldpV2Xdot3LocPSEAllocatedPowerValue  OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the PSE allocated power value.
            For a PSE, it is the power value that the PSE has currently
            allocated to the remote system. The PSE allocated power value
            is the maximum input average power that the PSE wants the PD
            to ever draw under this allocation if it is accepted. For a PD,
            it is the power value that the PD mirrors back to the remote
            system. This is the PSE allocated power value that was used by
            the PD to compute the power that it has currently requested from
            the remote system. The PSE allocated power value is encoded
            according to IEEE Std 802.3 Equation (79–2), where X is the
            decimal value of aLldpXdot3LocPSEAllocatedPowerValue."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.18"
    ::= { lldpV2Xdot3LocPowerEntry 11 }
```

```
lldpV2Xdot3LocResponseTime  OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the response time in seconds of the local system.
            For a PD, it is the maximum time required to update the value of
            lldpV2Xdot3LocPDRequestedPowerValue when the remote system
            requests the PD to change its max power draw. For a PSE, it is
            the maximum time required to update the value of
            lldpV2Xdot3LocPDRequestedPowerValue when the remote system
            requests of the PSE a new power value."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.19"
    ::= { lldpV2Xdot3LocPowerEntry 12 }

lldpV2Xdot3LocReady  OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to identify whether the local Data Link Layer
            classification engine has completed initialization and is ready to
            receive and transmit LLDPDUs."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.20"
    ::= { lldpV2Xdot3LocPowerEntry 13 }

lldpV2Xdot3LocReducedOperationPowerValue  OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the reduced operation power value. For a PD, it
            is a power value that is lower than the currently requested
            power value. This reduced operation power value represents a
            power state in which the PD could continue to operate, but with
            less functionality than at the current PD requested power value.
            The PSE could optionally use this information in the event that
            the PSE subsequently requests a lower PD power value than the
            PD requested power value. For a PSE, it is a power value that the
            PSE could ask the PD to move to if the PSE wants the PD to move
            to a lower power state. The definition and encoding of PD
            requested power value is the same as described in
            lldpV2Xdot3LocPDRequestedPowerValue. The default value for this
            field is the hexadecimal value FFFF"
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.21"
    ::= { lldpV2Xdot3LocPowerEntry 14 }

---
---
--- lldpV2Xdot3LocMaxFrameSizeTable: Maximum Frame Size information
--- V2 modified to be indexed by ifIndex.
---
---
lldpV2Xdot3LocMaxFrameSizeTable  OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3LocMaxFrameSizeEntry
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
    DESCRIPTION
            "This table contains one row per port of maximum frame
            size information (as a part of the LLDP IEEE 802.3 organizational
            extension) on the local system known to this agent."
    ::= { lldpV2Xdot3LocalData 3 }

lldpV2Xdot3LocMaxFrameSizeEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3LocMaxFrameSizeEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "Maximum Frame Size information about a particular port
            component."
    INDEX   { lldpV2LocPortIfIndex }
    ::= { lldpV2Xdot3LocMaxFrameSizeTable 1 }

LldpV2Xdot3LocMaxFrameSizeEntry ::= SEQUENCE {
        lldpV2Xdot3LocMaxFrameSize             Unsigned32
}

lldpV2Xdot3LocMaxFrameSize OBJECT-TYPE
    SYNTAX      Unsigned32(0..65535)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "An integer value indicating the maximum supported frame
             size in octets on the given port of the local system."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.13"
    ::= { lldpV2Xdot3LocMaxFrameSizeEntry 1 }

---
---
--- lldpV2Xdot3LocEEETable: Energy Efficient Ethernet Information Table
--- V2 modified to be indexed by ifIndex.
---
---

lldpV2Xdot3LocEEETable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3LocEEEEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "This table contains one row per port of Energy Efficient Ethernet
            information (as a part of the LLDP IEEE 802.3 organizational
            extension) on the local system known to this agent."
    ::= { lldpV2Xdot3LocalData 4 }

lldpV2Xdot3LocEEEEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3LocEEEEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "Information about a particular port component."
    INDEX   { lldpV2LocPortIfIndex }
    ::= { lldpV2Xdot3LocEEETable 1 }

LldpV2Xdot3LocEEEEntry ::= SEQUENCE {
```

```
          lldpV2Xdot3LocTxTwSys                  Integer32,
          lldpV2Xdot3LocTxTwSysEcho              Integer32,
          lldpV2Xdot3LocRxTwSys                  Integer32,
          lldpV2Xdot3LocRxTwSysEcho              Integer32,
          lldpV2Xdot3LocFbTwSys                  Integer32,
          lldpV2Xdot3TxDllReady                  TruthValue,
          lldpV2Xdot3RxDllReady                  TruthValue,
          lldpV2Xdot3LocDllEnabled               TruthValue
}

lldpV2Xdot3LocTxTwSys      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the value of Tw_sys_tx that the local system
            can support in the transmit direction.
            This object maps to the variable LocTxSystemValue as defined
            in IEEE Std 802.3 78.4.2.3."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.22"
    ::= {lldpV2Xdot3LocEEEEntry 1 }

lldpV2Xdot3LocTxTwSysEcho      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the value of Tw_sys_tx that the remote system is
            advertising that it can support in the transmit direction and is
            echoed by the local system under the control of the EEE DLL receiver
            state diagram. This object maps to the variable
            LocTxSystemValueEcho as defined in IEEE Std 802.3 78.4.2.3"
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.23"
    ::= {lldpV2Xdot3LocEEEEntry 2 }

lldpV2Xdot3LocRxTwSys      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the value of Tw_sys_tx that
            the local system is requesting in the receive direction.
            This object maps to the variable LocRxSystemValue as
            defined in IEEE Std 802.3 78.4.2.3."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.24"
    ::= {lldpV2Xdot3LocEEEEntry 3 }

lldpV2Xdot3LocRxTwSysEcho      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the value of Tw_sys_tx that
            the remote system is advertising that it is requesting in the
            receive direction and is echoed by the local system under the
            control of the EEE DLL transmitter state diagram. This object
```

```
            maps to the variable LocRxSystemValueEcho as defined in
            IEEE Std 802.3 78.4.2.3."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.25"
    ::= {lldpV2Xdot3LocEEEEntry 4 }

lldpV2Xdot3LocFbTwSys      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the value of the fallback Tw_sys_tx
            that the local system is advertising to the remote system.
            This object maps to the variable LocFbSystemValue as defined
            in IEEE Std 802.3 78.4.2.3."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.26"
    ::= {lldpV2Xdot3LocEEEEntry 5 }

lldpV2Xdot3TxDllReady      OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to identify whether the local Data Link Layer
            EEE layer management function has completed initialization and
            is ready to receive and transmit LLDPDUs."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.27"
    ::= {lldpV2Xdot3LocEEEEntry 6 }

lldpV2Xdot3RxDllReady      OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to identify whether the local Data Link Layer
            EEE layer management function has completed initialization and
            is ready to receive and transmit LLDPDUs."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.28"
    ::= {lldpV2Xdot3LocEEEEntry 7 }

lldpV2Xdot3LocDllEnabled      OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to identify whether the local system has
            completed auto-negotiation with a link partner that has
            indicated at leat one EEE capability."
    REFERENCE
            "IEEE Std 802.3 30.12.2.1.29"
    ::= {lldpV2Xdot3LocEEEEntry 8 }



------------------------------------------------------------------------------
-- IEEE 802.3 - Remote Devices Information
```

```
-------------------------------------------------------------------------------

---
---
--- lldpV2Xdot3RemPortTable: Ethernet Information Table
--- V2 modified to be indexed by ifIndex and destination MAC address.
---
---

lldpV2Xdot3RemPortTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3RemPortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "This table contains Ethernet port information (as a part
            of the LLDP IEEE 802.3 organizational extension) of the remote
            system."
    ::= { lldpV2Xdot3RemoteData 1 }

lldpV2Xdot3RemPortEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3RemPortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "Information about a particular physical network connection."
    INDEX   { lldpV2RemTimeMark,
              lldpV2RemLocalIfIndex,
              lldpV2RemLocalDestMACAddress,
              lldpV2RemIndex }
    ::= { lldpV2Xdot3RemPortTable 1 }

LldpV2Xdot3RemPortEntry ::= SEQUENCE {
              lldpV2Xdot3RemPortAutoNegSupported     TruthValue,
              lldpV2Xdot3RemPortAutoNegEnabled       TruthValue,
              lldpV2Xdot3RemPortAutoNegAdvertisedCap OCTET STRING,
              lldpV2Xdot3RemPortOperMauType          Unsigned32
}


lldpV2Xdot3RemPortAutoNegSupported OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to indicate whether the given port
            (associated with remote system) supports Auto-negotiation."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.1"
    ::= { lldpV2Xdot3RemPortEntry 1 }

lldpV2Xdot3RemPortAutoNegEnabled  OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to indicate whether port
            Auto-negotiation is enabled on the given port associated
            with the remote system."
    REFERENCE
```

```
            "IEEE Std 802.3 30.12.3.1.2"
    ::= { lldpV2Xdot3RemPortEntry 2 }

lldpV2Xdot3RemPortAutoNegAdvertisedCap  OBJECT-TYPE
    SYNTAX      OCTET STRING(SIZE(2))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "This object contains the value (bitmap) of the
            ifMauAutoNegCapAdvertisedBits object (defined in IETF RFC
            3636) which is associated with the given port on the
            remote system."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.3"
    ::= { lldpV2Xdot3RemPortEntry 3 }

lldpV2Xdot3RemPortOperMauType OBJECT-TYPE
    SYNTAX      Unsigned32(0..2147483647)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "An integer value that indicates the operational MAU type
            of the sending device.

            This object contains the integer value derived from the
            list position of the corresponding dot3MauType as listed in
            in Clause 13 and is equal to the last number in
            the respective dot3MauType OID.

            For example, if the ifMauType object is dot3MauType1000BaseTHD
            which corresponds to {dot3MauType 29}, the numerical value of
            this field is 29. For MAU types not listed in Clause 13,
            the value of this field shall be set to zero."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.4"
    ::= { lldpV2Xdot3RemPortEntry 4 }


---
---
--- lldpV2Xdot3RemPowerTable: Power Ethernet Information Table
--- V2 modified to be indexed by ifIndex and destination MAC address.
---
---

lldpV2Xdot3RemPowerTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3RemPowerEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "This table contains Ethernet power information (as a part
            of the LLDP IEEE 802.3 organizational extension) of the remote
            system."
    ::= { lldpV2Xdot3RemoteData 2 }

lldpV2Xdot3RemPowerEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3RemPowerEntry
    MAX-ACCESS  not-accessible
    STATUS      current
```

```
    DESCRIPTION
            "Information about a particular physical network connection."
    INDEX   { lldpV2RemTimeMark,
              lldpV2RemLocalIfIndex,
              lldpV2RemLocalDestMACAddress,
              lldpV2RemIndex }
    ::= { lldpV2Xdot3RemPowerTable 1 }

LldpV2Xdot3RemPowerEntry ::= SEQUENCE {
              lldpV2Xdot3RemPowerPortClass           LldpV2PowerPortClass,
              lldpV2Xdot3RemPowerMDISupported        TruthValue,
              lldpV2Xdot3RemPowerMDIEnabled          TruthValue,
              lldpV2Xdot3RemPowerPairControlable     TruthValue,
              lldpV2Xdot3RemPowerPairs               Unsigned32,
              lldpV2Xdot3RemPowerClass               Unsigned32,
              lldpV2Xdot3RemPowerType                INTEGER,
              lldpV2Xdot3RemPowerSource              INTEGER,
              lldpV2Xdot3RemPowerPriority            INTEGER,
              lldpV2Xdot3RemPDRequestedPowerValue    Integer32,
              lldpV2Xdot3RemPSEAllocatedPowerValue   Integer32
}


lldpV2Xdot3RemPowerPortClass  OBJECT-TYPE
    SYNTAX      LldpV2PowerPortClass
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The value that identifies the port Class of the given port
            associated with the remote system."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.5"
    ::= { lldpV2Xdot3RemPowerEntry 1 }

lldpV2Xdot3RemPowerMDISupported  OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to indicate whether the MDI power
            is supported on the given port associated with the remote
            system."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.6"
    ::= { lldpV2Xdot3RemPowerEntry 2 }

lldpV2Xdot3RemPowerMDIEnabled  OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value used to identify whether MDI power is
            enabled on the given port associated with the remote system."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.7"
    ::= { lldpV2Xdot3RemPowerEntry 3 }

lldpV2Xdot3RemPowerPairControlable  OBJECT-TYPE
    SYNTAX      TruthValue
```

```
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The truth value is derived from the value of
            pethPsePortPowerPairsControlAbility object (defined in
            Clause 8) and is used to indicate whether the pair selection
            can be controlled on the given port associated with the
            remote system."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.8"
    ::= { lldpV2Xdot3RemPowerEntry 4 }

lldpV2Xdot3RemPowerPairs  OBJECT-TYPE
    SYNTAX      Unsigned32(1|2)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "This object contains the value of the pethPsePortPowerPairs
            object (defined in Clause 8) which is associated with
            the given port on the remote system."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.9"
    ::= { lldpV2Xdot3RemPowerEntry 5 }

lldpV2Xdot3RemPowerClass  OBJECT-TYPE
    SYNTAX      Unsigned32(1|2|3|4|5)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "This object contains the value of the
            pethPsePortPowerClassifications object (defined in
            Clause 8) which is associated with the given port on the
            remote system."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.10"
    ::= { lldpV2Xdot3RemPowerEntry 6 }


lldpV2Xdot3RemPowerType  OBJECT-TYPE
    SYNTAX      INTEGER {
                    psetype1(0),
                    psetype2(1),
                    pdtype(2),
                    pdtype2(3)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns an integer indicating whether the remote
             system is a PSE or a PD and whether it is Type 1 or Type 2."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.14"
    ::= { lldpV2Xdot3RemPowerEntry 7 }

lldpV2Xdot3RemPowerSource  OBJECT-TYPE
    SYNTAX      INTEGER {
                    pseprimary(0),
                    psebackup(1),
                    pseunknown(2),
```

```
                    pdpseandlocal(3),
                    pdlocalonly(4),
                    pdpseonly(5),
                    pdunknown(6)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns an integer indicating the power sources of the
            remote system. When the remote system is a PSE, it indicates
            whether it is being powered by a primary power source; a backup
            power source; or unknown. When the remote system is a PD, it
            indicates whether it is being powered by a PSE and locally;
            locally only; by a PSE only; or unknown."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.15"
    ::= { lldpV2Xdot3RemPowerEntry 8 }

lldpV2Xdot3RemPowerPriority  OBJECT-TYPE
    SYNTAX      INTEGER {
                    low(0),
                    high(1),
                    critical(2),
                    unknown(3)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
            "A GET returns the priority of a PD system. For a PSE, this
            is the priority that the remote system requests. For a PD, this
            is the priority that the remote system has assigned."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.16"
    ::= { lldpV2Xdot3RemPowerEntry 9 }

lldpV2Xdot3RemPDRequestedPowerValue  OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the PD requested power value that was used
            by the remote system to compute the power value that is has
            currently allocated to the PD. For a PSE, it is the PD requested
            power value received from the remote system. The definition and
            encoding of PD requested power value is the same as described in
            lldpV2Xdot3LocPDRequestedPowerValue."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.17"
    ::= { lldpV2Xdot3RemPowerEntry 10 }

lldpV2Xdot3RemPSEAllocatedPowerValue  OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the PSE allocated power value
            received from the remote system. For a PSE, it is the PSE allocated
            power value that was used by the remote system to compute the power
            value that it has currently requested from the PSE. For a PD, it
```

```
              is the PSE allocated power value received from the remote system.
              The definition and encoding of PSE allocated power value is
              the same as described in lldpV2Xdot3LocPSEAllocatedPowerValue."
    REFERENCE
              "IEEE Std 802.3 30.12.3.1.18"
    ::= { lldpV2Xdot3RemPowerEntry 11 }

---
--- lldpV2Xdot3RemMaxFrameSizeTable: Maximum Frame Size information
--- V2 modified to be indexed by ifIndex and destination MAC address.
---
---

lldpV2Xdot3RemMaxFrameSizeTable  OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3RemMaxFrameSizeEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
              "This table contains one row per port/destination
              address pair of maximum frame
              size information (as a part of the LLDP IEEE 802.3
              organizational extension) of the remote system."
    ::= { lldpV2Xdot3RemoteData 3 }

lldpV2Xdot3RemMaxFrameSizeEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3RemMaxFrameSizeEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
              "Maximum Frame Size information about a particular port
              component."
    INDEX   { lldpV2RemTimeMark,
                lldpV2RemLocalIfIndex,
                lldpV2RemLocalDestMACAddress,
                lldpV2RemIndex }
    ::= { lldpV2Xdot3RemMaxFrameSizeTable 1 }

LldpV2Xdot3RemMaxFrameSizeEntry ::= SEQUENCE {
              lldpV2Xdot3RemMaxFrameSize   Unsigned32
}

lldpV2Xdot3RemMaxFrameSize OBJECT-TYPE
    SYNTAX      Unsigned32(0..65535)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
              "An integer value indicating the maximum supported frame
               size in octets on the port component associated with the
               remote system."
    REFERENCE
              "IEEE Std 802.3 30.12.3.1.13"
    ::= { lldpV2Xdot3RemMaxFrameSizeEntry 1 }

---
---
--- lldpV2Xdot3RemEEETable: Energy Efficient Ethernet Information Table
--- V2 modified to be indexed by ifIndex.
---
---
```

```
lldpV2Xdot3RemEEETable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3RemEEEEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "This table contains one row per port of Energy Efficient Ethernet
            information (as a part of the LLDP IEEE 802.3 organizational
            extension) on the local system known to this agent."
    ::= { lldpV2Xdot3RemoteData 4 }

lldpV2Xdot3RemEEEEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3RemEEEEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "Information about a particular port component."
    INDEX   { lldpV2RemLocalIfIndex }
    ::= { lldpV2Xdot3RemEEETable 1 }

LldpV2Xdot3RemEEEEntry ::= SEQUENCE {
         lldpV2Xdot3RemTxTwSys                  Integer32,
         lldpV2Xdot3RemTxTwSysEcho              Integer32,
         lldpV2Xdot3RemRxTwSys                  Integer32,
         lldpV2Xdot3RemRxTwSysEcho              Integer32,
         lldpV2Xdot3RemFbTwSys                  Integer32
}


lldpV2Xdot3RemTxTwSys      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the value of Tw_sys_tx that the remote system
            can support in the transmit direction.
            This object maps to the variable RemTxSystemValue as defined
            in IEEE Std 802.3 78.4.2.3."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.19"
    ::= {lldpV2Xdot3RemEEEEntry 1 }

lldpV2Xdot3RemTxTwSysEcho      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the value of Tw_sys_tx that the local system is
            advertising that it can support in the transmit direction as
            echoed by the remote system under the control of the EEE DLL receiver
            state diagram. This object maps to the variable
            RemTxSystemValueEcho as defined in IEEE Std 802.3 78.4.2.3"
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.20"
    ::= {lldpV2Xdot3RemEEEEntry 2 }

lldpV2Xdot3RemRxTwSys      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
```

```
    STATUS      current
    DESCRIPTION
            "A GET returns the value of Tw_sys_tx that
            the remote system is requesting in the receive direction.
            This object maps to the variable RemRxSystemValue as
            defined in IEEE Std 802.3 78.4.2.3."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.21"
    ::= {lldpV2Xdot3RemEEEEntry 3 }

lldpV2Xdot3RemRxTwSysEcho      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the value of Tw_sys_tx that
            the local system is advertising that it is requesting in the
            receive direction and is echoed by the remote system under the
            control of the EEE DLL transmitter state diagram. This object
            maps to the variable RemRxSystemValueEcho as defined in
            IEEE Std 802.3 78.4.2.3."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.22"
    ::= {lldpV2Xdot3RemEEEEntry 4 }

lldpV2Xdot3RemFbTwSys      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "A GET returns the value of the fallback Tw_sys_tx
            that the remote system is advertising.
            This object maps to the variable RemFbSystemValue as defined
            in IEEE Std 802.3 78.4.2.3."
    REFERENCE
            "IEEE Std 802.3 30.12.3.1.23"
    ::= {lldpV2Xdot3RemEEEEntry 5 }



-------------------------------------------------------------------------------
-- Conformance statements
-------------------------------------------------------------------------------
lldpV2Xdot3Conformance OBJECT IDENTIFIER ::= { ieee8023lldpV2Xdot3MIB 2 }
lldpV2Xdot3Compliances OBJECT IDENTIFIER ::= { lldpV2Xdot3Conformance 1 }
lldpV2Xdot3Groups      OBJECT IDENTIFIER ::= { lldpV2Xdot3Conformance 2 }

-- Compliance statements


lldpV2Xdot3TxRxCompliance MODULE-COMPLIANCE
    STATUS  current
    DESCRIPTION
            "A compliance statement for SNMP entities that implement
            the LLDP IEEE 802.3 organizational extension MIB.

            This group is mandatory for all agents that implement the
            LLDP IEEE 802.3 organizational extension in TX and/or RX mode.
```

```
            This version defines compliance requirements for
            V2 of the LLDP MIB."
    MODULE  -- this module
        MANDATORY-GROUPS { lldpV2Xdot3ConfigGroup,
                           ifGeneralInformationGroup
        }
    ::= { lldpV2Xdot3Compliances 1 }

lldpV2Xdot3TxCompliance MODULE-COMPLIANCE
    STATUS  current
    DESCRIPTION
            "The compliance statement for SNMP entities that implement
            the LLDP IEEE 802.3 organizational extension MIB.

            This group is mandatory for agents that implement the
            LLDP IEEE 802.3 organizational extension in the TX mode.

            This version defines compliance requirements for
            V2 of the LLDP MIB."
    MODULE  -- this module
        MANDATORY-GROUPS { lldpV2Xdot3LocSysGroup }
    ::= { lldpV2Xdot3Compliances 2 }

lldpV2Xdot3RxCompliance MODULE-COMPLIANCE
    STATUS  current
    DESCRIPTION
            "The compliance statement for SNMP entities that implement
            the LLDP IEEE 802.3 organizational extension MIB.

            This group is mandatory for agents that implement the
            LLDP IEEE 802.3 organizational extension in the RX mode.

            This version defines compliance requirements for
            V2 of the LLDP MIB."
    MODULE  -- this module
        MANDATORY-GROUPS { lldpV2Xdot3RemSysGroup }
    ::= { lldpV2Xdot3Compliances 3 }


-- MIB groupings


lldpV2Xdot3ConfigGroup    OBJECT-GROUP
    OBJECTS {
        lldpV2Xdot3PortConfigTLVsTxEnable
    }
    STATUS  current
    DESCRIPTION
            "The collection of objects that are used to configure the
            LLDP IEEE 802.3 organizational extension implementation behavior."
    ::= { lldpV2Xdot3Groups 1 }

lldpV2Xdot3LocSysGroup  OBJECT-GROUP
    OBJECTS {
        lldpV2Xdot3LocPortAutoNegSupported,
        lldpV2Xdot3LocPortAutoNegEnabled,
        lldpV2Xdot3LocPortAutoNegAdvertisedCap,
        lldpV2Xdot3LocPortOperMauType,
        lldpV2Xdot3LocPowerPortClass,
```

```
          lldpV2Xdot3LocPowerMDISupported,
          lldpV2Xdot3LocPowerMDIEnabled,
          lldpV2Xdot3LocPowerPairControlable,
          lldpV2Xdot3LocPowerPairs,
          lldpV2Xdot3LocPowerClass,
          lldpV2Xdot3LocMaxFrameSize,
          lldpV2Xdot3LocPowerType,
          lldpV2Xdot3LocPowerSource,
          lldpV2Xdot3LocPowerPriority,
          lldpV2Xdot3LocPDRequestedPowerValue,
          lldpV2Xdot3LocPSEAllocatedPowerValue,
          lldpV2Xdot3LocResponseTime,
          lldpV2Xdot3LocReady,
          lldpV2Xdot3LocReducedOperationPowerValue,
          lldpV2Xdot3LocTxTwSys,
          lldpV2Xdot3LocTxTwSysEcho,
          lldpV2Xdot3LocRxTwSys,
          lldpV2Xdot3LocRxTwSysEcho,
          lldpV2Xdot3LocFbTwSys,
          lldpV2Xdot3TxDllReady,
          lldpV2Xdot3RxDllReady,
          lldpV2Xdot3LocDllEnabled
      }
      STATUS  current
      DESCRIPTION
              "The collection of objects that are used to represent LLDP
              IEEE 802.3 organizational extension Local Device Information."
      ::= { lldpV2Xdot3Groups 2 }

lldpV2Xdot3RemSysGroup  OBJECT-GROUP
      OBJECTS {
          lldpV2Xdot3RemPortAutoNegSupported,
          lldpV2Xdot3RemPortAutoNegEnabled,
          lldpV2Xdot3RemPortAutoNegAdvertisedCap,
          lldpV2Xdot3RemPortOperMauType,
          lldpV2Xdot3RemPowerPortClass,
          lldpV2Xdot3RemPowerMDISupported,
          lldpV2Xdot3RemPowerMDIEnabled,
          lldpV2Xdot3RemPowerPairControlable,
          lldpV2Xdot3RemPowerPairs,
          lldpV2Xdot3RemPowerClass,
          lldpV2Xdot3RemMaxFrameSize,
          lldpV2Xdot3RemPowerType,
          lldpV2Xdot3RemPowerSource,
          lldpV2Xdot3RemPowerPriority,
          lldpV2Xdot3RemPDRequestedPowerValue,
          lldpV2Xdot3RemPSEAllocatedPowerValue,
          lldpV2Xdot3RemTxTwSys,
          lldpV2Xdot3RemTxTwSysEcho,
          lldpV2Xdot3RemRxTwSys,
          lldpV2Xdot3RemRxTwSysEcho,
          lldpV2Xdot3RemFbTwSys
      }
      STATUS  current
      DESCRIPTION
              "The collection of objects that are used to represent LLDP
              IEEE 802.3 organizational extension Local Device Information."
      ::= { lldpV2Xdot3Groups 3 }
```

```
END
```

6. Ethernet operations, administration, and maintenance (OAM) MIB module

6.1 Introduction

The IEEE 802.3ah Ethernet in the First Mile (EFM) Task Force added management capabilities to Ethernet-like interfaces to provide some basic operations, administration and maintenance (OAM) functions. The defined functionality includes discovery, error signaling, loopback, and link monitoring.

This clause defines a MIB module for use with SNMP to manage these Ethernet-like interface capabilities.

6.2 Overview

Ethernet OAM is composed of a core set of functions and a set of optional functional groups as described in Clause 57 of IEEE Std 802.3. The core functions include discovery operations (determining if the other end of the link is OAM capable and what OAM functions it supports), state machine implementation, and some critical event flows. The optional functional groups are for (1) link events, (2) remote loopback, and (3) variable retrieval and response. Each optional functional group is controlled by a separate MIB table(s).

Ethernet OAM is complementary with SNMP management in that it provides some basic management functions at layer 2, rather than using layer 3 and above as required by SNMP over an IP infrastructure. Ethernet OAM provides single-hop functionality in that it works only between two directly connected Ethernet stations. SNMP can be used to manage the Ethernet OAM interactions of one Ethernet station with another.

Ethernet OAM has three functional objectives, which are detailed in 6.2.1 through 6.2.3. The definition of a basic Ethernet OAM protocol data unit is given in 6.2.4.

6.2.1 Remote fault indication

Remote fault indication provides a mechanism for one end of an Ethernet link to signal the other end that the receive path is non-operational. Some Ethernet Physical Layers offer mechanisms to signal this condition at the Physical Layer. Ethernet OAM added a mechanism so that some Ethernet Physical Layers can operate in unidirectional mode, allowing frames to be transmitted in one direction even when the other direction is non-operational. Traditionally, Ethernet PHYs do not allow frame transmission in one direction if the other direction is not operational. Using this mode, Ethernet OAM allows frame-based signaling of remote fault conditions while still not allowing higher layer applications to be aware of the unidirectional capability. This clause includes mechanisms for capturing that fault information and reflecting such information in objects and notifications within the SNMP management framework.

6.2.2 Link monitoring

Ethernet OAM includes event signaling capability so that one end of an Ethernet link can indicate the occurrence of certain important events to the other end of the link. This happens via layer 2 protocols. This clause defines methods for incorporating the occurrence of these layer 2 events, at both the local end and the far end of the link, into the SNMP management framework.

Ethernet OAM also includes mechanisms for one Ethernet station to query another directly connected Ethernet station about the status of its Ethernet interface variables and status. This clause does not include mechanisms for controlling how one Ethernet endpoint may use this functionality to query the status or statistics of a peer Ethernet entity.

6.2.3 Remote loopback

Remote loopback is a link state where the peer Ethernet entity echoes every received packet (without modifications) back onto the link. Remote loopback is intrusive in that the other end of the link is not forwarding traffic from higher layers out over the link. This clause defines objects controlling loopback operation and reading the status of the loopback state.

6.2.4 Ethernet OAM protocol data units

An Ethernet OAM protocol data unit is a valid Ethernet frame with a destination Media Access Control (MAC) address equal to the reserved MAC address for Slow Protocols (see Annex 57A of IEEE Std 802.3), a lengthOrType field equal to the reserved type for Slow Protocols, and a Slow Protocols subtype equal to that of the subtype reserved for Ethernet OAM.

OAMPDU is used throughout this clause as an abbreviation for Ethernet OAM protocol data unit. OAMPDUs are the mechanism by which two directly connected Ethernet interfaces exchange OAM information.

6.3 Relation to other MIB modules

The definitions presented here are based on Clause 30 and Clause 57 of IEEE Std 802.3. Note that these clauses describe many of these variables and their effects on the MAC sublayer. In some cases, there is a one-to-one relationship between an object in this clause and an object in the Clause 30 MIB. In other cases, the objects of this clause reflect a more complex entity and are reflected by more than one object in the Clause 30 MIB.

The objects defined in this clause manage OAM functionality introduced as part of the IEEE 802.3ah project. These objects do not overlap with the Interfaces Group MIB module defined in IETF RFC 2863, the Ethernet-like interface MIB module defined in Clause 10, or any other MIB module currently used to manage various aspects of an Ethernet interface. The objects defined here are defined for Ethernet-like interfaces only and use the same ifIndex as the associated Ethernet interface. Ethernet OAM can be implemented on any Ethernet-like interface.

6.3.1 Relation to other EFM MIB modules

The Ethernet OAM functionality and MIB module is independent of the other functionality and MIB modules derived from IEEE Std 802.3 for copper and EPON. Ethernet OAM may be implemented (or not) on the new EFM interface types, just as it can on any other Ethernet interface.

6.3.2 Mapping of IEEE 802.3 managed objects

Table 6-1 contains the mapping between managed objects defined in Clause 30 of IEEE Std 802.3 and managed objects defined in this clause.

All IEEE 802.3 OAM managed objects are reflected in this MIB module.

Table 6-1—Mapping between IEEE 802.3 managed objects and SNMP objects

IEEE 802.3 managed object	Corresponding SNMP object
oOAM	
.aOAMID	IF-MIB ifIndex
.aOAMAdminState	dot3OamAdminState
.aOAMMode	dot3OamMode
.aOAMDiscoveryState	dot3OamOperStatus
.aOAMRemoteMACAddress	dot3OamPeerMacAddress
.aOAMLocalConfiguration	dot3OamFunctionsSupported
.aOAMRemoteConfiguration	dot3OamPeerFunctionsSupported, dot3Oam-PeerMode
.aOAMLocalPDUConfiguration	dot3OamMaxOamPduSize
.aOAMRemotePDUConfiguration	dot3OamPeerMaxOamPduSize
.aOAMLocalFlagsField	dot3OamOperStatus, dot3OamEventLogEntry
.aOAMRemoteFlagsField	dot3OamOperStatus, dot3OamEventLogEntry
.aOAMLocalRevision	dot3OamConfigRevision
.aOAMRemoteRevision	dot3OamPeerConfigRevision
.aOAMLocalState	dot3OamLoopbackStatus
.aOAMRemoteState	dot3OamLoopbackStatus
.aOAMRemoteVendorOUI	dot3OamPeerVendorOui
.aOAMRemoteVendorSpecificInfo	dot3OamPeerVendorInfo
.aOAMUnsupportedCodesTx	dot3OamUnsupportedCodesTx
.aOAMUnsupportedCodesRx	dot3OamUnsupportedCodesRx
.aOAMInformationTx	dot3OamInformationTx
.aOAMInformationRx	dot3OamInformationRx
.aOAMUniqueEventNotificationTx	dot3OamUniqueEventNotificationTx
.aOAMUniqueEventNotificationRx	dot3OamUniqueEventNotificationRx
.aOAMDuplicateEventNotificationTx	dot3OamDuplicateEventNotificationTx
.aOAMDuplicateEventNotificationRx	dot3OamDuplicateEventNotificationRx
.aOAMLoopbackControlTx	dot3OamLoopbackControlTx

Table 6-1—Mapping between IEEE 802.3 managed objects and SNMP objects *(continued)*

IEEE 802.3 managed object	Corresponding SNMP object
.aOAMLoopbackControlRx	dot3OamLoopbackControlRx
.aOAMVariableRequestTx	dot3OamVariableRequestTx
.aOAMVariableRequestRx	dot3OamVariableRequestRx
.aOAMVariableResponseTx	dot3OamVariableResponseTx
.aOAMVariableResponseRx	dot3OamVariableResponseRx
.aOAMOrganizationSpecificTx	dot3OamOrgSpecificTx
.aOAMOrganizationSpecificRx	dot3OamOrgSpecificTx
.aOAMLocalErrSymPeriodConfig	dot3OamErrSymPeriodWindow, dot3OamErrSymPeriodThreshold
.aOAMLocalErrSymPeriodEvent	dot3OamEventLogEntry
.aOAMLocalErrFrameConfig	dot3OamErrFrameWindow, dot3OamErr-FrameThreshold
.aOAMLocalErrFrameEvent	dot3OamEventLogEntry
.aOAMLocalErrFramePeriodConfig	dot3OamErrFramePeriodWindow, dot3OamEr-rFramePeriodThreshold
.aOAMLocalErrFramePeriodEvent	dot3OamEventLogEntry
.aOAMLocalErrFrameSecsSummaryConfig	dot3OamErrFrameSecsSummaryWindow, dot3OamErrFrameSecssummaryThreshold
.aOAMLocalErrFrameSecsSummaryEvent	dot3OamEventLogEntry
.aOAMRemoteErrSymPeriodEvent	dot3OamEventLogEntry
.aOAMRemoteErrFrameEvent	dot3OamEventLogEntry
.aOAMRemoteErrFramePeriodEvent	dot3OamEventLogEntry
.aOAMRemoteErrFrameSecsSummaryEvent	dot3OamEventLogEntry
.aFramesLostDueToOAmError	dot3OamFramesLostDueToOam
.acOAMAdminControl	dot3OamAdminState

6.4 MIB structure

The Ethernet OAM MIB objects of this clause focus on the OAM capabilities introduced in IEEE Std 802.3. The MIB objects are partitioned into six different MIB groups.

The dot3OamTable group manages the primary OAM objects of the Ethernet interface. This group controls the state and status of OAM as well as the mode in which it operates. The dot3OamPeerTable maintains the current information on the status and configuration of the peer OAM entity on the Ethernet interface. Managed information includes the capabilities and function available on the peer OAM entity.

The dot3OamLoopbackTable manages the loopback function introduced in IEEE Std 802.3. This table controls enabling and disabling loopback, as well as indicating the loopback status of Ethernet OAM on this interface.

The dot3OamStatsTable maintains statistics on the number and type of Ethernet OAM frames being transmitted and received on the Ethernet interface.

The dot3OamEventConfigTable defines the objects for managing the event notification capability available in Ethernet OAM. With Ethernet OAM, one device may send notifications to its peer devices whenever an important event happens on the local device. This table provides management of which events result in notifications via Ethernet OAM notifications and/or via SNMP notifications.

The dot3OamEventLogTable manages the current status of local and remote events detected via Ethernet OAM. This table is updated whenever local events are detected by Ethernet OAM or whenever Ethernet OAM Event Notifications are received from the peer OAM entity.

There are two notifications defined to report Ethernet OAM events (one for threshold crossing events and one for non-threshold crossing events). Both notifications are contained within the same conformance group.

6.5 Security considerations for Ethernet operations, administration, and maintenance (OAM) MIB module

The readable objects in this module can provide information about network traffic, and therefore, they may be considered sensitive. In particular, OAM provides mechanisms for reading the Clause 30 IEEE 802.3 MIB attributes from a link partner via a specialized layer 2 protocol. Unlike SNMP, IEEE 802.3 OAM does not include encryption or authentication mechanisms. It should not be used in environments where this interface information is considered sensitive, and where the facility terminations are unprotected. By default, OAM is disabled on Ethernet-like interfaces and is therefore not a risk.

IEEE 802.3 OAM is designed to support deployment in access and enterprise networks. In access networks, one end of a link is the CO-side, and the other is the CPE-side, and the facilities are often protected in wiring cages or closets. In such deployments, it is often the case that the CO-side is protected from access from the CPE-side. Within IEEE 802.3 OAM, this protection from remote access is accomplished by configuring the CPE-side in passive mode using the dot3OamMode attribute. This prevents the CPE from accessing functions and information at the CO-side of the connection. In enterprise networks, read-only interface information is often considered non-sensitive.

The frequency of OAM PDUs on an Ethernet interface does not adversely affect data traffic, as OAM is a slow protocol with very limited bandwidth potential, and it is not required for normal link operation. Although there are a number of objects in this module with read-write or read-create MAX-ACCESS, they have limited effects on user data.

The loopback capability of OAM can have potentially disruptive effects; when remote loopback is enabled, the remote station automatically transmits all received traffic back to the local station except for OAM traffic. This completely disrupts all higher layer protocols such as bridging, IP, and SNMP. Therefore, an attribute (dot3OamLoopbackIgnoreRx) was introduced to control whether the local station processes or ignores received loopback commands.

The administrative state and mode are also read-write objects. Disabling OAM can interrupt management activities between peer devices, potentially causing serious problems. Setting the dot3OamMode to an undesired value can allow access to Ethernet monitoring, events, and functions that may not be acceptable in a particular deployment scenario. In addition to loopback functionality, Ethernet interface statistics and events can be accessed via the OAM protocol, which may not be desired in some circumstances.

OAM event configuration also contains read-write objects. These objects control whether events are sent, and at what thresholds. Note that the frequency of event communication is limited by the frequency limits of Slow Protocols on Ethernet interfaces. Also, the information available via OAM events is also available via OAM Variable Requests. Access to this information via either OAM events or Variable Requests is controlled by the dot3OamAdminState and dot3OamMode objects. As mentioned previously, inadequate protection of these variables can result in access to link information and functions.

6.6 MIB module definition

An ASCII text version of the MIB definition can be found at the following URL[12]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C6mib.txt

[12]Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.

```
IEEE8023-DOT3-OAM-MIB DEFINITIONS ::= BEGIN
    IMPORTS
      MODULE-IDENTITY, OBJECT-TYPE, Counter32, Unsigned32,
        Integer32, NOTIFICATION-TYPE, org
        FROM SNMPv2-SMI
        -- from [RFC2578]
      TEXTUAL-CONVENTION, MacAddress, TimeStamp, TruthValue
        FROM SNMPv2-TC
        -- from [RFC2579]
      CounterBasedGauge64
        FROM HCNUM-TC
        -- from [RFC2856]
      ifIndex
        FROM IF-MIB
        -- from [RFC2863]
      MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
        FROM SNMPv2-CONF;
        -- from [RFC2580]
      ieee8023Dot3OamMIB MODULE-IDENTITY
        LAST-UPDATED "201304110000Z" -- April 11, 2013
        ORGANIZATION
          "IEEE 802.3 working group"
        CONTACT-INFO
            "WG-URL: http://www.ieee802.org/3/index.html
            WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

            Contact: Howard Frazier
            Postal:  3151 Zanker Road
                     San Jose, CA 95134
                     USA
            Tel:     +1.408.922.8164
            E-mail:  hfrazier@broadcom.com"
        DESCRIPTION
          "The MIB module for managing the new Ethernet OAM features
          introduced by the Ethernet in the First Mile Task Force (IEEE
          802.3ah). The functionality presented here is based on IEEE
          Std 802.3ah, released in October, 2004, which was prepared as
          an addendum to IEEE Std 802.3. Since then, IEEE Std 802.3ah
          has been merged into the base IEEE 802.3 standard.

          In particular, this MIB focuses on the new OAM functions
          introduced in Clause 57 of IEEE Std 802.3. The OAM functionality
          of Clause 57 is controlled by new management attributes
          introduced in Clause 30 of IEEE Std 802.3. The OAM functions are
          not specific to any particular Ethernet Physical Layer, and
          can be generically applied to any Ethernet interface.

          An Ethernet OAM protocol data unit is a valid Ethernet frame
          with a destination MAC address equal to the reserved MAC
          address for Slow Protocols (See Annex 57A of IEEE Std 802.3), a
          lengthOrType field equal to the reserved type for Slow
          Protocols, and a Slow Protocols subtype equal to that of the
          subtype reserved for Ethernet OAM. OAMPDU is used throughout
          this document as an abbreviation for Ethernet OAM protocol
          data unit."

        REVISION    "201304110000Z" -- April 11, 2013
        DESCRIPTION "Revision, based on an earlier version in
                    IEEE Std 802.3.1-2011."
```

```
       REVISION    "201102020000Z" -- February 2, 2011
       DESCRIPTION "Initial version, based on an earlier version in RFC 4878."


         ::= { org ieee(111)
               standards-association-numbers-series-standards(2)
               lan-man-stds(802) ieee802dot3(3) ieee802dot3dot1mibs(1) 6 }

      --
      -- Sections of the Ethernet OAM MIB
      --
         dot3OamNotifications OBJECT IDENTIFIER ::= { ieee8023Dot3OamMIB 0 }
         dot3OamObjects       OBJECT IDENTIFIER ::= { ieee8023Dot3OamMIB 1 }
         dot3OamConformance   OBJECT IDENTIFIER ::= { ieee8023Dot3OamMIB 2 }

      --
      -- Textual conventions for the OAM MIB
      --
      EightOTwoOui ::= TEXTUAL-CONVENTION
        DISPLAY-HINT "3x:"
        STATUS       current
        DESCRIPTION
          "24-bit Organizationally Unique Identifier. Information on
          OUIs can be found in IEEE 802-2001 [802-2001], Clause 9."
        SYNTAX       OCTET STRING(SIZE(3))

      -- ***************************************************************
      --
      -- Ethernet OAM Control group
      --

      dot3OamTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF Dot3OamEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
          "This table contains the primary controls and status for the
          OAM capabilities of an Ethernet-like interface. There will be
          one row in this table for each Ethernet-like interface in the
          system that supports the OAM functions defined in IEEE Std 802.3."
        ::= { dot3OamObjects 1 }

      dot3OamEntry OBJECT-TYPE
        SYNTAX     Dot3OamEntry
        MAX-ACCESS not-accessible
        STATUS     current
        DESCRIPTION
          "An entry in the table that contains information on the
          Ethernet OAM function for a single Ethernet like interface.
          Entries in the table are created automatically for each
          interface supporting Ethernet OAM. The status of the row
          entry can be determined from dot3OamOperStatus.

          A dot3OamEntry is indexed in the dot3OamTable by the ifIndex
          object of the Interfaces Group MIB.
          "
        INDEX       { ifIndex }
        ::= { dot3OamTable 1 }
```

```
Dot3OamEntry ::=
  SEQUENCE {
    dot3OamAdminState                  INTEGER,
    dot3OamOperStatus                  INTEGER,
    dot3OamMode                        INTEGER,
    dot3OamMaxOamPduSize               Unsigned32,
    dot3OamConfigRevision              Unsigned32,
    dot3OamFunctionsSupported          BITS
  }

dot3OamAdminState OBJECT-TYPE
  SYNTAX      INTEGER {
                enabled(1),
                disabled(2)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "This object is used to provision the default administrative
    OAM mode for this interface. This object represents the
    desired state of OAM for this interface.

    The dot3OamAdminState starts in the disabled(2) state
    until an explicit management action or configuration
    information retained by the system causes a transition to the
    enabled(1) state. When enabled(1), Ethernet OAM will attempt
    to operate over this interface."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.2"
  ::= { dot3OamEntry 1 }

dot3OamOperStatus OBJECT-TYPE
  SYNTAX      INTEGER {
                disabled(1),
                linkFault(2),
                passiveWait(3),
                activeSendLocal(4),
                sendLocalAndRemote(5),
                sendLocalAndRemoteOk(6),
                oamPeeringLocallyRejected(7),
                oamPeeringRemotelyRejected(8),
                operational(9),
                nonOperHalfDuplex(10)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "At initialization and failure conditions, two OAM entities on
    the same full-duplex Ethernet link begin a discovery phase to
    determine what OAM capabilities may be used on that link. The
    progress of this initialization is controlled by the OAM
    sublayer.

    This value is disabled(1) if OAM is disabled on this
    interface via the dot3OamAdminState.

    If the link has detected a fault and is transmitting OAMPDUs
    with a link fault indication, the value is linkFault(2).
```

```
            Also, if the interface is not operational (ifOperStatus is
            not up(1)), linkFault(2) is returned. Note that the object
            ifOperStatus may not be up(1) as a result of link failure or
            administrative action (ifAdminState being down(2) or
            testing(3)).

            The passiveWait(3) state is returned only by OAM entities in
            passive mode (dot3OamMode) and reflects the state in which the
            OAM entity is waiting to see if the peer device is OAM
            capable. The activeSendLocal(4) value is used by active mode
            devices (dot3OamMode) and reflects the OAM entity actively
            trying to discover whether the peer has OAM capability but has
            not yet made that determination.

            The state sendLocalAndRemote(5) reflects that the local OAM
            entity has discovered the peer but has not yet accepted or
            rejected the configuration of the peer. The local device can,
            for whatever reason, decide that the peer device is
            unacceptable and decline OAM peering. If the local OAM entity
            rejects the peer OAM entity, the state becomes
            oamPeeringLocallyRejected(7). If the OAM peering is allowed
            by the local device, the state moves to
            sendLocalAndRemoteOk(6). Note that both the
            sendLocalAndRemote(5) and oamPeeringLocallyRejected(7) states
            fall within the state SEND_LOCAL_REMOTE of the Discovery state
            diagram (see IEEE Std 802.3, Figure 57-5), with the difference being
            whether the local OAM client has actively rejected the peering
            or has just not indicated any decision yet. Whether a peering
            decision has been made is indicated via the local flags field
            in the OAMPDU (reflected in the aOAMLocalFlagsField of
            IEEE Std 802.3 30.3.6.1.10).

            If the remote OAM entity rejects the peering, the state
            becomes oamPeeringRemotelyRejected(8). Note that both the
            sendLocalAndRemoteOk(6) and oamPeeringRemotelyRejected(8)
            states fall within the state SEND_LOCAL_REMOTE_OK of the
            Discovery state diagram (see IEEE Std 802.3, Figure 57-5), with the
            difference being whether the remote OAM client has rejected
            the peering or has just not yet decided. This is indicated
            via the remote flags field in the OAMPDU (reflected in the
            aOAMRemoteFlagsField of IEEE Std 802.3 30.3.6.1.11).

            When the local OAM entity learns that both it and the remote
            OAM entity have accepted the peering, the state moves to
            operational(9) corresponding to the SEND_ANY state of the
            Discovery state diagram (see IEEE Std 802.3, Figure 57-5).

            Since Ethernet OAM functions are not designed to work
            completely over half-duplex interfaces, the value
            nonOperHalfDuplex(10) is returned whenever Ethernet OAM is
            enabled (dot3OamAdminState is enabled(1)), but the interface
            is in half-duplex operation."

          REFERENCE   "IEEE Std 802.3, 30.3.6.1.4, 30.3.6.1.10, 30.3.6.1.11"
          ::= { dot3OamEntry 2 }

        dot3OamMode OBJECT-TYPE
          SYNTAX      INTEGER {
                        passive(1),
```

```
                    active(2)
                  }
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
        "This object configures the mode of OAM operation for this
        Ethernet-like interface. OAM on Ethernet interfaces may be in
        ‘active’ mode or ‘passive’ mode. These two modes differ in
        that active mode provides additional capabilities to initiate
        monitoring activities with the remote OAM peer entity, while
        passive mode generally waits for the peer to initiate OAM
        actions with it. As an example, an active OAM entity can put
        the remote OAM entity in a loopback state, where a passive OAM
        entity cannot.

        The default value of dot3OamMode is dependent on the type of
        system on which this Ethernet-like interface resides. The
        default value should be ‘active(2)’ unless it is known that
        this system should take on a subservient role to the other
        device connected over this interface.

        Changing this value results in incrementing the configuration
        revision field of locally generated OAMPDUs (IEEE Std 802.3
        30.3.6.1.12) and potentially rerunning the OAM discovery process
        if the dot3OamOperStatus was already operational(9)."

      REFERENCE   "IEEE Std 802.3, 30.3.6.1.3"
      ::= { dot3OamEntry 3 }

    dot3OamMaxOamPduSize OBJECT-TYPE
      SYNTAX      Unsigned32 (64..1518)
      UNITS       "octets"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
        "The largest OAMPDU that the OAM entity supports. OAM
        entities exchange maximum OAMPDU sizes and negotiate to use
        the smaller of the two maximum OAMPDU sizes between the peers.
        This value is determined by the local implementation."

      REFERENCE   "IEEE Std 802.3, 30.3.6.1.8"
      ::= { dot3OamEntry 4 }

    dot3OamConfigRevision OBJECT-TYPE
      SYNTAX      Unsigned32(0..65535)
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
        "The configuration revision of the OAM entity as reflected in
        the latest OAMPDU sent by the OAM entity. The config revision
        is used by OAM entities to indicate that configuration changes
        have occurred, which might require the peer OAM entity to
        re-evaluate whether OAM peering is allowed."

      REFERENCE   "IEEE Std 802.3, 30.3.6.1.12"
      ::= { dot3OamEntry 5 }

    dot3OamFunctionsSupported OBJECT-TYPE
      SYNTAX      BITS {
```

```
                    unidirectionalSupport (0),
                    loopbackSupport(1),
                    eventSupport(2),
                    variableSupport(3)
                  }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The OAM functions supported on this Ethernet-like interface.
    OAM consists of separate functional sets beyond the basic
    discovery process that is required. These functional
    groups can be supported independently by any implementation.
    These values are communicated to the peer via the local
    configuration field of Information OAMPDUs.

    Setting ‘unidirectionalSupport(0)’ indicates that the OAM
    entity supports the transmission of OAMPDUs on links that are
    operating in unidirectional mode (traffic flowing in one
    direction only). Setting ‘loopbackSupport(1)’ indicates that
    the OAM entity can initiate and respond to loopback commands.
    Setting ‘eventSupport(2)’ indicates that the OAM entity can
    send and receive Event Notification OAMPDUs. Setting
    ‘variableSupport(3)’ indicates that the OAM entity can send
    and receive Variable Request and Response OAMPDUs."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.6"
  ::= { dot3OamEntry 6 }

-- ***************************************************************
--
-- Ethernet OAM Peer group
--

dot3OamPeerTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamPeerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains information about the OAM peer for a
    particular Ethernet-like interface. OAM entities communicate
    with a single OAM peer entity on Ethernet links on which OAM
    is enabled and operating properly. There is one entry in this
    table for each entry in the dot3OamTable for which information
    on the peer OAM entity is available."

  ::= { dot3OamObjects 2 }

dot3OamPeerEntry OBJECT-TYPE
  SYNTAX      Dot3OamPeerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the table containing information on the peer OAM
    entity for a single Ethernet-like interface.

    Note that there is at most one OAM peer for each Ethernet-like
    interface. Entries are automatically created when information
    about the OAM peer entity becomes available, and automatically
    deleted when the OAM peer entity is no longer in
```

```
      communication. Peer information is not available when
      dot3OamOperStatus is disabled(1), linkFault(2),
      passiveWait(3), activeSendLocal(4), or nonOperHalfDuplex(10)."

    INDEX       { ifIndex }
    ::= { dot3OamPeerTable 1 }

  Dot3OamPeerEntry ::=
    SEQUENCE {
      dot3OamPeerMacAddress              MacAddress,
      dot3OamPeerVendorOui               EightOTwoOui,
      dot3OamPeerVendorInfo              Unsigned32,
      dot3OamPeerMode                    INTEGER,
      dot3OamPeerMaxOamPduSize           Unsigned32,
      dot3OamPeerConfigRevision          Unsigned32,
      dot3OamPeerFunctionsSupported      BITS
    }

  dot3OamPeerMacAddress OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The MAC address of the peer OAM entity. The MAC address is
      derived from the most recently received OAMPDU."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.5."
    ::= { dot3OamPeerEntry 1 }

  dot3OamPeerVendorOui OBJECT-TYPE
    SYNTAX      EightOTwoOui
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The OUI of the OAM peer as reflected in the latest
      Information OAMPDU received with a Local Information TLV. The
      OUI can be used to identify the vendor of the remote OAM
      entity. This value is initialized to three octets of zero
      before any Local Information TLV is received."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.16."
    ::= { dot3OamPeerEntry 2 }

  dot3OamPeerVendorInfo OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The Vendor Info of the OAM peer as reflected in the latest
      Information OAMPDU received with a Local Information TLV.
      The semantics of the Vendor Information field is proprietary
      and specific to the vendor (identified by the
      dot3OamPeerVendorOui). This information could, for example,
      be used to identify a specific product or product family.
      This value is initialized to zero before any Local
      Information TLV is received."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.17."
    ::= { dot3OamPeerEntry 3 }
```

```
dot3OamPeerMode OBJECT-TYPE
  SYNTAX      INTEGER {
                passive(1),
                active(2),
                unknown(3)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The mode of the OAM peer as reflected in the latest
    Information OAMPDU received with a Local Information TLV. The
    mode of the peer can be determined from the Configuration
    field in the Local Information TLV of the last Information
    OAMPDU received from the peer. The value is unknown(3)
    whenever no Local Information TLV has been received. The
    values of active(2) and passive(1) are returned when a Local
    Information TLV has been received indicating that the peer is
    in active or passive mode, respectively."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.7."
  ::= { dot3OamPeerEntry 4 }

dot3OamPeerMaxOamPduSize OBJECT-TYPE
  SYNTAX      Unsigned32 (0 | 64..1518)
  UNITS       "octets"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The maximum size of OAMPDU supported by the peer as reflected
    in the latest Information OAMPDU received with a Local
    Information TLV. Ethernet OAM on this interface shall not use
    OAMPDUs that exceed this size. The maximum OAMPDU size can be
    determined from the PDU Configuration field of the Local
    Information TLV of the last Information OAMPDU received from
    the peer. A value of zero is returned if no Local Information
    TLV has been received. Otherwise, the value of the OAM peer’s
    maximum OAMPDU size is returned in this value."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.9."
  ::= { dot3OamPeerEntry 5 }
dot3OamPeerConfigRevision OBJECT-TYPE
  SYNTAX      Unsigned32(0..65535)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The configuration revision of the OAM peer as reflected in
    the latest OAMPDU. This attribute is changed by the peer
    whenever it has a local configuration change for Ethernet OAM
    on this interface. The configuration revision can be
    determined from the Revision field of the Local Information
    TLV of the most recently received Information OAMPDU with
    a Local Information TLV. A value of zero is returned if
    no Local Information TLV has been received."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.13."
  ::= { dot3OamPeerEntry 6 }

dot3OamPeerFunctionsSupported OBJECT-TYPE
```

```
  SYNTAX      BITS {
                unidirectionalSupport (0),
                loopbackSupport(1),
                eventSupport(2),
                variableSupport(3)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The OAM functions supported on this Ethernet-like interface.
    OAM consists of separate functionality sets above the basic
    discovery process. This value indicates the capabilities of
    the peer OAM entity with respect to these functions. This
    value is initialized so all bits are clear.

    If unidirectionalSupport(0) is set, then the peer OAM entity
    supports sending OAM frames on Ethernet interfaces when the
    receive path is known to be inoperable. If
    loopbackSupport(1) is set, then the peer OAM entity can send
    and receive OAM loopback commands. If eventSupport(2) is set,
    then the peer OAM entity can send and receive event OAMPDUs to
    signal various error conditions. If variableSupport(3) is
    set, then the peer OAM entity can send and receive variable
    requests to monitor the attribute value as described in Clause
    57 of IEEE Std 802.3.

    The capabilities of the OAM peer can be determined from the
    configuration field of the Local Information TLV of the most
    recently received Information OAMPDU with a Local Information
    TLV. All zeros are returned if no Local Information TLV has
    yet been received."

  REFERENCE   "IEEE Std 802.3 30.3.6.1.7."
  ::= { dot3OamPeerEntry 7 }

-- ***************************************************************
--
-- Ethernet OAM Loopback group
--

dot3OamLoopbackTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamLoopbackEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains controls for the loopback state of the
    local link as well as indicates the status of the loopback
    function. There is one entry in this table for each entry in
    dot3OamTable that supports loopback functionality (where
    dot3OamFunctionsSupported includes the loopbackSupport bit
    set).

    Loopback can be used to place the remote OAM entity in a state
    where every received frame (except OAMPDUs) is echoed back
    over the same interface on which they were received. In this
    state, at the remote entity, 'normal' traffic is disabled as
    only the looped back frames are transmitted on the interface.
    Loopback is thus an intrusive operation that prohibits normal
    data flow and should be used accordingly."
```

```
    ::= { dot3OamObjects 3 }

  dot3OamLoopbackEntry OBJECT-TYPE
    SYNTAX      Dot3OamLoopbackEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "An entry in the table, containing information on the loopback
      status for a single Ethernet-like interface. Entries in the
      table are automatically created whenever the local OAM entity
      supports loopback capabilities. The loopback status on the
      interface can be determined from the dot3OamLoopbackStatus
      object."

    INDEX       { ifIndex }
    ::= { dot3OamLoopbackTable 1 }

  Dot3OamLoopbackEntry ::=
    SEQUENCE {
      dot3OamLoopbackStatus             INTEGER,
      dot3OamLoopbackIgnoreRx           INTEGER
    }

  dot3OamLoopbackStatus OBJECT-TYPE
    SYNTAX      INTEGER {
                  -- all values, except where noted, can be read
                  -- but cannot be written
                  noLoopback (1),

                  -- initiatingLoopback can be read or written
                  initiatingLoopback (2),
                  remoteLoopback (3),

                  -- terminatingLoopback can be read or written
                  terminatingLoopback (4),
                  localLoopback (5),
                  unknown (6)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "The loopback status of the OAM entity. This status is
      determined by a combination of the local parser and
      multiplexer states, the remote parser and multiplexer states,
      as well as by the actions of the local OAM client. When
      operating in normal mode with no loopback in progress, the
      status reads noLoopback(1).

      The values initiatingLoopback(2) and terminatingLoopback(4)
      can be read or written. The other values can only be read -
      they can never be written. Writing initiatingLoopback causes
      the local OAM entity to start the loopback process with its
      peer. This value can only be written when the status is
      noLoopback(1). Writing the value initiatingLoopback(2) in any
      other state has no effect. When in remoteLoopback(3), writing
      terminatingLoopback(4) causes the local OAM entity to initiate
      the termination of the loopback state. Writing
      terminatingLoopack(4) in any other state has no effect.
```

```
          If the OAM client initiates a loopback and has sent a
          Loopback OAMPDU and is waiting for a response, where the local
          parser and multiplexer states are DISCARD (see IEEE Std 802.3,
          57.2.11.1), the status is ‘initiatingLoopback’. In this
          case, the local OAM entity has yet to receive any
          acknowledgment that the remote OAM entity has received its
          loopback command request.
          If the local OAM client knows that the remote OAM entity is in
          loopback mode (via the remote state information as described
          in IEEE Std 802.3, 57.2.11.1, 30.3.6.1.15), the status is
          remoteLoopback(3). If the local OAM client is in the process
          of terminating the remote loopback (see IEEE Std 802.3, 57.2.11.3,
          30.3.6.1.14) with its local multiplexer and parser states in
          DISCARD, the status is terminatingLoopback(4). If the remote
          OAM client has put the local OAM entity in loopback mode as
          indicated by its local parser state, the status is
          localLoopback(5).

          The unknown(6) status indicates that the parser and
          multiplexer combination is unexpected. This status may be
          returned if the OAM loopback is in a transition state but
          should not persist.

          The values of this attribute correspond to the following
          values of the local and remote parser and multiplexer states.

            value            LclPrsr   LclMux    RmtPrsr   RmtMux
            noLoopback         FWD       FWD       FWD       FWD
            initLoopback     DISCARD   DISCARD     FWD       FWD
            rmtLoopback      DISCARD     FWD      LPBK    DISCARD
            tmtngLoopback    DISCARD   DISCARD    LPBK    DISCARD
            lclLoopback        LPBK    DISCARD   DISCARD     FWD
            unknown            ***   any other combination   ***
          "
        REFERENCE   "IEEE Std 802.3, 57.2.11, 30.3.6.1.14, 30.3.6.1.15"
        ::= { dot3OamLoopbackEntry 1 }

      dot3OamLoopbackIgnoreRx OBJECT-TYPE
        SYNTAX      INTEGER { ignore(1), process(2) }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "Since OAM loopback is a disruptive operation (user traffic
          does not pass), this attribute provides a mechanism to provide
          controls over whether received OAM loopback commands are
          processed or ignored. When the value is ignore(1), received
          loopback commands are ignored. When the value is process(2),
          OAM loopback commands are processed. The default value is to
          ignore loopback commands (ignore(1))."

        REFERENCE   "IEEE Std 802.3, 57.2.11, 30.3.6.1.14, 30.3.6.1.15"
        ::= { dot3OamLoopbackEntry 2 }
      -- ***************************************************************
      --
      -- Ethernet OAM Statistics group
      --

      dot3OamStatsTable OBJECT-TYPE
```

```
    SYNTAX      SEQUENCE OF Dot3OamStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "This table contains statistics for the OAM function on a
      particular Ethernet-like interface. There is an entry in the
      table for every entry in the dot3OamTable.

      The counters in this table are defined as 32-bit entries to
      match the counter size as defined in IEEE Std 802.3. Given that
      the OAM protocol is a slow protocol, the counters increment at
      a slow rate."

    ::= { dot3OamObjects 4 }

  dot3OamStatsEntry OBJECT-TYPE
    SYNTAX      Dot3OamStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "An entry in the table containing statistics information on
      the Ethernet OAM function for a single Ethernet-like
      interface. Entries are automatically created for every entry
      in the dot3OamTable. Counters are maintained across
      transitions in dot3OamOperStatus."

    INDEX       { ifIndex }
    ::= { dot3OamStatsTable 1 }

  Dot3OamStatsEntry ::=
    SEQUENCE {
              dot3OamInformationTx                Counter32,
              dot3OamInformationRx                Counter32,
              dot3OamUniqueEventNotificationTx    Counter32,
              dot3OamUniqueEventNotificationRx    Counter32,
              dot3OamDuplicateEventNotificationTx Counter32,
              dot3OamDuplicateEventNotificationRx Counter32,
              dot3OamLoopbackControlTx            Counter32,
              dot3OamLoopbackControlRx            Counter32,
              dot3OamVariableRequestTx            Counter32,
              dot3OamVariableRequestRx            Counter32,
              dot3OamVariableResponseTx           Counter32,
              dot3OamVariableResponseRx           Counter32,
              dot3OamOrgSpecificTx                Counter32,
              dot3OamOrgSpecificRx                Counter32,
              dot3OamUnsupportedCodesTx           Counter32,
              dot3OamUnsupportedCodesRx           Counter32,
              dot3OamFramesLostDueToOam           Counter32
             }

  dot3OamInformationTx OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "frames"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "A count of the number of Information OAMPDUs transmitted on
      this interface.
```

```
          Discontinuities of this counter can occur at re-initialization
          of the management system, and at other times as indicated by
          the value of the ifCounterDiscontinuityTime."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.20."
        ::= { dot3OamStatsEntry 1 }

      dot3OamInformationRx OBJECT-TYPE
        SYNTAX      Counter32
        UNITS       "frames"
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "A count of the number of Information OAMPDUs received on this
          interface.

          Discontinuities of this counter can occur at re-initialization
          of the management system, and at other times as indicated by
          the value of the ifCounterDiscontinuityTime."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.21."
        ::= { dot3OamStatsEntry 2 }

      dot3OamUniqueEventNotificationTx OBJECT-TYPE
        SYNTAX      Counter32
        UNITS       "frames"
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "A count of the number of unique Event OAMPDUs transmitted on
          this interface. Event Notifications may be sent in duplicate
          to increase the probability of successfully being received,
          given the possibility that a frame may be lost in transit.
          Duplicate Event Notification transmissions are counted by
          dot3OamDuplicateEventNotificationTx.

          A unique Event Notification OAMPDU is indicated as an Event
          Notification OAMPDU with a Sequence Number field that is
          distinct from the previously transmitted Event Notification
          OAMPDU Sequence Number.

          Discontinuities of this counter can occur at re-initialization
          of the management system, and at other times as indicated by
          the value of the ifCounterDiscontinuityTime."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.22."
        ::= { dot3OamStatsEntry 3 }

      dot3OamUniqueEventNotificationRx OBJECT-TYPE
        SYNTAX      Counter32
        UNITS       "frames"
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "A count of the number of unique Event OAMPDUs received on
          this interface. Event Notification OAMPDUs may be sent in
          duplicate to increase the probability of successfully being
          received, given the possibility that a frame may be lost in
          transit. Duplicate Event Notification receptions are counted
```

```
          by dot3OamDuplicateEventNotificationRx.

          A unique Event Notification OAMPDU is indicated as an Event
          Notification OAMPDU with a Sequence Number field that is
          distinct from the previously received Event Notification
          OAMPDU Sequence Number.

          Discontinuities of this counter can occur at re-initialization
          of the management system, and at other times as indicated by
          the value of the ifCounterDiscontinuityTime."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.24."
        ::= { dot3OamStatsEntry 4 }

      dot3OamDuplicateEventNotificationTx OBJECT-TYPE
        SYNTAX      Counter32
        UNITS       "frames"
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "A count of the number of duplicate Event OAMPDUs transmitted
          on this interface. Event Notification OAMPDUs may be sent in
          duplicate to increase the probability of successfully being
          received, given the possibility that a frame may be lost in
          transit.

          A duplicate Event Notification OAMPDU is indicated as an Event
          Notification OAMPDU with a Sequence Number field that is
          identical to the previously transmitted Event Notification
          OAMPDU Sequence Number.

          Discontinuities of this counter can occur at re-initialization
          of the management system, and at other times as indicated by
          the value of the ifCounterDiscontinuityTime."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.23."
        ::= { dot3OamStatsEntry 5 }

      dot3OamDuplicateEventNotificationRx OBJECT-TYPE
        SYNTAX      Counter32
        UNITS       "frames"
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "A count of the number of duplicate Event OAMPDUs received on
          this interface. Event Notification OAMPDUs may be sent in
          duplicate to increase the probability of successfully being
          received, given the possibility that a frame may be lost in
          transit.

          A duplicate Event Notification OAMPDU is indicated as an Event
          Notification OAMPDU with a Sequence Number field that is
          identical to the previously received Event Notification OAMPDU
          Sequence Number.

          Discontinuities of this counter can occur at re-initialization
          of the management system, and at other times as indicated by
          the value of the ifCounterDiscontinuityTime."
```

```
    REFERENCE   "IEEE Std 802.3, 30.3.6.1.25."
    ::= { dot3OamStatsEntry 6 }

  dot3OamLoopbackControlTx OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "frames"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "A count of the number of Loopback Control OAMPDUs transmitted
      on this interface.

      Discontinuities of this counter can occur at re-initialization
      of the management system, and at other times as indicated by
      the value of the ifCounterDiscontinuityTime."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.26."
    ::= { dot3OamStatsEntry 7 }

  dot3OamLoopbackControlRx OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "frames"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "A count of the number of Loopback Control OAMPDUs received
      on this interface.

      Discontinuities of this counter can occur at re-initialization
      of the management system, and at other times as indicated by
      the value of the ifCounterDiscontinuityTime."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.27."
    ::= { dot3OamStatsEntry 8 }

  dot3OamVariableRequestTx OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "frames"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "A count of the number of Variable Request OAMPDUs transmitted
      on this interface.

      Discontinuities of this counter can occur at re-initialization
      of the management system, and at other times as indicated by
      the value of the ifCounterDiscontinuityTime."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.28."
    ::= { dot3OamStatsEntry 9 }

  dot3OamVariableRequestRx OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "frames"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "A count of the number of Variable Request OAMPDUs received on
      this interface.
```

```
    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.29."
  ::= { dot3OamStatsEntry 10 }

dot3OamVariableResponseTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Variable Response OAMPDUs
    transmitted on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.30."
  ::= { dot3OamStatsEntry 11 }

dot3OamVariableResponseRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Variable Response OAMPDUs received
    on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.31."
  ::= { dot3OamStatsEntry 12 }

 dot3OamOrgSpecificTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Organization Specific OAMPDUs
    transmitted on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.32."
  ::= { dot3OamStatsEntry 13 }

dot3OamOrgSpecificRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
```

```
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "A count of the number of Organization Specific OAMPDUs
      received on this interface.

      Discontinuities of this counter can occur at re-initialization
      of the management system, and at other times as indicated by
      the value of the ifCounterDiscontinuityTime."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.33."
    ::= { dot3OamStatsEntry 14 }

  dot3OamUnsupportedCodesTx OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "frames"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "A count of the number of OAMPDUs transmitted on this
      interface with an unsupported op-code.

      Discontinuities of this counter can occur at re-initialization
      of the management system, and at other times as indicated by
      the value of the ifCounterDiscontinuityTime."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.18."
    ::= { dot3OamStatsEntry 15 }

  dot3OamUnsupportedCodesRx OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "frames"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "A count of the number of OAMPDUs received on this interface
      with an unsupported op-code.

      Discontinuities of this counter can occur at re-initialization
      of the management system, and at other times as indicated by
      the value of the ifCounterDiscontinuityTime."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.19."
    ::= { dot3OamStatsEntry 16 }

  dot3OamFramesLostDueToOam OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "frames"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "A count of the number of frames that were dropped by the OAM
      multiplexer. Since the OAM multiplexer has multiple inputs
      and a single output, there may be cases where frames are
      dropped due to transmit resource contention. This counter is
      incremented whenever a frame is dropped by the OAM layer.
      Note that any Ethernet frame, not just OAMPDUs, may be dropped
      by the OAM layer. This can occur when an OAMPDU takes
      precedence over a ‘normal’ frame resulting in the ‘normal’
```

```
        frame being dropped.

        When this counter is incremented, no other counters in this
        MIB are incremented.

        Discontinuities of this counter can occur at re-initialization
        of the management system, and at other times as indicated by
        the value of the ifCounterDiscontinuityTime."

      REFERENCE   "IEEE Std 802.3, 30.3.6.1.46."
      ::= { dot3OamStatsEntry 17 }

    -- ***************************************************************
    --
    -- Ethernet OAM Event Configuration group
    --

    dot3OamEventConfigTable OBJECT-TYPE
      SYNTAX     SEQUENCE OF Dot3OamEventConfigEntry
      MAX-ACCESS not-accessible
      STATUS     current
      DESCRIPTION
        "Ethernet OAM includes the ability to generate and receive
        Event Notification OAMPDUs to indicate various link problems.
        This table contains the mechanisms to enable Event
        Notifications and configure the thresholds to generate the
        standard Ethernet OAM events. There is one entry in the table
        for every entry in dot3OamTable that supports OAM events
        (where dot3OamFunctionsSupported includes the eventSupport
        bit set). The values in the table are maintained across
        changes to dot3OamOperStatus.

        The standard threshold crossing events are:
          - Errored Symbol Period Event. Generated when the number of
            symbol errors exceeds a threshold within a given window
            defined by a number of symbols (for example, 1,000 symbols
            out of 1,000,000 had errors).
          - Errored Frame Period Event. Generated when the number of
            frame errors exceeds a threshold within a given window
            defined by a number of frames (for example, 10 frames out
            of 1000 had errors).
          - Errored Frame Event. Generated when the number of frame
            errors exceeds a threshold within a given window defined
            by a period of time (for example, 10 frames in 1 second
            had errors).
          - Errored Frame Seconds Summary Event. Generated when the
            number of errored frame seconds exceeds a threshold within
            a given time period (for example, 10 errored frame seconds
            within the last 100 seconds). An errored frame second is
            defined as a 1 second interval which had >0 frame errors.
        There are other events (dying gasp, critical events) that are
        not threshold crossing events but that can be
        enabled/disabled via this table."

      ::= { dot3OamObjects 5 }

    dot3OamEventConfigEntry OBJECT-TYPE
      SYNTAX      Dot3OamEventConfigEntry
      MAX-ACCESS  not-accessible
```

```
    STATUS      current
    DESCRIPTION
      "Entries are automatically created and deleted from this
      table, and exist whenever the OAM entity supports Ethernet OAM
      events (as indicated by the eventSupport bit in
      dot3OamFunctionsSuppported). Values in the table are
      maintained across changes to the value of dot3OamOperStatus.

      Event configuration controls when the local management entity
      sends Event Notification OAMPDUs to its OAM peer, and when
      certain event flags are set or cleared in OAMPDUs."

    INDEX       { ifIndex }
    ::= { dot3OamEventConfigTable 1 }

  Dot3OamEventConfigEntry ::=
    SEQUENCE {
              dot3OamErrSymPeriodWindowHi        Unsigned32,
              dot3OamErrSymPeriodWindowLo        Unsigned32,
              dot3OamErrSymPeriodThresholdHi     Unsigned32,
              dot3OamErrSymPeriodThresholdLo     Unsigned32,
              dot3OamErrSymPeriodEvNotifEnable   TruthValue,
              dot3OamErrFramePeriodWindow        Unsigned32,
              dot3OamErrFramePeriodThreshold     Unsigned32,
              dot3OamErrFramePeriodEvNotifEnable TruthValue,
              dot3OamErrFrameWindow              Unsigned32,
              dot3OamErrFrameThreshold           Unsigned32,
              dot3OamErrFrameEvNotifEnable       TruthValue,
              dot3OamErrFrameSecsSummaryWindow   Integer32,
              dot3OamErrFrameSecsSummaryThreshold Integer32,
              dot3OamErrFrameSecsEvNotifEnable   TruthValue,
              dot3OamDyingGaspEnable             TruthValue,
              dot3OamCriticalEventEnable         TruthValue
            }

  dot3OamErrSymPeriodWindowHi OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "2^32 symbols"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "The two objects dot3OamErrSymPeriodWindowHi and
      dot3OamErrSymPeriodLo together form an unsigned 64-bit
      integer representing the number of symbols over which this
      threshold event is defined. This is defined as
      dot3OamErrSymPeriodWindow = ((2^32)*dot3OamErrSymPeriodWindowHi)
                                  + dot3OamErrSymPeriodWindowLo

      If dot3OamErrSymPeriodThreshold symbol errors occur within a
      window of dot3OamErrSymPeriodWindow symbols, an Event
      Notification OAMPDU should be generated with an Errored Symbol
      Period Event TLV indicating that the threshold has been
      crossed in this window.

      The default value for dot3OamErrSymPeriodWindow is the number
      of symbols in one second for the underlying Physical Layer."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.34"
    ::= { dot3OamEventConfigEntry 1 }
```

```
dot3OamErrSymPeriodWindowLo OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "symbols"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodWindowHi and
    dot3OamErrSymPeriodWindowLo together form an unsigned 64-bit
    integer representing the number of symbols over which this
    threshold event is defined. This is defined as

    dot3OamErrSymPeriodWindow = ((2^32)*dot3OamErrSymPeriodWindowHi)
                                  + dot3OamErrSymPeriodWindowLo

    If dot3OamErrSymPeriodThreshold symbol errors occur within a
    window of dot3OamErrSymPeriodWindow symbols, an Event
    Notification OAMPDU should be generated with an Errored Symbol
    Period Event TLV indicating that the threshold has been
    crossed in this window.

    The default value for dot3OamErrSymPeriodWindow is the number
    of symbols in one second for the underlying Physical Layer."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.34"
  ::= { dot3OamEventConfigEntry 2 }

dot3OamErrSymPeriodThresholdHi OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "2^32 symbols"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodThresholdHi and
    dot3OamErrSymPeriodThresholdLo together form an unsigned
    64-bit integer representing the minimum number of symbol errors
    occuring within a given window to cause an Errored Symbol Period Event.

    This is defined as

      dot3OamErrSymPeriodThreshold =
                  ((2^32) * dot3OamErrSymPeriodThresholdHi)
                          + dot3OamErrSymPeriodThresholdLo

    If dot3OamErrSymPeriodThreshold symbol errors occur within a
    window of dot3OamErrSymPeriodWindow symbols, an Event
    Notification OAMPDU is generated with an Errored Symbol
    Period Event TLV indicating that the threshold has been
    crossed in this window.

    The default value for dot3OamErrSymPeriodThreshold is one
    symbol errors. If the threshold value is zero, then an Event
    Notification OAMPDU is sent periodically (at the end of every
    window). This can be used as an asynchronous notification to
    the peer OAM entity of the statistics related to this
    threshold crossing alarm."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.34"
  ::= { dot3OamEventConfigEntry 3 }
```

```
dot3OamErrSymPeriodThresholdLo OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "symbols"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodThresholdHi and
    dot3OamErrSymPeriodThresholdLo together form an unsigned
    64-bit integer representing the minimum number of symbol errors
    occuring within a given window to cause an Errored Symbol Period Event.

    This is defined as

      dot3OamErrSymPeriodThreshold =
                        ((2^32) * dot3OamErrSymPeriodThresholdHi)
                                + dot3OamErrSymPeriodThresholdLo

    If dot3OamErrSymPeriodThreshold symbol errors occur within a
    window of dot3OamErrSymPeriodWindow symbols, an Event
    Notification OAMPDU is generated with an Errored Symbol
    Period Event TLV indicating that the threshold has been
    crossed in this window.

    The default value for dot3OamErrSymPeriodThreshold is one
    symbol error. If the threshold value is zero, then an Event
    Notification OAMPDU is sent periodically (at the end of every
    window). This can be used as an asynchronous notification to
    the peer OAM entity of the statistics related to this
    threshold crossing alarm."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.34"
  ::= { dot3OamEventConfigEntry 4 }

dot3OamErrSymPeriodEvNotifEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "If true, the OAM entity sends an Event Notification
    OAMPDU when an Errored Symbol Period Event occurs.

    The default value for this object is true for
    Ethernet-like interfaces that support OAM. If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored."

  ::= { dot3OamEventConfigEntry 5 }

dot3OamErrFramePeriodWindow OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "frames"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The number of frames over which the threshold is defined.
    The default value of the window is the number of minimum size
    Ethernet frames that can be received over the Physical Layer
    in one second.
```

```
          If dot3OamErrFramePeriodThreshold frame errors occur within a
          window of dot3OamErrFramePeriodWindow frames, an Event
          Notification OAMPDU should be generated with an Errored Frame
          Period Event TLV indicating that the threshold has been
          crossed in this window."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.38"
        ::= { dot3OamEventConfigEntry 6 }

      dot3OamErrFramePeriodThreshold OBJECT-TYPE
        SYNTAX      Unsigned32
        UNITS       "frames"
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "The minimum number of frame errors that cause an Errored Frame
          Period Event. The default value is one frame error. If the
          threshold value is zero, then an Event Notification OAMPDU is
          sent periodically (at the end of every window). This can be
          used as an asynchronous notification to the peer OAM entity of
          the statistics related to this threshold crossing alarm.

          If dot3OamErrFramePeriodThreshold frame errors occur within a
          window of dot3OamErrFramePeriodWindow frames, an Event
          Notification OAMPDU is generated with an Errored Frame
          Period Event TLV indicating that the threshold has been
          crossed in this window."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.38"
        ::= { dot3OamEventConfigEntry 7 }

      dot3OamErrFramePeriodEvNotifEnable OBJECT-TYPE
        SYNTAX      TruthValue
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "If true, the OAM entity should send an Event Notification
          OAMPDU when an Errored Frame Period Event occurs.

          By default, this object should have the value true for
          Ethernet-like interfaces that support OAM. If the OAM layer
          does not support Event Notifications (as indicated via the
          dot3OamFunctionsSupported attribute), this value is ignored."

        ::= { dot3OamEventConfigEntry 8 }

      dot3OamErrFrameWindow OBJECT-TYPE
        SYNTAX      Unsigned32
        UNITS       "tenths of a second"
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "The amount of time (in 100 ms increments) over which the
          threshold is defined. The default value is 10 (1 second).

          If dot3OamErrFrameThreshold frame errors occur within a window
          of dot3OamErrFrameWindow seconds (measured in tenths of
          seconds), an Event Notification OAMPDU should be generated
```

```
          with an Errored Frame Event TLV indicating that the threshold
          has been crossed in this window."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.36"
        DEFVAL { 10 }
        ::= { dot3OamEventConfigEntry 9 }

      dot3OamErrFrameThreshold OBJECT-TYPE
        SYNTAX      Unsigned32
        UNITS       "frames"
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "The minimum number of frame errors that cause an Errored Frame
          Event. The default value is one frame error. If the
          threshold value is zero, then an Event Notification OAMPDU is
          sent periodically (at the end of every window). This can be
          used as an asynchronous notification to the peer OAM entity of
          the statistics related to this threshold crossing alarm.

          If dot3OamErrFrameThreshold frame errors occur within a window
          of dot3OamErrFrameWindow (in tenths of seconds), an Event
          Notification OAMPDU is generated with an Errored Frame
          Event TLV indicating the threshold has been crossed in this
          window."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.36"
        DEFVAL { 1 }
        ::= { dot3OamEventConfigEntry 10 }

      dot3OamErrFrameEvNotifEnable OBJECT-TYPE
        SYNTAX      TruthValue
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "If true, the OAM entity should send an Event Notification
          OAMPDU when an Errored Frame Event occurs.

          By default, this object should have the value true for
          Ethernet-like interfaces that support OAM. If the OAM layer
          does not support Event Notifications (as indicated via the
          dot3OamFunctionsSupported attribute), this value is ignored."

        DEFVAL { true }
        ::= { dot3OamEventConfigEntry 11 }

      dot3OamErrFrameSecsSummaryWindow OBJECT-TYPE
        SYNTAX      Integer32 (100..9000)
        UNITS       "tenths of a second"
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "The amount of time (in 100 ms intervals) over which the
          threshold is defined. The default value is 100 (10 seconds).

          If dot3OamErrFrameSecsSummaryThreshold frame errors occur
          within a window of dot3OamErrFrameSecsSummaryWindow (in tenths
          of seconds), an Event Notification OAMPDU should be generated
          with an Errored Frame Seconds Summary Event TLV indicating
```

```
            that the threshold has been crossed in this window."

          REFERENCE   "IEEE Std 802.3, 30.3.6.1.40"
          DEFVAL { 100 }
          ::= { dot3OamEventConfigEntry 12 }

        dot3OamErrFrameSecsSummaryThreshold OBJECT-TYPE
          SYNTAX      Integer32 (1..900)
          UNITS       "errored frame seconds"
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "The minimum number of errored frame seconds that cause an Errored
            Frame Seconds Summary Event. The default value is one errored frame
            second. If the threshold value is zero, then an Event
            Notification OAMPDU is sent periodically (at the end of every
            window). This can be used as an asynchronous notification to
            the peer OAM entity of the statistics related to this
            threshold crossing alarm.

            If dot3OamErrFrameSecsSummaryThreshold frame errors occur
            within a window of dot3OamErrFrameSecsSummaryWindow (in tenths
            of seconds), an Event Notification OAMPDU is generated
            with an Errored Frame Seconds Summary Event TLV indicating
            that the threshold has been crossed in this window."

          REFERENCE   "IEEE Std 802.3, 30.3.6.1.40"
          DEFVAL { 1 }
          ::= { dot3OamEventConfigEntry 13 }

        dot3OamErrFrameSecsEvNotifEnable OBJECT-TYPE
          SYNTAX      TruthValue
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "If true, the local OAM entity sends an Event Notification
            OAMPDU when an Errored Frame Seconds Event occurs.

            The default value for this object is true for
            Ethernet-like interfaces that support OAM. If the OAM layer
            does not support Event Notifications (as indicated via the
            dot3OamFunctionsSupported attribute), this value is ignored."

          DEFVAL { true }
          ::= { dot3OamEventConfigEntry 14 }

        dot3OamDyingGaspEnable OBJECT-TYPE
          SYNTAX      TruthValue
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "If true, the local OAM entity should attempt to indicate a
            dying gasp via the OAMPDU flags field to its peer OAM entity
            when a dying gasp event occurs. The exact definition of a
            dying gasp event is implementation dependent. If the system
            does not support dying gasp capability, setting this object
            has no effect, and reading the object returns ‘false’.

            The default value for this object is true for
```

```
      Ethernet-like interfaces that support OAM. If the OAM layer
      does not support Event Notifications (as indicated via the
      dot3OamFunctionsSupported attribute), this value is ignored."

    DEFVAL { true }
    ::= { dot3OamEventConfigEntry 15 }

  dot3OamCriticalEventEnable OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "If true, the local OAM entity should attempt to indicate a
      critical event via the OAMPDU flags to its peer OAM entity
      when a critical event occurs. The exact definition of a
      critical event is implementation dependent. If the system
      does not support critical event capability, setting this
      object has no effect, and reading the object should
      result in ‘false’.

      By default, this object should have the value true for
      Ethernet-like interfaces that support OAM. If the OAM layer
      does not support Event Notifications (as indicated via the
      dot3OamFunctionsSupported attribute), this value is ignored."

    DEFVAL { true }
    ::= { dot3OamEventConfigEntry 16 }

  -- **************************************************************
  --
  -- Ethernet OAM Event Log group
  --

  dot3OamEventLogTable OBJECT-TYPE
    SYNTAX       SEQUENCE OF Dot3OamEventLogEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
      "This table records a history of the events that have occurred
      at the Ethernet OAM level. These events can include locally
      detected events, which may result in locally generated
      OAMPDUs, and remotely detected events, which are detected by
      the OAM peer entity and signaled to the local entity via
      Ethernet OAM. Ethernet OAM events can be signaled by Event
      Notification OAMPDUs or by the flags field in any OAMPDU.

      This table contains both threshold crossing events and
      non-threshold crossing events. The parameters for the
      threshold window, threshold value, and actual value
      (dot3OamEventLogWindowXX, dot3OamEventLogThresholdXX,
      dot3OamEventLogValue) are only applicable to threshold
      crossing events, and are returned as all F’s (2^32 - 1) for
      non-threshold crossing events.

      Entries in the table are automatically created when such
      events are detected. The size of the table is implementation
      dependent. When the table reaches its maximum size, older
      entries are automatically deleted to make room for newer
      entries."
```

```
    ::= { dot3OamObjects 6 }

dot3OamEventLogEntry OBJECT-TYPE
  SYNTAX      Dot3OamEventLogEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the dot3OamEventLogTable. Entries are
    automatically created whenever Ethernet OAM events occur at
    the local OAM entity, and when Event Notification OAMPDUs are
    received at the local OAM entity (indicating that events have
    occurred at the peer OAM entity). The size of the table is
    implementation dependent, but when the table becomes full,
    older events are automatically deleted to make room for newer
    events. The table index dot3OamEventLogIndex increments for
    each new entry, and when the maximum value is reached, the
    value restarts at zero."

  INDEX       { ifIndex, dot3OamEventLogIndex }
  ::= { dot3OamEventLogTable 1 }

Dot3OamEventLogEntry ::=
  SEQUENCE {
    dot3OamEventLogIndex                Unsigned32,
    dot3OamEventLogTimestamp            TimeStamp,
    dot3OamEventLogOui                  EightOTwoOui,
    dot3OamEventLogType                 Unsigned32,
    dot3OamEventLogLocation             INTEGER,
    dot3OamEventLogWindowHi             Unsigned32,
    dot3OamEventLogWindowLo             Unsigned32,
    dot3OamEventLogThresholdHi          Unsigned32,
    dot3OamEventLogThresholdLo          Unsigned32,
    dot3OamEventLogValue                CounterBasedGauge64,
    dot3OamEventLogRunningTotal         CounterBasedGauge64,
    dot3OamEventLogEventTotal           Unsigned32
  }

dot3OamEventLogIndex       OBJECT-TYPE
  SYNTAX      Unsigned32(1..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An arbitrary integer for identifying individual events
    within the event log."
  ::= { dot3OamEventLogEntry 1 }

dot3OamEventLogTimestamp  OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The value of sysUpTime at the time of the logged event. For
    locally generated events, the time of the event can be
    accurately retrieved from sysUpTime. For remotely generated
    events, the time of the event is indicated by the reception of
    the Event Notification OAMPDU indicating that the event
    occurred on the peer. A system may attempt to adjust the
    timestamp value to more accurately reflect the time of the
```

```
          event at the peer OAM entity by using other information, such
          as that found in the timestamp found of the Event Notification
          TLVs, which provides an indication of the relative time
          between events at the peer entity."
        ::= { dot3OamEventLogEntry 2 }

      dot3OamEventLogOui  OBJECT-TYPE
        SYNTAX      EightOTwoOui
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "The OUI of the entity defining the object type. All IEEE
          802.3 defined events (as appearing in IEEE Std 802.3 except for the
          Organizationally Unique Event TLVs) use the IEEE 802.3 OUI of
          0x0180C2. Organizations defining their own Event Notification
          TLVs include their OUI in the Event Notification TLV that
          gets reflected here."
        ::= { dot3OamEventLogEntry 3 }

      dot3OamEventLogType      OBJECT-TYPE
        SYNTAX      Unsigned32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "The type of event that generated this entry in the event log.
          When the OUI is the IEEE 802.3 OUI of 0x0180C2, the following
          event types are defined:
              erroredSymbolEvent(1),
              erroredFramePeriodEvent(2),
              erroredFrameEvent(3),
              erroredFrameSecondsEvent(4),
              linkFault(256),
              dyingGaspEvent(257),
              criticalLinkEvent(258)
          The first four are considered threshold crossing events, as
          they are generated when a metric exceeds a given value within
          a specified window. The other three are not threshold
          crossing events.

          When the OUI is not 71874 (0x0180C2 in hex), then some other
          organization has defined the event space. If event subtyping
          is known to the implementation, it may be reflected here.
          Otherwise, this value should return all F’s (2^32 - 1)."

        REFERENCE   "IEEE Std 802.3, 30.3.6.1.10 and 57.5.3."
        ::= { dot3OamEventLogEntry 4 }

      dot3OamEventLogLocation OBJECT-TYPE
        SYNTAX      INTEGER { local(1), remote(2) }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "Whether this event occurred locally (local(1)), or was
          received from the OAM peer via Ethernet OAM (remote(2))."

        ::= { dot3OamEventLogEntry 5 }

      dot3OamEventLogWindowHi      OBJECT-TYPE
        SYNTAX      Unsigned32
```

```
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "If the event represents a threshold crossing event, the two
      objects dot3OamEventWindowHi and dot3OamEventWindowLo, form
      an unsigned 64-bit integer yielding the window over which the
      value was measured for the threshold crossing event (for
      example, 5, when 11 occurrences happened in 5 seconds while
      the threshold was 10). The two objects are combined as:
      dot3OamEventLogWindow = ((2^32) * dot3OamEventLogWindowHi)
                                      + dot3OamEventLogWindowLo

      Otherwise, this value is returned as all F’s (2^32 - 1) and
      adds no useful information."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.37 and 57.5.3.2."
    ::= { dot3OamEventLogEntry 6 }

  dot3OamEventLogWindowLo      OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "If the event represents a threshold crossing event, the two
      objects dot3OamEventWindowHi and dot3OamEventWindowLo form an
      unsigned 64-bit integer yielding the window over which the
      value was measured for the threshold crossing event (for
      example, 5, when 11 occurrences happened in 5 seconds while
      the threshold was 10). The two objects are combined as:

      dot3OamEventLogWindow = ((2^32) * dot3OamEventLogWindowHi)
                                      + dot3OamEventLogWindowLo

      Otherwise, this value is returned as all F’s (2^32 - 1) and
      adds no useful information."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.37 and 57.5.3.2."
    ::= { dot3OamEventLogEntry 7 }

  dot3OamEventLogThresholdHi      OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "If the event represents a threshold crossing event, the two
      objects dot3OamEventThresholdHi and dot3OamEventThresholdLo
      form an unsigned 64-bit integer yielding the value that was
      crossed for the threshold crossing event (for example, 10,
      when 11 occurrences happened in 5 seconds while the threshold
      was 10). The two objects are combined as:

    dot3OamEventLogThreshold = ((2^32) * dot3OamEventLogThresholdHi)
                                       + dot3OamEventLogThresholdLo

      Otherwise, this value is returned as all F’s (2^32 -1) and
      adds no useful information."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.37 and 57.5.3.2."
    ::= { dot3OamEventLogEntry 8 }
```

```
dot3OamEventLogThresholdLo      OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "If the event represents a threshold crossing event, the two
    objects dot3OamEventThresholdHi and dot3OamEventThresholdLo
    form an unsigned 64-bit integer yielding the value that was
    crossed for the threshold crossing event (for example, 10,
    when 11 occurrences happened in 5 seconds while the threshold
    was 10). The two objects are combined as:

  dot3OamEventLogThreshold = ((2^32) * dot3OamEventLogThresholdHi)
                                   + dot3OamEventLogThresholdLo

    Otherwise, this value is returned as all F’s (2^32 - 1) and
    adds no useful information."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 9 }

dot3OamEventLogValue      OBJECT-TYPE
  SYNTAX      CounterBasedGauge64
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "If the event represents a threshold crossing event, this
    value indicates the value of the parameter within the given
    window that generated this event (for example, 11, when 11
    occurrences happened in 5 seconds while the threshold was 10).

    Otherwise, this value is returned as all F’s
    (2^64 - 1) and adds no useful information."

  REFERENCE   "IEEE Std 802.3, 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 10 }

dot3OamEventLogRunningTotal      OBJECT-TYPE
  SYNTAX      CounterBasedGauge64
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "Each Event Notification TLV contains a running total of the
    number of times an event has occurred, as well as the number
    of times an Event Notification for the event has been
    transmitted. For non-threshold crossing events, the number of
    events (dot3OamLogRunningTotal) and the number of resultant
    Event Notifications (dot3OamLogEventTotal) should be
    identical.

    For threshold crossing events, since multiple occurrences may
    be required to cross the threshold, these values are likely
    different. This value represents the total number of times
    this event has happened since the last reset (for example,
    3253, when 3253 symbol errors have occurred since the last
    reset, which has resulted in 51 symbol error threshold
    crossing events since the last reset)."
```

```
    REFERENCE   "IEEE Std 802.3, 30.3.6.1.37 and 57.5.3.2."
    ::= { dot3OamEventLogEntry 11 }

  dot3OamEventLogEventTotal      OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "Each Event Notification TLV contains a running total of the
      number of times an event has occurred, as well as the number
      of times an Event Notification for the event has been
      transmitted. For non-threshold crossing events, the number of
      events (dot3OamLogRunningTotal) and the number of resultant
      Event Notifications (dot3OamLogEventTotal) should be
      identical.

      For threshold crossing events, since multiple occurrences may
      be required to cross the threshold, these values are likely
      different. This value represents the total number of times
      one or more of these occurrences have resulted in an Event
      Notification (for example, 51 when 3253 symbol errors have
      occurred since the last reset, which has resulted in 51 symbol
      error threshold crossing events since the last reset)."

    REFERENCE   "IEEE Std 802.3, 30.3.6.1.37 and 57.5.3.2."
    ::= { dot3OamEventLogEntry 12 }

  -- ***************************************************************
  --
  -- Ethernet OAM Notifications
  --

  dot3OamThresholdEvent NOTIFICATION-TYPE
    OBJECTS { dot3OamEventLogTimestamp,
              dot3OamEventLogOui,
              dot3OamEventLogType,
              dot3OamEventLogLocation,
              dot3OamEventLogWindowHi,
              dot3OamEventLogWindowLo,
              dot3OamEventLogThresholdHi,
              dot3OamEventLogThresholdLo,
              dot3OamEventLogValue,
              dot3OamEventLogRunningTotal,
              dot3OamEventLogEventTotal
            }
    STATUS  current
    DESCRIPTION
      "A dot3OamThresholdEvent notification is sent when a local or
      remote threshold crossing event is detected. A local
      threshold crossing event is detected by the local entity,
      while a remote threshold crossing event is detected by the
      reception of an Ethernet OAM Event Notification OAMPDU
      that indicates a threshold event.

      This notification should not be sent more than once per
      second.

      The OAM entity can be derived from extracting the ifIndex from
      the variable bindings. The objects in the notification
```

```
      correspond to the values in a row instance in the
      dot3OamEventLogTable.

      The management entity should periodically check
      dot3OamEventLogTable to detect any missed events."
   ::= { dot3OamNotifications 1 }

  dot3OamNonThresholdEvent NOTIFICATION-TYPE
    OBJECTS { dot3OamEventLogTimestamp,
              dot3OamEventLogOui,
              dot3OamEventLogType,
              dot3OamEventLogLocation,
              dot3OamEventLogEventTotal
            }
    STATUS  current
    DESCRIPTION
      "A dot3OamNonThresholdEvent notification is sent when a local
      or remote non-threshold crossing event is detected. A local
      event is detected by the local entity, while a remote event is
      detected by the reception of an Ethernet OAM Event
      Notification OAMPDU that indicates a non-threshold crossing
      event.

      This notification should not be sent more than once per
      second.

      The OAM entity can be derived from extracting the ifIndex from
      the variable bindings. The objects in the notification
      correspond to the values in a row instance of the
      dot3OamEventLogTable.

      The management entity should periodically check
      dot3OamEventLogTable to detect any missed events."
   ::= { dot3OamNotifications 2 }

  -- ***************************************************************
  --
  -- Conformance statements
  --

  dot3OamGroups OBJECT IDENTIFIER ::= { dot3OamConformance 1 }
  dot3OamCompliances OBJECT IDENTIFIER ::= { dot3OamConformance 2 }

  -- Compliance statements

  dot3OamCompliance MODULE-COMPLIANCE
    STATUS          current
    DESCRIPTION "The compliance statement for managed entities
                 supporting OAM on Ethernet-like interfaces."

  MODULE   -- this module
    MANDATORY-GROUPS { dot3OamControlGroup,
                       dot3OamPeerGroup,
                       dot3OamStatsBaseGroup
                     }

    GROUP       dot3OamLoopbackGroup
    DESCRIPTION
      "This group is mandatory for all IEEE 802.3 OAM
```

```
          implementations that support loopback functionality."

        GROUP       dot3OamErrSymbolPeriodEventGroup
        DESCRIPTION
          "This group is mandatory for all IEEE 802.3 OAM
          implementations that support event functionality."

        GROUP       dot3OamErrFramePeriodEventGroup
        DESCRIPTION
          "This group is mandatory for all IEEE 802.3 OAM
          implementations that support event functionality."

        GROUP       dot3OamErrFrameEventGroup
        DESCRIPTION
          "This group is mandatory for all IEEE 802.3 OAM
          implementations that support event functionality."

        GROUP       dot3OamErrFrameSecsSummaryEventGroup
        DESCRIPTION
          "This group is mandatory for all IEEE 802.3 OAM
          implementations that support event functionality."

        GROUP        dot3OamFlagEventGroup
        DESCRIPTION
          "This group is optional for all IEEE 802.3 OAM
          implementations. The ability to send critical events or dying
          gasp events is not required in any system."

        GROUP       dot3OamEventLogGroup
        DESCRIPTION
          "This group is optional for all IEEE 802.3 OAM
          implementations. Entries in this table are dependent on what
          event functionality is supported in the local OAM
          implementation. At least one type of event shall be supported
          for entries to appear in this table."

        GROUP       dot3OamNotificationGroup
        DESCRIPTION
          "This group is optional for all IEEE 802.3 OAM
          implementations. Since the information in the notifications
          is dependent on the dot3OamEventLogTable, that table shall be
          implemented for notifications."

        ::= { dot3OamCompliances 1}

     dot3OamControlGroup OBJECT-GROUP
        OBJECTS     {   dot3OamAdminState,
                        dot3OamOperStatus,
                        dot3OamMode,
                        dot3OamMaxOamPduSize,
                        dot3OamConfigRevision,
                        dot3OamFunctionsSupported
                    }
        STATUS      current
        DESCRIPTION
          "A collection of objects providing the abilities,
          configuration, and status of an Ethernet OAM entity."
        ::= { dot3OamGroups 1 }
```

```
dot3OamPeerGroup OBJECT-GROUP
   OBJECTS     {   dot3OamPeerMacAddress,
                   dot3OamPeerVendorOui,
                   dot3OamPeerVendorInfo,
                   dot3OamPeerMode,
                   dot3OamPeerFunctionsSupported,
                   dot3OamPeerMaxOamPduSize,
                   dot3OamPeerConfigRevision
               }
   STATUS      current
   DESCRIPTION
     "A collection of objects providing the abilities,
     configuration, and status of a peer Ethernet OAM entity."
   ::= { dot3OamGroups 2 }

dot3OamStatsBaseGroup OBJECT-GROUP
   OBJECTS     {   dot3OamInformationTx,
                   dot3OamInformationRx,
                   dot3OamUniqueEventNotificationTx,
                   dot3OamUniqueEventNotificationRx,
                   dot3OamDuplicateEventNotificationTx,
                   dot3OamDuplicateEventNotificationRx,
                   dot3OamLoopbackControlTx,
                   dot3OamLoopbackControlRx,
                   dot3OamVariableRequestTx,
                   dot3OamVariableRequestRx,
                   dot3OamVariableResponseTx,
                   dot3OamVariableResponseRx,
                   dot3OamOrgSpecificTx,
                   dot3OamOrgSpecificRx,
                   dot3OamUnsupportedCodesTx,
                   dot3OamUnsupportedCodesRx,
                   dot3OamFramesLostDueToOam
               }
   STATUS      current
   DESCRIPTION
     "A collection of objects providing the statistics for the
     number of various transmit and receive events for OAM on an
     Ethernet-like interface. Note that all of these counters shall
     be supported even if the related function (as described in
     dot3OamFunctionsSupported) is not supported."
   ::= { dot3OamGroups 3 }

dot3OamLoopbackGroup OBJECT-GROUP
   OBJECTS     {   dot3OamLoopbackStatus,
                   dot3OamLoopbackIgnoreRx
               }
   STATUS      current
   DESCRIPTION
     "A collection of objects for controlling the OAM remote
     loopback function."
   ::= { dot3OamGroups 4 }

dot3OamErrSymbolPeriodEventGroup OBJECT-GROUP
   OBJECTS     {   dot3OamErrSymPeriodWindowHi,
                   dot3OamErrSymPeriodWindowLo,
                   dot3OamErrSymPeriodThresholdHi,
                   dot3OamErrSymPeriodThresholdLo,
                   dot3OamErrSymPeriodEvNotifEnable
```

```
                 }
        STATUS      current
        DESCRIPTION
          "A collection of objects for configuring the thresholds for an
          Errored Symbol Period Event.

          Each IEEE Std 802.3 defined Event Notification TLV has its own
          conformance group because each event can be implemented
          independently of any other."
        ::= { dot3OamGroups 5 }

     dot3OamErrFramePeriodEventGroup OBJECT-GROUP
        OBJECTS     {   dot3OamErrFramePeriodWindow,
                        dot3OamErrFramePeriodThreshold,
                        dot3OamErrFramePeriodEvNotifEnable
                    }
        STATUS      current
        DESCRIPTION
          "A collection of objects for configuring the thresholds for an
          Errored Frame Period Event.

          Each IEEE Std 802.3 defined Event Notification TLV has its own
          conformance group because each event can be implemented
          independently of any other."
        ::= { dot3OamGroups 6 }

     dot3OamErrFrameEventGroup OBJECT-GROUP
        OBJECTS     {   dot3OamErrFrameWindow,
                        dot3OamErrFrameThreshold,
                        dot3OamErrFrameEvNotifEnable
                    }
        STATUS      current
        DESCRIPTION
          "A collection of objects for configuring the thresholds for an
          Errored Frame Event.

          Each IEEE Std 802.3 defined Event Notification TLV has its own
          conformance group because each event can be implemented
          independently of any other."
        ::= { dot3OamGroups 7 }

     dot3OamErrFrameSecsSummaryEventGroup OBJECT-GROUP
        OBJECTS     {   dot3OamErrFrameSecsSummaryWindow,
                        dot3OamErrFrameSecsSummaryThreshold,
                        dot3OamErrFrameSecsEvNotifEnable
                    }
        STATUS      current
        DESCRIPTION
          "A collection of objects for configuring the thresholds for an
          Errored Frame Seconds Summary Event.

          Each IEEE Std 802.3 defined Event Notification TLV has its own
          conformance group because each event can be implemented
          independently of any other."
        ::= { dot3OamGroups 8 }

     dot3OamFlagEventGroup OBJECT-GROUP
        OBJECTS     {   dot3OamDyingGaspEnable,
                        dot3OamCriticalEventEnable
```

```
                 }
        STATUS      current
        DESCRIPTION
          "A collection of objects for configuring the sending OAMPDUs
          with the critical event flag or dying gasp flag enabled."
        ::= { dot3OamGroups 9 }

     dot3OamEventLogGroup OBJECT-GROUP
       OBJECTS {  dot3OamEventLogTimestamp,
                  dot3OamEventLogOui,
                  dot3OamEventLogType,
                  dot3OamEventLogLocation,
                  dot3OamEventLogWindowHi,
                  dot3OamEventLogWindowLo,
                  dot3OamEventLogThresholdHi,
                  dot3OamEventLogThresholdLo,
                  dot3OamEventLogValue,
                  dot3OamEventLogRunningTotal,
                  dot3OamEventLogEventTotal
                }
       STATUS      current
       DESCRIPTION
          "A collection of objects for configuring the thresholds for an
          Errored Frame Seconds Summary Event and maintaining the event
          information."
        ::= { dot3OamGroups 10 }

     dot3OamNotificationGroup NOTIFICATION-GROUP
       NOTIFICATIONS {
                   dot3OamThresholdEvent,
                   dot3OamNonThresholdEvent
                     }
       STATUS      current
       DESCRIPTION
         "A collection of notifications used by Ethernet OAM to signal
         to a management entity that local or remote events have
         occurred on a specified Ethernet link."
       ::= { dot3OamGroups 11 }

      END
```

7. Ethernet repeater device MIB module

7.1 Overview

This clause defines a portion of the MIB for use with SNMP. In particular, it defines objects for managing IEEE 802.3 repeaters.

7.1.1 Repeater management

Instances of the object types defined in this clause represent attributes of an IEEE 802.3 (Ethernet-like) repeater, as defined by Clause 9 and Clause 27 of IEEE Std 802.3. Implementors of these MIB objects should note that IEEE Std 802.3 explicitly describes when, where, and how various repeater attributes are measured. IEEE Std 802.3 also describes the effects of repeater actions that may be invoked by manipulating instances of the MIB objects defined here. The definitions presented here are based on 30.4 of IEEE Std 802.3. The counters in this clause are defined to be the same as the counters defined in IEEE Std 802.3, with the intention that the same instrumentation can be used to implement both standards.

These repeater MIB module objects may be used to manage non-standard repeater-like devices; however, defining objects to describe implementation-specific properties of non-standard repeater-like devices is outside the scope of this standard.

7.1.2 Structure of the MIB

Objects in this MIB module are arranged into packages, each of which contains a set of related objects within a broad functional category. Objects within a package are generally defined under the same OID subtree. These packages are intended for organizational convenience only and have no relation to the conformance groups defined later in the document.

7.1.2.1 Basic definitions

The basic definitions include objects that are applicable to all repeaters: status, parameter, and control objects for each repeater within the managed system, for the port groups within the system, and for the individual ports themselves.

7.1.2.2 Monitor definitions

The monitor definitions include monitoring statistics for each repeater within the system and for individual ports.

7.1.2.3 Address tracking definitions

This collection includes objects for tracking the MAC addresses of the DTEs attached to the ports within the system and for mapping the topology of a network.

7.1.2.4 Top N definitions

These objects may be used for tracking the ports with the most activity within the system or within particular repeaters.

7.1.3 Relationship to MIB-II

It is assumed that a repeater implementing this MIB will also implement (at least) the “system” group defined in IETF RFC 1213 (MIB-II).

7.1.3.1 Relationship to the "system" group

In MIB-II, the "system" group is defined as being mandatory for all systems such that each managed entity contains one instance of each object in the "system" group. Thus, those objects apply to the entity even if the entity's sole functionality is management of repeaters.

7.1.3.2 Relationship to the "interfaces" group

In MIB-II, the "interfaces" group is defined as being mandatory for all systems and contains information on an entity's interfaces, where each interface is thought of as being attached to a "subnetwork." (Note that this term is not to be confused with "subnet," which refers to an addressing partitioning scheme used in the Internet suite of protocols.)

This repeater MIB module uses the notion of ports on a repeater. The concept of a MIB-II interface has no specific relationship to a repeater's port. Therefore, the "interfaces" group applies only to the one (or more) network interfaces on which the entity managing the repeater sends and receives management protocol operations, and does not apply to the repeater's ports. This is consistent with the physical-layer nature of a repeater. A repeater-unit is a bitwise store-and-forward device. A repeater port has no MAC address, no MAC implementation, and does not pass packets up to higher level protocol entities for processing.

NOTE—When a network management entity is observing a repeater, it may appear as though the repeater is passing packets to a higher level protocol entity. However, this is only a means of implementing management, and this passing of management information is not part of the repeater functionality.[13]

7.2 Topology mapping

Network topology mapping is described in section 4 of IETF RFC 2108 [B20].

7.3 MIB module definition

An ASCII text version of the MIB definition can be found at the following URL[14]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C7mib.txt

[13]Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

[14]Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.

```
IEEE8023-SNMP-REPEATER-MIB DEFINITIONS ::= BEGIN

IMPORTS
    Counter32, Counter64, Integer32, Gauge32,
    OBJECT-TYPE, MODULE-IDENTITY, NOTIFICATION-TYPE, org
        FROM SNMPv2-SMI
    TimeStamp, MacAddress, TEXTUAL-CONVENTION,
    RowStatus, TestAndIncr
        FROM SNMPv2-TC
    OBJECT-GROUP, MODULE-COMPLIANCE, NOTIFICATION-GROUP
        FROM SNMPv2-CONF
    OwnerString
        FROM RFC1271-MIB;


ieee8023snmpRptrMIB MODULE-IDENTITY
     LAST-UPDATED "201304110000Z" -- April 11, 2013
     ORGANIZATION
       "IEEE 802.3 working group"
     CONTACT-INFO
         "WG-URL: http://www.ieee802.org/3/index.html
         WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

         Contact: Howard Frazier
         Postal:  3151 Zanker Road
                  San Jose, CA 95134
                  USA
         Tel:     +1.408.922.8164
         E-mail:  hfrazier@broadcom.com"
    DESCRIPTION
        "Management information for IEEE 802.3 repeaters."

    REVISION    "201304110000Z" -- April 11, 2013
    DESCRIPTION
        "Revision, based on an earlier version in IEEE Std 802.3.1-2011."

    REVISION "201102020000Z" -- February 2, 2011
    DESCRIPTION
        "Initial revision, based on an earlier version in RFC 2108"


    ::= { org ieee(111) standards-association-numbers-series-standards(2)
          lan-man-stds(802) ieee802dot3(3) ieee802dot3dot1mibs(1) 7 }

ieee8023snmpDot3RptrMgt OBJECT IDENTIFIER ::= { ieee8023snmpRptrMIB 1}

OptMacAddr ::= TEXTUAL-CONVENTION
    DISPLAY-HINT    "1x:"
    STATUS          current
    DESCRIPTION
        "Either a 6 octet address in the ‘canonical’
        order defined by IEEE Std 802.1a, i.e., as if it
        were transmitted least significant bit first
        if a value is available or a zero length string."
    REFERENCE
        "See MacAddress in SNMPv2-TC. The only difference
        is that a zero length string is allowed as a value
        for OptMacAddr and not for MacAddress."
    SYNTAX OCTET STRING (SIZE (0 | 6))
```

```
-- Basic information at the repeater, group, and port level.

rptrBasicPackage
    OBJECT IDENTIFIER ::= { ieee8023snmpDot3RptrMgt 1 }
  rptrGroupInfo
        OBJECT IDENTIFIER ::= { rptrBasicPackage 1 }
  rptrPortInfo
        OBJECT IDENTIFIER ::= { rptrBasicPackage 2 }
  rptrAllRptrInfo
        OBJECT IDENTIFIER ::= { rptrBasicPackage 3 }

-- Monitoring information at the repeater, group, and port level.
rptrMonitorPackage
    OBJECT IDENTIFIER ::= { ieee8023snmpDot3RptrMgt 2 }
  rptrMonitorRptrInfo
        OBJECT IDENTIFIER ::= { rptrMonitorPackage 1 }
  rptrMonitorGroupInfo
        OBJECT IDENTIFIER ::= { rptrMonitorPackage 2 }
  rptrMonitorPortInfo
        OBJECT IDENTIFIER ::= { rptrMonitorPackage 3 }
  rptrMonitorAllRptrInfo
        OBJECT IDENTIFIER ::= { rptrMonitorPackage 4 }

-- Address tracking information at the repeater, group,
-- and port level.
rptrAddrTrackPackage
    OBJECT IDENTIFIER ::= { ieee8023snmpDot3RptrMgt 3 }
  rptrAddrTrackRptrInfo
        OBJECT IDENTIFIER ::= { rptrAddrTrackPackage 1 }
  rptrAddrTrackGroupInfo
        -- this subtree is currently unused
        OBJECT IDENTIFIER ::= { rptrAddrTrackPackage 2 }
  rptrAddrTrackPortInfo
        OBJECT IDENTIFIER ::= { rptrAddrTrackPackage 3 }

-- TopN information.
rptrTopNPackage
        OBJECT IDENTIFIER ::= { ieee8023snmpDot3RptrMgt 4 }
  rptrTopNRptrInfo
        -- this subtree is currently unused
        OBJECT IDENTIFIER ::= { rptrTopNPackage 1 }
  rptrTopNGroupInfo
        -- this subtree is currently unused
        OBJECT IDENTIFIER ::= { rptrTopNPackage 2 }
  rptrTopNPortInfo
        OBJECT IDENTIFIER ::= { rptrTopNPackage 3 }

-- Basic information at the group level.
--
-- Configuration and status objects for each
-- managed group in the repeater system, independent
-- of whether there is one or more managed
-- repeater-units in the repeater system.

rptrGroupTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RptrGroupEntry
```

```
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "Table of descriptive and status information about
                the groups of ports."
        ::= { rptrGroupInfo 1 }

    rptrGroupEntry OBJECT-TYPE
        SYNTAX      RptrGroupEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "An entry in the table, containing information
                about a single group of ports."
        INDEX    { rptrGroupIndex }
        ::= { rptrGroupTable 1 }

    RptrGroupEntry ::=
        SEQUENCE {
            rptrGroupIndex
                Integer32,
            rptrGroupObjectID
                OBJECT IDENTIFIER,
            rptrGroupOperStatus
                INTEGER,
            rptrGroupPortCapacity
                Integer32
        }

    rptrGroupIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "This object identifies the group within the
                repeater system for which this entry contains
                information."
        REFERENCE
                "IEEE Std 802.3, 30.4.2.1.1, aGroupID."
        ::= { rptrGroupEntry 1 }

    rptrGroupObjectID OBJECT-TYPE
        SYNTAX      OBJECT IDENTIFIER
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The vendor’s authoritative identification of the
                group. This value may be allocated within the SMI
                enterprises subtree (1.3.6.1.4.1) and provides a
                straight-forward and unambiguous means for
                determining what kind of group is being managed.

                For example, this object could take the value
                1.3.6.1.4.1.4242.1.2.14 if vendor ‘Flintstones,
                Inc.’ was assigned the subtree 1.3.6.1.4.1.4242,
                and had assigned the identifier
                1.3.6.1.4.1.4242.1.2.14 to its ‘Wilma Flintstone
                6-Port FOIRL Plug-in module.’"
        ::= { rptrGroupEntry 2 }
```

```
rptrGroupOperStatus OBJECT-TYPE
    SYNTAX      INTEGER {
                  other(1),
                  operational(2),
                  malfunctioning(3),
                  notPresent(4),
                  underTest(5),
                  resetInProgress(6)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "An object that indicates the operational status
            of the group.

            A status of notPresent(4) indicates that the group
            is temporarily or permanently physically and/or
            logically not a part of the repeater. It is an
            implementation-specific matter as to whether the
            agent effectively removes notPresent entries from
            the table.

            A status of operational(2) indicates that the
            group is functioning, and a status of
            malfunctioning(3) indicates that the group is
            malfunctioning in some way."
    ::= { rptrGroupEntry 3 }

rptrGroupPortCapacity OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The rptrGroupPortCapacity is the number of ports
            that can be contained within the group. Valid
            range is 1-2147483647. Within each group, the
            ports are uniquely numbered in the range from 1 to
            rptrGroupPortCapacity.

            Some ports may not be present in the repeater system, in
            which case the actual number of ports present
            will be less than the value of rptrGroupPortCapacity.
            The number of ports present in the group will never
            be greater than the value of rptrGroupPortCapacity.

            Note:  In practice, this will generally be the
            number of ports on a module, card, or board, and
            the port numbers will correspond to numbers marked
            on the physical embodiment."
    REFERENCE
            "IEEE Std 802.3, 30.4.2.1.2, aGroupPortCapacity."
    ::= { rptrGroupEntry 4 }


-- Basic information at the port level.
--
-- Configuration and status objects for
-- each managed repeater port in the repeater system,
```

```
-- independent of whether there is one or more
-- managed repeater-units in the repeater system.

rptrPortTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RptrPortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "Table of descriptive and status information about
            the repeater ports in the repeater system. The number of
            entries is independent of the number of repeaters
            in the managed repeater system."
    ::= { rptrPortInfo 1 }

rptrPortEntry OBJECT-TYPE
    SYNTAX      RptrPortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "An entry in the table, containing information
            about a single port."

    INDEX    { rptrPortGroupIndex, rptrPortIndex }
    ::= { rptrPortTable 1 }

RptrPortEntry ::=
    SEQUENCE {
        rptrPortGroupIndex
            Integer32,
        rptrPortIndex
            Integer32,
        rptrPortAdminStatus
            INTEGER,
        rptrPortAutoPartitionState
            INTEGER,
        rptrPortOperStatus
            INTEGER,
        rptrPortRptrId
            Integer32
    }

rptrPortGroupIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "This object identifies the group containing the
            port for which this entry contains information."
    ::= { rptrPortEntry 1 }

rptrPortIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "This object identifies the port within the group
            for which this entry contains information. This
            identifies the port independently from the repeater
            to which it may be attached. The numbering scheme for
```

```
                ports is implementation specific; however, this
                value can never be greater than
                rptrGroupPortCapacity for the associated group."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.1, aPortID."
        ::= { rptrPortEntry 2 }

    rptrPortAdminStatus OBJECT-TYPE
        SYNTAX      INTEGER {
                      enabled(1),
                      disabled(2)
                    }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
                "Setting this object to disabled(2) disables the
                port. A disabled port neither transmits nor
                receives. Once disabled, a port shall be
                explicitly enabled to restore operation. A port
                that is disabled when power is lost or when a
                reset is exerted shall remain disabled when normal
                operation resumes.

                The admin status takes precedence over auto-
                partition and functionally operates between the
                auto-partition mechanism and the AUI/PMA.

                Setting this object to enabled(1) enables the port
                and exerts a BEGIN on the port’s auto-partition
                state machine.

                (In effect, when a port is disabled, the value of
                rptrPortAutoPartitionState for that port is frozen
                until the port is next enabled. When the port
                becomes enabled, the rptrPortAutoPartitionState
                becomes notAutoPartitioned(1), regardless of its
                pre-disabling state.)"
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.2, aPortAdminState
                and 30.4.3.2.1, acPortAdminControl."
        ::= { rptrPortEntry 3 }

    rptrPortAutoPartitionState OBJECT-TYPE
        SYNTAX      INTEGER {
                      notAutoPartitioned(1),
                      autoPartitioned(2)
                    }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The autoPartitionState flag indicates whether the
                port is currently partitioned by the repeater’s
                auto-partition protection.

                The conditions that cause port partitioning are
                specified in partition state machine in Clauses
                9 and 27 of IEEE Std 802.3. They are not
                differentiated here."
        REFERENCE
```

```
                "IEEE Std 802.3, 30.4.3.1.3, aAutoPartitionState."
        ::= { rptrPortEntry 4 }

    rptrPortOperStatus  OBJECT-TYPE
        SYNTAX      INTEGER {
                      operational(1),
                      notOperational(2),
                      notPresent(3)
                    }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This object indicates the port's operational
                status. The notPresent(3) status indicates the
                port is physically removed (note this may or may
                not be possible depending on the type of port.)
                The operational(1) status indicates that the port
                is enabled (see rptrPortAdminStatus) and working,
                even though it might be auto-partitioned (see
                rptrPortAutoPartitionState).

                If this object has the value operational(1) and
                rptrPortAdminStatus is set to disabled(2), it is
                expected that this object's value will soon change
                to notOperational(2)."
        ::= { rptrPortEntry 5 }

    rptrPortRptrId OBJECT-TYPE
        SYNTAX      Integer32 (0..2147483647)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This object identifies the repeater to
                which this port belongs. The repeater
                identified by a particular value of this object
                is the same as that identified by the same
                value of rptrInfoId. A value of zero
                indicates that this port currently is not
                a member of any repeater."
        ::= { rptrPortEntry 6 }


    -- New version of basic information at the repeater level.
    --
    -- Configuration, status, and control objects for
    -- each managed repeater in the repeater system.

    rptrInfoTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF RptrInfoEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "A table of information about each
                non-trivial repeater. The number of entries
                depends on the physical configuration of the
                managed repeater system."
        ::= { rptrAllRptrInfo 1 }

    rptrInfoEntry OBJECT-TYPE
```

```
        SYNTAX      RptrInfoEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "An entry in the table, containing information
                about a single non-trivial repeater."
        INDEX    { rptrInfoId }
        ::= { rptrInfoTable 1 }

    RptrInfoEntry ::=
        SEQUENCE {
            rptrInfoId
                Integer32,
            rptrInfoRptrType
                INTEGER,
            rptrInfoOperStatus
                INTEGER,
            rptrInfoReset
                INTEGER,
            rptrInfoPartitionedPorts
                Gauge32,
            rptrInfoLastChange
                TimeStamp
        }

    rptrInfoId OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "This object identifies the repeater for which
                this entry contains information."
        ::= { rptrInfoEntry 1 }

    rptrInfoRptrType OBJECT-TYPE
        SYNTAX      INTEGER {
                      other(1),                -- undefined or unknown
                      tenMb(2),
                      onehundredMbClassI(3),
                      onehundredMbClassII(4)
                    }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The rptrInfoRptrType returns a value that identifies
                the CSMA/CD repeater type."
        REFERENCE
                "IEEE Std 802.3, 30.4.1.1.2, aRepeaterType."
        ::= { rptrInfoEntry 2 }

    rptrInfoOperStatus OBJECT-TYPE
        SYNTAX      INTEGER {
                      other(1),
                      ok(2),
                      failure(3)
                    }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
```

```
                "The rptrInfoOperStatus object indicates the
                operational state of the repeater."
        REFERENCE
                "IEEE Std 802.3, 30.4.1.1.5, aRepeaterHealthState."
        ::= { rptrInfoEntry 3 }

    rptrInfoReset OBJECT-TYPE
        SYNTAX      INTEGER {
                      noReset(1),
                      reset(2)
                    }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
                "Setting this object to reset(2) causes a
                transition to the START state of Figure 9-2 in
                Clause 9 IEEE Std 802.3 for a 10 Mb/s repeater,
                and to the START state of Figure 27-2 in Clause 27
                of that standard for a 100 Mb/s repeater.

                Setting this object to noReset(1) has no effect.
                The agent will return the value noReset(1)
                when this object is read.

                After receiving a request to set this variable to
                reset(2), the agent is allowed to delay the reset
                for a short period. For example, the implementor
                may choose to delay the reset long enough to allow
                the SNMP response to be transmitted. In any
                event, SNMP requires that a response be transmitted.

                This action does not reset the management counters
                defined in this document nor does it affect the
                portAdminStatus parameters. Included in this
                action is the execution of a disruptive Self-Test
                with the following characteristics:  a) The nature
                of the tests is not specified. b) The test resets
                the repeater but without affecting management
                information about the repeater. c) The test does
                not inject packets onto any segment. d) Packets
                received during the test may or may not be
                transferred. e) The test does not interfere with
                management functions.

                After performing this self-test, the agent will
                update the repeater health information (including
                rptrInfoOperStatus), and send a rptrInfoResetEvent
                notification."
        REFERENCE
                "IEEE Std 802.3, 30.4.1.2.1, acResetRepeater."
        ::= { rptrInfoEntry 4 }

    rptrInfoPartitionedPorts OBJECT-TYPE
        SYNTAX      Gauge32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This object returns the total number of ports in
                the repeater whose current state meets all three
```

```
                of the following criteria:  rptrPortOperStatus
                does not have the value notPresent(3),
                rptrPortAdminStatus is enabled(1), and
                rptrPortAutoPartitionState is autoPartitioned(2)."
        ::= { rptrInfoEntry 5 }

    rptrInfoLastChange OBJECT-TYPE
        SYNTAX      TimeStamp
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The value of sysUpTime when any of the following
                conditions occurred:
                  1) agent cold- or warm-started;
                  2) this instance of repeater was created
                     (such as when a device or module was
                     added to the repeater system);
                  3) a change in the value of rptrInfoOperStatus;
                  4) ports were added or removed as members of
                     the repeater; or
                  5) any of the counters associated with this
                     repeater had a discontinuity."
        ::= { rptrInfoEntry 6 }

    -- Statistics at the port level.
    --

    rptrMonitorPortTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF RptrMonitorPortEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "Table of performance and error statistics for the
                ports. The number of entries is the same as that
                in the rptrPortTable.

                The columnar object rptrMonitorPortLastChange
                is used to indicate possible discontinuities
                of counter type columnar objects in the table."
        ::= { rptrMonitorPortInfo 1 }

    rptrMonitorPortEntry OBJECT-TYPE
        SYNTAX      RptrMonitorPortEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "An entry in the table, containing performance and
                error statistics for a single port."
        INDEX    { rptrMonitorPortGroupIndex, rptrMonitorPortIndex }
        ::= { rptrMonitorPortTable 1 }

    RptrMonitorPortEntry ::=
        SEQUENCE {
            rptrMonitorPortGroupIndex
                Integer32,
            rptrMonitorPortIndex
                Integer32,
            rptrMonitorPortReadableFrames
                Counter32,
```

```
            rptrMonitorPortReadableOctets
                Counter32,
            rptrMonitorPortFCSErrors
                Counter32,
            rptrMonitorPortAlignmentErrors
                Counter32,
            rptrMonitorPortFrameTooLongs
                Counter32,
            rptrMonitorPortShortEvents
                Counter32,
            rptrMonitorPortRunts
                Counter32,
            rptrMonitorPortCollisions
                Counter32,
            rptrMonitorPortLateEvents
                Counter32,
            rptrMonitorPortVeryLongEvents
                Counter32,
            rptrMonitorPortDataRateMismatches
                Counter32,
            rptrMonitorPortAutoPartitions
                Counter32,
            rptrMonitorPortTotalErrors
                Counter32,
            rptrMonitorPortLastChange
                TimeStamp
        }

    rptrMonitorPortGroupIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "This object identifies the group containing the
                port for which this entry contains information."
        ::= { rptrMonitorPortEntry 1 }

    rptrMonitorPortIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "This object identifies the port within the group
                for which this entry contains information."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.1, aPortID."
        ::= { rptrMonitorPortEntry 2 }

    rptrMonitorPortReadableFrames OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This object is the number of frames of valid
                frame length that have been received on this port.
                This counter is incremented by one for each frame
                received on this port whose OctetCount is greater
                than or equal to minFrameSize and less than or
                equal to maxFrameSize (Ref: IEEE 802.3 Std,
```

```
                4.4.2.1) and for which the FCSError and
                CollisionEvent signals are not asserted.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes.

                This statistic provides one of the parameters
                necessary for obtaining the packet error ratio.
                The approximate minimum time for rollover of this
                counter is 80 hours at 10 Mb/s."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.4, aReadableFrames."
        ::= { rptrMonitorPortEntry 3 }

    rptrMonitorPortReadableOctets OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This object is the number of octets contained in
                valid frames that have been received on this port.
                This counter is incremented by OctetCount for each
                frame received on this port that has been
                determined to be a readable frame (i.e., including
                FCS octets but excluding framing bits and dribble
                bits).

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes.

                This statistic provides an indicator of the total
                data transferred. The approximate minimum time
                for rollover of this counter in a 10 Mb/s repeater
                is 58 minutes.

                For ports receiving traffic at a maximum rate in
                a 100 Mb/s repeater, this counter can roll over
                in less than 6 minutes. Since that amount of time
                could be less than a management station’s poll cycle
                time, in order to avoid a loss of information a
                management station is advised to also poll the
                rptrMonitorPortUpper32Octets object, or to use the
                64-bit counter defined by
                rptrMonitorPortHCReadableOctets instead of the
                two 32-bit counters."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.5, aReadableOctets."
        ::= { rptrMonitorPortEntry 4 }

    rptrMonitorPortFCSErrors OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one for each frame
                received on this port with the FCSError signal
                asserted and the FramingError and CollisionEvent
```

```
                signals deasserted and whose OctetCount is greater
                than or equal to minFrameSize and less than or
                equal to maxFrameSizeLimit (See IEEE Std 802.3 4.2.7.1).

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes.

                The approximate minimum time for rollover of this
                counter is 80 hours at 10 Mb/s."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.6,
                aFrameCheckSequenceErrors."
        ::= { rptrMonitorPortEntry 5 }

    rptrMonitorPortAlignmentErrors OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one for each frame
                received on this port with the FCSError and
                FramingError signals asserted and CollisionEvent
                signal deasserted and whose OctetCount is greater
                than or equal to minFrameSize and less than or
                equal to maxFrameSizeLimit (See IEEE Std 802.3, 4.2.7.1).
                If rptrMonitorPortAlignmentErrors is
                incremented then the rptrMonitorPortFCSErrors
                Counter shall not be incremented for the same
                frame.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes.

                The approximate minimum time for rollover of this
                counter is 80 hours at 10 Mb/s."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.7, aAlignmentErrors."
        ::= { rptrMonitorPortEntry 6 }

    rptrMonitorPortFrameTooLongs OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one for each frame
                received on this port whose OctetCount is greater
                than maxFrameSizeLimit (See IEEE Std 802.3, 4.2.7.1).
                If rptrMonitorPortFrameTooLongs is incremented
                then neither the rptrMonitorPortAlignmentErrors
                nor the rptrMonitorPortFCSErrors counter shall be
                incremented for the frame.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes.

                The approximate minimum time for rollover of this
```

```
                counter is 61 days in a 10 Mb/s repeater."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.8, aFramesTooLong."
        ::= { rptrMonitorPortEntry 7 }

    rptrMonitorPortShortEvents OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one for each
                CarrierEvent on this port with ActivityDuration
                less than ShortEventMaxTime. ShortEventMaxTime is
                greater than 74 bit times and less than 82 bit
                times. ShortEventMaxTime has tolerances included
                to provide for circuit losses between a
                conformance test point at the AUI and the
                measurement point within the state machine.

                Notes:

                ShortEvents may indicate externally
                generated noise hits that will cause the repeater
                to transmit Runts to its other ports, or propagate
                a collision (which may be late) back to the
                transmitting DTE and damaged frames to the rest of
                the network.

                Implementors may wish to consider selecting the
                ShortEventMaxTime towards the lower end of the
                allowed tolerance range to accommodate bit losses
                suffered through physical channel devices not
                budgeted for within this standard.

                The significance of this attribute is different
                in 10 and 100 Mb/s collision domains. Clause 9
                repeaters perform fragment extension of short
                events which would be counted as runts on the
                interconnect ports of other repeaters. Clause
                27 repeaters do not perform fragment extension.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes.

                The approximate minimum time for rollover of this
                counter is 16 hours in a 10 Mb/s repeater."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.9, aShortEvents."
        ::= { rptrMonitorPortEntry 8 }

    rptrMonitorPortRunts OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one for each
                CarrierEvent on this port that meets one of the
                following two conditions. Only one test need be
```

```
                made. a) The ActivityDuration is greater than
                ShortEventMaxTime and less than ValidPacketMinTime
                and the CollisionEvent signal is deasserted. b)
                The OctetCount is less than 64, the
                ActivityDuration is greater than ShortEventMaxTime
                and the CollisionEvent signal is deasserted.
                ValidPacketMinTime is greater than or equal to 552
                bit times and less than 565 bit times.

                An event whose length is greater than 74 bit times
                but less than 82 bit times shall increment either
                the shortEvents counter or the runts counter but
                not both. A CarrierEvent greater than or equal to
                552 bit times but less than 565 bit times may or
                may not be counted as a runt.

                ValidPacketMinTime has tolerances included to
                provide for circuit losses between a conformance
                test point at the AUI and the measurement point
                within the state machine.

                Runts usually indicate collision fragments, a
                normal network event. In certain situations
                associated with large diameter networks a
                percentage of collision fragments may exceed
                ValidPacketMinTime.
                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes.

                The approximate minimum time for rollover of this
                counter is 16 hours in a 10 Mb/s repeater."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.10, aRunts."
        ::= { rptrMonitorPortEntry 9 }

    rptrMonitorPortCollisions OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "For a Clause 9 repeater, this counter is
                incremented by one for any CarrierEvent signal
                on any port for which the CollisionEvent signal
                on this port is asserted. For a Clause 27
                repeater port the counter increments on entering
                the Collision Count Increment state of the
                partition state diagram (Figure 27-8 of
                IEEE Std 802.3).

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes.

                The approximate minimum time for rollover of this
                counter is 16 hours in a 10 Mb/s repeater."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.11, aCollisions."
        ::= { rptrMonitorPortEntry 10 }
```

```
rptrMonitorPortLateEvents OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "For a Clause 9 repeater port, this counter is
            incremented by one for each CarrierEvent
            on this port in which the CollIn(X)
            variable transitions to the value SQE (see
            9.6.6.2, IEEE Std 802.3) while the
            ActivityDuration is greater than the
            LateEventThreshold. For a Clause 27 repeater
            port, this counter is incremented by one on
            entering the Collision Count Increment state
            of the  partition state diagram (Figure 27-8)
            while the  ActivityDuration is greater than
            the LateEvent- Threshold. Such a CarrierEvent
            is counted twice, as both a collision and as a
            lateEvent.

            The LateEventThreshold is greater than 480 bit
            times and less than 565 bit times.
            LateEventThreshold has tolerances included to
            permit an implementation to build a single
            threshold to serve as both the LateEventThreshold
            and ValidPacketMinTime threshold.

            A discontinuity may occur in the value
            when the value of object
            rptrMonitorPortLastChange changes.

            The approximate minimum time for rollover of this
            counter is 81 hours in a 10 Mb/s repeater."
    REFERENCE
            "IEEE Std 802.3, 30.4.3.1.12, aLateEvents."
    ::= { rptrMonitorPortEntry 11 }

rptrMonitorPortVeryLongEvents OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "For a Clause 9 repeater port, this counter
            is incremented by one for each CarrierEvent
            whose ActivityDuration is greater than the
            MAU Jabber Lockup Protection timer TW3
            (See IEEE Std 802.3 9.6.1 and 9.6.5).

            For a Clause 27 repeater port, this counter
            is incremented by one on entry to the
            Rx Jabber state of the receiver timer state
            diagram (Figure 27-7). Other counters may
            be incremented as appropriate.

            A discontinuity may occur in the value
            when the value of object
            rptrMonitorPortLastChange changes."
    REFERENCE
```

```
                "IEEE Std 802.3, 30.4.3.1.13, aVeryLongEvents."
        ::= { rptrMonitorPortEntry 12 }

    rptrMonitorPortDataRateMismatches OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one for each
                frame received by this port that meets all
                of the conditions required by only one of the
                following two measurement methods:

                Measurement method A:  1) The CollisionEvent
                signal is not asserted (10 Mb/s operation) or
                the Collision Count Increment state of the
                partition state diagram (Figure 27-8 of
                IEEE Std 802.3) has not been entered
                (100 Mb/s operation). 2) The ActivityDuration
                is greater than ValidPacketMinTime. 3) The
                frequency (data rate) is detectably mismatched
                from the local transmit frequency.

                Measurement method B:  1) The CollisionEvent
                signal is not asserted (10 Mb/s operation)
                or the Collision Count Increment state of the
                partition state diagram (Figure 27-8 of
                IEEE Std 802.3) has not been entered
                (100 Mb/s operation). 2) The OctetCount is
                greater than 63. 3) The frequency (data
                rate) is detectably mismatched from the local
                transmit frequency. The exact degree of
                mismatch is vendor specific and is to be
                defined by the vendor for conformance testing.

                When this event occurs, other counters whose
                increment conditions were satisfied may or may not
                also be incremented, at the implementor's
                discretion. Whether or not the repeater was able
                to maintain data integrity is beyond the scope of
                this standard.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.14, aDataRateMismatches."
        ::= { rptrMonitorPortEntry 13 }

    rptrMonitorPortAutoPartitions OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one for
                each time the repeater has automatically
                partitioned this port.

                The conditions that cause a Clause 9
```

```
                repeater port to partition are specified in
                the partition state diagram in Clause 9 of
                IEEE Std 802.3. They are not differentiated
                here. A Clause 27 repeater port partitions
                on entry to the Partition Wait state of the
                partition state diagram (Figure 27-8 in
                IEEE Std 802.3).

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.15, aAutoPartitions."
        ::= { rptrMonitorPortEntry 14 }

    rptrMonitorPortTotalErrors OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The total number of errors which have occurred on
                this port. This counter is the summation of the
                values of other error counters (for the same
                port), namely:

                    rptrMonitorPortFCSErrors,
                    rptrMonitorPortAlignmentErrors,
                    rptrMonitorPortFrameTooLongs,
                    rptrMonitorPortShortEvents,
                    rptrMonitorPortLateEvents,
                    rptrMonitorPortVeryLongEvents,
                    rptrMonitorPortDataRateMismatches, and
                    rptrMonitorPortSymbolErrors.

                This counter is redundant in the sense that it is
                the summation of information already available
                through other objects. However, it is included
                specifically because the regular retrieval of this
                object as a means of tracking the health of a port
                provides a considerable optimization of network
                management traffic over the otherwise necessary
                retrieval of the summed counters.

                Note that rptrMonitorPortRunts is not included
                in this total; this is because runts usually
                indicate collision fragments, a normal network
                event.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes."
        ::= { rptrMonitorPortEntry 15 }

    rptrMonitorPortLastChange OBJECT-TYPE
        SYNTAX      TimeStamp
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The value of sysUpTime when the last of
```

```
                the following occurred:
                  1) the agent cold- or warm-started;
                  2) the row for the port was created
                     (such as when a device or module was added
                      to the repeater system); or
                  3) any condition that would cause one of
                     the counters for the row to experience
                     a discontinuity."
        ::= { rptrMonitorPortEntry 16 }

    rptrMonitor100PortTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF RptrMonitor100PortEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "Table of additional performance and error
                statistics for 100 Mb/s ports, above and
                beyond those parameters that apply to both
                10 and 100 Mb/s ports. Entries exist only for
                ports attached to 100 Mb/s repeaters.

                The columnar object rptrMonitorPortLastChange
                is used to indicate possible discontinuities
                of counter type columnar objects in this table."
        ::= { rptrMonitorPortInfo 2 }

    rptrMonitor100PortEntry OBJECT-TYPE
        SYNTAX      RptrMonitor100PortEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "An entry in the table, containing performance
                and error statistics for a single 100 Mb/s port."
        INDEX     { rptrMonitorPortGroupIndex, rptrMonitorPortIndex }
        ::= { rptrMonitor100PortTable 1 }

    RptrMonitor100PortEntry ::=
        SEQUENCE {
            rptrMonitorPortIsolates
                Counter32,
            rptrMonitorPortSymbolErrors
                Counter32,
            rptrMonitorPortUpper32Octets
                Counter32,
            rptrMonitorPortHCReadableOctets
                Counter64
        }

    rptrMonitorPortIsolates OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one each time that
                the repeater port automatically isolates as a
                consequence of false carrier events. The conditions
                which cause a port to automatically isolate are
                defined by the transition from the False Carrier
                state to the Link Unstable state of the carrier
```

```
                integrity state diagram (Figure 27-9 of
                IEEE Std 802.3).

                Note:  Isolates do not affect the value of
                the PortOperStatus object.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.16, aIsolates."
        ::= { rptrMonitor100PortEntry 1 }

    rptrMonitorPortSymbolErrors OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one each time when
                valid length packet was received at the port and
                there was at least one occurrence of an invalid
                data symbol. This can increment only once per valid
                carrier event. A collision presence at any port of
                the repeater containing port N, will not cause this
                attribute to increment.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes.

                The approximate minimum time for rollover of this
                counter is 7.4 hours at 100 Mb/s."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.17,
                aSymbolErrorDuringPacket."
        ::= { rptrMonitor100PortEntry 2 }

    rptrMonitorPortUpper32Octets OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This object is the number of octets contained in
                valid frames that have been received on this port,
                modulo 2**32. That is, it contains the upper 32
                bits of a 64-bit octets counter, of which the
                lower 32 bits are contained in the
                rptrMonitorPortReadableOctets object.

                This two-counter mechanism is provided for those
                network management protocols that do not support
                64-bit counters (e.g. SNMP V1) and are used to
                manage a repeater type of 100 Mb/s.

                Conformance clauses for this MIB are defined such
                that implementation of this object is not required
                in a repeater system which does not support 100 Mb/s.
                However, repeater systems with mixed 10 and 100 Mb/s ports
                may implement this object across all ports,
```

```
                including 10 Mb/s. If this object is implemented, the
                value shall be a valid count as defined
                in the first paragraph of this description.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes."
        ::= { rptrMonitor100PortEntry 3 }

    rptrMonitorPortHCReadableOctets OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This object is the number of octets contained in
                valid frames that have been received on this port.
                This counter is incremented by OctetCount for each
                frame received on this port which has been
                determined to be a readable frame (i.e., including
                FCS octets but excluding framing bits and dribble
                bits).

                This statistic provides an indicator of the total
                data transferred.

                This counter is a 64-bit version of rptrMonitor-
                PortReadableOctets. It should be used by network
                management protocols which suppport 64-bit counters
                (e.g., SNMPv2).

                Conformance clauses for this MIB are defined such
                that implementation of this object is not required
                in a repeater system which does not support 100 Mb/s.
                However, repeater systems with mixed 10 and 100 Mb/s ports
                may implement this object across all ports,
                including 10 Mb/s. If this object is implemented, the
                value shall be a valid count as defined
                in the first paragraph of this description.

                A discontinuity may occur in the value
                when the value of object
                rptrMonitorPortLastChange changes."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.5, aReadableOctets."
        ::= { rptrMonitor100PortEntry 4 }


    -- New version of statistics at the repeater level.
    --
    -- Statistics objects for each managed repeater
    -- in the repeater system.

    rptrMonTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF RptrMonEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "A table of information about each
                non-trivial repeater. The number of entries
```

```
                in this table is the same as the number of
                entries in the rptrInfoTable.

                The columnar object rptrInfoLastChange is
                used to indicate possible discontinuities of
                counter type columnar objects in this table."
        ::= { rptrMonitorAllRptrInfo 1 }

    rptrMonEntry OBJECT-TYPE
        SYNTAX      RptrMonEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "An entry in the table, containing information
                about a single non-trivial repeater."
        INDEX    { rptrInfoId }
        ::= { rptrMonTable 1 }

    RptrMonEntry ::=
        SEQUENCE {
            rptrMonTxCollisions
                Counter32,
            rptrMonTotalFrames
                Counter32,
            rptrMonTotalErrors
                Counter32,
            rptrMonTotalOctets
                Counter32
        }

    rptrMonTxCollisions OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "For a Clause 9 (10 Mb/s) repeater, this counter
                is incremented every time the repeater state
                machine enters the TRANSMIT COLLISION state
                from any state other than ONE PORT LEFT
                (see Figure 9-2 IEEE Std 802.3).

                For a Clause 27 repeater, this counter is
                incremented every time the repeater core state
                diagram enters the Jam state as a result of
                Activity(ALL) > 1 (see Figure 27-2 IEEE Std 802.3).

                The approximate minimum time for rollover of this
                counter is 16 hours in a 10 Mb/s repeater and 1.6
                hours in a 100 Mb/s repeater."
        REFERENCE
                "IEEE Std 802.3, 30.4.1.1.8, aTransmitCollisions"
        ::= { rptrMonEntry 1 }

    rptrMonTotalFrames OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The number of frames of valid frame length
```

```
                that have been received on the ports in this repeater
                and for which the FCSError and CollisionEvent
                signals were not asserted. If an implementation
                can not obtain a count of frames as seen by
                the repeater itself, this counter may be
                implemented as the summation of the values of the
                rptrMonitorPortReadableFrames counters for all of
                the ports in the repeater.

                This statistic provides one of the parameters
                necessary for obtaining the packet error ratio.
                The approximate minimum time for rollover of this
                counter is 80 hours in a 10 Mb/s repeater."
        ::= { rptrMonEntry 3 }

    rptrMonTotalErrors OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The total number of errors which have occurred on
                all of the ports in this repeater. The errors
                included in this count are the same as those listed
                for the rptrMonitorPortTotalErrors counter. If an
                implementation can not obtain a count of these
                errors as seen by the repeater itself, this counter
                may be implemented as the summation of the values of
                the rptrMonitorPortTotalErrors counters for all of
                the ports in the repeater."
        ::= { rptrMonEntry 4 }

    rptrMonTotalOctets OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The total number of octets contained in the valid
                frames that have been received on the ports in
                this group. If an implementation can not obtain
                a count of octets as seen by the repeater itself,
                this counter may be the summation of the
                values of the rptrMonitorPortReadableOctets
                counters for all of the ports in the group.

                This statistic provides an indicator of the total
                data transferred. The approximate minimum time
                for rollover of this counter in a 10 Mb/s repeater
                is 58 minutes divided by the number of ports in
                the repeater.

                For 100 Mb/s repeaters processing traffic at a
                maximum rate, this counter can roll over in less
                than 6 minutes divided by the number of ports in
                the repeater. Since that amount of time could
                be less than a management station’s poll cycle
                time, in order to avoid a loss of information a
                management station is advised to also poll the
                rptrMonUpper32TotalOctets object, or to use the
                64-bit counter defined by rptrMonHCTotalOctets
```

```
                instead of the two 32-bit counters."
        ::= { rptrMonEntry 5 }

    rptrMon100Table OBJECT-TYPE
        SYNTAX      SEQUENCE OF RptrMon100Entry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "A table of additional information about each
                100 Mb/s repeater, augmenting the entries in
                the rptrMonTable. Entries exist in this table
                only for 100 Mb/s repeaters.

                The columnar object rptrInfoLastChange is
                used to indicate possible discontinuities of
                counter type columnar objects in this table."
        ::= { rptrMonitorAllRptrInfo 2 }

    rptrMon100Entry OBJECT-TYPE
        SYNTAX      RptrMon100Entry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "An entry in the table, containing information
                about a single 100 Mb/s repeater."
        INDEX     { rptrInfoId }
        ::= { rptrMon100Table 1 }

    RptrMon100Entry ::=
        SEQUENCE {
            rptrMonUpper32TotalOctets
                Counter32,
            rptrMonHCTotalOctets
                Counter64
        }

    rptrMonUpper32TotalOctets OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The total number of octets contained in the valid
                frames that have been received on the ports in
                this repeater, modulo 2**32. That is, it contains
                the upper 32 bits of a 64-bit counter, of which
                the lower 32 bits are contained in the
                rptrMonTotalOctets object. If an implementation
                can not obtain a count of octets as seen
                by the repeater itself, the 64-bit value
                may be the summation of the values of the
                rptrMonitorPortReadableOctets counters combined
                with the corresponding rptrMonitorPortUpper32Octets
                counters for all of the ports in the repeater.

                This statistic provides an indicator of the total
                data transferred within the repeater.

                This two-counter mechanism is provided for those
                network management protocols that do not support
```

```
                64-bit counters (e.g., SNMP v1) and are used to
                manage a repeater type of 100 Mb/s.

                Conformance clauses for this MIB are defined such
                that implementation of this object is not required
                in a repeater system which does not support 100 Mb/s.
                However, repeater systems with mixed 10 and 100 Mb/s ports
                may implement this object across all ports,
                including 10 Mb/s. If this object is implemented, the
                value shall be a valid count as defined
                in the first paragraph of this description."
        ::= { rptrMon100Entry 1 }

    rptrMonHCTotalOctets OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The total number of octets contained in the valid
                frames that have been received on the ports in
                this group. If a implementation can not obtain
                a count of octets as seen by the repeater itself,
                this counter may be the summation of the
                values of the rptrMonitorPortReadableOctets
                counters for all of the ports in the group.

                This statistic provides an indicator of the total
                data transferred.

                This counter is a 64-bit (high-capacity) version
                of rptrMonUpper32TotalOctets and rptrMonTotalOctets.
                It should be used by network management protocols
                which support 64-bit counters (e.g. SNMPv2).

                Conformance clauses for this MIB are defined such
                that implementation of this object is not required
                in a repeater system which does not support 100 Mb/s.
                However, repeater systems with mixed 10 and 100 Mb/s ports
                may implement this object across all ports,
                including 10 Mb/s. If this object is implemented, the
                value shall be a valid count as defined
                in the first paragraph of this description."
        ::= { rptrMon100Entry 2 }


    --
    -- The Repeater Address Search Table
    --
    -- This table provides an active address tracking
    -- capability which can be also used to collect the
    -- necessary information for mapping the topology
    -- of a network. Note that an NMS is required to have
    -- read-write access to the table in order to access
    -- this function. Section 4 "Topology Mapping" of
    -- IETF RFC 2108 [B20] contains a description of an
    -- algorithm that can make use of this table,
    -- in combination with the forwarding databases
    -- of managed bridges/switches in the network,
    -- to map network topology. Devices may also
```

```
-- use the protocol and a set of managed
-- objects defined in IEEE Std 802.1AB Station
-- and Media Access Control Connectivity
-- Discovery to discover the physical topology
-- from adjacent stations.
--

rptrAddrSearchTable OBJECT-TYPE
    SYNTAX     SEQUENCE OF RptrAddrSearchEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
            "This table contains one entry per repeater in the
            repeater system. It defines objects that allow a network
            management application to instruct an agent to watch
            for a given MAC address and report which port it
            was seen on. Only one address search can be in
            progress on each repeater at any one time. Before
            starting an address search, a management application
            should obtain ‘ownership’ of the entry in
            rptrAddrSearchTable for the repeater that is to
            perform the search. This is accomplished with the
            rptrAddrSearchLock and rptrAddrSearchStatus as
            follows:

            try_again:
                get(rptrAddrSearchLock, rptrAddrSearchStatus)
                while (rptrAddrSearchStatus != notInUse)
                {
                    /* Loop waiting for objects to be available*/
                    short delay
                    get(rptrAddrSearchLock, rptrAddrSearchStatus)
                }

                /* Try to claim map objects */
                lock_value = rptrAddrSearchLock
                if ( set(rptrAddrSearchLock = lock_value,
                         rptrAddrSearchStatus = inUse,
                         rptrAddrSearchOwner = ‘my-IP-address)
                      == FAILURE)
                    /* Another manager got the lock */
                    goto try_again

                /* I have the lock */
                set (rptrAddrSearchAddress = <search target>)

                wait for rptrAddrSearchState to change from none

                if (rptrAddrSearchState == single)
                    get (rptrAddrSearchGroup, rptrAddrSearchPort)
                /* release the lock, making sure not to overwrite
                   anyone else’s lock */
                set (rptrAddrSearchLock = lock_value+1,
                     rptrAddrSearchStatus = notInUse,
                     rptrAddrSearchOwner = ‘’)

            A management station first retrieves the values of
            the appropriate instances of the rptrAddrSearchLock
            and rptrAddrSearchStatus objects, periodically
```

```
                repeating the retrieval if necessary, until the value
                of rptrAddrSearchStatus is 'notInUse'. The
                management station then tries to set the same
                instance of the rptrAddrSearchLock object to the
                value it just retrieved, the same instance of the
                rptrAddrSearchStatus object to 'inUse', and the
                corresponding instance of rptrAddrSearchOwner to a
                value indicating itself. If the set operation
                succeeds, then the management station has obtained
                ownership of the rptrAddrSearchEntry, and the value
                of rptrAddrSearchLock is incremented by the agent (as
                per the semantics of TestAndIncr). Failure of the
                set operation indicates that some other manager has
                obtained ownership of the rptrAddrSearchEntry.

                Once ownership is obtained, the management station
                can proceed with the search operation. Note that the
                agent will reset rptrAddrSearchStatus to 'notInUse'
                if it has been in the 'inUse' state for an abnormally
                long period of time, to prevent a misbehaving manager
                from permanently locking the entry. It is suggested
                that this timeout period be between one and five
                minutes.

                When the management station has completed its search
                operation, it should free the entry by setting
                the instance of the rptrAddrSearchLock object to the
                previous value + 1, the instance of the
                rptrAddrSearchStatus to 'notInUse', and the instance
                of rptrAddrSearchOwner to a zero length string. This
                is done to prevent overwriting another station's
                lock."
        ::= { rptrAddrTrackRptrInfo 1 }

    rptrAddrSearchEntry OBJECT-TYPE
        SYNTAX     RptrAddrSearchEntry
        MAX-ACCESS not-accessible
        STATUS     current
        DESCRIPTION
                "An entry containing objects for invoking an address
                search on a repeater."
        INDEX      { rptrInfoId }
        ::= { rptrAddrSearchTable 1 }

    RptrAddrSearchEntry ::=
        SEQUENCE {
            rptrAddrSearchLock     TestAndIncr,
            rptrAddrSearchStatus   INTEGER,
            rptrAddrSearchAddress  MacAddress,
            rptrAddrSearchState    INTEGER,
            rptrAddrSearchGroup    Integer32,
            rptrAddrSearchPort     Integer32,
            rptrAddrSearchOwner    OwnerString
        }


    rptrAddrSearchLock OBJECT-TYPE
        SYNTAX     TestAndIncr
        MAX-ACCESS read-write
```

```
        STATUS     current
        DESCRIPTION
                "This object is used by a management station as an
                advisory lock for this rptrAddrSearchEntry."
        ::= { rptrAddrSearchEntry 1 }

    rptrAddrSearchStatus  OBJECT-TYPE
        SYNTAX     INTEGER {
                       notInUse(1),
                       inUse(2)
                   }
        MAX-ACCESS read-write
        STATUS     current
        DESCRIPTION
                "This object is used to indicate that some management
                station is currently using this rptrAddrSearchEntry.
                Cooperating managers should set this object to
                'notInUse' when they are finished using this entry.
                The agent will automatically set the value of this
                object to 'notInUse' if it has been set to 'inUse'
                for an unusually long period of time."
        ::= { rptrAddrSearchEntry 2 }

    rptrAddrSearchAddress OBJECT-TYPE
        SYNTAX     MacAddress
        MAX-ACCESS read-write
        STATUS     current
        DESCRIPTION
                "This object is used to search for a specified MAC
                address. When this object is set, an address search
                begins. This automatically sets the corresponding
                instance of the rptrAddrSearchState object  to 'none'
                and the corresponding instances of the
                rptrAddrSearchGroup and rptrAddrSearchPort objects to
                0.

                When a valid frame is received by this repeater with
                a source MAC address that matches the current value
                of rptrAddrSearchAddress, the agent will update the
                corresponding instances of rptrAddrSearchState,
                rptrAddrSearchGroup and rptrAddrSearchPort to reflect
                the current status of the search, and the group and
                port on which the frame was seen."
        ::= { rptrAddrSearchEntry 3 }

    rptrAddrSearchState OBJECT-TYPE
        SYNTAX     INTEGER {
                        none(1),
                        single(2),
                        multiple(3)
                   }
        MAX-ACCESS read-only
        STATUS     current
        DESCRIPTION
                "The current state of the MAC address search on this
                repeater. This object is initialized to 'none' when
                the corresponding instance of rptrAddrSearchAddress
                is set. If the agent detects the address on exactly
                one port, it will set this object to 'single', and
```

```
                set the corresponding instances of
                rptrAddrSearchGroup and rptrAddrSearchPort to reflect
                the group and port on which the address was heard.
                If the agent detects the address on more than one
                port, it will set this object to ‘multiple’."
        ::= { rptrAddrSearchEntry 4 }

    rptrAddrSearchGroup OBJECT-TYPE
        SYNTAX     Integer32 (0..2147483647)
        MAX-ACCESS read-only
        STATUS     current
        DESCRIPTION
                "The group from which an error-free frame whose
                source address is equal to the corresponding instance
                of rptrAddrSearchAddress has been received. The
                value of this object is undefined when the
                corresponding instance of rptrAddrSearchState is
                equal to ‘none’ or ‘multiple’."
        ::= { rptrAddrSearchEntry 5 }

    rptrAddrSearchPort OBJECT-TYPE
        SYNTAX     Integer32 (0..2147483647)
        MAX-ACCESS read-only
        STATUS     current
        DESCRIPTION
                "The port from which an error-free frame whose
                source address is equal to the corresponding instance
                of rptrAddrSearchAddress has been received. The
                value of this object is undefined when the
                corresponding instance of rptrAddrSearchState is
                equal to ‘none’ or ‘multiple’."
        ::= { rptrAddrSearchEntry 6 }

    rptrAddrSearchOwner OBJECT-TYPE
        SYNTAX     OwnerString
        MAX-ACCESS read-write
        STATUS     current
        DESCRIPTION
                "The entity that currently has ‘ownership’ of this
                rptrAddrSearchEntry."
        ::= { rptrAddrSearchEntry 7 }


    --
    -- The Port Address Tracking Table
    --
    -- This table provides a way for a network management
    -- application to passively gather information (using
    -- read-only privileges) about which network addresses
    -- are connected to which ports of a repeater.
    --

    rptrAddrTrackTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF RptrAddrTrackEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "Table of address mapping information about the
                ports."
```

```
        ::= { rptrAddrTrackPortInfo 1 }

    rptrAddrTrackEntry OBJECT-TYPE
        SYNTAX      RptrAddrTrackEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "An entry in the table, containing address mapping
                information about a single port."
        INDEX    { rptrAddrTrackGroupIndex, rptrAddrTrackPortIndex }
        ::= { rptrAddrTrackTable 1 }

    RptrAddrTrackEntry ::=
        SEQUENCE {
            rptrAddrTrackGroupIndex
                INTEGER,
            rptrAddrTrackPortIndex
                INTEGER,
            rptrAddrTrackSourceAddrChanges
                Counter32,
            rptrAddrTrackNewLastSrcAddress
                OptMacAddr,
            rptrAddrTrackCapacity
                Integer32
        }

    rptrAddrTrackGroupIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "This object identifies the group containing the
                port for which this entry contains information."
        ::= { rptrAddrTrackEntry 1 }

    rptrAddrTrackPortIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "This object identifies the port within the group
                for which this entry contains information."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.1, aPortID."
        ::= { rptrAddrTrackEntry 2 }

    rptrAddrTrackSourceAddrChanges OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This counter is incremented by one for each time
                that the rptrAddrTrackNewLastSrcAddress attribute
                for this port has changed.

                This may indicate whether a link is connected to a
                single DTE or another multi-user segment.

                A discontinuity may occur in the value when the
```

```
                value of object rptrMonitorPortLastChange changes.

                The approximate minimum time for rollover of this
                counter is 81 hours in a 10 Mb/s repeater."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.19, aSourceAddressChanges."
        ::= { rptrAddrTrackEntry 3 }

    rptrAddrTrackNewLastSrcAddress OBJECT-TYPE
        SYNTAX      OptMacAddr
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This object is the SourceAddress of the last
                readable frame (i.e., counted by
                rptrMonitorPortReadableFrames) received by this
                port. If no frames have been received by this
                port since the agent began monitoring the port
                activity, the agent shall return a string of
                length zero."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.18, aLastSourceAddress."
        ::= { rptrAddrTrackEntry 4 }

    rptrAddrTrackCapacity OBJECT-TYPE
        SYNTAX      Integer32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The maximum number of addresses that can be
                detected on this port. This value indicates
                to the maximum  number of entries in the
                rptrExtAddrTrackTable relative to this port.

                If this object has the value of 1, the agent
                implements only the LastSourceAddress mechanism
                described by IETF RFC 1368 or IETF RFC 1516."
        ::= { rptrAddrTrackEntry 5 }


    -- Table for multiple addresses per port

    rptrExtAddrTrackTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF RptrExtAddrTrackEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "A table to extend the address tracking table (i.e.,
                rptrAddrTrackTable) with a list of source MAC
                addresses that were recently received on each port.
                The number of ports is the same as the number
                of entries in table rptrPortTable. The number of
                entries in this table depends on the agent/repeater
                implementation and the number of different
                addresses received on each port.

                The first entry for each port contains
                the same MAC address that is given by the
                rptrAddrTrackNewLastSrcAddress for that port.
```

```
                Entries in this table for a particular port are
                retained when that port is switched from one
                repeater to another.

                The ordering of MAC addresses listed for a
                particular port is implementation dependent."
        ::= { rptrAddrTrackPortInfo 2 }

    rptrExtAddrTrackEntry OBJECT-TYPE
        SYNTAX      RptrExtAddrTrackEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "A row in the table of extended address tracking
                information for ports. Entries cannot be directly
                created or deleted via SNMP operations."
        INDEX       { rptrAddrTrackGroupIndex,
                      rptrAddrTrackPortIndex,
                      rptrExtAddrTrackMacIndex }
        ::= { rptrExtAddrTrackTable 1 }

    RptrExtAddrTrackEntry ::= SEQUENCE {
        rptrExtAddrTrackMacIndex Integer32,
        rptrExtAddrTrackSourceAddress MacAddress
        }

    rptrExtAddrTrackMacIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "The index of a source MAC address seen on
                the port.

                The ordering of MAC addresses listed for a
                particular port is implementation dependent.

                There is no implied relationship between a
                particular index and a particular MAC
                address. The index for a particular MAC
                address may change without notice."
        ::= { rptrExtAddrTrackEntry 1 }

    rptrExtAddrTrackSourceAddress OBJECT-TYPE
        SYNTAX      MacAddress
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The source MAC address from a readable frame
                (i.e., counted by rptrMonitorPortReadableFrames)
                recently received by the port."
        REFERENCE
                "IEEE Std 802.3, 30.4.3.1.18, aLastSourceAddress."
        ::= { rptrExtAddrTrackEntry 2 }


    -- The Repeater Top "N" Port Group
    -- The Repeater Top N Port group is used to prepare reports that
```

```
-- describe a list of ports ordered by one of the statistics in the
-- Repeater Monitor Port Table. The statistic chosen by the
-- management station is sampled over a management
-- station-specified time interval, making the report rate based.
-- The management station also specifies the number of ports that
-- are reported.
--
-- The rptrTopNPortControlTable is used to initiate the generation
-- of a report. The management station may select the parameters
-- of such a report, such as which repeater, which statistic, how
-- many ports, and the start and stop times of the sampling. When
-- the report is prepared, entries are created in the
-- rptrTopNPortTable associated with the relevent
-- rptrTopNControlEntry. These entries are static for
-- each report after it has been prepared.

-- Note that counter discontinuities may appear in some
-- implementations if ports' assignment to repeaters changes
-- during the collection of data for a Top "N" report.
-- A management application could read the corresponding
-- rptrMonitorPortLastChange timestamp in order to check
-- whether a discontinuity occurred.


rptrTopNPortControlTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RptrTopNPortControlEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table of control records for reports on the top 'N'
        ports for the rate of a selected counter. The number
        of entries depends on the configuration of the agent.
        The maximum number of entries is implementation
        dependent."
    ::= { rptrTopNPortInfo 1 }

rptrTopNPortControlEntry OBJECT-TYPE
    SYNTAX      RptrTopNPortControlEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "A set of parameters that control the creation of a
            report of the top N ports according to several metrics."
    INDEX    { rptrTopNPortControlIndex }
    ::= { rptrTopNPortControlTable 1 }

RptrTopNPortControlEntry ::= SEQUENCE {
    rptrTopNPortControlIndex
        Integer32,
    rptrTopNPortRepeaterId
        Integer32,
    rptrTopNPortRateBase
        INTEGER,
    rptrTopNPortTimeRemaining
        Integer32,
    rptrTopNPortDuration
        Integer32,
    rptrTopNPortRequestedSize
        Integer32,
```

```
        rptrTopNPortGrantedSize
            Integer32,
        rptrTopNPortStartTime
            TimeStamp,
        rptrTopNPortOwner
            OwnerString,
        rptrTopNPortRowStatus
            RowStatus
    }

    rptrTopNPortControlIndex OBJECT-TYPE
        SYNTAX      Integer32 (1 .. 65535)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "An index that uniquely identifies an entry in the
                rptrTopNPortControl table. Each such entry defines
                one top N report prepared for a repeater or repeater system."
        ::= { rptrTopNPortControlEntry 1 }

    rptrTopNPortRepeaterId OBJECT-TYPE
        SYNTAX      Integer32 (0..2147483647)
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
                "Identifies the repeater for which a top N report will
                be prepared (see rptrInfoId). If the value of this
                object is positive, only ports assigned to this repeater
                will be used to form the list in which to order the
                Top N table. If this value is zero, all ports will be
                eligible for inclusion on the list.

                The value of this object may not be modified if the
                associated rptrTopNPortRowStatus object is equal to
                active(1).
                If, for a particular row in this table, the repeater
                specified by the value of this object goes away (is
                removed from the rptrInfoTable) while the associated
                rptrTopNPortRowStatus object is equal to active(1),
                the row in this table is preserved by the agent but
                the value of rptrTopNPortRowStatus is changed to
                notInService(2), and the agent may time out the row
                if appropriate. If the specified repeater comes
                back (reappears in the rptrInfoTable) before the row
                has been timed out, the management station sets
                the value of the rptrTopNPortRowStatus object back
                to active(1) if desired (the agent doesn’t do this
                automatically)."
        ::= { rptrTopNPortControlEntry 2 }

    rptrTopNPortRateBase OBJECT-TYPE
        SYNTAX      INTEGER  {
                      readableFrames(1),
                      readableOctets(2),
                      fcsErrors(3),
                      alignmentErrors(4),
                      frameTooLongs(5),
                      shortEvents(6),
                      runts(7),
```

```
                     collisions(8),
                     lateEvents(9),
                     veryLongEvents(10),
                     dataRateMismatches(11),
                     autoPartitions(12),
                     totalErrors(13),
                     isolates(14),
                     symbolErrors(15)
                   }
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
                "The monitored variable, which the rptrTopNPortRate
                variable is based upon.

                The value of this object may not be modified if
                the associated rptrTopNPortRowStatus object has
                a value of active(1)."
        ::= { rptrTopNPortControlEntry 3 }

    rptrTopNPortTimeRemaining OBJECT-TYPE
        SYNTAX      Integer32 (0..2147483647)
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
                "The number of seconds left in the report
                currently being collected. When this object
                is modified by the management station, a new
                collection is started, possibly aborting a
                currently running report. The new value is
                used as the requested duration of this report,
                which is loaded into the associated
                rptrTopNPortDuration object.

                When this object is set to a non-zero value,
                any associated rptrTopNPortEntries shall be
                made inaccessible by the agent. While the value
                of this object is non-zero, it decrements by one
                per second until it reaches zero. During this
                time, all associated rptrTopNPortEntries shall
                remain inaccessible. At the time that this object
                decrements to zero, the report is made accessible
                in the rptrTopNPortTable. Thus, the rptrTopNPort
                table needs to be created only at the end of the
                collection interval.

                If the value of this object is set to zero
                while the associated report is running, the
                running report is aborted and no associated
                rptrTopNPortEntries are created."
        DEFVAL { 0 }
        ::= { rptrTopNPortControlEntry 4 }

    rptrTopNPortDuration OBJECT-TYPE
        SYNTAX      Integer32 (0..2147483647)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The number of seconds that this report has
```

```
                collected during the last sampling interval,
                or if this report is currently being collected,
                the number of seconds that this report is being
                collected during this sampling interval.

                When the associated rptrTopNPortTimeRemaining
                object is set, this object shall be set by the
                agent to the same value and shall not be modified
                until the next time the rptrTopNPortTimeRemaining
                is set.

                This value shall be zero if no reports have been
                requested for this rptrTopNPortControlEntry."
         ::= { rptrTopNPortControlEntry 5 }

    rptrTopNPortRequestedSize OBJECT-TYPE
        SYNTAX      Integer32
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
                "The maximum number of repeater ports requested
                for the Top N Table.

                When this object is created or modified, the
                agent should set rptrTopNPortGrantedSize as close
                to this object as is possible for the particular
                implementation and available resources."
        DEFVAL { 10 }
        ::= { rptrTopNPortControlEntry 6 }

    rptrTopNPortGrantedSize OBJECT-TYPE
        SYNTAX      Integer32 (0..65535)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The maximum number of repeater ports in the
                top N table.

                When the associated rptrTopNPortRequestedSize object is
                created or modified, the agent should set this object as
                closely to the requested value as is possible for the
                particular implementation and available resources. The
                agent shall not lower this value except as a result of a
                set to the associated rptrTopNPortRequestedSize object."
        ::= { rptrTopNPortControlEntry 7 }

    rptrTopNPortStartTime OBJECT-TYPE
        SYNTAX      TimeStamp
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The value of sysUpTime when this top N report was
                last started. In other words, this is the time that
                the associated rptrTopNPortTimeRemaining object was
                modified to start the requested report.

                If the report has not yet been started, the value
                of this object is zero."
        ::= { rptrTopNPortControlEntry 8 }
```

```
rptrTopNPortOwner OBJECT-TYPE
    SYNTAX      OwnerString
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
            "The entity that configured this entry and is
            using the resources assigned to it."
    ::= { rptrTopNPortControlEntry 9 }

rptrTopNPortRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
           "The status of this row.

           If the value of this object is not equal to
           active(1), all associated entries in the
           rptrTopNPortTable shall be deleted by the
           agent."
    ::= { rptrTopNPortControlEntry 10 }


-- Top "N" reports

rptrTopNPortTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RptrTopNPortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "A table of reports for the top 'N' ports based on
            setting of associated control table entries. The
            maximum number of entries depends on the number
            of entries in table rptrTopNPortControlTable and
            the value of object rptrTopNPortGrantedSize for
            each entry.

            For each entry in the rptrTopNPortControlTable,
            repeater ports with the highest value of
            rptrTopNPortRate shall be placed in this table
            in decreasing order of that rate until there is
            no more room or until there are no more ports."
    ::= { rptrTopNPortInfo 2 }

rptrTopNPortEntry OBJECT-TYPE
    SYNTAX      RptrTopNPortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "A set of statistics for a repeater port that is
            part of a top N report."
    INDEX     { rptrTopNPortControlIndex,
                rptrTopNPortIndex }
    ::= { rptrTopNPortTable 1 }

RptrTopNPortEntry ::= SEQUENCE {
    rptrTopNPortIndex
        Integer32,
```

```
        rptrTopNPortGroupIndex
            Integer32,
        rptrTopNPortPortIndex
            Integer32,
        rptrTopNPortRate
            Gauge32
    }

    rptrTopNPortIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..65535)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
                "An index that uniquely identifies an entry in
                the rptrTopNPort table among those in the same
                report. This index is between 1 and N, where N
                is the number of entries in this report. Increasing
                values of rptrTopNPortIndex shall be assigned to
                entries with decreasing values of rptrTopNPortRate
                until index N is assigned to the entry with the
                lowest value of rptrTopNPortRate or there are no
                more rptrTopNPortEntries.

                No ports are included in a report where their
                value of rptrTopNPortRate would be zero."
        ::= { rptrTopNPortEntry 1 }

    rptrTopNPortGroupIndex OBJECT-TYPE
        SYNTAX      Integer32  (1..2147483647)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "This object identifes the group containing
                the port for this entry. (See also object
                type rptrGroupIndex.)"
        ::= { rptrTopNPortEntry 2 }

    rptrTopNPortPortIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
            "The index of the repeater port.
            (See object type rptrPortIndex.)"
        ::= { rptrTopNPortEntry 3 }

    rptrTopNPortRate OBJECT-TYPE
        SYNTAX      Gauge32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The amount of change in the selected variable
                during this sampling interval for the identified
                port. The selected variable is that port's
                instance of the object selected by
                rptrTopNPortRateBase."
        ::= { rptrTopNPortEntry 4 }
```

```
-- Notifications for use by Repeaters
-- Notifications for repeaters in a multiple-repeater implementation.
-- An implementation may send either the single-repeater OR
-- multiple-repeater version of these notifications (1 or 4; 2 or 5)
-- but not both.

ieee8023snmpDot3RptrNotifications OBJECT IDENTIFIER
            ::= {ieee8023snmpDot3RptrMgt 0}

rptrInfoHealth NOTIFICATION-TYPE
    OBJECTS     { rptrInfoOperStatus }
    STATUS      current
    DESCRIPTION
            "In a repeater system containing multiple managed repeaters,
            the rptrInfoHealth notification conveys information
            related to the operational status of a repeater.
            It is sent either when the value of rptrInfoOperStatus
            changes, or upon completion of a non-disruptive test.

            The agent shall limit the generation of
            consecutive rptrInfoHealth notifications for
            the same repeater so that there is at least
            a five-second gap between notifications of this type.
            When notifications are throttled, they are dropped,
            not queued for sending at a future time. (Note
            that ‘generating’ a notification means sending
            to all configured recipients.)"
    REFERENCE
            "IEEE Std 802.3, 30.4.1.3.1, nRepeaterHealth
            notification."
    ::= { ieee8023snmpDot3RptrNotifications 4 }

rptrInfoResetEvent NOTIFICATION-TYPE
    OBJECTS     { rptrInfoOperStatus }
    STATUS      current
    DESCRIPTION
            "In a repeater system containing multiple managed
            repeaters, the rptrInfoResetEvent notification
            conveys information related to the operational
            status of a repeater. This notification is sent
            on completion of a repeater reset action. A
            repeater reset action is defined as a transition
            to the START state of Figure 9-2 in Clause 9 of
            IEEE Std 802.3, when triggered by a management
            command (e.g., an SNMP Set on the rptrInfoReset
            object).

            The agent shall limit the generation of
            consecutive rptrInfoResetEvent notifications for
            a single repeater so that there is at least
            a five-second gap between notifications of
            this type. When notifications are throttled,
            they are dropped, not queued for sending at
            a future time. (Note that ‘generating’ a
            notification means sending to all configured
            recipients.)

            The rptrInfoResetEvent is not sent when the
```

```
                agent restarts and sends an SNMP coldStart or
                warmStart trap. However, it is recommended that
                a repeater agent send the rptrInfoOperStatus
                object as an optional object with its coldStart
                and warmStart trap PDUs."
        REFERENCE
                "IEEE Std 802.3, 30.4.1.3.2, nRepeaterReset
                notification."
        ::= { ieee8023snmpDot3RptrNotifications 5 }


    -- Conformance statements

    snmpRptrModConf
            OBJECT IDENTIFIER ::= { ieee8023snmpRptrMIB 2 }
      snmpRptrModCompls
            OBJECT IDENTIFIER ::= { snmpRptrModConf 1 }
      snmpRptrModObjGrps
            OBJECT IDENTIFIER ::= { snmpRptrModConf 2 }
      snmpRptrModNotGrps
            OBJECT IDENTIFIER ::= { snmpRptrModConf 3 }


    -- Object groups

    snmpRptrGrpBasic OBJECT-GROUP
        OBJECTS     { rptrGroupObjectID,
                      rptrGroupOperStatus,
                      rptrGroupPortCapacity,
                      rptrPortAdminStatus,
                      rptrPortAutoPartitionState,
                      rptrPortOperStatus,
                      rptrPortRptrId,
                      rptrInfoRptrType,
                      rptrInfoOperStatus,
                      rptrInfoReset,
                      rptrInfoPartitionedPorts,
                      rptrInfoLastChange }
        STATUS      current
        DESCRIPTION
            "Basic group for a repeater system with one or more
            repeater-units in multisegment (post-RFC 1516)
            version of the MIB module."
        ::= { snmpRptrModObjGrps 1 }

    snmpRptrGrpMonitor OBJECT-GROUP
        OBJECTS     { rptrMonitorPortReadableFrames,
                      rptrMonitorPortReadableOctets,
                      rptrMonitorPortFCSErrors,
                      rptrMonitorPortAlignmentErrors,
                      rptrMonitorPortFrameTooLongs,
                      rptrMonitorPortShortEvents,
                      rptrMonitorPortRunts,
                      rptrMonitorPortCollisions,
                      rptrMonitorPortLateEvents,
                      rptrMonitorPortVeryLongEvents,
                      rptrMonitorPortDataRateMismatches,
                      rptrMonitorPortAutoPartitions,
                      rptrMonitorPortTotalErrors,
```

```
                     rptrMonitorPortLastChange,

                     rptrMonTxCollisions,
                     rptrMonTotalFrames,
                     rptrMonTotalErrors,
                     rptrMonTotalOctets }
        STATUS      current
        DESCRIPTION
            "Monitor group for a repeater system with one or more
            repeater-units in multisegment (post-RFC 1516)
            version of the MIB module."
        ::= { snmpRptrModObjGrps 2 }

    snmpRptrGrpMonitor100 OBJECT-GROUP
        OBJECTS     { rptrMonitorPortIsolates,
                     rptrMonitorPortSymbolErrors,
                     rptrMonitorPortUpper32Octets,

                     rptrMonUpper32TotalOctets }
        STATUS      current
        DESCRIPTION
            "Monitor group for 100 Mb/s ports and repeaters
            in a repeater system with one or more repeater-units in
            multisegment (post-RFC 1516) version of the MIB
            module. Repeater systems which support Counter64 should
            also implement snmpRptrGrpMonitor100w64."
        ::= { snmpRptrModObjGrps 3 }

    snmpRptrGrpMonitor100w64 OBJECT-GROUP
        OBJECTS     { rptrMonitorPortHCReadableOctets,
                     rptrMonHCTotalOctets }
        STATUS      current
        DESCRIPTION
            "Monitor group for 100 Mb/s ports and repeaters in a
            repeater system with one or more repeater-units and support
            for Counter64."
        ::= { snmpRptrModObjGrps 4 }

    snmpRptrGrpAddrTrack OBJECT-GROUP
        OBJECTS     { rptrAddrTrackSourceAddrChanges,
                     rptrAddrTrackNewLastSrcAddress,
                     rptrAddrTrackCapacity }
        STATUS      current
        DESCRIPTION
            "Passive address tracking group for post-RFC 1516
            version of the MIB module."
        ::= { snmpRptrModObjGrps 5 }

    snmpRptrGrpExtAddrTrack OBJECT-GROUP
        OBJECTS     { rptrExtAddrTrackSourceAddress }
        STATUS      current
        DESCRIPTION
            "Extended passive address tracking group for
            a repeater system with one or more repeater-units in
            post-RFC 1516 version of the MIB module."
        ::= { snmpRptrModObjGrps 6 }

    snmpRptrGrpRptrAddrSearch OBJECT-GROUP
        OBJECTS     { rptrAddrSearchLock,
```

```
                      rptrAddrSearchStatus,
                      rptrAddrSearchAddress,
                      rptrAddrSearchState,
                      rptrAddrSearchGroup,
                      rptrAddrSearchPort,
                      rptrAddrSearchOwner }
        STATUS      current
        DESCRIPTION
            "Active MAC address search group and topology
            mapping support for repeaters."
        ::= { snmpRptrModObjGrps 7 }

    snmpRptrGrpTopNPort OBJECT-GROUP
        OBJECTS     { rptrTopNPortRepeaterId,
                      rptrTopNPortRateBase,
                      rptrTopNPortTimeRemaining,
                      rptrTopNPortDuration,
                      rptrTopNPortRequestedSize,
                      rptrTopNPortGrantedSize,
                      rptrTopNPortStartTime,
                      rptrTopNPortOwner,
                      rptrTopNPortRowStatus,
                      rptrTopNPortGroupIndex,
                      rptrTopNPortPortIndex,
                      rptrTopNPortRate }
        STATUS      current
        DESCRIPTION
            "Top ‘N’ group for repeater ports."
        ::= { snmpRptrModObjGrps 8 }

    ieee8023snmpDot3RptrNotGroup NOTIFICATION-GROUP
        NOTIFICATIONS { rptrInfoHealth,
                        rptrInfoResetEvent }
        STATUS      current
        DESCRIPTION
            "Conformance Group for repeater notifications.
             Formerly an empty group."
        ::= {snmpRptrModNotGrps 1}


    -- Compliance statements

    snmpRptrModCompl MODULE-COMPLIANCE
        STATUS      current
        DESCRIPTION
            "Compliance for the multisegment version of the
            MIB module for a repeater system with one or more
            repeater-units."

        MODULE -- this module
            MANDATORY-GROUPS { snmpRptrGrpBasic,
                               snmpRptrGrpMonitor,
                               snmpRptrGrpAddrTrack }

            GROUP snmpRptrGrpMonitor100
            DESCRIPTION
                "Implementation of this group is
                mandatory for managed repeater systems that
                contain 100 Mb/s repeaters."
```

```
        GROUP snmpRptrGrpMonitor100w64
        DESCRIPTION
            "Implementation of this group is
            mandatory for managed repeater systems that
            contain 100 Mb/s repeaters and that
            can support Counter64."

        GROUP snmpRptrGrpExtAddrTrack
        DESCRIPTION
            "Implementation of this group is
            recommended for repeater systems that have
            the necessary instrumentation to track
            MAC addresses of multiple DTEs attached
            to a single repeater port."

        GROUP snmpRptrGrpRptrAddrSearch
        DESCRIPTION
            "Implementation of this group is
            recommended for repeater systems that allow
            read-write access and that have
            the necessary instrumentation to
            search all incoming data streams
            for a particular MAC address."

        GROUP snmpRptrGrpTopNPort
        DESCRIPTION
            "Implementation of this group is
            recommended for repeater systems that have
            the necessary resources to support
            TopN statistics reporting."

        GROUP ieee8023snmpDot3RptrNotGroup
        DESCRIPTION
            "Implementation of this group is
             recommended for repeaters that
             support notifications."

    ::= { snmpRptrModCompls 1 }

END
```

8. Ethernet data terminal equipment (DTE) power via medium dependent interface (MDI) MIB module

8.1 Introduction

This clause defines a portion of the MIB for use with SNMP. In particular, it defines a set of MIB objects to manage Power via MDI Power Sourcing Equipment (PSE).

8.2 Overview

IEEE Std 802.3 defines the hardware registers that will allow for management interfaces to be built for a DTE Power via MDI device. The MIB module defined in this clause extends the Ethernet-like interface MIB defined in Clause 10 with the management objects required for the management of the DTE Power via MDI devices and ports.

8.3 MIB structure

These MIB objects are categorized into three MIB groups.

The pethPsePortTable defines the objects used for configuring and describing the status of ports on a PSE device. Examples of PSE devices are Ethernet switches that support power Ethernet and mid-span devices.

The pethMainPseObjects MIB group defines the management objects for a managed main power source in a PSE device. Ethernet switches are one example of devices that would support these objects.

The pethNotificationControlTable includes objects that control the transmission of notifications from the agent to a management application.

8.4 Security considerations for Ethernet data terminal equipment (DTE) power via medium dependent interface (MDI) MIB module

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

Setting the following objects to incorrect values can result in improper operation of the PSE, including the possibility that the PD does not receive power from the PSE port:

— pethPsePortAdminEnable
— pethPsePortPowerPairs
— pethPsePortPowerPriority
— pethPsePortType

Setting the following objects to incorrect values can result in an excessive number of traps being sent to network management stations:

— pethMainPseUsageThreshold
— pethNotificationControlEnable

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. These are as follows:

- pethPsePortPowerPairsControlAbility
- pethPsePortPowerPriority
- pethPsePortPowerClassifications

It is thus important to control GET and/or NOTIFY access to these objects and possibly to encrypt their values when sending them over the network via SNMP.

8.5 MIB module definition

An ASCII text version of the MIB definition can be found at the following URL[15]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C8mib.txt

[15]Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.

```
IEEE8023-POWER-ETHERNET-MIB DEFINITIONS ::= BEGIN

IMPORTS
           MODULE-IDENTITY, OBJECT-TYPE, Integer32,
           Gauge32, Counter32, NOTIFICATION-TYPE, org
                   FROM SNMPv2-SMI
           TruthValue
                   FROM SNMPv2-TC
           MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
                   FROM SNMPv2-CONF

            SnmpAdminString
                    FROM SNMP-FRAMEWORK-MIB;

    ieee8023powerEthernetMIB MODULE-IDENTITY

        LAST-UPDATED "201304110000Z" -- April 11, 2013
        ORGANIZATION
          "IEEE 802.3 working group"
        CONTACT-INFO
            "WG-URL: http://www.ieee802.org/3/index.html
            WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

            Contact: Howard Frazier
            Postal:  3151 Zanker Road
                     San Jose, CA 95134
                     USA
            Tel:     +1.408.922.8164
            E-mail:  hfrazier@broadcom.com"

        DESCRIPTION
              "The MIB module for managing Power Source Equipment
               (PSE)specified in IEEE Std 802.3 Clause 33."

      REVISION    "201304110000Z" -- April 11, 2013
      DESCRIPTION
             "Revision, based on an earlier version in IEEE Std 802.3.1-2011."

      REVISION    "201102020000Z" -- February 2, 2011
      DESCRIPTION
             "Initial version, based on an earlier version published
              as RFC 3621."

          ::= { org ieee(111) standards-association-numbers-series-standards(2)
                lan-man-stds(802) ieee802dot3(3) ieee802dot3dot1mibs(1) 8 }

pethNotifications OBJECT IDENTIFIER ::= { ieee8023powerEthernetMIB 0 }
pethObjects       OBJECT IDENTIFIER ::= { ieee8023powerEthernetMIB 1 }
pethConformance   OBJECT IDENTIFIER ::= { ieee8023powerEthernetMIB 2 }

-- PSE Objects

  pethPsePortTable OBJECT-TYPE
       SYNTAX      SEQUENCE OF PethPsePortEntry
       MAX-ACCESS  not-accessible
       STATUS      current
       DESCRIPTION
           "A table of objects that display and control the power
            characteristics of power Ethernet ports on a Power Source
```

```
            Equipment (PSE) device. This group will be implemented in
            managed power Ethernet switches and mid-span devices.
            Values of all read-write objects in this table are
            persistent at restart/reboot."
        ::= { pethObjects 1 }

    pethPsePortEntry OBJECT-TYPE
        SYNTAX      PethPsePortEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
               "A set of objects that display and control the power
               characteristics of a power Ethernet PSE port."
        INDEX    { pethPsePortGroupIndex , pethPsePortIndex  }
        ::= { pethPsePortTable 1 }

    PethPsePortEntry ::= SEQUENCE {
        pethPsePortGroupIndex                        Integer32,
        pethPsePortIndex                             Integer32,
        pethPsePortAdminEnable                       TruthValue,
        pethPsePortPowerPairsControlAbility          TruthValue,
        pethPsePortPowerPairs                        INTEGER,
        pethPsePortDetectionStatus                   INTEGER,
        pethPsePortPowerPriority                     INTEGER,
        pethPsePortMPSAbsentCounter                  Counter32,
        pethPsePortType                              SnmpAdminString,
        pethPsePortPowerClassifications              INTEGER,
        pethPsePortInvalidSignatureCounter           Counter32,
        pethPsePortPowerDeniedCounter                Counter32,
        pethPsePortOverLoadCounter                   Counter32,
        pethPsePortShortCounter                      Counter32,
        pethPsePortActualPower                       Integer32,
        pethPsePortPowerAccuracy                     Integer32,
        pethPsePortCumulativeEnergy                  Counter32

   }

      pethPsePortGroupIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "This variable uniquely identifies the group
             containing the port to which a power Ethernet PSE is
             connected. Group means box in the stack, module in a
             rack and the value 1 shall be used for non-modular devices.
             Furthermore, the same value shall be used in this variable,
             pethMainPseGroupIndex, and pethNotificationControlGroupIndex
             to refer to a given box in a stack or module in a rack."
        ::= { pethPsePortEntry 1 }

      pethPsePortIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "This variable uniquely identifies the power Ethernet PSE
             port within group pethPsePortGroupIndex to which the
             power Ethernet PSE entry is connected."
```

```
       ::= { pethPsePortEntry 2 }

     pethPsePortAdminEnable OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "true (1) An interface that can provide the PSE functions.
         false(2) The interface will act as it would if it had no PSE
         function."

    REFERENCE
      "IEEE Std 802.3, 30.9.1.1.2 aPSEAdminState"
    ::= { pethPsePortEntry 3 }

     pethPsePortPowerPairsControlAbility OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Describes the capability of controlling the power pairs
         functionality to switch pins for sourcing power.
         The value true indicate that the device has the capability
         to control the power pairs. When false the PSE Pinout
         Alternative used cannot be controlled through the
         PethPsePortAdminEnable attribute."
    REFERENCE
      "IEEE Std 802.3, 30.9.1.1.3
       aPSEPowerPairsControlAbility"
    ::= { pethPsePortEntry 4 }

    pethPsePortPowerPairs OBJECT-TYPE
    SYNTAX INTEGER   {
              signal(1),
              spare(2)
     }
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Describes or controls the pairs in use. If the value of
         pethPsePortPowerPairsControl is true, this object is
         writeable.
         A value of signal(1) means that the signal pairs
         only are in use.
         A value of spare(2) means that the spare pairs
         only are in use."
    REFERENCE
      "IEEE Std 802.3, 30.9.1.1.4 aPSEPowerPairs"
    ::= { pethPsePortEntry 5 }

     pethPsePortDetectionStatus OBJECT-TYPE
    SYNTAX INTEGER   {
            disabled(1),
            searching(2),
              deliveringPower(3),
              fault(4),
              test(5),
              otherFault(6)
     }
```

```
     MAX-ACCESS read-only
     STATUS current
     DESCRIPTION
         "Describes the operational status of the port PD detection.
          A value of disabled(1)- indicates that the PSE State diagram
          is in the state DISABLED.
          A value of deliveringPower(3) - indicates that the PSE State
          diagram is in the state POWER_ON for a duration greater than
          tlim max (see IEEE Std 802.3 Table 33-11).
          A value of fault(4) - indicates that the PSE State diagram is
          in the state TEST_ERROR.
          A value of test(5) - indicates that the PSE State diagram is
          in the state TEST_MODE.
          A value of otherFault(6) - indicates that the PSE State
          diagram is in the state IDLE due to the variable
          error_conditions.
          A value of searching(2)- indicates the PSE State diagram is
          in a state other than those listed above."
     REFERENCE
       "IEEE Std 802.3, 30.9.1.1.5
        aPSEPowerDetectionStatus"
     ::= { pethPsePortEntry 6 }

      pethPsePortPowerPriority OBJECT-TYPE
     SYNTAX INTEGER   {
                critical(1),
                high(2),
                low(3)
      }
     MAX-ACCESS read-write
     STATUS current
     DESCRIPTION
         "This object controls the priority of the port from the point
          of view of a power management algorithm. The priority that
          is set by this variable could be used by a control mechanism
          that prevents over current situations by disconnecting first
          ports with lower power priority. Ports that connect devices
          critical to the operation of the network - like the E911
          telephones ports - should be set to higher priority."
     ::= { pethPsePortEntry 7 }

    pethPsePortMPSAbsentCounter OBJECT-TYPE
     SYNTAX Counter32
     MAX-ACCESS read-only
     STATUS current
     DESCRIPTION
           "This counter is incremented when the PSE state diagram
              transitions directly from the state POWER_ON to the

              state IDLE due to tmpdo_timer_done being asserted."
     REFERENCE
       "IEEE Std 802.3, 30.9.1.1.11
        aPSEMPSAbsentCounter"
     ::= { pethPsePortEntry 8 }

    pethPsePortType OBJECT-TYPE
     SYNTAX SnmpAdminString
     MAX-ACCESS read-write
```

```
    STATUS current
    DESCRIPTION
        "A manager will set the value of this variable to indicate
         the type of powered device that is connected to the port.
         The default value supplied by the agent if no value has
         ever been set should be a zero-length octet string."
    ::= { pethPsePortEntry 9 }

    pethPsePortPowerClassifications OBJECT-TYPE
     SYNTAX INTEGER   {
               class0(1),
               class1(2),
               class2(3),
               class3(4),
               class4(5)
     }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Classification is a way to tag different terminals on the
        Power over LAN network according to their power consumption.
        Devices such as IP telephones, WLAN access points and others,
        will be classified according to their power requirements.

        The meaning of the classification labels is defined in the
        IEEE specification.

       This variable is valid only while a PD is being powered,
        that is, while the attribute pethPsePortDetectionStatus
        is reporting the enumeration deliveringPower."
    REFERENCE
      "IEEE Std 802.3, 30.9.1.1.6
       aPSEPowerClassification"
   ::= { pethPsePortEntry 10 }

   pethPsePortInvalidSignatureCounter OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current

    DESCRIPTION
       "This counter is incremented when the PSE state diagram
         enters the state SIGNATURE_INVALID."
    REFERENCE
          "IEEE Std 802.3, 30.9.1.1.7
           aPSEInvalidSignatureCounter"
    ::= { pethPsePortEntry 11 }

   pethPsePortPowerDeniedCounter OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
          "This counter is incremented when the PSE state diagram
             enters the state POWER_DENIED."
    REFERENCE
      "IEEE Std 802.3, 30.9.1.1.8
       aPSEPowerDeniedCounter"
    ::= { pethPsePortEntry 12 }
```

```
pethPsePortOverLoadCounter OBJECT-TYPE
 SYNTAX Counter32
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
       "This counter is incremented when the PSE state diagram
          enters the state ERROR_DELAY_OVER."
 REFERENCE
   "IEEE Std 802.3, 30.9.1.1.9
    aPSEOverLoadCounter"
 ::= { pethPsePortEntry 13 }

pethPsePortShortCounter OBJECT-TYPE
 SYNTAX Counter32
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
       "This counter is incremented when the PSE state diagram
          enters the state ERROR_DELAY_SHORT."
 REFERENCE
   "IEEE Std 802.3, 30.9.1.1.10
    aPSEShortCounter"
 ::= { pethPsePortEntry 14 }


pethPsePortActualPower       OBJECT-TYPE
  SYNTAX Integer32
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
        "See IEEE Std 802.3, 30.9.1.1.12 aPSEActualPower."
  REFERENCE
        "IEEE Std 802.3, 30.9.1.1.12 aPSEActualPower."
  ::= { pethPsePortEntry 15 }


pethPsePortPowerAccuracy     OBJECT-TYPE
  SYNTAX Integer32
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
        "See IEEE Std 802.3, 30.9.1.1.13 aPSEPowerAccuracy."
  REFERENCE
        "IEEE Std 802.3, 30.9.1.1.13 aPSEPowerAccuracy."
  ::= { pethPsePortEntry 16 }


pethPsePortCumulativeEnergy     OBJECT-TYPE
  SYNTAX Counter32
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
        "See IEEE Std 802.3, 30.9.1.1.14 aPSECumulativeEnergy."
  REFERENCE
        "IEEE Std 802.3, 30.9.1.1.14 aPSECumulativeEnergy."
  ::= { pethPsePortEntry 17 }
```

```
-- Main PSE Objects

pethMainPseObjects       OBJECT IDENTIFIER ::= { pethObjects 3 }

pethMainPseTable OBJECT-TYPE
       SYNTAX      SEQUENCE OF PethMainPseEntry
       MAX-ACCESS  not-accessible
       STATUS      current
       DESCRIPTION
           "A table of objects that display and control attributes
            of the main power source in a PSE  device. Ethernet
            switches are one example of devices that would support
            these objects.
            Values of all read-write objects in this table are
            persistent at restart/reboot."
       ::= { pethMainPseObjects 1 }

   pethMainPseEntry OBJECT-TYPE
       SYNTAX      PethMainPseEntry
       MAX-ACCESS  not-accessible
       STATUS      current
       DESCRIPTION
            "A set of objects that display and control the Main
             power of a PSE."
       INDEX    { pethMainPseGroupIndex }
       ::= { pethMainPseTable 1 }

   PethMainPseEntry ::= SEQUENCE {
       pethMainPseGroupIndex
           Integer32,
       pethMainPsePower
           Gauge32 ,
       pethMainPseOperStatus
           INTEGER,
       pethMainPseConsumptionPower
           Gauge32,
       pethMainPseUsageThreshold
           Integer32
   }
     pethMainPseGroupIndex OBJECT-TYPE
       SYNTAX       Integer32 (1..2147483647)
       MAX-ACCESS  not-accessible
       STATUS      current
       DESCRIPTION
           "This variable uniquely identifies the group to which
           power Ethernet PSE is connected. Group means (box in
           the stack, module in a rack) and the value 1 shall be
           used for non-modular devices. Furthermore, the same
           value shall be used in this variable, pethPsePortGroupIndex,
           and pethNotificationControlGroupIndex to refer to a
           given box in a stack or module in a rack."
       ::= { pethMainPseEntry 1 }

     pethMainPsePower OBJECT-TYPE
       SYNTAX      Gauge32  (1..65535)
       UNITS      "Watts"
       MAX-ACCESS  read-only
       STATUS      current
       DESCRIPTION
```

```
                "The nominal power of the PSE expressed in Watts."
        ::= { pethMainPseEntry 2 }

      pethMainPseOperStatus OBJECT-TYPE
        SYNTAX INTEGER   {
                on(1),
                off(2),
                faulty(3)
           }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "The operational status of the main PSE."
        ::= { pethMainPseEntry 3 }

      pethMainPseConsumptionPower OBJECT-TYPE
        SYNTAX      Gauge32
        UNITS      "Watts"
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
                "Measured usage power expressed in Watts."
        ::= { pethMainPseEntry 4 }

      pethMainPseUsageThreshold OBJECT-TYPE
        SYNTAX      Integer32  (1..99)
        UNITS      "%"
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
                 "The usage threshold expressed in percents for
                 comparing the measured power and initiating
                 an alarm if the threshold is exceeded."
        ::= { pethMainPseEntry 5 }

-- Notification  Control  Objects

pethNotificationControl        OBJECT IDENTIFIER ::= { pethObjects 4 }

pethNotificationControlTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF PethNotificationControlEntry
        MAX-ACCESS  not-accessible

        STATUS      current
        DESCRIPTION
             "A table of objects that display and control the
             Notification on a PSE  device.
             Values of all read-write objects in this table are
             persistent at restart/reboot."
        ::= { pethNotificationControl 1 }

    pethNotificationControlEntry OBJECT-TYPE
        SYNTAX      PethNotificationControlEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
             "A set of objects that control the Notification events."
        INDEX    { pethNotificationControlGroupIndex }
        ::= { pethNotificationControlTable 1 }
```

```
    PethNotificationControlEntry ::= SEQUENCE {
        pethNotificationControlGroupIndex
            Integer32,
        pethNotificationControlEnable
            TruthValue
    }
      pethNotificationControlGroupIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
             "This variable uniquely identifies the group. Group
             means box in the stack, module in a rack and the value
             1 shall be used for non-modular devices. Furthermore,
             the same value shall be used in this variable,
             pethPsePortGroupIndex, and
             pethMainPseGroupIndex to refer to a given box in a
             stack or module in a rack."
        ::= { pethNotificationControlEntry 1 }

       pethNotificationControlEnable  OBJECT-TYPE
        SYNTAX             TruthValue
        MAX-ACCESS         read-write
        STATUS             current
        DESCRIPTION
              "This object controls, on a per-group basis, whether
              or not notifications from the agent are enabled. The
              value true(1) means that notifications are enabled; the
              value false(2) means that they are not."
        ::= { pethNotificationControlEntry 2 }
--
-- Notifications Section
--
--

      pethPsePortOnOffNotification NOTIFICATION-TYPE
          OBJECTS     { pethPsePortDetectionStatus }
          STATUS      current
          DESCRIPTION
                "This Notification indicates if Pse Port is delivering or
                not power to the PD. This Notification should be sent on
                every status change except in the searching mode.
                At least 500 msec shall elapse between notifications
                being emitted by the same object instance."
           ::= { pethNotifications 1 }

      pethMainPowerUsageOnNotification NOTIFICATION-TYPE
          OBJECTS     { pethMainPseConsumptionPower  }
          STATUS      current
          DESCRIPTION
                "This Notification indicate PSE Threshold usage
                indication is on, the usage power is above the
                threshold. At least 500 msec shall elapse between
                notifications being emitted by the same object
                instance."
          ::= { pethNotifications 2 }

       pethMainPowerUsageOffNotification NOTIFICATION-TYPE
```

```
         OBJECTS     { pethMainPseConsumptionPower }
         STATUS      current
         DESCRIPTION
               "This Notification indicates PSE Threshold usage indication
               off, the usage power is below the threshold.
               At least 500 msec shall elapse between notifications being
               emitted by the same object instance."
         ::= { pethNotifications 3 }

--
-- Conformance statements
--
pethCompliances OBJECT IDENTIFIER ::= { pethConformance 1 }
pethGroups      OBJECT IDENTIFIER ::= { pethConformance 2 }

-- Compliance statements

pethCompliance MODULE-COMPLIANCE
       STATUS  current
       DESCRIPTION
               "Describes the requirements for conformance to the
               Power Ethernet MIB."

       MODULE  -- this module
           MANDATORY-GROUPS { pethPsePortGroup,
                              pethPsePortNotificationGroup,
                              pethNotificationControlGroup
                            }
           GROUP   pethMainPseGroup
           DESCRIPTION
                "The pethMainPseGroup is mandatory for PSE systems
                that implement a main power supply."
           GROUP   pethMainPowerNotificationGroup
           DESCRIPTION
               "The pethMainPowerNotificationGroup is mandatory for
               PSE systems that implement a main power supply."
       ::= { pethCompliances 1 }

pethPsePortGroup OBJECT-GROUP
    OBJECTS {
       pethPsePortAdminEnable,
       pethPsePortPowerPairsControlAbility,
       pethPsePortPowerPairs,
       pethPsePortDetectionStatus,
       pethPsePortPowerPriority,
       pethPsePortMPSAbsentCounter,
       pethPsePortInvalidSignatureCounter,
       pethPsePortPowerDeniedCounter,
       pethPsePortOverLoadCounter,
       pethPsePortShortCounter,
       pethPsePortType,
       pethPsePortPowerClassifications,
       pethPsePortActualPower,
       pethPsePortPowerAccuracy,
       pethPsePortCumulativeEnergy
    }
    STATUS  current
    DESCRIPTION
          "PSE Port objects."
```

```
   ::= { pethGroups 1 }

pethMainPseGroup OBJECT-GROUP
    OBJECTS {
       pethMainPsePower,
       pethMainPseOperStatus,
       pethMainPseConsumptionPower,
       pethMainPseUsageThreshold
    }
    STATUS  current
    DESCRIPTION
            "Main PSE Objects."
    ::= { pethGroups 2 }

pethNotificationControlGroup OBJECT-GROUP

    OBJECTS {
       pethNotificationControlEnable
    }
    STATUS  current
    DESCRIPTION
            "Notification Control Objects."
    ::= { pethGroups 3 }

pethPsePortNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS { pethPsePortOnOffNotification}
    STATUS           current
    DESCRIPTION  "Pse Port Notifications."
    ::= { pethGroups 4 }

  pethMainPowerNotificationGroup NOTIFICATION-GROUP
     NOTIFICATIONS { pethMainPowerUsageOnNotification,
                      pethMainPowerUsageOffNotification}
    STATUS           current
    DESCRIPTION  "Main PSE Notifications."
      ::= { pethGroups 5 }

END
```

9. Ethernet passive optical networks (EPON) MIB module

9.1 Overview

This clause defines a MIB module for use with SNMP to manage 1G-EPON interfaces for Ethernet Passive Optical Networks. The clause contains a list of management objects based on the attributes defined in the relevant parts of Clause 30 of IEEE Std 802.3, referring to EPON.

9.1.1 EPON architecture highlights

9.1.1.1 Introduction

The EPON standard, now part of IEEE Std 802.3, defines the Physical Layer and Media Access Control sublayer of EPON interfaces. EPON is a variant of Gigabit Ethernet used in optical access. The passive optical network (PON) comprises sections of single-mode fiber connected with passive optical splitter/coupler devices, forming a passive optical tree, as shown in Figure 9-1. Individual branches of the PON are terminated with the optical line terminal (OLT) in the central office and optical network units (ONUs) near the subscribers. ONUs can be located either in some remote location (e.g., basement in a multidwelling unit) or directly at the subscriber premises. Various types of customer premises equipment (CPE) can be connected to ONUs or even integrated with such devices. Figure 9-1 presents an example PON topology.



Figure 9-1—PON topology example

The IEEE layering architecture of an EPON interface is defined in the diagram of Figure 56-2 in IEEE Std 802.3. The following clauses in IEEE Std 802.3 define the corresponding layers of an EPON interface:

— Clause 30: Management
— Clause 60: PMD for EPON media (burst-mode PMD)
— Clause 64: MPCP (Multipoint Control Protocol), which defines the Multipoint architecture, and control protocol for the media access of EPON.
— Clause 65: Reconciliation Sublayer and Physical Coding Sublayer, which defines a number of extensions to standard Gigabit Ethernet PCS, i.e.:
  a) Definition of Point-to-Point emulation function for EPON
  b) Definition of the optional (frame-based) FEC for EPON
  c) PMA for EPON

9.1.1.2 Principles of operation

The EPON interface specification extends the specification of Gigabit Ethernet as described in Clause 35 and Clause 36 of IEEE Std 802.3. The Ethernet MAC operates at the data rate of 1 Gb/s, and it is connected to a media-dependent interface through the GMII interface, as described in Clause 35. The EPON PCS layer extends the Gigabit Ethernet PCS as described in Clause 36. New, EPON-specific layers are added to Gigabit Ethernet layers in the following locations:

— MPCP is placed in the MAC control layer, providing EPON media access, station discovery, and registration protocol.

— Functionality of the reconciliation sublayer (RS) of Gigabit Ethernet was extended, creating logical links over shared passive optical medium, providing private transmission channels to each of the connected ONUs.

— (Optional) FEC functionality located between the PCS and PMA layers was added, extending the Gigabit Ethernet PCS layer, enhancing reach and split performance of the EPON optical link.

Figure 9-2 presents the EPON layering model.



Figure 9-2—Relationship of Multipoint MAC control and the OSI protocol stack

9.1.1.3 Physical media

The physical link in EPON comprises single-mode fiber. The OLT and ONUs are connected through a passive optical network comprising sections of single-mode fiber interconnected with passive splitter/ coupler devices.

The term *downstream* denotes transmission from the OLT to all connected ONUs, while the term *upstream* denotes transmission from the connected ONUs (one at the time) to the OLT. Upstream and downstream transmissions are wavelength division multiplexed (WDM) into a single strand of single-mode fiber, sharing the same physical link.

The downstream transmission channel is continuously available to the OLT;; thus, Time Division Multiplexing (TDM) is used. Transmissions from the OLT arrive at all of the connected ONUs and the individual ONUs filter data from the OLT's transmission based on the logical link identifiers (LLIDs) assigned to them during the registration and discovery process.

The upstream transmission channel is shared among a number of connected and registered ONUs using Time Division Multiple Access (TDMA). Access to the upstream channel is controlled via the Multipoint Control Protocol (MPCP), where the OLT plays the role of the master and ONUs play the role of slave devices. An ONU upon registration remains silent until registered, and once registered, it transmits data toward OLT only when granted a transmission opportunity (slot).

9.1.1.4 PMD specifications

The EPON PMD specifications are based on a wavelength plan similar to that used by ITU-T G.983.1. The OLT and ONU optical parameters were derived in part from earlier 1000 Mb/s Ethernet PMD specifications, with the addition of WDM capabilities, and burst mode operation for ONU transmitters and the OLT receiver.

The upstream burst mode operation capability corresponds directly to the TDMA operation in the upstream direction, where queued data is burst from individual ONUs at full data rate for the duration of the allocated transmission period. Once completed, the ONU goes silent and another ONU starts transmitting its data.

9.1.1.5 Point-to-point emulation

The downstream link is a broadcast medium, which means that all data transmitted by the OLT is received by all connected ONUs. In order to facilitate compliance of EPON with Ethernet architecture, the P2PE function was included in the RS, creating a series of logical links between the OLT and connected ONUs. An additional broadcast link is also provided for delivery of any broadcast content. In this way, EPON becomes a collection of logical P2P connections established between the OLT and the ONUs. Therefore, the OLT can be seen as an Ethernet device with N+1 logical ports (N P2P logical interfaces and 1 broadcast interface, where N designates the number of connected ONUs).

Logical links also provide a solution for privacy of data, which otherwise would be shared by all subscribers connected to a single OLT port. In this way, each subscriber is isolated and restricted to accessing data streams addressed only to that particular subscriber.

This concept is illustrated in Figure 9-3, which shows an example of an EPON with a single OLT and three connected ONUs.

The single copy broadcast channel (addressed with a special, reserved LLID, see 65.1.3.1 of IEEE Std 802.3) was added to take advantage of the broadcast transmission capability of the underlying physical medium. In this way, it is very simple and very bandwidth efficient to deliver broadcast content to all ONUs at the same time, avoiding the need to replicate data into a series of P2P links.

Editor's Note (to be removed prior to publication):

Reference to IEEE Std 802.1D was replaced with IEEE Std 802.1Q (text and Figure 9-3) per Maintenance Request 1383 (see https://www.ieee802.org/3/maint/requests/maint_1383.pdf)

The ONUs filter all downstream data and drop all frames addressed to other devices. Only broadcast frames and frames with correct unicast logical link ID (LLID) are admitted and processed. The LLID replaces two octets of the Ethernet frame preamble, identifying a logical link established between the OLT and the given ONU during the discovery and registration process. The LLID indicates the destination port in the downstream and the source port in the upstream. The logical links are used effectively to prevent EPON from violating the IEEE 802.1Q bridging rules.



Figure 9-3—Example of point-to-point emulation used between an OLT and three ONUs

9.1.1.6 Principles of the MPCP

The EPON standard comprises a mechanism for media access control, referred to as the Multipoint Control Protocol (MPCP). An access network architecture is different from a typical LAN environment, primarily in terms of network provisioning. An access network is an administrated environment, with an operator providing services and subscribers consuming it depending on service provisioning contracts. The operator controls the network, manages traffic and medium access, and enforces the service level agreements (SLAs). For instance, the available bandwidth is controlled and subscribers may be billed for services. In this sense, the access network (and EPON specifically) requires a media access control protocol that provides a mechanism for station discovery and registration as well as bandwidth provisioning capabilities.

In the MPCP, the OLT is considered to be the master, controlling a series of connected ONUs (slave devices). The OLT manages the network and controls access to network resources from individual slave devices. The MPCP is also used for provisioning upstream channel access to individual slave devices via a MPCPDU pair, i.e., GATE and REPORT. The MPCP is part of the MAC control layer, and MPCPDUs are considered MAC control messages, carrying a specific Ethertype of 0x8808. These messages are not forwarded outside of the EPON domain and are used to manage the EPON link only.

A concept of time exists in the MPCP in order to schedule the upstream transmission. A timestamp, which is transmitted in the MPCPDUs downstream by the OLT and received by the connected ONUs, is used to synchronize slave devices to the master device clock. This coordinates upstream transmissions from individual ONUs so that the transmissions arrive at the OLT at precisely the anticipated time, and thus, data from different ONUs does not overlap.

The MPCP plane is also used to measure the round-trip time (RTT) for each connected ONU. Each MPCPDU carries a generalized timestamp field, which is filled in by the transmitting station with the current value of its MPCP clock at the time when the given MPCPDU is transmitted. The RTT is measured first during the discovery and registration process and then updated regularly upon each exchange of MPCPDUs between the OLT and one of the ONUs. RTT is used by the OLT bandwidth scheduler to schedule upstream transmission slots for individual ONUs in a non-overlapping manner. The IEEE 802.3 EPON standard provides support for the network diameter (distance between the OLT and the farthest ONU) of nominally up to 20 km, which corresponds to the RTT of approximately 200 µs. However, nothing in the standard precludes support for larger network diameters.

The TDMA control is performed using a pair of MPDPUs, namely GATE generated by the OLT to indicate a future transmission opportunity to an ONU and REPORT generated by the ONU with information on the current queue status (bandwidth demand). Internal structure and possible encoding of GATE and REPORT MPCPDUs are defined in Clause 64 of IEEE Std 802.3.

A scheduling algorithm at the OLT, which is not defined in IEEE Std 802.3, is responsible for dividing the bandwidth and controlling the transmission delay of each ONU according to its SLA. The MPCP defines a closed loop operation in order for this algorithm to be efficient. The MPCP allows the ONUs to report on the amount of bandwidth they require for transmission using a special REPORT message. This allows allocating bandwidth to an ONU only when requested, relying on the statistical burst property of the traffic, and allowing different peak bandwidths for different ONUs at different times, hence, allowing oversubscription of the bandwidth. The REPORT message reports the amount of data waiting in the ONU queues.

In addition, the MPCP defines a protocol of auto-discovery and registration of ONUs.

The MPCP registration process is presented in Figure 9-4, while details are described in Clause 64 of IEEE Std 802.3.



Figure 9-4—Discovery handshake message exchange

A new ONU requests to register during a special upstream window (called Discovery Window), sending the REGISTER_REQ MPCPDU. More than one ONU may attempt registration during that window, which means that their REGISTER_REQ MPCPDUs can potentially collide at the OLT receiver, since the ONU-specific RTT is not yet known and transmissions from individual ONUs cannot be scheduled in an non-overlapping manner. A random backoff mechanism was therefore developed and is used to increase the registration success probability.

When the OLT receives a REGISTER_REQ MPCPDU from an ONU, a decision on registration is taken and an LLID is assigned to that ONU. Next, the OLT sends a REGISTER MPCPDU to that ONU, informing the given slave device whether it is admitted to a network or not. The registration process is completed with the ONU sending REGISTER_ACK MPCPDU to the OLT, confirming assigned parameters and registration in the network. From that point onward, the OLT can schedule transmissions from that ONU using its LLID, using the measured RTT so that its transmissions do not collide with other ONUs.

Additional higher layer protocols may be employed to authenticate the ONU and allow it to participate in the network; however, their specification is outside the scope of IEEE Std 802.3.

9.1.1.7 Forward error correction (FEC)

The optional FEC mechanism is defined to enhance the EPON link budget. All the passive components of the fiber plant attenuate the optical signal; thus, the target distance (network diameter) and the number of supported splits are limited by the available link budget. The optional FEC mechanism increases the available link budget by improving the link BER from 10^{-4} to 10^{-12} (the target BER at the MAC), effectively increasing the target network diameter and/or split ratio. The target use of the increased power budget remains at the sole discretion of the network architects and is out of the scope of IEEE Std 802.3.

The optional FEC used in EPON is frame-based, meaning that parity information is added at the end of each Ethernet packet. Extra space between individual Ethernet packets is provided by the MAC rate adaptation function, while extra idle symbols were replaced within the FEC function.

The start and end of packet codewords also define the FEC boundaries, and they are outside the FEC protection. They are replaced by a series of symbols to reduce their vulnerability to link errors.

Figure 9-5 presents the structure of an FEC-protected EPON frame.

The optional FEC function is added to the extended Gigabit Ethernet PCS per 65.2 in IEEE Std 802.3. The added, optional FEC function introduces a fixed delay in the receive path and in the transmit path.

S_FEC	Preamble/SFD	Frame	FCS	T_FEC	Parity	T_FEC

Figure 9-5—FEC-protected frame

9.1.2 Management architecture

All EPON layers are accompanied by a management interface that is controlled through mechanisms defined in Clause 30 of IEEE Std 802.3. Since IEEE Std 802.3 specifications may be used for different applications (and hence are extensible), and some of the clauses may be used separately, the management clause allocates a separate package for each independent layer. The structure of the MIB modules follows this separation.

Figure 9-6 presents the relation of the MIB module groups to the individual IEEE 802.3 layers.

> ***Editor's Note (to be removed prior to publication):***
>
> Reference to IEEE Std 802.1D was replaced with IEEE Std 802.1Q (Figure 9-6) per Maintenance Request 1383 (see https://www.ieee802.org/3/maint/requests/maint_1383.pdf)

The association is straightforward for the ONU interface. There is one logical and one physical interface, and a single copy of each layer can be remotely queried by the OLT.

The OLT has a single physical interface and N logical interfaces, one for each logical link connected to an ONU. There is also one logical interface for the single copy broadcast link. Per layering diagram in Figure 9-6, the MAC sublayer is virtually replicated. Therefore, in this clause it was elected that management of logical interfaces is performed in the manner identical to management of any physical interfaces—an interface index is allocated for each one of the logical links, and an additional interface index is allocated for the OLT.



Figure 9-6—Relationship of the MIB groups to the EPON sublayers

For each physical interface, there would be an entry (ifIndex) in the tables of the interface MIB module defined in IETF RFC 2863, the MAU MIB module defined in Clause 13, and the Ethernet-like MIB module defined in Clause 10. Additionally, there would be entries (ifIndexes) for the virtual interfaces of the OLT interface. The justification for the additional allocation of indexes is that the virtual interfaces are quite well distinguished, as they connect different physical ONUs from the OLT side. For instance, there is a meaning for separate bad frames counter or bad octets counter for each virtual link, as the ONUs can be differently distanced. This is quite similar to a case of separate physical interfaces.

The same partition concept exists for the MIB module of this clause. Each row in the tables is indexed according to the ifIndex; specifically, there is a row for each virtual link. There are some control objects that are shared and are the same for the virtual interfaces (and they should have the same value for each ifIndex), but most of the objects have different values for N+1 logical interfaces at the OLT. This is done for each MIB group. It is different from the EPON layering diagram, which presents the P2MP layer as a single layer, while duplicating the MAC and MAC client layers (please see Figure 9-6). However, from a management perspective, it is more convenient to partition the management of the layers for the virtual links, as the atomic managed entity is the virtual link. It is also convenient to use the interface index of the virtual link for that purpose, as it is already used to index the rows of the virtual links at the Interface, MAU, and Ethernet-like interface MIBs.

9.2 MIB structure

This subclause defines the DOT3 EPON MIB module. The DOT3 EPON MIB module defines the objects used for management of the IEEE Std 802.3 EPON interfaces. These MIB objects are included in the following four groups:

a) MPCP MIB objects—MIB objects related to Clause 64 of IEEE Std 802.3, Multipoint Control Protocol attributes. The following tables are presented in this group:
    1) The dot3MpcpControlTable defines the objects used for the configuration and status indication, which are per logical link, of MPCP compliant interfaces.
    2) The dot3MpcpStatTable defines the statistics objects that are per logical link, of MPCP compliant interfaces.
    3) The operational mode of an OLT/ONU for the tables is defined by the dot3MpcpMode object in the dot3MpcpControlTable.
b) The OMPEmulation MIB objects—MIB objects related to Clause 65 of IEEE Std 802.3, point-to-point emulation attributes. The following tables are presented in this group:
    1) The dot3OmpEmulationTable defines the objects used for the configuration and status indication, which are per logical links, of OMPEmulation compliant interfaces.
    2) The dot3OmpEmulationStatTable defines the statistics objects that are per logical link, of OMPEmulation compliant interfaces.
    3) The operational mode of an OLT/ONU for the tables is defined by the dot3OmpEmulationType object in the dot3OmpEmulationTable.
c) The FEC MIB objects—MIB objects related to Clause 60 and Clause 65 of IEEE Std 802.3, EPON FEC attributes. The following table is presented in this group:
    1) The dot3EponFecTable defines the objects used for the configuration and status indication, which are per logical link, of FEC EPON compliant interfaces.
d) The EPON extended package MIB objects—MIB objects used for configuration and status indication with extended capabilities of the EPON interfaces. The following tables are presented in this group:
    1) The dot3ExtPkgControlTable defines the objects, which are per logical link, used for the configuration and status indication of EPON compliant interfaces.
    2) The dot3ExtPkgQueueTable defines the objects, which are per logical link, and per queue, used for the configuration and status indication of the ONU queues reported in the MPCP REPORT message, of EPON compliant interfaces.
    3) The dot3ExtPkgQueueSetsTable defines the objects, which are per logical link, per queue, and per queue_set, used for the configuration and status indication of the ONU queue_sets reported in the MPCP REPORT message, of EPON compliant interfaces.
    4) The dot3ExtPkgOptIfTable defines the objects, which are per logical link, used for the control and status indication of the optical interface of EPON compliant interfaces.

The interface MIB module defined in IETF RFC 2863 defines the interface index (ifIndex). Interface Index, as specified in IETF RFC 2863, is used in this MIB module as an index to the EPON MIB tables. The ifIndex is used to denote the physical interface and the virtual link interfaces at the OLT. The OLT interface and the virtual link interfaces are stacked using the ifStack table defined in IETF RFC 2863 and the ifInvStack defined in IETF RFC 2864. The OLT interface is the lower layer of all other interfaces associated with the virtual links.

As described in 9.1.2, each row in the tables is indexed according to the ifIndex; specifically, there is a row for each virtual link. There are a few control objects that are shared and have the same value for the virtual interfaces (and they should have the same value for each ifIndex), but most of the objects have different values for N+1 logical interfaces at the OLT. This is done for each MIB group. It is a bit different from the EPON layering diagram, which presents the P2MP layer as a single layer while duplicating the MAC and MAC client layers. However, from a management perspective, it is more convenient to partition the management of the layers for the virtual links, as the atomic managed entity is the virtual link. It is also convenient to use the interface index of the virtual link for that purpose, as it is already used to index the rows of the virtual links at the Interface, MAU, and Ethernet-like interface MIB modules.

The creation of the rows of the ONU interface is done at initialization. Table 9-1 presents the MPCP control table of ONU1 after initialization. A single row exists in the table.

Table 9-1—MPCP control table of ONU1 after initialization

MPCP control MIB object	Value
ifIndex	100
dot3MpcpOperStatus	true
dot3MpcpAdminState	true
dot3MpcpMode	onu
dot3MpcpSyncTime	0
dot3MpcpLinkID	0
dot3MpcpRemoteMACAddress	00:00:00:00:00:00
dot3MpcpRegistrationState	unregistered
dot3MpcpTransmitElapsed	0
dot3MpcpReceiveElapsed	0
dot3MpcpRoundTripTime	0

Table 9-2 presents the MPCP control table of ONU1 in working mode. A single row exists in the table.

Table 9-2—MPCP control table of ONU1 in working mode

MPCP control MIB object	Value
ifIndex	100
dot3MpcpOperStatus	true
dot3MpcpAdminState	true
dot3MpcpMode	onu
dot3MpcpSyncTime	25
dot3MpcpLinkID	1
dot3MpcpRemoteMACAddress	OLT_MAC_Address[a]
dot3MpcpRegistrationState	registered
dot3MpcpTransmitElapsed	10
dot3MpcpReceiveElapsed	10
dot3MpcpRoundTripTime	100

[a]OLT_MAC_Address is the MAC address of the OLT EPON interface.

The creation of the rows of the OLT interface and the broadcast virtual interface is done at initialization.

The creation of rows of the virtual interfaces at the OLT is done when the link is established (ONU registers) and the deletion is done when the link is deleted (ONU deregisters).

Table 9-3 presents the MPCP control table of the OLT after initialization, before the ONUs register. A single row exists in this table associated with the virtual broadcast link.

Table 9-3—MPCP control table of the OLT after initialization

MPCP control MIB object	Value
ifIndex	165535
dot3MpcpOperStatus	true
dot3MpcpAdminState	true
dot3MpcpMode	olt
dot3MpcpSyncTime	25
dot3MpcpLinkID	65535
dot3MpcpRemoteMACAddress	BRCT_MAC_Address[a]
dot3MpcpRegistrationState	registered
dot3MpcpTransmitElapsed	10
dot3MpcpReceiveElapsed	100000
dot3MpcpRoundTripTime	0

[a]BRCT_MAC_Address is the MAC address of the broadcast EPON interface, which is the OLT MAC address.

Table 9-4 presents the MPCP control table of the OLT in working mode. Three rows exist in the table associated with the virtual links.

9.3 Relationship to other MIB modules

9.3.1 Relation to the Interfaces Group MIB and Ethernet-like interface MIB

This MIB module extends the objects of the Interfaces Group MIB and the Ethernet-like interface MIB for the EPON type interface. Therefore, if this module is implemented, the Interfaces Group MIB module

Table 9-4—MPCP control table of the OLT in working mode

MPCP control MIB object	Value	Value	Value
ifIndex	100001	100002	165535
dot3MpcpOperStatus	true	true	true
dot3MpcpAdminState	true	true	true
dot3MpcpMode	olt	olt	olt
dot3MpcpSyncTime	25	25	25
dot3MpcpLinkID	1	2	65535
dot3MpcpRemote MACAddress	ONU1_MAC_Address[a]	ONU2_MAC_Address[b]	BRCT_MAC_Address[c]
dot3MpcpRegistrationState	registered	registered	registered
dot3MpcpTransmitElapsed	10	10	10
dot3MpcpReceiveElapsed	10	10	10
dot3MpcpRoundTripTime	100	60	0

[a]ONU1_MAC_Address is the MAC address of the ONU1 EPON interface.
[b]ONU2_MAC_Address is the MAC address of the ONU2 EPON interface.
[c]BRCT_MAC_Address is the MAC address of the broadcast EPON interface, which is the OLT MAC address.

defined in IETF RFC 2863 and the Ethernet-like interface MIB module defined in Clause 10 shall also be implemented.

Thus, each managed EPON interface would have a corresponding entry in the mandatory tables of the Ethernet-like MIB module found in Clause 10, and likewise in the tables of the Interfaces Group MIB module found in IETF RFC 2863. Also, each managed virtual EPON interface would have a corresponding entry in the mandatory tables of the Ethernet-like MIB module found in Clause 10, and likewise in the tables of the Interfaces Group MIB module found in IETF RFC 2863 with a dedicated ifIndex for this interface.

In this clause, there is no replication of the objects from these MIBs. Therefore, for instance, the clause is defining the dot3MpcpRemoteMACAddress only while assuming that the local MAC address object is already defined in Clause 10.

This clause defines the specific EPON objects of an ONU interface and an OLT interface. Information in the tables is per LLID. The rows in the EPON MIB tables referring to the LLIDs are denoted with the corresponding ifIndexes of the virtual link interfaces.

Note that all virtual interfaces have the same physical MAC address at the OLT since the physical OLT interface used by all virtual interfaces is the same. The value of this physical MAC interface is specified in 64.1.2 of IEEE Std 802.3. The corresponding object of the Ethernet-like interface MIB is replicated for all virtual interfaces.

For example, the values of the Interfaces Group MIB objects are presented in the following tables, for an OLT with three registered ONUs.

Table 9-5 presents the objects of the Interfaces Group MIB of an ONU in working mode.

Table 9-5—Interfaces Group MIB of an ONU in working mode

Interfaces Group MIB object	Value
ifIndex	1
ifDescr	“interface description”
ifType	ethernetCsmacd (6) 1000base-Px
ifMtu	MTU size (1522)
ifSpeed	1000000000
ifPhysAddress	ONU_MAC_Address[a]
ifAdminStatus	up
ifOperStatus	Up
ifLastChange	ONUup_time
ifInOctets	ONU_octets_number
ifInUcastPkts	ONU_unicast_frame_number
ifInNUcastPkts	ONU_non_unicast_frame_number
ifInDiscards	ONU_discard_frame_number
ifInErrors	ONU_error_frame_number
ifInUnknownProtos	ONU_unknown_frame_number
ifOutOctets	ONU_octets_number
ifOutUcastPkts	ONU_unicast_frame_number
ifOutNUcastPkts	ONU_non_unicast_frame_number
ifOutDiscards	ONU_discard_frame_number
ifOutErrors	ONU_error_frame_number
ifOutQLen	ONU_queue_frame_number

[a]ONU_MAC_Address is the MAC address of the ONU EPON interface.

Table 9-6 presents the objects of the Interfaces Group MIB of the ONU interface.

Table 9-6—Interfaces Group MIB of the ONU interface

Interfaces Group MIB object	Value
ifIndex	100
ifDescr	“interface description”
ifType	ethernetCsmacd (6) 1000base-Px
ifMtu	MTU size (1522)
ifSpeed	1000000000
ifPhysAddress	ONU_MAC_Address[a]
ifAdminStatus	up
ifOperStatus	Up
ifLastChange	up_time
ifInOctets	ONU1_octets_number
ifInUcastPkts	ONU1_unicast_frame_number
ifInNUcastPkts	ONU1_non_unicast_frame_number
ifInDiscards	ONU1_discard_frame_number
ifInErrors	ONU1_error_frame_number
ifInUnknownProtos	ONU1_unknown_frame_number
ifOutOctets	ONU1_octets_number
ifOutUcastPkts	ONU1_unicast_frame_number
ifOutNUcastPkts	ONU1_non_unicast_frame_number
ifOutDiscards	ONU1_discard_frame_number
ifOutErrors	ONU1_error_frame_number
ifOutQLen	ONU1_queue_frame_number

[a]ONU_MAC_Address is the MAC address of the ONU EPON interface.

The following values will be set in the ifStack and ifInvStack tables related to this example.

ifStackTable:

— ifStackHigherLayer = 100, ifStackLowerLayer = 1 – map between the physical interface and the ONU

ifInvStackTable:

— ifStackLowerLayer = 1, ifStackHigherLayer = 100 – map between the ONU and the physical interface

Table 9-7 presents the Interfaces Group MIB objects of an OLT interface.

Table 9-7—Interfaces Group MIB objects of an OLT interface

Interfaces Group MIB object	Value
ifIndex	2
ifDescr	“interface description”
ifType	ethernetCsmacd (6) 1000base-Px
ifMtu	MTU size (1522)
ifSpeed	1000000000
ifPhysAddress	OLT_MAC_Address[a]
ifAdminStatus	up
ifOperStatus	Up
ifLastChange	OLTup_time
ifInOctets	OLT_octets_number
ifInUcastPkts	OLT_unicast_frame_number
ifInNUcastPkts	OLT_non_unicast_frame_number
ifInDiscards	OLT_discard_frame_number
ifInErrors	OLT_error_frame_number
ifInUnknownProtos	OLT_unknown_frame_number
ifOutOctets	OLT_octets_number
ifOutUcastPkts	OLT_unicast_frame_number
ifOutNUcastPkts	OLT_non_unicast_frame_number

Table 9-7—Interfaces Group MIB objects of an OLT interface *(continued)*

Interfaces Group MIB object	Value
ifOutDiscards	OLT_discard_frame_number
ifOutErrors	OLT_error_frame_number
ifOutQLen	OLT_queue_frame_number

[a]OLT_MAC_Address is the MAC address of the OLT EPON interface.

Table 9-8 presents the Interfaces Group MIB objects of an OLT interface, associated with the virtual link interfaces.

Table 9-8—Interfaces Group MIB objects of an OLT interface, associated with the virtual link interfaces

Interface MIB object	Value	Value	Value
ifIndex	200001	200002	265535
ifDescr	“interface description”	“interface description”	“interface description”
ifType	ethernetCsmacd (6)	ethernetCsmacd (6)	ethernetCsmacd (6)
ifMtu	MTUsize(1522)	MTUsize(1522)	MTUsize(1522)
ifSpeed	1000000000	1000000000	1000000000
ifPhysAddress	OLT_MAC_Address[a]	OLT_MAC_Address	OLT_MAC_Address
ifAdminStatus	up	up	up
ifOperStatus	Up	Up	Up
ifLastChange	ONU1_up_time	ONU2_up_time	up_time
ifInOctets	ONU1_octets_number	ONU2_octets_number	BRCT_octets_number
ifInUcastPkts	ONU1_unic_frame_num	ONU2_unic_frame_num	BRCT_unic_frame_num
ifInNUcastPkts	ONU1_non_unic_frame_num	ONU2_non_unic_frame_num	BRCT_non_unic_frame_num
ifInDiscards	ONU1_disc_frame_num	ONU2_disc_frame_num	BRCT_disc_frame_numr
ifInErrors	ONU1_err_frame_num	ONU2_err_frame_num	BRCT_err_frame_num
ifInUnknownProtos	ONU1_unknw_frame_num	ONU2_unknw_frame_num	BRCT_unknw_frame_num
ifOutOctets	ONU1_octets_number	ONU2_octets_number	BRCT_octets_number
ifOutUcastPkts	ONU1_unic_frame_num	ONU2_unic_frame_num	BRCT_unic_frame_num
ifOutNUcastPkts	ONU1_non_unic_frame_num	ONU2_non_unic_frame_num	BRCT_non_unic_frame_num

Table 9-8—Interfaces Group MIB objects of an OLT interface, associated with the virtual link interfaces *(continued)*

Interface MIB object	Value	Value	Value
ifOutDiscards	ONU1_disc_frame_num	ONU2_disc_frame_num	BRCT_disc_frame_num
ifOutErrors	ONU1_err_frame_num	ONU2_err_frame_num	BRCT_err_frame_num
ifOutQLen	ONU1_queue_frame_num	ONU2_queue_frame_num	BRCt_queue_frame_num

[a]OLT_MAC_Address is the MAC address of the OLT EPON interface.

The following values will be set in the ifStack and ifInvStack tables related to this example:

ifStackTable:

— ifStackHigherLayer = 265535, ifStackLowerLayer = 2 – map between the OLT physical interface and its broadcast virtual interface

— ifStackHigherLayer = 200001, ifStackLowerLayer = 2 – map between the OLT physical interface and its virtual interface of the 1st ONU

— ifStackHigherLayer = 200002, ifStackLowerLayer = 2 – map between the OLT physical interface and its virtual interface of the 2nd ONU

— ifStackHigherLayer = 200003, ifStackLowerLayer = 2 – map between the OLT physical interface and its virtual interface of the 3rd ONU

ifInvStackTable:

— ifStackLowerLayer = 2, ifStackHigherLayer = 265535 – map between the broadcast interface of the OLT and the OLT physical interface

— ifStackLowerLayer = 2, ifStackHigherLayer = 200001 – map between the OLT virtual interface of the 1st ONU and the OLT physical interface

— ifStackLowerLayer = 2, ifStackHigherLayer = 200002 – map between the OLT virtual interface of the 2nd ONU and the OLT physical interface

— ifStackLowerLayer = 2, ifStackHigherLayer = 200003 – map between the OLT virtual interface of the 3rd ONU and the OLT physical interface

The rows for the ONU interface, the OLT interface, and the OLT broadcast interface are created in initialization. The creation of a row for a virtual link is done when the virtual link is established (ONU registers), and deletion is done when the virtual link is deleted (ONU deregisters).

The EPON MIB module also extends the Interfaces Group MIB module with a set of counters, which are specific for the EPON interface. The EPON MIB module implements the same handling of the counters when the operation of the interface starts or stops. The interface MIB clause describes the possible behavior of counters when an interface is re-initialized using the ifCounterDiscontinuityTime indicator, indicating the discontinuity of the counters. See Section 3.1.5 of IETF RFC 2863 for more information. The counters of the EPON MIB should be handled in a similar manner.

9.3.2 Relation to the IEEE 802.3 MAU MIBs

The MAU types of the EPON Interface are defined in Clause 13. This clause assumes the implementation of the MAU MIB for this purpose and does not repeat the EPON MAU types. Therefore, if this module is implemented, the MAU-MIB module defined in Clause 13 shall also be implemented.

The handling of the ifMAU tables for the EPON case is similar to the handling described in the former subclause for the Interface and Ethernet-like interface MIBs. A single row exists for the ONU in the ifMauTable. A row for each virtual link (N+1 rows) exists at the OLT, with a separate value of ifMauIfIndex for each virtual link.

As specified above, the rows for the ONU interface, the OLT interface, and the OLT broadcast interface are created in initialization. The creation of a row for a virtual link is done when the virtual link is established (ONU registers), and deletion is done when the virtual link is deleted (ONU deregisters).

9.3.3 Relation to the Ethernet OAM MIB

The EPON interfaces are intended for use in optical subscriber access networks and most probably will be accompanied with the implementation of the OAM protocol defined in Clause 57 of IEEE Std 802.3. Therefore, the Ethernet OAM MIB module defined in Clause 6 may be implemented when this MIB module is implemented defining managed objects for the OAM protocol that are complementary to the EPON MIB module.

9.3.4 Relation to the bridge MIB

Editor's Note (to be removed prior to publication):

Reference to IEEE Std 802.1D was replaced with IEEE Std 802.1Q per Maintenance Request 1383 (see https://www.ieee802.org/3/maint/requests/maint_1383.pdf)

It is very probable that an EPON OLT will implement a bridging functionality above the EPON interface layer, bridging between the EPON users and the network. Bridge functionality is specified in IEEE Std 802.1Q. In this scenario, the virtual ports of the EPON are corresponding to the virtual bridge ports. There is a direct mapping between the bridge ports and the LLIDs, which are virtual EPON channels.

Therefore, the bridge MIB modules defined in IEEE Std 802.1Q [B5] may be implemented when the EPON MIB module is implemented for an EPON OLT, defining managed objects for the bridge layer.

The values of dot1dBasePortIfIndex would correspond to the ifIndex of the virtual port (1 for LLID1, 2 for LLID2, etc.).

The broadcast virtual EPON interface of the OLT has no direct mapping to a virtual bridge port as it is not port specific but used for broadcast traffic.

9.4 Mapping of IEEE 802.3 managed objects

This subclause contains the mapping between the managed objects defined in this clause and the attributes defined in Clause 30 of IEEE Std 802.3. Table 9-9 provides the mapping between the dot3EPON MIB module MPCP objects and the MPCP attributes of Clause 30 of IEEE Std 802.3.

Table 9-10 provides the mapping between the dot3EPON MIB module OMPEmulation objects and the OMPE attributes of Clause 30 of IEEE Std 802.3.

Table 9-9—oMPCP managed object class (30.3.5 of IEEE Std 802.3)

dot3EPON MIB module object	IEEE 802.3 attribute	Reference
ifIndex	aMPCPID	30.3.5.1.1
dot3MpcpOperStatus	aMPCPAdminState	30.3.5.1.2
dot3MpcpMode	aMPCPMode	30.3.5.1.3
dot3MpcpLinkID	aMPCPLinkID	30.3.5.1.4
dot3MpcpRemoteMACAddress	aMPCPRemoteMACAddress	30.3.5.1.5
dot3MpcpRegistrationState	aMPCPRegistrationState	30.3.5.1.6
dot3MpcpMACCtrlFramesTransmitted	aMPCPMACCtrlFramesTransmitted	30.3.5.1.7
dot3MpcpMACCtrlFramesReceived	aMPCPMACCtrlFramesReceived	30.3.5.1.8
dot3MpcpTxGate	aMPCPTxGate	30.3.5.1.9
dot3MpcpTxRegAck	aMPCPTxRegAck	30.3.5.1.10
dot3MpcpTxRegister	aMPCPTxRegister	30.3.5.1.11
dot3MpcpTxRegRequest	aMPCPTxRegRequest	30.3.5.1.12
dot3MpcpTxReport	aMPCPTxReport	30.3.5.1.13
dot3MpcpRxGate	aMPCPRxGate	30.3.5.1.14
dot3MpcpRxRegAck	aMPCPRxRegAck	30.3.5.1.15
dot3MpcpRxRegister	aMPCPRxRegister	30.3.5.1.16
dot3MpcpRxRegRequest	aMPCPRxRegRequest	30.3.5.1.17
dot3MpcpRxReport	aMPCPRxReport	30.3.5.1.18
dot3MpcpTransmitElapsed	aMPCPTransmitElapsed	30.3.5.1.19
dot3MpcpReceiveElapsed	aMPCPReceiveElapsed	30.3.5.1.20
dot3MpcpRoundTripTime	aMPCPRoundTripTime	30.3.5.1.21
dot3MpcpDiscoveryWindowsSent	aMPCPDiscoveryWindowsSent	30.3.5.1.22
dot3MpcpDiscoveryTimeout	aMPCPDiscoveryTimeout	30.3.5.1.23
dot3MpcpMaximumPendingGrants	aMPCPMaximumPendingGrants	30.3.5.1.24
dot3MpcpAdminState	aMPCPAdminControl	30.3.5.2.1
dot3MpcpSyncTime	SyncTime	64.3.3.2

Table 9-10—oOMPEmulation managed object class (30.3.7 of IEEE Std 802.3)

dot3EPON MIB module object	IEEE 802.3 attribute	Reference
ifIndex	aOMPEmulationID	30.3.7.1.1
dot3OmpEmulationType	aOMPEmulationType	30.3.7.1.2
dot3OmpEmulationSLDErrors	aSLDErrors	30.3.7.1.3
dot3OmpEmulationCRC8Errors	aCRC8Errors	30.3.7.1.4
dot3OmpEmulationGoodLLID	aGoodLLID	30.3.7.1.5
dot3OmpEmulationOnuPonCastLLID	aONUPONcastLLID	30.3.7.1.6
dot3OmpEmulationOltPonCastLLID	aOLTPONcastLLID	30.3.7.1.7
dot3OmpEmulationBadLLID	aBadLLID	30.3.7.1.8
dot3OmpEmulationBroadcastBitNotOnuLLid	N/A	—
dot3OmpEmulationOnuLLIDNotBroadcast	N/A	—
dot3OmpEmulationBroadcastBitPlusOnuLlid	N/A	—
dot3OmpEmulationNotBroadcastBitNotOnuLlid	N/A	—

Table 9-11 provides the mapping between the dot3EPON MIB module FEC objects and the MAU attributes of Clause 30 of IEEE Std 802.3.

Table 9-11—oMAU managed object class (30.5.1 of IEEE Std 802.3)

dot3EPON MIB module object	IEEE 802.3 attribute	Reference
dot3EponFecPCSCodingViolation	aPCSCodingViolation	30.5.1.1.14
dot3EponFecAbility	aFECAbility	30.5.1.1.15
dot3EponFecMode	aFECmode	30.5.1.1.16
dot3EponFecCorrectedBlocks	aFECCorrectedBlocks	30.5.1.1.17
dot3EponFecUncorrectableBlocks	aFECUncorrectableBlocks	30.5.1.1.18
dot3EponFecBufferHeadCodingViolation	N/A	—

9.5 Security considerations for Ethernet passive optical network (EPON) MIB module

There are number of managed objects defined in this MIB module that have a MAX-ACCESS clause of read-write or read-create. Writing to these objects can have potentially disruptive effects on network operation, including those listed in 9.5.1 to 9.5.13.

9.5.1 dot3MpcpAdminState

Changing the dot3MpcpAdminState state can lead to disabling the Multipoint Control Protocol on the respective interface, leading to the interruption of service for the users connected to the respective EPON interface.

9.5.2 dot3EponFecMode

Changing the dot3EponFecMode state can lead to disabling the Forward Error Correction on the respective interface, which can lead to a degradation of the optical link, and therefore, it may lead to an interruption of service for the users connected to the respective EPON interface.

9.5.3 dot3ExtPkgObjectReset

Changing the dot3ExtPkgObjectReset state can lead to a reset of the respective interface leading to an interruption of service for the users connected to the respective EPON interface.

9.5.4 dot3ExtPkgObjectPowerDown

Changing the dot3ExtPkgObjectPowerDown state can lead to a power down of the respective interface, leading to an interruption of service for the users connected to the respective EPON interface.

9.5.5 dot3ExtPkgObjectFecEnabled

Changing the dot3ExtPkgObjectFecEnabled state can lead to disabling the Forward Error Correction on the respective interface, which can lead to a degradation of the optical link, and therefore, it may lead to an interruption of service for the users connected to the respective EPON interface.

9.5.6 dot3ExtPkgObjectRegisterAction

Changing the dot3ExtPkgObjectRegisterAction state can lead to a change in the registration state of the respective interface, leading to a deregistration and an interruption of service for the users connected to the respective EPON interface.

9.5.7 dot3ExtPkgObjectReportNumThreshold

Changing the dot3ExtPkgObjectReportNumThreshold can lead to a change in the reporting of the ONU interface and therefore to a change in the bandwidth allocation of the respective interface. This change may lead to a degradation or an interruption of service for the users connected to the respective EPON interface.

9.5.8 dot3ExtPkgObjectReportThreshold

Changing the dot3ExtPkgObjectReportThreshold can lead to a change in the reporting of the ONU interface and therefore to a change in the bandwidth allocation of the respective interface. This change may lead to a degradation or an interruption of service for the users connected to the respective EPON interface.

9.5.9 dot3ExtPkgOptIfLowerInputPowerThreshold

Changing the dot3ExtPkgOptIfLowerInputPowerThreshold can lead to a Threshold Crossing Alert (TCA) being sent for the respective interface. This alert may be leading to an interruption of service for the users connected to the respective EPON interface, depending on the system action on such an alert.

9.5.10 dot3ExtPkgOptIfUpperInputPowerThreshold

Changing the dot3ExtPkgOptIfUpperInputPowerThreshold can lead to a Threshold Crossing Alert (TCA) being sent for the respective interface. This alert may be leading to an interruption of service for the users connected to the respective EPON interface, depending on the system action on such an alert.

9.5.11 dot3ExtPkgOptIfLowerOutputPowerThreshold

Changing the dot3ExtPkgOptIfLowerOutputPowerThreshold can lead to a Threshold Crossing Alert (TCA) being sent for the respective interface. This alert may be leading to an interruption of service for the users connected to the respective EPON interface, depending on the system action on such an alert.

9.5.12 dot3ExtPkgOptIfUpperOutputPowerThreshold

Changing the dot3ExtPkgOptIfUpperOutputPowerThreshold can lead to a Threshold Crossing Alert (TCA) being sent for the respective interface. This alert may be leading to an interruption of service for the users connected to the respective EPON interface, depending on the system action on such an alert.

9.5.13 dot3ExtPkgOptIfTransmitEnable

Changing the dot3ExtPkgOptIfTransmitEnable state can lead to a halt in the optical transmission of the respective interface, leading to an interruption of service for the users connected to the respective EPON interface.

9.6 MIB module definition

An ASCII text version of the MIB definition can be found at the following URL[16]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C9mib.txt

[16]Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.

```
IEEE8023-DOT3-EPON-MIB DEFINITIONS ::= BEGIN

     IMPORTS
         MODULE-IDENTITY, OBJECT-TYPE, Counter32,
         Integer32, Unsigned32, Counter64, org
             FROM SNMPv2-SMI
         TruthValue, MacAddress
             FROM SNMPv2-TC
         ifIndex
             FROM IF-MIB
         MODULE-COMPLIANCE, OBJECT-GROUP
             FROM SNMPv2-CONF
         ;

ieee8023dot3EponMIB MODULE-IDENTITY
        LAST-UPDATED "201304110000Z" -- April 11, 2013
        ORGANIZATION
          "IEEE 802.3 working group"
        CONTACT-INFO
            "WG-URL: http://www.ieee802.org/3/index.html
            WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

            Contact: Howard Frazier
            Postal:  3151 Zanker Road
                     San Jose, CA 95134
                     USA
            Tel:     +1.408.922.8164
            E-mail:  hfrazier@broadcom.com"
    DESCRIPTION
            "The objects in this MIB module are used to manage the
             Ethernet in the First Mile (EFM) Ethernet Passive Optical
             Network (EPON) Interfaces as defined in IEEE Std 802.3
             Clauses 60, 64, and 65.

             Of particular interest are Clause 64 (MultiPoint Control
             Protocol - MPCP), Clause 65 (Point-to-Multipoint
             Reconciliation Sublayer - P2MP RS), Clause 60 (Ethernet
             Passive Optical Network Physical Medium Dependent - EPON
             PMDs), Clause 30, ‘Management’, and Clause 45, ‘Management
             Data Input/Output (MDIO) Interface’."

    REVISION     "201304110000Z" -- April 11, 2013
    DESCRIPTION
            "Revision, based on an earlier version in IEEE Std 802.3.1-2011."

    REVISION     "201102020000Z" -- February 2, 2011
    DESCRIPTION
            "Initial version, based on an earlier version published
             as RFC 4837."

          ::= { org ieee(111) standards-association-numbers-series-standards(2)
                lan-man-stds(802) ieee802dot3(3) ieee802dot3dot1mibs(1) 9 }

dot3EponObjects OBJECT IDENTIFIER ::= { ieee8023dot3EponMIB 1}

dot3EponConformance OBJECT IDENTIFIER ::= { ieee8023dot3EponMIB 2}

-- MPCP MIB modules definitions (IEEE Std 802.3, Clause 30.3.5)
```

```
dot3EponMpcpObjects
     OBJECT IDENTIFIER ::= { dot3EponObjects 1 }

dot3MpcpControlTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF Dot3MpcpControlEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
            "A Table of dot3 MultiPoint Control Protocol (MPCP)
             MIB objects. The entries in the table are control and
             status objects of the MPCP.
             Each object has a row for every virtual link denoted by
             the corresponding ifIndex.
             The LLID field, as defined in the IEEE Std 802.3, is a 2-byte
             register (15-bit field and a broadcast bit) limiting the
             number of virtual links to 32768. Typically the number
             of expected virtual links in a PON is like the number of
             ONUs, which is 32-64, plus an additional entry for
             broadcast LLID."
    ::= { dot3EponMpcpObjects 1 }

dot3MpcpControlEntry OBJECT-TYPE
    SYNTAX  Dot3MpcpControlEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
            "An entry in the dot3 MPCP Control table.
             Rows exist for an OLT interface and an ONU interface.
             A row in the table is denoted by the ifIndex of the link
             and it is created when the ifIndex is created.
             The rows in the table for an ONU interface are created
             at system initialization.
             The row in the table corresponding to the OLT ifIndex
             and the row corresponding to the broadcast virtual link
             are created at system initialization.
             A row in the table corresponding to the ifIndex of a
             virtual links is created when a virtual link is
             established (ONU registers) and deleted when the virtual
             link is deleted (ONU deregisters)."
    INDEX  { ifIndex }
    ::= { dot3MpcpControlTable 1}

Dot3MpcpControlEntry ::=
    SEQUENCE {
        dot3MpcpOperStatus                   TruthValue,
        dot3MpcpAdminState                   TruthValue,
        dot3MpcpMode                         INTEGER,
        dot3MpcpSyncTime                     Unsigned32,
        dot3MpcpLinkID                       Unsigned32,
        dot3MpcpRemoteMACAddress             MacAddress,
        dot3MpcpRegistrationState            INTEGER,
        dot3MpcpTransmitElapsed              Unsigned32,
        dot3MpcpReceiveElapsed               Unsigned32,
        dot3MpcpRoundTripTime                Unsigned32,
        dot3MpcpMaximumPendingGrants         Unsigned32
    }

dot3MpcpOperStatus OBJECT-TYPE
    SYNTAX  TruthValue
```

```
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "This object reflects the operational state of the
             MultiPoint MAC Control sublayer as defined in
             IEEE Std 802.3, Clause 64 and Clause 77. When the value is
             true(1), the interface will act as if the MultiPoint Control
             Protocol is enabled. When the value is false(2), the interface
             will act as if the MultiPoint Control Protocol is
             disabled. The operational state can be changed using the
             dot3MpcpAdminState object.
             This object is applicable for an OLT, with the same
             value for all virtual interfaces, and for an ONU."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.2."
    ::= { dot3MpcpControlEntry 1 }

dot3MpcpAdminState OBJECT-TYPE
    SYNTAX  TruthValue
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
            "This object is used to define the admin state of the
             MultiPoint MAC Control sublayer, as defined in
             IEEE Std 802.3, Clause 64, and to reflect its state.
             When selecting the value as true(1), the MultiPoint
             Control Protocol of the interface is enabled.
             When selecting the value as false(2), the MultiPoint
             Control Protocol of the interface is disabled.
             This object reflects the administrative state of the
             MultiPoint Control Protocol of the interface.
             The write operation is not restricted in this document
             and can be done at any time. Changing
             dot3MpcpAdminState state can lead to disabling the
             MultiPoint Control Protocol on the respective interface,
             leading to the interruption of service for the users
             connected to the respective EPON interface.
             This object is applicable for an OLT, with the same
             value for all virtual interfaces, and for an ONU."
    REFERENCE   "IEEE Std 802.3, 30.3.5.2.1."
    DEFVAL { false }
    ::= { dot3MpcpControlEntry 2 }

dot3MpcpMode  OBJECT-TYPE
    SYNTAX  INTEGER {
            olt(1),
            onu(2)
    }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "This object is used to identify the operational
             state of the MultiPoint MAC Control sublayer as
             defined in IEEE Std 802.3, Clause 64 and Clause 77. Reading
             olt(1) for an OLT (server) mode and onu(2) for an ONU (client)
             mode. This object is used to identify the operational mode
             for the MPCP tables.
             This object is applicable for an OLT, with the same
             value for all virtual interfaces, and for an ONU."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.3."
```

```
    DEFVAL { olt }
    ::= { dot3MpcpControlEntry 3 }

dot3MpcpSyncTime OBJECT-TYPE
    SYNTAX  Unsigned32
    UNITS       "TQ (16 ns)"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "An object that reports the ‘sync lock time’ of the
             OLT receiver in increments of Time Quanta (TQ)-16ns
             as defined in IEEE Std 802.3, Clauses 60, 64, and 65. The
             value returned shall be (sync lock time ns)/16, rounded up
             to the nearest TQ. If this value exceeds (2^32-1), the
             value (2^32-1) shall be returned. This object is applicable
             for an OLT, with distinct values for all virtual interfaces,
             and for an ONU."
    REFERENCE   "IEEE Std 802.3, 64.3.3.2."
   ::= { dot3MpcpControlEntry 4 }

dot3MpcpLinkID OBJECT-TYPE
    SYNTAX  Unsigned32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "An object that identifies the Logical Link
             Identifier (LLID) associated with the MAC of the virtual
             link as specified in IEEE Std 802.3, 65.1.3.2.2 or 76.2.6.1.3.2,
             as appropriate.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             The ONU and the corresponding virtual MAC of the OLT,
             for the same virtual link, have the same value.
             Value is assigned when the ONU registers.
             Value is freed when the ONU deregisters."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.4."
    ::= { dot3MpcpControlEntry 5 }

dot3MpcpRemoteMACAddress OBJECT-TYPE
    SYNTAX  MacAddress
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "An object that identifies the source_address
             parameter of the last MPCPDUs passed to the MAC Control.
             This value is updated on reception of a valid frame with
             1) a destination Field equal to the reserved multicast
             address for MAC Control as specified in IEEE Std 802.3, Annex
             31A; 2) the lengthOrType field value equal to the reserved
             Type for MAC Control as specified in IEEE Std 802.3, Annex
             31A; 3) an MPCP subtype value equal to the subtype
             reserved for MPCP as specified in IEEE Std 802.3, Annex 31A.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             The value reflects the MAC address of the remote entity
             and therefore the OLT holds a value for each LLID, which
             is the MAC address of the ONU; the ONU has a single
             value that is the OLT MAC address."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.5."
```

```
    ::= { dot3MpcpControlEntry 6 }

dot3MpcpRegistrationState OBJECT-TYPE
    SYNTAX  INTEGER {
            unregistered(1),
            registering(2),
            registered(3)
    }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "An object that identifies the registration state
             of the MultiPoint MAC Control sublayer as defined in
             IEEE Std 802.3, Clause 64. When this object has the
             enumeration unregistered(1), the interface is
             unregistered and may be used for registering a link
             partner. When this object has the enumeration
             registering(2), the interface is in the process of
             registering a link-partner. When this object has the
             enumeration registered(3), the interface has an
             established link-partner.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.6."
    ::= { dot3MpcpControlEntry 7 }

dot3MpcpTransmitElapsed OBJECT-TYPE
    SYNTAX  Unsigned32
    UNITS       "TQ (16 ns)"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "An object that reports the interval from the last
             MPCP frame transmission in increments of Time Quanta
             (TQ)-16ns. The value returned shall be (interval from
             last MPCP frame transmission in ns)/16. If this value
             exceeds (2^32-1), the value (2^32-1) shall be returned.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.19."
    ::= { dot3MpcpControlEntry 8 }

dot3MpcpReceiveElapsed OBJECT-TYPE
    SYNTAX  Unsigned32
    UNITS       "TQ (16 ns)"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "An object that reports the interval from last MPCP frame
             reception in increments of Time Quanta (TQ)-16ns. The
             value returned shall be (interval from last MPCP frame
             reception in ns)/16. If this value exceeds (2^32-1), the
             value (2^32-1) shall be returned.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.20."
    ::= { dot3MpcpControlEntry 9 }

dot3MpcpRoundTripTime OBJECT-TYPE
```

```
    SYNTAX  Unsigned32 (0..'ffff'h)
    UNITS       "TQ (16 ns)"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "An object that reports the MPCP round trip time in
             increments of Time Quanta (TQ)-16ns. The value returned
             shall be (round trip time in ns)/16. If this value
             exceeds (2^16-1), the value (2^16-1) shall be returned.
             This object is applicable for an OLT. At the
             OLT, it has a distinct value for each virtual interface."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.21."
    ::= { dot3MpcpControlEntry 10 }

dot3MpcpMaximumPendingGrants OBJECT-TYPE
    SYNTAX  Unsigned32 (0..255)
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "An object that reports the maximum number of grants
             that an ONU can store for handling. The maximum number
             of grants that an ONU can store for handling has a
             range of 0 to 255.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the OLT, the value should be zero."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.24."
    ::= { dot3MpcpControlEntry 11 }



dot3MpcpStatTable OBJECT-TYPE
    SYNTAX     SEQUENCE OF Dot3MpcpStatEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
            "This table defines the list of statistics counters of
             an interface implementing the IEEE Std 802.3, Clause 64 MPCP.
             Each object has a row for every virtual link denoted by
             the corresponding ifIndex.
             The LLID field, as defined in IEEE Std 802.3, is a 2-byte
             register (15-bit field and a broadcast bit) limiting the
             number of virtual links to 32768. Typically the number
             of expected virtual links in a PON is like the number of
             ONUs, which is 32-64, plus an additional entry for
             broadcast LLID."
::= { dot3EponMpcpObjects 2 }

dot3MpcpStatEntry OBJECT-TYPE
    SYNTAX     Dot3MpcpStatEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
            "An entry in the table of statistics counters of the
             IEEE Std 802.3, Clause 64, MPCP interface.
             Rows exist for an OLT interface and an ONU interface.
             A row in the table is denoted by the ifIndex of the link
             and it is created when the ifIndex is created.
             The rows in the table for an ONU interface are created
```

```
             at system initialization.
             The row in the table corresponding to the OLT ifIndex
             and the row corresponding to the broadcast virtual link
             are created at system initialization.
             A row in the table corresponding to the ifIndex of a
             virtual link is created when a virtual link is
             established (ONU registers) and deleted when the virtual
             link is deleted (ONU deregisters)."
    INDEX  { ifIndex}
    ::= { dot3MpcpStatTable 1 }

Dot3MpcpStatEntry ::=
    SEQUENCE {
            dot3MpcpMACCtrlFramesTransmitted       Counter64,
            dot3MpcpMACCtrlFramesReceived          Counter64,
            dot3MpcpDiscoveryWindowsSent           Counter32,
            dot3MpcpDiscoveryTimeout               Counter32,
            dot3MpcpTxRegRequest                   Counter64,
            dot3MpcpRxRegRequest                   Counter64,
            dot3MpcpTxRegAck                       Counter64,
            dot3MpcpRxRegAck                       Counter64,
            dot3MpcpTxReport                       Counter64,
            dot3MpcpRxReport                       Counter64,
            dot3MpcpTxGate                         Counter64,
            dot3MpcpRxGate                         Counter64,
            dot3MpcpTxRegister                     Counter64,
            dot3MpcpRxRegister                     Counter64
    }

dot3MpcpMACCtrlFramesTransmitted OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of MPCP frames passed to the MAC sublayer for
             transmission. This counter is incremented when a
             MA_CONTROL.request service primitive is generated within
             the MAC control sublayer with an opcode indicating an
             MPCP frame.
             This object is applicable for an OLT and an ONU. At the
             OLT it has a distinct value for each virtual interface.
             Discontinuities of this counter can occur at
             re-initialization of the management system, and at other
             times as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.7."
    ::= { dot3MpcpStatEntry 1 }

dot3MpcpMACCtrlFramesReceived OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of MPCP frames passed by the MAC sublayer to the
             MAC Control sublayer. This counter is incremented when a
             ReceiveFrame function call returns a valid frame with
```

```
             1) a lengthOrType field value equal to the reserved
             Type for 802.3_MAC_Control as specified in IEEE Std 802.3
             31.4.1.3, and
             2) an opcode indicating an MPCP frame.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
   REFERENCE   "IEEE Std 802.3, 30.3.5.1.8."
    ::= { dot3MpcpStatEntry 2}

dot3MpcpDiscoveryWindowsSent OBJECT-TYPE
    SYNTAX  Counter32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of discovery windows generated. The counter is
             incremented by one for each generated discovery window.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the ONU, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
   REFERENCE   "IEEE Std 802.3, 30.3.5.1.22."
    ::= { dot3MpcpStatEntry 3}

dot3MpcpDiscoveryTimeout OBJECT-TYPE
    SYNTAX  Counter32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of the number of times a discovery timeout
             occurs. Increment the counter by one for each discovery
             processing state-machine reset resulting from timeout
             waiting for message arrival.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
   REFERENCE   "IEEE Std 802.3, 30.3.5.1.23."
    ::= { dot3MpcpStatEntry 4}

dot3MpcpTxRegRequest OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of the number of times a REGISTER_REQ MPCP
             frame transmission occurs. Increment the counter by one
```

```
              for each REGISTER_REQ MPCP frame transmitted as defined
              in IEEE Std 802.3, Clause 64.
              This object is applicable for an OLT and an ONU. At the
              OLT, it has a distinct value for each virtual interface.
              At the OLT, the value should be zero.
              Discontinuities of this counter can occur at
              re-initialization of the management system and at other
              times, as indicated by the value of the
              ifCounterDiscontinuityTime object of the Interfaces Group MIB
              module."
     REFERENCE   "IEEE Std 802.3, 30.3.5.1.12."
     ::= { dot3MpcpStatEntry 5}

dot3MpcpRxRegRequest OBJECT-TYPE
     SYNTAX  Counter64
     UNITS      "frames"
     MAX-ACCESS  read-only
     STATUS  current
     DESCRIPTION
             "A count of the number of times a REGISTER_REQ MPCP
              frame reception occurs.
              Increment the counter by one for each REGISTER_REQ MPCP
              frame received as defined in IEEE Std 802.3, Clause 64.
              This object is applicable for an OLT and an ONU. At the
              OLT, it has a distinct value for each virtual interface.
              At the ONU, the value should be zero.
              Discontinuities of this counter can occur at
              re-initialization of the management system and at other
              times, as indicated by the value of the
              ifCounterDiscontinuityTime object of the Interfaces Group MIB
              module."
   REFERENCE   "IEEE Std 802.3, 30.3.5.1.17."
     ::= { dot3MpcpStatEntry 6}

dot3MpcpTxRegAck OBJECT-TYPE
     SYNTAX  Counter64
     UNITS      "frames"
     MAX-ACCESS  read-only
     STATUS  current
     DESCRIPTION
             "A count of the number of times a REGISTER_ACK MPCP
              frame transmission occurs. Increment the counter by one
              for each REGISTER_ACK MPCP frame transmitted as defined
              in IEEE Std 802.3, Clause 64.
              This object is applicable for an OLT and an ONU. At the
              OLT, it has a distinct value for each virtual interface.
              At the OLT, the value should be zero.
              Discontinuities of this counter can occur at
              re-initialization of the management system and at other
              times, as indicated by the value of the
              ifCounterDiscontinuityTime object of the Interfaces Group MIB
              module."
  REFERENCE   "IEEE Std 802.3, 30.3.5.1.10."
     ::= { dot3MpcpStatEntry 7}

dot3MpcpRxRegAck OBJECT-TYPE
     SYNTAX  Counter64
     UNITS      "frames"
     MAX-ACCESS  read-only
```

```
    STATUS  current
    DESCRIPTION
            "A count of the number of times a REGISTER_ACK MPCP
             frame reception occurs.
             Increment the counter by one for each REGISTER_ACK MPCP
             frame received as defined in IEEE Std 802.3, Clause 64.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the ONU, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.15."
    ::= { dot3MpcpStatEntry 8}

dot3MpcpTxReport OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of the number of times a REPORT MPCP frame
             transmission occurs. Increment the counter by one for
             each REPORT MPCP frame transmitted as defined in
             IEEE Std 802.3, Clause 64.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the OLT, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.13."
    ::= { dot3MpcpStatEntry 9}

dot3MpcpRxReport OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of the number of times a REPORT MPCP frame
             reception occurs.
             Increment the counter by one for each REPORT MPCP frame
             received as defined in IEEE Std 802.3, Clause 64.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the ONU, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.18."
    ::= { dot3MpcpStatEntry 10}
```

```
dot3MpcpTxGate OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of the number of times a GATE MPCP frame
             transmission occurs.
             Increment the counter by one for each GATE MPCP frame
             transmitted as defined in IEEE Std 802.3, Clause 64.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the ONU, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.9."
    ::= { dot3MpcpStatEntry 11}

dot3MpcpRxGate OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of the number of times a GATE MPCP frame
             reception occurs.
             Increment the counter by one for each GATE MPCP frame
             received as defined in IEEE Std 802.3, Clause 64.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the OLT, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.14."
    ::= { dot3MpcpStatEntry 12}

dot3MpcpTxRegister OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of the number of times a REGISTER MPCP frame
             transmission occurs.
             Increment the counter by one for each REGISTER MPCP
             frame transmitted as defined in IEEE Std 802.3, Clause 64.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the ONU, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
```

```
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.11."
     ::= { dot3MpcpStatEntry 13}

dot3MpcpRxRegister OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of the number of times a REGISTER MPCP frame
             reception occurs.
             Increment the counter by one for each REGISTER MPCP
             frame received as defined in IEEE Std 802.3, Clause 64.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the OLT, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.16."
    ::= { dot3MpcpStatEntry 14}

-- Optical Multi Point Emulation (OMPEmulation)
-- managed object definitions

dot3OmpEmulationObjects OBJECT IDENTIFIER ::={dot3EponObjects 2}

dot3OmpEmulationTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF Dot3OmpEmulationEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
            "A table of dot3 OmpEmulation MIB objects. The table
             contain objects for the management of the OMPEmulation
             sublayer.
             Each object has a row for every virtual link denoted by
             the corresponding ifIndex.
             The LLID field, as defined in the IEEE Std 802.3, is a 2-byte
             register (15-bit field and a broadcast bit) limiting the
             number of virtual links to 32768. Typically the number
             of expected virtual links in a PON is like the number of
             ONUs, which is 32-64, plus an additional entry for
             broadcast LLID."
    ::= { dot3OmpEmulationObjects 1 }

dot3OmpEmulationEntry OBJECT-TYPE
    SYNTAX  Dot3OmpEmulationEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
            "An entry in the dot3 OmpEmulation table.
             Rows exist for an OLT interface and an ONU interface.
             A row in the table is denoted by the ifIndex of the link
             and it is created when the ifIndex is created.
             The rows in the table for an ONU interface are created
             at system initialization.
```

```
              The row in the table corresponding to the OLT ifIndex
              and the row corresponding to the broadcast virtual link
              are created at system initialization.
              A row in the table corresponding to the ifIndex of a
              virtual links is created when a virtual link is
              established (ONU registers) and deleted when the virtual
              link is deleted (ONU deregisters)."
     INDEX  { ifIndex }
     ::= { dot3OmpEmulationTable 1 }

     Dot3OmpEmulationEntry ::=
     SEQUENCE {
             dot3OmpEmulationType               INTEGER
     }

 dot3OmpEmulationType OBJECT-TYPE
     SYNTAX  INTEGER {
             unknown(1),
             olt(2),
             onu(3)
     }
     MAX-ACCESS  read-only
     STATUS  current
     DESCRIPTION
             "An object that indicates the mode of operation
              of the Reconciliation Sublayer for Point-to-Point
              Emulation (see IEEE Std 802.3, 65.1 or 76.2 as appropriate).
              unknown(1) value is assigned in initialization; true state
              or type is not yet known. olt(2) value is assigned when the
              sublayer is operating in OLT mode. onu(3) value is assigned when
              the sublayer is operating in ONU mode.
              This object is applicable for an OLT, with the same
              value for all virtual interfaces, and for an ONU."
     REFERENCE   "IEEE Std 802.3, 30.3.7.1.2."
     ::= { dot3OmpEmulationEntry 1}

 dot3OmpEmulationStatTable OBJECT-TYPE
     SYNTAX     SEQUENCE OF Dot3OmpEmulationStatEntry
     MAX-ACCESS not-accessible
     STATUS     current
     DESCRIPTION
             "This table defines the list of statistics counters of
              IEEE Std 802.3, Clause 65, OMPEmulation sublayer.
              Each object has a row for every virtual link denoted by
              the corresponding ifIndex.
              The LLID field, as defined in the IEEE Std 802.3, is a 2-byte
              register (15-bit field and a broadcast bit) limiting the
              number of virtual links to 32768. Typically the number
              of expected virtual links in a PON is like the number of
              ONUs, which is 32-64, plus an additional entry for
              broadcast LLID."
     ::= { dot3OmpEmulationObjects 2}

 dot3OmpEmulationStatEntry OBJECT-TYPE
     SYNTAX     Dot3OmpEmulationStatEntry
     MAX-ACCESS not-accessible
     STATUS     current
     DESCRIPTION
             "An entry in the table of statistics counters of
```

```
             IEEE Std 802.3, Clause 65, OMPEmulation sublayer.
             Rows exist for an OLT interface and an ONU interface.
             A row in the table is denoted by the ifIndex of the link
             and it is created when the ifIndex is created.
             The rows in the table for an ONU interface are created
             at system initialization.
             The row in the table corresponding to the OLT ifIndex
             and the row corresponding to the broadcast virtual link
             are created at system initialization.
             A row in the table corresponding to the ifIndex of a
             virtual links is created when a virtual link is
             established (ONU registers) and deleted when the virtual
             link is deleted (ONU deregisters)."
    INDEX  { ifIndex}
    ::= { dot3OmpEmulationStatTable 1 }

Dot3OmpEmulationStatEntry::=
    SEQUENCE {
            dot3OmpEmulationSLDErrors                 Counter64,
            dot3OmpEmulationCRC8Errors                Counter64,
            dot3OmpEmulationBadLLID                   Counter64,
            dot3OmpEmulationGoodLLID                  Counter64,
            dot3OmpEmulationOnuPonCastLLID            Counter64,
            dot3OmpEmulationOltPonCastLLID            Counter64,
            dot3OmpEmulationBroadcastBitNotOnuLlid    Counter64,
            dot3OmpEmulationOnuLLIDNotBroadcast       Counter64,
            dot3OmpEmulationBroadcastBitPlusOnuLlid    Counter64,
            dot3OmpEmulationNotBroadcastBitNotOnuLlid  Counter64
    }

dot3OmpEmulationSLDErrors OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of frames received that do not contain a valid
             SLD field as defined in IEEE Std 802.3, 65.1.3.3.1 or
             76.2.6.1.3.1, as appropriate.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.s
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.7.1.3."
    ::= { dot3OmpEmulationStatEntry 1}

dot3OmpEmulationCRC8Errors OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of frames received that contain a valid SLD
             field, as defined in IEEE Std 802.3, 65.1.3.3.1 or 76.2.6.1.3.1
             as appropriate, but do not pass the CRC-8 check as defined in
             IEEE Std 802.3, 65.1.3.3.3 or 76.2.6.1.3.3 as appropriate.
```

```
              This object is applicable for an OLT and an ONU. At the
              OLT, it has a distinct value for each virtual interface.
              Discontinuities of this counter can occur at
              re-initialization of the management system and at other
              times, as indicated by the value of the
              ifCounterDiscontinuityTime object of the Interfaces Group MIB
              module."
    REFERENCE   "IEEE Std 802.3, 30.3.7.1.4."
    ::= { dot3OmpEmulationStatEntry 2}

dot3OmpEmulationBadLLID OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of frames received that contain a valid SLD field in an
             OLT, and pass the CRC-8 check, but are discarded due to the
             LLID check. The SLD is defined in IEEE Std 802.3, 65.1.3.3.1
             or 76.2.6.1.3.1, as appropriate. The CRC-8 check is defined in
             IEEE Std 802.3, 65.1.3.3.3 or 76.2.6.1.3.3, as appropriate. The
             LLID check is defined in IEEE Std 802.3, 65.1.3.3.2 or
             76.2.6.1.3.2, as appropriate.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.7.1.8."
    ::= { dot3OmpEmulationStatEntry 3}

dot3OmpEmulationGoodLLID OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of frames received that contain a valid SLD
             field, as defined in IEEE Std 802.3, 65.1.3.3.1 or 76.2.6.1.3.1,
             as appropriate, and pass the CRC-8 check as defined in
             IEEE Std 802.3, 65.1.3.3.3 or 76.2.6.1.3.3, as appropriate.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.3.7.1.5."
    ::= { dot3OmpEmulationStatEntry 4}

dot3OmpEmulationOnuPonCastLLID OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
```

```
                "A count of frames received that: 1) contain a valid SLD field
                 in an  ONU, 2) meet the rules for frame acceptance, and
                 3) pass the CRC-8 check. The SLD is defined in
                 IEEE Std 802.3, 65.1.3.3.1 or 76.2.6.1.3.1, as appropriate. The
                rules for LLID acceptance are defined in IEEE Std 802.3, 65.1.3.3.2
                 or 76.2.6.1.3.2, as appropriate. The CRC-8 check is defined
                 in IEEE Std 802.3, 65.1.3.3.3 or 76.2.6.1.3.3, as appropriate.
                 This object is applicable for an OLT and an ONU. At the
                 OLT, it has a distinct value for each virtual interface.
                 At the OLT, the value should be zero.
                 Discontinuities of this counter can occur at
                 re-initialization of the management system and at other
                 times, as indicated by the value of the
                 ifCounterDiscontinuityTime object of the Interfaces Group MIB
                 module."
        REFERENCE   "IEEE Std 802.3, 30.3.7.1.6."
        ::= { dot3OmpEmulationStatEntry 5}

    dot3OmpEmulationOltPonCastLLID OBJECT-TYPE
        SYNTAX  Counter64
        UNITS      "frames"
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "A count of frames received that contain a valid SLD field, as
                 defined in IEEE Std 802.3, 65.1.3.3.1 or 76.2.6.1.3.1, as
                 appropriate, pass the CRC-8 check, as defined in
                 IEEE Std 802.3, 65.1.3.3.3 or 76.2.6.1.3.3, as appropriate,
                 and meet the rules of acceptance for an OLT defined in
                 IEEE Std 802.3, 65.1.3.3.2 or 76.2.6.1.3.2, as appropriate.
                 This object is applicable for an OLT and an ONU. At the
                 OLT, it has a distinct value for each virtual interface.
                 At the ONU, the value should be zero.
                 Discontinuities of this counter can occur at
                 re-initialization of the management system and at other
                 times, as indicated by the value of the
                 ifCounterDiscontinuityTime object of the Interfaces Group MIB
                 module."
      REFERENCE   "IEEE Std 802.3, 30.3.7.1.7."
        ::= { dot3OmpEmulationStatEntry 6}

    dot3OmpEmulationBroadcastBitNotOnuLlid OBJECT-TYPE
        SYNTAX  Counter64
        UNITS      "frames"
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "A count of frames received that contain a valid SLD
                 field, as defined in IEEE Std 802.3,
                 65.1.3.3.1, pass the CRC-8 check, as defined in
                 IEEE Std 802.3, 65.1.3.3.3, and contain the broadcast
                 bit in the LLID and not the ONU's LLID (frame accepted)
                 as defined in IEEE Std 802.3, Clause 65.
                 This object is applicable for an OLT and an ONU. At the
                 OLT, it has a distinct value for each virtual interface.
                 At the OLT, the value should be zero.
                 Discontinuities of this counter can occur at
                 re-initialization of the management system and at other
                 times, as indicated by the value of the
```

```
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
   ::= { dot3OmpEmulationStatEntry 7}

dot3OmpEmulationOnuLLIDNotBroadcast OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of frames received that contain a valid SLD
             field, as defined in IEEE Std 802.3,
             65.1.3.3.1, pass the CRC-8 check, as defined in
             IEEE Std 802.3, 65.1.3.3.3, and contain the ONU’s LLID
             as defined in IEEE Std 802.3, Clause 65.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the OLT, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
   ::= { dot3OmpEmulationStatEntry 8}

dot3OmpEmulationBroadcastBitPlusOnuLlid OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of frames received that contain a valid SLD
             field, as defined in IEEE Std 802.3,
             65.1.3.3.1, pass the CRC-8 check, as defined in
             IEEE Std 802.3, 65.1.3.3.3, and contain the broadcast
             bit in the LLID and match the ONU’s LLID (frame
             reflected) as defined in IEEE Std 802.3, Clause 65.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             At the OLT, the value should be zero.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    ::= { dot3OmpEmulationStatEntry 9}

dot3OmpEmulationNotBroadcastBitNotOnuLlid OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "frames"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A count of frames received that contain a valid SLD
             field, as defined in IEEE Std 802.3,
             65.1.3.3.1, pass the CRC-8 check, as defined in
             IEEE Std 802.3, 65.1.3.3.3, and do not contain
             the ONU’s LLID as defined in IEEE Std 802.3, Clause 65.
             This object is applicable for an OLT and an ONU. At the
```

```
              OLT, it has a distinct value for each virtual interface.
              At the OLT, the value should be zero.
              Discontinuities of this counter can occur at
              re-initialization of the management system and at other
              times, as indicated by the value of the
              ifCounterDiscontinuityTime object of the Interfaces Group MIB
              module."
    ::= { dot3OmpEmulationStatEntry 10}

--  FEC managed object definitions (30.5.1)

dot3EponFecObjects OBJECT IDENTIFIER ::={dot3EponObjects 3}

dot3EponFecTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF Dot3EponFecEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
            "A table of dot3 EPON FEC management objects.
             The entries in the table are control and status objects
             and statistic counters for the FEC layer.
             Each object has a row for every virtual link denoted by
             the corresponding ifIndex.
             The LLID field, as defined in the IEEE Std 802.3, is a 2-byte
             register (15-bit field and a broadcast bit) limiting the
             number of virtual links to 32768. Typically the number
             of expected virtual links in a PON is like the number of
             ONUs, which is 32-64, plus an additional entry for
             broadcast LLID."
    ::= { dot3EponFecObjects 1 }

dot3EponFecEntry OBJECT-TYPE
    SYNTAX  Dot3EponFecEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
            "An entry in the dot3 EPON FEC table.
             Rows exist for an OLT interface and an ONU interface.
             A row in the table is denoted by the ifIndex of the link
             and it is created when the ifIndex is created.
             The rows in the table for an ONU interface are created
             at system initialization.
             The row in the table corresponding to the OLT ifIndex
             and the row corresponding to the broadcast virtual link
             are created at system initialization.
             A row in the table corresponding to the ifIndex of a
             virtual links is created when a virtual link is
             established (ONU registers) and deleted when the virtual
             link is deleted (ONU deregisters)."
    INDEX  { ifIndex}
    ::= { dot3EponFecTable 1 }

Dot3EponFecEntry ::=
    SEQUENCE {
            dot3EponFecPCSCodingViolation           Counter64,
            dot3EponFecAbility                      INTEGER,
            dot3EponFecMode                         INTEGER,
            dot3EponFecCorrectedBlocks              Counter64,
            dot3EponFecUncorrectableBlocks          Counter64,
```

```
            dot3EponFecBufferHeadCodingViolation    Counter64
    }

dot3EponFecPCSCodingViolation OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "octets"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "For a 100 Mb/s operation, it is a count of the number of
             times an invalid code-group is received, other than the
             /H/ code-group. For a 1000 Mb/s operation, it is a count
             of the number of times an invalid codegroup is received,
             other than the /V/ code-group. /H/ denotes a special
             4b5b codeword of the IEEE Std 802.3 Clause 24 100 Mb/s PCS layer,
             and /V/ denotes a special 8b10b codeword of the IEEE Std 802.3
             Clause 36 1000 Mb/s PCS layer.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             Discontinuities of this counter can occur at
             re-initialization of the management system and at other
             times, as indicated by the value of the
             ifCounterDiscontinuityTime object of the Interfaces Group MIB
             module."
    REFERENCE   "IEEE Std 802.3, 30.5.1.1.14."
    ::= { dot3EponFecEntry 1}

dot3EponFecAbility OBJECT-TYPE
    SYNTAX  INTEGER {
            unknown(1),
            supported(2),
            unsupported(3)
    }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "An object that indicates the support of operation of the
             optional FEC sublayer of the 1000BASE-PX PHY specified
             in IEEE Std 802.3, 65.2.
             unknown(1) value is assigned in the initialization, for non
             FEC support state or type not yet known. unsupported(3)
             value is assigned when the sublayer is not supported.
             supported(2) value is assigned when the sublayer is
             supported.
             This object is applicable for an OLT, with the same
             value for all virtual interfaces, and for an ONU.
             The FEC counters will have a zero value when the
             interface is not supporting FEC.
             The counters:
              dot3EponFecPCSCodingViolation - not affected by FEC
              ability.
              dot3EponFecCorrectedBlocks    - has a zero value when
               dot3EponFecAbility is unknown(1) and unsupported(3).
              dot3EponFecUncorrectableBlocks  - has a zero value when
               dot3EponFecAbility is unknown(1) and unsupported(3).
              dot3EponFecBufferHeadCodingViolation - has a zero value
               when dot3EponFecAbility is unknown(1) and
               unsupported(3)."
    REFERENCE   "IEEE Std 802.3, 30.5.1.1.15."
```

```
    ::= { dot3EponFecEntry 2}

dot3EponFecMode OBJECT-TYPE
    SYNTAX  INTEGER {
            unknown(1),
            disabled(2),
            enabled(3)
    }
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
            "An object that defines the mode of operation of the
             optional FEC sublayer of the 1000BASE-PX PHY, specified
             in IEEE Std 802.3, 65.2, and reflects its state.
             A GET operation returns the current mode of operation
             of the PHY. A SET operation changes the mode of
             operation of the PHY to the indicated value.
             unknown(1) value is assigned in the initialization for non
            FEC support state or type not yet known.
             disabled(2) value is assigned when the FEC sublayer is
            operating in disabled mode.
             enabled(3) value is assigned when the FEC sublayer is
            operating in FEC mode.
             The write operation is not restricted in this document
             and can be done at any time. Changing dot3EponFecMode
             state can lead to disabling the Forward Error Correction
             on the respective interface, which can lead to a
             degradation of the optical link, and therefore may lead
             to an interruption of service for the users connected to
             the respective EPON interface.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             The counting of
             the FEC counters will stop when the FEC of the interface
             is disabled.
             The counters:
            dot3EponFecPCSCodingViolation - not affected by FEC
            mode.
            dot3EponFecCorrectedBlocks - stops counting when
            Rx_FEC is not enabled. (unknown(1) and disabled(2)).
            dot3EponFecUncorrectableBlocks - stops counting when
            Rx_FEC is not enabled (unknown(1) and disabled(2)).
            dot3EponFecBufferHeadCodingViolation - stops counting
            when Rx_FEC is not enabled (unknown(1) and
            disabled(2)).
            The object:
            dot3EponFecAbility - indicates the FEC ability and
            is not affected by the dot3EponFecMode object."
    REFERENCE   "IEEE Std 802.3, 30.5.1.1.16."
    DEFVAL { unknown }
    ::= { dot3EponFecEntry 3}

dot3EponFecCorrectedBlocks OBJECT-TYPE
    SYNTAX  Counter64
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "For 1000BASE-PX, 10GBASE-PR or 10/1GBASE-PRX PHYs, it is a
             count of corrected FEC blocks. This counter will not
```

```
                increment for other PHY Types. Increment the counter by
                one for each received block that is corrected by the FEC
                function in the PHY.
                This object is applicable for an OLT and an ONU. At the
                OLT, it has a distinct value for each virtual interface.
                Discontinuities of this counter can occur at
                re-initialization of the management system and at other
                times, as indicated by the value of the
                ifCounterDiscontinuityTime object of the Interfaces Group MIB
                module."
    REFERENCE   "IEEE Std 802.3, 30.5.1.1.17."
    ::= { dot3EponFecEntry 4}

dot3EponFecUncorrectableBlocks OBJECT-TYPE
    SYNTAX  Counter64
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
               "For 1000BASE-PX, 10GBASE-PR or 10/1GBASE-PRX PHYs, it is a
                count of uncorrectable FEC blocks. This counter will not
                increment for other PHY Types. Increment the counter by
                one for each FEC block that is determined to be
                uncorrectable by the FEC function in the PHY.
                This object is applicable for an OLT and an ONU. At the
                OLT, it has a distinct value for each virtual interface.
                Discontinuities of this counter can occur at
                re-initialization of the management system and at other
                times, as indicated by the value of the
                ifCounterDiscontinuityTime object of the Interfaces Group MIB
                module."
    REFERENCE   "IEEE Std 802.3, 30.5.1.1.18."
    ::= { dot3EponFecEntry 5}

dot3EponFecBufferHeadCodingViolation OBJECT-TYPE
    SYNTAX  Counter64
    UNITS      "octets"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
               "For a 1000 Mb/s operation, it is a count of the number of
                invalid code-group received directly from the link. The
                value has a meaning only in 1000 Mb/s mode and it is
                zero otherwise.
                This object is applicable for an OLT and an ONU. At the
                OLT, it has a distinct value for each virtual interface.
                Discontinuities of this counter can occur at
                re-initialization of the management system and at other
                times, as indicated by the value of the
                ifCounterDiscontinuityTime object of the Interfaces Group MIB
                module."
    ::= { dot3EponFecEntry 6}

-- ExtendedPackage managed object definitions

dot3ExtPkgObjects OBJECT IDENTIFIER ::={dot3EponObjects 4}

dot3ExtPkgControlObjects OBJECT IDENTIFIER ::= { dot3ExtPkgObjects 1}

dot3ExtPkgControlTable OBJECT-TYPE
```

```
    SYNTAX  SEQUENCE OF Dot3ExtPkgControlEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
            "A table of Extended package Control management
             objects. Entries in the table are control and status
             indication objects of an EPON interface, which are
             gathered in an extended package as an addition to the
             objects based on the IEEE Std 802.3, Clause 30, attributes.
             Each object has a row for every virtual link denoted by
             the corresponding ifIndex.
             The LLID field, as defined in the IEEE Std 802.3, is a 2-byte
             register (15-bit field and a broadcast bit) limiting the
             number of virtual links to 32768. Typically the number
             of expected virtual links in a PON is like the number of
             ONUs, which is 32-64, plus an additional entry for
             broadcast LLID."
    ::= { dot3ExtPkgControlObjects 1 }

dot3ExtPkgControlEntry OBJECT-TYPE
    SYNTAX  Dot3ExtPkgControlEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
            "An entry in the Extended package Control table.
             Rows exist for an OLT interface and an ONU interface.
             A row in the table is denoted by the ifIndex of the link
             and it is created when the ifIndex is created.
             The rows in the table for an ONU interface are created
             at system initialization.
             The row in the table corresponding to the OLT ifIndex
             and the row corresponding to the broadcast virtual link
             are created at system initialization.
             A row in the table corresponding to the ifIndex of a
             virtual links is created when a virtual link is
             established (ONU registers) and deleted when the virtual
             link is deleted (ONU deregisters)."
    INDEX  { ifIndex}
    ::= { dot3ExtPkgControlTable 1 }

Dot3ExtPkgControlEntry ::=
    SEQUENCE {
     dot3ExtPkgObjectReset                      INTEGER,
     dot3ExtPkgObjectPowerDown                  TruthValue,
     dot3ExtPkgObjectNumberOfLLIDs              Unsigned32,
     dot3ExtPkgObjectFecEnabled                 INTEGER,
     dot3ExtPkgObjectReportMaximumNumQueues     Unsigned32,
     dot3ExtPkgObjectRegisterAction             INTEGER
    }

dot3ExtPkgObjectReset OBJECT-TYPE
    SYNTAX  INTEGER {
            running(1),
            reset(2)
    }
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
            "This object is used to reset the EPON interface. The
```

```
              interface may be unavailable while the reset occurs and
              data may be lost.
              Setting this object to running(1) will cause the
              interface to enter into running mode. Setting this
              object to reset(2) will cause the interface to go into
              reset mode. When getting running(1), the interface is in
              running mode. When getting reset(2), the interface is in
              reset mode.
              The write operation is not restricted in this document
              and can be done at any time. Changing
              dot3ExtPkgObjectReset state can lead to a reset of the
              respective interface, leading to an interruption of
              service for the users connected to the respective EPON
              interface.
              This object is applicable for an OLT and an ONU. At the
              OLT, it has a distinct value for each virtual interface.
              A reset for a specific virtual interface resets only
              this virtual interface and not the physical interface.
              Thus, a virtual link that is malfunctioning can be
              reset without affecting the operation of other virtual
              interfaces.
              The reset can cause Discontinuities in the values of the
              counters of the interface, similar to re-initialization
              of the management system. Discontinuity should be
              indicated by the ifCounterDiscontinuityTime object of
              the Interfaces Group MIB module."
    DEFVAL { running }
    ::= { dot3ExtPkgControlEntry 1 }

dot3ExtPkgObjectPowerDown OBJECT-TYPE
    SYNTAX  TruthValue
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
            "This object is used to power down the EPON interface.
             The interface may be unavailable while the power down
             occurs and data may be lost.
             Setting this object to true(1) will cause the interface
             to enter into power down mode. Setting this object to
             false(2) will cause the interface to go out of power
             down mode. When getting true(1), the interface is in
             power down mode. When getting false(2), the interface is
             not in power down mode.
             The write operation is not restricted in this document
             and can be done at any time. Changing
             dot3ExtPkgObjectPowerDown state can lead to a power down
             of the respective interface, leading to an interruption
             of service of the users connected to the respective EPON
             interface.
             This object is applicable for an OLT and an ONU. At the
             OLT, it has a distinct value for each virtual interface.
             A power down/up of a specific virtual interface affects
             only the virtual interface and not the physical
             interface. Hence a virtual link, which needs a certain
             handling, can be powered down and then powered up without
             disrupting the operation of other virtual interfaces.
             The object is relevant when the admin state of the
             interface is active as set by the dot3MpcpAdminState."
    DEFVAL { false }
```

```
    ::= { dot3ExtPkgControlEntry 2 }

dot3ExtPkgObjectNumberOfLLIDs OBJECT-TYPE
    SYNTAX  Unsigned32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "A read only object that indicates the number of
             registered LLIDs. The initialization value is 0.
             This object is applicable for an OLT with the same
             value for all virtual interfaces and for an ONU.
             The LLID field, as defined in the IEEE Std 802.3, is a 2-byte
             register (15-bit field and a broadcast bit) limiting the
             number of virtual links to 32768. Typically the number
             of expected virtual links in a PON is like the number of
             ONUs, which is 32-64, plus an additional entry for
             broadcast LLID. At the ONU the
             number of LLIDs for an interface is one."
    ::= { dot3ExtPkgControlEntry 3 }

dot3ExtPkgObjectFecEnabled OBJECT-TYPE
    SYNTAX  INTEGER {
            noFecEnabled(1),
            fecTxEnabled(2),
            fecRxEnabled(3),
            fecTxRxEnabled(4)
    }
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
           "An object defining the FEC mode of operation of the
            interface, and indicating its state. The modes defined in
            this object are extensions to the FEC modes defined in
            the dot3EponFecMode object.
            When noFECEnabled(1), the interface does not enable FEC
            mode.
            When fecTxEnabled(2), the interface enables the FEC
            transmit mode.
            When fecRxEnabled(3), the interface enables the FEC
            receive mode.
            When fecTxRxEnabled(4), the interface enables the FEC
            transmit and receive mode.
            This object is applicable for an OLT and an ONU. At the
            OLT, it has a distinct value for each virtual interface.
            The FEC counters are referring to the receive path. The
            FEC counters will stop when the FEC receive mode of the
            interface is disabled, as defined by fecRxEnabled(3)
            and fecTxRxEnabled(4) values.
            The counters:
             dot3EponFecPCSCodingViolation - not affected by FEC
             mode.
             dot3EponFecCorrectedBlocks - stops counting when
             Rx_FEC is not enabled (noFecEnabled(1) and
             fecTxEnabled(2)).
             dot3EponFecUncorrectableBlocks - stops counting when
             Rx_FEC is not enabled (noFecEnabled(1) and
             fecTxEnabled(2)).
             dot3EponFecBufferHeadCodingViolation - stops counting
             when Rx_FEC is not enabled (noFecEnabled(1) and
```

```
              fecTxEnabled(2)).
             The objects:
              dot3EponFecAbility - indicates the FEC ability and is
              not affected by the FEC mode.
              dot3EponFecMode - indicates the FEC mode for combined RX
              and TX.
             The write operation is not restricted in this document
             and can be done at any time. Changing
             dot3ExtPkgObjectFecEnabled state can lead to disabling
             the Forward Error Correction on the respective interface,
             which can lead to a degradation of the optical link, and
             therefore may lead to an interruption of service for the
             users connected to the respective EPON interface."
     DEFVAL { noFecEnabled }
     ::= { dot3ExtPkgControlEntry 4 }

dot3ExtPkgObjectReportMaximumNumQueues OBJECT-TYPE
     SYNTAX  Unsigned32 (0..7)
     MAX-ACCESS  read-only
     STATUS  current
     DESCRIPTION
             "An object, that defines the maximal number of queues in
              the REPORT message as defined in IEEE Std 802.3, Clause 64. For
              further information please see the description of the
              queue table.
              This object is applicable for an OLT and an ONU. At the
              OLT, it has a distinct value for each virtual interface."
     DEFVAL { 0 }
     ::= { dot3ExtPkgControlEntry 5 }

dot3ExtPkgObjectRegisterAction OBJECT-TYPE
     SYNTAX  INTEGER {
             none(1),
             register(2),
             deregister(3),
             reregister(4)
     }
     MAX-ACCESS  read-write
     STATUS  current
     DESCRIPTION
            "An object configuring the registration state of an
            interface, and indicating its registration state.
             Write operation changes the registration state to its new
             value.
             Read operation returns the value of the state.
             The registration state is reflected in this object and in
             the dot3MpcpRegistrationState object.
             none(1) indicates an unknown state,
             register(2) indicates a registered LLID,
             deregister(3) indicates a deregistered LLID,
             reregister(4) indicates an LLID that is reregistering.
             The following list describes the operation of the
             interface, as specified in the IEEE Std 802.3, when a write
             operation is setting a value.
              none(1) - not doing any action.
              register(2) - registering an LLID that has been requested
              for registration (The LLID is in registering mode.
                dot3MpcpRegistrationState - registering(2) ).
                deregister(3) - deregisters an LLID that is registered
```

```
                  (dot3MpcpRegistrationState - registered(3) ).
                reregister(4) - reregister an LLID that is registered
                  (dot3MpcpRegistrationState - registered(3) ).
                The behavior of an ONU and OLT interfaces, at each one
                of the detailed operation at each state, is described in
                the registration state machine of figure 64-22,
                IEEE Std 802.3.
               This object is applicable for an OLT and an ONU. At the
               OLT, it has a distinct value for each virtual interface.
               The write operation is not restricted in this document
               and can be done at any time. Changing
               dot3ExtPkgObjectRegisterAction state can lead to a change
               in the registration state of the respective interface
               leading to a deregistration and an interruption of
               service of the users connected to the respective EPON
               interface."
       DEFVAL { none }
       ::= { dot3ExtPkgControlEntry 6 }

   dot3ExtPkgQueueTable OBJECT-TYPE
       SYNTAX  SEQUENCE OF Dot3ExtPkgQueueEntry
       MAX-ACCESS  not-accessible
       STATUS  current
       DESCRIPTION
               "A table of the extended package objects for queue
                management. The IEEE Std 802.3 MPCP defines a report message
                of the occupancy of the transmit queues for the feedback
                BW request from the ONUs. These queues serve the uplink
                transmission of the ONU and data is gathered there until
                the ONU is granted for transmission.
                The management table of the queues is added here mainly
                to control the reporting and to gather some statistics
                of their operation. This table is not duplicating
                existing management objects of bridging queues,
                specified in IEEE Std 802.1D, since the existence of a
                dedicated transmit queuing mechanism is implied in the
                IEEE Std 802.3, and the ONU may be a device that is not a
                bridge with embedded bridging queues.
                The format of the REPORT message, as specified
                in IEEE Std 802.3, is presented below:
                +-----------------------------------+
                |          Destination Address      |
                +-----------------------------------+
                |          Source Address           |
                +-----------------------------------+
                |          Length/Type              |
                +-----------------------------------+
                |          OpCode                   |
                +-----------------------------------+
                |          TimeStamp                |
                +-----------------------------------+
                |          Number of queue Sets     |
                +-----------------------------------+   /|\
                |          Report bitmap            |    |
                +-----------------------------------+    |
                |          Queue 0 report           |    |
                +-----------------------------------+    | repeated for
                |          Queue 1 report           |    | every
                +-----------------------------------+    | queue_set
```

```
                 |          Queue 2 report          |    |
                 +----------------------------------+    |
                 |          Queue 3 report          |    |
                 +----------------------------------+    |
                 |          Queue 4 report          |    |
                 +----------------------------------+    |
                 |          Queue 5 report          |    |
                 +----------------------------------+    |
                 |          Queue 6 report          |    |
                 +----------------------------------+    |
                 |          Queue 7 report          |    |
                 +----------------------------------+   \|/
                 |          Pad/reserved            |
                 +----------------------------------+
                 |          FCS                     |
                 +----------------------------------+

                 The ‘Queue report’ field reports the occupancy of each
                 uplink transmission queue.
                 The number of queue sets defines the number of the
                 reported sets, as would be explained in the description
                 of the dot3ExtPkgQueueSetsTable table. For each set the
                 report bitmap defines which queue is present in the
                 report, meaning that although the MPCP REPORT message
                 can report up to 8 queues in a REPORT message, the
                 actual number is flexible. The Queue table has a
                 variable size that is limited by the
                 dot3ExtPkgObjectReportMaximumNumQueues object, as an
                 ONU can have fewer queues to report.
                 The entries in the table are control and status
                 indication objects for managing the queues of an EPON
                 interface that are gathered in an extended package as
                 an addition to the objects that are based on the
                 IEEE Std 802.3 attributes.
                 Each object has a row for every virtual link and for
                 every queue in the report.
                 The LLID field, as defined in the IEEE Std 802.3, is a 2-byte
                 register (15-bit field and a broadcast bit) limiting the
                 number of virtual links to 32768. Typically the number
                 of expected virtual links in a PON is like the number of
                 ONUs, which is 32-64, plus an additional entry for
                 broadcast LLID.
                 The number of queues is between 0 and 7 and limited by
                 dot3ExtPkgObjectReportMaximumNumQueues."
        ::= { dot3ExtPkgControlObjects 2 }

    dot3ExtPkgQueueEntry OBJECT-TYPE
        SYNTAX  Dot3ExtPkgQueueEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "An entry in the Extended package Queue table. At the
                 OLT, the rows exist for each ifIndex and dot3QueueIndex.
                 At the ONU, rows exist for the single ifIndex for each
                 dot3QueueIndex.
                 Rows in the table are created when the ifIndex of the
                 link is created. A set of rows per queue are added for
                 each ifIndex, denoted by the dot3QueueIndex.
                 A set of rows per queue in the table, for an ONU
```

```
                 interface, are created at the system initialization.
                 A set of rows per queue in the table, corresponding to
                 the OLT ifIndex and a set of rows per queue
                 corresponding to the broadcast virtual link, are
                 created at the system initialization.
                 A set of rows per queue in the table, corresponding to
                 the ifIndex of a virtual link, are created when the
                 virtual link is established (ONU registers), and deleted
                 when the virtual link is deleted (ONU deregisters)."
        INDEX  { ifIndex, dot3QueueIndex }
        ::= { dot3ExtPkgQueueTable 1 }

    Dot3ExtPkgQueueEntry ::=
        SEQUENCE {
         dot3QueueIndex                              Unsigned32,
         dot3ExtPkgObjectReportNumThreshold           Unsigned32,
         dot3ExtPkgObjectReportMaximumNumThreshold    Unsigned32,
         dot3ExtPkgStatTxFramesQueue                  Counter64,
         dot3ExtPkgStatRxFramesQueue                  Counter64,
         dot3ExtPkgStatDroppedFramesQueue             Counter64
        }

    dot3QueueIndex OBJECT-TYPE
        SYNTAX  Unsigned32 (0..7)
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "An object that identifies an index for the queue table
                 reflecting the queue index of the queues that are
                 reported in the MPCP REPORT message as defined in
                 IEEE Std 802.3, Clause 64.
                 The number of queues is between 0 and 7, and limited by
                 dot3ExtPkgObjectReportMaximumNumQueues."
        ::= { dot3ExtPkgQueueEntry 1 }

    dot3ExtPkgObjectReportNumThreshold OBJECT-TYPE
        SYNTAX  Unsigned32 (0..7)
        MAX-ACCESS  read-write
        STATUS  current
        DESCRIPTION
                "An object that defines the number of thresholds for each
                 queue in the REPORT message as defined in IEEE Std 802.3,
                 Clause 64.
                 Each queue_set reporting will provide information on the
                 queue occupancy of frames below the matching Threshold.
                 Read operation reflects the number of thresholds.
                 Write operation sets the number of thresholds for each
                 queue.
                 The write operation is not restricted in this document
                 and can be done at any time. Value cannot exceed the
                 maximal value defined by the
                 dot3ExtPkgObjectReportMaximumNumThreshold object.
                 Changing dot3ExtPkgObjectReportNumThreshold can lead to
                 a change in the reporting of the ONU interface and
                 therefore to a change in the bandwidth allocation of the
                 respective interface. This change may lead a degradation
                 or an interruption of service of the users connected to
                 the respective EPON interface.
                 This object is applicable for an OLT and an ONU. At the
```

```
                OLT, it has a distinct value for each virtual interface
                and for each queue. At the ONU, it has a distinct value
                for each queue."
        DEFVAL { 0 }
        ::= { dot3ExtPkgQueueEntry 2 }

    dot3ExtPkgObjectReportMaximumNumThreshold OBJECT-TYPE
        SYNTAX  Unsigned32 (0..7)
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
               "An object, that defines the maximal number of thresholds
                for each queue in the REPORT message as defined in
                IEEE Std 802.3, Clause 64. Each queue_set reporting will
                provide information on the queue occupancy of frames
                below the matching Threshold.
                This object is applicable for an OLT and an ONU. At the
                OLT, it has a distinct value for each virtual interface
                and for each queue. At the ONU, it has a distinct value
                for each queue."
        DEFVAL { 0 }
        ::= { dot3ExtPkgQueueEntry 3 }

     dot3ExtPkgStatTxFramesQueue OBJECT-TYPE
        SYNTAX  Counter64
        UNITS      "frames"
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
               "A count of the number of times a frame transmission
                occurs from the corresponding 'Queue'.
                Increment the counter by one for each frame transmitted,
                which is an output of the 'Queue'.
                The 'Queue' marking matches the REPORT MPCP message
                Queue field as defined in IEEE Std 802.3, Clause 64.
                This object is applicable for an OLT and an ONU. At the
                OLT, it has a distinct value for each virtual interface
                and for each queue. At the ONU, it has a distinct value
                for each queue.
                At the OLT the value should be zero.
                Discontinuities of this counter can occur at
                re-initialization of the management system and at other
                times, as indicated by the value of the
                ifCounterDiscontinuityTime object of the Interfaces Group MIB
                module."
        ::= { dot3ExtPkgQueueEntry 4}

    dot3ExtPkgStatRxFramesQueue OBJECT-TYPE
        SYNTAX  Counter64
        UNITS      "frames"
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
               "A count of the number of times a frame reception
                occurs from the corresponding 'Queue'.
                Increment the counter by one for each frame received,
                which is an input to the corresponding 'Queue'.
                The 'Queue' marking matches the REPORT MPCP message
                Queue field as defined in IEEE Std 802.3, Clause 64.
```

```
                This object is applicable for an OLT and an ONU. At the
                OLT, it has a distinct value for each virtual interface
                and for each queue. At the ONU, it has a distinct value
                for each queue.
                Discontinuities of this counter can occur at
                re-initialization of the management system and at other
                times, as indicated by the value of the
                ifCounterDiscontinuityTime object of the Interfaces Group MIB
                module."
         ::= { dot3ExtPkgQueueEntry 5}

    dot3ExtPkgStatDroppedFramesQueue OBJECT-TYPE
        SYNTAX  Counter64
        UNITS      "frames"
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "A count of the number of times a frame drop
                occurs from the corresponding ‘Queue’.
                Increment the counter by one for each frame dropped
                from the corresponding ‘Queue’.
                The ‘Queue’ marking matches the REPORT MPCP message
                Queue field as defined in IEEE Std 802.3, Clause 64.
                This object is applicable for an OLT and an ONU. At the
                OLT, it has a distinct value for each virtual interface
                and for each queue. At the ONU, it has a distinct value
                for each queue.
                At the OLT, the value should be zero.
                Discontinuities of this counter can occur at
                re-initialization of the management system and at other
                times, as indicated by the value of the
                ifCounterDiscontinuityTime object of the Interfaces Group MIB
                module."
       ::= { dot3ExtPkgQueueEntry 6}

    dot3ExtPkgQueueSetsTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF Dot3ExtPkgQueueSetsEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
               "A table of Extended package objects used for the
                management of the queue_sets. Entries are control and
                status indication objects of an EPON interface, which
                are gathered in an extended package as an addition to
                the objects based on the IEEE Std 802.3 attributes. The
                objects in this table are specific for the queue_sets,
                which are reported in the MPCP REPORT message as defined
                in IEEE Std 802.3, Clause 64.
                The IEEE Std 802.3 MPCP defines a report message of the
                occupancy of the transmit queues for the feedback BW
                request from the ONUs. These queues serve the uplink
                transmission of the ONU and data is gathered there until
                the ONU is granted for transmission.
                The management table of the queues_sets is added here
                mainly to control the reporting and to gather some
                statistics of their operation. This table is not
                duplicating existing management objects of bridging
                queues, specified in IEEE Std 802.1D, since the existence of a
                dedicated transmit queuing mechanism is implied in the
```

```
IEEE Std 802.3, and the ONU may be a device that is not a
bridge with embedded bridging queues.
The format of the REPORT message, as specified
in IEEE Std 802.3, is presented below:
+----------------------------------+
|          Destination Address     |
+----------------------------------+
|          Source Address          |
+----------------------------------+
|          Length/Type             |
+----------------------------------+
|          OpCode                  |
+----------------------------------+
|          TimeStamp               |
+----------------------------------+
|          Number of queue Sets    |
+----------------------------------+   /|\
|          Report bitmap           |    |
+----------------------------------+    |
|          Queue 0 report          |    |
+----------------------------------+    | repeated for
|          Queue 1 report          |    | every
+----------------------------------+    | queue_set
|          Queue 2 report          |    |
+----------------------------------+    |
|          Queue 3 report          |    |
+----------------------------------+    |
|          Queue 4 report          |    |
+----------------------------------+    |
|          Queue 5 report          |    |
+----------------------------------+    |
|          Queue 6 report          |    |
+----------------------------------+    |
|          Queue 7 report          |    |
+----------------------------------+   \|/
|          Pad/reserved            |
+----------------------------------+
|          FCS                     |
+----------------------------------+

As can be seen from the message format, the ONU
interface reports of the status of up to 8 queues
and it can report in a single MPCP REPORT message
of a few sets of queues.
The number of queue_sets defines the number of the
reported sets, and it can reach a value of up to 8.
It means that an ONU can hold a variable number of
sets between 0 and 7.
The dot3ExtPkgQueueSetsTable table has a variable
queue_set size that is limited by the
dot3ExtPkgObjectReportMaximumNumThreshold object as an
ONU can have fewer queue_sets to report.
The ‘Queue report’ field reports the occupancy of each
uplink transmission queue. The queue_sets can be used to
report the occupancy of the queues in a few levels as to
allow granting, in an accurate manner, of only part of
the data available in the queues. A Threshold is
defined for each queue_set to define the level of the
queue that is counted for the report of the occupancy.
```

```
                The threshold is reflected in the queue_set table by the
                dot3ExtPkgObjectReportThreshold object.
                For each queue set, the report bitmap defines which
                queues are present in the report, meaning that
                although the MPCP REPORT message can report of up to 8
                queues in a REPORT message, the actual number is
                flexible.
                The dot3ExtPkgQueueSetsTable table has a variable queue
                size that is limited by the
                dot3ExtPkgObjectReportMaximumNumQueues object as an ONU
                can have fewer queues to report.
                Each object has a row for every virtual link, for each
                queue in the report and for each queue_set in the queue.
                The LLID field, as defined in the IEEE Std 802.3, is a 2-byte
                register (15-bit field and a broadcast bit) limiting the
                number of virtual links to 32768. Typically the number
                of expected virtual links in a PON is like the number of
                ONUs, which is 32-64, plus an additional entry for
                broadcast LLID.
                The number of queues is between 0 and 7 and limited by
                dot3ExtPkgObjectReportMaximumNumQueues.
                The number of queues_sets is between 0 and 7 and limited
                by dot3ExtPkgObjectReportMaximumNumThreshold."
        ::= { dot3ExtPkgControlObjects 3 }

    dot3ExtPkgQueueSetsEntry OBJECT-TYPE
        SYNTAX  Dot3ExtPkgQueueSetsEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
               "An entry in the Extended package queue_set table. At
                the OLT, the rows exist for each ifIndex,
                dot3QueueSetQueueIndex and dot3QueueSetIndex. At the
                ONU, rows exist for the single ifIndex, for each
                dot3QueueSetQueueIndex and dot3QueueSetIndex.
                Rows in the table are created when the ifIndex of the
                link is created. A set of rows per queue and per
                queue_set are added for each ifIndex, denoted by
                dot3QueueSetIndex and dot3QueueSetQueueIndex.
                A set of rows per queue and per queue_set in the table,
                for an ONU interface are created at system
                initialization.
                A set of rows per queue and per queue_Set in the table,
                corresponding to the OLT ifIndex and a set of rows per
                queue and per queue_set, corresponding to the broadcast
                virtual link, are created at system initialization.
                A set of rows per queue and per queue_set in the table,
                corresponding to the ifIndex of a virtual link are
                created when the virtual link is established (ONU
                registers) and deleted when the virtual link is deleted
                (ONU deregisters)."
                INDEX { ifIndex,
               dot3QueueSetQueueIndex,dot3QueueSetIndex}
        ::= { dot3ExtPkgQueueSetsTable 1 }

    Dot3ExtPkgQueueSetsEntry ::=
        SEQUENCE {
         dot3QueueSetQueueIndex                    Unsigned32,
         dot3QueueSetIndex                         Unsigned32,
```

```
        dot3ExtPkgObjectReportThreshold             Unsigned32
       }

   dot3QueueSetQueueIndex OBJECT-TYPE
       SYNTAX  Unsigned32 (0..7)
       MAX-ACCESS  not-accessible
       STATUS  current
       DESCRIPTION
               "An object that identifies the queue index for the
                dot3ExtPkgQueueSetsTable table. The queues are reported
                in the MPCP REPORT message as defined in IEEE Std 802.3,
                Clause 64.
                The number of queues is between 0 and 7, and limited by
                dot3ExtPkgObjectReportMaximumNumQueues.
                Value corresponds to the dot3QueueIndex of the queue
                table."
       ::= { dot3ExtPkgQueueSetsEntry 1 }

   dot3QueueSetIndex OBJECT-TYPE
       SYNTAX  Unsigned32 (0..7)
       MAX-ACCESS  not-accessible
       STATUS  current
       DESCRIPTION
               "An object that identifies the queue_set index for the
                dot3ExtPkgQueueSetsTable table. The queues are reported
                in the MPCP REPORT message as defined in IEEE Std 802.3,
                Clause 64.
                The number of queues_sets is between 0 and 7, and
                limited by dot3ExtPkgObjectReportMaximumNumThreshold."
       ::= { dot3ExtPkgQueueSetsEntry 2 }

       dot3ExtPkgObjectReportThreshold OBJECT-TYPE
       SYNTAX  Unsigned32
       UNITS       "TQ (16 ns)"
       MAX-ACCESS  read-write
       STATUS  current
       DESCRIPTION
               "An object that defines the value of a threshold report
                for each queue_set in the REPORT message as defined in
                IEEE Std 802.3, Clause 64. The number of sets for each queue
                is dot3ExtPkgObjectReportNumThreshold.
                In the REPORT message, each queue_set reporting will
                provide information on the occupancy of the queues for
                frames below the matching Threshold.
                The value returned shall be in Time quanta (TQ), which
                is 16 ns or 2 octets increments.
                Read operation provides the threshold value. Write
                operation sets the value of the threshold.
                The write operation is not restricted in this document
                and can be done at any time. Changing
                dot3ExtPkgObjectReportThreshold can lead to a change in
                the reporting of the ONU interface and therefore to a
                change in the bandwidth allocation of the respective
                interface. This change may lead a degradation or an
                interruption of service for the users connected to the
                respective EPON interface.
                This object is applicable for an OLT and an ONU. At the
                OLT, it has a distinct value for each virtual interface,
                for each queue and for each queue_set. At the ONU, it has
```

```
                 a distinct value for each queue and for each queue_set."
        DEFVAL { 0 }
        ::= { dot3ExtPkgQueueSetsEntry 3 }

    --Optical Interface status tables

    dot3ExtPkgOptIfTable OBJECT-TYPE
        SYNTAX     SEQUENCE OF Dot3ExtPkgOptIfEntry
        MAX-ACCESS not-accessible
        STATUS     current
        DESCRIPTION
                "This table defines the control and status indication
                 objects for the optical interface of the EPON interface.
                 Each object has a row for every virtual link denoted by
                 the corresponding ifIndex.
                 The LLID field, as defined in the IEEE Std 802.3, is a 2-byte
                 register (15-bit field and a broadcast bit) limiting the
                 number of virtual links to 32768. Typically the number
                 of expected virtual links in a PON is like the number of
                 ONUs, which is 32-64, plus an additional entry for
                 broadcast LLID.
                 Although the optical interface is a physical interface,
                 there is a row in the table for each virtual interface.
                 The reason for having a separate row for each virtual
                 link is that the OLT has a separate link for each one of
                 the ONUs. For instance, ONUs could be in different
                 distances with different link budgets and different
                 receive powers, therefore having different power alarms.
                 It is quite similar to a case of different physical
                 interfaces."
        ::= { dot3ExtPkgControlObjects 5}

    dot3ExtPkgOptIfEntry OBJECT-TYPE
        SYNTAX     Dot3ExtPkgOptIfEntry
        MAX-ACCESS not-accessible
        STATUS     current
        DESCRIPTION
                "An entry in the optical interface table of the EPON
                 interface.
                 Rows exist for an OLT interface and an ONU interface.
                 A row in the table is denoted by the ifIndex of the link
                 and it is created when the ifIndex is created.
                 The rows in the table for an ONU interface are created
                 at system initialization.
                 The row in the table corresponding to the OLT ifIndex
                 and the row corresponding to the broadcast virtual link
                 are created at system initialization.
                 A row in the table corresponding to the ifIndex of a
                 virtual links is created when a virtual link is
                 established (ONU registers) and deleted when the virtual
                 link is deleted (ONU deregisters)."
        INDEX       { ifIndex }
        ::= { dot3ExtPkgOptIfTable 1 }

     Dot3ExtPkgOptIfEntry ::=
       SEQUENCE {
         dot3ExtPkgOptIfSuspectedFlag             TruthValue,
         dot3ExtPkgOptIfInputPower                Integer32,
         dot3ExtPkgOptIfLowInputPower             Integer32,
```

```
        dot3ExtPkgOptIfHighInputPower            Integer32,
        dot3ExtPkgOptIfLowerInputPowerThreshold  Integer32,
        dot3ExtPkgOptIfUpperInputPowerThreshold  Integer32,
        dot3ExtPkgOptIfOutputPower               Integer32,
        dot3ExtPkgOptIfLowOutputPower            Integer32,
        dot3ExtPkgOptIfHighOutputPower           Integer32,
        dot3ExtPkgOptIfLowerOutputPowerThreshold Integer32,
        dot3ExtPkgOptIfUpperOutputPowerThreshold Integer32,
        dot3ExtPkgOptIfSignalDetect              TruthValue,
        dot3ExtPkgOptIfTransmitAlarm             TruthValue,
        dot3ExtPkgOptIfTransmitEnable            TruthValue
        }

  dot3ExtPkgOptIfSuspectedFlag OBJECT-TYPE
    SYNTAX  TruthValue
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
      "This object is a reliability indication.
       If true, the data in this entry may be unreliable.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
    ::= { dot3ExtPkgOptIfEntry 1 }

  dot3ExtPkgOptIfInputPower OBJECT-TYPE
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
      "The optical power monitored at the input.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
  ::= { dot3ExtPkgOptIfEntry 2 }

  dot3ExtPkgOptIfLowInputPower OBJECT-TYPE
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
      "The lowest optical power monitored at the input during the
       current 15-minute interval.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
    ::= { dot3ExtPkgOptIfEntry 3 }
  dot3ExtPkgOptIfHighInputPower OBJECT-TYPE
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
      "The highest optical power monitored at the input during the
       current 15-minute interval.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
    ::= { dot3ExtPkgOptIfEntry 4 }

  dot3ExtPkgOptIfLowerInputPowerThreshold OBJECT-TYPE
```

```
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
      "The lower limit threshold on input power. If
       dot3ExtPkgOptIfInputPower drops to this value or below,
       a Threshold Crossing Alert (TCA) should be sent.
       Reading will present the threshold value. Writing will
       set the value of the threshold.
       The write operation is not restricted in this document
       and can be done at any time. Changing
       dot3ExtPkgOptIfLowerInputPowerThreshold can lead to a Threshold
       Crossing Alert (TCA) being sent for the respective interface.
       This alert may be leading to an interruption of service for the
       users connected to the respective EPON interface, depending on
       the system action on such an alert.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
    ::= { dot3ExtPkgOptIfEntry 5 }

  dot3ExtPkgOptIfUpperInputPowerThreshold OBJECT-TYPE
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
      "The upper limit threshold on input power. If
       dot3ExtPkgOptIfInputPower reaches or exceeds this value,
       a Threshold Crossing Alert (TCA) should be sent.
       Reading will present the threshold value. Writing will
       set the value of the threshold.
       The write operation is not restricted in this document
       and can be done at any time. Changing
       dot3ExtPkgOptIfUpperInputPowerThreshold can lead to a Threshold
       Crossing Alert (TCA) being sent for the respective interface.
       This alert may be leading to an interruption of service for the
       users connected to the respective EPON interface, depending on
       the system action on such an alert.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
   ::= { dot3ExtPkgOptIfEntry 6 }

  dot3ExtPkgOptIfOutputPower OBJECT-TYPE
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
      "The optical power monitored at the output.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
    ::= { dot3ExtPkgOptIfEntry 7 }

  dot3ExtPkgOptIfLowOutputPower OBJECT-TYPE
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-only
    STATUS  current
```

```
    DESCRIPTION
      "The lowest optical power monitored at the output during the
       current 15-minute interval.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
    ::= { dot3ExtPkgOptIfEntry 8 }

  dot3ExtPkgOptIfHighOutputPower OBJECT-TYPE
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
      "The highest optical power monitored at the output during the
       current 15-minute interval.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
   ::= { dot3ExtPkgOptIfEntry 9 }

  dot3ExtPkgOptIfLowerOutputPowerThreshold OBJECT-TYPE
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
      "The lower limit threshold on output power. If
       dot3ExtPkgOptIfOutputPower drops to this value or below,
       a Threshold Crossing Alert (TCA) should be sent.
       Reading will present the threshold value. Writing will
       set the value of the threshold.
       The write operation is not restricted in this document
       and can be done at any time. Changing
       dot3ExtPkgOptIfLowerOutputPowerThreshold can lead to a Threshold
       Crossing Alert (TCA) being sent for the respective interface.
       This alert may be leading to an interruption of service for the
       users connected to the respective EPON interface, depending on
       the system action on such an alert.
       This object is applicable for an OLT and an ONU. At the
       OLT, it has a distinct value for each virtual interface."
  ::= { dot3ExtPkgOptIfEntry 10 }

  dot3ExtPkgOptIfUpperOutputPowerThreshold OBJECT-TYPE
    SYNTAX  Integer32
    UNITS  "0.1 dbm"
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
      "The upper limit threshold on output power. If
       dot3ExtPkgOptIfOutputPower reaches or exceeds this value,
       a Threshold Crossing Alert (TCA) should be sent.
       Reading will present the threshold value. Writing will
       set the value of the threshold.
       The write operation is not restricted in this document
       and can be done at any time. Changing
       dot3ExtPkgOptIfUpperOutputPowerThreshold can lead to a Threshold
       Crossing Alert (TCA) being sent for the respective interface.
       This alert may be leading to an interruption of service of the
       users connected to the respective EPON interface, depending on
       the system action on such an alert.
```

```
         This object is applicable for an OLT and an ONU. At the
         OLT, it has a distinct value for each virtual interface."
      ::= { dot3ExtPkgOptIfEntry 11 }

    dot3ExtPkgOptIfSignalDetect OBJECT-TYPE
        SYNTAX  TruthValue
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "When getting true(1), there is a valid optical signal at
                 the receive that is above the optical power level for
                 signal detection. When getting false(2) the optical
                 signal at the receive is below the optical power level
                 for signal detection.
                 This object is applicable for an OLT and an ONU. At the
                 OLT, it has a distinct value for each virtual interface."
        DEFVAL { false }
        ::= { dot3ExtPkgOptIfEntry 12 }

    dot3ExtPkgOptIfTransmitAlarm OBJECT-TYPE
        SYNTAX  TruthValue
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "When getting true(1) there is a non-valid optical signal
                 at the transmit of the interface, either a higher level
                 or lower level than expected. When getting false(2) the
                 optical signal at the transmit is valid and in the
                 required range.
                 This object is applicable for an OLT and an ONU. At the
                 OLT, it has a distinct value for each virtual interface."
        DEFVAL { false }
        ::= { dot3ExtPkgOptIfEntry 13 }

    dot3ExtPkgOptIfTransmitEnable OBJECT-TYPE
        SYNTAX  TruthValue
        MAX-ACCESS  read-write
        STATUS  current
        DESCRIPTION
                "Setting this object to true(1) will cause the optical
                 interface to start transmission (according to the
                 control protocol specified for the logical interface).
                 Setting this object to false(2) will cause the
                 interface to stop the optical transmission.
                 When getting true(1), the optical interface is in
                 transmitting mode (obeying to the logical control
                 protocol).
                 When getting false(2), the optical interface is not in
                 transmitting mode.
                 The write operation is not restricted in this document
                 and can be done at any time. Changing
                 dot3ExtPkgOptIfTransmitEnable state can lead to a halt
                 in the optical transmission of the respective interface
                 leading to an interruption of service of the users
                 connected to the respective EPON interface.
                 The object is relevant when the admin state of the
                 interface is active as set by the dot3MpcpAdminState.
                 This object is applicable for an OLT and an ONU. At the
                 OLT it, has a distinct value for each virtual interface."
```

```
      DEFVAL { false }
      ::= { dot3ExtPkgOptIfEntry 14 }

      --
      -- The MulticastIDs Table
      --
dot3RecognizedMulticastIDsTable OBJECT-TYPE
    SYNTAX     SEQUENCE OF Dot3RecognizedMulticastIDsEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
            "A table of MulticastIDs to be recognized by this device."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.25."
    ::= { dot3EponObjects 5 }

dot3RecognizedMulticastIDsEntry OBJECT-TYPE
    SYNTAX     Dot3RecognizedMulticastIDsEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
            "An entry in the table of MulticastIDs to be recognized by this
             device."
    INDEX      { ifIndex, dot3RecognizedMulticastIDIndex }
    ::= { dot3RecognizedMulticastIDsTable 1 }

Dot3RecognizedMulticastIDsEntry ::=
    SEQUENCE {
            dot3RecognizedMulticastIDIndex    Unsigned32,
            dot3RecognizedMulticastID         Unsigned32
             }

dot3RecognizedMulticastIDIndex OBJECT-TYPE
    SYNTAX     Unsigned32 (0..127)
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
            "An index into the table of MulticastIDs to be recognized by this
             device."
    ::= { dot3RecognizedMulticastIDsEntry 1 }

dot3RecognizedMulticastID OBJECT-TYPE
    SYNTAX     Unsigned32
    MAX-ACCESS read-write
    STATUS     current
    DESCRIPTION
            "An Uunsigned32 representing a single MulticastID to be recognized
             by this device."
    REFERENCE   "IEEE Std 802.3, 30.3.5.1.25."
    ::= { dot3RecognizedMulticastIDsEntry 2 }

  -- Conformance statements

  -- Conformance Groups

  dot3EponGroups      OBJECT IDENTIFIER ::= { dot3EponConformance 1 }

  dot3MpcpGroupBase OBJECT-GROUP
      OBJECTS {
               dot3MpcpOperStatus,
```

```
                dot3MpcpAdminState,
                dot3MpcpMode,
                dot3MpcpSyncTime,
                dot3MpcpLinkID,
                dot3MpcpRemoteMACAddress,
                dot3MpcpRegistrationState,
                dot3MpcpMaximumPendingGrants,
                dot3MpcpTransmitElapsed,
                dot3MpcpReceiveElapsed,
                dot3MpcpRoundTripTime
        }
        STATUS  current
        DESCRIPTION
               "A collection of objects of dot3 Mpcp Control entity state
                definition. Objects are per LLID."
        ::= { dot3EponGroups 1 }

    dot3MpcpGroupStat OBJECT-GROUP
        OBJECTS {
                dot3MpcpMACCtrlFramesTransmitted,
                dot3MpcpMACCtrlFramesReceived,
                dot3MpcpDiscoveryWindowsSent,
                dot3MpcpDiscoveryTimeout,
                dot3MpcpTxRegRequest,
                dot3MpcpRxRegRequest,
                dot3MpcpTxRegAck,
                dot3MpcpRxRegAck,
                dot3MpcpTxReport,
                dot3MpcpRxReport,
                dot3MpcpTxGate,
                dot3MpcpRxGate,
                dot3MpcpTxRegister,
                dot3MpcpRxRegister
        }
        STATUS  current
        DESCRIPTION
                "A collection of objects of dot3 Mpcp Statistics.
                 Objects are per LLID."
        ::= { dot3EponGroups 2 }
    dot3OmpeGroupID OBJECT-GROUP
        OBJECTS {
                dot3OmpEmulationType

        }
        STATUS  current
        DESCRIPTION
                "A collection of objects of dot3 OMP emulation entity
                 state definition. Objects are per LLID."
        ::= { dot3EponGroups 3 }

    dot3OmpeGroupStat OBJECT-GROUP
        OBJECTS {
                dot3OmpEmulationSLDErrors,
                dot3OmpEmulationCRC8Errors,
                dot3OmpEmulationBadLLID,
                dot3OmpEmulationGoodLLID,
                dot3OmpEmulationOnuPonCastLLID,
                dot3OmpEmulationOltPonCastLLID,
                dot3OmpEmulationBroadcastBitNotOnuLlid,
```

```
                dot3OmpEmulationOnuLLIDNotBroadcast,
                dot3OmpEmulationBroadcastBitPlusOnuLlid,
                dot3OmpEmulationNotBroadcastBitNotOnuLlid
        }
        STATUS  current
        DESCRIPTION
                "A collection of objects of dot3 OMP emulation
                 Statistics. Objects are per LLID."
        ::= { dot3EponGroups 4 }

    dot3EponFecGroupAll OBJECT-GROUP
        OBJECTS {
                dot3EponFecPCSCodingViolation,
                dot3EponFecAbility,
                dot3EponFecMode,
                dot3EponFecCorrectedBlocks,
                dot3EponFecUncorrectableBlocks,
                dot3EponFecBufferHeadCodingViolation
        }
        STATUS  current
        DESCRIPTION
                "A collection of objects of dot3 FEC group control and
                statistics. Objects are per LLID."
        ::= { dot3EponGroups 5 }

    dot3ExtPkgGroupControl OBJECT-GROUP
        OBJECTS {
                dot3ExtPkgObjectReset,
                dot3ExtPkgObjectPowerDown,
                dot3ExtPkgObjectNumberOfLLIDs,
                dot3ExtPkgObjectFecEnabled,
                dot3ExtPkgObjectReportMaximumNumQueues,
                dot3ExtPkgObjectRegisterAction
        }
        STATUS  current
        DESCRIPTION
                "A collection of objects of dot3ExtPkg control
                 definition. Objects are per LLID."
        ::= { dot3EponGroups 6 }

    dot3ExtPkgGroupQueue OBJECT-GROUP
        OBJECTS {
         dot3ExtPkgObjectReportNumThreshold,
         dot3ExtPkgObjectReportMaximumNumThreshold,
         dot3ExtPkgStatTxFramesQueue,
         dot3ExtPkgStatRxFramesQueue,
         dot3ExtPkgStatDroppedFramesQueue
        }
        STATUS  current
        DESCRIPTION
                "A collection of objects of dot3ExtPkg Queue
                 control. Objects are per LLID, per queue."
        ::= { dot3EponGroups 7 }

    dot3ExtPkgGroupQueueSets OBJECT-GROUP
        OBJECTS {
         dot3ExtPkgObjectReportThreshold
        }
        STATUS  current
```

```
    DESCRIPTION
            "A collection of objects of dot3ExtPkg queue_set
             control. Objects are per LLID, per queue, per
             queue_set."
    ::= { dot3EponGroups 8 }

dot3ExtPkgGroupOptIf OBJECT-GROUP
    OBJECTS {
     dot3ExtPkgOptIfSuspectedFlag,
     dot3ExtPkgOptIfInputPower,
     dot3ExtPkgOptIfLowInputPower,
     dot3ExtPkgOptIfHighInputPower,
     dot3ExtPkgOptIfLowerInputPowerThreshold,
     dot3ExtPkgOptIfUpperInputPowerThreshold,
     dot3ExtPkgOptIfOutputPower,
     dot3ExtPkgOptIfLowOutputPower,
     dot3ExtPkgOptIfHighOutputPower,
     dot3ExtPkgOptIfLowerOutputPowerThreshold,
     dot3ExtPkgOptIfUpperOutputPowerThreshold,
     dot3ExtPkgOptIfSignalDetect,
     dot3ExtPkgOptIfTransmitAlarm,
     dot3ExtPkgOptIfTransmitEnable
     }
    STATUS  current
    DESCRIPTION
            "A collection of objects of control and status indication
             of the optical interface.
             Objects are per LLID."
    ::= { dot3EponGroups 9 }

dot3EponGroupMulticastIDs OBJECT-GROUP
     OBJECTS {
      dot3RecognizedMulticastID
      }
     STATUS  current
     DESCRIPTION
           "One of a set of MulticastIDs recognized by an EPON interface."
    ::= { dot3EponGroups 10 }

-- Compliance statements

   dot3EponCompliances
       OBJECT IDENTIFIER ::= { dot3EponConformance 2 }

dot3MPCPCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION "The compliance statement for MultiPoint
                 Control Protocol interfaces."

    MODULE  -- this module
    MANDATORY-GROUPS { dot3MpcpGroupBase}

    GROUP       dot3MpcpGroupStat
   DESCRIPTION "This group is mandatory for all MPCP supporting
                interfaces for statistics collection."
   ::= { dot3EponCompliances 1}

dot3OmpeCompliance MODULE-COMPLIANCE
    STATUS      current
```

```
    DESCRIPTION "The compliance statement for OMPEmulation
                 interfaces."

    MODULE  -- this module
    MANDATORY-GROUPS { dot3OmpeGroupID}

    GROUP       dot3OmpeGroupStat
    DESCRIPTION "This group is mandatory for all OMPemulation
                 supporting interfaces for statistics collection."

    ::= { dot3EponCompliances 2}

dot3EponFecCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION "The compliance statement for FEC EPON interfaces.
                 This group is mandatory for all FEC supporting
                 interfaces for control and statistics collection."

    MODULE  -- this module
    MANDATORY-GROUPS { dot3EponFecGroupAll }

    ::= { dot3EponCompliances 3}

dot3ExtPkgCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION "The compliance statement for EPON Interfaces
                 using the extended package."
    MODULE  -- this module
    MANDATORY-GROUPS { dot3ExtPkgGroupControl }

    GROUP       dot3ExtPkgGroupQueue
    DESCRIPTION " This group is mandatory for all EPON interfaces
                 supporting REPORT queue management of the extended
                 package."

    GROUP       dot3ExtPkgGroupQueueSets
    DESCRIPTION " This group is mandatory for all EPON interfaces
                 supporting REPORT queue_sets management of the
                 extended package."

    GROUP       dot3ExtPkgGroupOptIf
    DESCRIPTION "This group is mandatory for all EPON interfaces
                 supporting optical interfaces management,
                 of the extended package."

    ::= { dot3EponCompliances 4}

dot3EponMulticastIDsCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION "The compliance statement for EPON Interfaces that
                 support MulticastIDs."
    MODULE  -- this module
    MANDATORY-GROUPS { dot3EponGroupMulticastIDs }

    ::= { dot3EponCompliances 5 }

END
```

10. Ethernet-like interface MIB module

10.1 Introduction

This clause defines a portion of the MIB for use with SNMP. In particular, it defines objects for managing Ethernet-like interfaces.

10.2 Overview

Instances of these object types represent attributes of an interface to an Ethernet-like communications medium.

The definitions presented here are based on Clause 30 of IEEE Std 802.3. Implementors of these MIB objects should note that IEEE Std 802.3 explicitly describes (in the form of Pascal pseudocode) when, where, and how various MAC attributes are measured. IEEE Std 802.3 also describes the effects of MAC actions that may be invoked by manipulating instances of the MIB objects defined here.

To the extent that some of the attributes defined in IEEE Std 802.3 are represented by previously defined objects in MIB-2 from IETF RFC 1213 or in the Interfaces Group MIB defined in IETF RFC 2863, such attributes are not redundantly represented by objects defined in this clause. Among the attributes represented by objects defined in other MIB module specifications are the number of octets transmitted or received on a particular interface, the number of frames transmitted or received on a particular interface, the promiscuous status of an interface, the MAC address of an interface, and multicast information associated with an interface.

10.2.1 Relation to MIB-2

This subclause applies only when this MIB is used in conjunction with the IETF RFC 1213 interface group.

The relationship between an Ethernet-like interface and an interface in the context of MIB-2 is one-to-one. As such, the value of an ifIndex object instance can be directly used to identify corresponding instances of the objects defined herein.

10.2.2 Relation to the Interfaces Group MIB

The Interfaces Group MIB defined in IETF RFC 2863 requires that any MIB that is an adjunct of the Interfaces Group MIB clarify specific areas within the Interfaces Group MIB. These areas were intentionally left vague in the Interfaces Group MIB to avoid overconstraining the MIB, thereby precluding management of certain media-types.

Section 4 of IETF RFC 2863 enumerates several areas that a media-specific MIB must (wherein the word “must” is used in accordance with the requirements of IETF RFC 2119) clarify. Each of these areas is addressed in a following subclause. The implementor is referred to IETF RFC 2863 in order to understand the general intent of these areas.

10.2.2.1 ifRcvAddressTable

This table contains all IEEE 802.3 addresses, unicast, multicast, and broadcast, for which this interface will receive packets and forward them up to a higher layer entity for local consumption. The format of the address, contained in ifRcvAddressAddress, is the same as for ifPhysAddress.

In the event that the interface is part of a MAC bridge, this table does not include unicast addresses that are accepted for possible forwarding out some other port. This table is explicitly not intended to provide a bridge address filtering mechanism.

10.2.2.2 ifType

All Ethernet-like interfaces shall return ethernetCsmacd(6) for ifType. Information on the particular port type and operating speed is available from ifSpeed in the Interfaces Group MIB, and ifMauType in the MAU-MIB module defined in Clause 13. All Ethernet-like interfaces shall also implement the MAU-MIB module defined in Clause 13.[17]

10.2.2.3 ifXxxOctets

The Interfaces Group MIB octet counters, ifInOctets, ifOutOctets, ifHCInOctets, and ifHCOutOctets, include all octets in valid frames sent or received on the interface, including the MAC header and FCS, but not the preamble, start of frame delimiter, or extension octets. This corresponds to the definition of frameSize/8 in 4.2.7.1 of IEEE Std 802.3 (frameSize is defined in bits rather than in octets, and it is defined as 2 × addressSize + lengthOrTypeSize + dataSize + crcSize). They do not include the number of octets in collided or failed transmit attempts, since the MAC layer driver typically does not have visibility to count these octets. They also do not include octets in received invalid frames, since this information is normally not passed to the MAC layer, and since non-promiscuous MAC implementations cannot reliably determine whether an invalid frame was actually addressed to this station.

Note that these counters do include octets in valid MAC control frames sent or received on the interface, as well as octets in otherwise valid received MAC frames that are discarded by the MAC layer for some reason (insufficient buffer space, unknown protocol, etc.).

Note that the octet counters in IF-MIB do not exactly match the definition of the octet counters in IEEE Std 802.3. aOctetsTransmittedOK and aOctetsReceivedOK count only the octets in the clientData and Pad fields, whereas ifInOctets and ifOutOctets include the entire MAC frame, including MAC header and FCS. However, the IF-MIB counters can be derived from the IEEE 802.3 counters as follows in Equation (1) and Equation (2):

$$\mathrm{ifInOctets} = \mathrm{aOctetsReceivedOK} + (18 \times \mathrm{aFramesReceivedOK}) \tag{1}$$

$$\mathrm{ifOutOctets} = \mathrm{aOctetsTransmittedOK} + (18 \times \mathrm{aFramesTransmittedOK}) \tag{2}$$

Another difference to keep in mind between the IF-MIB counters and IEEE 802.3 counters is that, in IEEE Std 802.3, the frame counters and octet counters are incremented together. aOctetsTransmittedOK counts the number of octets in frames that were counted by aFramesTransmittedOK. aOctetsReceivedOK counts the number of octets in frames that were counted by aFramesReceivedOK. This is not the case with the IF-MIB counters. The IF-MIB octet counters count the number of octets sent to or received from the layer below this interface, whereas the packet counters count the number of packets sent to or received from the layer above. Therefore, received MAC Control frames, ifInDiscards, and ifInUnknownProtos are counted by ifInOctets, but not by ifInXcastPkts. Transmitted MAC Control frames are counted by ifOutOctets, but not by ifOutXcastPkts. ifOutDiscards and ifOutErrors are counted by ifOutXcastPkts, but not by ifOutOctets.

[17]There are three other interface types defined in IANAifType-MIB for Ethernet, namely, fastEther(62), fastEtherFX(69), and gigabitEthernet(117). Management applications should be prepared to receive these obsolete ifType values from older implementations.

10.2.2.4 ifXxxXcastPkts

The packet counters in the IF-MIB do not exactly match the definition of the frame counters in IEEE Std 802.3. aFramesTransmittedOK counts the number of frames successfully transmitted on the interface, whereas ifOutUcastPkts, ifOutMulticastPkts, and ifOutBroadcastPkts count the number of transmit requests made from a higher layer, whether or not the transmit attempt was successful. This means that packets counted by ifOutErrors or ifOutDiscards are also counted by ifOutXcastPkts, but they are not counted by aFramesTransmittedOK. This also means that, since MAC Control frames are generated by a sublayer internal to the interface layer rather than by a higher layer, they are not counted by ifOutXcastPkts, but they are counted by aFramesTransmittedOK:

$$\begin{aligned} \text{aFramesTransmittedOK} = {} & \text{ifOutUcastPkts} + \text{ifOutMulticastPkts} \\ & + \text{ifOutBroadcastPkts} + \text{dot3OutPauseFrames} \\ & - (\text{ifOutErrors} + \text{ifOutDiscards}) \end{aligned} \tag{3}$$

Similarly, aFramesReceivedOK counts the number of frames received successfully by the interface, whether or not they are passed to a higher layer, whereas ifInUcastPkts, ifInMulticastPkts, and ifInBroadcastPkts count only the number of packets passed to a higher layer. This means that packets counted by ifInDiscards or ifInUnknownProtos are also counted by aFramesReceivedOK, but they are not counted by ifInXcastPkts. This also means that, since MAC Control frames are consumed by a sublayer internal to the interface layer and not passed to a higher layer, they are not counted by ifInXcastPkts, but they are counted by aFramesReceivedOK:

$$\begin{aligned} \text{aFramesReceivedOK} = {} & \text{ifInUcastPkts} + \text{ifInMulticastPkts} \\ & + \text{ifInBroadcastPkts} + \text{dot3InPauseFrames} \\ & + \text{ifInDiscards} + \text{ifInUnknownProtos} \end{aligned} \tag{4}$$

This specification chooses to treat MAC control frames as being originated and consumed within the interface and not counted by the IF-MIB packet counters. MAC control frames are normally sent as multicast packets. In many network environments, MAC control frames can greatly outnumber multicast frames carrying actual data. If MAC control frames were included in the ifInMulticastPkts and ifOutMulticastPkts, the count of data-carrying multicast packets would tend to be drowned out by the count of MAC control frames, rendering those counters considerably less useful.

To better understand the issues surrounding the mapping of the IF-MIB packet and octet counters to an Ethernet interface, it is useful to refer to a Case diagram (Case and Partridge [B2]) for the IF-MIB counters, with modifications to show the proper interpretation for the Ethernet interface. This is depicted in Figure 10-1.



Figure 10-1—Case diagram for the IF-MIB counters

10.2.2.5 ifMtu

The defined standard MTU for Ethernet-like interfaces is 1500 octets. However, many implementations today support larger packet sizes than IEEE Std 802.3. The value of this object shall reflect the actual MTU in use on the interface, whether it matches the standard MTU or not.

This value should reflect the value seen by the MAC client interface. When a higher layer protocol, like IP, is running over Ethernet framing, this is the MTU that will be seen by that higher layer protocol. However, most Ethernet-like interfaces today run multiple protocols that use a mix of different framing types. For example, an IEEE 802.2 LLC type 1 client protocol will see an MTU of 1497 octets on an interface using the IEEE standard maximum packet size, and a protocol running over SNAP will see an MTU of 1492 octets on an interface using the IEEE standard maximum packet size. However, since the specification mandates using the MTU as seen at the MAC client interface, the value of ifMtu would be reported as 1500 octets in these cases.

10.2.2.6 ifSpeed and ifHighSpeed

For Ethernet-like interfaces operating at 1000 Megabits per second (Mb/s) or less, ifSpeed will represent the current operational speed of the interface in bits per second. For such interface types, this will be equal to 1 000 000 (1 million), 10 000 000 (10 million), 100 000 000 (100 million), or 1 000 000 000 (1 billion). ifHighSpeed will represent the current operational speed in millions of bits per second. For such Ethernet-like interfaces, this will be equal to 1, 10, 100, or 1000. If the interface implements Auto-Negotiation, Auto-Negotiation is enabled for this interface, and the interface has not yet negotiated to an operational speed, then these objects should reflect the maximum speed supported by the interface.

For Ethernet-like interfaces operating at greater than 1000 Mb/s, ifHighSpeed will represent the current operational speed of the interface in millions of bits per second. Note that for WAN implementations, this will be the payload data rate over the WAN interface sublayer. For current implementations, this will be equal to 10 000 for LAN implementations of 10 Gb/s, and 9294 for WAN implementations of the 10 Gb/s MAC over an OC-192 PHY. For these speeds, ifSpeed should report a maximum unsigned 32-bit value of 4 294 967 295 as specified in IETF RFC 2863.

These objects shall indicate the correct line speed regardless of the current duplex mode. They shall not indicate a doubled value when operating in full-duplex mode. The duplex mode of the interface may be determined by examining either the dot3StatsDuplexStatus object in this MIB module or the ifMauType MAU-MIB module object defined in Clause 13.

10.2.2.7 ifPhysAddress

This object contains the IEEE 802.3 address that is placed in the source-address field of any Ethernet, Starlan, or IEEE 802.3 frames that originate at this interface. Usually this will be kept in ROM on the interface hardware. Some systems may set this address via software.

In a system where there are several such addresses, the designer has a tougher choice. The address chosen should be the one most likely to be of use to network management (e.g., the address placed in ARP responses for systems that are primarily IP systems).

If the designer truly cannot choose, use of the factory-provided ROM address is suggested.

If the address cannot be determined, an octet string of zero length should be returned.

The address is stored in binary in this object. The address is stored in “canonical” bit order; that is, the Group Bit is positioned as the low-order bit of the first octet. Thus, the first byte of a multicast address would have the bit 0x01 set.

10.2.2.8 Specific Interfaces Group MIB objects

Table 10-1 provides specific implementation guidelines for applying the Interfaces Group objects to Ethernet-like interfaces.

Table 10-1—Implementation guidelines

Object	Guidelines
ifIndex	Each Ethernet-like interface is represented by an ifEntry. The dot3StatsTable in this MIB module is indexed by dot3StatsIndex. The interface identified by a particular value of dot3StatsIndex is the same interface as identified by the same value of ifIndex.
ifDescr	Refer to IETF RFC 2863.
ifType	Refer to 10.2.2.2.
ifMtu	Refer to 10.2.2.5.
ifSpeed	Refer to 10.2.2.6.
ifPhysAddress	Refer to 10.2.2.7.
ifAdminStatus	Write access is not required. Support for “testing” is not required.
ifOperStatus	The operational state of the interface. Support for “testing” is not required. The value “dormant” has no meaning for an Ethernet-like interface.
ifLastChange	Refer to IETF RFC 2863.
ifInOctets	The number of octets in valid MAC frames received on this interface, including the MAC header and FCS. This does include the number of octets in valid MAC Control frames received on this interface. See 10.2.2.3.
ifInUcastPkts	Refer to IETF RFC 2863. Note that this does not include MAC Control frames, since MAC Control frames are consumed by the interface layer and are not passed to any higher layer protocol. See 10.2.2.4.
ifInDiscards	Refer to IETF RFC 2863.
ifInErrors	The sum for this interface of dot3StatsAlignmentErrors, dot3StatsFCSErrors, dot3StatsFrameTooLongs, and dot3StatsInternalMacReceiveErrors.
ifInUnknownProtos	Refer to IETF RFC 2863.
ifOutOctets	The number of octets transmitted in valid MAC frames on this interface, including the MAC header and FCS. This does include the number of octets in valid MAC Control frames transmitted on this interface. See 10.2.2.3.
ifOutUcastPkts	Refer to IETF RFC 2863. Note that this does not include MAC Control frames, since MAC Control frames are generated by the interface layer, and are not passed from any higher layer protocol. See 10.2.2.4.
ifOutDiscards	Refer to IETF RFC 2863.
ifOutErrors	The sum for this interface of: dot3StatsSQETestErrors, dot3StatsLateCollisions, dot3StatsExcessiveCollisions, dot3StatsInternalMacTransmitErrors and dot3StatsCarrierSenseErrors.

Table 10-1—Implementation guidelines *(continued)*

Object	Guidelines
ifName	Locally significant textual name for the interface (e.g., lan0).
ifInMulticastPkts	Refer to IETF RFC 2863. Note that this does not include MAC Control frames, since MAC Control frames are consumed by the interface layer and are not passed to any higher layer protocol. See 10.2.2.4.
ifInBroadcastPkts	Refer to IETF RFC 2863. Note that this does not include MAC Control frames, since MAC Control frames are consumed by the interface layer, and are not passed to any higher layer protocol. See 10.2.2.4.
ifOutMulticastPkts	Refer to IETF RFC 2863. Note that this does not include MAC Control frames, since MAC Control frames are generated by the interface layer, and are not passed from any higher layer protocol. See 10.2.2.4.
ifOutBroadcastPkts	Refer to IETF RFC 2863. Note that this does not include MAC Control frames, since MAC Control frames are generated by the interface layer, and are not passed from any higher layer protocol. See 10.2.2.4.
ifHCInOctets, ifHCOutOctets	64-bit versions of counters. Required for Ethernet-like interfaces that are capable of operating at 20 Mb/s or faster, even if the interface is currently operating at less than 20 Mb/s.
ifHCInUcastPkts, ifHCInMulticastPkts, ifHCInBroadcastPkts, ifHCOutUcastPkts, ifHCOutMulticastPkts, ifHCOutBroadcastPkts	64-bit versions of packet counters. Required for Ethernet-like interfaces that are capable of operating at 640 Mb/s or faster, even if the interface is currently operating at less than 640 Mb/s.
ifLinkUpDownTrapEnable	Refer to IETF RFC 2863. Default is “enabled.”
ifHighSpeed	Refer to 10.2.2.6.
ifPromiscuousMode	Refer to IETF RFC 2863.
ifConnectorPresent	This will normally be “true.” It will be “false” in the case where this interface uses the WAN Interface Sublayer. See Clause 12 for details.
ifAlias	Refer to IETF RFC 2863.
ifCounterDiscontinuityTime	Refer to IETF RFC 2863. Note that a discontinuity in the Interfaces Group MIB counters may also indicate a discontinuity in some or all of the counters in this MIB that are associated with that interface.
ifStackHigherLayer, ifStackLowerLayer, ifStackStatus	Refer to 11.2.1.1.
ifRcvAddressAddress, ifRcvAddressStatus, ifRcvAddressType	Refer to 10.2.2.1.

10.2.3 Relation to the IEEE 802.3 MAU-MIB module

Support for the mauModIfCompl3 compliance statement of the MAU-MIB module defined in Clause 13 is required for Ethernet-like interfaces. This MIB module is needed in order to allow applications to determine the current MAU type in use by the interface, and to control autonegotiation and duplex mode for the interface. Implementing this MIB module without implementing the MAU-MIB module would leave applications with no standard way to determine the media type in use, and no standard way to control the duplex mode of the interface.

10.2.4 Mapping of IEEE 802.3 managed objects

The mapping of IEEE 802.3 managed objects to SNMP objects is shown in Table 10-2.

Table 10-2—Mapping of IEEE 802.3 managed objects

IEEE 802.3 managed object		Corresponding SNMP object
oMacEntity	.aMACID	dot3StatsIndex or IF-MIB – ifIndex
	.aFramesTransmittedOK	IF-MIB – ifOutUCastPkts + ifOutMulticastPkts + ifOutBroadcastPkts[a]
	.aSingleCollisionFrames	dot3StatsSingleCollisionFrames
	.aMultipleCollisionFrames	dot3StatsMultipleCollisionFrames
	.aFramesReceivedOK	IF-MIB – ifInUcastPkts + ifInMulticastPkts + ifInBroadcastPkts[a]
	.aFrameCheckSequenceErrors	dot3StatsFCSErrors
	.aAlignmentErrors	dot3StatsAlignmentErrors
	.aOctetsTransmittedOK	IF-MIB – ifOutOctets[a]
	.aFramesWithDeferredXmissions	dot3StatsDeferredTransmissions
	.aLateCollisions	dot3StatsLateCollisions
	.aFramesAbortedDueToXSColls	dot3StatsExcessiveCollisions
	.aFramesLostDueToIntMACXmitError	dot3StatsInternalMacTransmitErrors
	.aCarrierSenseErrors	dot3StatsCarrierSenseErrors
	.aOctetsReceivedOK	IF-MIB – ifInOctets[a]
	.aFramesLostDueToIntMACRcvError	dot3StatsInternalMacReceiveErrors
	.aPromiscuousStatus	IF-MIB – ifPromiscuousMode
	.aReadMulticastAddressList	IF-MIB – ifRcvAddressTable
	.aMulticastFramesXmittedOK	IF-MIB – ifOutMulticastPkts[a]
	.aBroadcastFramesXmittedOK	IF-MIB – ifOutBroadcastPkts[a]
	.aMulticastFramesReceivedOK	IF-MIB – ifInMulticastPkts[a]
	.aBroadcastFramesReceivedOK	IF-MIB – ifInBroadcastPkts[a]
	.aFrameTooLongErrors	dot3StatsFrameTooLongs
	.aReadWriteMACAddress	IF-MIB – ifPhysAddress
	.aCollisionFrames	dot3CollFrequencies
	.aDuplexStatus	dot3StatsDuplexStatus
	.aRateControlAbility	dot3StatsRateControlAbility
	.aMaxFrameLength	dot3StatsMaxFrameLength

Table 10-2—Mapping of IEEE 802.3 managed objects *(continued)*

IEEE 802.3 managed object		Corresponding SNMP object
	.aSlowProtocolFrameLimit	dot3SlowProtocolFrameLimit
	.aRateControlStatus	dot3StatsRateControlStatus
	.acAddGroupAddress	IF-MIB - ifRcvAddressTable
	.acDeleteGroupAddress	IF-MIB - ifRcvAddressTable
	.acExecuteSelfTest	dot3TestLoopBack
oPHYEntity	.aPHYID	dot3StatsIndex or IF-MIB – ifIndex
	.aSQETestErrors	dot3StatsSQETestErrors
	.aSymbolErrorDuringCarrier	dot3StatsSymbolErrors
oMACControlEntity	.aMACControlID	dot3StatsIndex or IF-MIB – ifIndex
	.aMACControlFunctionsSupported	dot3ControlFunctionsSupported and dot3ControlFunctionsEnabled
	.aUnsupportedOpcodesReceived	dot3ControlInUnknownOpcodes
oPAUSEEntity	.aPAUSEMACCtrlFramesTransmitted	dot3OutPauseFrames
	.aPAUSEMACCtrlFramesReceived	dot3InPauseFrames

[a]Note that the octet counters in IF-MIB do not exactly match the definition of the octet counters in IEEE Std 802.3. See 10.2.2.3 for details. Also note that the packet counters in the IF-MIB do not exactly match the definition of the frame counters in IEEE Std 802.3. See 10.2.2.4 for details.

10.3 Security considerations for Ethernet-like interface MIB module

There is one management object defined in this MIB that has a MAX-ACCESS clause of read-write. That object, dot3PauseAdminMode, may be used to change the flow control configuration on a network interface, which may result in dropped packets, or sending flow control packets on links where the link partner will not understand them. Either action could be detrimental to network performance.

Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

Most of the objects in this MIB module contain statistical information about particular network links. In some network environments, this information may be considered sensitive. It is thus important to control GET and/or NOTIFY access to these objects and possibly to encrypt the values of these objects when sending them over the network via SNMP.

10.4 MIB module definition

An ASCII text version of the MIB definition can be found at the following URL[18]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C10mib.txt

[18]Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.

```
IEEE8023-EtherLike-MIB DEFINITIONS ::= BEGIN

    IMPORTS
        MODULE-IDENTITY, OBJECT-TYPE,
        Integer32, Counter32, Counter64, org, Unsigned32
            FROM SNMPv2-SMI
        MODULE-COMPLIANCE, OBJECT-GROUP
            FROM SNMPv2-CONF
        TruthValue
            FROM SNMPv2-TC
        ifIndex, InterfaceIndex
            FROM IF-MIB;

    ieee8023etherMIB MODULE-IDENTITY
     LAST-UPDATED "201304110000Z" -- April 11, 2013
     ORGANIZATION
       "IEEE 802.3 working group"
     CONTACT-INFO
         "WG-URL: http://www.ieee802.org/3/index.html
         WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

         Contact: Howard Frazier
         Postal:  3151 Zanker Road
                  San Jose, CA 95134
                  USA
         Tel:     +1.408.922.8164
         E-mail:  hfrazier@broadcom.com"

        DESCRIPTION "The MIB module to describe generic objects for
                    Ethernet-like network interfaces."

        REVISION    "201304110000Z" -- April 11, 2013
        DESCRIPTION
          "Revision, based on an earlier version in IEEE Std 802.3.1-2011."

        REVISION    "201102020000Z" -- February 2, 2011
        DESCRIPTION
          "Initial version, based on an earlier version published
           in RFC 3635."

         ::= { org ieee(111) standards-association-numbers-series-standards(2)
               lan-man-stds(802) ieee802dot3(3) ieee802dot3dot1mibs(1) 10 }


    ieee8023etherMIBObjects OBJECT IDENTIFIER ::= { ieee8023etherMIB 1 }

    -- the Ethernet-like Statistics group

    dot3StatsTable OBJECT-TYPE
        SYNTAX     SEQUENCE OF Dot3StatsEntry
        MAX-ACCESS not-accessible
        STATUS     current
        DESCRIPTION "Statistics for a collection of Ethernet-like
                    interfaces attached to a particular system.
                    There will be one row in this table for each
                    Ethernet-like interface in the system."
        ::= { ieee8023etherMIBObjects 2 }

    dot3StatsEntry OBJECT-TYPE
```

```
            SYNTAX     Dot3StatsEntry
            MAX-ACCESS not-accessible
            STATUS     current
            DESCRIPTION "Statistics for a particular interface to an
                        Ethernet-like medium."
            INDEX       { dot3StatsIndex }
            ::= { dot3StatsTable 1 }

        Dot3StatsEntry ::=
            SEQUENCE {

                dot3StatsIndex                      InterfaceIndex,
                dot3StatsAlignmentErrors            Counter32,
                dot3StatsFCSErrors                  Counter32,
                dot3StatsSingleCollisionFrames      Counter32,
                dot3StatsMultipleCollisionFrames    Counter32,
                dot3StatsSQETestErrors              Counter32,
                dot3StatsDeferredTransmissions      Counter32,
                dot3StatsLateCollisions             Counter32,
                dot3StatsExcessiveCollisions        Counter32,
                dot3StatsInternalMacTransmitErrors  Counter32,
                dot3StatsCarrierSenseErrors         Counter32,
                dot3StatsFrameTooLongs              Counter32,
                dot3StatsInternalMacReceiveErrors   Counter32,
                dot3StatsSymbolErrors               Counter32,
                dot3StatsDuplexStatus               INTEGER,
                dot3StatsRateControlAbility         TruthValue,
                dot3StatsRateControlStatus          INTEGER,
                dot3StatsMaxFrameLength             INTEGER
            }

        dot3StatsIndex OBJECT-TYPE
            SYNTAX      InterfaceIndex
            MAX-ACCESS  not-accessible
            STATUS      current
            DESCRIPTION "An index value that uniquely identifies an
                        interface to an Ethernet-like medium. The
                        interface identified by a particular value of
                        this index is the same interface as identified
                        by the same value of ifIndex."
            REFERENCE   "IETF RFC 2863, ifIndex"
            ::= { dot3StatsEntry 1 }

        dot3StatsAlignmentErrors OBJECT-TYPE
            SYNTAX      Counter32
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of frames received on a particular
                        interface that are not an integral number of
                        octets in length and do not pass the FCS check.

                        The count represented by an instance of this
                        object is incremented when the alignmentError
                        status is returned by the MAC service to the
                        LLC (or other MAC user). Received frames for
                        which multiple error conditions pertain are,
                        according to the conventions of IEEE 802.3
                        Layer Management, counted exclusively according
                        to the error status presented to the LLC.
```

```
                This counter does not increment for group
                encoding schemes greater than 4 bits per group.

                For interfaces operating at 10 Gb/s, this
                counter can roll over in less than 5 minutes if
                it is incrementing at its maximum rate. Since
                that amount of time could be less than a
                management station’s poll cycle time, in order
                to avoid a loss of information, a management
                station is advised to poll the
                dot3HCStatsAlignmentErrors object for 10 Gb/s
                or faster interfaces.

                Discontinuities in the value of this counter can
                occur at re-initialization of the management
                system, and at other times as indicated by the
                value of ifCounterDiscontinuityTime."
    REFERENCE   "IEEE Std 802.3, 30.3.1.1.7,
                aAlignmentErrors"
    ::= { dot3StatsEntry 2 }

dot3StatsFCSErrors OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A count of frames received on a particular
                interface that are an integral number of octets
                in length but do not pass the FCS check. This
                count does not include frames received with
                frame-too-long or frame-too-short error.

                The count represented by an instance of this
                object is incremented when the frameCheckError
                status is returned by the MAC service to the
                LLC (or other MAC user). Received frames for
                which multiple error conditions pertain are,
                according to the conventions of IEEE 802.3
                Layer Management, counted exclusively according
                to the error status presented to the LLC.

                Note:  Coding errors detected by the Physical
                Layer for speeds above 10 Mb/s will cause the
                frame to fail the FCS check.

                For interfaces operating at 10 Gb/s, this
                counter can roll over in less than 5 minutes if

                it is incrementing at its maximum rate. Since
                that amount of time could be less than a
                management station’s poll cycle time, in order
                to avoid a loss of information, a management
                station is advised to poll the
                dot3HCStatsFCSErrors object for 10 Gb/s or
                faster interfaces.

                Discontinuities in the value of this counter can
                occur at re-initialization of the management
                system, and at other times as indicated by the
```

```
                    value of ifCounterDiscontinuityTime."
        REFERENCE   "IEEE Std 802.3, 30.3.1.1.6,
                    aFrameCheckSequenceErrors."
        ::= { dot3StatsEntry 3 }

    dot3StatsSingleCollisionFrames OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of frames that are involved in a single
                    collision, and are subsequently transmitted
                    successfully.

                    A frame that is counted by an instance of this
                    object is also counted by the corresponding
                    instance of either the ifOutUcastPkts,
                    ifOutMulticastPkts, or ifOutBroadcastPkts,
                    and is not counted by the corresponding
                    instance of the dot3StatsMultipleCollisionFrames
                    object.

                    This counter does not increment when the
                    interface is operating in full-duplex mode.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system, and at other times as indicated by the
                    value of ifCounterDiscontinuityTime."
        REFERENCE   "IEEE Std 802.3, 30.3.1.1.3,
                    aSingleCollisionFrames."
        ::= { dot3StatsEntry 4 }

    dot3StatsMultipleCollisionFrames OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of frames that are involved in more

                    than one collision and are subsequently
                    transmitted successfully.

                    A frame that is counted by an instance of this
                    object is also counted by the corresponding
                    instance of either the ifOutUcastPkts,
                    ifOutMulticastPkts, or ifOutBroadcastPkts,
                    and is not counted by the corresponding
                    instance of the dot3StatsSingleCollisionFrames
                    object.

                    This counter does not increment when the
                    interface is operating in full-duplex mode.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system, and at other times as indicated by the
                    value of ifCounterDiscontinuityTime."
        REFERENCE   "IEEE Std 802.3, 30.3.1.1.4,
                    aMultipleCollisionFrames."
        ::= { dot3StatsEntry 5 }
```

```
dot3StatsSQETestErrors OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A count of times that the SQE TEST ERROR
                is received on a particular interface. The
                SQE TEST ERROR is set in accordance with the
                rules for verification of the SQE detection
                mechanism in the PLS Carrier Sense Function as
                described in IEEE Std 802.3, 7.2.4.6.

                This counter does not increment on interfaces
                operating at speeds greater than 10 Mb/s, or on
                interfaces operating in full-duplex mode.

                Discontinuities in the value of this counter can
                occur at re-initialization of the management
                system, and at other times as indicated by the
                value of ifCounterDiscontinuityTime."
    REFERENCE   "IEEE Std 802.3, 7.2.4.6, also 30.3.2.1.4,
                aSQETestErrors."
    ::= { dot3StatsEntry 6 }

dot3StatsDeferredTransmissions OBJECT-TYPE
    SYNTAX      Counter32

    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A count of frames for which the first
                transmission attempt on a particular interface
                is delayed because the medium is busy.

                The count represented by an instance of this
                object does not include frames involved in
                collisions.

                This counter does not increment when the
                interface is operating in full-duplex mode.

                Discontinuities in the value of this counter can
                occur at re-initialization of the management
                system, and at other times as indicated by the
                value of ifCounterDiscontinuityTime."
    REFERENCE   "IEEE Std 802.3, 30.3.1.1.9,
                aFramesWithDeferredXmissions."
    ::= { dot3StatsEntry 7 }

dot3StatsLateCollisions OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The number of times that a collision is
                detected on a particular interface later than
                one slotTime into the transmission of a packet.

                A (late) collision included in a count
                represented by an instance of this object is
                also considered as a (generic) collision for
```

```
                    purposes of other collision-related
                    statistics.

                    This counter does not increment when the
                    interface is operating in full-duplex mode.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system, and at other times as indicated by the
                    value of ifCounterDiscontinuityTime."
        REFERENCE   "IEEE Std 802.3, 30.3.1.1.10,
                    aLateCollisions."
        ::= { dot3StatsEntry 8 }

    dot3StatsExcessiveCollisions OBJECT-TYPE
        SYNTAX      Counter32

        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of frames for which transmission on a
                    particular interface fails due to excessive
                    collisions.

                    This counter does not increment when the
                    interface is operating in full-duplex mode.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system, and at other times as indicated by the
                    value of ifCounterDiscontinuityTime."
        REFERENCE   "IEEE Std 802.3, 30.3.1.1.11,
                    aFramesAbortedDueToXSColls."
        ::= { dot3StatsEntry 9 }

    dot3StatsInternalMacTransmitErrors OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of frames for which transmission on a
                    particular interface fails due to an internal
                    MAC sublayer transmit error. A frame is only
                    counted by an instance of this object if it is
                    not counted by the corresponding instance of
                    either the dot3StatsLateCollisions object, the
                    dot3StatsExcessiveCollisions object, or the
                    dot3StatsCarrierSenseErrors object.

                    The precise meaning of the count represented by
                    an instance of this object is implementation-
                    specific. In particular, an instance of this
                    object may represent a count of transmission
                    errors on a particular interface that are not
                    otherwise counted.

                    For interfaces operating at 10 Gb/s, this
                    counter can roll over in less than 5 minutes if
                    it is incrementing at its maximum rate. Since
                    that amount of time could be less than a
                    management station’s poll cycle time, in order
```

```
                        to avoid a loss of information, a management
                        station is advised to poll the
                        dot3HCStatsInternalMacTransmitErrors object for
                        10 Gb/s or faster interfaces.

                        Discontinuities in the value of this counter can

                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.1.1.12,
                        aFramesLostDueToIntMACXmitError."
            ::= { dot3StatsEntry 10 }

        dot3StatsCarrierSenseErrors OBJECT-TYPE
            SYNTAX      Counter32
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "The number of times that the carrier sense
                        condition was lost or never asserted when
                        attempting to transmit a frame on a particular
                        interface.

                        The count represented by an instance of this
                        object is incremented at most once per
                        transmission attempt, even if the carrier sense
                        condition fluctuates during a transmission
                        attempt.

                        This counter does not increment when the
                        interface is operating in full-duplex mode.

                        Discontinuities in the value of this counter can
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.1.1.13,
                        aCarrierSenseErrors."
            ::= { dot3StatsEntry 11 }

        -- { dot3StatsEntry 12 } is not assigned

        dot3StatsFrameTooLongs OBJECT-TYPE
            SYNTAX      Counter32
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of frames received on a particular
                        interface that exceed the maximum permitted
                        frame size.

                        The count represented by an instance of this
                        object is incremented when the frameTooLong
                        status is returned by the MAC service to the
                        LLC (or other MAC user). Received frames for
                        which multiple error conditions pertain are,

                        according to the conventions of IEEE 802.3
                        Layer Management, counted exclusively according
                        to the error status presented to the LLC.
```

```
                    For interfaces operating at 10 Gb/s, this
                    counter can roll over in less than 80 minutes if
                    it is incrementing at its maximum rate. Since
                    that amount of time could be less than a
                    management station’s poll cycle time, in order
                    to avoid a loss of information, a management
                    station is advised to poll the
                    dot3HCStatsFrameTooLongs object for 10 Gb/s
                    or faster interfaces.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system, and at other times as indicated by the
                    value of ifCounterDiscontinuityTime."
    REFERENCE       "IEEE Std 802.3, 30.3.1.1.25,
                    aFrameTooLongErrors."
    ::= { dot3StatsEntry 13 }

-- { dot3StatsEntry 14 } is not assigned

-- { dot3StatsEntry 15 } is not assigned

dot3StatsInternalMacReceiveErrors OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION     "A count of frames for which reception on a
                    particular interface fails due to an internal
                    MAC sublayer receive error. A frame is only
                    counted by an instance of this object if it is
                    not counted by the corresponding instance of
                    either the dot3StatsFrameTooLongs object, the
                    dot3StatsAlignmentErrors object, or the
                    dot3StatsFCSErrors object.

                    The precise meaning of the count represented by
                    an instance of this object is implementation-
                    specific. In particular, an instance of this
                    object may represent a count of receive errors
                    on a particular interface that are not
                    otherwise counted.

                    For interfaces operating at 10 Gb/s, this
                    counter can roll over in less than 5 minutes if

                    it is incrementing at its maximum rate. Since
                    that amount of time could be less than a
                    management station’s poll cycle time, in order
                    to avoid a loss of information, a management
                    station is advised to poll the
                    dot3HCStatsInternalMacReceiveErrors object for
                    10 Gb/s or faster interfaces.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system, and at other times as indicated by the
                    value of ifCounterDiscontinuityTime."
    REFERENCE       "IEEE Std 802.3, 30.3.1.1.15,
```

```
                aFramesLostDueToIntMACRcvError."
        ::= { dot3StatsEntry 16 }

    dot3StatsSymbolErrors OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "For an interface operating at 100 Mb/s, the
                    number of times there was an invalid data symbol
                    when a valid carrier was present.

                    For an interface operating in half-duplex mode
                    at 1000 Mb/s, the number of times the receiving
                    media is non-idle (a carrier event) for a period
                    of time equal to or greater than slotTime, and
                    during which there was at least one occurrence
                    of an event that causes the PHY to indicate
                    ‘Data reception error’ or ‘carrier extend error’
                    on the GMII.

                    For an interface operating in full-duplex mode
                    at 1000 Mb/s, the number of times the receiving
                    media is non-idle (a carrier event) for a period
                    of time equal to or greater than minFrameSize,
                    and during which there was at least one
                    occurrence of an event that causes the PHY to
                    indicate ‘Data reception error’ on the GMII.

                    For an interface operating at 10 Gb/s, 40 Gb/s, and
                    100 Gb/s, it is a count of the number of times the
                    receiving media is non-idle (the time between the
                    Start of Packet Delimiter and the End of Packet
                    Delimiter) for a period of time equal to or greater
                    than minFrameSize, and during which there was at least
                    one occurrence of an event that causes the PHY to
                    indicate ‘Receive Error’ on the XGMII, the XLGMII,
                    or the CGMII.

                    The count represented by an instance of this
                    object is incremented at most once per carrier
                    event, even if multiple symbol errors occur
                    during the carrier event. This count does
                    not increment if a collision is present.

                    This counter does not increment when the
                    interface is operating at 10 Mb/s.

                    For interfaces operating at 10 Gb/s, this
                    counter can roll over in less than 5 minutes if
                    it is incrementing at its maximum rate. Since
                    that amount of time could be less than a
                    management station’s poll cycle time, in order
                    to avoid a loss of information, a management
                    station is advised to poll the
                    dot3HCStatsSymbolErrors object for 10 Gb/s
                    or faster interfaces.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
```

```
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.2.1.5,
                        aSymbolErrorDuringCarrier."
            ::= { dot3StatsEntry 17 }

        dot3StatsDuplexStatus OBJECT-TYPE
            SYNTAX      INTEGER {
                            unknown(1),
                            halfDuplex(2),
                            fullDuplex(3)
                        }
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "The current mode of operation of the MAC
                        entity. ‘unknown’ indicates that the current
                        duplex mode could not be determined.

                        Management control of the duplex mode is
                        accomplished through the MAU MIB. When
                        an interface does not support autonegotiation,
                        or when autonegotiation is not enabled, the
                        duplex mode is controlled using
                        ifMauDefaultType. When autonegotiation is
                        supported and enabled, duplex mode is controlled
                        using ifMauAutoNegAdvertisedBits. In either
                        case, the currently operating duplex mode is
                        reflected both in this object and in ifMauType.

                        Note that this object provides redundant
                        information with ifMauType. Normally, redundant
                        objects are discouraged. However, in this
                        instance, it allows a management application to
                        determine the duplex status of an interface
                        without having to know every possible value of
                        ifMauType. This was felt to be sufficiently
                        valuable to justify the redundancy."
            REFERENCE   "IEEE Std 802.3, 30.3.1.1.32,
                        aDuplexStatus."
            ::= { dot3StatsEntry 18 }

        dot3StatsRateControlAbility OBJECT-TYPE
            SYNTAX      TruthValue
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "‘true’ for interfaces operating at speeds above
                        1000 Mb/s that support Rate Control through
                        lowering the average data rate of the MAC
                        sublayer, with frame granularity, and ‘false’
                        otherwise."
            REFERENCE   "IEEE Std 802.3, 30.3.1.1.33,
                        aRateControlAbility."
            ::= { dot3StatsEntry 19 }

        dot3StatsRateControlStatus OBJECT-TYPE
            SYNTAX      INTEGER {
                            rateControlOff(1),
                            rateControlOn(2),
                            unknown(3)
```

```
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "The current Rate Control mode of operation of
                the MAC sublayer of this interface."
    REFERENCE   "IEEE Std 802.3, 30.3.1.1.34,
                aRateControlStatus."
    ::= { dot3StatsEntry 20 }

dot3StatsMaxFrameLength OBJECT-TYPE
    SYNTAX      INTEGER {
                    unknown(1),
                    baseFrame(2),
                    qTaggedFrame(3),
                    envelopeFrame(4)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "This indicates the MAC frame length at
                 which the dot3StatsFrameTooLongs counter is
                 incremented."
    REFERENCE   "IEEE Std 802.3, 30.3.1.1.37, aMaxFrameLength."
    ::= { dot3StatsEntry 21 }

-- the Ethernet-like Collision Statistics group

-- Implementation of this group is optional; it is appropriate
-- for all systems which have the necessary metering

dot3CollTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Dot3CollEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "A collection of collision histograms for a
                particular set of interfaces."
    REFERENCE   "IEEE Std 802.3, 30.3.1.1.30,
                aCollisionFrames."
    ::= { ieee8023etherMIBObjects 5 }

dot3CollEntry OBJECT-TYPE
    SYNTAX      Dot3CollEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "A cell in the histogram of per-frame
                collisions for a particular interface. An

                instance of this object represents the
                frequency of individual MAC frames for which
                the transmission (successful or otherwise) on a
                particular interface is accompanied by a
                particular number of media collisions."
    INDEX       { ifIndex, dot3CollCount }
    ::= { dot3CollTable 1 }

Dot3CollEntry ::=
    SEQUENCE {
        dot3CollCount        Integer32,
        dot3CollFrequencies  Counter32
    }
```

```
-- { dot3CollEntry 1 } is no longer in use

dot3CollCount OBJECT-TYPE
    SYNTAX      Integer32 (1..16)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "The number of per-frame media collisions for
                which a particular collision histogram cell
                represents the frequency on a particular
                interface."
    ::= { dot3CollEntry 2 }

dot3CollFrequencies OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A count of individual MAC frames for which the
                transmission (successful or otherwise) on a
                particular interface occurs after the
                frame has experienced exactly the number
                of collisions in the associated
                dot3CollCount object.

                For example, a frame which is transmitted
                on interface 77 after experiencing
                exactly 4 collisions would be indicated
                by incrementing only dot3CollFrequencies.77.4.
                No other instance of dot3CollFrequencies would
                be incremented in this example.

                This counter does not increment when the
                interface is operating in full-duplex mode.

                Discontinuities in the value of this counter can

                occur at re-initialization of the management
                system, and at other times as indicated by the
                value of ifCounterDiscontinuityTime."
    ::= { dot3CollEntry 3 }

dot3ControlTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Dot3ControlEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "A table of descriptive and status information
                about the MAC Control sublayer on the
                Ethernet-like interfaces attached to a
                particular system. There will be one row in
                this table for each Ethernet-like interface in
                the system which implements the MAC Control
                sublayer. If some, but not all, of the
                Ethernet-like interfaces in the system implement
                the MAC Control sublayer, there will be fewer
                rows in this table than in the dot3StatsTable."
    ::= { ieee8023etherMIBObjects 9 }

dot3ControlEntry OBJECT-TYPE
    SYNTAX      Dot3ControlEntry
```

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "An entry in the table, containing information
                about the MAC Control sublayer on a single
                Ethernet-like interface."
    INDEX       { dot3StatsIndex }
    ::= { dot3ControlTable 1 }

Dot3ControlEntry ::=
    SEQUENCE {
        dot3ControlFunctionsSupported       BITS,
        dot3ControlInUnknownOpcodes         Counter32,
        dot3HCControlInUnknownOpcodes       Counter64
    }

dot3ControlFunctionsSupported OBJECT-TYPE
    SYNTAX      BITS {
                    pause(0),   -- 802.3 pause flow control
                    mpcp(1),    -- 802.3 multi-point control protocol
                    pfc(2)     -- 802.3 priority-based flow control
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A list of the possible MAC Control functions
                implemented for this interface."
    REFERENCE   "IEEE Std 802.3, 30.3.3.2,
                aMACControlFunctionsSupported."

    ::= { dot3ControlEntry 1 }

dot3ControlInUnknownOpcodes OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A count of MAC Control frames received on this
                interface that contain an opcode that is not
                supported by this device.

                For interfaces operating at 10 Gb/s, this
                counter can roll over in less than 5 minutes if
                it is incrementing at its maximum rate. Since
                that amount of time could be less than a
                management station’s poll cycle time, in order
                to avoid a loss of information, a management
                station is advised to poll the
                dot3HCControlInUnknownOpcodes object for 10 Gb/s
                or faster interfaces.

                Discontinuities in the value of this counter can
                occur at re-initialization of the management
                system, and at other times as indicated by the
                value of ifCounterDiscontinuityTime."
    REFERENCE   "IEEE Std 802.3, 30.3.3.5,
                aUnsupportedOpcodesReceived"
    ::= { dot3ControlEntry 2 }

dot3HCControlInUnknownOpcodes OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
```

```
    STATUS      current
    DESCRIPTION "A count of MAC Control frames received on this
                interface that contain an opcode that is not
                supported by this device.

                This counter is a 64-bit version of
                dot3ControlInUnknownOpcodes. It should be used
                on interfaces operating at 10 Gb/s or faster.

                Discontinuities in the value of this counter can
                occur at re-initialization of the management
                system, and at other times as indicated by the
                value of ifCounterDiscontinuityTime."
    REFERENCE   "IEEE Std 802.3, 30.3.3.5,
                aUnsupportedOpcodesReceived"
    ::= { dot3ControlEntry 3 }


dot3PauseTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Dot3PauseEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "A table of descriptive and status information
                about the MAC Control PAUSE function on the
                Ethernet-like interfaces attached to a
                particular system. There will be one row in
                this table for each Ethernet-like interface in
                the system which supports the MAC Control PAUSE
                function (i.e., the 'pause' bit in the
                corresponding instance of
                dot3ControlFunctionsSupported is set). If some,
                but not all, of the Ethernet-like interfaces in
                the system implement the MAC Control PAUSE
                function (for example, if some interfaces only
                support half-duplex), there will be fewer rows
                in this table than in the dot3StatsTable."
    ::= { ieee8023etherMIBObjects 10 }

dot3PauseEntry OBJECT-TYPE
    SYNTAX      Dot3PauseEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "An entry in the table, containing information
                about the MAC Control PAUSE function on a single
                Ethernet-like interface."
    INDEX       { dot3StatsIndex }
    ::= { dot3PauseTable 1 }

Dot3PauseEntry ::=

    SEQUENCE {
        dot3PauseAdminMode                  INTEGER,
        dot3PauseOperMode                   INTEGER,
        dot3InPauseFrames                   Counter32,
        dot3OutPauseFrames                  Counter32,
        dot3HCInPauseFrames                 Counter64,
        dot3HCOutPauseFrames                Counter64
    }
```

```
    dot3PauseAdminMode OBJECT-TYPE
        SYNTAX      INTEGER {
                        disabled(1),
                        enabledXmit(2),
                        enabledRcv(3),
                        enabledXmitAndRcv(4)
                    }

        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION "This object is used to configure the default
                    administrative PAUSE mode for this interface.

                    This object represents the
                    administratively-configured PAUSE mode for this
                    interface. If Auto-Negotiation is not enabled
                    or is not implemented for the active MAU
                    attached to this interface, the value of this
                    object determines the operational PAUSE mode
                    of the interface whenever it is operating in
                    full-duplex mode. In this case, a set to this
                    object will force the interface into the
                    specified mode.

                    If Auto-Negotiation is implemented and enabled
                    for the MAU attached to this interface, the
                    PAUSE mode for this interface is determined by
                    Auto-Negotiation, and the value of this object
                    denotes the mode to which the interface will
                    automatically revert if/when Auto-Negotiation is
                    later disabled. Note that when Auto-Negotiation
                    is running, administrative control of the PAUSE
                    mode may be accomplished using the
                    ifMauAutoNegCapAdvertisedBits object in the
                    MAU-MIB module.

                    Note that the value of this object is ignored
                    when the interface is not operating in
                    full-duplex mode.

                    An attempt to set this object to
                    ‘enabledXmit(2)’ or ‘enabledRcv(3)’ will fail
                    on interfaces that do not support operation
                    at greater than 100 Mb/s."
        ::= { dot3PauseEntry 1 }

    dot3PauseOperMode OBJECT-TYPE
        SYNTAX      INTEGER {
                        disabled(1),
                        enabledXmit(2),
                        enabledRcv(3),
                        enabledXmitAndRcv(4)
                    }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "This object reflects the PAUSE mode currently

                    in use on this interface, as determined by
                    either (1) the result of the Auto-Negotiation
```

```
                     function or (2) if Auto-Negotiation is not
                     enabled or is not implemented for the active MAU
                     attached to this interface, by the value of
                     dot3PauseAdminMode. Interfaces operating at
                     100 Mb/s or less will never return
                     ‘enabledXmit(2)’ or ‘enabledRcv(3)’. Interfaces
                     operating in half-duplex mode will return
                     ‘disabled(1)’. Interfaces on which
                     Auto-Negotiation is enabled but not yet
                     completed should return the value
                     ‘disabled(1)’."
        ::= { dot3PauseEntry 2 }

    dot3InPauseFrames OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of MAC Control frames received on this
                     interface with an opcode indicating the PAUSE
                     operation.

                     This counter does not increment when the
                     interface is operating in half-duplex mode.

                     For interfaces operating at 10 Gb/s, this
                     counter can roll over in less than 5 minutes if
                     it is incrementing at its maximum rate. Since
                     that amount of time could be less than a
                     management station’s poll cycle time, in order
                     to avoid a loss of information, a management
                     station is advised to poll the
                     dot3HCInPauseFrames object for 10 Gb/s or
                     faster interfaces.

                     Discontinuities in the value of this counter can
                     occur at re-initialization of the management
                     system, and at other times as indicated by the
                     value of ifCounterDiscontinuityTime."
        REFERENCE   "IEEE Std 802.3, 30.3.4.3,
                     aPAUSEMACCtrlFramesReceived."
        ::= { dot3PauseEntry 3 }

    dot3OutPauseFrames OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current

        DESCRIPTION "A count of MAC Control frames transmitted on
                     this interface with an opcode indicating the
                     PAUSE operation.

                     This counter does not increment when the
                     interface is operating in half-duplex mode.

                     For interfaces operating at 10 Gb/s, this
                     counter can roll over in less than 5 minutes if
                     it is incrementing at its maximum rate. Since
                     that amount of time could be less than a
                     management station’s poll cycle time, in order
```

```
                        to avoid a loss of information, a management
                        station is advised to poll the
                        dot3HCOutPauseFrames object for 10 Gb/s or
                        faster interfaces.

                        Discontinuities in the value of this counter can
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.4.2,
                        aPAUSEMACCtrlFramesTransmitted."
            ::= { dot3PauseEntry 4 }

        dot3HCInPauseFrames OBJECT-TYPE
            SYNTAX      Counter64
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of MAC Control frames received on this
                        interface with an opcode indicating the PAUSE
                        operation.

                        This counter does not increment when the
                        interface is operating in half-duplex mode.

                        This counter is a 64-bit version of
                        dot3InPauseFrames. It should be used on
                        interfaces operating at 10 Gb/s or faster.

                        Discontinuities in the value of this counter can
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.4.3,
                        aPAUSEMACCtrlFramesReceived."
            ::= { dot3PauseEntry 5 }


        dot3HCOutPauseFrames OBJECT-TYPE
            SYNTAX      Counter64
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of MAC Control frames transmitted on
                        this interface with an opcode indicating the
                        PAUSE operation.

                        This counter does not increment when the
                        interface is operating in half-duplex mode.

                        This counter is a 64-bit version of
                        dot3OutPauseFrames. It should be used on
                        interfaces operating at 10 Gb/s or faster.

                        Discontinuities in the value of this counter can
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.4.2,
                        aPAUSEMACCtrlFramesTransmitted."
            ::= { dot3PauseEntry 6 }
```

```
        dot3HCStatsTable OBJECT-TYPE
            SYNTAX      SEQUENCE OF Dot3HCStatsEntry
            MAX-ACCESS  not-accessible
            STATUS      current
            DESCRIPTION "A table containing 64-bit versions of error
                        counters from the dot3StatsTable. The 32-bit
                        versions of these counters may roll over quite
                        quickly on higher speed Ethernet interfaces.
                        The counters that have 64-bit versions in this
                        table are the counters that apply to full-duplex
                        interfaces, since 10 Gb/s and faster
                        Ethernet-like interfaces do not support
                        half-duplex, and very few 1000 Mb/s
                        Ethernet-like interfaces support half-duplex.

                        Entries in this table are recommended for
                        interfaces capable of operating at 1000 Mb/s or
                        faster, and are required for interfaces capable
                        of operating at 10 Gb/s or faster. Lower speed
                        Ethernet-like interfaces do not need entries in
                        this table, in which case there may be fewer
                        entries in this table than in the
                        dot3StatsTable. However, implementations
                        containing interfaces with a mix of speeds may
                        choose to implement entries in this table for
                        all Ethernet-like interfaces."
            ::= { ieee8023etherMIBObjects 11 }

        dot3HCStatsEntry OBJECT-TYPE
            SYNTAX      Dot3HCStatsEntry
            MAX-ACCESS  not-accessible
            STATUS      current
            DESCRIPTION "An entry containing 64-bit statistics for a
                        single Ethernet-like interface."
            INDEX       { dot3StatsIndex }
            ::= { dot3HCStatsTable 1 }

        Dot3HCStatsEntry ::=
            SEQUENCE {
                dot3HCStatsAlignmentErrors           Counter64,
                dot3HCStatsFCSErrors                 Counter64,
                dot3HCStatsInternalMacTransmitErrors Counter64,
                dot3HCStatsFrameTooLongs             Counter64,
                dot3HCStatsInternalMacReceiveErrors  Counter64,
                dot3HCStatsSymbolErrors              Counter64,
                dot3HCStatsTransmitLPIMicroseconds   Counter64,
                dot3HCStatsReceiveLPIMicroseconds    Counter64,
                dot3HCStatsTransmitLPITransitions    Counter64,
                dot3HCStatsReceiveLPITransitions     Counter64
}

        dot3HCStatsAlignmentErrors OBJECT-TYPE
            SYNTAX      Counter64
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of frames received on a particular
                        interface that are not an integral number of
                        octets in length and do not pass the FCS check.
```

```
                 The count represented by an instance of this
                 object is incremented when the alignmentError
                 status is returned by the MAC service to the
                 LLC (or other MAC user). Received frames for
                 which multiple error conditions pertain are,
                 according to the conventions of IEEE 802.3
                 Layer Management, counted exclusively according
                 to the error status presented to the LLC.

                 This counter does not increment for group
                 encoding schemes greater than 4 bits per group.

                 This counter is a 64-bit version of
                 dot3StatsAlignmentErrors. It should be used
                 on interfaces operating at 10 Gb/s or faster.

                 Discontinuities in the value of this counter can
                 occur at re-initialization of the management

                 system, and at other times as indicated by the
                 value of ifCounterDiscontinuityTime."
    REFERENCE   "IEEE Std 802.3, 30.3.1.1.7,
                 aAlignmentErrors"
    ::= { dot3HCStatsEntry 1 }

dot3HCStatsFCSErrors OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A count of frames received on a particular
                 interface that are an integral number of octets
                 in length but do not pass the FCS check. This
                 count does not include frames received with
                 frame-too-long or frame-too-short error.

                 The count represented by an instance of this
                 object is incremented when the frameCheckError
                 status is returned by the MAC service to the
                 LLC (or other MAC user). Received frames for
                 which multiple error conditions pertain are,
                 according to the conventions of IEEE 802.3
                 Layer Management, counted exclusively according
                 to the error status presented to the LLC.

                 Note:  Coding errors detected by the Physical
                 Layer for speeds above 10 Mb/s will cause the
                 frame to fail the FCS check.

                 This counter is a 64-bit version of
                 dot3StatsFCSErrors. It should be used on
                 interfaces operating at 10 Gb/s or faster.

                 Discontinuities in the value of this counter can
                 occur at re-initialization of the management
                 system, and at other times as indicated by the
                 value of ifCounterDiscontinuityTime."
    REFERENCE   "IEEE Std 802.3, 30.3.1.1.6,
                 aFrameCheckSequenceErrors."
```

```
        ::= { dot3HCStatsEntry 2 }

    dot3HCStatsInternalMacTransmitErrors OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of frames for which transmission on a
                    particular interface fails due to an internal
                    MAC sublayer transmit error. A frame is only

                    counted by an instance of this object if it is
                    not counted by the corresponding instance of
                    either the dot3StatsLateCollisions object, the
                    dot3StatsExcessiveCollisions object, or the
                    dot3StatsCarrierSenseErrors object.

                    The precise meaning of the count represented by
                    an instance of this object is implementation-
                    specific. In particular, an instance of this
                    object may represent a count of transmission
                    errors on a particular interface that are not
                    otherwise counted.

                    This counter is a 64-bit version of
                    dot3StatsInternalMacTransmitErrors. It should
                    be used on interfaces operating at 10 Gb/s or
                    faster.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system, and at other times as indicated by the
                    value of ifCounterDiscontinuityTime."
        REFERENCE   "IEEE Std 802.3, 30.3.1.1.12,
                    aFramesLostDueToIntMACXmitError."
        ::= { dot3HCStatsEntry 3 }

    dot3HCStatsFrameTooLongs OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of frames received on a particular
                    interface that exceed the maximum permitted
                    frame size.

                    The count represented by an instance of this
                    object is incremented when the frameTooLong
                    status is returned by the MAC service to the
                    LLC (or other MAC user). Received frames for
                    which multiple error conditions pertain are,
                    according to the conventions of IEEE 802.3
                    Layer Management, counted exclusively according
                    to the error status presented to the LLC.

                    This counter is a 64-bit version of
                    dot3StatsFrameTooLongs. It should be used on
                    interfaces operating at 10 Gb/s or faster.

                    Discontinuities in the value of this counter can
```

```
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.1.1.25,
                        aFrameTooLongErrors."
            ::= { dot3HCStatsEntry 4 }

        dot3HCStatsInternalMacReceiveErrors OBJECT-TYPE
            SYNTAX      Counter64
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of frames for which reception on a
                        particular interface fails due to an internal
                        MAC sublayer receive error. A frame is only
                        counted by an instance of this object if it is
                        not counted by the corresponding instance of
                        either the dot3StatsFrameTooLongs object, the
                        dot3StatsAlignmentErrors object, or the
                        dot3StatsFCSErrors object.

                        The precise meaning of the count represented by
                        an instance of this object is implementation-
                        specific. In particular, an instance of this
                        object may represent a count of receive errors
                        on a particular interface that are not
                        otherwise counted.

                        This counter is a 64-bit version of
                        dot3StatsInternalMacReceiveErrors. It should be
                        used on interfaces operating at 10 Gb/s or
                        faster.

                        Discontinuities in the value of this counter can
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.1.1.15,
                        aFramesLostDueToIntMACRcvError."
            ::= { dot3HCStatsEntry 5 }

        dot3HCStatsSymbolErrors OBJECT-TYPE
            SYNTAX      Counter64
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "For an interface operating at 100 Mb/s, the
                        number of times there was an invalid data symbol
                        when a valid carrier was present.


                        For an interface operating in half-duplex mode
                        at 1000 Mb/s, the number of times the receiving
                        media is non-idle (a carrier event) for a period
                        of time equal to or greater than slotTime, and
                        during which there was at least one occurrence
                        of an event that causes the PHY to indicate
                        'Data reception error' or 'carrier extend error'
                        on the GMII.

                        For an interface operating in full-duplex mode
```

```
                 at 1000 Mb/s, the number of times the receiving
                 media is non-idle (a carrier event) for a period
                 of time equal to or greater than minFrameSize,
                 and during which there was at least one
                 occurrence of an event that causes the PHY to
                 indicate ‘Data reception error’ on the GMII.

                 For an interface operating at 10 Gb/s, 40 Gb/s and
                 100 Gb/s, the number of times the receiving media is
                 non-idle (a carrier event) for a period of time equal
                 to or greater than minFrameSize, and during which
                 there was at least one occurrence of an event
                 that causes the PHY to indicate ‘Receive Error’
                 on the XGMII, the XLGMII, or the CGMII.

                 The count represented by an instance of this
                 object is incremented at most once per carrier
                 event, even if multiple symbol errors occur
                 during the carrier event. This count does
                 not increment if a collision is present.

                 This counter is a 64-bit version of
                 dot3StatsSymbolErrors. It should be used on
                 interfaces operating at 10 Gb/s or faster.

                 Discontinuities in the value of this counter can
                 occur at re-initialization of the management
                 system, and at other times as indicated by the
                 value of ifCounterDiscontinuityTime."
    REFERENCE    "IEEE Std 802.3, 30.3.2.1.5,
                 aSymbolErrorDuringCarrier."
    ::= { dot3HCStatsEntry 6 }

    dot3HCStatsTransmitLPIMicroseconds   OBJECT-TYPE
    SYNTAX       Counter64
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION  "A count reflecting the amount of time that the
                 LPI_REQUEST parameter has the value ASSERT. The
                 request is indicated to the PHY according to the
                 requirements of the RS (see IEEE Std 802.3 22.7,
                 35.4, and 46.4).

                 This counter has a maximum increment rate of
                 1 000 000 counts per second."
    REFERENCE    "IEEE Std 802.3, 30.3.2.1.8 aTransmitLPIMicroseconds."
    ::= { dot3HCStatsEntry 7 }

    dot3HCStatsReceiveLPIMicroseconds   OBJECT-TYPE
    SYNTAX       Counter64
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION  "A count reflecting the amount of time that the
                 LPI_INDICATION parameter has the value ASSERT. The
                 indication reflects the state of the PHY according to
                 the requirements of the RS (see IEEE Std 802.3 22.7,
                 35.4, and 46.4).

                 This counter has a maximum increment rate of
```

```
                 1 000 000 counts per second."
    REFERENCE   "IEEE Std 802.3, 30.3.2.1.9 aReceiveLPIMicroseconds."
    ::= { dot3HCStatsEntry 8 }


    dot3HCStatsTransmitLPITransitions   OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A count of occurrences of the transition from
                  state LPI_DEASSERTED to state LPI_ASSERTED of
                  the LPI transmit state diagram is the RS.
                  The state transition corresponds to the assertion
                  of the LPI_REQUEST parameter. The request is indicated
                  to the PHY according to the requirements of the RS
                  (see IEEE Std 802.3 22.7, 35.4, 46.4.)

                  This counter has a maximum increment rate of 50 000
                  counts per second at 100 Mb/s; 90 000 counts per
                  second at 1000 Mb/s; and 230 000 counts per second
                  at 10 Gb/s."
    REFERENCE   "IEEE Std 802.3, 30.3.2.1.10 aTransmitLPITransitions."
    ::= { dot3HCStatsEntry 9 }

    dot3HCStatsReceiveLPITransitions   OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A count of occurrences of the transition from DEASSERT
                 to ASSERT of the LPI_INDICATE parameter. The
                 indication reflects the state of the PHY according to
                 the requirements of the RS
                 (see IEEE Std 802.3 22.7, 35.4, and 46.4).

                 This counter has a maximum increment rate of 50 000
                 counts per second at 100 Mb/s; 90 000 counts per second
                 at 1000 Mb/s; and 230 000 counts per second at 10 Gb/s."
    REFERENCE   "IEEE Std 802.3, 30.3.2.1.11 aReceiveLPITransitions."
    ::= { dot3HCStatsEntry 10 }

    dot3SlowProtocolFrameLimit OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION "The maximum number of Slow Protocol frames
                  of a given subtype that can be transmitted
                  in a one second interval. The default value
                  is 10."
    REFERENCE    "IEEE Std 802.3, 30.3.1.1.38,
                  aSlowProtocolFrameLimit."
    DEFVAL     { 10 }
    ::= { ieee8023etherMIBObjects 12 }

    dot3ExtensionTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Dot3ExtensionEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "A table of status information
                 about the Extension MAC Control frames transmitted
```

```
                        and received on the Ethernet-like interfaces attached
                        to a particular system. There will be one row in
                        this table for each Ethernet-like interface in
                        the system which supports Extension MAC Control
                        function (i.e., the 'mpcp' bit in the
                        corresponding instance of
                        dot3ControlFunctionsSupported is set). If some,
                        but not all, of the Ethernet-like interfaces in
                        the system implement the Extension MAC Control
                        function, there will be fewer rows
                        in this table than in the dot3StatsTable."
            ::= { ieee8023etherMIBObjects 13 }

        dot3ExtensionEntry OBJECT-TYPE
            SYNTAX      Dot3ExtensionEntry
            MAX-ACCESS  not-accessible
            STATUS      current
            DESCRIPTION "An entry in the table, containing information
                        about the Extension MAC Control function on a single
                        Ethernet-like interface."
            INDEX       { dot3StatsIndex }
            ::= { dot3ExtensionTable 1 }

        Dot3ExtensionEntry ::=

            SEQUENCE {
                dot3HCInExtensionFrames            Counter64,
                dot3HCOutExtensionFrames           Counter64,
                dot3ExtensionMacCtrlStatus         Unsigned32
            }

        dot3HCInExtensionFrames OBJECT-TYPE
            SYNTAX      Counter64
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of Extension MAC Control frames received on
                        this interface.

                        Discontinuities in the value of this counter can
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.8.2
                        aEXTENSIONMACCtrlFramesReceived."

            ::= { dot3ExtensionEntry 1 }

        dot3HCOutExtensionFrames OBJECT-TYPE
            SYNTAX      Counter64
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of Extension MAC Control frames transmitted on
                        this interface.

                        Discontinuities in the value of this counter can
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            REFERENCE   "IEEE Std 802.3, 30.3.8.1
```

```
                    aEXTENSIONMACCtrlFramesTransmitted."
        ::= { dot3ExtensionEntry 2 }

    dot3ExtensionMacCtrlStatus OBJECT-TYPE
        SYNTAX      Unsigned32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The current EXTENSIONMACCtrlStatus as described in
                     IEEE Std 802.3, 30.3.8.3."
        REFERENCE   "IEEE Std 802.3, 30.3.8.3, aEXTENSIONMACCtrlStatus."
        ::= { dot3ExtensionEntry 3 }

    dot3PFCTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF Dot3PFCEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "A table of descriptive and status information
                    about the MAC Control Priority-based Flow Control
                    function on the Ethernet-like interfaces attached to
                    a particular system. There will be one row in
                    this table for each Ethernet-like interface in
                    the system which supports the MAC Control PFC
                    function (i.e., the 'pfc' bit in the
                    corresponding instance of
                    dot3ControlFunctionsSupported is set). If some,
                    but not all, of the Ethernet-like interfaces in
                    the system implement the MAC Control PFC
                    function (for example, if some interfaces only
                    support half-duplex), there will be fewer rows
                    in this table than in the dot3StatsTable."
        ::= { ieee8023etherMIBObjects 14 }

    dot3PFCEntry OBJECT-TYPE
        SYNTAX      Dot3PFCEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "An entry in the table, containing information
                    about the MAC Control PFC function on a single
                    Ethernet-like interface."
        INDEX       { dot3StatsIndex }
        ::= { dot3PFCTable 1 }

    Dot3PFCEntry ::=

        SEQUENCE {
            dot3PFCAdminMode                INTEGER,
            dot3PFCOperMode                 INTEGER,
            dot3HCInPFCFrames               Counter64,
            dot3HCOutPFCFrames              Counter64
        }

    dot3PFCAdminMode OBJECT-TYPE
        SYNTAX      INTEGER {
                        disabled(1),
                        enabled(2)
                    }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION "This object is used to configure the default
```

```
                   administrative PFC mode for this interface.

                   This object represents the
                   administratively-configured PFC mode for this
                   interface. The value of this
                   object determines the operational PFC mode
                   of the interface. A set to this
                   object will force the interface into the
                   specified mode.

                   Note that the value of this object is ignored
                   when the interface is not operating in
                   full-duplex mode."
            ::= { dot3PFCEntry 1 }

        dot3PFCOperMode OBJECT-TYPE
            SYNTAX      INTEGER {
                            disabled(1),
                            enabled(2)
                        }
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "This object reflects the PFC mode currently
                        in use on this interface, as determined by
                        by the value of dot3PFCAdminMode."
            REFERENCE   "IEEE Std 802.3, 30.3.3.6 aPFCenableStatus"
            ::= { dot3PFCEntry 2 }

        dot3HCInPFCFrames OBJECT-TYPE
            SYNTAX      Counter64
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of MAC Control frames received on this
                        interface with an opcode indicating the PFC
                        operation.

                        Discontinuities in the value of this counter can
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."

            ::= { dot3PFCEntry 3 }


        dot3HCOutPFCFrames OBJECT-TYPE
            SYNTAX      Counter64
            MAX-ACCESS  read-only
            STATUS      current
            DESCRIPTION "A count of MAC Control frames transmitted on
                        this interface with an opcode indicating the
                        PFC operation.

                        Discontinuities in the value of this counter can
                        occur at re-initialization of the management
                        system, and at other times as indicated by the
                        value of ifCounterDiscontinuityTime."
            ::= { dot3PFCEntry 4 }
```

```
-- { ieee8023etherMIBObjects 6 }, the dot3ChipSets tree,
--   is defined in [RFC2666]

-- Conformance statements

etherConformance OBJECT IDENTIFIER ::= { ieee8023etherMIB 2 }

etherGroups      OBJECT IDENTIFIER ::= { etherConformance 1 }
etherCompliances OBJECT IDENTIFIER ::= { etherConformance 2 }

-- Compliance statements

    dot3Compliance2 MODULE-COMPLIANCE
        STATUS      current
        DESCRIPTION "The compliance statement for managed network
                    entities which have Ethernet-like network
                    interfaces.

                    Note that compliance with this MIB module
                    requires compliance with the ifCompliance3
                    MODULE-COMPLIANCE statement of the IF-MIB
                    (IETF RFC 2863). In addition, compliance with this
                    MIB module requires compliance  with the
                    mauModIfCompl3 MODULE-COMPLIANCE statement of
                    the MAU-MIB module defined in Clause 13."

    MODULE  -- this module
        MANDATORY-GROUPS { etherStatsBaseGroup2 }

        GROUP       etherDuplexGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces which are
                    capable of operating in full-duplex mode.
                    It is highly recommended for all
                    Ethernet-like network interfaces."

        GROUP       etherRateControlGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces which are
                    capable of operating at speeds faster than
                    1000 Mb/s. It is highly recommended for all
                    Ethernet-like network interfaces."

        GROUP       etherStatsLowSpeedGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces which are
                    capable of operating at 10 Mb/s or slower in
                    half-duplex mode."

        GROUP       etherStatsHighSpeedGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces which are
                    capable of operating at 100 Mb/s or faster."

        GROUP       etherStatsHalfDuplexGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces which are
                    capable of operating in half-duplex mode."
```

```
        GROUP       etherHCStatsGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces which are
                    capable of operating at 10 Gb/s or faster.
                    It is recommended for all Ethernet-like
                    network interfaces which are capable of
                    operating at 1000 Mb/s or faster."

        GROUP       etherControlGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces that
                    support the MAC Control sublayer."

        GROUP       etherHCControlGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces that
                    support the MAC Control sublayer and are
                    capable of operating at 10 Gb/s or faster."

        GROUP       etherControlPauseGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces that
                    support the MAC Control PAUSE function."

        GROUP       etherHCControlPauseGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces that
                    support the MAC Control PAUSE function and
                    are capable of operating at 10 Gb/s or
                    faster."

        GROUP       etherCollisionTableGroup
        DESCRIPTION "This group is optional. It is appropriate
                    for all Ethernet-like network interfaces
                    which are capable of operating in
                    half-duplex mode and have the necessary
                    metering. Implementation in systems with
                    such interfaces is highly recommended."

        GROUP       etherHCStatsLpiGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces that
                    support the Low Power Idle function."

        GROUP       etherSlowProtocolsGroup
        DESCRIPTION "This group is optional. It is appropriate for
                    Ethernet-like network interfaces that implement OAM
                    as defined in Clause 57 of IEEE Std 802.3."

        GROUP       etherExtensionMacCtrlGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces that implement
                    Extension MAC Control."

        GROUP       etherPfcGroup
        DESCRIPTION "This group is mandatory for all
                    Ethernet-like network interfaces that implement
                    Priority Flow Control."
```

```
            ::= { etherCompliances 1 }

        -- units of conformance

        etherCollisionTableGroup OBJECT-GROUP
            OBJECTS     { dot3CollFrequencies
                        }
            STATUS      current
            DESCRIPTION "A collection of objects providing a histogram
                        of packets successfully transmitted after
                        experiencing exactly N collisions."
            ::= { etherGroups 1 }

        etherStatsLowSpeedGroup OBJECT-GROUP
            OBJECTS     { dot3StatsSQETestErrors }
            STATUS      current
            DESCRIPTION "A collection of objects providing information
                        applicable to Ethernet-like network interfaces
                        capable of operating at 10 Mb/s or slower in
                        half-duplex mode."
            ::= { etherGroups 2 }

        etherStatsHighSpeedGroup OBJECT-GROUP
            OBJECTS     { dot3StatsSymbolErrors }
            STATUS      current
            DESCRIPTION "A collection of objects providing information
                        applicable to Ethernet-like network interfaces
                        capable of operating at 100 Mb/s or faster."
            ::= { etherGroups 3 }

        etherDuplexGroup OBJECT-GROUP
            OBJECTS     { dot3StatsDuplexStatus }
            STATUS      current
            DESCRIPTION "A collection of objects providing information
                        about the duplex mode of an Ethernet-like
                        network interface."
            ::= { etherGroups 4 }

        etherControlGroup OBJECT-GROUP
            OBJECTS     { dot3ControlFunctionsSupported,
                          dot3ControlInUnknownOpcodes
                        }
            STATUS      current
            DESCRIPTION "A collection of objects providing information
                        about the MAC Control sublayer on Ethernet-like
                        network interfaces."
            ::= { etherGroups 5 }

        etherControlPauseGroup OBJECT-GROUP
            OBJECTS     { dot3PauseAdminMode,
                          dot3PauseOperMode,
                          dot3InPauseFrames,
                          dot3OutPauseFrames
                        }
            STATUS      current
            DESCRIPTION "A collection of objects providing information
                        about and control of the MAC Control PAUSE
                        function on Ethernet-like network interfaces."
            ::= { etherGroups 6 }
```

```
etherStatsBaseGroup2 OBJECT-GROUP
    OBJECTS     { dot3StatsAlignmentErrors,
                  dot3StatsFCSErrors,
                  dot3StatsInternalMacTransmitErrors,
                  dot3StatsFrameTooLongs,
                  dot3StatsInternalMacReceiveErrors,
                  dot3StatsMaxFrameLength
                }
    STATUS      current
    DESCRIPTION "A collection of objects providing information
                applicable to all Ethernet-like network
                interfaces."
    ::= { etherGroups 7 }

etherStatsHalfDuplexGroup OBJECT-GROUP
    OBJECTS     { dot3StatsSingleCollisionFrames,
                  dot3StatsMultipleCollisionFrames,
                  dot3StatsDeferredTransmissions,
                  dot3StatsLateCollisions,
                  dot3StatsExcessiveCollisions,
                  dot3StatsCarrierSenseErrors
                }
    STATUS      current
    DESCRIPTION "A collection of objects providing information
                applicable only to half-duplex Ethernet-like
                network interfaces."
    ::= { etherGroups 8 }

etherHCStatsGroup OBJECT-GROUP
    OBJECTS     { dot3HCStatsAlignmentErrors,
                  dot3HCStatsFCSErrors,
                  dot3HCStatsInternalMacTransmitErrors,
                  dot3HCStatsFrameTooLongs,
                  dot3HCStatsInternalMacReceiveErrors,
                  dot3HCStatsSymbolErrors
                }
    STATUS      current
    DESCRIPTION "A collection of objects providing high-capacity
                statistics applicable to higher-speed
                Ethernet-like network interfaces."
    ::= { etherGroups 9 }

etherHCControlGroup OBJECT-GROUP
    OBJECTS     { dot3HCControlInUnknownOpcodes }
    STATUS      current
    DESCRIPTION "A collection of objects providing high-capacity
                statistics for the MAC Control sublayer on
                higher-speed Ethernet-like network interfaces."
    ::= { etherGroups 10 }

etherHCControlPauseGroup OBJECT-GROUP
    OBJECTS     { dot3HCInPauseFrames,
                  dot3HCOutPauseFrames


                }
    STATUS      current
    DESCRIPTION "A collection of objects providing high-capacity
                statistics for the MAC Control PAUSE function on
```

```
                        higher-speed Ethernet-like network interfaces."
            ::= { etherGroups 11 }

        etherRateControlGroup OBJECT-GROUP
            OBJECTS     { dot3StatsRateControlAbility,
                          dot3StatsRateControlStatus
                        }
            STATUS      current
            DESCRIPTION "A collection of objects providing information
                        about the Rate Control function on Ethernet-like
                        interfaces."
            ::= { etherGroups 12 }

        etherHCStatsLpiGroup OBJECT-GROUP
             OBJECTS    { dot3HCStatsTransmitLPIMicroseconds,
                          dot3HCStatsReceiveLPIMicroseconds,
                          dot3HCStatsTransmitLPITransitions,
                          dot3HCStatsReceiveLPITransitions
                        }
             STATUS     current
             DESCRIPTION "A collection of objects providing information
                        about the Low Power Idle function on Ethernet-like
                        interfaces."
            ::= { etherGroups 13 }


        etherSlowProtocolsGroup OBJECT-GROUP
             OBJECTS      { dot3SlowProtocolFrameLimit }
             STATUS       current
             DESCRIPTION  "An object providing control and information
                           about the frame transmission rate limit for
                           Slow Protocols on Ethernet-like interfaces."
             ::= { etherGroups 14 }

        etherExtensionMacCtrlGroup OBJECT-GROUP
             OBJECTS      { dot3HCInExtensionFrames,
                            dot3HCOutExtensionFrames,
                            dot3ExtensionMacCtrlStatus
                          }
             STATUS       current
             DESCRIPTION  "A collection of objects providing information
                           about the Extension MAC Control function on
                           Ethernet-like interfaces."
             ::= { etherGroups 15 }

         etherPfcGroup OBJECT-GROUP
              OBJECTS     { dot3PFCAdminMode,
                            dot3PFCOperMode,
                            dot3HCInPFCFrames,
                            dot3HCOutPFCFrames
                          }
              STATUS       current
              DESCRIPTION  "A collection of objects providing information
                           about the Priority Flow Control function on
                           Ethernet-like interfaces."
              ::= { etherGroups 16 }


    END
```

11. Ethernet in the First Mile copper (EFMCu) interfaces MIB module

11.1 Introduction

Ethernet-like interfaces have been defined in IEEE Std 802.3 known as Ethernet in the First Mile (EFM). In particular, 2BASE-TL and 10PASS-TS physical interfaces (PHYs), defined over voice-grade copper pairs, have been specified for the long and short reach, respectively. These interfaces, collectively called EFM Copper (EFMCu), are based on single-pair high-speed digital subscriber line (SHDSL; see ITU-T G.991.2) and very high-speed digital subscriber line (VDSL; see ITU-T G.993.1) technology, supporting optional physical medium entity (PME) aggregation (a.k.a. multi-pair bonding) with variable rates.

The 2BASE-TL PHY is capable of providing at least 2 Mb/s over a 2700 m long single copper pair with a mean bit error ratio (BER) of 10^{-7} (using 5 dB target noise margin).

The 10PASS-TS PHY is capable of providing at least 10 Mb/s over a 750 m long single copper pair with a mean BER of 10^{-7} (using 6 dB target noise margin). This clause defines a MIB module for use with SNMP to manage EFMCu interfaces. In addition, a MIB module is defined describing the cross-connect capability of a stacked interface.

11.2 Relation to other MIB modules

This subclause outlines the relationship of the MIB modules defined in this clause with other MIB modules described in other clauses of this standard, or the relevant RFCs. Specifically, the Interfaces Group MIB (IF-MIB), Ethernet-Like (IEEE8023-EtherLike-MIB), MAU (MAU-MIB), SHDSL (HDSL2-SHDSL-LINE-MIB), and VDSL (VDSL-LINE-EXT-MCM-MIB) modules are discussed.

11.2.1 Relation to Interfaces Group MIB module

2BASE-TL and 10PASS-TS PHYs specified in the EFM-CU-MIB module are stacked (a.k.a. aggregated or bonded) Ethernet interfaces and as such are managed using generic interface management objects defined in the IF-MIB defined in IETF RFC 2863.

The stack management (i.e., actual connection of the sublayers to the top-layer interface) is done via the ifStackTable, as defined in the IF-MIB defined in IETF RFC 2863, and its inverse ifInvStackTable, as defined in the IF-INVERTED-STACK-MIB defined in IETF RFC 2864.

The table ifCapStackTable and its inverse ifInvCapStackTable are defined in the IF-CAP-STACK-MIB module. These tables extend the stack management with an ability to describe possible connections or cross-connect capability, when a flexible cross-connect matrix is present between the interface layers. The IF-CAP-STACK-MIB module definition (Beili [B1]) can be found in:

https://datatracker.ietf.org/doc/draft-ietf-opsawg-rfc5066bis/

11.2.1.1 Layering model

An EFMCu interface can aggregate up to 32 physical medium entity (PME) sublayer devices (modems), using the so-called PME aggregation function (PAF).

A generic EFMCu device can have a number of physical coding sublayer (PCS) ports, each connected to a media access controller (MAC) via a media independent interface (MII) at the upper layer, and cross-connected to a number of underlying PMEs, with a single PCS per PME relationship. See 61.1 of IEEE Std 802.3 for more details.

Each PME in the aggregated EFMCu port is represented in the Interface table (ifTable) as a separate interface with ifType of shdsl(169) for 2BASE-TL or vdsl(97) for 10PASS-TS. The ifType values are defined in [IANAifType-MIB].

The ifSpeed for each PME shall return the actual data bitrate of the active PME (e.g., for 2BaseTL PMEs, it is a multiple of 64 kb/s). A zero value shall be returned when the PME is Initializing or Down.

The ifSpeed of the PCS is the sum of the current operating data rates of all PMEs in the aggregation group, without the 64/65-octet encapsulation overhead and PAF overhead, but accounting for the inter-frame gaps (IFGs).

When using the stated definition of ifSpeed for the PCS, there would be no frame loss in the configuration shown in Figure 11-1 (the test-sets are configured to generate 100% of back-to-back traffic, i.e., minimal IFG, at 10 Mb/s or 100 Mb/s, with min and max frame sizes; the EFM interfaces are aggregated to achieve the shown speed).



Figure 11-1—Example configuration with no frame loss

Figure 11-2 shows the IEEE 802.3 layering diagram and corresponding use of ifTable and ifMauTable.



MAC = Media Access Control
PCS = Physical Coding Sublayer
TC = Transmission Convergence
PMA = Physical Medium Attachment
PMD = Physical Medium Dependent
PME = Physical Medium Entity

Figure 11-2—Use of ifTable and ifMauTable for EFMCu ports

The ifStackTable is indexed by the ifIndex values of the aggregated EFMCu port (PCS) and the PMEs connected to it. The ifStackTable allows a Network Management application to determine which PMEs are connected to a particular PCS and change connections (if supported by the application). The ifInvStackTable, being an inverted version of the ifStackTable, provides an efficient means for a Network Management application to read a subset of the ifStackTable and thereby determine which PCS runs on top of a particular PME.

The ifCapStackTable, defined in the IF-CAP-STACK-MIB module, specifies for each higher layer interface (e.g., PCS port) a list of lower layer interfaces (e.g., PMEs), which can possibly be cross-connected to that higher layer interface, determined by the cross-connect capability of the device. This table, modeled after the ifStackTable, is read-only, reflecting the current cross-connect capability of the stacked interface, which can be dynamic in some implementations (e.g., if PMEs are located on a pluggable module and the module is pulled out). Note that PME availability per PCS, described by the ifCapStackTable, can be constrained by other parameters, for example, by the aggregation capacity of a PCS or by the PME in question being already connected to another PCS. So that a particular PME can be connected to the PCS, all respective parameters (e.g., ifCapStackTable, ifStackTable, and efmCuPAFCapacity) shall be inspected.

The ifInvCapStackTable, also defined in the IF-CAP-STACK-MIB module, describes which higher layer interfaces (e.g., PCS ports) can possibly be connected to a particular lower layer interface (e.g., PME), providing an inverted mapping of the ifCapStackTable. While it contains no additional information beyond that already contained in the ifCapStackTable, the ifInvCapStackTable has the ifIndex values in its INDEX clause in the reverse order, i.e., the lower layer interface first, and the higher layer interface second, providing an efficient means for a Network Management application to read a subset of the ifCapStackTable and thereby determine which interfaces can be connected to run on top of a particular interface.

11.2.1.2 PME aggregation function (PAF)

The PME aggregation function (PAF) allows a number of PMEs to be aggregated onto a PCS port, by fragmenting the Ethernet frames, transmitting the fragments over multiple PMEs, and assembling the original frames at the remote port. PAF is optional, meaning that a device with a single PME may perform fragmentation and reassembly if this function is supported by the device. Note that the agent is required to report on the PAF capability for all EFMCu ports (2BASE-TL and 10PASS-TS).

The EFM-CU-MIB module allows a network management application to query the PAF capability and enable/disable it if supported. Note that enabling PAF effectively turns on fragmentation and reassembly, even on a single-PME port.

11.2.1.3 Discovery operation

The EFMCu ports may optionally support discovery operation, whereby PMEs, during initialization, exchange information about their respective aggregation groups (PCS). This information can then be used to detect copper misconnections or for an automatic assignment of the local PMEs into aggregation groups instead of a fixed pre-configuration.

The MIB modules defined in this clause allow a network management application to control the EFM discovery mechanism and query its results. Note that the discovery mechanism can work only if PAF is supported and enabled.

Two tables are used by the EFM discovery mechanism: ifStackTable and ifCapStackTable. The following pseudo-code gives an example of the discovery and automatic PME assignment for a generic PAF-enabled multi-PCS EFMCu device, located at central office (CO), using objects defined in these MIB modules and in the IF-MIB. (Note that automatic PME assignment is only shown here for the purposes of the example. Fixed PME pre-assignment, manual assignment, or auto-assignment using an alternative internal algorithm may be chosen by a particular implementation.)

```
// Go over all PCS ports in the CO device
FOREACH pcs[i] IN CO_device
{ // Perform discovery and auto-assignment only on PAF enabled ports
  // with room for more PMEs
  IF ( pcs[i].PAFSupported AND pcs[i].NumPMEs &lt; pcs[i].PAFCapacity )
  { // Assign a unique 6-octet local discovery code to the PCS
    // e.g., MAC address
    dc = pcs[i].DiscoveryCode = MAC[i];
    // Go over all disconnected PMEs, which can
    // potentially be connected to the PCS
    FOREACH pme[j] IN ifCapStackTable[pcs[i]] AND
                   NOT IN ifStackTable[pcs[i]]  // not connected
    { // Try to grab the remote RT_device, by writing the value
      // of the local 6-octet discovery code to the remote
      // discovery code register (via handshake mechanism).
      // This operation is atomic Set-if-Clear action, i.e., it
      // would succeed only if the remote discovery register was
      // zero. Read the remote discovery code register via Get
      // operation to see if the RT_device, attached via the PME
      // is indeed marked as being the CO_device peer.
      pme[j].RemoteDiscoveryCode = dc;          // Set-if-Clear
      r = pme[j].RemoteDiscoveryCode;           // Get
      IF ( r == dc AND pcs[i].NumPMEs &lt; pcs[i].PAFCapacity)
      { // Remote RT_device connected via PME[j] is/was a peer
```

```
         // for PCS[i] and there is room for another PME in the
         // PCS[i] aggregation group (max. PAF capacity is not
         // reached yet).
         // Connect this PME to the PCS (via ifStackTable,
         // ifInvStackTable being inverse of ifStackTable is
         // updated automatically, i.e., pcs[i] is auto-added
         // to ifInvStackTable[pme[j]])
         ADD pme[j] TO ifStackTable[pcs[i]];
         pcs[i].NumPMEs = pcs[i].NumPMEs + 1;
         // Discover all other disconnected PMEs,
         // attached to the same RT_device and connect them to
         // the PCS provided there is enough room for more PMEs.
         FOREACH pme[k] IN ifCapStackTable[pcs[i]] AND
                        NOT IN ifStackTable[pcs[i]]
{ // Get Remote Discovery Code from the PME to see if
           // it belongs to a connected RT_device "grabbed" by
           // the CO_device.
           r = pme[k].RemoteDiscoveryCode;
           IF ( r == dc AND pcs[i].NumPMEs &lt; pcs[i].PAFCapacity)
           { // Physically connect the PME to the PCS
             // (pcs[i] is auto-added TO ifInvStackTable[pme[k]])
             ADD pme[k] TO ifStackTable[pcs[i]];
             pcs[i].NumPMEs = pcs[i].NumPMEs + 1;
           }
         }
       }
       // At this point we have discovered all local PMEs which
       // are physically connected to the same remote RT_device
       // and connected them to PCS[i]. Go to the next PCS.
       BREAK;
     }
   }
 }
```

An SNMP Agent for an EFMCu device builds the ifCapStackTable and its inverse ifInvCapStackTable according to the information contained in the Clause 45 PME_Available_register (see 61.1.5.3 and 45.2.3.27 of IEEE Std 802.3).

Adding a PME to the ifStackTable row for a specific PCS involves actual connection of the PME to the PCS, which can be done by modifying the Clause 45 PME_Aggregate_register (see 61.1.5.3 and 45.2.3.28 of IEEE Std 802.3).

Note that the PCS port does not have to be operationally “down” for the connection to succeed. In fact, a dynamic PME addition (and removal) may be implemented with an available PME being initialized first (by setting its ifAdminStatus to “up”) and then added to an operationally “up” PCS port, by modifying a respective ifStackTable (and respective ifInvStackTable) entry.

It is recommended that a removal of the last operationally “up” PME from an operationally “up” PCS would be rejected by the implementation, as this action would completely drop the link.

11.2.1.4 EFMCu ports initialization

EFMCu ports being built on top of xDSL technology require a lengthy initialization or “training” process, before any data can pass. During this initialization, both ends of a link (peers) work cooperatively to achieve the required data rate on a particular copper pair. Sometimes, when the copper line is too long or the noise on the line is too high, that "training" process may fail to achieve a specific target rate with required characteristics.

The ifAdminStatus object from the IF-MIB controls the desired state of a PCS with all the PMEs connected to it or of an individual PME port. Setting this object to "up" instructs a particular PCS or PME to start the initialization process, which may take tens of seconds for EFMCu ports, especially if PAF is involved. The ifOperStatus object shows the operational state of an interface (extended by the ifMauMediaAvailable object from the MAU-MIB module for PCS and efmCuPmeOperStatus defined in the EFM-CU-MIB module for PME interfaces).

A disconnected PME may be initialized by changing the ifAdminState from "down" to "up." Changing the ifAdminState to "up" on the PCS initializes all PMEs connected to that particular PCS. Note that in case of PAF, some interfaces may fail to initialize while others succeed. The PCS is considered operationally "up" if at least one PME aggregated by its PAF is operationally "up." When all PMEs connected to the PCS are "down," the PCS shall be considered operationally "lowerLayerDown." The PCS shall be considered operationally "notPresent" if it is not connected to any PME. The PCS/PME interface shall remain operationally "down" during initialization.

The efmCuPmeOperStatus defined in the EFM-CU-MIB module expands PME's ifOperStatus value of "down" to "downReady," "downNotReady," and "init" values, indicating various EFMCu PME-specific states.

11.2.1.5 Usage of ifTable

Both the PME and PCS interfaces of the EFMCu PHY are managed using interface-specific management objects defined in the EFM-CU-MIB module and generic interface objects from the ifTable of IF-MIB, with all management table entries referenced by the interface index ifIndex.

Table 11-1 summarizes EFMCu-specific interpretations for some of the ifTable objects specified in the mandatory ifGeneralInformationGroup.

Table 11-1—EFMCu interpretation of IF-MIB objects

IF-MIB object	EFMCu interpretation
ifIndex	Interface index. Each PME and each PCS in the EFMCu PHY shall have a unique index, as there are some PCS- and PME-specific attributes accessible only on the PCS or the PME level.
ifType	ethernetCsmacd(6) for PCS, shdsl(169) for 2BASE-TL PME, vdsl(97) for 10PASS-TS PME. Operating data rate for the PME. For the PCS, it is the sum of the current operating data rates of all PMEs in the aggregation group, without the 64/65-octet encapsulation overhead and PAF overhead, but accounting for the Inter-Frame Gaps (IFGs).
ifSpeed	Setting this object to "up" instructs a particular PCS (with all PMEs connected to it) or PME to start the initialization process.
ifAdminStatus	Setting this object to "up" instructs a particular PCS (with all PMEs connected to it) or PME to start the initialization process.
ifOperStatus	efmCuPmeOperStatus supplements the "down" value of ifOperStatus for PMEs.

11.2.2 Relation to SHDSL MIB module

G.SHDSL.bis modems, similar to PMEs comprising a 2BASE-TL port, are described in the HDSL2-SHDSL-LINE-MIB module defined in IETF RFC 4319 [B34]. Note that not all attributes of G.SHDSL modems reflected in the HDSL2-SHDSL-LINE-MIB module have adequate management objects (Clause 30 attributes and Clause 45 registers) in IEEE Std 802.3.

Because of these differences and for the purposes of simplicity, unification of attributes common to both 2BASE-TL and 10PASS-TS PMEs, and name consistency (e.g., prefixing the 2BASE-TL PME related objects with “efmCuPme2B” instead of “hdsl2shdsl”), it was decided not to reference HDSL2-SHDSL-LINE-MIB objects but to define all the relevant objects in the EFM-CU-MIB module.

However, if some functionality not available in the EFM-CU-MIB module is required and supported by the PME, e.g., performance monitoring, relevant HDSL2-SHDSL-LINE-MIB groups may be included and applied for PMEs of 2BASE-TL subtype.

11.2.3 Relation to VDSL MIB module

VDSL modems, similar to the PME(s) comprising a 10PASS-TS port, are described in the VDSL-LINE-EXT-MCM-MIB module defined in IETF RFC 4070 [B31]. Note that not all attributes of VDSL modems reflected in the VDSL-LINE-EXT-MCM-MIB module have adequate management objects (Clause 30 attributes and Clause 45 registers) in IEEE Std 802.3.

Because of these differences and for the purposes of simplicity, unification of attributes common to both 2BASE-TL and 10PASS-TS PMEs, and name consistency, it was decided not to reference VDSL-LINE-EXT-MCM-MIB objects but to define all the relevant objects in the EFM-CU-MIB module.

However, if some functionality not available in the EFM-CU-MIB module is required and supported by the PME, relevant VDSL-LINE-EXT-MCM-MIB groups may be included and applied for PMEs of 10PASS-TS subtype.

11.2.4 Relation to Ethernet-Like and MAU MIB modules

An agent implementing the objects defined in this clause shall also implement the objects required by the Ethernet-like interface MIB module defined in Clause 10 and the objects required by the MAU MIB module defined in Clause 13.

Two new values of ifMauType (OBJECT-IDENTITIES of dot3MauType) and corresponding bit definitions of ifMauTypeListBits (IANAifMauTypeListBits) have been defined in the IANA-MAU-MIB module for EFMCu MAUs:

— dot3MauType2BaseTL and b2BaseTL, for 2BASE-TL MAU
— dot3MauType10PassTS and b10PassTS, for 10PASS-TS MAU

Additionally, the IANA-MAU-MIB module defines two new values of ifMauMediaAvailable, specifically for EFMCu ports: availableReduced and ready (in textual convention IANAifMauMediaAvailable). Due to the PME aggregation, the EFMCu interpretation of some possible ifMauMediaAvailable values differs from other MAUs as follows:

— unknown: the EFMCu interface (PCS with connected PMEs) is Initializing
— ready: the interface is Down, at least one PME in the aggregation group (all PMEs connected to the PCS) is ready for handshake
— available: the interface is Up, all PMEs in the aggregation group are up

— notAvailable: the interface is Down, all PMEs in the aggregation group are Down, no handshake tones are detected by any PME
— availableReduced: the interface is Up, a link fault is detected at the receive direction by one or more PMEs in the aggregation group, but at least one PME is Up
— pmdLinkFault: a link fault is detected at the receive direction by all PMEs in the aggregation group

As an Ethernet-like interface, every EFMCu port [an ifEntry representing a consolidation of LLC, MAC, and PCS (sub)layers] shall return an ifType of ethernetCsmacd(6). While most of the MAU characteristics are not applicable to the EFMCu ports (no Auto-Negotiation, false carriers, or jabber), they shall return an appropriate ifMauType (dot3MauType2BaseTL or dot3mauType10PassTS) in order to direct the management software to look in the EFM-CU-MIB module for the desired information. For example, the information on the particular EFMCu flavor that an EFMCu port is running is available from efmCuOperSubType, defined in the EFM-CU-MIB module.

Since EFMCu PMEs are not Ethernet-like interfaces, they cannot be instantiated as MAU interface objects.

11.3 MIB structure

11.3.1 EFM copper MIB overview

The main management objects defined in the EFM-CU-MIB module are split into two groups:

— efmCuPort—containing objects for configuration, capabilities, status, and notifications, common to all EFMCu PHYs.
— efmCuPme—containing objects for configuration, capabilities, status, and notifications of EFMCu PMEs.

The efmCuPme group in turn contains efmCuPme2B and efmCuPme10P groups, which define PME profiles specific to 2BASE-TL and 10PASS-TS PMEs, respectively, as well as PME-specific status information.

11.3.2 PME profiles

Since a managed node can have a large number of EFMCu PHYs, provisioning every parameter on every EFMCu PHY may become burdensome. Moreover, most PMEs are provisioned identically with the same set of parameters. To simplify the provisioning process, the EFM-CU-MIB module makes use of configuration profiles, similar to the HDSL2-SHDSL-LINE-MIB and VDSL-LINE-EXT-MCM-MIB modules. A profile is a set of parameters, used for either configuration or representation of a PME. The same profile can be shared by multiple PME ports using the same configuration.

The PME profiles are defined in the efmCuPme2BProfileTable and efmCuPme10PProfileTable for 2BASE-TL and 10PASS-TS PMEs, respectively. There are 12 predefined standard profiles for 2BASE-TL and 22 standard profiles for 10PASS-TS, defined in IEEE Std 802.3 and dedicated for rapid provisioning of EFMCu PHYs in most scenarios. In addition, the EFM-CU-MIB defines two additional predefined profiles for “best-effort” provisioning of 2BASE-TL PMEs. An ability to define new configuration profiles is also provided to allow for EFMCu deployment tailored to specific copper environments and spectral regulations.

A specific configuration or administrative profile is assigned to a specific PME via the efmCuPmeAdminProfile object. If efmCuPmeAdminProfile is zero, then the efmCuAdminProfile object of the PCS port connected to the PME determines the configuration profile (or a list of possible profiles) for that PME. This mechanism allows specifying a common profile for all PMEs connected to the PCS port, with an ability to change individual PME profiles by setting the efmCuPmeAdminProfile object, which overwrites the profile set by efmCuAdminProfile.

A current operating PME profile is pointed to by the efmCuPmeOperProfile object. Note that this profile entry can be created automatically to reflect achieved parameters in adaptive (not fixed) initialization.

11.3.3 Mapping of IEEE 802.3 managed objects

This subclause contains the mapping between relevant managed objects (attributes) defined in Clause 30 of IEEE Std 802.3, and managed objects defined in this clause and in associated MIB modules, i.e., the IF-MIB defined in IETF RFC 2863. Note that the majority of the objects defined in the EFM-CU-MIB module do not have direct counterparts in Clause 30 and instead refer to Clause 45 registers.

Table 11-2—Mapping of IEEE 802.3 managed objects

IEEE 802.3 managed object		Corresponding SNMP object
oMAU - Basic Package (Mandatory)	aMAUType	ifMauType (MAU-MIB)
	aMAUTypeList	ifMauTypeListBits (MAU-MIB)
	aMediaAvailable	ifMediaAvailable (MAU-MIB)
oPAF - Basic Package (Mandatory)	aPAFID	ifIndex (IF-MIB)
	aPhyEnd	efmCuPhySide
	aPHYCurrentStatus	efmCuStatus
	aPAFSupported	efmCuPAFSupported
oPAF - PME Aggregation Package (Optional)	aPAFAdminState	efmCuPAFAdminState
	aLocalPAFCapacity	efmCuPAFCapacity
	aLocalPMEAvailable	ifCapStackTable (IF-CAP-STACK-MIB)
	aLocalPMEAggregate	ifStackTable (IF-MIB)
	aRemotePAFSupported	efmCuRemotePAFSupported
	aRemotePAFCapacity	efmCuRemotePAFCapacity
	aRemotePMEAggregate	
oPME - 10P/2B Package (Mandatory)	aPMEID	ifIndex (IF-MIB)
	aPMEAdminState aPMEStatus	ifAdminState (IF-MIB) efmCuPmeStatus
	aPMESNRMgn	efmCuPmeSnrMgn
	aTCCodingViolations	efmCuPmeTCCodingErrors
	aTCCRCErrors	efmCuPmeTCCrcErrors
	aProfileSelect	efmCuAdminProfile, efmCuPmeAdminProfile
	aOperatingProfile	efmCuPmeOperProfile
	aPMEFECCorrectedBlocks	efmCuPme10PFECCorrectedBlocks
	aPMEFECUncorrectableBlocks	efmCuPme10PFECUncorrectedBlocks

11.4 Security considerations for Ethernet in the First Mile copper interfaces MIB module

There are a number of managed objects defined in the EFM-CU-MIB module that have a MAX-ACCESS clause of read-write or read-create. Most objects are writeable only when the link is Down. Writing to these objects can have potentially disruptive effects on network operation, for example:

— Changing of efmCuPmeAdminSubType may lead to a potential locking of the link, as peer PMEs of the same subtype cannot exchange handshake messages.

— Changing of efmCuPAFAdminState to enabled may lead to a potential locking of the link, if the peer PHY does not support PAF.

— Changing of efmCuPAFDiscoveryCode, before the discovery operation, may lead to a wrongful discovery, for example, when two -O ports are connected to the same multi-PME -R port and both -O ports have the same Discovery register value.

— Changing PCS or PME configuration parameters (e.g., profile of a PCS or PME via efmCuAdminProfile or efmCuPmeAdminProfile) may lead to anything from link quality and rate degradation to a complete link initialization failure, as the ability of an EFMCu port to support a particular configuration depends on the copper environment.

— Activation of a PME can cause a severe degradation of service for another EFMCu PHY, whose PME(s) may be affected by the crosstalk from the newly activated PME.

— Removal of a PME from an operationally “up” EFMCu port, aggregating several PMEs, may cause the port’s rate degradation.

The user of the EFM-CU-MIB module should therefore be aware that support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

The readable objects in the EFM-CU-MIB module (i.e., those with MAX-ACCESS other than not-accessible) may be considered sensitive in some environments since, collectively, they provide information about the performance of network interfaces and can reveal some aspects of their configuration. In particular, since EFMCu can be carried over Unshielded Twisted Pair (UTP) voice-grade copper in a bundle with other pairs belonging to another operator/customer, it is theoretically possible to eavesdrop to an EFMCu transmission simply by “listening” to a crosstalk from the EFMCu pairs, especially if the parameters of the EFMCu link in question are known.

In such environments, it is important to control also GET and NOTIFY access to these objects and possibly to encrypt their values when sending them over the network via SNMP.

11.5 MIB module definition

An ASCII text version of the MIB definition can be found at the following URL[19]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C11mib.txt

[19]Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.

```
IEEE8023-EFM-CU-MIB DEFINITIONS ::= BEGIN

  IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE, Integer32,
    Unsigned32, Counter32, org
      FROM SNMPv2-SMI         -- [RFC2578]
    TEXTUAL-CONVENTION, TruthValue, RowStatus, PhysAddress
      FROM SNMPv2-TC          -- [RFC2579]
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
      FROM SNMPv2-CONF        -- [RFC2580]
    SnmpAdminString
      FROM SNMP-FRAMEWORK-MIB -- [RFC3411]
    ifIndex, ifSpeed
      FROM IF-MIB             -- [RFC2863]
    ;

  ieee8023efmCuMIB MODULE-IDENTITY
     LAST-UPDATED "201304110000Z" -- April 11, 2013
     ORGANIZATION
       "IEEE 802.3 working group"
     CONTACT-INFO
         "WG-URL: http://www.ieee802.org/3/index.html
         WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

         Contact: Howard Frazier
         Postal:  3151 Zanker Road
                  San Jose, CA 95134
                  USA
         Tel:     +1.408.922.8164
         E-mail:  hfrazier@broadcom.com"

    DESCRIPTION
      "The objects in this MIB module are used to manage
      the Ethernet in the First Mile (EFM) Copper (EFMCu) Interfaces
      2BASE-TL and 10PASS-TS, defined in IEEE Std 802.3.

      Of particular interest are Clause 61, ‘Physical Coding
      Sublayer (PCS) and common specifications, type 10PASS-TS and
      type 2BASE-TL’, Clause 30, ‘Management’, Clause 45,
      ‘Management Data Input/Output (MDIO) Interface’, Annex 62A,
      ‘PMD profiles for 10PASS-TS’ and Annex 63A, ‘PMD profiles for
      2BASE-TL’."

    REVISION    "201304110000Z" -- April 11, 2013
    DESCRIPTION
          "Revision, based on an earlier version in IEEE Std 802.3.1-2011."

    REVISION    "201102020000Z" -- February 2, 2011
    DESCRIPTION
          "Initial version, based on an earlier version published
           as RFC 5066."

         ::= { org ieee(111) standards-association-numbers-series-standards(2)
               lan-man-stds(802) ieee802dot3(3) ieee802dot3dot1mibs(1)
               ieee8023efmcu(11) 2 }


   -- Sections of the module
```

```
efmCuObjects     OBJECT IDENTIFIER ::= { ieee8023efmCuMIB 1 }

efmCuConformance OBJECT IDENTIFIER ::= { ieee8023efmCuMIB 2 }

-- Groups in the module

efmCuPort        OBJECT IDENTIFIER ::= { efmCuObjects 1 }

efmCuPme         OBJECT IDENTIFIER ::= { efmCuObjects 2 }

-- Textual Conventions

EfmProfileIndex ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d"
  STATUS       current
  DESCRIPTION
    "A unique value, greater than zero, for each PME configuration
     profile in the managed EFMCu port. Values should be assigned
     contiguously starting from 1. The value for each profile shall
     remain constant at least from one re-initialization of the
     entity’s network management system to the next re-initialization."
  SYNTAX       Unsigned32 (1..255)

EfmProfileIndexOrZero ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d"
  STATUS       current
  DESCRIPTION
    "This textual convention is an extension of the
    EfmProfileIndex convention. The latter defines a greater than
    zero value used to identify a PME profile in the managed EFMCu
    port. This extension permits the additional value of zero.
    The value of zero is object-specific and shall therefore be
    defined as part of the description of any object that uses
    this syntax.
    Examples of the usage of zero value might include situations
    where the current operational profile is unknown."
  SYNTAX       Unsigned32 (0..255)

EfmProfileIndexList ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "1d:"

  STATUS       current
  DESCRIPTION
    "This textual convention represents a list of up to 6
    EfmProfileIndex values, any of which can be chosen for
    configuration of a PME in a managed EFMCu port.
    The EfmProfileIndex textual convention defines a greater than
    zero value used to identify a PME profile.
    The value of this object is a concatenation of zero or
    more (up to 6) octets, where each octet contains an 8-bit
    EfmProfileIndex value.
    A zero-length octet string is object-specific and shall
    therefore be defined as part of the description of any object
    that uses this syntax. Examples of the usage of a zero-length
    value might include situations where an object using this
    textual convention is irrelevant for a specific EFMCu port
    type."
  SYNTAX       OCTET STRING (SIZE(0..6))
```

```
 EfmTruthValueOrUnknown ::= TEXTUAL-CONVENTION
   STATUS       current
   DESCRIPTION
     "This textual convention is an extension of the TruthValue
     convention. The latter defines a Boolean value with possible
     values of true(1) and false(2). This extension permits the
     additional value of unknown(0), which can be returned as the
     result of a GET operation when an exact true or false value
     of the object cannot be determined."
   SYNTAX       INTEGER { unknown(0), true(1), false(2) }

-- Port Notifications Group

 efmCuPortNotifications OBJECT IDENTIFIER ::= { efmCuPort 0 }

 efmCuLowRateCrossing NOTIFICATION-TYPE
   OBJECTS {
     ifSpeed,
     efmCuThreshLowRate
   }
   STATUS      current
   DESCRIPTION
     "This notification indicates that the EFMCu port’s data rate
     has reached/dropped below or exceeded the low rate threshold,
     specified by efmCuThreshLowRate.

     This notification may be sent for the -O subtype ports
     (2BaseTL-O/10PassTS-O) while the port is Up, on the crossing
     event in both directions: from normal (rate is above the
     threshold) to low (rate equals the threshold or below it) and
     from low to normal. This notification is not applicable to
     the -R subtypes.

     A small debouncing period of 2.5 sec, between the detection
     of the condition and the notification, should be implemented to
     prevent simultaneous LinkUp/LinkDown and efmCuLowRateCrossing
     notifications to be sent.

     The adaptive nature of the EFMCu technology allows the port to
     adapt itself to the changes in the copper environment, e.g.,
     an impulse noise, alien crosstalk, or a micro-interruption may
     temporarily drop one or more PMEs in the aggregation group,
     causing a rate degradation of the aggregated EFMCu link.
     The dropped PMEs would then try to re-initialize, possibly at
     a lower rate than before, adjusting the rate to provide
     required target SNR margin.

     Generation of this notification is controlled by the
     efmCuLowRateCrossingEnable object."
   ::= { efmCuPortNotifications 1 }

 -- PCS Port group

 efmCuPortConfTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF EfmCuPortConfEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
     "Table for Configuration of EFMCu 2BASE-TL/10PASS-TS (PCS)
```

```
          Ports. Entries in this table shall be maintained in a
          persistent manner."
        ::= { efmCuPort 1 }

      efmCuPortConfEntry OBJECT-TYPE
        SYNTAX      EfmCuPortConfEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
          "An entry in the EFMCu Port Configuration table.
          Each entry represents an EFMCu port indexed by the ifIndex.
          Note that an EFMCu PCS port runs on top of a single
          or multiple PME port(s), which are also indexed by ifIndex."
        INDEX  { ifIndex }
        ::= { efmCuPortConfTable 1 }

      EfmCuPortConfEntry ::=
        SEQUENCE {
          efmCuPAFAdminState               INTEGER,
          efmCuPAFDiscoveryCode            PhysAddress,
          efmCuAdminProfile                EfmProfileIndexList,
          efmCuTargetDataRate              Unsigned32,
          efmCuTargetSnrMgn                Unsigned32,
          efmCuAdaptiveSpectra             TruthValue,
          efmCuThreshLowRate               Unsigned32,
          efmCuLowRateCrossingEnable       TruthValue
        }

      efmCuPAFAdminState  OBJECT-TYPE
        SYNTAX      INTEGER {
          enabled(1),
          disabled(2)
        }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "Administrative (desired) state of the PAF of the EFMCu port
          (PCS).
          When ‘disabled’, PME aggregation will not be performed by the
          PCS. No more than a single PME can be assigned to this PCS in
          this case.
          When ‘enabled’, PAF will be performed by the PCS when the link
          is Up, even on a single attached PME, if PAF is supported.

          PCS ports incapable of supporting PAF shall return a value of
          ‘disabled’. Attempts to ‘enable’ such ports shall be
          rejected.

          A PAF ‘enabled’ port with multiple PMEs assigned cannot be
          ‘disabled’. Attempts to ‘disable’ such port shall be
          rejected, until at most one PME is left assigned.

          Changing PAFAdminState is a traffic-disruptive operation and
          as such shall be done when the link is Down. Attempts to
          change this object shall be rejected if the link is Up or
          Initializing.

          This object maps to the Clause 30 attribute aPAFAdminState.
```

```
          If a Clause 45 MDIO Interface to the PCS is present, then this
          object maps to the PAF enable bit in the 10P/2B PCS control
          register.

          This object shall be maintained in a persistent manner."
        REFERENCE
          "IEEE Std 802.3, 61.2.2, 45.2.3.26.3"
        ::= { efmCuPortConfEntry 1 }
      efmCuPAFDiscoveryCode  OBJECT-TYPE
        SYNTAX      PhysAddress (SIZE(0|6))
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "PAF Discovery Code of the EFMCu port (PCS).
          A unique 6-octet code used by the Discovery function,
          when PAF is supported.
          PCS ports incapable of supporting PAF shall return a
          zero-length octet string on an attempt to read this object.
          An attempt to write to this object shall be rejected for such
          ports.
          This object shall be instantiated for the -O subtype PCS before
          writing operations on the efmCuPAFRemoteDiscoveryCode
          (Set_if_Clear and Clear_if_Same) are performed by PMEs
          associated with the PCS.
          The initial value of this object for -R subtype ports after
          reset is all zeros. For -R subtype ports, the value of this
          object cannot be changed directly. This value may be changed
          as a result of writing operation on the
          efmCuPAFRemoteDiscoveryCode object of remote PME of -O
          subtype, connected to one of the local PMEs associated with
          the PCS.

          Discovery shall be performed when the link is Down.
          Attempts to change this object shall be rejected (in case of
          SNMP with the error inconsistentValue), if the link is Up or
          Initializing.

          The PAF Discovery Code maps to the local Discovery code
          variable in PAF (note that it does not have a corresponding
          Clause 45 register)."
        REFERENCE
          "IEEE Std 802.3, 61.2.2.8.3, 61.2.2.8.4, 45.2.6.6.1, 45.2.6.8,
          61A.2"
        ::= { efmCuPortConfEntry 2 }

      efmCuAdminProfile  OBJECT-TYPE
        SYNTAX      EfmProfileIndexList
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "Desired configuration profile(s), common for all PMEs in the
          EFMCu port. This object is a list of pointers to entries in
          either efmCuPme2BProfileTable or
          efmCuPme10PProfileTable, depending on the current
          operating SubType of the EFMCu port as indicated by
          efmCuPortSide.
          The value of this object is a list of up to 6 indices of
          profiles. If this list consists of a single profile index,
          then all PMEs assigned to this EFMCu port shall be configured
```

```
            according to the profile referenced by that index, unless it
            is overwritten by a corresponding non-zero
            efmCuPmeAdminProfile instance, which takes precedence over
            efmCuAdminProfile.
            A list consisting of more than one index allows each PME
            in the port to be configured according to any profile
            specified in the list.
            By default, this object has a value of 0x01, referencing the
            1st entry in efmCuPme2BProfileTable or
            efmCuPme10PProfileTable.

            This object is writeable and readable for the -O subtype
            (2BaseTL-O or 10PassTS-O) EFMCu ports. It is irrelevant for
            the -R  subtype (2BaseTL-R or 10PassTS-R) ports -- a
            zero-length octet string shall be returned on an attempt to
            read this object and an attempt to change this object shall be
            rejected in this case.

            Note that the current operational profile value is available
            via the efmCuPmeOperProfile object.

            Any modification of this object shall be performed when the
            link is Down. Attempts to change this object shall be
            rejected, if the link is Up or Initializing.
            Attempts to set this object to a list with a member value that
            is not the value of the index for an active entry in the
            corresponding profile table shall be rejected.

            This object maps to the Clause 30 attribute aProfileSelect.

            This object shall be maintained in a persistent manner."
          REFERENCE
            "IEEE Std 802.3, 30.11.2.1.6"
          DEFVAL { ‘01’H }
          ::= { efmCuPortConfEntry 3 }

        efmCuTargetDataRate  OBJECT-TYPE
          SYNTAX      Unsigned32(1..100000|999999)
          UNITS       "Kbps"
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "Desired EFMCu port ‘net’ (as seen across MII) Data Rate in
            kb/s, to be achieved during initialization, under spectral
            restrictions placed on each PME via efmCuAdminProfile or
            efmCuPmeAdminProfile, with the desired SNR margin specified by
            efmCuTargetSnrMgn.
            In case of PAF, this object represents a sum of individual PME
            data rates, modified to compensate for fragmentation and
            64/65-octet encapsulation overhead (e.g., target data rate of
            10 Mb/s shall allow lossless transmission of a full-duplex
            10 Mb/s Ethernet frame stream with minimal inter-frame gap).

            The value is limited above by 100 Mb/s as this is the max
            burst rate across MII for EFMCu ports.

            The value between 1 and 100000 indicates that the total data
            rate (ifSpeed) of the EFMCu port after initialization shall be
            equal to the target data rate or less, if the target data rate
```

```
          cannot be achieved under spectral restrictions specified by
          efmCuAdminProfile/efmCuPmeAdminProfile and with the desired
          SNR margin. In case the copper environment allows a higher
          total data rate to be achieved than that specified by the
          target, the excess capability shall be either converted to
          additional SNR margin or reclaimed by minimizing transmit
          power as controlled by efmCuAdaptiveSpectra.

          The value of 999999 means that the target data rate is not
          fixed and shall be set to the maximum attainable rate during
          initialization (Best Effort), under specified spectral
          restrictions and with the desired SNR margin.

          This object is read-write for the -O subtype EFMCu ports
          (2BaseTL-O/10PassTS-O) and not available for the -R subtypes.

          Changing of the Target Data Rate shall be performed when the
          link is Down. Attempts to change this object shall be rejected
          (in case of SNMP with the error inconsistentValue), if the
          link is Up or Initializing.

          Note that the current Data Rate of the EFMCu port is
          represented by the ifSpeed object of IF-MIB.

          This object shall be maintained in a persistent manner."
        ::= { efmCuPortConfEntry 4 }

      efmCuTargetSnrMgn  OBJECT-TYPE
        SYNTAX      Unsigned32(0..21)
        UNITS       "dB"
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
          "Desired EFMCu port SNR margin to be achieved on all PMEs
          assigned to the port, during initialization. (The SNR margin
          is the difference between the desired SNR and the actual SNR.)

          Note that IEEE Std 802.3 recommends using a default target SNR margin
          of 5 dB for 2BASE-TL ports and 6 dB for 10PASS-TS ports in
          order to achieve a mean bit error ratio (BER) of 10^-7 at the
          PMA service interface.

          This object is read-write for the -O subtype EFMCu ports
          (2BaseTL-O/10PassTS-O) and not available for the -R subtypes.

          Changing of the target SNR margin shall be performed when the
          link is Down. Attempts to change this object shall be rejected
          (in case of SNMP with the error inconsistentValue), if the
          link is Up or Initializing.

          Note that the current SNR margin of the PMEs comprising the
          EFMCu port is represented by efmCuPmeSnrMgn.

          This object shall be maintained in a persistent manner."
        REFERENCE
          "IEEE Std 802.3, 61.1.2"
        ::= { efmCuPortConfEntry 5 }

      efmCuAdaptiveSpectra  OBJECT-TYPE
```

```
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "Indicates how to utilize excess capacity when the copper
      environment allows a higher total data rate to be achieved
      than that specified by the efmCuTargetDataRate.

      A value of true(1) indicates that the excess capability shall
      be reclaimed by minimizing transmit power, e.g., using higher
      constellations and Power Back-Off, in order to reduce
      interference to other copper pairs in the binder and the
      adverse impact to link/system performance.

      A value of false(2) indicates that the excess capability shall
      be converted to additional SNR margin and spread evenly across
      all active PMEs assigned to the (PCS) port, to increase link
      robustness.

      This object is read-write for the -O subtype EFMCu ports
      (2BaseTL-O/10PassTS-O) and not available for the -R subtypes.

      Changing of this object shall be performed when the link is
      Down. Attempts to change this object shall be rejected (in
      case of SNMP with the error inconsistentValue), if the link
      is Up or Initializing.

      This object shall be maintained in a persistent manner."
    ::= { efmCuPortConfEntry 6 }

  efmCuThreshLowRate  OBJECT-TYPE
    SYNTAX      Unsigned32(1..100000)
    UNITS       "Kbps"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "This object configures the EFMCu port low-rate crossing alarm
      threshold. When the current value of ifSpeed for this port
      reaches/drops below or exceeds this threshold, an
      efmCuLowRateCrossing notification may be generated if enabled
      by efmCuLowRateCrossingEnable.

      This object is read-write for the -O subtype EFMCu ports
      (2BaseTL-O/10PassTS-O) and not available for the -R subtypes.

      This object shall be maintained in a persistent manner."
    ::= { efmCuPortConfEntry 7 }

  efmCuLowRateCrossingEnable  OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "Indicates whether efmCuLowRateCrossing notifications should
      be generated for this interface.

      A value of true(1) indicates that efmCuLowRateCrossing
      notification is enabled. A value of false(2) indicates that
      the notification is disabled.
```

```
          This object is read-write for the -O subtype EFMCu ports
          (2BaseTL-O/10PassTS-O) and not available for the -R subtypes.

          This object shall be maintained in a persistent manner."
        ::= { efmCuPortConfEntry 8 }


      efmCuPortCapabilityTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF EfmCuPortCapabilityEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
          "Table for Capabilities of EFMCu 2BASE-TL/10PASS-TS (PCS)
          Ports. Entries in this table shall be maintained in a
          persistent manner"
        ::= { efmCuPort 2 }

      efmCuPortCapabilityEntry OBJECT-TYPE
        SYNTAX      EfmCuPortCapabilityEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
          "An entry in the EFMCu Port Capability table.
          Each entry represents an EFMCu port indexed by the ifIndex.
          Note that an EFMCu PCS port runs on top of a single
          or multiple PME port(s), which are also indexed by ifIndex."
        INDEX  { ifIndex }
        ::= { efmCuPortCapabilityTable 1 }

      EfmCuPortCapabilityEntry ::=
        SEQUENCE {
          efmCuPAFSupported                TruthValue,
          efmCuPeerPAFSupported            EfmTruthValueOrUnknown,
          efmCuPAFCapacity                 Unsigned32,
          efmCuPeerPAFCapacity             Unsigned32
        }

      efmCuPAFSupported  OBJECT-TYPE
        SYNTAX      TruthValue
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "PME Aggregation Function (PAF) capability of the EFMCu port
          (PCS).
          This object has a value of true(1) when the PCS can perform
          PME aggregation on the available PMEs.
          Ports incapable of PAF shall return a value of false(2).

          This object maps to the Clause 30 attribute aPAFSupported.

          If a Clause 45 MDIO Interface to the PCS is present,
          then this object maps to the PAF available bit in the
          10P/2B capability register."
        REFERENCE
          "IEEE Std 802.3, 61.2.2, 30.11.1.1.4, 45.2.3.25.1"
        ::= { efmCuPortCapabilityEntry 1 }

      efmCuPeerPAFSupported  OBJECT-TYPE
```

```
    SYNTAX      EfmTruthValueOrUnknown
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "PME Aggregation Function (PAF) capability of the EFMCu port
      (PCS) link partner.
      This object has a value of true(1) when the remote PCS can
      perform PME aggregation on its available PMEs.
      Ports whose peers are incapable of PAF shall return a value
      of false(2).
      Ports whose peers cannot be reached because of the link
      state shall return a value of unknown(0).

      This object maps to the Clause 30 attribute
      aRemotePAFSupported.

      If a Clause 45 MDIO Interface to the PCS is present, then
      this object maps to the Remote PAF supported bit in the
      10P/2B capability register."
    REFERENCE
      "IEEE Std 802.3, 61.2.2, 30.11.1.1.9, 45.2.3.25.2"
    ::= { efmCuPortCapabilityEntry 2 }

  efmCuPAFCapacity  OBJECT-TYPE
    SYNTAX      Unsigned32 (1..32)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "Number of PMEs that can be aggregated by the local PAF.
      The number of PMEs currently assigned to a particular
      EFMCu port (efmCuNumPMEs) is never greater than
      efmCuPAFCapacity.

      This object maps to the Clause 30 attribute
      aLocalPAFCapacity."
    REFERENCE
      "IEEE Std 802.3, 61.2.2, 30.11.1.1.6"
    ::= { efmCuPortCapabilityEntry 3 }

  efmCuPeerPAFCapacity  OBJECT-TYPE
    SYNTAX      Unsigned32 (0|1..32)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "Number of PMEs that can be aggregated by the PAF of the peer
      PHY (PCS port).
      A value of 0 is returned when peer PAF capacity is unknown
      (peer cannot be reached).
      This object maps to the Clause 30 attribute
      aRemotePAFCapacity."
    REFERENCE
      "IEEE Std 802.3, 61.2.2, 30.11.1.1.10"
    ::= { efmCuPortCapabilityEntry 4 }

  efmCuPortStatusTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF EfmCuPortStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
```

```
          "This table provides overall status information of EFMCu
          2BASE-TL/10PASS-TS ports, complementing the generic status
          information from the ifTable of IF-MIB and ifMauTable of the
          MAU-MIB module. Additional status information about connected PMEs
          is available from the efmCuPmeStatusTable.

          This table contains live data from the equipment. As such,
          it is not persistent."
        ::= { efmCuPort 3 }

      efmCuPortStatusEntry OBJECT-TYPE
        SYNTAX      EfmCuPortStatusEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
          "An entry in the EFMCu Port Status table.
          Each entry represents an EFMCu port indexed by the ifIndex.
          Note that an EFMCu PCS port runs on top of a single
          or multiple PME port(s), which are also indexed by ifIndex."
        INDEX  { ifIndex }
        ::= { efmCuPortStatusTable 1 }

      EfmCuPortStatusEntry ::=
        SEQUENCE {
          efmCuFltStatus                  BITS,
          efmCuPortSide                   INTEGER,
          efmCuNumPMEs                    Unsigned32,
          efmCuPAFInErrors                Counter32,
          efmCuPAFInSmallFragments        Counter32,
          efmCuPAFInLargeFragments        Counter32,
          efmCuPAFInBadFragments          Counter32,
          efmCuPAFInLostFragments         Counter32,
          efmCuPAFInLostStarts            Counter32,
          efmCuPAFInLostEnds              Counter32,
          efmCuPAFInOverflows             Counter32
        }

      efmCuFltStatus  OBJECT-TYPE
        SYNTAX      BITS {
          noPeer(0),
          peerPowerLoss(1),
          pmeSubTypeMismatch(2),
          lowRate(3)
        }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "EFMCu (PCS) port Fault Status. This is a bitmap of possible
          conditions. The various bit positions are:
            noPeer             - the peer PHY cannot be reached (e.g.,
                                 no PMEs attached, all PMEs are Down,
                                 etc.). More info is available in
                                 efmCuPmeFltStatus.
            peerPowerLoss      - the peer PHY has indicated impending
                                 unit failure due to loss of local
                                 power ('Dying Gasp').
            pmeSubTypeMismatch - local PMEs in the aggregation group
                                 are not of the same subtype, e.g.,
                                 some PMEs in the local device are -O
```

```
                                 while others are -R subtype.
             lowRate            - ifSpeed of the port reached or dropped
                                 below efmCuThreshLowRate.

           This object is intended to supplement the ifOperStatus object
           in IF-MIB and ifMauMediaAvailable in the MAU-MIB module.

           Additional information is available via the efmCuPmeFltStatus
           object for each PME in the aggregation group (single PME if
           PAF is disabled)."
         REFERENCE
           "IF-MIB, ifOperStatus; MAU-MIB, ifMauMediaAvailable;
            efmCuPmeFltStatus"
         ::= { efmCuPortStatusEntry 1 }

       efmCuPortSide  OBJECT-TYPE
         SYNTAX      INTEGER {
           subscriber(1),
           office(2),
           unknown(3)
         }
         MAX-ACCESS  read-only
         STATUS      current
         DESCRIPTION
           "EFM port mode of operation (subtype).
           The value of ‘subscriber’ indicates that the port is
           designated as ‘-R’ subtype (all PMEs assigned to this port are
           of subtype ‘-R’).
           The value of the ‘office’ indicates that the port is
           designated as ‘-O’ subtype (all PMEs assigned to this port are
           of subtype ‘-O’).
           The value of ‘unknown’ indicates that the port has no assigned
           PMEs yet or that the assigned PMEs are not of the same side
           (subTypePMEMismatch).

           This object partially maps to the Clause 30 attribute
           aPhyEnd."
         REFERENCE
            "IEEE Std 802.3, 61.1, 30.11.1.1.2"
         ::= { efmCuPortStatusEntry 2 }

       efmCuNumPMEs  OBJECT-TYPE
         SYNTAX      Unsigned32 (0..32)
         MAX-ACCESS  read-only
         STATUS      current
         DESCRIPTION
           "The number of PMEs that is currently aggregated by the local
           PAF (assigned to the EFMCu port using the ifStackTable).
           This number is never greater than efmCuPAFCapacity.

           This object shall be automatically incremented or decremented
           when a PME is added or deleted to/from the EFMCu port using
           the ifStackTable."
         REFERENCE
           "IEEE Std 802.3, 61.2.2, 30.11.1.1.6"
         ::= { efmCuPortStatusEntry 3 }

       efmCuPAFInErrors OBJECT-TYPE
         SYNTAX      Counter32
```

```
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The number of fragments that have been received across the
      gamma interface with RxErr asserted and discarded.
      This read-only counter is inactive (not incremented) when the
      PAF is unsupported or disabled. Upon disabling the PAF, the
      counter retains its previous value.

      If a Clause 45 MDIO Interface to the PCS is present, then
      this object maps to the 10P/2B PAF RX error register.

      Discontinuities in the value of this counter can occur at
      re-initialization of the management system, and at other times
      as indicated by the value of ifCounterDiscontinuityTime,
      defined in IF-MIB."
    REFERENCE
      "IEEE Std 802.3, 45.2.3.29"
    ::= { efmCuPortStatusEntry 4 }

  efmCuPAFInSmallFragments OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The number of fragments smaller than minFragmentSize
      (64 bytes) that have been received across the gamma interface
      and discarded.
      This read-only counter is inactive when the PAF is
      unsupported or disabled. Upon disabling the PAF, the counter
      retains its previous value.

      If a Clause 45 MDIO Interface to the PCS is present, then
      this object maps to the 10P/2B PAF small fragments register.

      Discontinuities in the value of this counter can occur at
      re-initialization of the management system, and at other times
      as indicated by the value of ifCounterDiscontinuityTime,
      defined in IF-MIB."
    REFERENCE
      "IEEE Std 802.3, 45.2.3.30"
    ::= { efmCuPortStatusEntry 5 }

  efmCuPAFInLargeFragments OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The number of fragments larger than maxFragmentSize
      (512 bytes) that have been received across the gamma interface
      and discarded.
      This read-only counter is inactive when the PAF is
      unsupported or disabled. Upon disabling the PAF, the counter
      retains its previous value.

      If a Clause 45 MDIO Interface to the PCS is present, then
      this object maps to the 10P/2B PAF large fragments register.

      Discontinuities in the value of this counter can occur at
```

```
          re-initialization of the management system, and at other times
          as indicated by the value of ifCounterDiscontinuityTime,
          defined in IF-MIB."
        REFERENCE
          "IEEE Std 802.3, 45.2.3.31"
        ::= { efmCuPortStatusEntry 6 }

      efmCuPAFInBadFragments OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "The number of fragments that do not fit into the sequence
          expected by the frame assembly function and that have been
          received across the gamma interface and discarded (the
          frame buffer is flushed to the next valid frame start).
          This read-only counter is inactive when the PAF is
          unsupported or disabled. Upon disabling the PAF, the counter
          retains its previous value.

          If a Clause 45 MDIO Interface to the PCS is present, then
          this object maps to the 10P/2B PAF bad fragments register.

          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other times
          as indicated by the value of ifCounterDiscontinuityTime,
          defined in IF-MIB."
        REFERENCE
          "IEEE Std 802.3, 45.2.3.33"
        ::= { efmCuPortStatusEntry 7 }

      efmCuPAFInLostFragments OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "The number of gaps in the sequence of fragments that have
          been received across the gamma interface (the frame buffer is
          flushed to the next valid frame start, when fragment/fragments
          expected by the frame assembly function is/are not received).
          This read-only counter is inactive when the PAF is
          unsupported or disabled. Upon disabling the PAF, the counter
          retains its previous value.

          If a Clause 45 MDIO Interface to the PCS is present, then
          this object maps to the 10P/2B PAF lost fragment register.

          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other times
          as indicated by the value of ifCounterDiscontinuityTime,
          defined in IF-MIB."
        REFERENCE
          "IEEE Std 802.3, 45.2.3.34"
        ::= { efmCuPortStatusEntry 8 }

      efmCuPAFInLostStarts OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
```

```
    DESCRIPTION
      "The number of missing StartOfPacket indicators expected by
      the frame assembly function.
      This read-only counter is inactive when the PAF is
      unsupported or disabled. Upon disabling the PAF, the counter
      retains its previous value.

      If a Clause 45 MDIO Interface to the PCS is present, then
      this object maps to the 10P/2B PAF lost start of fragment
      register.

      Discontinuities in the value of this counter can occur at
      re-initialization of the management system, and at other times
      as indicated by the value of ifCounterDiscontinuityTime,
      defined in IF-MIB."
    REFERENCE
      "IEEE Std 802.3, 45.2.3.35"
    ::= { efmCuPortStatusEntry 9 }

  efmCuPAFInLostEnds OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The number of missing EndOfPacket indicators expected by the
      frame assembly function.
      This read-only counter is inactive when the PAF is
      unsupported or disabled. Upon disabling the PAF, the counter
      retains its previous value.

      If a Clause 45 MDIO Interface to the PCS is present, then
      this object maps to the 10P/2B PAF lost ends of fragments
      register.

      Discontinuities in the value of this counter can occur at
      re-initialization of the management system, and at other times
      as indicated by the value of ifCounterDiscontinuityTime,
      defined in IF-MIB."
    REFERENCE
      "IEEE Std 802.3, 45.2.3.36"
    ::= { efmCuPortStatusEntry 10 }
  efmCuPAFInOverflows OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The number of fragments, received across the gamma interface
      and discarded, which would have caused the frame assembly
      buffer to overflow.
      This read-only counter is inactive when the PAF is
      unsupported or disabled. Upon disabling the PAF, the counter
      retains its previous value.

      If a Clause 45 MDIO Interface to the PCS is present, then
      this object maps to the 10P/2B PAF overflow register.

      Discontinuities in the value of this counter can occur at
      re-initialization of the management system, and at other times
      as indicated by the value of ifCounterDiscontinuityTime,
```

```
          defined in IF-MIB."
        REFERENCE
          "IEEE Std 802.3, 45.2.3.32"
        ::= { efmCuPortStatusEntry 11 }

   -- PME Notifications Group

    efmCuPmeNotifications OBJECT IDENTIFIER ::= { efmCuPme 0 }

    efmCuPmeLineAtnCrossing NOTIFICATION-TYPE
      OBJECTS {
        efmCuPmeLineAtn,
        efmCuPmeThreshLineAtn
      }
      STATUS      current
      DESCRIPTION
        "This notification indicates that the loop attenuation
        threshold (as per the efmCuPmeThreshLineAtn
        value) has been reached/exceeded for the 2BASE-TL/10PASS-TS
        PME. This notification may be sent on the crossing event in
        both directions: from normal to exceeded and from exceeded
        to normal.

        A small debouncing period of 2.5 sec, between the detection
        of the condition and the notification, should be implemented
        to prevent intermittent notifications from being sent.

        Generation of this notification is controlled by the
        efmCuPmeLineAtnCrossingEnable object."
      ::= { efmCuPmeNotifications 1 }

    efmCuPmeSnrMgnCrossing NOTIFICATION-TYPE
      OBJECTS {
        efmCuPmeSnrMgn,
        efmCuPmeThreshSnrMgn
      }
      STATUS      current
      DESCRIPTION
        "This notification indicates that the SNR margin threshold
        (as per the efmCuPmeThreshSnrMgn value) has been
        reached/exceeded for the 2BASE-TL/10PASS-TS PME.
        This notification may be sent on the crossing event in
        both directions: from normal to exceeded and from exceeded
        to normal.

        A small debouncing period of 2.5 sec, between the detection
        of the condition and the notification, should be implemented
        to prevent intermittent notifications from being sent.

        Generation of this notification is controlled by the
        efmCuPmeSnrMgnCrossingEnable object."
      ::= { efmCuPmeNotifications 2 }

    efmCuPmeDeviceFault NOTIFICATION-TYPE
      OBJECTS {
        efmCuPmeFltStatus
      }
      STATUS      current
      DESCRIPTION
```

```
      "This notification indicates that a fault in the PME has been
      detected by a vendor-specific diagnostic or a self-test.

      Generation of this notification is controlled by the
      efmCuPmeDeviceFaultEnable object."
    ::= { efmCuPmeNotifications 3 }

  efmCuPmeConfigInitFailure NOTIFICATION-TYPE
    OBJECTS {
      efmCuPmeFltStatus,
      efmCuAdminProfile,
      efmCuPmeAdminProfile
    }
    STATUS      current
    DESCRIPTION
      "This notification indicates that PME initialization has
      failed, due to inability of the PME link to achieve the
      requested configuration profile.

      Generation of this notification is controlled by the
      efmCuPmeConfigInitFailEnable object."
    ::= { efmCuPmeNotifications 4 }

  efmCuPmeProtocolInitFailure NOTIFICATION-TYPE
    OBJECTS {
      efmCuPmeFltStatus,
      efmCuPmeOperSubType
    }
    STATUS     current
    DESCRIPTION
      "This notification indicates that the peer PME was using
      an incompatible protocol during initialization.

      Generation of this notification is controlled by the
      efmCuPmeProtocolInitFailEnable object."
    ::= { efmCuPmeNotifications 5 }

  -- The PME group

  efmCuPmeConfTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF EfmCuPmeConfEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "Table for Configuration of common aspects for EFMCu
      2BASE-TL/10PASS-TS PME ports (modems). Configuration of
      aspects specific to 2BASE-TL or 10PASS-TS PME types is
      represented in efmCuPme2BConfTable and efmCuPme10PConfTable,
      respectively.

      Entries in this table shall be maintained in a persistent
      manner."
    ::= { efmCuPme 1 }

  efmCuPmeConfEntry OBJECT-TYPE
    SYNTAX      EfmCuPmeConfEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
```

```
      "An entry in the EFMCu PME Configuration table.
      Each entry represents common aspects of an EFMCu PME port
      indexed by the ifIndex. Note that an EFMCu PME port can be
      stacked below a single PCS port, also indexed by ifIndex,
      possibly together with other PME ports if PAF is enabled."
    INDEX  { ifIndex }
    ::= { efmCuPmeConfTable 1 }

  EfmCuPmeConfEntry ::=
    SEQUENCE {
      efmCuPmeAdminSubType           INTEGER,
      efmCuPmeAdminProfile           EfmProfileIndexOrZero,
      efmCuPAFRemoteDiscoveryCode    PhysAddress,
      efmCuPmeThreshLineAtn          Integer32,
      efmCuPmeThreshSnrMgn           Integer32,
      efmCuPmeLineAtnCrossingEnable  TruthValue,
      efmCuPmeSnrMgnCrossingEnable   TruthValue,
      efmCuPmeDeviceFaultEnable      TruthValue,
      efmCuPmeConfigInitFailEnable   TruthValue,
      efmCuPmeProtocolInitFailEnable TruthValue
    }

  efmCuPmeAdminSubType  OBJECT-TYPE
    SYNTAX      INTEGER {
      ieee2BaseTLO(1),
      ieee2BaseTLR(2),
      ieee10PassTSO(3),
      ieee10PassTSR(4),
      ieee2BaseTLor10PassTSR(5),
      ieee2BaseTLor10PassTSO(6),
      ieee10PassTSor2BaseTLO(7)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "Administrative (desired) subtype of the PME.
      Possible values are:
        ieee2BaseTLO           - PME shall operate as 2BaseTL-O
        ieee2BaseTLR           - PME shall operate as 2BaseTL-R
        ieee10PassTSO          - PME shall operate as 10PassTS-O
        ieee10PassTSR          - PME shall operate as 10PassTS-R
        ieee2BaseTLor10PassTSR - PME shall operate as 2BaseTL-R or
                                 10PassTS-R. The actual value will
                                 be set by the -O link partner
                                 during initialization (handshake).
        ieee2BaseTLor10PassTSO - PME shall operate as 2BaseTL-O
                                 (preferred) or 10PassTS-O. The
                                 actual value will be set during
                                 initialization depending on the -R
                                 link partner capability (i.e., if
                                 -R is incapable of the preferred
                                 2BaseTL mode, 10PassTS will be
                                 used).
        ieee10PassTSor2BaseTLO - PME shall operate as 10PassTS-O
                                 (preferred) or 2BaseTL-O. The
                                 actual value will be set during
                                 initialization depending on the -R
                                 link partner capability (i.e., if
                                 -R is incapable of the preferred
```

```
                                  10PassTS mode, 2BaseTL will be
                                  used).

            Changing efmCuPmeAdminSubType is a traffic-disruptive
            operation and as such shall be done when the link is Down.
            Attempts to change this object shall be rejected if the link
            is Up or Initializing.
            Attempts to change this object to an unsupported subtype
            (see efmCuPmeSubTypesSupported) shall be rejected.

            The current operational subtype is indicated by the
            efmCuPmeOperSubType variable.

            If a Clause 45 MDIO Interface to the PMA/PMD is present, then
            this object combines values of the Port subtype select bits
            and the PMA/PMD type selection bits in the 10P/2B PMA/PMD
            control register."
          REFERENCE
            "IEEE Std 802.3, 61.1, 45.2.1.14.4, 45.2.1.14.7"
          ::= { efmCuPmeConfEntry 1 }

        efmCuPmeAdminProfile  OBJECT-TYPE
          SYNTAX      EfmProfileIndexOrZero
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "Desired PME configuration profile. This object is a pointer
            to an entry in either the efmCuPme2BProfileTable or the
            efmCuPme10PProfileTable, depending on the current operating
            SubType of the PME. The value of this object is the index of
            the referenced profile.
            The value of zero (default) indicates that the PME is
            configured via the efmCuAdminProfile object for the PCS port
            to which this PME is assigned. That is, the profile
            referenced by efmCuPmeAdminProfile takes precedence
            over the profile(s) referenced by efmCuAdminProfile.

            This object is writeable and readable for the CO subtype PMEs
            (2BaseTL-O or 10PassTS-O). It is irrelevant for the CPE
            subtype (2BaseTL-R or 10PassTS-R) -- a zero value shall be
            returned on an attempt to read this object and any attempt
            to change this object shall be rejected in this case.
            Note that the current operational profile value is available
            via efmCuPmeOperProfile object.

            Any modification of this object shall be performed when the
            link is Down. Attempts to change this object shall be
            rejected, if the link is Up or Initializing.

            Attempts to set this object to a value that is not the value
            of the index for an active entry in the corresponding profile
            table shall be rejected.

            This object maps to the Clause 30 attribute aProfileSelect.

            This object shall be maintained in a persistent manner."
          REFERENCE
            "IEEE Std 802.3, 30.11.2.1.6"
          DEFVAL { 0 }
```

```
    ::= { efmCuPmeConfEntry 2 }

  efmCuPAFRemoteDiscoveryCode  OBJECT-TYPE
    SYNTAX      PhysAddress (SIZE(0|6))
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "PAF Remote Discovery Code of the PME port at the CO.
      The 6-octet Discovery Code of the peer PCS connected via
      the PME.
      Reading this object results in a Discovery Get operation.
      Setting this object to all zeros results in a Discovery
      Clear_if_Same operation (the value of efmCuPAFDiscoveryCode
      at the peer PCS shall be the same as efmCuPAFDiscoveryCode of
      the local PCS associated with the PME for the operation to
      succeed).
      Writing a non-zero value to this object results in a
      Discovery Set_if_Clear operation.
      A zero-length octet string shall be returned on an attempt to
      read this object when PAF aggregation is not enabled.

      This object is irrelevant in CPE port (-R) subtypes: in this
      case, a zero-length octet string shall be returned on an
      attempt to read this object; writing to this object shall
      be rejected.

      Discovery shall be performed when the link is Down.
      Attempts to change this object shall be rejected (in case of
      SNMP with the error inconsistentValue), if the link is Up or
      Initializing.

      If a Clause 45 MDIO Interface to the PMA/PMD is present, then
      this object is a function of 10P/2B aggregation discovery
      control register, Discovery operation result bits in 10P/2B
      aggregation and discovery status register and
      10P/2B aggregation discovery code register."
    REFERENCE
      "IEEE Std 802.3, 61.2.2.8.4, 45.2.6.6 to 45.2.6.8"
    ::= { efmCuPmeConfEntry 3 }

  efmCuPmeThreshLineAtn  OBJECT-TYPE
    SYNTAX  Integer32(-127..128)
    UNITS       "dB"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "Desired Line Attenuation threshold for the 2B/10P PME.
      This object configures the line attenuation alarm threshold.
      When the current value of Line Attenuation reaches or
      exceeds this threshold, an efmCuPmeLineAtnCrossing
      notification may be generated, if enabled by
      efmCuPmeLineAtnCrossingEnable.

      This object is writeable for the CO subtype PMEs (-O).
      It is read-only for the CPE subtype (-R).

      Changing of the Line Attenuation threshold shall be performed
      when the link is Down. Attempts to change this object shall be
      rejected (in case of SNMP with the error inconsistentValue),
```

```
            if the link is Up or Initializing.

            If a Clause 45 MDIO Interface to the PME is present, then this
            object maps to the loop attenuation threshold bits in
            the 2B PMD line quality thresholds register."
          REFERENCE
            "IEEE Std 802.3, 45.2.1.23"
          ::= { efmCuPmeConfEntry 4 }

        efmCuPmeThreshSnrMgn  OBJECT-TYPE
          SYNTAX      Integer32(-127..128)
          UNITS       "dB"
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "Desired SNR margin threshold for the 2B/10P PME.
            This object configures the SNR margin alarm threshold.
            When the current value of SNR margin reaches or exceeds this
            threshold, an efmCuPmeSnrMgnCrossing notification may be
            generated, if enabled by efmCuPmeSnrMgnCrossingEnable.
            This object is writeable for the CO subtype PMEs
            (2BaseTL-O/10PassTS-O). It is read-only for the CPE subtype
            (2BaseTL-R/10PassTS-R).

            Changing of the SNR margin threshold shall be performed when
            the link is Down. Attempts to change this object shall be
            rejected (in case of SNMP with the error inconsistentValue),
            if the link is Up or Initializing.

            If a Clause 45 MDIO Interface to the PME is present, then this
            object maps to the SNR margin threshold bits in the 2B PMD
            line quality thresholds register."
          REFERENCE
            "IEEE Std 802.3, 45.2.1.23"
          ::= { efmCuPmeConfEntry 5 }

        efmCuPmeLineAtnCrossingEnable  OBJECT-TYPE
          SYNTAX      TruthValue
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "Indicates whether efmCuPmeLineAtnCrossing notifications
            should be generated for this interface.

            A value of true(1) indicates that efmCuPmeLineAtnCrossing
            notification is enabled. A value of false(2) indicates that
            the notification is disabled."
          ::= { efmCuPmeConfEntry 6 }

        efmCuPmeSnrMgnCrossingEnable  OBJECT-TYPE
          SYNTAX      TruthValue
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "Indicates whether efmCuPmeSnrMgnCrossing notifications
            should be generated for this interface.

            A value of true(1) indicates that efmCuPmeSnrMgnCrossing
            notification is enabled. A value of false(2) indicates that
```

```
            the notification is disabled."
          ::= { efmCuPmeConfEntry 7 }

        efmCuPmeDeviceFaultEnable  OBJECT-TYPE
          SYNTAX      TruthValue
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "Indicates whether efmCuPmeDeviceFault notifications
            should be generated for this interface.

            A value of true(1) indicates that efmCuPmeDeviceFault
            notification is enabled. A value of false(2) indicates that
            the notification is disabled."
          ::= { efmCuPmeConfEntry 8 }

        efmCuPmeConfigInitFailEnable  OBJECT-TYPE
          SYNTAX      TruthValue
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "Indicates whether efmCuPmeConfigInitFailure notifications
            should be generated for this interface.

            A value of true(1) indicates that efmCuPmeConfigInitFailure
            notification is enabled. A value of false(2) indicates that
            the notification is disabled."
          ::= { efmCuPmeConfEntry 9 }

        efmCuPmeProtocolInitFailEnable  OBJECT-TYPE
          SYNTAX      TruthValue
          MAX-ACCESS  read-write
          STATUS      current
          DESCRIPTION
            "Indicates whether efmCuPmeProtocolInitFailure notifications
            should be generated for this interface.

            A value of true(1) indicates that efmCuPmeProtocolInitFailure
            notification is enabled. A value of false(2) indicates that
            the notification is disabled."
          ::= { efmCuPmeConfEntry 10 }


        efmCuPmeCapabilityTable OBJECT-TYPE
          SYNTAX      SEQUENCE OF EfmCuPmeCapabilityEntry
          MAX-ACCESS  not-accessible
          STATUS      current
          DESCRIPTION
            "Table for the configuration of common aspects for EFMCu
            2BASE-TL/10PASS-TS PME ports (modems). The configuration of
            aspects specific to 2BASE-TL or 10PASS-TS PME types is
            represented in the efmCuPme2BConfTable and the
            efmCuPme10PConfTable, respectively.

            Entries in this table shall be maintained in a persistent
            manner."
          ::= { efmCuPme 2 }
        efmCuPmeCapabilityEntry OBJECT-TYPE
          SYNTAX      EfmCuPmeCapabilityEntry
```

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "An entry in the EFMCu PME Capability table.
      Each entry represents common aspects of an EFMCu PME port
      indexed by the ifIndex. Note that an EFMCu PME port can be
      stacked below a single PCS port, also indexed by ifIndex,
      possibly together with other PME ports if PAF is enabled."
    INDEX  { ifIndex }
    ::= { efmCuPmeCapabilityTable 1 }

  EfmCuPmeCapabilityEntry ::=
    SEQUENCE {
      efmCuPmeSubTypesSupported     BITS
    }

  efmCuPmeSubTypesSupported  OBJECT-TYPE
    SYNTAX      BITS {
      ieee2BaseTLO(0),
      ieee2BaseTLR(1),
      ieee10PassTSO(2),
      ieee10PassTSR(3)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "PME supported subtypes. This is a bitmap of possible
      subtypes. The various bit positions are:
        ieee2BaseTLO    - PME is capable of operating as 2BaseTL-O
        ieee2BaseTLR    - PME is capable of operating as 2BaseTL-R
        ieee10PassTSO   - PME is capable of operating as 10PassTS-O
        ieee10PassTSR   - PME is capable of operating as 10PassTS-R

      The desired mode of operation is determined by
      efmCuPmeAdminSubType, while efmCuPmeOperSubType reflects the
      current operating mode.

      If a Clause 45 MDIO Interface to the PCS is present, then this
      object combines the 10PASS-TS capable and 2BASE-TL capable
      bits in the 10P/2B PMA/PMD speed ability register and the
      CO supported and CPE supported bits in the 10P/2B PMA/PMD
      status register."
    REFERENCE
      "IEEE Std 802.3, 61.1, 45.2.1.4.7, 45.2.1.4.8, 45.2.1.15.2,
      45.2.1.15.3"
    ::= { efmCuPmeCapabilityEntry 1 }
  efmCuPmeStatusTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF EfmCuPmeStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "This table provides common status information of EFMCu
      2BASE-TL/10PASS-TS PME ports. Status information specific
      to 10PASS-TS PME is represented in efmCuPme10PStatusTable.

      This table contains live data from the equipment. As such,
      it is not persistent."
    ::= { efmCuPme 3 }
```

```
efmCuPmeStatusEntry OBJECT-TYPE
  SYNTAX      EfmCuPmeStatusEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the EFMCu PME Status table.
    Each entry represents common aspects of an EFMCu PME port
    indexed by the ifIndex. Note that an EFMCu PME port can be
    stacked below a single PCS port, also indexed by ifIndex,
    possibly together with other PME ports if PAF is enabled."
  INDEX  { ifIndex }
  ::= { efmCuPmeStatusTable 1 }

EfmCuPmeStatusEntry ::=
  SEQUENCE {
    efmCuPmeOperStatus            INTEGER,
    efmCuPmeFltStatus             BITS,
    efmCuPmeOperSubType           INTEGER,
    efmCuPmeOperProfile           EfmProfileIndexOrZero,
    efmCuPmeSnrMgn                Integer32,
    efmCuPmePeerSnrMgn            Integer32,
    efmCuPmeLineAtn               Integer32,
    efmCuPmePeerLineAtn           Integer32,
    efmCuPmeEquivalentLength      Unsigned32,
    efmCuPmeTCCodingErrors        Counter32,
    efmCuPmeTCCrcErrors           Counter32
  }

efmCuPmeOperStatus  OBJECT-TYPE
  SYNTAX      INTEGER {
    up(1),
    downNotReady(2),
    downReady(3),
    init(4)
  }

  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "Current PME link Operational Status. Possible values are:
      up(1)           - The link is Up and ready to pass
                        64/65-octet encoded frames or fragments.
      downNotReady(2) - The link is Down and the PME does not
                        detect Handshake tones from its peer.
                        This value may indicate a possible
                        problem with the peer PME.
      downReady(3)    - The link is Down and the PME detects
                        Handshake tones from its peer.
      init(4)         - The link is Initializing, as a result of
                        ifAdminStatus being set to ‘up’ for a
                        particular PME or a PCS to which the PME
                        is connected.

    This object is intended to supplement the Down(2) state of
    ifOperStatus.

    This object partially maps to the Clause 30 attribute
    aPMEStatus.
```

```
          If a Clause 45 MDIO Interface to the PME is present, then this
          object partially maps to PMA/PMD link status bits in 10P/2B
          PMA/PMD status register."
        REFERENCE
          "IEEE Std 802.3, 30.11.2.1.3, 45.2.1.15.4"
        ::= { efmCuPmeStatusEntry 1 }

      efmCuPmeFltStatus  OBJECT-TYPE
        SYNTAX      BITS {
          lossOfFraming(0),
          snrMgnDefect(1),
          lineAtnDefect(2),
          deviceFault(3),
          configInitFailure(4),
          protocolInitFailure(5)
        }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "Current/Last PME link Fault Status. This is a bitmap of
          possible conditions. The various bit positions are:

            lossOfFraming       - Loss of Framing for 10P or
                                  Loss of Sync word for 2B PMD or
                                  Loss of 64/65-octet framing.
            snrMgnDefect        - SNR margin dropped below the
                                  threshold.
            lineAtnDefect       - Line Attenuation exceeds the
                                  threshold.
            deviceFault         - Indicates a vendor-dependent
                                  diagnostic or self-test fault
                                  has been detected.
            configInitFailure   - Configuration initialization failure,
                                  due to inability of the PME link to
                                  support the configuration profile,
                                  requested during initialization.
            protocolInitFailure - Protocol initialization failure, due
                                  to an incompatible protocol used by
                                  the peer PME during init (that could
                                  happen if a peer PMD is a regular
                                  G.SDHSL/VDSL modem instead of a
                                  2BASE-TL/10PASS-TS PME).

          This object is intended to supplement ifOperStatus in IF-MIB.

          This object holds information about the last fault.
          efmCuPmeFltStatus is cleared by the device restart.
          In addition, lossOfFraming, configInitFailure, and
          protocolInitFailure are cleared by PME init;
          deviceFault is cleared by successful diagnostics/test;
          snrMgnDefect and lineAtnDefect are cleared by SNR margin
          and Line attenuation, respectively, returning to norm and by
          PME init.

          This object partially maps to the Clause 30 attribute
          aPMEStatus.

          If a Clause 45 MDIO Interface to the PME is present, then this
          object consolidates information from various PMA/PMD
```

```
      registers, namely: Fault bit in PMA/PMD status 1 register,
      10P/2B PMA/PMD link loss register,
      10P outgoing indicator bits status register,
      10P incoming indicator bits status register,
      2B state defects register."
    REFERENCE
      "IEEE Std 802.3, 30.11.2.1.3, 45.2.1.2.1, 45.2.1.41,
      45.2.1.42, 45.2.1.57"
    ::= { efmCuPmeStatusEntry 2 }

  efmCuPmeOperSubType  OBJECT-TYPE
    SYNTAX      INTEGER {
      ieee2BaseTLO(1),
      ieee2BaseTLR(2),
      ieee10PassTSO(3),
      ieee10PassTSR(4)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "Current operational subtype of the PME.
      Possible values are:
        ieee2BaseTLO          - PME operates as 2BaseTL-O
        ieee2BaseTLR          - PME operates as 2BaseTL-R
        ieee10PassTSO         - PME operates as 10PassTS-O
        ieee10PassTSR         - PME operates as 10PassTS-R

      The desired operational subtype of the PME can be configured
      via the efmCuPmeAdminSubType variable.

      If a Clause 45 MDIO Interface to the PMA/PMD is present, then
      this object combines values of the Port subtype select
      bits, the PMA/PMD type selection bits in the 10P/2B
      PMA/PMD control register, and the PMA/PMD link status bits in
      the 10P/2B PMA/PMD status register."
    REFERENCE
      "IEEE Std 802.3, 61.1, 45.2.1.14.4, 45.2.1.14.7, 45.2.1.15.4"
    ::= { efmCuPmeStatusEntry 3 }

  efmCuPmeOperProfile  OBJECT-TYPE
    SYNTAX      EfmProfileIndexOrZero
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "PME current operating profile. This object is a pointer to
      an entry in either the efmCuPme2BProfileTable or the
      efmCuPme10PProfileTable, depending on the current operating
      SubType of the PME as indicated by efmCuPmeOperSubType.
      Note that a profile entry to which efmCuPmeOperProfile is
      pointing can be created automatically to reflect achieved
      parameters in adaptive (not fixed) initialization,
      i.e., values of efmCuPmeOperProfile and efmCuAdminProfile or
      efmCuPmeAdminProfile may differ.
      The value of zero indicates that the PME is Down or
      Initializing.

      This object partially maps to the aOperatingProfile attribute
      in Clause 30."
    REFERENCE
```

```
      "IEEE Std 802.3, 30.11.2.1.7"
    ::= { efmCuPmeStatusEntry 4 }
  efmCuPmeSnrMgn OBJECT-TYPE
    SYNTAX      Integer32(-127..128|65535)
    UNITS       "dB"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The current signal-to-noise ratio (SNR) margin with respect
      to the received signal as perceived by the local PME.
      The value of 65535 is returned when the PME is Down or
      Initializing.

      This object maps to the aPMESNRMgn attribute in Clause 30.

      If a Clause 45 MDIO Interface is present, then this
      object maps to the 10P/2B RX SNR margin register."
    REFERENCE
      "IEEE Std 802.3, 30.11.2.1.4, 45.2.1.19"
    ::= { efmCuPmeStatusEntry 5 }

  efmCuPmePeerSnrMgn OBJECT-TYPE
    SYNTAX      Integer32(-127..128|65535)
    UNITS       "dB"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The current SNR margin in dB with respect to the received
      signal, as perceived by the remote (link partner) PME.
      The value of 65535 is returned when the PME is Down or
      Initializing.

      This object is irrelevant for the -R PME subtypes. The value
      of 65535 shall be returned in this case.

      If a Clause 45 MDIO Interface is present, then this
      object maps to the 10P/2B link partner RX SNR margin
      register."
    REFERENCE
      "IEEE Std 802.3, 45.2.1.20"
    ::= { efmCuPmeStatusEntry 6}

  efmCuPmeLineAtn OBJECT-TYPE
    SYNTAX      Integer32(-127..128|65535)
    UNITS       "dB"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The current Line Attenuation in dB as perceived by the local
      PME.
      The value of 65535 is returned when the PME is Down or
      Initializing.

      If a Clause 45 MDIO Interface is present, then this
      object maps to the Line Attenuation register."
    REFERENCE
      "IEEE Std 802.3, 45.2.1.21"
    ::= { efmCuPmeStatusEntry 7 }
```

```
efmCuPmePeerLineAtn OBJECT-TYPE
  SYNTAX      Integer32(-127..128|65535)
  UNITS       "dB"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The current Line Attenuation in dB as perceived by the remote
    (link partner) PME.
    The value of 65535 is returned when the PME is Down or
    Initializing.

    This object is irrelevant for the -R PME subtypes. The value
    of 65535 shall be returned in this case.

    If a Clause 45 MDIO Interface is present, then this
    object maps to the 20P/2B link partner Line Attenuation
    register."
  REFERENCE
    "IEEE Std 802.3, 45.2.1.22"
  ::= { efmCuPmeStatusEntry 8 }

efmCuPmeEquivalentLength  OBJECT-TYPE
  SYNTAX      Unsigned32(0..8192|65535)
  UNITS       "m"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "An estimate of the equivalent loop's physical length in
    meters, as perceived by the PME after the link is established.
    An equivalent loop is a hypothetical 26AWG (0.4mm) loop with a
    perfect square root attenuation characteristic, without any
    bridged taps.
    The value of 65535 is returned if the link is Down or
    Initializing or the PME is unable to estimate the equivalent
    length.

    For a 10BASE-TL PME, if a Clause 45 MDIO Interface to the PME
    is present, then this object maps to the 10P Electrical Length
    register."
  REFERENCE
    "IEEE Std 802.3, 45.2.1.29"
  ::= { efmCuPmeStatusEntry 9 }

efmCuPmeTCCodingErrors OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The number of 64/65-octet encapsulation errors. This counter
    is incremented for each 64/65-octet encapsulation error
    detected by the 64/65-octet receive function.

    This object maps to aTCCodingViolations attribute in
    Clause 30.

    If a Clause 45 MDIO Interface to the PME TC is present, then
    this object maps to the TC coding violations register
    (see IEEE Std 802.3 45.2.6.12).
```

```
          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other times
          as indicated by the value of ifCounterDiscontinuityTime,
          defined in IF-MIB."
        REFERENCE
          "IEEE Std 802.3, 61.3.3.1, 30.11.2.1.5, 45.2.6.12"
        ::= { efmCuPmeStatusEntry 10 }

      efmCuPmeTCCrcErrors OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
          "The number of TC-CRC errors. This counter is incremented for
          each TC-CRC error detected by the 64/65-octet receive function
          (see IEEE Std 802.3 61.3.3.3 and IEEE Std 802.3 Figure 61-19).

          This object maps to aTCCRCErrors attribute in
          Clause 30.

          If a Clause 45 MDIO Interface to the PME TC is present, then
          this object maps to the TC CRC error register
          (see IEEE Std 802.3 45.2.6.11).

          Discontinuities in the value of this counter can occur at
          re-initialization of the management system, and at other times
          as indicated by the value of ifCounterDiscontinuityTime,
          defined in IF-MIB."
        REFERENCE
          "IEEE Std 802.3, 61.3.3.3, 30.11.2.1.10, 45.2.6.11"
        ::= { efmCuPmeStatusEntry 11 }

     -- 2BASE-TL specific PME group

      efmCuPme2B      OBJECT IDENTIFIER ::= { efmCuPme 5 }

      efmCuPme2BProfileTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF EfmCuPme2BProfileEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
          "This table supports definitions of administrative and
          operating profiles for 2BASE-TL PMEs.
          The first 14 entries in this table shall be defined as
          follows (see IEEE Std 802.3 Annex 63A):
          -------+-------+-------+-----+------+-------------+-----------
          Profile MinRate MaxRate Power Region Constellation Comment
           index  (kb/s)  (kb/s)  (dBm)
          -------+-------+-------+-----+------+-------------+-----------
             1     5696    5696    13.5    1   32-TCPAM      default
             2     3072    3072    13.5    1   32-TCPAM
             3     2048    2048    13.5    1   16-TCPAM
             4     1024    1024    13.5    1   16-TCPAM
             5      704     704    13.5    1   16-TCPAM
             6      512     512    13.5    1   16-TCPAM
             7     5696    5696    14.5    2   32-TCPAM
             8     3072    3072    14.5    2   32-TCPAM
             9     2048    2048    14.5    2   16-TCPAM
            10     1024    1024    13.5    2   16-TCPAM
```

```
      11      704     704    13.5    2   16-TCPAM
      12      512     512    13.5    2   16-TCPAM
      13      192    5696       0    1   0             best effort
      14      192    5696       0    2   0             best effort
    -------+-------+-------+-----+------+-------------+----------

    These default entries shall be created during agent
    initialization and shall not be deleted.

    Entries following the first 14 can be dynamically created and
    deleted to provide custom administrative (configuration)
    profiles and automatic operating profiles.

    This table shall be maintained in a persistent manner."
  REFERENCE
    "IEEE Std 802.3, Annex 63A, 30.11.2.1.6"
  ::= { efmCuPme2B  2 }
efmCuPme2BProfileEntry OBJECT-TYPE
  SYNTAX      EfmCuPme2BProfileEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "Each entry corresponds to a single 2BASE-TL PME profile.
    Each profile contains a set of parameters, used either for
    configuration or representation of a 2BASE-TL PME.
    In case a particular profile is referenced via the
    efmCuPmeAdminProfile object (or efmCuAdminProfile if
    efmCuPmeAdminProfile is zero), it represents the desired
    parameters for the 2BaseTL-O PME initialization.
    If a profile is referenced via an efmCuPmeOperProfile object,
    it represents the current operating parameters of an
    operational PME.

    Profiles may be created/deleted using the row creation/
    deletion mechanism via efmCuPme2BProfileRowStatus. If an
    active entry is referenced, the entry shall remain ‘active’
    until all references are removed.
    Default entries shall not be removed."
  INDEX { efmCuPme2BProfileIndex }
  ::= { efmCuPme2BProfileTable 1 }

EfmCuPme2BProfileEntry ::=
  SEQUENCE {
    efmCuPme2BProfileIndex           EfmProfileIndex,
    efmCuPme2BProfileDescr           SnmpAdminString,
    efmCuPme2BRegion                 INTEGER,
    efmCuPme2BsMode                  EfmProfileIndexOrZero,
    efmCuPme2BMinDataRate            Unsigned32,
    efmCuPme2BMaxDataRate            Unsigned32,
    efmCuPme2BPower                  Unsigned32,
    efmCuPme2BConstellation          INTEGER,
    efmCuPme2BProfileRowStatus       RowStatus
  }

efmCuPme2BProfileIndex OBJECT-TYPE
  SYNTAX      EfmProfileIndex
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
```

```
          "2BASE-TL PME profile index.
          This object is the unique index associated with this profile.
          Entries in this table are referenced via efmCuAdminProfile or
          efmCuPmeAdminProfile objects."
        ::= { efmCuPme2BProfileEntry 1 }
      efmCuPme2BProfileDescr OBJECT-TYPE
        SYNTAX      SnmpAdminString
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
          "A textual string containing information about a 2BASE-TL PME
          profile. The string may include information about the data
          rate and spectral limitations of this particular profile."
        ::= { efmCuPme2BProfileEntry 2 }

      efmCuPme2BRegion  OBJECT-TYPE
        SYNTAX      INTEGER {
          region1(1),
          region2(2)
        }
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
          "Regional settings for a 2BASE-TL PME, as specified in the
          relevant Regional Annex of ITU-T Recommendation G.991.2.
          Regional settings specify the Power Spectral Density (PSD)
          mask and the Power Back-Off (PBO) values, and place
          limitations on the max allowed data rate, power, and
          constellation.

          Possible values for this object are:
            region1      - Annexes A and F (e.g., North America)
            region2      - Annexes B and G (e.g., Europe)

          Annex A/B specify regional settings for data rates from
          192 kb/s to 2304 kb/s using 16-TCPAM encoding.
          Annex F/G specify regional settings for rates from
          2320 kb/s to 3840 kb/s using 16-TCPAM encoding and from
          768 kb/s to 5696 kb/s using 32-TCPAM encoding.

          If a Clause 45 MDIO Interface to the PME is present, then this
          object partially maps to the Region bits in the 2B general
          parameter register."
        REFERENCE
          "IEEE Std 802.3, 45.2.1.45; ITU-T Recommendation G.991.2,
           Annexes A, B, F and G"
        ::= { efmCuPme2BProfileEntry 3 }

      efmCuPme2BsMode  OBJECT-TYPE
        SYNTAX      EfmProfileIndexOrZero
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
          "Desired custom Spectral Mode for a 2BASE-TL PME. This object
          is a pointer to an entry in efmCuPme2BsModeTable and a block
          of entries in efmCuPme2BRateReachTable, which together define
          (country-specific) reach-dependent rate limitations in
          addition to those defined by efmCuPme2BRegion.
```

```
            The value of this object is the index of the referenced
            spectral mode.
            The value of zero (default) indicates that no specific
            spectral mode is applicable.

            Attempts to set this object to a value that is not the value
            of the index for an active entry in the corresponding spectral
            mode table shall be rejected."
          REFERENCE
            "efmCuPme2BsModeTable, efmCuPme2BRateReachTable"
          DEFVAL { 0 }
          ::= { efmCuPme2BProfileEntry 4 }

        efmCuPme2BMinDataRate  OBJECT-TYPE
          SYNTAX  Unsigned32(192..5696)
          UNITS       "Kbps"
          MAX-ACCESS  read-create
          STATUS      current
          DESCRIPTION
            "Minimum Data Rate for the 2BASE-TL PME.
            This object can take values of (n x 64)kb/s,
            where n=3..60 for 16-TCPAM and n=12..89 for 32-TCPAM encoding.

            The data rate of the 2BASE-TL PME is considered ‘fixed’ when
            the value of this object equals that of efmCuPme2BMaxDataRate.
            If efmCuPme2BMinDataRate is less than efmCuPme2BMaxDataRate in
            the administrative profile, the data rate is considered
            ‘adaptive’, and shall be set to the maximum attainable rate
            not exceeding efmCuPme2BMaxDataRate, under the spectral
            limitations placed by the efmCuPme2BRegion and
            efmCuPme2BsMode.

            Note that the current operational data rate of the PME is
            represented by the ifSpeed object of IF-MIB.

            If a Clause 45 MDIO Interface to the PME is present, then this
            object maps to the Min Data Rate1 bits in the 2B PMD
            parameters register.

            This object shall be maintained in a persistent manner."
          REFERENCE
            "IEEE Std 802.3, 45.2.1.46"
          ::= { efmCuPme2BProfileEntry 5 }
        efmCuPme2BMaxDataRate  OBJECT-TYPE
          SYNTAX  Unsigned32(192..5696)
          UNITS       "Kbps"
          MAX-ACCESS  read-create
          STATUS      current
          DESCRIPTION
            "Maximum Data Rate for the 2BASE-TL PME.
            This object can take values of (n x 64)kb/s,
            where n=3..60 for 16-TCPAM and n=12..89 for 32-TCPAM encoding.

            The data rate of the 2BASE-TL PME is considered ‘fixed’ when
            the value of this object equals that of efmCuPme2BMinDataRate.
            If efmCuPme2BMinDataRate is less than efmCuPme2BMaxDataRate in
            the administrative profile, the data rate is considered
            ‘adaptive’, and shall be set to the maximum attainable rate
            not exceeding efmCuPme2BMaxDataRate, under the spectral
```

```
            limitations placed by the efmCuPme2BRegion and
            efmCuPme2BsMode.

            Note that the current operational data rate of the PME is
            represented by the ifSpeed object of IF-MIB.

            If a Clause 45 MDIO Interface to the PME is present, then this
            object maps to the Max Data Rate1 bits in the 2B PMD
            parameters register.

            This object shall be maintained in a persistent manner."
          REFERENCE
            "IEEE Std 802.3, 45.2.1.46"
          ::= { efmCuPme2BProfileEntry 6 }

        efmCuPme2BPower  OBJECT-TYPE
          SYNTAX      Unsigned32(0|10..42)
          UNITS       "0.5 dBm"
          MAX-ACCESS  read-create
          STATUS      current
          DESCRIPTION
            "Signal Transmit Power. Multiple of 0.5 dBm.
            The value of 0 in the administrative profile means that the
            signal transmit power is not fixed and shall be set to
            maximize the attainable rate, under the spectral limitations
            placed by the efmCuPme2BRegion and efmCuPme2BsMode.

            If a Clause 45 MDIO Interface to the PME is present, then this
            object maps to the Power1 bits in the 2B PMD parameters
            register."
          REFERENCE
            "IEEE Std 802.3, 45.2.1.46"
          ::= { efmCuPme2BProfileEntry 7 }

        efmCuPme2BConstellation  OBJECT-TYPE
          SYNTAX      INTEGER {
            adaptive(0),
            tcpam16(1),
            tcpam32(2)
          }
          MAX-ACCESS  read-create
          STATUS      current
          DESCRIPTION
            "TCPAM Constellation of the 2BASE-TL PME.
            The possible values are:
              adaptive(0)    - either 16- or 32-TCPAM
              tcpam16(1)     - 16-TCPAM
              tcpam32(2)     - 32-TCPAM

            The value of adaptive(0) in the administrative profile means
            that the constellation is not fixed and shall be set to
            maximize the attainable rate, under the spectral limitations
            placed by the efmCuPme2BRegion and efmCuPme2BsMode.

            If a Clause 45 MDIO Interface to the PME is present, then this
            object maps to the Constellation1 bits in the 2B general
            parameter register."
          REFERENCE
             "IEEE Std 802.3, 45.2.1.46"
```

```
          ::= { efmCuPme2BProfileEntry 8 }

        efmCuPme2BProfileRowStatus OBJECT-TYPE
          SYNTAX      RowStatus
          MAX-ACCESS  read-create
          STATUS      current
          DESCRIPTION
            "This object controls the creation, modification, or deletion
            of the associated entry in the efmCuPme2BProfileTable per the
            semantics of RowStatus.

            If an ‘active’ entry is referenced via efmCuAdminProfile or
            efmCuPmeAdminProfile instance(s), the entry shall remain
            ‘active’.

            An ‘active’ entry shall not be modified. In order to modify
            an existing entry, it shall be taken out of service (by setting
            this object to ‘notInService’), modified, and set ‘active’
            again."
          ::= { efmCuPme2BProfileEntry 9 }
        efmCuPme2BsModeTable OBJECT-TYPE
          SYNTAX      SEQUENCE OF EfmCuPme2BsModeEntry
          MAX-ACCESS  not-accessible
          STATUS      current
          DESCRIPTION
            "This table, together with efmCu2BReachRateTable, supports
            definition of administrative custom spectral modes for
            2BASE-TL PMEs, describing spectral limitations in addition to
            those specified by efmCuPme2BRegion.

            In some countries, spectral regulations (e.g., UK ANFP) limit
            the length of the loops for certain data rates. This table
            allows these country-specific limitations to be specified.

            Entries in this table referenced by the efmCuPme2BsMode
            shall not be deleted until all the active references are
            removed.

            This table shall be maintained in a persistent manner."
          REFERENCE
            "efmCu2BReachRateTable"
          ::= { efmCuPme2B  3 }

        efmCuPme2BsModeEntry OBJECT-TYPE
          SYNTAX      EfmCuPme2BsModeEntry
          MAX-ACCESS  not-accessible
          STATUS      current
          DESCRIPTION
            "Each entry specifies a spectral mode description and its
            index, which is used to reference corresponding entries in the
            efmCu2BReachRateTable.

            Entries may be created/deleted using the row creation/
            deletion mechanism via efmCuPme2BsModeRowStatus."
          INDEX { efmCuPme2BsModeIndex }
          ::= { efmCuPme2BsModeTable 1 }

        EfmCuPme2BsModeEntry ::=
          SEQUENCE {
```

```
    efmCuPme2BsModeIndex             EfmProfileIndex,
    efmCuPme2BsModeDescr             SnmpAdminString,
    efmCuPme2BsModeRowStatus         RowStatus
  }

efmCuPme2BsModeIndex OBJECT-TYPE
  SYNTAX      EfmProfileIndex
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "2BASE-TL PME Spectral Mode index.
    This object is the unique index associated with this spectral
    mode.
    Entries in this table are referenced via the efmCuPme2BsMode
    object."
  ::= { efmCuPme2BsModeEntry 1 }

efmCuPme2BsModeDescr OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "A textual string containing information about a 2BASE-TL PME
    spectral mode. The string may include information about
    corresponding (country-specific) spectral regulations
    and rate/reach limitations of this particular spectral mode."
  ::= { efmCuPme2BsModeEntry 2 }

efmCuPme2BsModeRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "This object controls creation, modification, or deletion of
    the associated entry in efmCuPme2BsModeTable per the semantics
    of RowStatus.

    If an ‘active’ entry is referenced via efmCuPme2BsMode
    instance(s), the entry shall remain ‘active’.

    An ‘active’ entry shall not be modified. In order to modify
    an existing entry, it shall be taken out of service (by setting
    this object to ‘notInService’), modified, and set ‘active’
    again."
  ::= { efmCuPme2BsModeEntry 3 }


efmCuPme2BReachRateTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF EfmCuPme2BReachRateEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table supports the definition of administrative custom
    spectral modes for 2BASE-TL PMEs, providing spectral
    limitations in addition to those specified by
    efmCuPme2BRegion.
    The spectral regulations in some countries (e.g., UK ANFP)
    limit the length of the loops for certain data rates.
    This table allows these country-specific limitations to be
```

```
          specified.

          Below is an example of this table for NICC Document ND1602:2005/08:
          ----------+-------+-------
          Equivalent MaxRate MaxRate
            Length    PAM16   PAM32
              (m)     (kb/s)  (kb/s)
          ----------+-------+-------
              975      2304    5696
             1125      2304    5504
             1275      2304    5120
             1350      2304    4864
             1425      2304    4544
             1500      2304    4288
             1575      2304    3968
             1650      2304    3776
             1725      2304    3520
             1800      2304    3264
             1875      2304    3072
             1950      2048    2688
             2100      1792    2368
             2250      1536       0
             2400      1408       0
             2550      1280       0
             2775      1152       0
             2925      1152       0
             3150      1088       0
             3375      1024       0
          ----------+-------+-------

          Entries in this table referenced by an efmCuPme2BsMode
          instance shall not be deleted.

          This table shall be maintained in a persistent manner."
        REFERENCE
          "NICC Document ND1602:2005/08"
        ::= { efmCuPme2B  4 }

      efmCuPme2BReachRateEntry OBJECT-TYPE
        SYNTAX      EfmCuPme2BReachRateEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
          "Each entry specifies maximum 2BASE-TL PME data rates
          allowed for a certain equivalent loop length, when using
          16-TCPAM or 32-TCPAM encoding.

          When a 2BASE-TL PME is initialized, its data rate shall not
          exceed the following limitations:
          - the value of efmCuPme2BMaxDataRate
          - maximum data rate allowed by efmCuPme2BRegion and
            efmCuPme2BPower
          - maximum data rate for a given encoding specified in the
            efmCuPme2BsModeEntry, corresponding to the equivalent loop
            length, estimated by the PME

          efmCuPme2BEquivalentLength values should be assigned
          in increasing order, starting from the minimum value.
```

```
      Entries may be created/deleted using the row creation/
      deletion mechanism via efmCuPme2ReachRateRowStatus."
    INDEX { efmCuPme2BsModeIndex, efmCuPme2BReachRateIndex }
    ::= { efmCuPme2BReachRateTable 1 }

  EfmCuPme2BReachRateEntry ::=
    SEQUENCE {
      efmCuPme2BReachRateIndex         EfmProfileIndex,
      efmCuPme2BEquivalentLength       Unsigned32,
      efmCuPme2BMaxDataRatePam16       Unsigned32,
      efmCuPme2BMaxDataRatePam32       Unsigned32,
      efmCuPme2BReachRateRowStatus     RowStatus
    }

  efmCuPme2BReachRateIndex OBJECT-TYPE
    SYNTAX      EfmProfileIndex
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "2BASE-TL custom spectral mode Reach-Rate table index.
      This object is the unique index associated with each entry."
    ::= { efmCuPme2BReachRateEntry 1 }

  efmCuPme2BEquivalentLength  OBJECT-TYPE
    SYNTAX      Unsigned32(0..8192)
    UNITS       "m"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "Maximum allowed equivalent loop’s physical length in meters
      for the specified data rates.
      An equivalent loop is a hypothetical 26AWG (0.4mm) loop with a
      perfect square root attenuation characteristic, without any
      bridged taps."
    ::= { efmCuPme2BReachRateEntry 2 }

  efmCuPme2BMaxDataRatePam16  OBJECT-TYPE
    SYNTAX      Unsigned32(0|192..5696)
    UNITS       "Kbps"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "Maximum data rate for a 2BASE-TL PME at the specified
      equivalent loop’s length using TC-PAM16 encoding.
      The value of zero means that TC-PAM16 encoding should not be
      used at this distance."
    ::= { efmCuPme2BReachRateEntry 3 }

  efmCuPme2BMaxDataRatePam32  OBJECT-TYPE
    SYNTAX      Unsigned32(0|192..5696)
    UNITS       "Kbps"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "Maximum data rate for a 2BASE-TL PME at the specified
      equivalent loop’s length using TC-PAM32 encoding.
      The value of zero means that TC-PAM32 encoding should not be
      used at this distance."
    ::= { efmCuPme2BReachRateEntry 4 }
```

```
 efmCuPme2BReachRateRowStatus OBJECT-TYPE
   SYNTAX      RowStatus
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
     "This object controls the creation, modification, or deletion
     of the associated entry in the efmCuPme2BReachRateTable per
     the semantics of RowStatus.

     If an ‘active’ entry is referenced via efmCuPme2BsMode
     instance(s), the entry shall remain ‘active’.

     An ‘active’ entry shall not be modified. In order to modify
     an existing entry, it shall be taken out of service (by setting
     this object to ‘notInService’), modified, and set ‘active’
     again."
   ::= { efmCuPme2BReachRateEntry 5 }


-- 10PASS-TS specific PME group
 efmCuPme10P      OBJECT IDENTIFIER ::= { efmCuPme 6 }

 efmCuPme10PProfileTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF EfmCuPme10PProfileEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
     "This table supports definitions of configuration profiles for
     10PASS-TS PMEs.
     The first 22 entries in this table shall be defined as
     follows (see IEEE Std 802.3 Annex 62B.3, Table 62B-1):
     -------+--------+----+---------+-----+-----+---------------
     Profile Bandplan UPBO BandNotch DRate URate Comment
      Index  PSDMask#  p#    p#        p#    p#
     -------+--------+----+---------+-----+-----+---------------
        1       1      3    2,6,10,11    20    20 default profile
        2      13      5    0            20    20
        3       1      1    0            20    20
        4      16      0    0           100   100
        5      16      0    0            70    50
        6       6      0    0            50    10
        7      17      0    0            30    30
        8       8      0    0            30     5
        9       4      0    0            25    25
       10       4      0    0            15    15
       11      23      0    0            10    10
       12      23      0    0             5     5
       13      16      0    2,5,9,11    100   100
       14      16      0    2,5,9,11     70    50
       15       6      0    2,6,10,11    50    10
       16      17      0    2,5,9,11     30    30
       17       8      0    2,6,10,11    30     5
       18       4      0    2,6,10,11    25    25
       19       4      0    2,6,10,11    15    15
       20      23      0    2,5,9,11     10    10
       21      23      0    2,5,9,11      5     5
       22      30      0    0           200    50
     -------+--------+----+---------+-----+-----+---------------
```

```
          These default entries shall be created during agent
          initialization and shall not be deleted.

          Entries following the first 22 can be dynamically created and
          deleted to provide custom administrative (configuration)
          profiles and automatic operating profiles.

          This table shall be maintained in a persistent manner."
        REFERENCE
          "IEEE Std 802.3, Annex 62B.3, 30.11.2.1.6"
        ::= { efmCuPme10P  1 }

      efmCuPme10PProfileEntry OBJECT-TYPE
        SYNTAX      EfmCuPme10PProfileEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
          "Each entry corresponds to a single 10PASS-TS PME profile.

          Each profile contains a set of parameters, used either for
          configuration or representation of a 10PASS-TS PME.
          In case a particular profile is referenced via the
          efmCuPmeAdminProfile object (or efmCuAdminProfile if
          efmCuPmeAdminProfile is zero), it represents the desired
          parameters for the 10PassTS-O PME initialization.
          If a profile is referenced via an efmCuPmeOperProfile object,
          it represents the current operating parameters of the PME.

          Profiles may be created/deleted using the row creation/
          deletion mechanism via efmCuPme10PProfileRowStatus. If an
          ‘active’ entry is referenced, the entry shall remain ‘active’
          until all references are removed.
          Default entries shall not be removed."
        INDEX { efmCuPme10PProfileIndex }
        ::= { efmCuPme10PProfileTable 1 }

      EfmCuPme10PProfileEntry ::=
        SEQUENCE {
          efmCuPme10PProfileIndex           EfmProfileIndex,
          efmCuPme10PProfileDescr           SnmpAdminString,
          efmCuPme10PBandplanPSDMskProfile  INTEGER,
          efmCuPme10PUPBOReferenceProfile   INTEGER,
          efmCuPme10PBandNotchProfiles      BITS,
          efmCuPme10PPayloadDRateProfile    INTEGER,
          efmCuPme10PPayloadURateProfile    INTEGER,
          efmCuPme10PProfileRowStatus       RowStatus
        }

      efmCuPme10PProfileIndex OBJECT-TYPE
        SYNTAX      EfmProfileIndex
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
          "10PASS-TS PME profile index.
          This object is the unique index associated with this profile.
          Entries in this table are referenced via efmCuAdminProfile or
          efmCuPmeAdminProfile."
        ::= { efmCuPme10PProfileEntry 1 }
```

```
efmCuPme10PProfileDescr OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "A textual string containing information about a 10PASS-TS PME
    profile. The string may include information about data rate
    and spectral limitations of this particular profile."
  ::= { efmCuPme10PProfileEntry 2 }

efmCuPme10PBandplanPSDMskProfile  OBJECT-TYPE
  SYNTAX  INTEGER {
    profile1(1),
    profile2(2),
    profile3(3),
    profile4(4),
    profile5(5),
    profile6(6),
    profile7(7),
    profile8(8),
    profile9(9),
    profile10(10),
    profile11(11),
    profile12(12),
    profile13(13),
    profile14(14),
    profile15(15),
    profile16(16),
    profile17(17),
    profile18(18),
    profile19(19),
    profile20(20),
    profile21(21),
    profile22(22),
    profile23(23),
    profile24(24),
    profile25(25),
    profile26(26),
    profile27(27),
    profile28(28),
    profile29(29),
    profile30(30)
  }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The 10PASS-TS PME Bandplan and PSD Mask Profile, as specified
    in IEEE Std 802.3 Annex 62A, table 62A-1. Possible values are:
    --------------+------------------------+------------+--------
    Profile Name    PSD Mask                     Bands      ITU-T G.993.1
                                               0/1/2/3/4/5  Bandplan
    --------------+------------------------+------------+--------
    profile1(1)    ANSI T1.424 FTTCab.M1         x/D/U/D/U    A
    profile2(2)    ANSI T1.424 FTTEx.M1          x/D/U/D/U    A
    profile3(3)    ANSI T1.424 FTTCab.M2         x/D/U/D/U    A
    profile4(4)    ANSI T1.424 FTTEx.M2          x/D/U/D/U    A
    profile5(5)    ANSI T1.424 FTTCab.M1         D/D/U/D/U    A
    profile6(6)    ANSI T1.424 FTTEx.M1          D/D/U/D/U    A
```

```
          profile7(7)    ANSI T1.424 FTTCab.M2         D/D/U/D/U    A
          profile8(8)    ANSI T1.424 FTTEx.M2          D/D/U/D/U    A
          profile9(9)    ANSI T1.424 FTTCab.M1         U/D/U/D/x    A
          profile10(10)  ANSI T1.424 FTTEx.M1          U/D/U/D/x    A
          profile11(11)  ANSI T1.424 FTTCab.M2         U/D/U/D/x    A
          profile12(12)  ANSI T1.424 FTTEx.M2          U/D/U/D/x    A
          profile13(13)  ETSI TS 101 270-1 Pcab.M1.A   x/D/U/D/U    B
          profile14(14)  ETSI TS 101 270-1 Pcab.M1.B   x/D/U/D/U    B
          profile15(15)  ETSI TS 101 270-1 Pex.P1.M1   x/D/U/D/U    B
          profile16(16)  ETSI TS 101 270-1 Pex.P2.M1   x/D/U/D/U    B
          profile17(17)  ETSI TS 101 270-1 Pcab.M2     x/D/U/D/U    B
          profile18(18)  ETSI TS 101 270-1 Pex.P1.M2   x/D/U/D/U    B
          profile19(19)  ETSI TS 101 270-1 Pex.P2.M2   x/D/U/D/U    B
          profile20(20)  ETSI TS 101 270-1 Pcab.M1.A   U/D/U/D/x    B
          profile21(21)  ETSI TS 101 270-1 Pcab.M1.B   U/D/U/D/x    B
          profile22(22)  ETSI TS 101 270-1 Pex.P1.M1   U/D/U/D/x    B
          profile23(23)  ETSI TS 101 270-1 Pex.P2.M1   U/D/U/D/x    B
          profile24(24)  ETSI TS 101 270-1 Pcab.M2     U/D/U/D/x    B
          profile25(25)  ETSI TS 101 270-1 Pex.P1.M2   U/D/U/D/x    B
          profile26(26)  ETSI TS 101 270-1 Pex.P2.M2   U/D/U/D/x    B
          profile27(27)  ITU-T G.993.1 F.1.2.1         x/D/U/D/U    Annex F
          profile28(28)  ITU-T G.993.1 F.1.2.2         x/D/U/D/U    Annex F
          profile29(29)  ITU-T G.993.1 F.1.2.3         x/D/U/D/U    Annex F
          profile30(30)  ANSI T1.424 FTTCab.M1 (ext.)  x/D/U/D/U/D  Annex A
          --------------+-----------------------+------------+--------
          "
        REFERENCE
          "IEEE Std 802.3, Annex 62A"
        ::= { efmCuPme10PProfileEntry 3 }

      efmCuPme10PUPBOReferenceProfile  OBJECT-TYPE
        SYNTAX  INTEGER {
          profile0(0),
          profile1(1),
          profile2(2),
          profile3(3),
          profile4(4),
          profile5(5),
          profile6(6),
          profile7(7),
          profile8(8),
          profile9(9)
        }
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
          "The 10PASS-TS PME Upstream Power Back-Off (UPBO) Reference
          PSD Profile, as specified in 802.3 Annex 62A, table 62A-3.
          Possible values are:
          ------------+----------------------------
          Profile Name   Reference        PSD
          ------------+----------------------------
          profile0(0)  no profile
          profile1(1)  ANSI T1.424        Noise A    M1
          profile2(2)  ANSI T1.424        Noise A    M2
          profile3(3)  ANSI T1.424        Noise F    M1
          profile4(4)  ANSI T1.424        Noise F    M2
          profile5(5)  ETSI TS 101 270-1  Noise A&B
          profile6(6)  ETSI TS 101 270-1  Noise C
```

```
      profile7(7)  ETSI TS 101 270-1  Noise D
      profile8(8)  ETSI TS 101 270-1  Noise E
      profile9(9)  ETSI TS 101 270-1  Noise F
      ------------+----------------------------
      "
    REFERENCE
      "IEEE Std 802.3, Annex 62A.3.5"
    ::= { efmCuPme10PProfileEntry 4 }

  efmCuPme10PBandNotchProfiles  OBJECT-TYPE
    SYNTAX  BITS {
      profile0(0),
      profile1(1),
      profile2(2),
      profile3(3),
      profile4(4),
      profile5(5),
      profile6(6),
      profile7(7),
      profile8(8),
      profile9(9),
      profile10(10),
      profile11(11)
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The 10PASS-TS PME Egress Control Band Notch Profile bitmap,
      as specified in IEEE Std 802.3 Annex 62A, table 62A-4. Possible
      values are:
      --------------+--------+------+-----------+------+------
      Profile Name   G.991.3  T1.424 TS 101 270-1 StartF EndF
                     table    table  table        (MHz)  (MHz)
      --------------+--------+------+-----------+------+------
      profile0(0)    no profile
      profile1(1)    F-5 #01  -      -            1.810  1.825
      profile2(2)    6-2      15-1   17           1.810  2.000
      profile3(3)    F-5 #02  -      -            1.907  1.912
      profile4(4)    F-5 #03  -      -            3.500  3.575
      profile5(5)    6-2      -      17           3.500  3.800
      profile6(6)    -        15-1   -            3.500  4.000
      profile7(7)    F-5 #04  -      -            3.747  3.754
      profile8(8)    F-5 #05  -      -            3.791  3.805
      profile9(9)    6-2      -      17           7.000  7.100
      profile10(10)  F-5 #06  15-1   -            7.000  7.300
      profile11(11)  6-2      15-1   1            10.100 10.150
      --------------+--------+------+-----------+------+------

      Any combination of profiles can be specified by ORing
      individual profiles, for example, a value of 0x2230 selects
      profiles 2, 6, 10, and 11."
    REFERENCE
      "IEEE Std 802.3, Annex 62A.3.5"
    ::= { efmCuPme10PProfileEntry 5 }

  efmCuPme10PPayloadDRateProfile  OBJECT-TYPE
    SYNTAX      INTEGER {
      profile5(5),
      profile10(10),
```

```
      profile15(15),
      profile20(20),
      profile25(25),
      profile30(30),
      profile50(50),
      profile70(70),
      profile100(100),
      profile140(140),
      profile200(200)
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The 10PASS-TS PME Downstream Payload Rate Profile, as
      specified in IEEE Std 802.3 Annex 62A. Possible values are:
        profile5(5)      - 2.5 Mb/s
        profile10(10)    - 5 Mb/s
        profile15(15)    - 7.5 Mb/s
        profile20(20)    - 10 Mb/s
        profile25(25)    - 12.5 Mb/s
        profile30(30)    - 15 Mb/s
        profile50(50)    - 25 Mb/s
        profile70(70)    - 35 Mb/s
        profile100(100)  - 50 Mb/s
        profile140(140)  - 70 Mb/s
        profile200(200)  - 100 Mb/s

      Each value represents a target for the PME’s Downstream
      Payload Bitrate as seen at the MII. If the payload rate of
      the selected profile cannot be achieved based on the loop
      environment, bandplan, and PSD mask, the PME initialization
      shall fail."
    REFERENCE
      "IEEE Std 802.3, Annex 62A.3.6"
    ::= { efmCuPme10PProfileEntry 6 }

  efmCuPme10PPayloadURateProfile  OBJECT-TYPE
    SYNTAX      INTEGER {
      profile5(5),
      profile10(10),
      profile15(15),
      profile20(20),
      profile25(25),
      profile30(30),
      profile50(50),
      profile70(70),
      profile100(100)
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The 10PASS-TS PME Upstream Payload Rate Profile, as specified
       in 802.3 Annex 62A. Possible values are:
        profile5(5)       - 2.5 Mb/s
        profile10(10)     - 5 Mb/s
        profile15(15)     - 7.5 Mb/s
        profile20(20)     - 10 Mb/s
        profile25(25)     - 12.5 Mb/s
        profile30(30)     - 15 Mb/s
```

```
          profile50(50)     - 25 Mb/s
          profile70(70)     - 35 Mb/s
          profile100(100)   - 50 Mb/s
        Each value represents a target for the PME’s Upstream Payload
        Bitrate as seen at the MII. If the payload rate of the
        selected profile cannot be achieved based on the loop
        environment, bandplan, and PSD mask, the PME initialization
        shall fail."
      REFERENCE
        "IEEE Std 802.3, Annex 62A.3.6"
      ::= { efmCuPme10PProfileEntry 7 }

    efmCuPme10PProfileRowStatus OBJECT-TYPE
      SYNTAX      RowStatus
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
        "This object controls creation, modification, or deletion of
        the associated entry in efmCuPme10PProfileTable per the
        semantics of RowStatus.

        If an active entry is referenced via efmCuAdminProfile or
        efmCuPmeAdminProfile, the entry shall remain ‘active’ until
        all references are removed.

        An ‘active’ entry shall not be modified. In order to modify
        an existing entry, it shall be taken out of service (by setting
        this object to ‘notInService’), modified, and set ‘active’
        again."
      ::= { efmCuPme10PProfileEntry 8 }


    efmCuPme10PStatusTable OBJECT-TYPE
      SYNTAX      SEQUENCE OF EfmCuPme10PStatusEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
        "This table provides status information of EFMCu 10PASS-TS
        PMEs (modems).

        This table contains live data from the equipment. As such,
        it is not persistent."
      ::= { efmCuPme10P 2 }

    efmCuPme10PStatusEntry OBJECT-TYPE
      SYNTAX      EfmCuPme10PStatusEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
        "An entry in the EFMCu 10PASS-TS PME Status table."
      INDEX  { ifIndex }
      ::= { efmCuPme10PStatusTable 1 }

    EfmCuPme10PStatusEntry ::=
      SEQUENCE {
        efmCuPme10PFECCorrectedBlocks     Counter32,
        efmCuPme10PFECUncorrectedBlocks   Counter32
      }
```

```
 efmCuPme10PFECCorrectedBlocks  OBJECT-TYPE
   SYNTAX      Counter32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "The number of received and corrected Forward Error Correction
     (FEC) codewords in this 10PASS-TS PME.

     This object maps to the aPMEFECCorrectedBlocks attribute in
     Clause 30.

     If a Clause 45 MDIO Interface to the PMA/PMD is present,
     then this object maps to the 10P FEC correctable errors
     register.

     Discontinuities in the value of this counter can occur at
     re-initialization of the management system, and at other times
     as indicated by the value of ifCounterDiscontinuityTime,
     defined in IF-MIB."
   REFERENCE
     "IEEE Std 802.3, 45.2.1.25, 30.11.2.1.8"
   ::= { efmCuPme10PStatusEntry 1 }

 efmCuPme10PFECUncorrectedBlocks  OBJECT-TYPE
   SYNTAX      Counter32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "The number of received uncorrectable FEC codewords in this
     10PASS-TS PME.

     This object maps to the aPMEFECUncorrectableBlocks attribute
     in Clause 30.

     If a Clause 45 MDIO Interface to the PMA/PMD is present,
     then this object maps to the 10P FEC uncorrectable errors
     register.

     Discontinuities in the value of this counter can occur at
     re-initialization of the management system, and at other times
     as indicated by the value of ifCounterDiscontinuityTime,
     defined in IF-MIB."
   REFERENCE
     "IEEE Std 802.3, 45.2.1.26, 30.11.2.1.9"
   ::= { efmCuPme10PStatusEntry 2 }

--
-- Conformance statements
--

 efmCuGroups      OBJECT IDENTIFIER ::= { efmCuConformance 1 }

 efmCuCompliances OBJECT IDENTIFIER ::= { efmCuConformance 2 }

 -- Object Groups

 efmCuBasicGroup OBJECT-GROUP
   OBJECTS {
     efmCuPAFSupported,
```

```
    efmCuAdminProfile,
    efmCuTargetDataRate,
    efmCuTargetSnrMgn,
    efmCuAdaptiveSpectra,
    efmCuPortSide,
    efmCuFltStatus
  }
  STATUS      current
  DESCRIPTION
    "A collection of objects representing management information
    common for all types of EFMCu ports."
  ::= { efmCuGroups 1 }

efmCuPAFGroup OBJECT-GROUP
  OBJECTS {
    efmCuPeerPAFSupported,
    efmCuPAFCapacity,
    efmCuPeerPAFCapacity,
    efmCuPAFAdminState,
    efmCuPAFDiscoveryCode,
    efmCuPAFRemoteDiscoveryCode,
    efmCuNumPMEs
  }
  STATUS      current
  DESCRIPTION
    "A collection of objects supporting optional PME
    Aggregation Function (PAF) and PAF discovery in EFMCu ports."
  ::= { efmCuGroups 2 }
efmCuPAFErrorsGroup OBJECT-GROUP
  OBJECTS {
    efmCuPAFInErrors,
    efmCuPAFInSmallFragments,
    efmCuPAFInLargeFragments,
    efmCuPAFInBadFragments,
    efmCuPAFInLostFragments,
    efmCuPAFInLostStarts,
    efmCuPAFInLostEnds,
    efmCuPAFInOverflows
  }
  STATUS      current
  DESCRIPTION
    "A collection of objects supporting optional error counters
    of PAF on EFMCu ports."
  ::= { efmCuGroups 3 }

efmCuPmeGroup OBJECT-GROUP
  OBJECTS {
    efmCuPmeAdminProfile,
    efmCuPmeOperStatus,
    efmCuPmeFltStatus,
    efmCuPmeSubTypesSupported,
    efmCuPmeAdminSubType,
    efmCuPmeOperSubType,
    efmCuPAFRemoteDiscoveryCode,
    efmCuPmeOperProfile,
    efmCuPmeSnrMgn,
    efmCuPmePeerSnrMgn,
    efmCuPmeLineAtn,
    efmCuPmePeerLineAtn,
```

```
      efmCuPmeEquivalentLength,
      efmCuPmeTCCodingErrors,
      efmCuPmeTCCrcErrors,
      efmCuPmeThreshLineAtn,
      efmCuPmeThreshSnrMgn
    }
    STATUS      current
    DESCRIPTION
      "A collection of objects providing information about
      a 2BASE-TL/10PASS-TS PME."
    ::= { efmCuGroups 4 }

  efmCuAlarmConfGroup OBJECT-GROUP
    OBJECTS {
      efmCuThreshLowRate,
      efmCuLowRateCrossingEnable,
      efmCuPmeThreshLineAtn,
      efmCuPmeLineAtnCrossingEnable,
      efmCuPmeThreshSnrMgn,
      efmCuPmeSnrMgnCrossingEnable,
      efmCuPmeDeviceFaultEnable,
      efmCuPmeConfigInitFailEnable,
      efmCuPmeProtocolInitFailEnable
    }
    STATUS      current
    DESCRIPTION
      "A collection of objects supporting configuration of alarm
      thresholds and notifications in EFMCu ports."
    ::= { efmCuGroups 5 }

  efmCuNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS {
      efmCuLowRateCrossing,
      efmCuPmeLineAtnCrossing,
      efmCuPmeSnrMgnCrossing,
      efmCuPmeDeviceFault,
      efmCuPmeConfigInitFailure,
      efmCuPmeProtocolInitFailure
    }
    STATUS      current
    DESCRIPTION
      "This group supports notifications of significant conditions
      associated with EFMCu ports."
    ::= { efmCuGroups 6 }

  efmCuPme2BProfileGroup OBJECT-GROUP
    OBJECTS {
      efmCuPme2BProfileDescr,
      efmCuPme2BRegion,
      efmCuPme2BsMode,
      efmCuPme2BMinDataRate,
      efmCuPme2BMaxDataRate,
      efmCuPme2BPower,
      efmCuPme2BConstellation,
      efmCuPme2BProfileRowStatus,
      efmCuPme2BsModeDescr,
      efmCuPme2BsModeRowStatus,
      efmCuPme2BEquivalentLength,
      efmCuPme2BMaxDataRatePam16,
```

```
      efmCuPme2BMaxDataRatePam32,
      efmCuPme2BReachRateRowStatus
    }
    STATUS      current
    DESCRIPTION
      "A collection of objects that constitute a configuration
      profile for configuration of 2BASE-TL ports."
    ::= { efmCuGroups 7}

  efmCuPme10PProfileGroup OBJECT-GROUP
    OBJECTS {
      efmCuPme10PProfileDescr,
      efmCuPme10PBandplanPSDMskProfile,
      efmCuPme10PUPBOReferenceProfile,
      efmCuPme10PBandNotchProfiles,
      efmCuPme10PPayloadDRateProfile,
      efmCuPme10PPayloadURateProfile,
      efmCuPme10PProfileRowStatus
    }
    STATUS  current
    DESCRIPTION
      "A collection of objects that constitute a configuration
      profile for configuration of 10PASS-TS ports."
    ::= { efmCuGroups 8 }

  efmCuPme10PStatusGroup OBJECT-GROUP
    OBJECTS {
      efmCuPme10PFECCorrectedBlocks,
      efmCuPme10PFECUncorrectedBlocks
    }
    STATUS  current
    DESCRIPTION
      "A collection of objects providing status information
      specific to 10PASS-TS PMEs."
    ::= { efmCuGroups 9 }

 -- Compliance statements

  efmCuCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
      "The compliance statement for 2BASE-TL/10PASS-TS interfaces.
      Compliance with the following external compliance statements
      is required:

      MIB module             Compliance Statement
      ----------             --------------------
      IF-MIB                 ifCompliance3
      IEEE8023-EtherLike-MIB dot3Compliance2
      MAU-MIB                mauModIfCompl3

      Compliance with the following external compliance statements
      is optional for implementations supporting PME Aggregation
      Function (PAF) with flexible cross-connect between the PCS
      and PME ports:

      MIB module             Compliance Statement
      ----------             --------------------
      IF-INVERTED-STACK-MIB  ifInvCompliance
```

```
            IF-CAP-STACK-MIB       ifCapStackCompliance"

        MODULE  -- this module
          MANDATORY-GROUPS {
            efmCuBasicGroup,
            efmCuPmeGroup,
            efmCuAlarmConfGroup,
            efmCuNotificationGroup
          }

          GROUP       efmCuPme2BProfileGroup
          DESCRIPTION
            "Support for this group is only required for implementations
            supporting 2BASE-TL PHY."

          GROUP       efmCuPme10PProfileGroup
          DESCRIPTION
            "Support for this group is only required for implementations
            supporting 10PASS-TS PHY."

          GROUP       efmCuPAFGroup
          DESCRIPTION
            "Support for this group is only required for
            implementations supporting PME Aggregation Function (PAF)."

          GROUP       efmCuPAFErrorsGroup
          DESCRIPTION
            "Support for this group is optional for implementations
            supporting PME Aggregation Function (PAF)."

          GROUP       efmCuPme10PStatusGroup
          DESCRIPTION
            "Support for this group is optional for implementations
            supporting 10PASS-TS PHY."

          OBJECT      efmCuPmeSubTypesSupported
          SYNTAX      BITS {
            ieee2BaseTLO(0),
            ieee2BaseTLR(1),
            ieee10PassTSO(2),
            ieee10PassTSR(3)
          }
          DESCRIPTION
            "Support for all subtypes is not required. However, at
            least one value shall be supported."

          OBJECT      efmCuPmeAdminSubType
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is not required (needed only for PMEs
            supporting more than a single subtype, e.g.,
            ieee2BaseTLO and ieee2BaseTLR or ieee10PassTSO and
            ieee10PassTSR)."

          OBJECT      efmCuTargetSnrMgn
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is optional. For PHYs without write access,
            the target SNR margin shall be fixed at 5dB for 2BASE-TL
```

```
            and 6dB for 10PASS-TS."

          OBJECT      efmCuAdaptiveSpectra
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is optional. For PHYs without write access,
            the default value should be false."

        ::= { efmCuCompliances 1 }
   END
```

12. Ethernet wide area network (WAN) interface sublayer (WIS) MIB module

This clause defines a portion of the MIB for use with SNMP. In particular, it defines objects for managing IEEE 802.3 WAN interface sublayers.

12.1 Overview

The objects defined in this clause are used in conjunction with objects defined in the Interfaces Group MIB in IETF RFC 2863, the SONET/SDH Interface MIB in IETF RFC 3592, and the IEEE 802.3 MAU MIB defined in Clause 13 of this document to manage the Ethernet WAN interface sublayer (WIS) defined in IEEE Std 802.3. The WIS contains functions to perform OC-192c/VC-4-64c framing and scrambling. It resides between the Physical Coding Sublayer (PCS) and the Physical Medium Attachment (PMA) sublayer within a 10GBASE-W 10 Gb/s WAN-compatible Physical Layer device (PHY) and may be used in conjunction with any of the PCS, PMA, and physical medium dependent (PMD) sublayers defined in IEEE Std 802.3 for 10GBASE-W PHYs. Three types of 10GBASE-W PHYs are defined, distinguished by the type of optics employed: 10GBASE-SW, 10GBASE-LW, and 10GBASE-EW. The objects defined in this clause may be used to manage an Ethernet interface employing any type of 10GBASE-W PHY. They do not apply to any other kind of interface. In particular, they do not apply to so-called Ethernet line terminating equipment (ELTE) residing within a SONET network element that uses the 10GBASE-W PMA/PMD sublayers but otherwise acts as SONET line terminating equipment (LTE).

The objects presented here—along with those incorporated by reference from the Interfaces Group MIB, the SONET/SDH Interface MIB, and the IEEE 802.3 MAU MIB—are intended to provide exact representations of the mandatory attributes in the oWIS managed object class (i.e., the members of the pWISBasic package) defined in Clause 30 of IEEE Std 802.3. They are also intended to provide approximate representations of the optional attributes (i.e., the members of the pWISOptional package). Some objects with no analogs in oWIS are defined to support WIS testing features required by Clause 50 of IEEE Std 802.3.

12.1.1 Relationship to the SONET/SDH interface MIB

Since the Ethernet WAN interface sublayer was designed to be SONET-compatible, information similar to that provided by most of the members of the oWIS managed object class is available from objects defined in the SONET-MIB in IETF RFC 3592. Thus, the MIB module defined in this clause is a sparse augmentation of the SONET-MIB—in other words, every table defined here is an extension of some table in the SONET-MI—and its compliance statement REQUIRES that an agent implementing the objects defined in this clause also implement the relevant SONET-MIB objects. That includes all objects required by sonetCompliance2 as well as some that it leaves optional.

It should be noted that some of the objects incorporated by reference from the SONET-MIB—specifically, the threshold objects and interval counter objects—provide only approximate representations of the corresponding oWIS attributes, as detailed in 12.1.6. An alternative approach would have been to define new objects to exactly match the oWIS definitions. That approach was rejected because the SONET-MIB objects are already used in deployed systems to manage the SONET sublayers of ATM over SONET and PPP over SONET interfaces, and it was deemed undesirable to use a different scheme to manage the SONET sublayers of 10 Gb/s WAN-compatible Ethernet interfaces. Note that the approach adopted by this clause requires no hardware support beyond that mandated by 50.3.11 of IEEE Std 802.3.

12.1.2 Relationship to the Ethernet-like interface MIB

An interface that includes the Ethernet WIS is, by definition, an Ethernet-like interface, and an agent implementing the objects defined in this clause shall also implement the objects required by the Ethernet-like interface MIB module defined in Clause 10.

12.1.3 Relationship to the IEEE 802.3 MAU MIB

Support for the mauModIfCompl3 compliance statement of the MAU-MIB module defined in Clause 13 is required for all Ethernet-like interfaces. The MAU-MIB module is needed in order to allow applications to control and/or determine the media type in use; this is important for devices that can support both the 10GBASE-R 10 Gb/s LAN format (which does not include the WIS) and the 10GBASE-W 10 Gb/s WAN format (which does include the WIS). The MAU-MIB module also provides the means to put a device in standby mode or to reset it; the latter may be used to re-initialize the WIS.

12.1.4 Use of the ifTable

This subclause specifies how the ifTable, as defined in IETF RFC 2863, is used for the Ethernet WIS application.

12.1.4.1 Layering model

Ethernet interfaces that employ the WIS are layered as defined in IEEE Std 802.3. The corresponding use of the ifTable defined in IETF RFC 2863 is shown in Figure 12-1.



Figure 12-1—Use of ifTable for an Ethernet WIS port

The exact configuration and multiplexing of the layers is maintained in the ifStackTable in IETF RFC 2863 and in the ifInvStackTable in IETF RFC 2864.

12.1.4.2 Use of ifTable for LLC layer/MAC sublayer/reconciliation sublayer/physical coding sublayer

The ifTable shall be used as specified in Clause 10 and Clause 13 for the LLC Layer/MAC sublayer/reconciliation sublayer/physical coding sublayer.

12.1.4.3 Use of ifTable for SONET/SDH path layer

The ifTable shall be used as specified in IETF RFC 3592 for the SONET/SDH path layer. The value of ifHighSpeed is set to 9585. ifSpeed reports a value of 4294967295.

12.1.4.4 Use of ifTable for SONET/SDH medium/section/line layer

The ifTable shall be used as specified in IETF RFC 3592 for the SONET/SDH Medium/Section/Line Layer. The value of ifHighSpeed is set to 9953. ifSpeed reports a value of 4294967295.

12.1.5 SONET/SDH terminology

The SONET/SDH terminology used in IEEE Std 802.3 is mostly the same as in IETF RFC 3592, but there are a few differences. In those cases, the definitions in Clause 3 take precedence.

12.1.6 Mapping of IEEE 802.3 managed objects

Table 12-1 contains the mapping between oWIS managed objects in the pWIS Basic package defined in IEEE Std 802.3 and managed objects defined in this clause and in associated MIB modules, i.e., the IF-MIB in IETF RFC 2863, the SONET-MIB in IETF RFC 3592, and the IEEE 802.3 MAU-MIB module defined in Clause 13 of this document.

Table 12-1—Mapping of IEEE 802.3 managed objects (pWIS Basic package)

IEEE 802.3 managed object		Corresponding SNMP object
oWIS - pWISBasic package	aWISID	IF-MIB - ifIndex
	aSectionStatus	SONET-MIB - sonetSectionCurrentStatus
	aLineStatus	SONET-MIB - sonetLineCurrentStatus
	aPathStatus	etherWisPathCurrentStatus
	aFarEndPathStatus	etherWisFarEndPathCurrentStatus

The Unequipped defect is not defined by IEEE Std 802.3.

Table 12-2 contains the same mapping information for the pWIS optional package.

The threshold and counter objects imported from the SONET-MIB are not completely equivalent to the corresponding IEEE 802.3 objects. The specific differences are presented in Table 12-3. Despite the semantic differences between the threshold objects and counter objects imported from the SONET-MIB and the corresponding IEEE 802.3 objects, the hardware support mandated by 50.3.11 of IEEE Std 802.3 suffices for both. See Annex 12A for details.

Table 12-2—Mapping of IEEE 802.3 managed objects (pWIS optional package)

IEEE 802.3 managed object		Corresponding SNMP object
oWIS – pWISOptional package	aSectionSESThreshold	SONET-MIB – sonetSESthresholdSe
	aSectionSESs	SONET-MIB – sonetSectionCurrentSESs + sonetSectionIntervalSESs
	aSectionESs	SONET-MIB – sonetSectionCurrentESs + sonetSectionIntervalESs
	aSectionSEFSs	SONET-MIB – sonetSectionCurrentSEFSs + sonetSectionIntervalSEFSs
	aSectionCVs	SONET-MIB – sonetSectionCurrentCVs + sonetSectionIntervalCVs
	aJ0ValueTX	etherWisSectionCurrentJ0Transmitted
	aJ0ValueRX	etherWisSectionCurrentJ0Received
	aLineSESThreshold	SONET-MIB – sonetSESthresholdSet
	aLineSESs	SONET-MIB – sonetLineCurrentSESs + sonetLineIntervalSESs
	aLineESs	SONET-MIB – sonetLineCurrentESs + sonetLineIntervalESs
	aLineCVs	SONET-MIB – sonetLineCurrentCVs + sonetLineIntervalCVs
	aFarEndLineSESs	SONET-MIB – sonetFarEndLineCurrentSESs + sonetFarEndLineIntervalSESs
	aFarEndLineESs	SONET-MIB – sonetFarEndLineCurrentESs + sonetFarEndLineIntervalESs
	aFarEndLineCVs	SONET-MIB – sonetFarEndLineCurrentCVs + sonetFarEndLineIntervalCVs
	aPathSESThreshold	SONET-MIB – sonetSESthresholdSet
	aPathSESs	SONET-MIB – sonetPathCurrentSESs + sonetPathIntervalSESs
	aPathESs	SONET-MIB – sonetPathCurrentESs + sonetPathIntervalESs
	aPathCVs	SONET-MIB – sonetPathCurrentCVs + sonetPathIntervalCVs
	aJ1ValueTX	etherWisPathCurrentJ1Transmitted

Table 12-2—Mapping of IEEE 802.3 managed objects (pWIS optional package) *(continued)*

IEEE 802.3 managed object		Corresponding SNMP object
oWIS - pWISOptional package (continued)	aJ1ValueRX	etherWisPathCurrentJ1Received
	aFarEndPathSESs	SONET-MIB – sonetFarEndPathCurrentSESs + sonetFarEndPathIntervalSESs
	aFarEndPathESs	SONET-MIB – sonetFarEndPathCurrentESs + sonetFarEndPathIntervalESs
	aFarEndPathCVs	SONET-MIB – sonetFarEndPathCurrentCVs + sonetFarEndPathIntervalCVs

Table 12-3—IEEE 802.3 managed object and SNMP object differences

IEEE 802.3 managed object	How corresponding SNMP object differs
aSectionSESThreshold	This object is defined in IEEE Std 802.3 as an integer with one instance per interface. sonetSESthresholdSet is an enumerated value that has one instance per network element; it controls the thresholds for all layers simultaneously and allows only certain discrete values to be selected.
aSectionSESs	This object is defined in IEEE Std 802.3 as a generalized nonresettable counter. The objects sonetSectionCurrentSESs and sonetSectionIntervalSESs are 15-minute interval counters.
aSectionESs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3. The objects sonetSectionCurrentESs and sonetSectionIntervalESs are 15-minute interval counters.
aSectionSEFSs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3. The objects sonetSectionCurrentSEFSs and sonetSectionIntervalSEFSs are 15-minute interval counters.
aSectionCVs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetSectionCurrentCVs and sonetSectionIntervalCVs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify as severely errored seconds.
aLineSESThreshold	This object is defined in IEEE Std 802.3 as an integer with one instance per interface. sonetSESthresholdSet is an enumerated value that has one instance per network element; it controls the thresholds for all layers simultaneously and allows only certain discrete values to be selected.
aLineSESs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetLineCurrentSESs and sonetLineIntervalSESs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify as unavailable seconds.
aLineESs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetLineCurrentESs and sonetLineIntervalESs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify as unavailable seconds.

Table 12-3—IEEE 802.3 managed object and SNMP object differences *(continued)*

IEEE 802.3 managed object	How corresponding SNMP object differs
aLineCVs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetLineCurrentCVs and sonetLineIntervalCVs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify either as severely errored seconds or as unavailable seconds.
aFarEndLineSESs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetFarEndLineCurrentSESs and sonetFarEndLineIntervalSESs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify as unavailable seconds.
aFarEndLineESs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetFarEndLineCurrentESs and sonetFarEndLineIntervalESs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify as unavailable seconds.
aFarEndLineCVs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetFarEndLineCurrentCVs and sonetFarEndLineIntervalCVs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify either as severely errored seconds or as unavailable seconds.
aPathSESThreshold	This object is defined in IEEE Std 802.3 as an integer with one instance per interface. sonetSESthresholdSet is an enumerated value that has one instance per network element; it controls the thresholds for all layers simultaneously and allows only certain discrete values to be selected.
aPathSESs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetPathCurrentSESs and sonetPathIntervalSESs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify as unavailable seconds. In addition, IEEE Std 802.3 includes PLM-P and LCD-P defects in the criteria for declaring path layer severely errored seconds, while IETF RFC 3592 does not.
aPathESs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetPathCurrentESs and sonetPathIntervalESs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify as unavailable seconds. In addition, IEEE Std 802.3 includes PLM-P and LCD-P defects in the criteria for declaring path layer errored seconds, while IETF RFC 3592 does not.
aPathCVs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetPathCurrentCVs and sonetPathIntervalCVs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify either as severely errored seconds or as unavailable seconds.

Table 12-3—IEEE 802.3 managed object and SNMP object differences *(continued)*

IEEE 802.3 managed object	How corresponding SNMP object differs
aFarEndPathSESs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetFarEndPathCurrentSESs and sonetFarEndPathIntervalSESs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify as unavailable seconds. In addition, IEEE Std 802.3 includes far-end PLM-P and LCD-P defects in the criteria for declaring far-end path layer severely errored seconds, while IETF RFC 3592 does not.
aFarEndPathESs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetFarEndPathCurrentESs and sonetFarEndPathIntervalESs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify as unavailable seconds. In addition, IEEE Std 802.3 includes far-end PLM-P and LCD-P defects in the criteria for declaring far-end path layer errored seconds, while IETF RFC 3592 does not.
aFarEndPathCVs	This object is defined as a generalized nonresettable counter in IEEE Std 802.3, and it is not subject to inhibiting. The objects sonetFarEndPathCurrentCVs and sonetFarEndPathIntervalCVs are 15-minute interval counters, and they are inhibited (not incremented) during 1-second intervals that qualify either as severely errored seconds or as unavailable seconds.

12.1.7 Mapping of SNMP objects to WIS station management registers

Some of the objects defined in this clause or incorporated by reference from the SONET-MIB IETF RFC 3592, or the MAU-MIB module defined in Clause 13 require WIS-specific hardware support. Subclause 50.3.11 of IEEE Std 802.3 specifies WIS management interface requirements, including a required subset of the WIS Management Data Input/Output (MDIO) registers defined in 45.2.2 of IEEE Std 802.3. Table 12-4 provides a cross-reference between those managed objects and the WIS MDIO registers from the subset in 50.3.11 of IEEE Std 802.3 required to support them. Note that the MDIO interface is optional; however, if it is not implemented, then the capabilities of the required register subset shall be provided by other means.

Table 12-4—Cross-reference between SNMP objects and WIS MDIO registers

SMNP object	WIS MDIO register(s)
ETHER-WIS - etherWisDeviceTxTestPatternMode	10G WIS control 2
ETHER-WIS - etherWisDeviceRxTestPatternMode	10G WIS control 2
ETHER-WIS - etherWisDeviceRxTestPatternErrors	10G WIS test pattern error counter
SONET-MIB - sonetMediumType	None required
SONET-MIB - sonetMediumTimeElapsed	None required
SONET-MIB - sonetMediumValidIntervals	None required
SONET-MIB - sonetMediumLineCoding	None required
SONET-MIB - sonetMediumLineType	None required

Table 12-4—Cross-reference between SNMP objects and WIS MDIO registers *(continued)*

<table>
<tr><th>SMNP object</th><th>WIS MDIO register(s)</th></tr>
<tr><td>SONET-MIB - sonetMediumCircuitIdentifier</td><td>None required</td></tr>
<tr><td>SONET-MIB - sonetMediumInvalidIntervals</td><td>None required</td></tr>
<tr><td>SONET-MIB - sonetMediumLoopbackConfig</td><td>None required</td></tr>
<tr><td>SONET-MIB - sonetSESthresholdSet</td><td>None required</td></tr>
<tr><td>ETHER-WIS - etherWisSectionCurrentJ0Transmitted</td><td>10G WIS J0 transmit</td></tr>
<tr><td>ETHER-WIS - etherWisSectionCurrentJ0Received</td><td>10G WIS J0 receive</td></tr>
<tr><td>SONET-MIB - sonetSectionCurrentStatus</td><td>10G WIS status 3</td></tr>
<tr><td>SONET-MIB - sonetSectionCurrentESs</td><td rowspan="8">10G WIS status 3
+
10G WIS section
BIP error count</td></tr>
<tr><td>SONET-MIB - sonetSectionCurrentSESs</td></tr>
<tr><td>SONET-MIB - sonetSectionCurrentSEFSs</td></tr>
<tr><td>SONET-MIB - sonetSectionCurrentCVs</td></tr>
<tr><td>SONET-MIB - sonetSectionIntervalESs</td></tr>
<tr><td>SONET-MIB - sonetSectionIntervalSESs</td></tr>
<tr><td>SONET-MIB - sonetSectionIntervalSEFSs</td></tr>
<tr><td>SONET-MIB - sonetSectionIntervalCVs</td></tr>
<tr><td>SONET-MIB - sonetSectionIntervalValidData</td><td>None required</td></tr>
<tr><td>SONET-MIB - sonetLineCurrentStatus</td><td>10G WIS status 3</td></tr>
<tr><td>SONET-MIB - sonetLineCurrentESs</td><td rowspan="8">10G WIS status 3
+
10G WIS line
BIP errors</td></tr>
<tr><td>SONET-MIB - sonetLineCurrentSESs</td></tr>
<tr><td>SONET-MIB - sonetLineCurrentCVs</td></tr>
<tr><td>SONET-MIB - sonetLineCurrentUASs</td></tr>
<tr><td>SONET-MIB - sonetLineIntervalESs</td></tr>
<tr><td>SONET-MIB - sonetLineIntervalSESs</td></tr>
<tr><td>SONET-MIB - sonetLineIntervalCVs</td></tr>
<tr><td>SONET-MIB - sonetLineIntervalUASs</td></tr>
<tr><td>SONET-MIB - sonetLineIntervalValidData</td><td>None required</td></tr>
</table>

Table 12-4—Cross-reference between SNMP objects and WIS MDIO registers *(continued)*

SMNP object	WIS MDIO register(s)
SONET-MIB - sonetFarEndLineCurrentESs	10G WIS status 3 + 10G WIS far end line BIP errors
SONET-MIB - sonetFarEndLineCurrentSESs	
SONET-MIB - sonetFarEndLineCurrentCVs	
SONET-MIB - sonetFarEndLineCurrentUASs	
SONET-MIB - sonetFarEndLineIntervalESs	
SONET-MIB - sonetFarEndLineIntervalSESs	
SONET-MIB - sonetFarEndLineIntervalCVs	
SONET-MIB - sonetFarEndLineIntervalUASs	
SONET-MIB - sonetFarEndLineIntervalValidData	10G WIS status 3
ETHER-WIS - etherWisPathCurrentStatus	10G WIS status 3
ETHER-WIS - etherWisPathCurrentJ1Transmitted	10G WIS J1 transmit
ETHER-WIS - etherWisPathCurrentJ1Received	10G WIS J1 receive
SONET-MIB - sonetPathCurrentWidth	None required
SONET-MIB - sonetPathCurrentStatus	10G WIS status 3
SONET-MIB - sonetPathCurrentESs	10G WIS status 3 + 10G WIS path block error count
SONET-MIB - sonetPathCurrentSESs	
SONET-MIB - sonetPathCurrentCVs	
SONET-MIB - sonetPathCurrentUASs	
SONET-MIB - sonetPathIntervalESs	
SONET-MIB - sonetPathIntervalCVs	
SONET-MIB - sonetPathIntervalUASs	
SONET-MIB - sonetPathIntervalValidData	None required
ETHER-WIS - etherWisFarEndPathCurrentStatus	10G WIS status 3

Table 12-4—Cross-reference between SNMP objects and WIS MDIO registers *(continued)*

SMNP object	WIS MDIO register(s)
SONET-MIB - sonetFarEndPathCurrentESs	10G WIS status 3 + 10G WIS far end path block error count
SONET-MIB - sonetFarEndPathCurrentSESs	
SONET-MIB - sonetFarEndPathCurrentCVs	
SONET-MIB - sonetFarEndPathCurrentUASs	
SONET-MIB - sonetFarEndPathIntervalESs	
SONET-MIB - sonetFarEndPathIntervalSESs	
SONET-MIB - sonetFarEndPathIntervalCVs	
SONET-MIB - sonetFarEndPathIntervalUASs	
SONET-MIB - sonetFarEndPathIntervalValidData	
MAU-MIB - ifMauIfIndex	None required
MAU-MIB - ifMauIndex	None required
MAU-MIB - ifMauType	10G WIS control 2
MAU-MIB - ifMauStatus	WIS control 1
MAU-MIB - ifMauMediaAvailable	WIS status 1 + 10G WIS status 3
MAU-MIB - ifMauMediaAvailableStateExits	
MAU-MIB - ifMauJabberState	None required
MAU-MIB - ifMauJabberingStateEnters	None required
MAU-MIB - ifMauFalseCarriers	None required
MAU-MIB - ifMauDefaultType	10G WIS control 2
MAU-MIB - ifMauAutoNegSupported	none required
MAU-MIB - ifMauTypeListBits	10G WIS status 2

12.1.8 Structure of the MIB module

Four tables are defined in this MIB module.

12.1.8.1 etherWisDeviceTable

The purpose of this table is to define managed objects to control the WIS test pattern mode. These objects are required to support mandatory and optional WIS test features specified in 50.3.8 of IEEE Std 802.3.

The etherWisDeviceTable is a sparse augmentation of the sonetMediumTable of the SONET-MIB; in other words, for each entry in the etherWisDeviceTable, there shall be an entry in the sonetMediumTable and the same ifIndex value shall be used for both entries.

12.1.8.2 etherWisSectionCurrentTable

The purpose of this table is to define managed objects for the transmitted and received section trace messages (J0 byte).

The etherWisSectionCurrentTable is a sparse augmentation of the sonetSectionCurrentTable of the SONET-MIB; in other words, for each entry in the etherWisSectionCurrentTable, there shall be an entry in the sonetSectionCurrentTable and the same ifIndex value shall be used for both entries.

12.1.8.3 etherWisPathCurrentTable

The purpose of this table is to define managed objects for the current WIS path layer status and for the transmitted and received path trace messages (J1 byte). The path layer status object is provided because the WIS supports some near-end path status conditions that are not reported in sonetPathCurrentStatus.

The etherWisPathCurrentTable is a sparse augmentation of the sonetPathCurrentTable of the SONET-MIB; in other words, for each entry in the etherWisPathCurrentTable, there shall be an entry in the sonetPathCurrentTable and the same ifIndex value shall be used for both entries.

12.1.8.4 etherWisFarEndPathCurrentTable

The purpose of this table is to define a managed object for the current status of the far end of the path. This object is provided because the WIS supports some far-end path status conditions that are not reported in sonetPathCurrentStatus.

The etherWisFarEndPathCurrentTable is a sparse augmentation of the sonetFarEndPathCurrentTable of the SONET-MIB; in other words, for each entry in the etherWisFarEndPathCurrentTable, there shall be an entry in the sonetFarEndPathCurrentTable and the same ifIndex value shall be used for both entries.

12.2 Security considerations for Ethernet wide area network (WAN) interface sublayer (WIS) MIB module

There are five managed objects defined in this MIB module that have a MAX-ACCESS clause of read-write: (1) etherWisDeviceTxTestPatternMode, (2) etherWisDeviceRxTestPatternMode, (3) etherWisDeviceRxTest PatternErrors, (4) etherWisSectionCurrentJ0Transmitted, and (5) etherWisPathCurrentJ1Transmitted. Writing to these objects can have the following potentially disruptive effects on network operation:

- Changing the transmit or receive test pattern mode or modifying the accumulated error count from a PRBS31 pattern test on an administratively disabled 10GBASE-W interface, which can interfere with an in-progress pattern test.
- Modifying the transmitted section trace and/or path trace message on an operational 10GBASE-W interface, which can cause connectivity alarms to be raised at the remote of the link.

The user of this MIB module should therefore be aware that support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

The readable objects in this MIB module (i.e., those with MAX-ACCESS other than not-accessible) may be considered sensitive in some environments since, collectively, they provide information about the performance of network interfaces and can reveal some aspects of their configuration. In such environments it is important to control GET and NOTIFY access to these objects and possibly to encrypt their values when sending them over the network via SNMP.

12.3 MIB module definition

An ASCII text version of the MIB definition can be found at the following URL[20]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C12mib.txt

[20]Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.

```
IEEE8023-ETHER-WIS-MIB DEFINITIONS ::= BEGIN

   IMPORTS
       MODULE-IDENTITY, OBJECT-TYPE,
       Gauge32, org
           FROM SNMPv2-SMI
       ifIndex
           FROM IF-MIB
       MODULE-COMPLIANCE, OBJECT-GROUP
           FROM SNMPv2-CONF
       sonetMediumStuff2, sonetSectionStuff2,
       sonetLineStuff2, sonetFarEndLineStuff2,
       sonetPathStuff2, sonetFarEndPathStuff2,
       sonetMediumType, sonetMediumLineCoding,
       sonetMediumLineType, sonetMediumCircuitIdentifier,
       sonetMediumLoopbackConfig, sonetSESthresholdSet,
       sonetPathCurrentWidth
           FROM SONET-MIB;

   ieee8023etherWisMIB MODULE-IDENTITY
        LAST-UPDATED "201304110000Z" -- April 11, 2013
        ORGANIZATION
          "IEEE 802.3 working group"
        CONTACT-INFO
            "WG-URL: http://www.ieee802.org/3/index.html
            WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

            Contact: Howard Frazier
            Postal:  3151 Zanker Road
                     San Jose, CA 95134
                     USA
            Tel:     +1.408.922.8164
            E-mail:  hfrazier@broadcom.com"
DESCRIPTION
         "The objects in this MIB module are used in conjunction
         with objects in the SONET-MIB module and the MAU-MIB module to manage
         the Ethernet WAN Interface Sublayer (WIS) defined in
         IEEE Std 802.3.

         Of particular interest are Clause 50, ‘WAN Interface
         Sublayer (WIS), type 10GBASE-W’, Clause 30, ‘10 Mb/s,
         100 Mb/s, 1000 Mb/s, and 10 Gb/s Management, and Link
         Aggregation Management’, and Clause 45, ‘Management
         Data Input/Output (MDIO) Interface’."

       REVISION "201304110000Z" -- April 11, 2013
       DESCRIPTION
            "Revision, based on an earlier version in IEEE Std 802.3.1-2011."

       REVISION "201102020000Z" -- February 2, 2011
       DESCRIPTION
            "Initial version, based on an earlier version published
             as RFC 3637."

           ::= { org ieee(111) standards-association-numbers-series-standards(2)
                 lan-man-stds(802) ieee802dot3(3) ieee802dot3dot1mibs(1) 12 }


   -- The main sections of the module
```

```
etherWisObjects     OBJECT IDENTIFIER ::= { ieee8023etherWisMIB 1 }

etherWisObjectsPath OBJECT IDENTIFIER ::= { ieee8023etherWisMIB 2 }

etherWisConformance OBJECT IDENTIFIER ::= { ieee8023etherWisMIB 3 }

-- groups in the Ethernet WIS MIB module

etherWisDevice      OBJECT IDENTIFIER ::= { etherWisObjects 1 }

etherWisSection     OBJECT IDENTIFIER ::= { etherWisObjects 2 }

etherWisPath        OBJECT IDENTIFIER ::= { etherWisObjectsPath 1 }

etherWisFarEndPath  OBJECT IDENTIFIER ::= { etherWisObjectsPath 2 }

-- The Device group

-- These objects provide WIS extensions to
-- the SONET-MIB Medium Group.

etherWisDeviceTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF EtherWisDeviceEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
       "The table for Ethernet WIS devices"
     ::= { etherWisDevice 1 }

etherWisDeviceEntry OBJECT-TYPE
    SYNTAX  EtherWisDeviceEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
       "An entry in the Ethernet WIS device table. For each
       instance of this object there shall be a corresponding
       instance of sonetMediumEntry."
    INDEX  { ifIndex }
     ::= { etherWisDeviceTable 1 }

EtherWisDeviceEntry ::=
    SEQUENCE {
        etherWisDeviceTxTestPatternMode     INTEGER,
        etherWisDeviceRxTestPatternMode     INTEGER,
        etherWisDeviceRxTestPatternErrors   Gauge32
        }

etherWisDeviceTxTestPatternMode OBJECT-TYPE
    SYNTAX  INTEGER {
                none(1),
                squareWave(2),
                prbs31(3),
                mixedFrequency(4)
            }
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
       "This variable controls the transmit test pattern mode.
```

```
          The value none(1) puts the the WIS transmit path into
          the normal operating mode. The value squareWave(2) puts
          the WIS transmit path into the square wave test pattern
          mode described in IEEE Std 802.3, 50.3.8.1.
          The value prbs31(3) puts the WIS transmit path into the
          PRBS31 test pattern mode described in IEEE Std 802.3
          50.3.8.2. The value mixedFrequency(4) puts the
          WIS transmit path into the mixed frequency test pattern
          mode described in IEEE Std 802.3, 50.3.8.3.
          Any attempt to set this object to a value other than
          none(1) when the corresponding instance of ifAdminStatus
          has the value up(1) shall be rejected with the error
          inconsistentValue, and any attempt to set the corresponding
          instance of ifAdminStatus to the value up(1) when an
          instance of this object has a value other than none(1)
          shall be rejected with the error inconsistentValue."
       REFERENCE
          "IEEE Std 802.3, 50.3.8, WIS test pattern generator and
          checker, 45.2.2.6, 10G WIS control 2 register (2.7), and
          45.2.2.7.2, PRBS31 pattern testing ability (2.8.1)."
        ::= { etherWisDeviceEntry 1 }

   etherWisDeviceRxTestPatternMode OBJECT-TYPE
       SYNTAX  INTEGER {
                   none(1),
                   prbs31(3),
                   mixedFrequency(4)
               }
       MAX-ACCESS  read-write
       STATUS  current
       DESCRIPTION
          "This variable controls the receive test pattern mode.
          The value none(1) puts the the WIS receive path into the
          normal operating mode. The value prbs31(3) puts the WIS
          receive path into the PRBS31 test pattern mode described
          in IEEE Std 802.3, 50.3.8.2. The value
          mixedFrequency(4) puts the WIS receive path into the mixed
          frequency test pattern mode described in IEEE Std 802.3,
          50.3.8.3. Any attempt to set this object to a
          value other than none(1) when the corresponding instance
          of ifAdminStatus has the value up(1) shall be rejected with
          the error inconsistentValue, and any attempt to set the
          corresponding instance of ifAdminStatus to the value up(1)
          when an instance of this object has a value other than
          none(1) shall be rejected with the error inconsistentValue."
       REFERENCE
          "IEEE Std 802.3, 50.3.8, WIS test pattern generator and
          checker, 45.2.2.6, 10G WIS control 2 register (2.7), and
          45.2.2.7.2, PRBS31 pattern testing ability (2.8.1)."
        ::= { etherWisDeviceEntry 2 }

   etherWisDeviceRxTestPatternErrors OBJECT-TYPE
       SYNTAX  Gauge32 ( 0..65535 )
       MAX-ACCESS  read-write
       STATUS  current
       DESCRIPTION
          "This object counts the number of errors detected when the
          WIS receive path is operating in the PRBS31 test pattern
          mode. It is reset to zero when the WIS receive path
```

```
          initially enters that mode, and it increments each time
          the PRBS pattern checker detects an error as described in
          IEEE Std 802.3, 50.3.8.2 unless its value is
          65535, in which case it remains unchanged. This object is
          writeable so that it may be reset upon explicit request
          of a command generator application while the WIS receive
          path continues to operate in PRBS31 test pattern mode."
       REFERENCE
          "IEEE Std 802.3, 50.3.8, WIS test pattern generator and
          checker, 45.2.2.7.2, PRBS31 pattern testing ability
          (2.8.1), and 45.2.2.8, 10G WIS test pattern error counter
          register (2.9)."
        ::= { etherWisDeviceEntry 3 }
   -- The Section group

   -- These objects provide WIS extensions to
   -- the SONET-MIB Section Group.

   etherWisSectionCurrentTable OBJECT-TYPE
       SYNTAX  SEQUENCE OF EtherWisSectionCurrentEntry
       MAX-ACCESS  not-accessible
       STATUS  current
       DESCRIPTION
          "The table for the current state of Ethernet WIS sections."
        ::= { etherWisSection 1 }

   etherWisSectionCurrentEntry OBJECT-TYPE
       SYNTAX  EtherWisSectionCurrentEntry
       MAX-ACCESS  not-accessible
       STATUS  current
       DESCRIPTION
          "An entry in the etherWisSectionCurrentTable. For each
          instance of this object there shall be a corresponding
          instance of sonetSectionCurrentEntry."
       INDEX  { ifIndex }
        ::= { etherWisSectionCurrentTable 1 }

   EtherWisSectionCurrentEntry ::=
       SEQUENCE {
           etherWisSectionCurrentJ0Transmitted OCTET STRING,
           etherWisSectionCurrentJ0Received    OCTET STRING
           }

   etherWisSectionCurrentJ0Transmitted OBJECT-TYPE
       SYNTAX  OCTET STRING (SIZE (16))
       MAX-ACCESS  read-write
       STATUS  current
       DESCRIPTION
          "This is the 16-octet section trace message that
          is transmitted in the J0 byte. The value should
          be ‘89’h followed by fifteen octets of ‘00’h
          (or some cyclic shift thereof) when the section
          trace function is not used, and the implementation
          should use that value (or a cyclic shift thereof)
          as a default if no other value has been set."
       REFERENCE
          "IEEE Std 802.3, 30.8.1.1.8, aJ0ValueTX."
        ::= { etherWisSectionCurrentEntry 1 }
```

```
etherWisSectionCurrentJ0Received OBJECT-TYPE
    SYNTAX  OCTET STRING (SIZE (16))
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
       "This is the 16-octet section trace message that
       was most recently received in the J0 byte."
    REFERENCE
       "IEEE Std 802.3, 30.8.1.1.9, aJ0ValueRX."
     ::= { etherWisSectionCurrentEntry 2 }

-- The Path group

-- These objects provide WIS extensions to
-- the SONET-MIB Path Group.

etherWisPathCurrentTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF EtherWisPathCurrentEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
       "The table for the current state of Ethernet WIS paths."
     ::= { etherWisPath 1 }

etherWisPathCurrentEntry OBJECT-TYPE
    SYNTAX  EtherWisPathCurrentEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
       "An entry in the etherWisPathCurrentTable. For each
       instance of this object there shall be a corresponding
       instance of sonetPathCurrentEntry."
    INDEX  { ifIndex }
     ::= { etherWisPathCurrentTable 1 }

EtherWisPathCurrentEntry ::=
    SEQUENCE {
        etherWisPathCurrentStatus           BITS,
        etherWisPathCurrentJ1Transmitted    OCTET STRING,
        etherWisPathCurrentJ1Received       OCTET STRING
        }
etherWisPathCurrentStatus OBJECT-TYPE
    SYNTAX  BITS {
                etherWisPathLOP(0),
                etherWisPathAIS(1),
                etherWisPathPLM(2),
                etherWisPathLCD(3)
            }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
       "This variable indicates the current status of the
       path payload with a bit map that can indicate multiple
       defects at once. The bit positions are assigned as
       follows:

       etherWisPathLOP(0)
          This bit is set to indicate that an
          LOP-P (Loss of Pointer - Path) defect
```

```
              is being experienced. When this
              bit is set, sonetPathSTSLOP shall be set
              in the corresponding instance of
              sonetPathCurrentStatus.

           etherWisPathAIS(1)
              This bit is set to indicate that an
              AIS-P (Alarm Indication Signal - Path)
              defect is being experienced. When
              this bit is set, sonetPathSTSAIS shall be
              set in the corresponding instance of
              sonetPathCurrentStatus.

           etherWisPathPLM(1)
              This bit is set to indicate that a
              PLM-P (Payload Label Mismatch - Path)
              defect is being experienced. When
              this bit is set, sonetPathSignalLabelMismatch
              shall be set in the corresponding instance of
              sonetPathCurrentStatus.
           etherWisPathLCD(3)
              This bit is set to indicate that an
              LCD-P (Loss of Codegroup Delination - Path)
              defect is being experienced. Since this
              defect is detected by the PCS and not by
              the path layer itself, there is no
              corresponding bit in sonetPathCurrentStatus."
        REFERENCE
           "IEEE Std 802.3, 30.8.1.1.18, aPathStatus."
         ::= { etherWisPathCurrentEntry 1 }

    etherWisPathCurrentJ1Transmitted OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE (16))
        MAX-ACCESS  read-write
        STATUS  current
        DESCRIPTION
           "This is the 16-octet path trace message that
           is transmitted in the J1 byte. The value should
           be ‘89’h followed by fifteen octets of ‘00’h
           (or some cyclic shift thereof) when the path
           trace function is not used, and the implementation
           should use that value (or a cyclic shift thereof)
           as a default if no other value has been set."
        REFERENCE
           "IEEE Std 802.3, 30.8.1.1.23, aJ1ValueTX."
         ::= { etherWisPathCurrentEntry 2 }

    etherWisPathCurrentJ1Received OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE (16))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
           "This is the 16-octet path trace message that
           was most recently received in the J1 byte."
        REFERENCE
           "IEEE Std 802.3, 30.8.1.1.24, aJ1ValueRX."
         ::= { etherWisPathCurrentEntry 3 }
    -- The Far End Path group
```

```
-- These objects provide WIS extensions to
-- the SONET-MIB Far End Path Group.

etherWisFarEndPathCurrentTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF EtherWisFarEndPathCurrentEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
       "The table for the current far-end state of Ethernet WIS
       paths."
     ::= { etherWisFarEndPath 1 }

etherWisFarEndPathCurrentEntry OBJECT-TYPE
    SYNTAX  EtherWisFarEndPathCurrentEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
       "An entry in the etherWisFarEndPathCurrentTable. For each
       instance of this object there shall be a corresponding
       instance of sonetFarEndPathCurrentEntry."
    INDEX  { ifIndex }
     ::= { etherWisFarEndPathCurrentTable 1 }

EtherWisFarEndPathCurrentEntry ::=
    SEQUENCE {
        etherWisFarEndPathCurrentStatus     BITS
        }

etherWisFarEndPathCurrentStatus OBJECT-TYPE
    SYNTAX  BITS {
                etherWisFarEndPayloadDefect(0),
                etherWisFarEndServerDefect(1)
            }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
       "This variable indicates the current status at the
       far end of the path using a bit map that can indicate
       multiple defects at once. The bit positions are
       assigned as follows:

       etherWisFarEndPayloadDefect(0)
          A far end payload defect (i.e., far end
          PLM-P or LCD-P) is currently being signaled
          in G1 bits 5-7.

       etherWisFarEndServerDefect(1)
          A far end server defect (i.e., far end
          LOP-P or AIS-P) is currently being signaled
          in G1 bits 5-7. When this bit is set,
          sonetPathSTSRDI shall be set in the corresponding
          instance of sonetPathCurrentStatus."
    REFERENCE
       "IEEE Std 802.3, 30.8.1.1.25, aFarEndPathStatus."
     ::= { etherWisFarEndPathCurrentEntry 1 }

--
--     Conformance Statements
--
```

```
etherWisGroups      OBJECT IDENTIFIER ::= { etherWisConformance 1 }

etherWisCompliances OBJECT IDENTIFIER ::= { etherWisConformance 2 }

--     Object Groups

etherWisDeviceGroupBasic OBJECT-GROUP
    OBJECTS {
        etherWisDeviceTxTestPatternMode,
        etherWisDeviceRxTestPatternMode
        }
    STATUS  current
    DESCRIPTION
       "A collection of objects that support test
       features required of all WIS devices."
     ::= { etherWisGroups 1 }

etherWisDeviceGroupExtra OBJECT-GROUP
    OBJECTS {
        etherWisDeviceRxTestPatternErrors
        }
    STATUS  current
    DESCRIPTION
       "A collection of objects that support
       optional WIS device test features."
     ::= { etherWisGroups 2 }
etherWisSectionGroup OBJECT-GROUP
    OBJECTS {
        etherWisSectionCurrentJ0Transmitted,
        etherWisSectionCurrentJ0Received
        }
    STATUS  current
    DESCRIPTION
       "A collection of objects that provide
       required information about a WIS section."
     ::= { etherWisGroups 3 }

etherWisPathGroup OBJECT-GROUP
    OBJECTS {
        etherWisPathCurrentStatus,
        etherWisPathCurrentJ1Transmitted,
        etherWisPathCurrentJ1Received
        }
    STATUS  current
    DESCRIPTION
       "A collection of objects that provide
       required information about a WIS path."
     ::= { etherWisGroups 4 }

etherWisFarEndPathGroup OBJECT-GROUP
    OBJECTS {
        etherWisFarEndPathCurrentStatus
        }
    STATUS  current
    DESCRIPTION
       "A collection of objects that provide required
       information about the far end of a WIS path."
     ::= { etherWisGroups 5 }
```

```
--     Compliance Statements

etherWisCompliance MODULE-COMPLIANCE
    STATUS  current
    DESCRIPTION
       "The compliance statement for interfaces that include
       the Ethernet WIS. Compliance with the following
       external compliance statements is prerequisite:

       MIB module             Compliance Statement
       ----------             --------------------
       IF-MIB                 ifCompliance3
       IF-INVERTED-STACK-MIB  ifInvCompliance
       IEEE8023-EtherLike-MIB dot3Compliance2
       MAU-MIB                mauModIfCompl3"
    MODULE  -- this module
        MANDATORY-GROUPS {
            etherWisDeviceGroupBasic,
            etherWisSectionGroup,
            etherWisPathGroup,
            etherWisFarEndPathGroup
            }

        OBJECT       etherWisDeviceTxTestPatternMode
        SYNTAX       INTEGER {
            none(1),
            squareWave(2),
            mixedFrequency(4)
            }
        DESCRIPTION
            "Support for values other than none(1),
            squareWave(2), and mixedFrequency(4)
            is not required."

        OBJECT       etherWisDeviceRxTestPatternMode
        SYNTAX       INTEGER {
            none(1),
            mixedFrequency(4)
            }
        DESCRIPTION
            "Support for values other than none(1)
            and mixedFrequency(4) is not required."

        GROUP        etherWisDeviceGroupExtra
        DESCRIPTION
            "Implementation of this group, along with support for
            the value prbs31(3) for etherWisDeviceTxTestPatternMode
            and etherWisDeviceRxTestPatternMode, is necessary if the
            optional PRBS31 test pattern mode is to be supported."

        OBJECT       etherWisDeviceRxTestPatternErrors
        WRITE-SYNTAX Gauge32 ( 0 )
        DESCRIPTION
            "An implementation is not required to
            allow values other than zero to be
            written to this object."
    MODULE SONET-MIB
        MANDATORY-GROUPS {
```

```
        sonetMediumStuff2,
        sonetSectionStuff2,
        sonetLineStuff2,
        sonetFarEndLineStuff2,
        sonetPathStuff2,
        sonetFarEndPathStuff2
        }

    OBJECT       sonetMediumType
    SYNTAX       INTEGER {
        sonet(1)
        }
    MIN-ACCESS   read-only
    DESCRIPTION
        "Write access is not required, nor is support
        for any value other than sonet(1)."

    OBJECT       sonetMediumLineCoding
    SYNTAX       INTEGER {
        sonetMediumNRZ(4)
        }
    MIN-ACCESS   read-only
    DESCRIPTION
        "Write access is not required, nor is support
        for any value other than sonetMediumNRZ(4)."

    OBJECT       sonetMediumLineType
    MIN-ACCESS   read-only
    DESCRIPTION
        "Write access is not required."

    OBJECT       sonetMediumCircuitIdentifier
    MIN-ACCESS   read-only
    DESCRIPTION
        "Write access is not required."

    OBJECT       sonetMediumLoopbackConfig
    SYNTAX       BITS {
        sonetNoLoop(0),
        sonetFacilityLoop(1)
        }
    MIN-ACCESS   read-only
    DESCRIPTION
        "Write access is not required, nor is support for values
        other than sonetNoLoop(0) and sonetFacilityLoop(1)."

    OBJECT       sonetSESthresholdSet
    MIN-ACCESS   read-only
    DESCRIPTION
        "Write access is not required, and only one
        of the enumerated values need be supported."

    OBJECT       sonetPathCurrentWidth
    SYNTAX       INTEGER {
        sts192cSTM64(6)
        }
    MIN-ACCESS   read-only
    DESCRIPTION
        "Write access is not required, nor is support
```

```
              for any value other than sts192cSTM64(6)."

        ::= { etherWisCompliances 1 }

   END
```

13. Ethernet medium attachment units (MAUs) MIB module

13.1 Introduction

This clause defines a portion of the MIB for use with SNMP. In particular, it defines objects for managing IEEE 802.3 medium attachment units (MAUs).

A previous version of this clause, IETF RFC 3636 [B28], defined a single MIB module. IETF RFC 4836 [B35] split the original MIB module into two, putting frequently updated object identities and textual conventions into a separate, IANA-maintained MIB module, in order to decrease the need of updating the basic MAU-MIB module. The MIB module defined in this clause incorporates the IANA-MAU-MIB module by reference.

13.2 Overview

Instances of these object types represent attributes of an IEEE 802.3 MAU. Several types of MAUs are defined in IEEE Std 802.3. These MAUs may be connected to IEEE 802.3 repeaters or to IEEE 802.3 (Ethernet-like) interfaces. For convenience, this clause refers to these devices as “repeater MAUs” and “interface MAUs.”

The definitions presented here are based on 30.5 and 30.6 of IEEE Std 802.3. This specification is intended to provide for management of all types of Ethernet/IEEE 802.3 MAUs.

13.2.1 Relationship to IETF RFC 3636 and IETF RFC 4836

The management definitions provided in this clause are intended to be a superset of those defined by IETF RFC 3636 [B28] and IETF RFC 4836 [B35].

In order to decrease the need of updating the basic MAU MIB module due to the new MAU type, Media Available state, Auto Negotiation capability, and/or Jack type introduction, all relevant object identities and textual conventions have been moved to a separate, IANA-maintained MIB module, IANA-MAU-MIB. Thus, when a new MAU type, Media Available state, Auto Negotiation capability, and/or Jack type is defined by the IEEE 802.3 working group, only the IANA-maintained module needs to be revised, leaving the basic MAU-MIB module defined in this clause unchanged.

The changes made in this revision are not entirely backward-compatible with MIB modules that currently import MAU-type object identity descriptors from the MAU-MIB; such modules need to be revised to import those DESCRIPTORS from the IANA-MAU-MIB. Similarly, any management applications that process the object identity definitions (e.g., to present the DESCRIPTION text to a user) need to get those definitions from the IANA-MAU-MIB instead of the MAU-MIB. While it is true that changes that require such adjustments are not strictly compliant with the SMIv2 rules governing MIB module revisions (see Section 10 of IETF STD 58, RFC 2578), in this case continued high maintenance costs that would result from not making these changes make the deviation from the rules justified.

13.2.2 Relationship to other MIBs

It is assumed that an agent implementing the MAU-MIB module will also implement (at least) the “system” group defined in the SNMPv2 MIB of IETF RFC 3418 [B26]. The following subclauses identify other MIBs that such an agent should implement.

13.2.2.1 Relationship to the Interfaces Group MIB

The subclauses of this clause that define interface MAU-related objects specify an extension to the Interfaces Group MIB of IETF RFC 2863. An agent implementing these interface-MAU related objects shall also implement the relevant groups of the ifCompliance3 MODULE-COMPLIANCE statement of the Interfaces Group MIB. The value of the object ifMauIfIndex is the same as the value of "ifIndex" used to instantiate the interface to which the given MAU is connected.

An agent implementing the interface-MAU related objects in the MAU-MIB module shall also fully comply with the dot3Compliance2 MODULE-COMPLIANCE statement of the Ethernet-like interface MIB defined in Clause 10. Furthermore, when the interface-MAU related objects are used to manage a 10GBASE-W PHY—i.e., when ifMauType is equal to dot3MauType10GigBaseW or any other 10GBASE-W variant—then the agent shall also support the Ethernet WAN Interface Sublayer (WIS) MIB module defined in Clause 12, and shall follow the interface layering model specified therein. In that case, the value of the object ifMauIfIndex is the same as the value of "ifIndex" for the layer at the top of the stack, i.e., for the ifTable entry that has "ifType" equal to ethernetCsmacd(6). If the interface-MAU related objects are used to manage a PHY that allows the MAU type to be changed dynamically, then the agent shall create ifTable, ifStackTable, and ifInvStackTable entries that pertain to the WIS when ifMauDefaultType is changed to a 10GBASEW variant (i.e., one of dot3MauType10GigBaseW, dot3MauType10GigBaseEW, dot3MauType10 GigBaseLW, or dot3MauType10GigBaseSW) from any other type, and shall destroy the WIS-related entries when ifMauDefaultType is changed to a non-10GBASE-W type. The agent shall also change the values of "ifConnectorPresent" and "ifHighSpeed" in the ifTable entry indexed by ifMauIfIndex as specified in Clause 10 and Clause 12 when ifMauDefaultType is manipulated in this way, but shall NOT otherwise alter that entry.

NOTE—Repeater ports are not represented as interfaces in the Interfaces Group MIB.

13.2.2.2 Relationship to the IEEE 802.3 repeater MIB module

The subclause of this clause that defines repeater MAU-related objects specifies an extension to the IEEE 802.3 repeater MIB module defined in Clause 7. An agent implementing these repeater-MAU related objects shall also comply with the snmpRptrModCompl compliance statement of the IEEE 802.3 repeater MIB module.

The values of "rpMauGroupIndex" and "rpMauPortIndex" used to instantiate a repeater MAU variable shall be the same as the values of "rptrPortGroupIndex" and "rptrPortIndex" used to instantiate the port to which the given MAU is connected.

13.2.3 Management of internal MAUs

In some situations, a MAU can be "internal"; i.e., its functionality is implemented entirely within a device. For example, a managed repeater may contain an internal repeater-MAU and/or an internal interface-MAU through which management communications originating on one of the repeater's external ports pass, in order to reach the management agent associated with the repeater. Such internal MAUs may or may not be managed. If they are managed, objects describing their attributes should appear in the appropriate MIB subtree: dot3RpMauBasicGroup for internal repeater-MAUs and dot3IfMauBasicGroup for internal interface-MAUs.

13.2.4 Mapping of IEEE 802.3 managed objects

Table 13-1 depicts the mapping between relevant managed objects (attributes) defined in Clause 30 of IEEE Std 802.3 and managed objects defined in this clause.|

Table 13-1—Mapping of IEEE 802.3 managed objects

IEEE 802.3 managed object		Corresponding SNMP object
oMAU	.aMAUID	rpMauIndex or ifMauIndex or broadMauIndex
	.aMAUType	rpMauType or ifMauType
	.aMAUTypeList	ifMauTypeListBits
	.aMediaAvailable	rpMauMediaAvailable or ifMauMediaAvailable
	.aLoseMediaCounter	rpMauMediaAvailableStateExits or ifMauMediaAvailableStateExits
	.aJabber	rpMauJabberState and rpMauJabberingStateEnters or ifMauJabberState and ifMauJabberingStateEnters
	.aMAUAdminState	rpMauStatus or ifMauStatus
	.aFalseCarriers	rpMauFalseCarriers or ifMauFalseCarriers
	.acResetMAU	rpMauStatus or ifMauStatus
	.acMAUAdminControl	rpMauStatus or ifMauStatus
	.nJabber	rpMauJabberTrap or ifMauJabberTrap

Table 13-1—Mapping of IEEE 802.3 managed objects *(continued)*

IEEE 802.3 managed object		Corresponding SNMP object
oAutoNegotiation	.aAutoNegID	ifMauIndex
	.aAutoNegAdminState	ifMauAutoNegAdminStatus
	.aAutoNegRemoteSignalling	ifMauAutoNegRemoteSignalling
	.aAutoNegAutoConfig	ifMauAutoNegConfig
	.aAutoNegLocalTechnologyAbility	ifMauAutoNegCapabilityBits
	.aAutoNegAdvertisedTechnologyAbility	ifMauAutoNegAdvertisedBits and ifMauAutoNegRemoteFaultAdvertised
	.aAutoNegReceivedTechnologyAbility	ifMauAutoNegReceivedBits and ifMauAutoNegRemoteFaultReceived
	.acAutoNegRestartAutoConfig	ifMauAutoNegRestart
	.acAutoNegAdminControl	ifMauAutoNegAdminStatus
oTimeSync	.aTimeSyncCapabilityTX	ifMauTimeSyncCapabilityTX
	.aTimeSyncCapabilityRX	ifMauTimeSyncCapabilityRX
	.aTimeSyncDelayTXmax	ifMauTimeSyncDelayTXmax
	.aTimeSyncDelayTXmin	ifMauTimeSyncDelayTXmin
	.aTimeSyncDelayRXmax	ifMauTimeSyncDelayRXmax
	.aTimeSyncDelayRXmin	ifMauTimeSyncDelayRXmin

Table 13-2 depicts the IEEE 802.3 managed objects that have not been included in the MAU-MIB module, and the reason for the exclusion.

Table 13-2—Unmapped IEEE 802.3 managed objects

IEEE 802.3 managed object		Reason for exclusion
oMAU	.aIdleErrorCount	Only useful for 100BaseT2, which is not widely implemented
oAutoNegotiation	.aAutoNegLocalSeletorAbility	Only needed for support of isoethernet (IEEE Std 802.9a-1995), which is not supported by MAU-MIB
	.aAutoNegAdvertisedSelectorAbility	
	.aAutoNegReceivedSelectorAbility	

13.2.5 Addition of new MAU types

13.2.5.1 dot3MauType OBJECT-IDENTITIES

The dot3MauType OBJECT IDENTIFIER and its OBJECT-IDENTITY definitions have been moved from the MAU-MIB module into the IANA-maintained IANA-MAU-MIB module.

When a new IEEE 802.3 MAU is defined, IANA can reissue a version of the IANA-MAU-MIB module with the new dot3MauType OBJECT-IDENTITY and its matching IANAifMauTypeListBits textual convention value and, possibly, with new IANAifMauMediaAvailable, IANAifMauAutoNegCapBits, and/or IANAifJackType values.

An Expert Review, as defined in IETF RFC 2434, is required for the addition of the new MAU, Media Available states, Auto Negotiation capabilities, and/or Jack types.

In some cases, new MAU types may require additional managed objects or may have side effects on the behavior of existing managed objects. In such cases, a standards-track specification (which may be a new document or a revision of this document) is also required. Any such document is required to note any special properties of the MAU types that it defines—for example, side effects on the ifStackTable as noted in this document for 10GBASE-W MAUs.

13.2.5.2 IANAifMauTypeListBits TEXTUAL-CONVENTION

The syntax of ifMauTypeListBits is changed to be a textual convention, such that the enumerated integer values are now defined in the textual convention IANAifMauTypeListBits, which can be respecified (with additional values, when defined by IEEE Std 802.3) in the IANA-maintained MIB module without issuing a new version of this document.

13.2.5.3 IANAifMauMediaAvailable TEXTUAL-CONVENTION

The syntax of ifMauMediaAvailable and rpMauMediaAvailable is changed to be a textual convention, such that the enumerated integer values are now defined in the textual convention IANAifMauMediaAvailable, which can be respecified (with additional values, when defined by IEEE Std 802.3) in the IANA-maintained MIB module without issuing a new version of this document.

13.2.5.4 IANAifMauAutoNegCapBits TEXTUAL-CONVENTION

The syntax of ifMauAutoNegCapabilityBits, ifMauAutoNegCapAdvertisedBits, and ifMauAutoNegCapReceivedBits objects is changed to be a textual convention, such that the enumerated integer values are now defined in the textual convention IANAifMauAutoNegCapBits, which can be respecified (with additional values, when defined by IEEE Std 802.3) in the IANA-maintained MIB module without issuing a new version of this document.

13.2.5.5 JackType TEXTUAL-CONVENTION

The JackType Textual Convention has been deprecated in favor of the IANAifJackType defined in the IANA-maintained MIB module, so the new Jack types can be added (when defined by IEEE Std 802.3) without issuing a new version of this document.

13.3 Security considerations for Ethernet medium attachment units (MAUs) MIB module

The IANA-MAU-MIB module does not define any management objects. Instead, it defines a set of textual conventions that are used by the MAU-MIB module and may be used by other MIB modules to define management objects. Meaningful security considerations can only be written for MIB modules that define management objects.

There are a number of management objects defined in the MAU-MIB module that have a MAX-ACCESS clause of read-write. Setting these objects can have a serious effect on the operation of the network, including:

- Enabling or disabling a MAU
- Changing a MAU's default type
- Enabling, disabling, or restarting autonegotiation
- Modifying the capabilities that a MAU advertises during autonegotiation.

Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

Some of the readable objects in the MAU-MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. In some environments, it may be undesirable to allow unauthorized parties to access statistics or status information about individual links in a network. It is thus important to control GET and/or NOTIFY access to these objects and possibly to encrypt the values of these objects when sending them over the network via SNMP.

13.4 IANA considerations

It is intended that each new MAU type, Media Available state, Auto Negotiation capability, and/or Jack type defined by the IEEE 802.3 working group and approved for publication in a revision of IEEE Std 802.3 will be added to the IANA-maintained MIB module, provided that it is suitable for being managed by the base objects in the MAU-MIB module.

For each new MAU type added, a short description of the MAU technology and, wherever possible, a reference to a publicly available specification should be specified. An Expert Review, as defined in IETF RFC 2434, is required, for each modification.

13.5 MIB module definition

An ASCII text version of the MIB definition can be found at the following URL[21]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C13mib.txt

The IANA-MAU-MIB module can be found at the following URL:

http://www.iana.org/assignments/ianamau-mib

[21]Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.

```
IEEE8023-MAU-MIB DEFINITIONS ::= BEGIN

     IMPORTS
       Counter32, Integer32, Counter64, Unsigned32,
       OBJECT-TYPE, MODULE-IDENTITY, NOTIFICATION-TYPE, org
         FROM SNMPv2-SMI         -- RFC 2578
       TruthValue, AutonomousType
         FROM SNMPv2-TC          -- RFC 2579
       OBJECT-GROUP, MODULE-COMPLIANCE, NOTIFICATION-GROUP
         FROM SNMPv2-CONF        -- RFC 2580
       InterfaceIndex
         FROM IF-MIB             -- RFC 2863
       IANAifMauTypeListBits, IANAifMauMediaAvailable,
       IANAifMauAutoNegCapBits, IANAifJackType
         FROM IANA-MAU-MIB
                       -- http://www.iana.org/assignments/ianamau-mib
       ;

     ieee8023mauMIB MODULE-IDENTITY
        LAST-UPDATED "201304110000Z" -- April 11, 2013
        ORGANIZATION
          "IEEE 802.3 working group"
        CONTACT-INFO
            "WG-URL: http://www.ieee802.org/3/index.html
            WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

            Contact: Howard Frazier
            Postal:  3151 Zanker Road
                     San Jose, CA 95134
                     USA
            Tel:     +1.408.922.8164
            E-mail:  hfrazier@broadcom.com"
DESCRIPTION
         "Management information for 802.3 MAUs."

       REVISION    "201304110000Z" -- April 11, 2013
       DESCRIPTION
             "Revision, based on an earlier version in IEEE Std 802.3.1-2011."

       REVISION    "201102020000Z" -- February 2, 2011
       DESCRIPTION
             "Initial version, based on an earlier version published
              as RFC 4836."

           ::= { org ieee(111) standards-association-numbers-series-standards(2)
                 lan-man-stds(802) ieee802dot3(3) ieee802dot3dot1mibs(1) 13 }


      ieee8023snmpDot3MauMgt OBJECT IDENTIFIER ::= { ieee8023mauMIB 1 }

      dot3RpMauBasicGroup
          OBJECT IDENTIFIER ::= { ieee8023snmpDot3MauMgt 1 }
      dot3IfMauBasicGroup
          OBJECT IDENTIFIER ::= { ieee8023snmpDot3MauMgt 2 }
      -- The following object is a placeholder
      -- to preserve the arc assignments that follow it.
      dot3PlaceholderGroup
          OBJECT IDENTIFIER ::= { ieee8023snmpDot3MauMgt 3 }
```

```
-- OIDs under the following branch are reserved for
-- the IANA-MAU-MIB to assign as MAU type values:
--                        { ieee8023snmpDot3MauMgt 4 }

dot3IfMauAutoNegGroup
    OBJECT IDENTIFIER ::= { ieee8023snmpDot3MauMgt 5 }

--
-- The Basic Repeater MAU Table
--

rpMauTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF RpMauEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION "Table of descriptive and status information
              about the MAU(s) attached to the ports of a
              repeater."
  ::= { dot3RpMauBasicGroup 1 }

rpMauEntry OBJECT-TYPE
  SYNTAX      RpMauEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION "An entry in the table, containing information
              about a single MAU."
  INDEX       { rpMauGroupIndex,
                rpMauPortIndex,
                rpMauIndex
              }
  ::= { rpMauTable 1 }

RpMauEntry ::=
  SEQUENCE {
      rpMauGroupIndex                     Integer32,
      rpMauPortIndex                      Integer32,
      rpMauIndex                          Integer32,
      rpMauType                           AutonomousType,
      rpMauStatus                         INTEGER,
      rpMauMediaAvailable                 IANAifMauMediaAvailable,
      rpMauMediaAvailableStateExits       Counter32,
      rpMauJabberState                    INTEGER,
      rpMauJabberingStateEnters           Counter32,
      rpMauFalseCarriers                  Counter32
}

rpMauGroupIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..2147483647)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION "This variable uniquely identifies the group
              containing the port to which the MAU described
              by this entry is connected.

              Note:  In practice, a group will generally be
              a field-replaceable unit (i.e., module, card,
              or board) that can fit in the physical system
              enclosure, and the group number will correspond
              to a number marked on the physical enclosure.
```

```
                The group denoted by a particular value of this
                object is the same as the group denoted by the
                same value of rptrGroupIndex."
  REFERENCE   "RFC 2108, rptrGroupIndex."
  ::= { rpMauEntry 1 }

rpMauPortIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..2147483647)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION "This variable uniquely identifies the repeater
              port within group rpMauGroupIndex to which the
              MAU described by this entry is connected."
  REFERENCE   "RFC 2108, rptrPortIndex."
  ::= { rpMauEntry 2 }

rpMauIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..2147483647)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION "This variable uniquely identifies the MAU
              described by this entry from among other
              MAUs connected to the same port
              (rpMauPortIndex)."
  REFERENCE   "IEEE Std 802.3, 30.5.1.1.1, aMAUID."
  ::= { rpMauEntry 3 }

rpMauType OBJECT-TYPE
  SYNTAX      AutonomousType
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION "This object identifies the MAU type. Values for
              standard IEEE 802.3 MAU types are defined in the
              IANA maintained IANA-MAU-MIB module, as
              OBJECT-IDENTITIES of dot3MauType.
              If the MAU type is unknown, the object identifier
              zeroDotZero is returned."
  REFERENCE   "IEEE Std 802.3, 30.5.1.1.2, aMAUType."
  ::= { rpMauEntry 4 }

rpMauStatus OBJECT-TYPE
    SYNTAX      INTEGER {
                    other(1),
                    unknown(2),
                    operational(3),
                    standby(4),
                    shutdown(5),
                    reset(6)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION "The current state of the MAU. This object may
                be implemented as a read-only object by those
                agents and MAUs that do not implement software
                control of the MAU state. Some agents may not
                support setting the value of this object to some
                of the enumerated values.
```

```
                    The value other(1) is returned if the MAU is in
                    a state other than one of the states 2 through
                    6.
                    The value unknown(2) is returned when the MAU’s
                    true state is unknown; for example, when it is
                    being initialized.

                    A MAU in the operational(3) state is fully
                    functional; it operates, and passes signals to its
                    attached DTE or repeater port in accordance to
                    its specification.

                    A MAU in standby(4) state forces DI and CI to
                    idle, and the media transmitter to idle or fault,
                    if supported. Standby(4) mode only applies to
                    link type MAUs. The state of
                    rpMauMediaAvailable is unaffected.

                    A MAU in shutdown(5) state assumes the same
                    condition on DI, CI, and the media transmitter,
                    as though it were powered down or not connected.
                    The MAU may return other(1) value for the
                    rpMauJabberState and rpMauMediaAvailable objects
                    when it is in this state. For an AUI, this
                    state will remove power from the AUI.

                    Setting this variable to the value reset(6)
                    resets the MAU in the same manner as a
                    power-off, power-on cycle of at least one-half
                    second would. The agent is not required to
                    return the value reset(6).

                    Setting this variable to the value
                    operational(3), standby(4), or shutdown(5)
                    causes the MAU to assume the respective state,
                    except that setting a mixing-type MAU or an AUI
                    to standby(4) will cause the MAU to enter the
                    shutdown state."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.7, aMAUAdminState,
                    30.5.1.2.2, acMAUAdminControl, and 30.5.1.2.1,
                    acResetMAU."
        ::= { rpMauEntry 5 }

    rpMauMediaAvailable OBJECT-TYPE
        SYNTAX      IANAifMauMediaAvailable
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "This object identifies Media Available state of
                    the MAU, complementary to the rpMauStatus. Values
                    for the standard IEEE 802.3 Media Available states
                    are defined in the IANA maintained IANA-MAU-MIB
                    module, as IANAifMauMediaAvailable TC."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.4, aMediaAvailable."
        ::= { rpMauEntry 6 }

    rpMauMediaAvailableStateExits OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
```

```
        DESCRIPTION "A count of the number of times that
                    rpMauMediaAvailable for this MAU instance leaves
                    the state available(3).

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system and at other times, as indicated by the
                    value of rptrMonitorPortLastChange."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.5, aLoseMediaCounter.
                    RFC 2108, rptrMonitorPortLastChange"
        ::= { rpMauEntry 7 }

    rpMauJabberState OBJECT-TYPE
        SYNTAX      INTEGER {
                        other(1),
                        unknown(2),
                        noJabber(3),
                        jabbering(4)
                    }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The value other(1) is returned if the jabber
                    state is not 2, 3, or 4. The agent shall
                    return other(1) for MAU type dot3MauTypeAUI.

                    The value unknown(2) is returned when the MAU's
                    true state is unknown; for example, when it is
                    being initialized.

                    If the MAU is not jabbering the agent returns
                    noJabber(3). This is the 'normal' state.

                    If the MAU is in jabber state the agent returns
                    the jabbering(4) value."
        REFERENCE "IEEE Std 802.3, 30.5.1.1.6, aJabber.jabberFlag."
        ::= { rpMauEntry 8 }

    rpMauJabberingStateEnters OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of the number of times that
                    mauJabberState for this MAU instance enters the
                    state jabbering(4). For MAUs of type
                    dot3MauTypeAUI, dot3MauType100BaseT4,
                    dot3MauType100BaseTX, dot3MauType100BaseFX, and
                    all 1000 Mb/s types, this counter will
                    indicate zero.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system and at other times, as indicated by the
                    value of rptrMonitorPortLastChange."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.6, aJabber.jabberCounter.
                    RFC 2108, rptrMonitorPortLastChange"
        ::= { rpMauEntry 9 }

    rpMauFalseCarriers OBJECT-TYPE
        SYNTAX      Counter32
```

```
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A count of the number of false carrier events
                during IDLE in 100BASE-X links. This counter
                does not increment at the symbol rate. It can
                increment after a valid carrier completion at a
                maximum rate of once per 100 ms until the next
                carrier event.

                This counter increments only for MAUs of type
                dot3MauType100BaseT4, dot3MauType100BaseTX,
                dot3MauType100BaseFX, and all 1000 Mb/s types.

                For all other MAU types, this counter will
                indicate zero.

                The approximate minimum time for rollover of
                this counter is 7.4 hours.

                Discontinuities in the value of this counter can
                occur at re-initialization of the management
                system and at other times, as indicated by the
                value of rptrMonitorPortLastChange."
    REFERENCE   "IEEE Std 802.3, 30.5.1.1.10, aFalseCarriers.
                RFC 2108, rptrMonitorPortLastChange"
    ::= { rpMauEntry 10 }

-- The rpJackTable applies to MAUs attached to repeaters
-- which have one or more external jacks (connectors).
rpJackTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RpJackEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "Information about the external jacks attached
                to MAUs attached to the ports of a repeater."
    ::= { dot3RpMauBasicGroup 2 }

rpJackEntry OBJECT-TYPE
    SYNTAX      RpJackEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "An entry in the table, containing information
                about a particular jack."
    INDEX       { rpMauGroupIndex,
                  rpMauPortIndex,
                  rpMauIndex,
                  rpJackIndex
                }
    ::= { rpJackTable 1 }

RpJackEntry ::=
    SEQUENCE {
        rpJackIndex                         Integer32,
        rpJackType                          IANAifJackType
    }

rpJackIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
```

```
        STATUS      current
        DESCRIPTION "This variable uniquely identifies the jack
                    described by this entry from among other jacks
                    attached to the same MAU (rpMauIndex)."
        ::= { rpJackEntry 1 }

    rpJackType OBJECT-TYPE
        SYNTAX      IANAifJackType
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The jack connector type, as it appears on the
                    outside of the system."
        ::= { rpJackEntry 2 }

    --
    -- The Basic Interface MAU Table
    --
    ifMauTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF IfMauEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "Table of descriptive and status information
                    about MAU(s) attached to an interface."
        ::= { dot3IfMauBasicGroup 1 }

    ifMauEntry OBJECT-TYPE
        SYNTAX      IfMauEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "An entry in the table, containing information
                    about a single MAU."
        INDEX       { ifMauIfIndex,
                      ifMauIndex
                    }
        ::= { ifMauTable 1 }

    IfMauEntry ::=
        SEQUENCE {
            ifMauIfIndex                      InterfaceIndex,
            ifMauIndex                        Integer32,
            ifMauType                         AutonomousType,
            ifMauStatus                       INTEGER,
            ifMauMediaAvailable               IANAifMauMediaAvailable,
            ifMauMediaAvailableStateExits     Counter32,
            ifMauJabberState                  INTEGER,
            ifMauJabberingStateEnters         Counter32,
            ifMauFalseCarriers                Counter32,
            ifMauDefaultType                  AutonomousType,
            ifMauAutoNegSupported             TruthValue,
            ifMauTypeListBits                 IANAifMauTypeListBits,
            ifMauHCFalseCarriers              Counter64,
            ifMauPCSCodingViolations          Counter64,
            ifMauFECAbility                   INTEGER,
            ifMauFECMode                      INTEGER,
            ifMauFECCorrectedBlocks           Counter64,
            ifMauFECUnCorrectableBlocks       Counter64,
            ifMauSNROpMarginChnlA             Integer32,
            ifMauSNROpMarginChnlB             Integer32,
            ifMauSNROpMarginChnlC             Integer32,
```

```
            ifMauSNROpMarginChnlD             Integer32,
            ifMauEEESupportList               IANAifMauTypeListBits,
            ifMauEEELDFastRetrainCount        Counter32,
            ifMauEEELPFastRetrainCount        Counter32,
            ifMauTimeSyncCapabilityTX         TruthValue,
            ifMauTimeSyncCapabilityRX         TruthValue,
            ifMauTimeSyncDelayTXmax           Integer32,
            ifMauTimeSyncDelayTXmin           Integer32,
            ifMauTimeSyncDelayRXmax           Integer32,
            ifMauTimeSyncDelayRXmin           Integer32
        }

    ifMauIfIndex OBJECT-TYPE
        SYNTAX      InterfaceIndex
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "This variable uniquely identifies the interface
                    to which the MAU described by this entry is
                    connected."
        REFERENCE   "RFC 2863, ifIndex"
        ::= { ifMauEntry 1 }

    ifMauIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "This variable uniquely identifies the MAU
                    described by this entry from among other MAUs
                    connected to the same interface (ifMauIfIndex)."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.1, aMAUID."
        ::= { ifMauEntry 2 }

    ifMauType OBJECT-TYPE
      SYNTAX      AutonomousType
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION "This object identifies the MAU type. Values for
                  standard IEEE 802.3 MAU types are defined in the
                  IANA maintained IANA-MAU-MIB module, as
                  OBJECT-IDENTITIES of dot3MauType.
                  If the MAU type is unknown, the object identifier
                  zeroDotZero is returned.

                  This object represents the operational type of
                  the MAU, as determined by either 1) the result
                  of the Auto-Negotiation function or 2) if
                  Auto-Negotiation is not enabled or is not
                  implemented for this MAU, by the value of the
                  object ifMauDefaultType. In case 2), a set to
                  the object ifMauDefaultType will force the MAU
                  into the new operating mode."
      REFERENCE   "IEEE Std 802.3, 30.5.1.1.2, aMAUType."
      ::= { ifMauEntry 3 }

    ifMauStatus OBJECT-TYPE
        SYNTAX      INTEGER {
                        other(1),
                        unknown(2),
                        operational(3),
```

```
                        standby(4),
                        shutdown(5),
                        reset(6)
                    }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION "The current state of the MAU. This object may
                    be implemented as a read-only object by those
                    agents and MAUs that do not implement software
                    control of the MAU state. Some agents may not
                    support setting the value of this object to some
                    of the enumerated values.

                    The value other(1) is returned if the MAU is in
                    a state other than one of the states 2 through
                    6.

                    The value unknown(2) is returned when the MAU's
                    true state is unknown; for example, when it is
                    being initialized.

                    A MAU in the operational(3) state is fully
                    functional; it operates, and passes signals to its
                    attached DTE or repeater port in accordance to
                    its specification.

                    A MAU in standby(4) state forces DI and CI to
                    idle and the media transmitter to idle or fault,
                    if supported. Standby(4) mode only applies to
                    link type MAUs. The state of
                    ifMauMediaAvailable is unaffected.

                    A MAU in shutdown(5) state assumes the same
                    condition on DI, CI, and the media transmitter,
                    as though it were powered down or not connected.
                    The MAU may return other(1) value for the
                    ifMauJabberState and ifMauMediaAvailable objects
                    when it is in this state. For an AUI, this
                    state will remove power from the AUI.

                    Setting this variable to the value reset(6)
                    resets the MAU in the same manner as a
                    power-off, power-on cycle of at least one-half
                    second would. The agent is not required to
                    return the value reset(6).

                    Setting this variable to the value
                    operational(3), standby(4), or shutdown(5)
                    causes the MAU to assume the respective state,
                    except that setting a mixing-type MAU or an AUI
                    to standby(4) will cause the MAU to enter the
                    shutdown state."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.7, aMAUAdminState,
                    30.5.1.2.2, acMAUAdminControl, and 30.5.1.2.1,
                    acResetMAU."
        ::= { ifMauEntry 4 }

    ifMauMediaAvailable OBJECT-TYPE
        SYNTAX      IANAifMauMediaAvailable
```

```
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "This object identifies Media Available state of
                    the MAU, complementary to the ifMauStatus. Values
                    for the standard IEEE 802.3 Media Available states
                    are defined in the IANA maintained IANA-MAU-MIB
                    module, as IANAifMauMediaAvailable TC."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.4, aMediaAvailable."
        ::= { ifMauEntry 5 }

    ifMauMediaAvailableStateExits OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of the number of times that
                    ifMauMediaAvailable for this MAU instance leaves
                    the state available(3).

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system and at other times, as indicated by the
                    value of ifCounterDiscontinuityTime."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.5, aLoseMediaCounter.
                    RFC 2863, ifCounterDiscontinuityTime."
        ::= { ifMauEntry 6 }

    ifMauJabberState OBJECT-TYPE
        SYNTAX      INTEGER {
                        other(1),
                        unknown(2),
                        noJabber(3),
                        jabbering(4)
                    }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The value other(1) is returned if the jabber
                    state is not 2, 3, or 4. The agent shall
                    return other(1) for MAU type dot3MauTypeAUI.

                    The value unknown(2) is returned when the MAU’s
                    true state is unknown; for example, when it is
                    being initialized.

                    If the MAU is not jabbering the agent returns
                    noJabber(3). This is the ‘normal’ state.

                    If the MAU is in jabber state the agent returns
                    the jabbering(4) value."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.6, aJabber.jabberFlag."
        ::= { ifMauEntry 7 }

    ifMauJabberingStateEnters OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of the number of times that
                    mauJabberState for this MAU instance enters the
                    state jabbering(4). This counter will
                    indicate zero for MAUs of type dot3MauTypeAUI
```

```
                     and those of speeds above 10 Mb/s.

                     Discontinuities in the value of this counter can
                     occur at re-initialization of the management
                     system and at other times, as indicated by the
                     value of ifCounterDiscontinuityTime."
         REFERENCE   "IEEE Std 802.3, 30.5.1.1.6, aJabber.jabberCounter.
                     RFC 2863, ifCounterDiscontinuityTime."
         ::= { ifMauEntry 8 }

     ifMauFalseCarriers OBJECT-TYPE
         SYNTAX      Counter32
         MAX-ACCESS  read-only
         STATUS      current
         DESCRIPTION "A count of the number of false carrier events
                     during IDLE in 100BASE-X and 1000BASE-X links.

                     For all other MAU types, this counter will
                     indicate zero. This counter does not
                     increment at the symbol rate.

                     It can increment after a valid carrier
                     completion at a maximum rate of once per 100 ms
                     for 100BASE-X and once per 10us for 1000BASE-X
                     until the next CarrierEvent.

                     This counter can roll over very quickly. A
                     management station is advised to poll the
                     ifMauHCFalseCarriers instead of this counter in
                     order to avoid loss of information.

                     Discontinuities in the value of this counter can
                     occur at re-initialization of the management
                     system and at other times, as indicated by the
                     value of ifCounterDiscontinuityTime."
         REFERENCE   "IEEE Std 802.3, 30.5.1.1.10, aFalseCarriers.
                     RFC 2863, ifCounterDiscontinuityTime."
         ::= { ifMauEntry 9 }

     ifMauDefaultType OBJECT-TYPE
         SYNTAX      AutonomousType
         MAX-ACCESS  read-write
         STATUS      current
         DESCRIPTION "This object identifies the default
                     administrative baseband MAU type to be used in
                     conjunction with the operational MAU type
                     denoted by ifMauType.

                     The set of possible values for this object is
                     the same as the set defined for the ifMauType
                     object.

                     This object represents the
                     administratively-configured type of the MAU. If
                     Auto-Negotiation is not enabled or is not
                     implemented for this MAU, the value of this
                     object determines the operational type of the
                     MAU. In this case, a set to this object will
                     force the MAU into the specified operating mode.
```

```
                     If Auto-Negotiation is implemented and enabled
                     for this MAU, the operational type of the MAU
                     is determined by Auto-Negotiation, and the value
                     of this object denotes the type to which the MAU
                     will automatically revert if/when
                     Auto-Negotiation is later disabled.

                     It may be necessary to provide for underlying hardware
                     implementations which do not follow the exact behavior
                     specified above.
                     In particular, when ifMauAutoNegAdminStatus transitions
                     from enabled to disabled, the agent implementation shall
                     verify that the operational type of the MAU
                     (as reported by ifMauType) correctly transitions to
                     the value specified by this object, rather than
                     continuing to operate at the value earlier
                     determined by the Auto-Negotiation function."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.1, aMAUID, and 22.2.4.1.4."
        ::= { ifMauEntry 10 }

    ifMauAutoNegSupported OBJECT-TYPE
        SYNTAX      TruthValue
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "This object indicates whether or not
                     Auto-Negotiation is supported on this MAU."
        ::= { ifMauEntry 11 }

    ifMauTypeListBits OBJECT-TYPE
        SYNTAX      IANAifMauTypeListBits
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A value that uniquely identifies the set of
                     possible IEEE 802.3 types that the MAU could be.
                     If Auto-Negotiation is present on this MAU, this
                     object will map to ifMauAutoNegCapabilityBits.

                     Note that this MAU may be capable of operating
                     as a MAU type that is beyond the scope of this
                     MIB. This is indicated by returning the
                     bit value bOther in addition to any bit values
                     for standard capabilities that are listed in the
                     IANAifMauTypeListBits TC."
        ::= { ifMauEntry 12 }

    ifMauHCFalseCarriers OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of the number of false carrier events
                     during IDLE in 100BASE-X and 1000BASE-X links.

                     For all other MAU types, this counter will
                     indicate zero. This counter does not
                     increment at the symbol rate.

                     This counter is a 64-bit version of
                     ifMauFalseCarriers. Since the 32-bit version of
```

```
                    this counter can roll over very quickly,
                    management stations are advised to poll the
                    64-bit version instead, in order to avoid loss
                    of information.

                    Discontinuities in the value of this counter can
                    occur at re-initialization of the management
                    system and at other times, as indicated by the
                    value of ifCounterDiscontinuityTime."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.10, aFalseCarriers.
                    RFC 2863, ifCounterDiscontinuityTime."
        ::= { ifMauEntry 13 }

    ifMauPCSCodingViolations OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "Generalized nonresettable counter. This counter
                     has a maximum increment rate of 25 000 000
                     counts per second for 100 Mb/s implementations and
                     125 000 000 counts per second for 1000 Mb/s
                     implementations.

                     For 100 Mb/s operation it is a count of the number
                     of events that cause the PHY to indicate ‘Data
                     reception with errors’ on the MII (see IEEE Std 802.3
                     Table 22–2).

                     For 1000 Mb/s operation it is a count of the
                     number of events that cause the PHY to indicate ‘Data
                     reception error’ or ‘Carrier Extend Error’ on the GMII
                     (see IEEE Std 802.3, Table 35–2). The contents of this
                     attribute is undefined when FEC is operating."
          REFERENCE "IEEE Std 802.3, 30.5.1.1.14 aPCSCodingViolations."
          ::= {ifMauEntry 14}

    ifMauFECAbility OBJECT-TYPE
        SYNTAX     INTEGER {
                         unknown(1),
                         supported(2),
                         notsupported(3)
                     }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A read-only value that indicates if the
                    PHY supports an optional FEC sublayer for
                    forward error correction (see IEEE Std 802.3, 65.2
                    and IEEE Std 802.3, Clause 74).

                    If an IEEE Std 802.3 Clause 45 MDIO Interface to the
                    PCS is present, then this attribute will map to the
                    FEC capability register (see IEEE Std 802.3, 45.2.8.2)."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.15 aFECAbility."
        ::= {ifMauEntry 15}

    ifMauFECMode OBJECT-TYPE
        SYNTAX     INTEGER {
                         unknown(1),
                         disabled(2),
```

```
                        enabled(3)
                    }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION "A read-write value that indicates the mode of
                    operation of the optional FEC sublayer for forward
                    error correction (see IEEE Std 802.3, 65.2 and
                    IEEE Std 802.3, Clause 74).

                    A GET operation returns the current mode of operation
                    of the PHY. A SET operation changes the mode of
                    operation of the PHY to the indicated value. When
                    IEEE Std 802.3 Clause 73 Auto-Negotiation is enabled
                    a SET operation is not allowed and a GET operation maps
                    to the variable FEC enabled in Clause 74.

                    If an IEEE Std 802.3 Clause 45 MDIO Interface to the
                    PCS is present, then this object will map to the FEC
                    control register (see IEEE Std 802.3 45.2.8.3) for
                    1000BASE-PX or FEC enable bit in the BASE-R FEC control
                    register (see IEEE Std 802.3 45.2.1.90)."
        REFERENCE   "IEEE Std 802.3. 30.5.1.1.16 aFECMode."
        ::= {ifMauEntry 16}

    ifMauFECCorrectedBlocks OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS  read-only
        STATUS      deprecated
        DESCRIPTION
                    "********** THIS OBJECT IS DEPRECATED **********

                    Generalized nonresettable counter. This counter
                    has a maximum increment rate of 1 200 000
                    counts per second for 1000 Mb/s implementations,
                    and 5 000 000 counts per second for 10 Gb/s
                    implementations.

                    For 1000BASE-PX PHYs or 10GBASE-R PHYs, a count
                    of corrected FEC blocks. This counter will not
                    increment for other PHY types.
                    Increment the counter by one for each received block
                    that is corrected by the FEC function in the PHY.
                    If a Clause 45 MDIO Interface to the PCS is present,
                    then this object will map to the FEC corrected blocks
                    counter (see IEEE Std 802.3, 45.2.8.5 and 45.2.1.91)"
        REFERENCE   "IEEE Std 802.3. 30.5.1.1.17 aFECCorrectedBlocks."
        ::= {ifMauEntry 17}

    ifMauFECUnCorrectableBlocks OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS  read-only
        STATUS      deprecated
        DESCRIPTION
                    "********** THIS OBJECT IS DEPRECATED **********

                    Generalized nonresettable counter. This counter
                    has a maximum increment rate of 1 200 000
                    counts per second for 1000 Mb/s implementations,
                    and 5 000 000 counts per second for 10 Gb/s
```

```
                     implementations.

                     For 1000BASE-PX PHYs or 10GBASE-R PHYs, a count
                     of uncorrectable FEC blocks. This counter will not
                     increment for other PHY types.
                     Increment the counter by one for each received block
                     that is determined to be uncorrectable by the FEC
                     function in the PHY.

                     If a Clause 45 MDIO Interface to the PCS is present,
                     then this object will map to the FEC uncorrectable
                     blocks counter (see IEEE Std 802.3 45.2.8.6 and
                     45.2.1.92)"
        REFERENCE   "IEEE Std 802.3. 30.5.1.1.18 aFECUnCorrectableBlocks."
        ::= {ifMauEntry 18}

    ifMauSNROpMarginChnlA OBJECT-TYPE
        SYNTAX      Integer32 (-127..127)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The current SNR operating margin measured at the
                     slicer input for channel A for the 10GBASE-T PMA.
                     It is reported in units of 0.1 dB to an accuracy of
                     0.5 dB within the range of -12.7 dB to 12.7 dB.
                     If an IEEE Std 802.3 Clause 45 MDIO Interface to the
                     PMA/PMD is present, then this attribute maps to the SNR
                     operating margin channel A register
                     (see IEEE Std 802.3, 45.2.1.65)."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.19 aSNROpMarginChnlA."
        ::= {ifMauEntry 19}

    ifMauSNROpMarginChnlB OBJECT-TYPE
        SYNTAX      Integer32 (-127..127)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The current SNR operating margin measured at the
                     slicer input for channel B for the 10GBASE-T PMA.
                     It is reported in units of 0.1 dB to an accuracy of
                     0.5 dB within the range of -12.7 dB to 12.7 dB.
                     If an IEEE Std 802.3 Clause 45 MDIO Interface to the
                     PMA/PMD is present, then this attribute maps to the SNR
                     operating margin channel B register
                     (see IEEE Std 802.3, 45.2.1.66)."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.20 aSNROpMarginChnlB."
        ::= {ifMauEntry 20}

    ifMauSNROpMarginChnlC OBJECT-TYPE
        SYNTAX      Integer32 (-127..127)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The current SNR operating margin measured at the
                     slicer input for channel C for the 10GBASE-T PMA.
                     It is reported in units of 0.1 dB to an accuracy of
                     0.5 dB within the range of -12.7 dB to 12.7 dB.
                     If an IEEE Std 802.3 Clause 45 MDIO Interface to the
                     PMA/PMD is present, then this attribute maps to the SNR
                     operating margin channel C register
                     (see IEEE Std 802.3, 45.2.1.67)."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.21 aSNROpMarginChnlC."
```

```
        ::= {ifMauEntry 21}

    ifMauSNROpMarginChnlD OBJECT-TYPE
        SYNTAX      Integer32 (-127..127)
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The current SNR operating margin measured at the
                     slicer input for channel D for the 10GBASE-T PMA.
                     It is reported in units of 0.1 dB to an accuracy of
                     0.5 dB within the range of -12.7 dB to 12.7 dB.
                     If an IEEE Std 802.3 Clause 45 MDIO Interface to the
                     PMA/PMD is present, then this attribute maps to the SNR
                     operating margin channel D register
                     (see IEEE Std 802.3, 45.2.1.68)."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.22 aSNROpMarginChnlD."
        ::= {ifMauEntry 22}

    ifMauEEESupportList OBJECT-TYPE
        SYNTAX      IANAifMauTypeListBits
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A read-only list of the possible PHY types for which
                    the underlying system supports Energy-Efficient Ethernet
                    (EEE) as defined in IEEE Std 802.3 Clause 78."
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.23 aEEESupportList."
        ::= { ifMauEntry 23 }

    ifMauEEELDFastRetrainCount OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of the number of 10GBASE-T fast retrains
                     initiated by the local device. The indication reflects
                     the state of the PHY event counter (see IEEE Std 802.3,
                     45.2.1.78.2 and 55.4.5.1.)"
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.24 aLDFastRetrainCount."
        ::= { ifMauEntry 24 }

    ifMauEEELPFastRetrainCount OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A count of the number of 10GBASE-T fast retrains
                     initiated by the link partner. The indication reflects
                     the state of the PHY event counter (see IEEE Std 802.3,
                     45.2.1.78.1 and 55.4.5.1.)"
        REFERENCE   "IEEE Std 802.3, 30.5.1.1.25 aLPFastRetrainCount."
        ::= { ifMauEntry 25 }

    ifMauTimeSyncCapabilityTX OBJECT-TYPE
        SYNTAX      TruthValue
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "This object indicates whether or not transmit
                    Time Sync is supported on this MAU."
        REFERENCE   "IEEE Std 802.3, 30.13.1.1 aTimeSyncCapabilityTX."
        ::= { ifMauEntry 26 }

    ifMauTimeSyncCapabilityRX OBJECT-TYPE
```

```
        SYNTAX      TruthValue
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "This object indicates whether or not receive
                    Time Sync is supported on this MAU."
        REFERENCE   "IEEE Std 802.3, 30.13.1.2 aTimeSyncCapabilityRX."
        ::= { ifMauEntry 27 }

    ifMauTimeSyncDelayTXmax OBJECT-TYPE
        SYNTAX      Integer32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The maximum data delay as specified in IEEE Std 802.3
                     90.7, expressed in units of ns.

                     If an IEEE Std 802.3 Clause 45 MDIO Interface to
                     PMA/PMD, WIS, PCS, PHY XS, DTE XS and/or TC is
                     present, then the value stored in this attribute
                     represents the maximum transmit path data delay
                     values, consisting of the sum of the values of the
                     registers in the instantiated sublayers (for each MMD,
                     in case of multiple instances)"
        REFERENCE   "IEEE Std 802.3, 30.13.1.3 aTimeSyncDelayTXmax."
        ::= { ifMauEntry 28 }

    ifMauTimeSyncDelayTXmin OBJECT-TYPE
        SYNTAX      Integer32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The minimum data delay as specified in IEEE Std 802.3
                     90.7, expressed in units of ns.

                     If an IEEE Std 802.3 Clause 45 MDIO Interface to
                     PMA/PMD, WIS, PCS, PHY XS, DTE XS and/or TC is
                     present, then the value stored in this attribute
                     represents the minimum transmit path data delay
                     values, consisting of the sum of the values of the
                     registers in the instantiated sublayers (for each MMD,
                     in case of multiple instances)"
        REFERENCE   "IEEE Std 802.3, 30.13.1.4 aTimeSyncDelayTXmin."
        ::= { ifMauEntry 29 }

    ifMauTimeSyncDelayRXmax OBJECT-TYPE
        SYNTAX      Integer32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The maximum data delay as specified in IEEE Std 802.3
                     90.7, expressed in units of ns.

                     If an IEEE Std 802.3 Clause 45 MDIO Interface to
                     PMA/PMD, WIS, PCS, PHY XS, DTE XS and/or TC is
                     present, then the value stored in this attribute
                     represents the maximum receive path data delay
                     values, consisting of the sum of the values of the
                     registers in the instantiated sublayers (for each MMD,
                     in case of multiple instances)"
        REFERENCE   "IEEE Std 802.3, 30.13.1.5 aTimeSyncDelayRXmax."
        ::= { ifMauEntry 30 }
```

```
    ifMauTimeSyncDelayRXmin OBJECT-TYPE
        SYNTAX      Integer32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "The minimum data delay as specified in IEEE Std 802.3
                     90.7, expressed in units of ns.

                     If an IEEE Std 802.3 Clause 45 MDIO Interface to
                     PMA/PMD, WIS, PCS, PHY XS, DTE XS and/or TC is
                     present, then the value stored in this attribute
                     represents the minimum receive path data delay
                     values, consisting of the sum of the values of the
                     registers in the instantiated sublayers (for each MMD,
                     in case of multiple instances)"
        REFERENCE   "IEEE Std 802.3, 30.13.1.6 aTimeSyncDelayRXmin."
        ::= { ifMauEntry 31 }


    -- The ifJackTable applies to MAUs attached to interfaces
    -- which have one or more external jacks (connectors).

    ifJackTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF IfJackEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "Information about the external jacks attached
                    to MAUs attached to an interface."
        ::= { dot3IfMauBasicGroup 2 }

    ifJackEntry OBJECT-TYPE
        SYNTAX      IfJackEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "An entry in the table, containing information
                    about a particular jack."
        INDEX       { ifMauIfIndex,
                      ifMauIndex,
                      ifJackIndex
                    }
        ::= { ifJackTable 1 }

    IfJackEntry ::=
        SEQUENCE {
            ifJackIndex                         Integer32,
            ifJackType                          IANAifJackType
        }

    ifJackIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "This variable uniquely identifies the jack
                    described by this entry from among other jacks
                    attached to the same MAU."
        ::= { ifJackEntry 1 }

    ifJackType OBJECT-TYPE
        SYNTAX      IANAifJackType
        MAX-ACCESS  read-only
```

```
        STATUS      current
        DESCRIPTION "The jack connector type, as it appears on the
                    outside of the system."
        ::= { ifJackEntry 2 }

    --
    -- The MAU Per-PCS Lane Statistics Table
    --

    ifMauPerPCSLaneStatsTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF IfMauPerPCSLaneStatsEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "Table of Per-PCS lane status information
                     about MAUs attached to an interface."
        ::= { dot3IfMauBasicGroup 3 }

    ifMauPerPCSLaneStatsEntry OBJECT-TYPE
        SYNTAX      IfMauPerPCSLaneStatsEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION "An entry in the table, containing information
                     about a single PCS lane."
        INDEX       { ifMauIfIndex,
                      ifMauIndex,
                      ifPCSLaneIndex
                    }
        ::= { ifMauPerPCSLaneStatsTable 1 }

    IfMauPerPCSLaneStatsEntry ::=
        SEQUENCE {
                 ifPCSLaneIndex                  Unsigned32,
                 ifMauPPLFECCorrectedBlocks      Counter64,
                 ifMauPPLFECUncorrectableBlocks  Counter64,
                 ifMauBIPErrorCount              Counter32,
                 ifMauPCStoPHYLaneMapping        Unsigned32
                 }

    ifPCSLaneIndex OBJECT-TYPE
        SYNTAX      Unsigned32 (0..255)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION  "This object provides the identification of the
                      PCS lane for which this ifMauPerPCSLaneStatsEntry
                      is applicable. This object can hold an integer value
                      from 0 to N-1, where N is the total number of PCS
                      lanes supported by the given PCS. "
        ::= { ifMauPerPCSLaneStatsEntry 1 }

    ifMauPPLFECCorrectedBlocks OBJECT-TYPE
        SYNTAX     Counter64
        MAX-ACCESS read-only
        STATUS     current
        DESCRIPTION "Generalized nonresettable counter. This counter has a
                    maximum increment rate of 1 200 000 counts per second
                    for 1000 Mb/s implementations, 5 000 000 counts per
                    second for 10 Gb/s and 40 Gb/s implementations, and
                    2 500 000 counts per second for 100 Gb/s implementations.
```

```
                      For 1000BASE-PX, 10/40/100GBASE-R PHYs, a count of
                      corrected FEC blocks received on the PSC lane identified
                      by ifPCSLaneIndex object. This counter will not increment
                      for other PHY types.

                      Increment the counter by one for each received block that
                      is corrected by the FE C function in the PHY for the
                      corresponding lane identified by the ifPCSLaneIndex
                      object.

                      If a Clause 45 MDIO Interface to the PCS is present,
                      then this object will map to the FEC corrected blocks
                      counter for PCS lane number n, identified by the
                      ifPCSLaneIndex object
                      (see IEEE Std 802.3 45.2.8.5, 45.2.1.91 , and 45.2.1.93)."
           REFERENCE "IEEE Std 802.3 30.5.1.1.17"
           ::= { ifMauPerPCSLaneStatsEntry 2 }

       ifMauPPLFECUncorrectableBlocks OBJECT-TYPE
           SYNTAX     Counter64
           MAX-ACCESS read-only
           STATUS     current
           DESCRIPTION "Generalized nonresettable counter. This counter has a
                        maximum increment rate of 1 200 000 counts per second
                        for 1000 Mb/s implementations, 5 000 000 counts
                        per second for 10 Gb/s and 40 Gb/s implementations,
                        and 2 500 000 counts per second for 100 Gb/s
                        implementations.

                        For 1000BASE-PX, 10/40/100GBASE-R PHYs, a count of
                        uncorrectable FEC blocks received on the PSC lane
                        identified by ifPCSLaneIndex object. This counter will
                        not increment for other PHY types.

                        Increment the counter by one for each FEC block that
                        is determined to be uncorrectable by the FEC function
                        in the PHY for the corresponding lane identified by
                        the ifPCSLaneIndex object.

                        If a Clause 45 MDIO Interface to the PCS is present,
                        then this object will map to the FEC uncorrectable
                        blocks counter for PSC lane number n, identified by
                        the ifPCSLaneIndex object
                       (see IEEE Std 802.3 45.2.8.6, 45.2.1.92, and 45.2.1.94)."
           REFERENCE    "IEEE Std 802.3 30.5.1.1.18"
           ::= { ifMauPerPCSLaneStatsEntry 3 }

       ifMauBIPErrorCount OBJECT-TYPE
          SYNTAX       Counter32
          MAX-ACCESS   read-only
          STATUS        current
          DESCRIPTION   "Generalized nonresettable counter. This counter
                         has a maximum increment rate of 10 000 counts per
                         second for 40 Gb/s implementations and 5 000 counts
                         per second for 100 Gb/ s implementations.

                         For 40/100GBASE-R PHYs, a count of BIP errors on the
                         PCS lane identified by ifPCSLaneIndex object. This
                         counter will not increment for other PHY types.
```

```
                     Increment the counter by one for each BIP error
                     detected during alignment marker removal in the
                     PCS identified by the ifPCSLaneIndex object.

                     If a Clause 45 MDIO Interface to the PCS is
                     present, then this object will map to the BIP error
                     counter for PCS lane number n, identified by the
                     ifPCSLaneIndex object
                     (see IEEE Std 802.3, 45.2.3.44 and 45.2.3.45)."
    REFERENCE       "IEEE Std 802.3, 30.5.1.1.11"
    ::= { ifMauPerPCSLaneStatsEntry 4 }

ifMauPCStoPHYLaneMapping OBJECT-TYPE
    SYNTAX          Unsigned32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION     "For 40/100GBASE-R PHYs, an array of PCS lane
                     identifiers. The indices of this array (0 to n–1)
                     denote the service interface lane number where n is
                     the number of PCS lanes in use. Each element of
                     this array contains the PCS lane number for the PCS
                     lane that has been detected in the corresponding
                     service interface lane.

                     If a Clause 45 MDIO Interface to the PCS is
                     present, then this object will map to the Lane
                     mapping register for PCS lane number n, identified
                     by the ifPCSLaneIndex object
                     (see IEEE Std 802.3 45.2.3.46 and 45.2.3.47)."
    REFERENCE       "IEEE Std 802.3 30.5.1.1.12"
    ::= { ifMauPerPCSLaneStatsEntry 5 }

--
-- The MAU Auto-Negotiation Table
--

ifMauAutoNegTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IfMauAutoNegEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "Configuration and status objects for the
                Auto-Negotiation function of MAUs attached to
                interfaces.

                The ifMauAutoNegTable applies to systems in
                which Auto-Negotiation is supported on one or
                more MAUs attached to interfaces. Note that if
                Auto-Negotiation is present and enabled, the
                ifMauType object reflects the result of the
                Auto-Negotiation function."
    ::= { dot3IfMauAutoNegGroup 1 }

ifMauAutoNegEntry OBJECT-TYPE
    SYNTAX      IfMauAutoNegEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION "An entry in the table, containing configuration
                and status information for the Auto-Negotiation
```

```
                function of a particular MAU."
    INDEX       { ifMauIfIndex,
                  ifMauIndex
                }
    ::= { ifMauAutoNegTable 1 }

IfMauAutoNegEntry ::=
    SEQUENCE {
        ifMauAutoNegAdminStatus           INTEGER,
        ifMauAutoNegRemoteSignaling       INTEGER,
        ifMauAutoNegConfig                INTEGER,
        ifMauAutoNegRestart               INTEGER,
        ifMauAutoNegCapabilityBits        IANAifMauAutoNegCapBits,
        ifMauAutoNegCapAdvertisedBits     IANAifMauAutoNegCapBits,
        ifMauAutoNegCapReceivedBits       IANAifMauAutoNegCapBits,
        ifMauAutoNegRemoteFaultAdvertised INTEGER,
        ifMauAutoNegRemoteFaultReceived   INTEGER
    }
ifMauAutoNegAdminStatus OBJECT-TYPE
    SYNTAX      INTEGER {
                    enabled(1),
                    disabled(2)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION "Setting this object to enabled(1) will cause
                the interface that has the Auto-Negotiation
                signaling ability to be enabled.

                If the value of this object is disabled(2) then
                the interface will act as it would if it had no
                Auto-Negotiation signaling. Under these
                conditions, an IEEE 802.3 MAU will immediately
                be forced to the state indicated by the value of
                the object ifMauDefaultType.

                When ifMauAutoNegAdminStatus transitions from enabled
                to disabled, the agent implementation shall
                verify that the operational type of the MAU (as
                reported by ifMauType) correctly transitions to
                the value specified by the ifMauDefaultType
                object, rather than continuing to operate at the
                value earlier determined by the Auto-Negotiation
                function."
    REFERENCE   "IEEE Std 802.3, 30.6.1.1.2, aAutoNegAdminState,
                and 30.6.1.2.2, acAutoNegAdminControl."
    ::= { ifMauAutoNegEntry 1 }

ifMauAutoNegRemoteSignaling OBJECT-TYPE
    SYNTAX      INTEGER {
                    detected(1),
                    notdetected(2)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A value indicating whether the remote end of
                the link is using Auto-Negotiation signaling. It
                takes the value detected(1) if and only if,
                during the previous link negotiation, FLP Bursts
```

```
                    were received."
        REFERENCE   "IEEE Std 802.3, 30.6.1.1.3,
                    aAutoNegRemoteSignaling."
        ::= { ifMauAutoNegEntry 2 }

    ifMauAutoNegConfig OBJECT-TYPE
        SYNTAX      INTEGER {
                        other(1),
                        configuring(2),
                        complete(3),
                        disabled(4),
                        parallelDetectFail(5)
                    }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A value indicating the current status of the
                    Auto-Negotiation process. The enumeration
                    parallelDetectFail(5) maps to a failure in
                    parallel detection as defined in 28.2.3.1 of
                    IEEE Std 802.3."
        REFERENCE   "IEEE Std 802.3, 30.6.1.1.4, aAutoNegAutoConfig."
        ::= { ifMauAutoNegEntry 4 }

    ifMauAutoNegRestart OBJECT-TYPE
        SYNTAX      INTEGER {
                        restart(1),
                        norestart(2)
                    }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION "If the value of this object is set to
                    restart(1) then this will force Auto-Negotiation
                    to begin link renegotiation. If Auto-Negotiation
                    signaling is disabled, a write to this object
                    has no effect.
                    Setting the value of this object to norestart(2)
                    has no effect."
        REFERENCE   "IEEE Std 802.3, 30.6.1.2.1,
                    acAutoNegRestartAutoConfig."
        ::= { ifMauAutoNegEntry 5 }

    ifMauAutoNegCapabilityBits OBJECT-TYPE
        SYNTAX      IANAifMauAutoNegCapBits
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A value that uniquely identifies the set of
                    capabilities of the local Auto-Negotiation
                    entity. Note that interfaces that support this
                    MIB may have capabilities that extend beyond the
                    scope of this MIB.

                    Note that the local Auto-Negotiation entity may
                    support some capabilities beyond the scope of
                    this MIB. This is indicated by returning the
                    bit value bOther in addition to any bit values
                    for standard capabilities that are listed in the
                    IANAifMauAutoNegCapBits TC."
        REFERENCE   "IEEE Std 802.3, 30.6.1.1.5,
                    aAutoNegLocalTechnologyAbility."
```

```
        ::= { ifMauAutoNegEntry 6 }

    ifMauAutoNegCapAdvertisedBits OBJECT-TYPE
        SYNTAX      IANAifMauAutoNegCapBits
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION "A value that uniquely identifies the set of
                    capabilities advertised by the local
                    Auto-Negotiation entity.

                    Capabilities in this object that are not
                    available in ifMauAutoNegCapabilityBits cannot
                    be enabled.

                    Note that the local Auto-Negotiation entity may
                    advertise some capabilities beyond the scope of
                    this MIB. This is indicated by returning the
                    bit value bOther in addition to any bit values
                    for standard capabilities that are listed in the
                    IANAifMauAutoNegCapBits TC."
        REFERENCE   "IEEE Std 802.3, 30.6.1.1.6,
                    aAutoNegAdvertisedTechnologyAbility."
        ::= { ifMauAutoNegEntry 7 }

    ifMauAutoNegCapReceivedBits OBJECT-TYPE
        SYNTAX      IANAifMauAutoNegCapBits
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION "A value that uniquely identifies the set of
                    capabilities received from the remote
                    Auto-Negotiation entity.
                    Note that interfaces that support this MIB may
                    be attached to remote Auto-Negotiation entities
                    that have capabilities beyond the scope of this
                    MIB. This is indicated by returning the bit
                    value bOther in addition to any bit values for
                    standard capabilities that are listed in the
                    IANAifMauAutoNegCapBits TC."
        REFERENCE   "IEEE Std 802.3, 30.6.1.1.7,
                    aAutoNegReceivedTechnologyAbility."
        ::= { ifMauAutoNegEntry 8 }

    ifMauAutoNegRemoteFaultAdvertised OBJECT-TYPE
        SYNTAX      INTEGER {
                        noError(1),
                        offline(2),
                        linkFailure(3),
                        autoNegError(4)
                    }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION "A value that identifies any local fault
                    indications that this MAU has detected and will
                    advertise at the next Auto-Negotiation
                    interaction for 1000 Mb/s MAUs."
        REFERENCE   "IEEE Std 802.3, 30.6.1.1.6,
                    aAutoNegAdvertisedTechnologyAbility."
        ::= { ifMauAutoNegEntry 9 }
```

```
ifMauAutoNegRemoteFaultReceived OBJECT-TYPE
    SYNTAX      INTEGER {
                    noError(1),
                    offline(2),
                    linkFailure(3),
                    autoNegError(4)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION "A value that identifies any fault indications
                received from the far end of a link by the
                local Auto-Negotiation entity for 1000 Mb/s
                MAUs."
    REFERENCE   "IEEE Std 802.3, 30.6.1.1.7,
                aAutoNegReceivedTechnologyAbility."
    ::= { ifMauAutoNegEntry 10 }

-- Placeholder to preserve module structure and assignments
dot3Placeholder OBJECT-TYPE
   SYNTAX       INTEGER {
                    placeholder(1)
                }
   MAX-ACCESS   read-only
   STATUS       current
   DESCRIPTION  "A placeholder object to preserve the assignments
                 that follow in the module. The assignment was given
                 to the object broadMauBasicTable in earlier
                 versions of this module. Preserving the assignments that
                 follow is considered important because they are used for
                 the IANA-MAU-MIB to assign as MAU type values."
   REFERENCE    "none"
   ::= { dot3PlaceholderGroup 1 }

-- Notifications for use by 802.3 MAUs

snmpDot3MauTraps OBJECT IDENTIFIER ::= { ieee8023snmpDot3MauMgt 0 }

rpMauJabberTrap NOTIFICATION-TYPE
    OBJECTS     { rpMauJabberState }
    STATUS      current
    DESCRIPTION "This trap is sent whenever a managed repeater
                MAU enters the jabber state.

                The agent shall limit the generation of
                consecutive rpMauJabberTraps so that there is at
                least a five-second gap between them."
    REFERENCE   "IEEE Std 802.3, 30.5.1.3.1, nJabber notification."
    ::= { snmpDot3MauTraps 1 }

ifMauJabberTrap NOTIFICATION-TYPE
    OBJECTS     { ifMauJabberState }
    STATUS      current
    DESCRIPTION "This trap is sent whenever a managed interface
                MAU enters the jabber state.

                The agent shall limit the generation of
                consecutive ifMauJabberTraps so that there is at
                least a five-second gap between them."
```

```
    REFERENCE   "IEEE Std 802.3, 30.5.1.3.1, nJabber notification."
    ::= { snmpDot3MauTraps 2 }

-- Conformance statements

mauModConf
        OBJECT IDENTIFIER ::= { ieee8023mauMIB 2 }
  mauModCompls
        OBJECT IDENTIFIER ::= { mauModConf 1 }
  mauModObjGrps
        OBJECT IDENTIFIER ::= { mauModConf 2 }
  mauModNotGrps
        OBJECT IDENTIFIER ::= { mauModConf 3 }

-- Object groups
mauRpGrpBasic OBJECT-GROUP
    OBJECTS     { rpMauType,
                  rpMauStatus,
                  rpMauMediaAvailable,
                  rpMauMediaAvailableStateExits,
                  rpMauJabberState,
                  rpMauJabberingStateEnters
                }
    STATUS      current
    DESCRIPTION "Basic conformance group for MAUs attached to
                repeater ports. This group is also the
                conformance specification for RFC 1515
                implementations."
    ::= { mauModObjGrps 1 }

mauRpGrp100Mbs OBJECT-GROUP
    OBJECTS     { rpMauFalseCarriers }
    STATUS      current
    DESCRIPTION "Conformance group for MAUs attached to
                repeater ports with 100 Mb/s or greater
                capability."
    ::= { mauModObjGrps 2 }

mauRpGrpJack OBJECT-GROUP
    OBJECTS     { rpJackType }
    STATUS      current
    DESCRIPTION "Conformance group for MAUs attached to
                repeater ports with managed jacks."
    ::= { mauModObjGrps 3 }

mauIfGrpBasic OBJECT-GROUP
    OBJECTS     { ifMauType,
                  ifMauStatus,
                  ifMauMediaAvailable,
                  ifMauMediaAvailableStateExits,
                  ifMauJabberState,
                  ifMauJabberingStateEnters,
                  dot3Placeholder
                }
    STATUS      current
    DESCRIPTION "Basic conformance group for MAUs attached to
                interfaces. This group also provides a
                conformance specification for RFC 1515
                implementations."
```

```
        ::= { mauModObjGrps 4 }

    mauIfGrpJack OBJECT-GROUP
        OBJECTS     { ifJackType }
        STATUS      current
        DESCRIPTION "Conformance group for MAUs attached to
                    interfaces with managed jacks."
        ::= { mauModObjGrps 5 }

    mauIfGrpHighCapacity OBJECT-GROUP
        OBJECTS     { ifMauFalseCarriers,
                      ifMauTypeListBits,
                      ifMauDefaultType,
                      ifMauAutoNegSupported
                    }
        STATUS      current
        DESCRIPTION "Conformance group for MAUs attached to
                    interfaces with 100 Mb/s or greater capability."
        ::= { mauModObjGrps 6 }

    mauIfGrpAutoNeg2 OBJECT-GROUP
        OBJECTS     { ifMauAutoNegAdminStatus,
                      ifMauAutoNegRemoteSignaling,
                      ifMauAutoNegConfig,
                      ifMauAutoNegCapabilityBits,
                      ifMauAutoNegCapAdvertisedBits,
                      ifMauAutoNegCapReceivedBits,
                      ifMauAutoNegRestart
                    }
        STATUS      current
        DESCRIPTION "Conformance group for MAUs attached to
                    interfaces with managed Auto-Negotiation."
        ::= { mauModObjGrps 7 }

    mauIfGrpAutoNeg1000Mbps OBJECT-GROUP
        OBJECTS     { ifMauAutoNegRemoteFaultAdvertised,
                      ifMauAutoNegRemoteFaultReceived
                    }
        STATUS      current
        DESCRIPTION "Conformance group for 1000 Mb/s MAUs attached to
                    interfaces with managed Auto-Negotiation."
        ::= { mauModObjGrps 8 }

    mauIfGrpHCStats OBJECT-GROUP
        OBJECTS     { ifMauHCFalseCarriers,
                      ifMauPCSCodingViolations
                    }
        STATUS      current
        DESCRIPTION "Conformance for high capacity statistics for
                    MAUs attached to interfaces."
        ::= { mauModObjGrps 9 }

   mauIfGrpFEC OBJECT-GROUP
        OBJECTS     { ifMauFECAbility,
                      ifMauFECMode,
                      ifMauFECCorrectedBlocks,
                      ifMauFECUnCorrectableBlocks
                    }
        STATUS      current
```

```
        DESCRIPTION "Conformance for FEC capable
                    MAUs attached to interfaces."
        ::= { mauModObjGrps 10 }

   mauIfGrpSNR OBJECT-GROUP
        OBJECTS     { ifMauSNROpMarginChnlA,
                      ifMauSNROpMarginChnlB,
                      ifMauSNROpMarginChnlC,
                      ifMauSNROpMarginChnlD
                    }
        STATUS      current
        DESCRIPTION "Conformance for SNR operating margin reporting
                    MAUs attached to interfaces."
        ::= { mauModObjGrps 11 }

    mauIfGrpEEE OBJECT-GROUP
        OBJECTS      { ifMauEEESupportList,
                       ifMauEEELDFastRetrainCount,
                       ifMauEEELPFastRetrainCount
                     }
        STATUS      current
        DESCRIPTION "Conformance EEE support and Fast Retrain count
                     reporting MAUs attached to interfaces."
        ::= { mauModObjGrps 12 }

    mauIfGrpTimeSync OBJECT-GROUP
        OBJECTS      { ifMauTimeSyncCapabilityTX,
                       ifMauTimeSyncCapabilityRX,
                       ifMauTimeSyncDelayTXmax,
                       ifMauTimeSyncDelayTXmin,
                       ifMauTimeSyncDelayRXmax,
                       ifMauTimeSyncDelayRXmin
                     }
        STATUS      current
        DESCRIPTION "Conformance Time Sync support and delay
                     reporting MAUs attached to interfaces."
        ::= { mauModObjGrps 13 }

    mauIfGrpPerPCSLaneStats OBJECT-GROUP
        OBJECTS      { ifMauPPLFECCorrectedBlocks,
                       ifMauPPLFECUncorrectableBlocks,
                       ifMauBIPErrorCount,
                       ifMauPCStoPHYLaneMapping
                     }
        STATUS      current
        DESCRIPTION "Conformance Per-PCS lane statistics
                     reporting MAUs attached to interfaces."
        ::= { mauModObjGrps 14 }

    -- Notification groups

    rpMauNotifications NOTIFICATION-GROUP
        NOTIFICATIONS { rpMauJabberTrap }
        STATUS      current
        DESCRIPTION "Notifications for repeater MAUs."
        ::= { mauModNotGrps 1 }

    ifMauNotifications NOTIFICATION-GROUP
        NOTIFICATIONS { ifMauJabberTrap }
```

```
        STATUS      current
        DESCRIPTION "Notifications for interface MAUs."
        ::= { mauModNotGrps 2 }

    -- Compliance statements

    mauModRpCompl2 MODULE-COMPLIANCE
        STATUS      current
        DESCRIPTION "Compliance for MAUs attached to repeater
                    ports.

                    Note that compliance with this compliance
                    statement requires compliance with the
                    snmpRptrModCompl MODULE-COMPLIANCE statement of
                    the IEEE8023-SNMP-REPEATER-MIB defined in Clause 7."

        MODULE -- this module
            MANDATORY-GROUPS { mauRpGrpBasic }

            GROUP       mauRpGrp100Mbs
            DESCRIPTION "Implementation of this optional group is
                        recommended for MAUs that have 100 Mb/s or
                        greater capability."

            GROUP       mauRpGrpJack
            DESCRIPTION "Implementation of this optional group is
                        recommended for MAUs that have one or more
                        external jacks."

            GROUP       rpMauNotifications

            DESCRIPTION "Implementation of this group is recommended
                        for MAUs attached to repeater ports."

            OBJECT      rpMauStatus
            MIN-ACCESS  read-only
            DESCRIPTION "Write access is not required."
        ::= { mauModCompls 1 }

    mauModIfCompl3 MODULE-COMPLIANCE
        STATUS      current
        DESCRIPTION "Compliance for MAUs attached to interfaces.

                    Note that compliance with this compliance
                    statement requires compliance with the
                    ifCompliance3 MODULE-COMPLIANCE statement of the
                    IF-MIB (RFC 2863) and the dot3Compliance2
                    MODULE-COMPLIANCE statement of the
                    IEEE8023-EtherLike-MIB defined in Clause 10."

        MODULE -- this module
            MANDATORY-GROUPS { mauIfGrpBasic }

            GROUP       mauIfGrpHighCapacity
            DESCRIPTION "Implementation of this optional group is
                        recommended for MAUs that have 100 Mb/s
                        or greater capability."
            GROUP       mauIfGrpHCStats
            DESCRIPTION "Implementation of this group is mandatory
```

```
                        for MAUs that have 1000 Mb/s capacity, and
                        is recommended for MAUs that have 100 Mb/s
                        capacity."


            GROUP       mauIfGrpJack
            DESCRIPTION "Implementation of this optional group is
                        recommended for MAUs that have one or more
                        external jacks."
            GROUP       mauIfGrpAutoNeg2
            DESCRIPTION "Implementation of this group is mandatory
                        for MAUs that support managed
                        Auto-Negotiation."
            GROUP       mauIfGrpAutoNeg1000Mbps
            DESCRIPTION "Implementation of this group is mandatory
                        for MAUs that have 1000 Mb/s or greater
                        capability and support managed
                        Auto-Negotiation."
            GROUP       ifMauNotifications
            DESCRIPTION "Implementation of this group is recommended
                        for MAUs attached to interfaces."
            OBJECT      ifMauStatus
            MIN-ACCESS  read-only
            DESCRIPTION "Write access is not required."
            GROUP        mauIfGrpFEC
            DESCRIPTION "Implementation of this optional group is
                         recommended for MAUs that incorporate FEC."
            GROUP        mauIfGrpSNR
            DESCRIPTION "Implementation of this optional group is
                         recommended for MAUs that report SNR operating
                         margin."
            GROUP        mauIfGrpEEE
            DESCRIPTION "Implementation of this group is
                         mandatory for MAUs that support EEE."
            GROUP        mauIfGrpTimeSync
            DESCRIPTION "Implementation of this group is
                         mandatory for MAUs that support Time Sync"
            GROUP        mauIfGrpPerPCSLaneStats
            DESCRIPTION "Implementation of this group is
                         mandatory for MAUs that report per-PCS lane
                         statistics."
      ::= { mauModCompls 2 }

END
```

Annex 12A

(informative)

Collection of performance data using WIS MDIO registers

The purpose of this annex is to illustrate how the WIS MDIO registers specified in 45.2.2 of IEEE Std 802.3 (and more specifically the subset required by 50.3.11 of IEEE Std 802.3) can be used to collect performance data either according to the conventions adopted by this document or according to the conventions specified in Clause 30 of IEEE Std 802.3.

For an agent implementing the SNMP managed objects required by this document, the first step in collecting WIS performance data would be to poll the 10G WIS status 3 register and the various error count registers (10G WIS section BIP error count, 10G WIS line BIP errors, 10G WIS far end line BIP errors, 10G WIS path block error count, and 10G WIS far end path block error count) once per second. The 10G WIS status 3 register bits are all latched until read and so would indicate whether a given defect occurred any time during the previous second. The error count registers roll over modulo 2^{16} or 2^{32}, and so to find the number of errors within the previous second, the agent would need to subtract (modulo 2^{16} or 2^{32}) the current reading from the reading taken 1 second ago. Armed with that information, the agent could determine for any layer whether the 1-second interval was an errored second, a severely errored second (that requires comparison with a threshold unless a defect is present), or a severely errored frame second. Determining whether a given second is or is not part of unavailable time requires additional logic; the most straightforward and accurate method is the delay-line approach outlined in Appendix A of IETF RFC 3592. With that information available, the agent would be able to determine by how much each current count should be incremented (including effects of inhibiting). Implementations that conform to ANSI T1.231-1997 would end each 15-minute interval on time-of-day clock 1/4 hour boundaries; if the delay-line approach is used, then a time-of-day timestamp would accompany the 1-second statistics. At the end of each interval, the current registers would be pushed onto the history stack and then would be cleared. The xyxIntervalValidData flags would be set to False(2) if the number of samples was not between 890 and 910 or, in the case of far-end counts, if a near-end defect occurred during the just-completed interval (see Section 9.1.2.2 of ANSI T1.231-1997 for details).

An agent implementing the oWIS objects of Clause 30 of IEEE Std 802.3 could also start by polling the 10G WIS status 3 register and the various error count registers to find the defects and error counts for the previous second, and it could determine the number of errors and whether the second was an errored second, a severely errored second, or a severely errored frame second in the same manner as above. The rest of the process would simply be to increment the generalized non-resettable counters without consideration of any inhibiting rules.

Annex A

(informative)

Bibliography

[B1] Beili, E., "Interface Stack Capability MIB."[22]

[B2] Case, J., and C. Partridge, "Case diagrams: A first step to diagrammed management information bases," *Computer Communications Review*, vol. 19, no. 1, pp. 13–16, Jan. 1989.

[B3] Faulk, Jr., R. L., C. A. Black, and A. S. Fraley, "Detection on a network by a mapping application of a relative location of a first device to a second device," U.S. Patent 5,293,635, filed Apr. 30, 1991 and issued Mar. 8, 1994.

[B4] Faulk, Jr. R. L., and C. A. Black, "Detection of a relative location of a network device using a multicast packet processed only by hubs," U.S. Patent 5,421,024, filed Aug. 30, 1993 and issued May 30, 1995.

Editor's Note (to be removed prior to publication):

Reference to IEEE Std 802.1Q was removed per Maintenance Request 1383 (see https://www.ieee802.org/3/maint/requests/maint_1383.pdf) and remaining references were renumbered.

[B5] IEEE Std 802.9™, IEEE Standard for Local and Metropolitan Area Networks: Integrated Services (IS) LAN Interface at the Medium Access Control (MAC) and Physical (PHY) Layers.[23, 24]

[B6] IETF RFC 1157, Simple Network Management Protocol, Case, J., Fedor, M., Schoffstall, M., and Davin, J., May 1990.[25]

[B7] IETF RFC 1573, Evolution of the Interfaces Group of MIB-II, McCloghrie, K., and Kastenholz, F., Jan. 1994.

[B8] IETF RFC 1212, Concise MIB Definitions, Rose, M., and McCloghrie, K., Mar. 1991.

[B9] IETF RFC 1284, Definitions of Managed Objects for Ethernet-Like Interface Types, Cook, J., Dec. 1991.

[B10] IETF RFC 1368, Definitions of Managed Objects for IEEE 802.3 Repeater Devices, McMaster, D., and McCloghrie, K., Oct. 1992.

[B11] IETF RFC 1369, Implementation Notes and Experience for The Internet Ethernet MIB, Kastenholz, F., Oct. 1992.

[B12] IETF RFC 1398, Definitions of Managed Objects for the Ethernet-like Interface Types, Kastenholz, F., Jan. 1993.

[B13] IETF RFC 1515, Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs), McMaster, D., McCloghrie, K., and Roberts, S., Sept. 1993.

[22]This document is available at the following URL: https://datatracker.ietf.org/doc/draft-ietf-opsawg-rfc5066bis/.
[23]IEEE publications are available from The Institute of Electrical and Electronics Engineers (http://standards.ieee.org/).
[24]The IEEE standards or products referred to in this clause are trademarks of The Institute of Electrical and Electronics Engineers, Inc.
[25]IETF documents (i.e., RFCs) are available for download at http://www.rfc-archive.org/.

[B14] IETF RFC 1525, Definitions of Managed Objects for Source Routing Bridges, Decker, E., McCloghrie, K., Langille, P., and Rijsinghani, A., Sept. 1993.

[B15] IETF RFC 1643, Definitions of Managed Objects for the Ethernet-like Interface Types, Kastenholz, F., July 1994.

[B16] IETF RFC 1650, Definitions of Managed Objects for the Ethernet-like Interface Types using SMIv2, Kastenholz, F., Aug. 1994.

[B17] IETF RFC 1905, Protocol Operations for version 2 of the Simple Network Management Protocol (SNMPv2), Case, J., McCloghrie, K., Rose, M., and Waldbusser, S., Jan. 1996.

[B18] IETF RFC 2026, The Internet Standards Process - Revision 3, Bradner, S., Oct. 1996.

[B19] IETF RFC 2108, Definitions of Managed Objects for IEEE 802.3 Repeater Devices using SMIv2, de Graaf, K., Romascanu, D., McMaster, D., and McCloghrie, K., Feb. 1997.

[B20] IETF RFC 2239, Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs) using SMIv2, de Graaf, K., Romascanu, D., McMaster, D., McCloghrie, K., and Roberts, S., Nov. 1997.

[B21] IETF RFC 2358, Definitions of Managed Objects for the Ethernet-like Interface Types, Flick, J., and Johnson, J., June 1998.

[B22] IETF RFC 2665, Definitions of Managed Objects for the Ethernet-like Interface Types, Flick, J., and Johnson, J., Aug. 1999.

[B23] IETF RFC 2666, Definitions of Object Identifiers for Identifying Ethernet Chip Sets, Flick, J., Aug. 1999.

[B24] IETF RFC 2668, Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs), Smith, A., Flick, J., de Graaf, K., Romascanu, D., McMaster, D., McCloghrie, K., and Roberts, S., Aug. 1999.

[B25] IETF RFC 3418, Management Information Base (MIB) for the Simple Network Management Protocol (SNMP), Presuhn, R., Dec. 2002.

[B26] IETF RFC 3621, Power Ethernet MIB, Berger, A., and Romascanu, D., Dec. 2003.

[B27] IETF RFC 3636, Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs), Flick, J., Sept. 2003.

[B28] IETF RFC 3635, Definitions of Managed Objects for the Ethernet-like Interface Types, Flick, J., Sept. 2003.

[B29] IETF RFC 3637, Definitions of Managed Objects for the Ethernet WAN Interface Sublayer, Heard, C., Sept. 2003.

[B30] IETF RFC 4070, Definitions of Managed Object Extensions for Very High Speed Digital Subscriber Lines (VDSL) Using Multiple Carrier Modulation (MCM) Line Coding, Dodge, M., and Ray, B., May 2005.

[B31] IETF RFC 4181, Guidelines for Authors and Reviewers of MIB Documents, Heard, C., Sept. 2005.

[B32] IETF RFC 4188, Definitions of Managed Objects for Bridges, Norseth, K., and Bell, E., Sept. 2005.

[B33] IETF RFC 4319, Definitions of Managed Objects for High Bit-Rate DSL—2nd generation (HDSL2) and Single-Pair High-Speed Digital Subscriber Line (SHDSL) Lines, Sikes, C., Ray, B., and Abbi, R., Dec. 2005.

[B34] IETF RFC 4836, Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs), Beili, E., Apr. 2007.

[B35] IETF RFC 4837, Managed Objects of Ethernet Passive Optical Networks (EPON), Khermosh, L., July 2007.

[B36] IETF RFC 4878, Definitions and Managed Objects for Operations, Administration, and Maintenance (OAM) Functions on Ethernet-Like Interfaces, Squire, M., June 2007.

[B37] IETF RFC 5066, Ethernet in the First Mile Copper (EFMCu) Interfaces MIB, Beili, E., Nov. 2007.

[B38] IETF, "Ethernet Interfaces and Hub MIB (hubmib) Charter."[26]

[B39] Internet Assigned Numbers Authority (IANA), "IANAifType Textual Convention definition."[27]

[B40] ISO/IEC 8824:1990, Information technology—Abstract Syntax Notation One (ASN.1).[28]

[B41] ISO/IEC 10165-4:1992, Information technology—Open Systems Interconnection—Structure of management information—Part 4: Guidelines for the definition of managed objects.

[B42] ISO/IEC 10165-5:1994, Information technology—Open Systems Interconnection—Structure of management information: Generic management information.

[B43] Kastenholz, F., "IEEE 802.3 Layer Management Draft compatible MIB for TCP/IP Networks," electronic mail message to mib-wg@nnsc.nsf.net, 9 June 1989.

[B44] Network Interoperability Consultative Committee (NICC), "Specification of the Access Network Frequency Plan (ANFP) applicable to transmission systems used on the BT Access Network," NICC Document ND1602:2005/08, Aug. 2005.[29]

[26]This document is available at the following URL: http://www.ietf.org/html.charters/OLD/ hubmib-charter.html.

[27]This document is available at the following URL: http://www.iana.org/assignments/ianaiftype-mib.

[28]ISO/IEC publications are available from the ISO Central Secretariat (http://www.iso.org/). ISO publications are also available in the United States from the American National Standards Institute (http://www.ansi.org/).

[29]NICC publications are available from the Network Interoperability Consultative Committee (http://www.niccstandards.org.uk/).

Annex B

(normative)

Branch and leaf assignments for IEEE 802.3 and IEEE 802.3.1 managed objects

This annex formally defines the branch and leaf assignments for the IEEE 802.3 and IEEE 802.3.1 managed objects. The branch and leaf assignments currently specified in this annex supercede any object identifiers (OIDs) formerly specified in this annex.

One use for these branch and leaf assignments can be found in Clause 57 of IEEE Std 802.3, which defines OAM, for example the variable descriptor format found in 57.6.1 of IEEE Std 802.3.

B.1 Branch and leaf table

An ASCII machine readable extract of Table B-1 can be obtained at the following URL[30]:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1AB.txt

Table B-1contains the branch and leaf assignments for Ethernet managed objects. The branch and leaf assignments are provided for use in the variable descriptors found in Clause 57 of IEEE Std 802.3.

Table B-1—Branch and leaf assignments for managed objects

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aResourceTypeIDName	ATTRIBUTE	GET	7	1
aResourceInfo	ATTRIBUTE	GET	7	2
oMACEntity	OBJECT	GET	3	1
aMACID	ATTRIBUTE	GET	7	1
aFramesTransmittedOK	ATTRIBUTE	GET	7	2
aSingleCollisionFrames	ATTRIBUTE	GET	7	3
aMultipleCollisionFrames	ATTRIBUTE	GET	7	4
aFramesReceivedOK	ATTRIBUTE	GET	7	5
aFrameCheckSequenceErrors	ATTRIBUTE	GET	7	6
aAlignmentErrors	ATTRIBUTE	GET	7	7
aOctetsTransmittedOK	ATTRIBUTE	GET	7	8

[30]Copyright release for branch and leaf table: Users of this standard may freely reproduce the branch and leaf table contained in this subclause so that it can be used for its intended purpose.

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aFramesWithDeferredXmissions	ATTRIBUTE	GET	7	9
aLateCollisions	ATTRIBUTE	GET	7	10
aFramesAbortedDueToXSColls	ATTRIBUTE	GET	7	11
aFramesLostDueToIntMACXmitError	ATTRIBUTE	GET	7	12
aCarrierSenseErrors	ATTRIBUTE	GET	7	13
aOctetsReceivedOK	ATTRIBUTE	GET	7	14
aFramesLostDueToIntMACRcvError	ATTRIBUTE	GET	7	15
aPromiscousStatus	ATTRIBUTE	GET-SET	7	16
aReadMulticastAddressList	ATTRIBUTE	GET	7	17
aMaxFrameLength	ATTRIBUTE	GET	7	357
aSlowProtocolFrameLimit	ATTRIBUTE	GET	7	426
aMulticastFramesXmittedOK	ATTRIBUTE	GET	7	18
aBroadcastFramesXmittedOK	ATTRIBUTE	GET	7	19
aFramesWithExcessiveDeferral	ATTRIBUTE	GET	7	20
aMulticastFramesReceivedOK	ATTRIBUTE	GET	7	21
aBroadcastFramesReceivedOK	ATTRIBUTE	GET	7	22
aInRangeLengthErrors	ATTRIBUTE	GET	7	23
aOutOfRangeLengthField	ATTRIBUTE	GET	7	24
aFrameTooLongErrors	ATTRIBUTE	GET	7	25
aMACEnableStatus	ATTRIBUTE	GET-SET	7	26
aTransmitEnableStatus	ATTRIBUTE	GET-SET	7	27
aMulticastReceiveStatus	ATTRIBUTE	GET-SET	7	28
aReadWriteMACAddress	ATTRIBUTE	GET-SET	7	29
aCollisionFrames	ATTRIBUTE	GET	7	30
aMACCapabilities	ATTRIBUTE	GET	7	89
aDuplexStatus	ATTRIBUTE	GET-SET	7	90
aRateControlAbility	ATTRIBUTE	GET	7	179

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aRateControlStatus	ATTRIBUTE	GET-SET	7	180
aDeferControlAbility	ATTRIBUTE	GET	7	311
aDeferControlStatus	ATTRIBUTE	GET-SET	7	312
acInitializeMAC	ACTION	—	9	1
acAddGroupAddress	ACTION	—	9	2
acDeleteGroupAddress	ACTION	—	9	3
acExecuteSelfTest	ACTION	—	9	4
oPHYEntity	OBJECT	GET	3	2
aPHYID	ATTRIBUTE	GET	7	31
aPHYType	ATTRIBUTE	GET	7	32
aPHYTypeList	ATTRIBUTE	GET	7	33
aSQETestErrors	ATTRIBUTE	GET	7	34
aSymbolErrorDuringCarrier	ATTRIBUTE	GET	7	35
aMIIDetect	ATTRIBUTE	GET	7	36
aPHYAdminState	ATTRIBUTE	GET	7	37
acPHYAdminControl	ACTION	—	9	5
oMACControlEntity	OBJECT	GET	3	8
aMACControlID	ATTRIBUTE	GET	7	92
aMACControlFunctionsSupported	ATTRIBUTE	GET-SET	7	93
aMACControlFramesTransmitted	ATTRIBUTE	GET	7	94
aMACControlFramesReceived	ATTRIBUTE	GET	7	95
aUnsupportedOpcodesReceived	ATTRIBUTE	GET	7	96
aPFCEnableStatus	ATTRIBUTE	GET	7	415
oMACControlFunctionEntity	OBJECT	GET	3	9
aPAUSELinkDelayAllowance	ATTRIBUTE	GET-SET	7	97
aPAUSEMACCtrlFramesTransmitted	ATTRIBUTE	GET	7	98
aPAUSEMACCtrlFramesReceived	ATTRIBUTE	GET	7	99

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
oMPCP	OBJECT	GET	3	21
aMPCPID	ATTRIBUTE	GET	7	351
aMPCPAdminState	ATTRIBUTE	GET	7	278
aMPCPMode	ATTRIBUTE	GET	7	279
aMPCPLinkID	ATTRIBUTE	GET	7	282
aMPCPRemoteMACAddress	ATTRIBUTE	GET	7	283
aMPCPRegistrationState	ATTRIBUTE	GET	7	284
aMPCPMACCtrlFramesTransmitted	ATTRIBUTE	GET	7	280
aMPCPMACCtrlFramesReceived	ATTRIBUTE	GET	7	281
aMPCPTxGate	ATTRIBUTE	GET	7	315
aMPCPTxRegAck	ATTRIBUTE	GET	7	316
aMPCPTxRegister	ATTRIBUTE	GET	7	317
aMPCPTxRegRequest	ATTRIBUTE	GET	7	318
aMPCPTxReport	ATTRIBUTE	GET	7	319
aMPCPRxGate	ATTRIBUTE	GET	7	320
aMPCPRxRegAck	ATTRIBUTE	GET	7	321
aMPCPRxRegister	ATTRIBUTE	GET	7	322
aMPCPRxRegRequest	ATTRIBUTE	GET	7	318
aMPCPRxReport	ATTRIBUTE	GET	7	324
aMPCPTransmitElapsed	ATTRIBUTE	GET	7	285
aMPCPReceiveElapsed	ATTRIBUTE	GET	7	286
aMPCPRoundTripTime	ATTRIBUTE	GET	7	287
aMPCPDiscoveryWindowsSent	ATTRIBUTE	GET	7	288
aMPCPDiscoveryTimeout	ATTRIBUTE	GET	7	290
aMPCPMaximumPendingGrants	ATTRIBUTE	GET	7	291
acMPCPAdminControl	ACTION	—	9	16
oOAM	OBJECT	GET	3	20

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aOAMID	ATTRIBUTE	GET	7	236
aOAMAdminState	ATTRIBUTE	GET	7	237
aOAMMode	ATTRIBUTE	GET-SET	7	238
aOAMDiscoveryState	ATTRIBUTE	GET	7	333
aOAMRemoteMACAddress	ATTRIBUTE	GET	7	239
aOAMLocalConfiguration	ATTRIBUTE	GET	7	334
aOAMRemoteConfiguration	ATTRIBUTE	GET	7	240
aOAMLocalPDUConfiguration	ATTRIBUTE	GET	7	335
aOAMRemotePDUConfiguration	ATTRIBUTE	GET	7	241
aOAMLocalFlagsField	ATTRIBUTE	GET	7	242
aOAMRemoteFlagsField	ATTRIBUTE	GET	7	243
aOAMLocalRevision	ATTRIBUTE	GET	7	336
aOAMRemoteRevision	ATTRIBUTE	GET	7	244
aOAMLocalState	ATTRIBUTE	GET	7	337
aOAMRemoteState	ATTRIBUTE	GET	7	245
aOAMRemoteVendorOUI	ATTRIBUTE	GET	7	246
aOAMRemoteVendorSpecificInfo	ATTRIBUTE	GET	7	247
aOAMUnsupportedCodesTx	ATTRIBUTE	GET	7	338
aOAMUnsupportedCodesRx	ATTRIBUTE	GET	7	250
aOAMInformationTx	ATTRIBUTE	GET	7	251
aOAMInformationRx	ATTRIBUTE	GET	7	252
aOAMUniqueEventNotificationTx	ATTRIBUTE	GET	7	339
aOAMDuplicateEventNotificationTx	ATTRIBUTE	GET	7	340
aOAMUniqueEventNotificationRx	ATTRIBUTE	GET	7	254
aOAMDuplicateEventNotificationRx	ATTRIBUTE	GET	7	255
aOAMLoopbackControlTx	ATTRIBUTE	GET	7	256
aOAMLoopbackControlRx	ATTRIBUTE	GET	7	257

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aOAMVariableRequestTx	ATTRIBUTE	GET	7	258
aOAMVariableRequestRx	ATTRIBUTE	GET	7	259
aOAMVariableResponseTx	ATTRIBUTE	GET	7	260
aOAMVariableResponseRx	ATTRIBUTE	GET	7	261
aOAMOrganizationSpecificTx	ATTRIBUTE	GET	7	262
aOAMOrganizationSpecificRx	ATTRIBUTE	GET	7	263
aOAMLocalErrSymPeriodConfig	ATTRIBUTE	GET	7	264
aOAMLocalErrSymPeriodEvent	ATTRIBUTE	GET	7	265
aOAMLocalErrFrameConfig	ATTRIBUTE	GET	7	266
aOAMLocalErrFrameEvent	ATTRIBUTE	GET	7	267
aOAMLocalErrFramePeriodConfig	ATTRIBUTE	GET	7	268
aOAMLocalErrFramePeriodEvent	ATTRIBUTE	GET	7	269
aOAMLocalErrFrameSecsSummaryConfig	ATTRIBUTE	GET	7	270
aOAMLocalErrFrameSecsSummaryEvent	ATTRIBUTE	GET	7	271
aOAMRemoteErrSymPeriodEvent	ATTRIBUTE	GET	7	272
aOAMRemoteErrFrameEvent	ATTRIBUTE	GET	7	273
aOAMRemoteErrFramePeriodEvent	ATTRIBUTE	GET	7	274
aOAMRemoteErrFrameSecsSummaryEvent	ATTRIBUTE	GET	7	275
aFramesLostDueToOAMError	ATTRIBUTE	GET	7	276
acOAMAdminControl	ACTION	—	9	15
oOMPEmulation	OBJECT	GET	3	19
aOMPEmulationID	ATTRIBUTE	GET	7	231
aOMPEmulationType	ATTRIBUTE	GET	7	232
aSLDErrors	ATTRIBUTE	GET	7	233
aCRC8Errors	ATTRIBUTE	GET	7	234
aGoodLLID	ATTRIBUTE	GET	7	341
aONUPONcastLLID	ATTRIBUTE	GET	7	342

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aOLTPONcastLLID	ATTRIBUTE	GET	7	343
aBadLLID	ATTRIBUTE	GET	7	235
oRepeater	OBJECT	GET	3	3
aRepeaterID	ATTRIBUTE	GET	7	38
aRepeaterType	ATTRIBUTE	GET	7	39
aRepeaterGroupCapacity	ATTRIBUTE	GET	7	40
aGroupMap	ATTRIBUTE	GET	7	41
aRepeaterHealthState	ATTRIBUTE	GET	7	42
aRepeaterHealthText	ATTRIBUTE	GET	7	43
aRepeaterHealthData	ATTRIBUTE	GET	7	44
aTransmitCollisions	ATTRIBUTE	GET	7	45
acResetRepeater	ACTION	—	9	6
acExecuteNonDisruptiveSelfTest	ACTION	—	9	7
nRepeaterHealth	NOTIFICATION	—	10	1
nRepeaterReset	NOTIFICATION	—	10	2
nGroupMapChange	NOTIFICATION	—	10	3
oGroup	OBJECT	GET	3	4
aGroupID	ATTRIBUTE	GET	7	46
aGroupPortCapacity	ATTRIBUTE	GET	7	47
aPortMap	ATTRIBUTE	GET	7	48
nPortMapChange	NOTIFICATION	—	10	4
oRepeaterPort	OBJECT	GET	3	5
aPortID	ATTRIBUTE	GET	7	49
aPortAdminState	ATTRIBUTE	GET	7	50
aAutoPartitionState	ATTRIBUTE	GET	7	51
aReadableFrames	ATTRIBUTE	GET	7	52
aReadableOctets	ATTRIBUTE	GET	7	53

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aFrameCheckSequenceErrors	ATTRIBUTE	GET	7	54
aAlignmentErrors	ATTRIBUTE	GET	7	55
aFramesTooLong	ATTRIBUTE	GET	7	56
aShortEvents	ATTRIBUTE	GET	7	57
aRunts	ATTRIBUTE	GET	7	58
aCollisions	ATTRIBUTE	GET	7	59
aLateEvents	ATTRIBUTE	GET	7	60
aVeryLongEvents	ATTRIBUTE	GET	7	61
aDataRateMismatches	ATTRIBUTE	GET	7	62
aAutoPartitions	ATTRIBUTE	GET	7	63
aIsolates	ATTRIBUTE	GET	7	64
aSymbolErrorDuringPacket	ATTRIBUTE	GET	7	65
aLastSourceAddress	ATTRIBUTE	GET	7	66
aSourceAddressChanges	ATTRIBUTE	GET	7	67
aBursts	ATTRIBUTE	GET	7	100
acPortAdminControl	ACTION	—	9	8
oMAU	OBJECT	GET	3	6
aMAUID	ATTRIBUTE	GET	7	68
aMAUType	ATTRIBUTE	GET-SET	7	69
aMAUTypeList	ATTRIBUTE	GET	7	70
aMediaAvailable	ATTRIBUTE	GET	7	71
aLoseMediaCounter	ATTRIBUTE	GET	7	72
aJabber	ATTRIBUTE	GET	7	73
aMAUAdminState	ATTRIBUTE	GET	7	74
aBbMAUXmitRcvSplitType	ATTRIBUTE	GET	7	75
aBroadbandFrequencies	ATTRIBUTE	GET	7	76
aFalseCarriers	ATTRIBUTE	GET	7	77

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aIdleErrorCount	ATTRIBUTE	GET	7	91
aSNROpMarginChnlA	ATTRIBUTE	GET	7	353
aSNROpMarginChnlB	ATTRIBUTE	GET	7	354
aSNROpMarginChnlC	ATTRIBUTE	GET	7	355
aSNROpMarginChnlD	ATTRIBUTE	GET	7	356
aPCSCodingViolation	ATTRIBUTE	GET	7	292
aFECAbility	ATTRIBUTE	GET	7	313
aFECmode	ATTRIBUTE	GET-SET	7	314
aFECCorrectedBlocks	ATTRIBUTE	GET	7	293
aFECUncorrectableBlocks	ATTRIBUTE	GET	7	294
acResetMAU	ACTION	—	9	9
acMAUAdminControl	ACTION	—	9	10
nJabber	NOTIFICATION	—	10	5
oAutoNegotiation	OBJECT	GET	3	7
aAutoNegID	ATTRIBUTE	GET	7	78
aAutoNegAdminState	ATTRIBUTE	GET	7	79
aAutoNegRemoteSignaling	ATTRIBUTE	GET	7	80
aAutoNegAutoConfig	ATTRIBUTE	GET-SET	7	81
aAutoNegLocalTechnologyAbility	ATTRIBUTE	GET	7	82
aAutoNegAdvertisedTechnologyAbility	ATTRIBUTE	GET-SET	7	83
aAutoNegReceivedTechnologyAbility	ATTRIBUTE	GET	7	84
aAutoNegLocalSelectorAbility	ATTRIBUTE	GET	7	85
aAutoNegAdvertisedSelectorAbility	ATTRIBUTE	GET-SET	7	86
aAutoNegReceivedSelectorAbility	ATTRIBUTE	GET	7	87
acAutoNegRestartAutoConfig	ACTION	—	9	11
acAutoNegAdminControl	ACTION	—	9	12
oAggregator	OBJECT	GET	3	10

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aAggID	ATTRIBUTE	GET	7	101
aAggDescription	ATTRIBUTE	GET	7	102
aAggName	ATTRIBUTE	GET-SET	7	103
aAggActorSystemID	ATTRIBUTE	GET-SET	7	104
aAggActorSystemPriority	ATTRIBUTE	GET-SET	7	105
aAggAggregateOrIndividual	ATTRIBUTE	GET	7	106
aAggActorAdminKey	ATTRIBUTE	GET-SET	7	107
aAggActorOperKey	ATTRIBUTE	GET	7	108
aAggMACAddress	ATTRIBUTE	GET	7	109
aAggPartnerSystemID	ATTRIBUTE	GET	7	110
aAggPartnerSystemPriority	ATTRIBUTE	GET	7	111
aAggPartnerOperKey	ATTRIBUTE	GET	7	112
aAggAdminState	ATTRIBUTE	GET-SET	7	113
aAggOperState	ATTRIBUTE	GET	7	114
aAggTimeOfLastOperChange	ATTRIBUTE	GET	7	115
aAggDataRate	ATTRIBUTE	GET	7	116
aAggOctetsTxOK	ATTRIBUTE	GET	7	117
aAggOctetsRxOK	ATTRIBUTE	GET	7	118
aAggFramesTxOK	ATTRIBUTE	GET	7	119
aAggFramesRxOK	ATTRIBUTE	GET	7	120
aAggMulticastFramesTxOK	ATTRIBUTE	GET	7	121
aAggMulticastFramesRxOK	ATTRIBUTE	GET	7	122
aAggBroadcastFramesTxOK	ATTRIBUTE	GET	7	123
aAggBroadcastFramesRxOK	ATTRIBUTE	GET	7	124
aAggFramesDiscardedOnTx	ATTRIBUTE	GET	7	125
aAggFramesDiscardedOnRx	ATTRIBUTE	GET	7	126
aAggFramesWithTxErrors	ATTRIBUTE	GET	7	127

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aAggFramesWithRxErrors	ATTRIBUTE	GET	7	128
aAggUnknownProtocolFrames	ATTRIBUTE	GET	7	129
aAggLinkUpDownNotificationEnable	ATTRIBUTE	GET-SET	7	130
nAggLinkUpNotification	NOTIFICATION	—	10	6
nAggLinkDownNotification	NOTIFICATION	—	10	7
aAggPortList	ATTRIBUTE	GET	7	131
aAggCollectorMaxDelay	ATTRIBUTE	GET-SET	7	132
oAggregationPort	OBJECT	GET	3	11
aAggPortID	ATTRIBUTE	GET	7	133
aAggPortActorSystemPriority	ATTRIBUTE	GET-SET	7	134
aAggPortActorSystemID	ATTRIBUTE	GET	7	135
aAggPortActorAdminKey	ATTRIBUTE	GET-SET	7	136
aAggPortActorOperKey	ATTRIBUTE	GET	7	137
aAggPortPartnerAdminSystemPriority	ATTRIBUTE	GET-SET	7	138
aAggPortPartnerOperSystemPriority	ATTRIBUTE	GET	7	139
aAggPortPartnerAdminSystemID	ATTRIBUTE	GET-SET	7	140
aAggPortPartnerOperSystemID	ATTRIBUTE	GET	7	141
aAggPortPartnerAdminKey	ATTRIBUTE	GET-SET	7	142
aAggPortPartnerOperKey	ATTRIBUTE	GET	7	143
aAggPortSelectedAggID	ATTRIBUTE	GET	7	144
aAggPortAttachedAggID	ATTRIBUTE	GET	7	145
aAggPortActorPort	ATTRIBUTE	GET	7	146
aAggPortActorPortPriority	ATTRIBUTE	GET-SET	7	147
aAggPortPartnerAdminPort	ATTRIBUTE	GET-SET	7	148
aAggPortPartnerOperPort	ATTRIBUTE	GET	7	149
aAggPortPartnerAdminPortPriority	ATTRIBUTE	GET-SET	7	150
aAggPortPartnerOperPortPriority	ATTRIBUTE	GET	7	151

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aAggPortActorAdminState	ATTRIBUTE	GET-SET	7	152
aAggPortActorOperState	ATTRIBUTE	GET	7	153
aAggPortPartnerAdminState	ATTRIBUTE	GET-SET	7	154
aAggPortPartnerOperState	ATTRIBUTE	GET	7	155
aAggPortAggregateOrIndividual	ATTRIBUTE	GET	7	156
oAggPortStats	OBJECT	GET	3	12
aAggPortStatsID	ATTRIBUTE	GET	7	157
aAggPortStatsLACPDUsRx	ATTRIBUTE	GET	7	158
aAggPortStatsMarkerPDUsRx	ATTRIBUTE	GET	7	159
aAggPortStatsMarkerResponsePDUsRx	ATTRIBUTE	GET	7	160
aAggPortStatsUnknownRx	ATTRIBUTE	GET	7	161
aAggPortStatsIllegalRx	ATTRIBUTE	GET	7	162
aAggPortStatsLACPDUsTx	ATTRIBUTE	GET	7	163
aAggPortStatsMarkerPDUsTx	ATTRIBUTE	GET	7	164
aAggPortStatsMarkerResponsePDUsTx	ATTRIBUTE	GET	7	165
oAggPortDebugInformation	OBJECT	GET	3	13
aAggPortDebugInformationID	ATTRIBUTE	GET	7	166
aAggPortDebugRxState	ATTRIBUTE	GET	7	167
aAggPortDebugLastRxTime	ATTRIBUTE	GET	7	168
aAggPortDebugMuxState	ATTRIBUTE	GET	7	169
aAggPortDebugMuxReason	ATTRIBUTE	GET	7	170
aAggPortDebugActorChurnState	ATTRIBUTE	GET	7	171
aAggPortDebugPartnerChurnState	ATTRIBUTE	GET	7	172
aAggPortDebugActorChurnCount	ATTRIBUTE	GET	7	173
aAggPortDebugPartnerChurnCount	ATTRIBUTE	GET	7	174
aAggPortDebugActorSyncTransitionCount	ATTRIBUTE	GET	7	175
aAggPortDebugPartnerSyncTransitionCount	ATTRIBUTE	GET	7	176

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aAggPortDebugActorChangeCount	ATTRIBUTE	GET	7	177
aAggPortDebugPartnerChangeCount	ATTRIBUTE	GET	7	178
oWIS	OBJECT	GET	3	14
aWISID	ATTRIBUTE	GET	7	181
aSectionStatus	ATTRIBUTE	GET	7	182
aSectionSESThreshold	ATTRIBUTE	GET-SET	7	183
aSectionSESs	ATTRIBUTE	GET	7	184
aSectionESs	ATTRIBUTE	GET	7	185
aSectionSEFSs	ATTRIBUTE	GET	7	186
aSectionCVs	ATTRIBUTE	GET	7	187
aJ0ValueTX	ATTRIBUTE	GET-SET	7	188
aJ0ValueRX	ATTRIBUTE	GET	7	189
aLineStatus	ATTRIBUTE	GET	7	190
aLineSESThreshold	ATTRIBUTE	GET-SET	7	191
aLineSESs	ATTRIBUTE	GET	7	192
aLineESs	ATTRIBUTE	GET	7	193
aLineCVs	ATTRIBUTE	GET	7	194
aFarEndLineSESs	ATTRIBUTE	GET	7	195
aFarEndLineESs	ATTRIBUTE	GET	7	196
aFarEndLineCVs	ATTRIBUTE	GET	7	197
aPathStatus	ATTRIBUTE	GET	7	198
aPathSESThreshold	ATTRIBUTE	GET-SET	7	199
aPathSESs	ATTRIBUTE	GET	7	200
aPathESs	ATTRIBUTE	GET	7	201
aPathCVs	ATTRIBUTE	GET	7	202
aJ1ValueTX	ATTRIBUTE	GET-SET	7	203
aJ1ValueRX	ATTRIBUTE	GET	7	204

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aFarEndPathStatus	ATTRIBUTE	GET	7	205
aFarEndPathSESs	ATTRIBUTE	GET	7	206
aFarEndPathESs	ATTRIBUTE	GET	7	207
aFarEndPathCVs	ATTRIBUTE	GET	7	208
oPSE	OBJECT	GET	3	15
aPSEID	ATTRIBUTE	GET	7	209
aPSEAdminState	ATTRIBUTE	GET	7	210
aPSEPowerPairsControlAbility	ATTRIBUTE	GET	7	211
aPSEPowerPairs	ATTRIBUTE	GET-SET	7	212
aPSEPowerDetectionStatus	ATTRIBUTE	GET	7	214
aPSEPowerClassification	ATTRIBUTE	GET	7	215
aPSEInvalidSignatureCounter	ATTRIBUTE	GET	7	227
aPSEPowerDeniedCounter	ATTRIBUTE	GET	7	228
aPSEOverLoadCounter	ATTRIBUTE	GET	7	229
aPSEShortCounter	ATTRIBUTE	GET	7	230
aPSEMPSAbsentCounter	ATTRIBUTE	GET	7	217
acPSEAdminControl	ACTION	—	9	13
aPSEActualPower	ATTRIBUTE	GET	7	427
aPSEPowerAccuracy	ATTRIBUTE	GET	7	428
aPSECumulativeEnergy	ATTRIBUTE	GET	7	429
oMidSpan	OBJECT	GET	3	17
aMidSpanID	ATTRIBUTE	GET	7	221
aMidSpanPSEGroupCapacity	ATTRIBUTE	GET	7	222
aMidSpanPSEGroupMap	ATTRIBUTE	GET	7	223
nMidSpanPSEGroupMapChange	NOTIFICATION	—	10	8
oPSEGroup	OBJECT	GET	3	18
aPSEGroupID	ATTRIBUTE	GET	7	224

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aPSECapacity	ATTRIBUTE	GET	7	225
aPSEMap	ATTRIBUTE	GET	7	226
nPSEMapChange	NOTIFICATION	—	10	9
oPAF	OBJECT	GET	3	24
aPAFID	ATTRIBUTE	GET	7	344
aPhyEnd	ATTRIBUTE	GET	7	326
aPHYCurrentStatus	ATTRIBUTE	GET	7	296
aPAFSupported	ATTRIBUTE	GET	7	304
aPAFAdminState	ATTRIBUTE	GET-SET	7	305
aLocalPAFCapacity	ATTRIBUTE	GET	7	327
aLocalPMEAvailable	ATTRIBUTE	GET	7	306
aLocalPMEAggregate	ATTRIBUTE	GET	7	307
aRemotePAFSupported	ATTRIBUTE	GET	7	328
aRemotePAFCapacity	ATTRIBUTE	GET	7	329
aRemotePMEAggregate	ATTRIBUTE	GET	7	310
oPME	OBJECT	GET	3	25
aPMEID	ATTRIBUTE	GET	7	330
aPMEAdminState	ATTRIBUTE	GET-SET	7	345
aPMEStatus	ATTRIBUTE	GET	7	346
aPMESNRMgn	ATTRIBUTE	GET	7	331
aTCCodingViolations	ATTRIBUTE	GET	7	332
aProfileSelect	ATTRIBUTE	GET-SET	7	347
aOperatingProfile	ATTRIBUTE	GET	7	348
aPMEFECCorrectedBlocks	ATTRIBUTE	GET	7	349
aPMEFECUncorrectableBlocks	ATTRIBUTE	GET	7	350
aTCCRCErrors	ATTRIBUTE	GET	7	352
aCMCounter	ATTRIBUTE	GET	7	88

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
oMACEntity	OBJECT	GET	—	—
Basic Package (Mandatory)	PACKAGE	—	—	—
Mandatory Package (Mandatory)	PACKAGE	—	4	1
Recommended Package (Conditional)	PACKAGE	—	4	2
Conditional Package (Conditional)	PACKAGE	—	4	3
Array Package (Conditional)	PACKAGE	—	4	4
ExcessiveDeferral Package (Conditional)	PACKAGE	—	4	5
PHYRecommended Package (Conditional)	PACKAGE	—	4	6
oPHYEntity	OBJECT	GET	—	—
Basic Package (Mandatory)	PACKAGE	—	—	—
MultiplePHY Package (Conditional)	PACKAGE	—	4	7
100MbsMonitor Capability (Conditional)	PACKAGE	—	4	8
oMACControlEntity	OBJECT	GET	—	—
Mandatory Package (Mandatory)	PACKAGE	—	—	—
Recommended Package (Conditional)	PACKAGE	—	4	17
oMACControlFunctionEntity	OBJECT	GET	—	—
Mandatory Package (Mandatory)	PACKAGE	—	—	—
Recommended Package (Conditional)	PACKAGE	—	4	25
oAggregator	OBJECT	GET	—	—
AggregatorBasic Package (Mandatory)	PACKAGE	—	—	—
AggregatorMandatory Package (Mandatory)	PACKAGE	—	4	19
AggregatorRecommended Package (Conditional)	PACKAGE	—	4	20
AggregatorConditional Package (Conditional)	PACKAGE	—	4	21
oAggregationPort	OBJECT	GET	—	—
AggregationPortBasic Package (Mandatory)	PACKAGE	—	—	—
AggregationPortMandatory Package (Mandatory)	PACKAGE	—	4	22
oAggPortStats	OBJECT	GET	—	—

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
AggPortStatsPackage (Conditional)	PACKAGE	—	4	23
oAggPortDebugInformation	OBJECT	GET	—	—
AggPortDebugInformation Package (Conditional)	PACKAGE	—	4	24
oOMP	OBJECT	GET	—	—
Optical Multipoint Emulation Package (Conditional)	PACKAGE	—	—	—
Optical Multipoint Emulation Error Package (Conditional)	PACKAGE	—	4	37
oRepeater	OBJECT	GET	—	—
RepeaterBasicControl Package (Mandatory)	PACKAGE	—	—	—
RepeaterPerfMonitor Package (Conditional)	PACKAGE	—	4	9
oGroup	OBJECT	GET	—	—
GroupBasicControl Package (Mandatory)	PACKAGE	—	—	—
oRepeaterPort	OBJECT	GET	—	—
PortBasicControl Package (Mandatory)	PACKAGE	—	—	—
PortPerfMonitor Package (Conditional)	PACKAGE	—	4	10
PortAddrTracking Package (Conditional)	PACKAGE	—	4	11
100MbpsMonitor Package (Conditional)	PACKAGE	—	4	12
Burst Package (Conditional)	PACKAGE	—	4	18
oMAU	OBJECT	GET	—	—
Basic Package (Mandatory)	PACKAGE	—	—	—
MAUControl Package (Conditional)	PACKAGE	—	4	13
MediaLossTracking Package (Conditional)	PACKAGE	—	4	14
BroadbandDTEMAU Package (Conditional)	PACKAGE	—	4	15
100MbsMonitor Capability (Conditional)	PACKAGE	—	4	16
10GBASE-T Operating Margin package (Conditional)	PACKAGE	—	4	39
PCS Code Error Monitor Capability (Optional)	PACKAGE	—	4	35
Forward Error Correction Capability (Conditional)	PACKAGE	—	4	30
oWIS	OBJECT	GET	—	—

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
WIS Basic Package (Mandatory)	PACKAGE	—	—	—
WIS Recommended Package (Conditional)	PACKAGE	—	4	26
oAutoNegotiation	OBJECT	GET	—	—
Auto Negotiation Package (Mandatory)	PACKAGE	—	—	—
oPSE	OBJECT	GET	—	—
PSEBasic Package (Mandatory)	PACKAGE	—	—	—
PSERecommended Package (Conditional)	PACKAGE	—	4	27
oMidSpan	OBJECT	GET	—	—
MidSpanBasic (Mandatory)	PACKAGE	—	—	—
oPAF	OBJECT	GET	—	—
Basic Package (Mandatory)	PACKAGE	—	—	—
PME Aggregation Package (Optional)	PACKAGE	—	4	38
oPME	OBJECT	GET	—	—
10P/2B Package (Mandatory)	PACKAGE	—	—	—
oResourceTypeID	OBJECT	GET	—	—
MII Package (Conditional)	PACKAGE	—	—	—
oTimeSync	OBJECT	GET	—	—
Support for Time Sync (Mandatory)	PACKAGE	—	4	40
aLldpXdot3LocPowerType	ATTRIBUTE	GET	7	358
aLldpXdot3LocPowerSource	ATTRIBUTE	GET	7	359
aLldpXdot3LocPowerPriority	ATTRIBUTE	GET	7	360
aLldpXdot3LocPDRequestedPowerValue	ATTRIBUTE	GET	7	361
aLldpXdot3LocPSEAllocatedPowerValue	ATTRIBUTE	GET	7	362
aLldpXdot3LocResponseTime	ATTRIBUTE	GET	7	363
aLldpXdot3LocReady	ATTRIBUTE	GET	7	364
aLldpXdot3LocReducedOperationPowerValue	ATTRIBUTE	GET	7	365
aLldpXdot3RemPowerType	ATTRIBUTE	GET	7	366

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aLldpXdot3RemPowerSource	ATTRIBUTE	GET	7	367
aLldpXdot3RemPowerPriority	ATTRIBUTE	GET	7	368
aLldpXdot3RemPDRequestedPowerValue	ATTRIBUTE	GET	7	369
aLldpXdot3RemPSEAllocatedPowerValue	ATTRIBUTE	GET	7	370
aTransmitLPIMicroseconds	ATTRIBUTE	GET	7	371
aReceiveLPIMicroseconds	ATTRIBUTE	GET	7	372
aTransmitLPITransitions	ATTRIBUTE	GET	7	373
aReceiveLPITransitions	ATTRIBUTE	GET	7	374
aLDFastRetrainCount	ATTRIBUTE	GET	7	375
aLPFastRetrainCount	ATTRIBUTE	GET	7	376
aEEESupportList	ATTRIBUTE	GET	7	377
oLldpXdot3Config	OBJECT	GET	3	27
LLDP Basic Package (mandatory)	PACKAGE	—	4	41
oLldpXdot3LocSystemsGroup	OBJECT	GET	3	28
LLDP MAC/PHY Configuration/Status Local Package (conditional)	PACKAGE	—	4	42
LLDP Power via MDI Local Package (conditional)	PACKAGE	—	4	44
LLDP Link Aggregation Local Package (conditional)	PACKAGE	—	4	46
LLDP Maximum Frame Size Local Package (conditional)	PACKAGE	—	4	48
LLDP EEE Local Package (optional)	PACKAGE	—	4	50
oLldpXdot3RemSystemsGroup	OBJECT	GET	3	29
LLDP MAC/PHY Configuration/Status Remote Package (conditional)	PACKAGE	—	4	43
LLDP Power via MDI Remote Package (conditional)	PACKAGE	—	4	45
LLDP Link Aggregation Remote Package (conditional)	PACKAGE	—	4	47
LLDP Maximum Frame Size Remote Package (conditional)	PACKAGE	—	4	49
LLDP EEE Remote Package (optional)	PACKAGE	—	4	51
aLldpXdot3LocTxTwSys	ATTRIBUTE	GET	7	378

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aLldpXdot3LocTxTwSysEcho	ATTRIBUTE	GET	7	379
aLldpXdot3LocRxTwSys	ATTRIBUTE	GET	7	380
aLldpXdot3LocRxTwSysEcho	ATTRIBUTE	GET	7	381
aLldpXdot3LocFbTwSys	ATTRIBUTE	GET	7	382
aLldpXdot3TxDllReady	ATTRIBUTE	GET	7	383
aLldpXdot3RxDllReady	ATTRIBUTE	GET	7	384
aLldpXdot3LocDllEnabled	ATTRIBUTE	GET	7	385
aLldpXdot3RemTxTwSys	ATTRIBUTE	GET	7	386
aLldpXdot3RemTxTwSysEcho	ATTRIBUTE	GET	7	387
aLldpXdot3RemRxTwSys	ATTRIBUTE	GET	7	388
aLldpXdot3RemRxTwSysEcho	ATTRIBUTE	GET	7	389
aLldpXdot3RemFbTwSys	ATTRIBUTE	GET	7	390
aLldpXdot3PortConfigTLVsTxEnable	ATTRIBUTE	GET	7	391
aLldpXdot3LocPortAutoNegSupported	ATTRIBUTE	GET	7	392
aLldpXdot3LocPortAutoNegEnabled	ATTRIBUTE	GET	7	393
aLldpXdot3LocPortAutoNegAdvertisedCap	ATTRIBUTE	GET	7	394
aLldpXdot3LocPortOperMauType	ATTRIBUTE	GET	7	395
aLldpXdot3LocPowerPortClass	ATTRIBUTE	GET	7	396
aLldpXdot3LocPowerMDISupported	ATTRIBUTE	GET	7	397
aLldpXdot3LocPowerMDIEnabled	ATTRIBUTE	GET	7	398
aLldpXdot3LocPowerPairControlable	ATTRIBUTE	GET	7	399
aLldpXdot3LocPowerPairs	ATTRIBUTE	GET	7	400
aLldpXdot3LocPowerClass	ATTRIBUTE	GET	7	401
aLldpXdot3LocMaxFrameSize	ATTRIBUTE	GET	7	402
aLldpXdot3RemPortAutoNegSupported	ATTRIBUTE	GET	7	403
aLldpXdot3RemPortAutoNegEnabled	ATTRIBUTE	GET	7	404
aLldpXdot3RemPortAutoNegAdvertisedCap	ATTRIBUTE	GET	7	405

Table B-1—Branch and leaf assignments for managed objects *(continued)*

IEEE Std 802.3 Clause 30 object name	Type	Access	BRANCH	LEAF
aLldpXdot3RemPortOperMauType	ATTRIBUTE	GET	7	406
aLldpXdot3RemPowerPortClass	ATTRIBUTE	GET	7	407
aLldpXdot3RemPowerMDISupported	ATTRIBUTE	GET	7	408
aLldpXdot3RemPowerMDIEnabled	ATTRIBUTE	GET	7	409
aLldpXdot3RemPowerPairControlable	ATTRIBUTE	GET	7	410
aLldpXdot3RemPowerPairs	ATTRIBUTE	GET	7	411
aLldpXdot3RemPowerClass	ATTRIBUTE	GET	7	412
aLldpXdot3RemMaxFrameSize	ATTRIBUTE	GET	7	413
oTimeSync	OBJECT	GET	3	26
aTimeSyncCapabilityTX	ATTRIBUTE	GET	7	416
aTimeSyncCapabilityRX	ATTRIBUTE	GET	7	417
aTimeSyncDelayTXmax	ATTRIBUTE	GET	7	418
aTimeSyncDelayTXmin	ATTRIBUTE	GET	7	419
aTimeSyncDelayRXmax	ATTRIBUTE	GET	7	420
aTimeSyncDelayRXmin	ATTRIBUTE	GET	7	421
oEXTENSION	OBJECT	GET	3	30
aEXTENSIONMACCtrlStatus	ATTRIBUTE	GET	7	422
aEXTENSIONMACCtrlFramesTransmitted	ATTRIBUTE	GET	7	423
aEXTENSIONMACCtrlFramesReceived	ATTRIBUTE	GET	7	424
aMPCPRecognizedMulticastIDs	ATTRIBUTE	GET	7	425
ifMauPerPCSLaneStatsTable	ATTRIBUTE	GET	7	430
ifMauPerPCSLaneStatsEntry	ATTRIBUTE	GET	7	431
ifPCSLaneIndex	ATTRIBUTE	GET	7	432
ifMauPPLFECCorrectedBlocks	ATTRIBUTE	GET	7	433
ifMauPPLFECUncorrectableBlocks	ATTRIBUTE	GET	7	434
ifMauBIPErrorCount	ATTRIBUTE	GET	7	435
ifMauPCStoPHYLaneMapping	ATTRIBUTE	GET	7	436