Draft Standard for
Local and metropolitan area networks—

Timing and Synchronization for Time-Sensitive Applications

Amendment: YANG Data Model

Sponsor

LAN/MAN Standards Committee
of the
IEEE Computer Society

Time-Sensitive Networking Task Group of IEEE 802.1

All participants in IEEE standards development have responsibilities under the IEEE patent policy and should familiarize themselves with that policy, see http://standards.ieee.org/about/sasb/patcom/materials.html

As part of our IEEE 802® process, the text of the PAR (Project Authorization Request) and CSD (Criteria for Standards Development) is reviewed regularly to ensure their continued validity. A vote of "Approve" on this draft is also an affirmation that the PAR is still valid. It is included in these cover pages.

The text proper of this draft begins with the title page (1). The cover pages (a), (b), (c) etc. are for 802.1 WG information, and will be removed prior to Sponsor Ballot.

Editors' Foreword

This draft standard is an amendment. The scope of changes to the base standard is thus strictly limited, as detailed in the PAR.

Information on participation in this project, and in the IEEE 802.1 Working Group can be found here.

Participation in 802.1 standards development

Comments on this draft are encouraged. **NOTE: All issues related to IEEE standards presentation style, formatting, spelling, etc. are routinely handled between the 802.1 Editor and the IEEE Staff Editors prior to publication, after balloting and the process of achieving agreement on the technical content of the standard is complete.** Readers are urged to devote their valuable time and energy only to comments that materially affect either the technical content of the document or the clarity of that technical content. Comments should not simply state what is wrong, but also what might be done to fix the problem.

Full participation in the work of IEEE 802.1 requires attendance at IEEE 802 meetings. Information on 802.1 activities, working papers, and email distribution lists etc. can be found on the 802.1 Website:

http://ieee802.org/1/

Use of the email distribution list is not presently restricted to 802.1 members, and the working group has a policy of considering ballot comments from all who are interested and willing to contribute to the development of the draft. Individuals not attending meetings have helped to identify sources of misunderstanding and ambiguity in past projects. The email lists exist primarily to allow the members of the working group to develop standards, and are not a general forum. All contributors to the work of 802.1 should familiarize themselves with the IEEE patent policy and anyone using the mail distribution will be assumed to have done so. Information can be found at http://standards.ieee.org/about/sasb/patcom/materials.html/

Comments on this document may be sent to the 802.1 email exploder, to the Editor, or to the Chair of the 802.1 Working Group.

Johannes Specht	Glenn Parsons
Editor, P802.1ASdn	Chair, 802.1 Working Group
Email:johannes.specht.standards@gmail.com	Email:l glenn.parsons@ericsson.com

NOTE: Comments whose distribution is restricted in any way cannot be considered, and may not be acknowledged.

All participants in IEEE standards development have responsibilities under the IEEE patent policy and should familiarize themselves with that policy, see http://standards.ieee.org/about/sasb/patcom/materials.html

As part of our IEEE 802 process, the text of the PAR and CSD (Criteria for Standards Development, formerly referred to as the 5 Criteria or 5C's) is reviewed on a regular basis in order to ensure their continued validity. A vote of "Approve" on this draft is also an affirmation by the balloter that the PAR is still valid.

Project Authorization Request, Scope, Purpose, and Criteria for Standards Development (CSD)

The complete amendment PAR, as approved by IEEE NesCom on the 24th of September 2020, can be found at:

https://development.standards.ieee.org/myproject-web/public/view.html#pardetail/8477

The 'Scope of the Proposed changes' and the 'Need for the Project' specify the changes to be made by this amendment (see below).

Scope of the Proposed changes:

This amendment specifies a YANG data model that allows configuring and state reporting for all managed objects of the base standard. This amendment specifies a Unified Modeling Language (UML)-based figure to explain the managed objects and the associated YANG data model.

Need for the Project:

YANG (IETF RFC 7950) is a formalized data modeling language that is widely accepted and can be used to simplify network configuration. The ability to manage timing and synchronization via YANG data models is needed for compatibility with modern network management systems.

Criteria for Standards Development:

The complete Criteria for Standards Development (CSD) can be found at:

https://mentor.ieee.org/802-ec/dcn/20/ec-20-0202-00-ACSD-p802-1asdn.pdf

Draft IEEE Standard for Local and metropolitan area networks—

Timing and Synchronization for Time-Sensitive Applications

Amendment: YANG Data Model

[This amendment is based on IEEE Std 802.1AS™-2020 as modified by IEEE Std 802.1AS™-2020/Cor 1-2021 and IEEE Std 802.1ASdr-2023.]

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in **_bold italic_**. Four editing instructions are used: change, delete, insert, and replace. **_Change_** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strikethrough~~ (to remove old material) and <u>underscore</u> (to add new material). **_Delete_** removes existing material. **_Insert_** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. **_Replace_** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.[1]

---

[1]Notes in text, tables, and figures are given for information only, and do not contain requirements needed to implement the standard.

P802.1ASdn/D1.2
October 13, 2023
(Amendment to
IEEE Std 802.1AS™-2020 as modified by IEEE Std 802.1AS™-2020/Cor 1-2021 and IEEE Std
802.1ASdr-2023)

Draft IEEE Standard for
Local and metropolitan area networks—

Timing and Synchronization for Time-Sensitive Applications

Amendment: YANG Data Model

Prepared by the
Time-Sensitive Networking Task Group of IEEE 802.1

Sponsor
LAN/MAN Standards Committee
of the
IEEE Computer Society

IEEE Standards Activities Department
445 Hoes Lane
Piscataway, NJ 08854, USA

Abstract: This amendment to IEEE Std 802.1AS^{TM}-2020 specifies a YANG data model that allows configuration and state reporting for all managed objects of the base standard.

Keywords: YANG, data model, network management, managed objects, IEEE 802.1AS™, synchronization, syntonization, time-aware system

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading "Important Notices and Disclaimers Concerning IEEE Standards Documents." They can also be obtained on request from IEEE or viewed at http://standards.ieee.org/ipr/disclaimers.html.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association ("IEEE-SA") Standards Board. IEEE ("the Institute") develops its standards through a consensus development process, approved by the American National Standards Institute ("ANSI"), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied "AS IS" and "WITH ALL FAULTS."

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

    Secretary, IEEE-SA Standards Board
    445 Hoes Lane
    Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at https://ieeexplore.ieee.org or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE-SA Website at https://standards.ieee.org.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: https://standards.ieee.org/standard/index.html. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at https://standards.ieee.org/about/sasb/patcom/patents.html. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Trademarks

OMG®, UML® and Unified Modeling Language™ are either registered trademarks or trademarks of Object
Management Group, Inc. In the United States and/or other countries.

Participants

<<The following lists will be updated in the usual way prior to publication>>

At the time this standard was completed, the IEEE 802.1 working group had the following membership:

Glenn Parsons, *Chair*
Jessy Rouyer, *Vice Chair*
János Farkas, *TSN Task Group Chair*
Geoffrey Garner, *Editor, IEEE Std 802.1AS*
Johannes Specht, *Editor, P802.1ASdn*

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

<<The above lists will be updated in the usual way prior to publication>>

When the IEEE-SA Standards Board approved this standard on <dd> <month> <year>, it had the following
membership:

Jean-Philippe Faure, *Chair*
Vacant Position, *Vice-Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Chuck Adams   Michael Janezic   Robby Robson
Masayuki Ariyoshi   Thomas Koshy   Dorothy Stanley
Ted Burse   Joseph L. Koepfinger1   Adrian Stephens
Stephen Dukes   Kevin Lu   Mehmet Ulema
Doug Edwards   Daleep Mohla   Phil Wennblom
J. Travis Griffith   Damir Novosel   Howard Wolfman
Gary Hoffman   Ronald C. Petersen   Yu Yuan
                             Annette D. Reilly

   *Member Emeritus

<<The above lists will be updated in the usual way prior to publication>>

Introduction

This introduction is not part of IEEE Std 802.1ASdn™-2023, IEEE Standard for Local and metropolitan
area networks—Timing and Synchronization for Time-Sensitive Applications—Amendment: YANG Data
Model

The first edition of IEEE Std 802.1AS was published in 2011. A first corrigendum, IEEE Std
802.1AS™-2011/Cor1-2013, provided technical and editorial corrections. A second corrigendum, IEEE Std
802.1AS™-2011/Cor2-2015 provided additional technical and editorial corrections.

The second edition, IEEE Std 802.1AS-2020, added support for multiple gPTP domains, Common Mean
Link Delay Service, external port configuration, and Fine Timing Measurement for 802.11 transport.
Backward compatibility with IEEE Std 802.1AS-2011 was maintained. The corrigendum IEEE
802.1AS-2020/Cor 1-2021 provides technical and editorial corrections. The amendment IEEE Std
802.1ASdr-2023 changes non-inclusive terms, replacing them with their suitable and inclusive terminology
wherever possible.

This amendment to IEEE Std 802.1AS™-2020 specifies a YANG data model that allows configuration and
state reporting for all managed objects of the base standard.

Contents

List of Figures

P802.1ASdn/D1.2   October 13, 2023

Draft IEEE Standard for Local and metropolitan area networks—Timing and Synchronization for Time-Sensitive Applications—Amendment: YANG Data Model

List of Tables

2. Normative references

Insert the following references in alphanumeric order:

IEEE Std 802d™-2017, IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture—Amendment 1: Allocation of Uniform Resource Name (URN) Values in IEEE 802® Standards.

IEEE Std 1588e™-20**xx**, IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems—Amendment: MIB and YANG Data Models.

IETF RFC 7950, The YANG 1.1 Data Modeling Language, August 2016.

4. Acronyms and abbreviations

Insert the following abbreviations in alphanumeric order, renumbering footnotes as necessary:

NETCONF   Network Configuration Protocol

UML®   Unified Modeling Language™

5. Conformance

5.4.2 PTP Instance Options

Insert the following item 5.4.2 k) 4) after 5.4.2 k) 3) (MIB), renumbering as necessary:

4)   If YANG is supported with a remote management protocol, support the YANG data model in
     Clause 17.

Change the title of Clause 15 as follows:

15. ~~Managed object definitions~~Management Information Base (MIB)

Insert the following new Clause 17:

17. YANG Data Model

YANG (IETF RFC 7950 [B45]) is a data modeling language used to model configuration data and state data for remote network management protocols. Examples of YANG-based remote network management protocols include NETCONF (IETF RFC 6241 [B41]) and RESTCONF (IETF RFC 8040 [B46]). Each remote network management protocol uses a specific encoding on-the-wire, such as XML or JSON. A YANG module specifies the organization and rules for the management data, and a mapping from YANG to the specific encoding enables the data to be understood correctly by both client (e.g., network manager) and server (e.g., PTP Instances).

This clause specifies the YANG data model for IEEE Std 802.1AS.

This clause:

   a)   Introduces the organization of the data models, including the relationship with other standards (17.1)
   b)   Provides an overview of the hierarchy of the data models using a UML-like representation (17.2)
   c)   Summarizes the structure of the YANG data model (17.3)
   d)   Reviews security considerations (17.4)
   e)   Provides a schema tree as an overview of the YANG module (17.5)
   f)   Specifies the YANG module (17.6)

17.1 YANG framework

Clause 14 specifies the information model for management of this standard. The data model for a specific management mechanism is derived from the information model. Since YANG-based protocols are an example of a management mechanism, the YANG data model of this clause is derived from Clause 14.

NOTE 1 - The MIB modules specified in Clause 15 were also derived from Clause 14. Consequently, the capabilities and structure of the YANG data models are aligned with those represented by the MIB. However the YANG data model has not been derived from the MIB, and there has been no attempt to include data or modeling constructs that might appear in the MIB but not in the information model.

The information model in Clause 14 is organized as a hierarchy of data sets. Each data set contains one or more related members (items of data that can be read or written). In the context of YANG, each data set is represented as a YANG "container", and each member is represented as a YANG "leaf".

17.1.1 Relationship to the IEEE Std 1588 data model

The YANG data models specified in this standard are based on, and augment, those specified in IEEE Std 1588. In particular the ieee802-dot1as-ptp.yang module imports the ieee1588-ptp module as a whole, augmenting that module as necessary to meet the requirements of this standard. This import makes existing and new IEEE Std 1588 YANG capabilities not specifically addressed by the present standard available to its implementors without delay, without the need to revise or amend IEEE Std 802.1AS.

Some of the data sets in Clause 14 (e.g., defaultDS) are derived from IEEE Std 1588, and some of the data sets are unique to IEEE Std 802.1AS (i.e., not derived from IEEE Std 1588). For each data set in Clause 14 that is derived from IEEE Std 1588, a portion of the members are derived from IEEE Std 1588, and the

remaining members are unique to IEEE Std 802.1AS. For the members that are derived from IEEE Std 1588, the specifications in both standards are analogous (i.e., same name, data type, semantics, etc).

The YANG data model for IEEE Std 1588-2019 is published as amendment IEEE Std 1588e. The YANG module of IEEE Std 1588e (ieee1588-ptp.yang) contains the hierarchy (tree) of data sets and their members.

The YANG module of this clause (ieee802-dot1as-ptp.yang) uses the YANG "import" statement to import the YANG module of IEEE Std 1588e. This effectively uses the IEEE Std 1588 YANG tree as the foundation of the IEEE Std 802.1AS YANG tree. By importing the tree and its data set containers, all members from Clause 14 that are derived from IEEE Std 1588 are also imported.

The core of the YANG module for IEEE Std 802.1AS consists of YANG "augment" statements, used to add members to the tree that are unique for IEEE Std 802.1AS.

NOTE 2 - IETF RFC8575 [B48] is the standard YANG data model for IEEE Std 1588-2008. The YANG data model of IEEE Std 1588e is effectively a newer version of RFC8575. Therefore, the YANG module of RFC8575 is not imported by the YANG module of this clause.

17.2 IEEE 802.1AS YANG data model

This clause uses a UML-like representation to provide an overview of the hierarchy of the IEEE Std 802.1AS YANG data model.

A representation of the management model is provided in Figures 17-1 through 17-4. The purpose of the diagram is to express the model design in a concise manner. The structure of the representation shows the name of the object followed by a list of properties for the object. The properties indicate their type and accessibility. It should be noted that the representation is meant to express simplified semantics for the properties. It is not meant to provide the specific datatype used to encode the object in either MIB or YANG. In the representation, a box with a white background represents information that comes from sources outside of this IEEE standard. A box with a gray background represents objects that are defined by this IEEE standard.

NOTE 1 - OMG® UML 2.5 [B49] conventions together with C++ language constructs are used in this clause as a representation to convey model structure and relationships.

NOTE 2 - This standard specifies YANG for Clause 14 of this standard. There are optional features in the YANG module of IEEE Std 1588 that are not specified in Clause 14, and therefore not shown in the figures of this subclause. If optional IEEE Std 1588 YANG features are implemented, conformance is specified by IEEE Std 1588.

For all figures, Clause 14 data that is imported from the ieee1588-ptp.yang module is shown in white, and Clause 14 data in augments of ieee802-dot1as-ptp.yang is shown in gray.

Figure 17-1 provides an overview of the IEEE Std 802.1AS YANG tree. The top level instance-list provides the list of one or more PTP Instances, each with data sets. For each PTP Instance, port-ds-list provides the list of one or more PTP Ports, each with data sets. The common-services apply to all PTP Instances, including the Common Mean Link Delay Service (cmlds).

Figure 17-2 provides detail for the data sets of each PTP Instance, including each data set member.

Figure 17-3 provides detail for the data sets of each PTP Port, including each data set member.

NOTE 2 - 14.8.4 specifies ptpPortEnabled (ptp-port-enabled), which is provided in YANG as the semantically equivalent node in ieee1588-ptp named port-enable (in port-ds of Figure 17-3). 14.8.15 specifies

mgtSettableLogAnnounceInterval (mgt-settable-log-announce-interval), which is provided in YANG as the semantically equivalent node in ieee1588-ptp named log-announce-interval (in port-ds of Figure 17-3). 14.8.20 specifies mgtSettableLogSyncInterval (mgt-settable-log-sync-interval), which is provided in YANG as the semantically equivalent node in ieee1588-ptp named log-sync-interval (in port-ds of Figure 17-3).

Figure 17-4 provides detail for the common services, including each data set member. The Common Mean Link Delay Service (cmlds) has a data sets for the service itself (e.g., default-ds), and data sets for each PTP Link Port.

NOTE 3 - 14.16.9 specifies neighborRateRatio (neighbor-rate-ratio), which is provided in YANG as the semantically equivalent node in ieee1588-ptp named scaled-neighbor-rate-ratio (in link-port-ds of Figure 17-4).

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54

Figure 17-1—Overview of YANG tree

Figure 17-2—PTP Instance detail

NOTE 4 - IEEE Std 1588-2019 uses the original terminology of 'master' and 'slave', and therefore ieee1588-ptp.yang uses that terminology. IEEE Std 802.1ASdr-2023 uses the alternative terminology of 'timeTransmitter' and 'timeReceiver' (from IEEE Std 1588g-2022), and therefore Clause 14 uses that terminology. In the UML-like diagrams, and associated YANG data model, YANG nodes that are imported from ieee1588-ptp.yang use the original terminology, but are equivalent to the corresponding data set members from Clause 14 (using alternate terminology). This includes:
– 1588 acceptable-master-ds is equivalent to 802.1AS acceptable-time-transmitter-ds.
– 1588 acceptable-master-port-ds is equivalent to 802.1AS acceptable-time-transmitter-port- ds.
– 1588 current-ds.offset-from-master is equivalent to 802.1AS current-ds.offset-from-time-transmitter.

P802.1ASdn/D1.2   October 13, 2023

Draft IEEE Standard for Local and metropolitan area networks—Timing and Synchronization for Time-Sensitive Applications—Amendment: YANG Data Model

ports

* port-index

port

port-ds

|		
struct	port-identity;	// r
enum	port-state;	// r
time-interval	mean-link-delay;	// r
int8	log-announce-interval;	// r-w
uint8	announce-receipt-timeout;	// r-w
int8	log-sync-interval;	// r-w
enum	delay-mechanism;	// r-w
uint8	version-number;	// r-w
uint8	minor-version-number;	// r-w
time-interval	delay-asymmetry;	// r-w
bool	port-enable;	// r-w
bool	is-measuring-delay;	// r
bool	as-capable;	// r
time-interval	mean-link-delay-thresh;	// r-w
int32	neighbor-rate-ratio;	// r
int8	initial-log-announce-interval;	// r-w
int8	current-log-announce-interval;	// r
bool	use-mgt-log-announce-interval;	// r-w
int8	initial-log-sync-interval;	// r-w
int8	current-log-sync-interval;	// r
bool	use-mgt-log-sync-interval;	// r-w
uint8	sync-receipt-timeout;	// r-w
uscaled-ns	sync-receipt-timeout-interval;	// r
int8	initial-log-pdelay-req-interval;	// r-w
int8	current-log-pdelay-req-interval;	// r
bool	use-mgt-log-pdelay-req-interval;	// r-w
int8	mgt-log-pdelay-req-interval;	// r-w
int8	initial-log-gptp-cap-interval;	// r-w
int8	current-log-gptp-cap-interval;	// r
bool	use-mgt-log-gptp-cap-interval;	// r-w
int8	mgt-log-gptp-cap-interval;	// r-w
int8	initial-compute-rate-ratio;	// r-w
int8	current-compute-rate-ratio;	// r
bool	use-mgt-compute-rate-ratio;	// r-w
int8	mgt-compute-rate-ratio;	// r-w
int8	initial-compute-mean-link-delay;	// r-w
int8	current-compute-mean-link-delay;	// r
bool	use-mgt-compute-mean-link-delay;	// r-w
int8	mgt-compute-mean-link-delay;	// r-w
uint8	allowed-lost-responses;	// r-w
uint8	allowed-faults;	// r-w
uint8	gptp-cap-receipt-timeout;	// r-w
float64	nup;	// r-w
float64	ndown;	// r-w
bool	one-step-tx-oper;	// r
bool	one-step-receive;	// r
bool	one-step-transmit;	// r
int8	initial-one-step-tx-oper;	// r-w
int8	current-one-step-tx-oper;	// r
bool	use-mgt-one-step-tx-oper;	// r-w
int8	mgt-one-step-tx-oper;	// r-w
bool	sync-locked;	// r
uint64	*pdelay-truncated-timestamps;	// r

description-port-ds

string	profile-identifier;	// r

port-statistics-ds

counter32	rx-sync-count;	// r
counter32	rx-one-step-sync-count;	// r
counter32	rx-follow-up-count;	// r
counter32	rx-pdelay-req-count;	// r
counter32	rx-pdelay-resp-count;	// r
counter32	rx-pdelay-resp-follow-up-count;	// r
counter32	rx-announce-count;	// r
counter32	rx-packet-discard-count;	// r
counter32	sync-receipt-timeout-count;	// r
counter32	announce-receipt-timeout-count;	// r
counter32	pdelay-allowed-lost-exceeded-count;	// r
counter32	tx-sync-count;	// r
counter32	tx-one-step-sync-count;	// r
counter32	tx-follow-up-count;	// r
counter32	tx-pdelay-req-count;	// r
counter32	tx-pdelay-resp-count;	// r
counter32	tx-pdelay-resp-follow-up-count;	// r
counter32	tx-announce-count;	// r

acceptable-master-port-ds

bool	enable;	// r-w

external-port-config-port-ds

port-state	desired-state;	// r-w

asymmetry-measurement-mode-ds

bool	enabled;	// r-w

common-services-port-ds

|		
uint16	cmlds-link-port-port-number	// r

Figure 17-3—PTP Port detail

Figure 17-4—Common services detail

17.3 Structure of the YANG data model

The YANG data model specified by this standard uses the YANG modules summarized in Table 17-1.[1]

In the YANG module definitions, if any discrepancy between the "description" text and the corresponding definition in any other part of this standard occur, the definitions outside this clause (Clause 17) take precedence..

---

[1]An amendment's designation is often used to refer to functionality in an IEEE standard after the amendment has been incorporated in a revision of the standard, even if the functionality has been revised. The amendment that added each YANG module is identified to help locate the relevant provisions of this standard.

Table 17-1—Summary of the YANG modules

Module	Managed functionality	YANG specification notes
ietf-yang-types	Type definitions	IETF RFC 6991 - Common YANG Data Types.
ieee1588-ptp	Clause 14	IEEE Std 1588e - MIB and YANG Data Models. IEEE Std 802.1ASdn imports this YANG module as its foundational tree, including a subset of members from Clause 14.
ieee802-dot1as-ptp	Clause 14	IEEE Std 802.1ASdn - YANG Data Model. The YANG module of this clause uses YANG augments to add members from Clause 14 that are unique to IEEE Std 802.1AS.

29

17.4 Security considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF ([B41]) and RESTCONF ([B46]). NETCONF and RESTCONF protocols provide the means to secure communication between client and server, using secure transport layers such as Secure Shell (SSH) ([B42]) and Transport Layer Security (TLS) ([B44]).

It is the responsibility of a system's implementor and administrator to ensure that the protocol entities in the system that support NETCONF, and any other remote configuration protocols that make use of these YANG modules, are properly configured to allow access only to those principals (users) that have legitimate rights to read or write data nodes. This standard does not specify how the credentials of those users are to be stored or validated.

The Network Configuration Access Control Model (NACM) ([B43]) provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data sets in this YANG module that contain writable data nodes ([B45]), such as:

```
/ptp/instances/instance/default-ds
/ptp/instances/instance/path-trace-ds
/ptp/instances/instance/acceptable-master-ds
/ptp/instances/instance/ports/port/port-ds
/ptp/instances/instance/ports/port/acceptable-master-port-ds
/ptp/instances/instance/ports/port/external-port-config-port-ds
/ptp/instances/instance/ports/port/asymmetry-measurement-mode-ds
/ptp/cmlds/ports/port/link-port-ds
/ptp/cmlds/ports/port/asymmetry-measurement-mode-ds
```

Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. Specifically, an inappropriate configuration of them may adversely impact a PTP synchronization network. For example, loss of synchronization on a clock, accuracy degradation on a set of clocks, or even break down of a whole synchronization network.

17.5 YANG schema tree definitions

The schema tree in this clause is provided as an overview of the YANG module in 17.6. The symbols and their meaning are specified in YANG Tree Diagrams (IETF RFC 8340 [B47]).

17.5.1 Tree diagram for ieee802-dot1as-ptp.yang

```
module: ieee802-dot1as-ptp

  augment /ptp:ptp/ptp:instances/ptp:instance/ptp:default-ds:
    +--ro gm-capable?                boolean
    +--ro current-utc-offset?        int16
    +--ro current-utc-offset-valid?  boolean
    +--ro leap59?                    boolean
    +--ro leap61?                    boolean
    +--ro time-traceable?            boolean
    +--ro frequency-traceable?       boolean
    +--ro ptp-timescale?             boolean
    +--ro time-source?               identityref
  augment /ptp:ptp/ptp:instances/ptp:instance/ptp:current-ds:
    +--ro last-gm-phase-change?        scaled-ns
```

```
1      +--ro last-gm-freq-change?        float64
2      +--ro gm-timebase-indicator?      uint16
3      +--ro gm-change-count?            yang:counter32
4      +--ro time-of-last-gm-change?     yang:timestamp
5      +--ro time-of-last-phase-change?  yang:timestamp
6      +--ro time-of-last-freq-change?   yang:timestamp
7   augment /ptp:ptp/ptp:instances/ptp:instance/ptp:parent-ds:
8      +--ro cumulative-rate-ratio?    int32
9   augment /ptp:ptp/ptp:instances/ptp:instance/ptp:ports/ptp:port/ptp:port-ds:
10     +--ro is-measuring-delay?                boolean
11     +--ro as-capable?                        boolean
12     +--rw mean-link-delay-thresh?            ptp:time-interval
13     +--ro neighbor-rate-ratio?               int32
14     +--rw initial-log-announce-interval?     int8
15     +--ro current-log-announce-interval?     int8
16     +--rw use-mgt-log-announce-interval?     boolean
17     +--rw initial-log-sync-interval?         int8
18     +--ro current-log-sync-interval?         int8
19     +--rw use-mgt-log-sync-interval?         boolean
20     +--rw sync-receipt-timeout?              uint8
21     +--ro sync-receipt-timeout-interval?     uscaled-ns
22     +--rw initial-log-pdelay-req-interval?   int8
23     +--ro current-log-pdelay-req-interval?   int8
24     +--rw use-mgt-log-pdelay-req-interval?   boolean
25     +--rw mgt-log-pdelay-req-interval?       int8
26     +--rw initial-log-gptp-cap-interval?     int8
27     +--ro current-log-gptp-cap-interval?     int8
28     +--rw use-mgt-log-gptp-cap-interval?     boolean
29     +--rw mgt-log-gptp-cap-interval?         int8
30     +--rw initial-compute-rate-ratio?        int8
31     +--ro current-compute-rate-ratio?        int8
32     +--rw use-mgt-compute-rate-ratio?        boolean
33     +--rw mgt-compute-rate-ratio?            int8
34     +--rw initial-compute-mean-link-delay?   int8
35     +--ro current-compute-mean-link-delay?   int8
36     +--rw use-mgt-compute-mean-link-delay?   boolean
37     +--rw mgt-compute-mean-link-delay?       int8
38     +--rw allowed-lost-responses?            uint8
39     +--rw allowed-faults?                    uint8
40     +--rw gptp-cap-receipt-timeout?          uint8
41     +--rw nup?                               float64
42     +--rw ndown?                             float64
43     +--ro one-step-tx-oper?                  boolean
44     +--ro one-step-receive?                  boolean
45     +--ro one-step-transmit?                 boolean
46     +--rw initial-one-step-tx-oper?          int8
47     +--ro current-one-step-tx-oper?          int8
48     +--rw use-mgt-one-step-tx-oper?          boolean
49     +--rw mgt-one-step-tx-oper?              int8
50     +--ro sync-locked?                       boolean
51     +--ro pdelay-truncated-timestamps*       uint64
52  augment /ptp:ptp/ptp:instances/ptp:instance/ptp:ports/ptp:port:
53     +--rw port-statistics-ds
54        +--ro rx-sync-count?                    yang:counter32
          +--ro rx-one-step-sync-count?           yang:counter32
          +--ro rx-follow-up-count?               yang:counter32
          +--ro rx-pdelay-req-count?              yang:counter32
          +--ro rx-pdelay-resp-count?             yang:counter32
          +--ro rx-pdelay-resp-follow-up-count?   yang:counter32
```

31

```
 1        +--ro rx-announce-count?                    yang:counter32
 2        +--ro rx-packet-discard-count?             yang:counter32
 3        +--ro sync-receipt-timeout-count?          yang:counter32
 4        +--ro announce-receipt-timeout-count?      yang:counter32
 5        +--ro pdelay-allowed-lost-exceeded-count?  yang:counter32
 6        +--ro tx-sync-count?                       yang:counter32
 7        +--ro tx-one-step-sync-count?              yang:counter32
 8        +--ro tx-follow-up-count?                  yang:counter32
 9        +--ro tx-pdelay-req-count?                 yang:counter32
10        +--ro tx-pdelay-resp-count?                yang:counter32
11        +--ro tx-pdelay-resp-follow-up-count?      yang:counter32
          +--ro tx-announce-count?                   yang:counter32
12    augment /ptp:ptp/ptp:instances/ptp:instance/ptp:ports/ptp:port:
13      +--rw asymmetry-measurement-mode-ds
14        +--rw enabled?   boolean
15    augment   /ptp:ptp/ptp:common-services/ptp:cmlds/ptp:ports/ptp:port/ptp:link-
16  port-ds:
17        +--ro cmlds-link-port-enabled?        boolean
18        +--ro is-measuring-delay?             boolean
19        +--ro as-capable-across-domains?      boolean
20        +--rw mean-link-delay-thresh?         ptp:time-interval
21        +--rw initial-log-pdelay-req-interval?  int8
22        +--ro current-log-pdelay-req-interval?  int8
23        +--rw use-mgt-log-pdelay-req-interval?  boolean
24        +--rw mgt-log-pdelay-req-interval?    int8
25        +--rw initial-compute-rate-ratio?     int8
26        +--ro current-compute-rate-ratio?     int8
27        +--rw use-mgt-compute-rate-ratio?     boolean
28        +--rw mgt-compute-rate-ratio?         int8
29        +--rw initial-compute-mean-link-delay?  int8
30        +--ro current-compute-mean-link-delay?  int8
31        +--rw use-mgt-compute-mean-link-delay?  boolean
32        +--rw mgt-compute-mean-link-delay?    int8
33        +--rw allowed-lost-responses?         uint8
          +--rw allowed-faults?                 uint8
          +--ro pdelay-truncated-timestamps*    uint64
34    augment /ptp:ptp/ptp:common-services/ptp:cmlds/ptp:ports/ptp:port:
35      +--rw port-statistics-ds
36        +--ro rx-pdelay-req-count?                 yang:counter32
37        +--ro rx-pdelay-resp-count?                yang:counter32
38        +--ro rx-pdelay-resp-follow-up-count?      yang:counter32
39        +--ro rx-packet-discard-count?             yang:counter32
40        +--ro pdelay-allowed-lost-exceeded-count?  yang:counter32
41        +--ro tx-pdelay-req-count?                 yang:counter32
42        +--ro tx-pdelay-resp-count?                yang:counter32
          +--ro tx-pdelay-resp-follow-up-count?      yang:counter32
43    augment /ptp:ptp/ptp:common-services/ptp:cmlds/ptp:ports/ptp:port:
44      +--rw asymmetry-measurement-mode-ds
45        +--rw enabled?   boolean
46
47
48
49
50
51
52
53
54
```

17.6 YANG module[1] [2]

Although not formally specified by this standard, the YANG module specified by IEEE Std 1588e (ieee1588-ptp.yang) serves as the foundation of the YANG module specified in this clause.

17.6.1 Module ieee802-dot1as-ptp.yang

```
module ieee802-dot1as-ptp {
  yang-version 1.1;
  namespace urn:ieee:std:802.1AS:yang:ieee802-dot1as-ptp;
  prefix dot1as-ptp;

  import ietf-yang-types {
    prefix yang;
  }
  import ieee1588-ptp {
    prefix ptp;
  }

  organization
    "IEEE 802.1 Working Group";
  contact
    "WG-URL: http://ieee802.org/1/
     WG-EMail: stds-802-1-l@ieee.org

     Contact: IEEE 802.1 Working Group Chair
              Postal: C/O IEEE 802.1 Working Group
              IEEE Standards Association
              445 Hoes Lane
              Piscataway, NJ 08854
              USA

     E-mail: stds-802-1-chairs@ieee.org";
  description
    "Management objects that control timing and synchronization
     for time sensitive applications, as specified in
     IEEE Std 802.1AS-2020.

     Copyright (C) IEEE (2023).
     This version of this YANG module is part of IEEE Std 802.1AS;
     see the standard itself for full legal notices.";

  revision 2023-04-04 {
    description
      "Published as part of IEEE Std 802.1ASdn-2023.
       Initial version.";
    reference
      "IEEE Std 802.1ASdn-2023 - YANG Data Model";
  }

  typedef scaled-ns {
    type string {
      pattern "[0-9A-F]{2}(-[0-9A-F]{2}){11}";
```

---

[1]Copyright release for YANG modules: Users of this standard may freely reproduce the YANG modules contained in this subclause so that they can be used for their intended purpose.

[2]An ASCII version of the YANG modules are attached to the PDF version of this standard, and can be obtained by Web browser from the IEEE 802.1 Website at https://1.ieee802.org/yang-modules/.

```
        }
      description
        "The IEEE Std 802.1AS ScaledNs type represents
        signed values of time and time interval in units
        of 2^16 ns, as a signed 96-bit integer.
        YANG does not support a signed 96-bit integer.
        Each of the 12 octets is represented in YANG as a pair of
        hexadecimal characters, using uppercase for a letter.
        Each octet in the array is separated by the dash
        character. The most significant octet is first.";
      reference
        "6.4.3.1 of IEEE Std 802.1AS-2020";
    }

    typedef uscaled-ns {
      type string {
        pattern "[0-9A-F]{2}(-[0-9A-F]{2}){11}";
      }
      description
        "The IEEE Std 802.1AS UScaledNs type represents
        unsigned values of time and time interval in units
        of 2^16 ns, as an unsigned 96-bit integer.
        YANG does not support an unsigned 96-bit integer.
        Each of the 12 octets is represented in YANG as a pair of
        hexadecimal characters, using uppercase for a letter.
        Each octet in the array is separated by the dash
        character. The most significant octet is first.";
      reference
        "6.4.3.2 of IEEE Std 802.1AS-2020";
    }

    typedef float64 {
      type string {
        pattern "[0-9A-F]{2}(-[0-9A-F]{2}){7}";
      }
      description
        "The IEEE Std 802.1AS Float64 type represents
        IEEE Std 754 binary64 (64-bit
        double-precision floating-point format).
        YANG does not support floating-point,
        Each of the 8 octets is represented in YANG as a pair of
        hexadecimal characters, using uppercase for a letter.
        Each octet in the array is separated by the dash
        character. The most significant octet is first.";
      reference
        "6.4.2 of IEEE Std 802.1AS-2020";
    }

    augment "/ptp:ptp/ptp:instances/ptp:instance/ptp:default-ds" {
      description
        "Augment IEEE Std 1588 defaultDS.";

      leaf gm-capable {
        type boolean;
        config false;
        description
          "The value is true if the time-aware system is capable
          of being a grandmaster, and false if the time-aware
          system is not capable of being a grandmaster.";
```

```
        reference
          "14.2.7 of IEEE Std 802.1AS-2020";
      }

      leaf current-utc-offset {
        when "../current-utc-offset-valid='true'";
        type int16;
        config false;
        description
          "Offset from UTC (TAI - UTC).
          The offset is in units of seconds.
          This leaf applies to the ClockTimeTransmitter entity
          (i.e., local only, unrelated to a remote GM).";
        reference
          "14.2.8 of IEEE Std 802.1AS-2020";
      }

      leaf current-utc-offset-valid {
        type boolean;
        config false;
        description
          "The value of current-utc-offset-valid shall be true
          if the value of current-utc-offset is known to be
          correct, otherwise it shall be false.
          This leaf applies to the ClockTimeTransmitter entity
          (i.e., local only, unrelated to a remote GM).";
        reference
          "14.2.9 of IEEE Std 802.1AS-2020";
      }

      leaf leap59 {
        type boolean;
        config false;
        description
          "If the timescale is PTP, a true value for leap59
          shall indicate that the last minute of the
          current UTC day contains 59 seconds.
          If the timescale is not PTP, the value shall be
          false.
          This leaf applies to the ClockTimeTransmitter entity
          (i.e., local only, unrelated to a remote GM).";
        reference
          "14.2.10 of IEEE Std 802.1AS-2020";
      }

      leaf leap61 {
        type boolean;
        config false;
        description
          "If the timescale is PTP, a true value for leap61
          shall indicate that the last minute of the
          current UTC day contains 61 seconds.
          If the timescale is not PTP, the value shall be
          false.
          This leaf applies to the ClockTimeTransmitter entity
          (i.e., local only, unrelated to a remote GM).";
         reference
           "14.2.11 of IEEE Std 802.1AS-2020";
      }
```

```
leaf time-traceable {
  type boolean;
  config false;
  description
    "The value of time-traceable shall be true if the
    timescale is traceable to a primary reference;
    otherwise, the value shall be false.
    This leaf applies to the ClockTimeTransmitter entity
    (i.e., local only, unrelated to a remote GM).";
  reference
    "14.2.12 of IEEE Std 802.1AS-2020";
}

leaf frequency-traceable {
  type boolean;
  config false;
  description
    "The value of frequency-traceable shall be true if
    the frequency determining the timescale is traceable
    to a primary reference; otherwise, the value shall
    be false.
    This leaf applies to the ClockTimeTransmitter entity
    (i.e., local only, unrelated to a remote GM).";
   reference
    "14.2.13 of IEEE Std 802.1AS-2020";
}

leaf ptp-timescale {
  type boolean;
  config false;
  description
    "If ptp-timescale is true, the timescale of
    the ClockTimeTransmitter entity is PTP, which is
    the elapsed time since the PTP epoch measured
    using the second defined by International Atomic
    Time (TAI).
    If ptp-timescale is false, the timescale of
    the ClockTimeTransmitter entity is ARB, which is
    the elapsed time since an arbitrary epoch.
    This leaf applies to the ClockTimeTransmitter entity
    (i.e., local only, unrelated to a remote GM).";
  reference
    "14.2.14 of IEEE Std 802.1AS-2020";
}

leaf time-source {
  type identityref {
    base ptp:time-source;
  }
  config false;
  description
    "The source of time used by the Grandmaster Clock
    This leaf applies to the ClockTimeTransmitter entity
    (i.e., local only, unrelated to a remote GM).";
  reference
    "14.2.15 of IEEE Std 802.1AS-2020";
}
}
```

```
  augment "/ptp:ptp/ptp:instances/ptp:instance/ptp:current-ds" {
    description
      "Augment IEEE Std 1588 currentDS.";

    leaf last-gm-phase-change {
      type scaled-ns;
      config false;
      description
        "Phase change that occurred on the most recent
        change in either the Grandmaster PTP Instance
        or gm-timebase-indicator leaf.";
      reference
        "14.3.4 of IEEE Std 802.1AS-2020";
    }

    leaf last-gm-freq-change {
      type float64;
      config false;
      description
        "Frequency change that occurred on the most recent
        change in either the Grandmaster PTP Instance
        or gm-timebase-indicator leaf.";
      reference
        "14.3.5 of IEEE Std 802.1AS-2020";
    }

    leaf gm-timebase-indicator {
      type uint16;
      config false;
      description
        "The timeBaseIndicator of the current
        Grandmaster PTP Instance.";
      reference
        "14.3.6 of IEEE Std 802.1AS-2020";
    }

    leaf gm-change-count {
      type yang:counter32;
      config false;
      description
        "This statistics counter tracks the number of times
        the Grandmaster PTP Instance has changed in a
        gPTP domain.";
      reference
        "14.3.7 of IEEE Std 802.1AS-2020";
    }

    leaf time-of-last-gm-change {
      type yang:timestamp;
      config false;
      description
        "System time when the most recent Grandmaster Clock
        change occurred in a gPTP domain.
        This leaf's type is YANG timestamp, which is based
        on system time. System time is an unsigned integer
        in units of 10 milliseconds, using an epoch defined
        by the implementation (typically time of boot-up).";
      reference
```

```
                    "14.3.8 of IEEE Std 802.1AS-2020";
      }

    leaf time-of-last-phase-change {
      type yang:timestamp;
      config false;
      description
        "System time when the most recent change in Grandmaster
        Clock phase occurred.
        This leaf's type is YANG timestamp, which is based
        on system time. System time is an unsigned integer
        in units of 10 milliseconds, using an epoch defined
        by the implementation (typically time of boot-up).";
      reference
        "14.3.9 of IEEE Std 802.1AS-2020";
      }

    leaf time-of-last-freq-change {
      type yang:timestamp;
      config false;
      description
        "System time when the most recent change in Grandmaster
        Clock frequency occurred.
        This leaf's type is YANG timestamp, which is based
        on system time. System time is an unsigned integer
        in units of 10 milliseconds, using an epoch defined
        by the implementation (typically time of boot-up).";
      reference
        "14.3.10 of IEEE Std 802.1AS-2020";
      }
  }

  augment "/ptp:ptp/ptp:instances/ptp:instance/ptp:parent-ds" {
    description
      "Augment IEEE Std 1588 parentDS.";

    leaf cumulative-rate-ratio {
      type int32;
      config false;
      description
        "Estimate of the ratio of the frequency of the Grandmaster
        Clock to the frequency of the LocalClock entity of this
        PTP Instance. cumulative-rate-ratio is expressed as
        the fractional frequency offset multiplied by 2^41,
        i.e., the quantity (rateRatio - 1.0)(2^41).";
      reference
        "14.4.3 of IEEE Std 802.1AS-2020";
    }
  }

  augment "/ptp:ptp/ptp:instances/ptp:instance/ptp:ports/ptp:port/ptp:port-ds" {
    description
      "Augment IEEE Std 1588 portDS.

      14.8.4 of IEEE Std 802.1AS-2020 specifies ptpPortEnabled
      (ptp-port-enabled), which is provided in YANG as the
      semantically equivalent node in ieee1588-ptp named
      port-enable (in port-ds).
```

```
            14.8.15 of IEEE Std 802.1AS-2020 specifies
            mgtSettableLogAnnounceInterval
            (mgt-settable-log-announce-interval), which is provided in
            YANG as the semantically equivalent node in ieee1588-ptp named
            log-announce-interval (in port-ds). In the context of
            IEEE Std 802.1AS, log-announce-interval cannot be used
            unless use-mgt-log-announce-interval is true.

            14.8.20 of IEEE Std 802.1AS-2020 specifies
            mgtSettableLogSyncInterval
            (mgt-settable-log-sync-interval), which is provided in YANG
            as the semantically equivalent node in ieee1588-ptp named
            log-sync-interval (in port-ds). In the context of
            IEEE Std 802.1AS, log-sync-interval cannot be used
            unless use-mgt-log-sync-interval is true.";

        leaf is-measuring-delay {
          type boolean;
          config false;
          description
            "Boolean that is true if the port is measuring
            PTP Link propagation delay.";
          reference
            "14.8.6 of IEEE Std 802.1AS-2020";
        }

        leaf as-capable {
          type boolean;
          config false;
          description
            "Boolean that is true if and only if it is determined
            that this PTP Instance and the PTP Instance at the
            other end of the link attached to this port can
            interoperate with each other via the IEEE Std
            802.1AS protocol.";
          reference
            "10.2.5.1 of IEEE Std 802.1AS-2020
            14.8.7 of IEEE Std 802.1AS-2020";
        }

        leaf mean-link-delay-thresh {
          type ptp:time-interval;
          description
            "Propagation time threshold for mean-link-delay,
            above which a port is not considered capable of
            participating in the IEEE Std 802.1AS protocol.";
          reference
            "14.8.9 of IEEE Std 802.1AS-2020";
        }

        leaf neighbor-rate-ratio {
          type int32;
          config false;
          description
            "Estimate of the ratio of the frequency of the LocalClock
            entity of the PTP Instance at the other end of the
            link attached to this PTP Port, to the frequency of the
            LocalClock entity of this PTP Instance.
            neighbor-rate-ratio is expressed as the fractional
```

```
          frequency offset multiplied by 2^41,
          i.e., the quantity (rateRatio - 1.0)(2^41).”;
        reference
          “14.8.11 of IEEE Std 802.1AS-2020”;
      }

      leaf initial-log-announce-interval {
        type int8;
        description
          “When use-mgt-log-announce-interval is false
          (i.e., change with Signaling message), this is the
          the logarithm to base 2 of the announce
          interval used when the port is initialized.”;
        reference
          “14.8.12 of IEEE Std 802.1AS-2020”;
      }

      leaf current-log-announce-interval {
        type int8;
        config false;
        description
          “Logarithm to base 2 of the current
          announce interval.”;
        reference
          “14.8.13 of IEEE Std 802.1AS-2020”;
      }

      leaf use-mgt-log-announce-interval {
        type boolean;
        description
          “Boolean that determines the source of the
          announce interval.
          If the value is true, the announce interval
          (current-log-announce-interval) is set equal to the value
          of mgt-log-announce-interval.
          If the value is false, the announce interval is determined
          by the AnnounceIntervalSetting state machine (i.e., changed
          with Signaling message).”;
        reference
          “14.8.14 of IEEE Std 802.1AS-2020”;
      }

      leaf initial-log-sync-interval {
        type int8;
        description
          “When use-mgt-log-sync-interval is false
          (i.e., change with Signaling message), this is the
          the logarithm to base 2 of the sync
          interval used when the port is initialized.”;
    reference
          “14.8.17 of IEEE Std 802.1AS-2020”;
      }

      leaf current-log-sync-interval {
        type int8;
        config false;
        description
          “Logarithm to base 2 of the current sync
          interval.”;
```

```
      reference
        "14.8.18 of IEEE Std 802.1AS-2020";
    }

    leaf use-mgt-log-sync-interval {
      type boolean;
      description
        "Boolean that determines the source of the
        sync interval.
        If the value is true, the sync interval
        (current-log-sync-interval) is set equal to the value
        of mgt-log-sync-interval.
        If the value is false, the sync interval is determined
        by the SyncIntervalSetting state machine (i.e., changed
        with Signaling message).";
      reference
        "14.8.19 of IEEE Std 802.1AS-2020";
    }

    leaf sync-receipt-timeout {
      type uint8;
      description
        "Number of sync intervals that a timeReceiver port waits
        without receiving synchronization information, before
        assuming that the timeTransmitter is no longer transmitting
        synchronization information and that the BTCA needs to be
        run, if appropriate.";
      reference
        "14.8.21 of IEEE Std 802.1AS-2020";
    }

    leaf sync-receipt-timeout-interval {
      type uscaled-ns;
      config false;
      description
        "Time interval after which sync receipt timeout occurs
        if time-synchronization information has not been
        received during the interval.";
    reference
        "14.8.22 of IEEE Std 802.1AS-2020";
    }

    leaf initial-log-pdelay-req-interval {
      type int8;
      description
        "When use-mgt-log-pdelay-req-interval is false
        (i.e., change with Signaling message), this is the
        the logarithm to base 2 of the Pdelay_Req transmit
        interval used when the port is initialized.";
      reference
        "14.8.23 of IEEE Std 802.1AS-2020";
    }

    leaf current-log-pdelay-req-interval {
      type int8;
      config false;
      description
        "Logarithm to base 2 of the current Pdelay_Req transmit
        interval.";
```

41

```
        reference
          "14.8.24 of IEEE Std 802.1AS-2020";
      }

      leaf use-mgt-log-pdelay-req-interval {
        type boolean;
        description
          "Boolean that determines the source of the
          Pdelay_Req transmit interval.
          If the value is true, the Pdelay_Req transmit interval
          (current-log-pdelay-req-interval) is set equal to the value
          of mgt-log-pdelay-req-interval.
          If the value is false, the Pdelay_Req transmit interval is
          determined by the LinkDelayIntervalSetting state machine
          (i.e., changed with Signaling message).";
        reference
          "14.8.25 of IEEE Std 802.1AS-2020";
      }

      leaf mgt-log-pdelay-req-interval {
        type int8;
        description
          "Logarithm to base 2 of the Pdelay_Req transmit interval,
          used if use-mgt-log-pdelay-req-interval is true.
          This value is not used if use-mgt-log-pdelay-req-interval
          is false.";
        reference
          "14.8.26 of IEEE Std 802.1AS-2020";
      }

      leaf initial-log-gptp-cap-interval {
        type int8;
        description
          "When use-mgt-log-gptp-cap-interval is false
          (i.e., change with Signaling message), this is the
          the logarithm to base 2 of the gPTP capable message
          interval used when the port is initialized.";
        reference
          "14.8.27 of IEEE Std 802.1AS-2020";
      }

      leaf current-log-gptp-cap-interval {
        type int8;
        config false;
        description
          "Logarithm to base 2 of the current gPTP capable message
          interval.";
        reference
          "14.8.28 of IEEE Std 802.1AS-2020";
      }

      leaf use-mgt-log-gptp-cap-interval {
        type boolean;
        description
          "Boolean that determines the source of the
          gPTP capable message interval.
          If the value is true, the gPTP capable message interval
          (current-log-gptp-cap-interval) is set equal to the value
          of mgt-gptp-cap-req-interval.
```

```
           If the value is false, the gPTP capable message interval is
           determined by the GptpCapableMessageIntervalSetting
           state machine (i.e., changed with Signaling message).";
         reference
           "14.8.29 of IEEE Std 802.1AS-2020";
       }

       leaf mgt-log-gptp-cap-interval {
         type int8;
         description
           "Logarithm to base 2 of the gPTP capable message interval,
           used if use-mgt-log-gptp-cap-interval is true.
           This value is not used if use-mgt-log-pdelay-req-interval
           is false.";
         reference
           "14.8.30 of IEEE Std 802.1AS-2020";
       }

       leaf initial-compute-rate-ratio {
         type int8;
         description
           "When use-mgt-compute-rate-ratio is false
           (i.e., change with Signaling message), this is the
           initial value of computeNeighborRateRatio.";
         reference
           "14.8.31 of IEEE Std 802.1AS-2020";
       }

       leaf current-compute-rate-ratio {
         type int8;
         config false;
         description
           "Current value of computeNeighborRateRatio.";
         reference
           "14.8.32 of IEEE Std 802.1AS-2020";
       }

       leaf use-mgt-compute-rate-ratio {
         type boolean;
         description
           "Boolean that determines the source of
           computeNeighborRateRatio..
           If the value is true, computeNeighborRateRatio
           is set equal to the value of mgt-compute-rate-ratio.
           If the value is false, computeNeighborRateRatio is
           determined by the LinkDelayIntervalSetting
           state machine (i.e., changed with Signaling message).";
         reference
           "14.8.33 of IEEE Std 802.1AS-2020";
       }

       leaf mgt-compute-rate-ratio {
         type int8;
         description
           "Value of computeNeighborRateRatio, used if
           use-mgt-compute-rate-ratio is true.
           This value is not used if use-mgt-compute-rate-ratio
           is false.";
         reference
```

```
          "14.8.34 of IEEE Std 802.1AS-2020";
      }

      leaf initial-compute-mean-link-delay {
        type int8;
        description
          "When use-mgt-compute-mean-link-delay is false
          (i.e., change with Signaling message), this is the
          initial value of computeMeanLinkDelay.";
        reference
          "14.8.35 of IEEE Std 802.1AS-2020";
      }

      leaf current-compute-mean-link-delay {
        type int8;
        config false;
        description
          "Current value of computeMeanLinkDelay.";
        reference
          "14.8.36 of IEEE Std 802.1AS-2020";
      }

      leaf use-mgt-compute-mean-link-delay {
        type boolean;
        description
          "Boolean that determines the source of
          computeMeanLinkDelay.
          If the value is true, computeMeanLinkDelay
          is set equal to the value of mgt-compute-mean-link-delay.
          If the value is false, computeMeanLinkDelay is
          determined by the LinkDelayIntervalSetting
          state machine (i.e., changed with Signaling message).";
        reference
          "14.8.37 of IEEE Std 802.1AS-2020";
      }

      leaf mgt-compute-mean-link-delay {
        type int8;
        description
          "Value of computeMeanLinkDelay, used if
          use-mgt-compute-mean-link-delay is true.
          This value is not used if use-mgt-compute-mean-link-delay
          is false.";
        reference
          "14.8.38 of IEEE Std 802.1AS-2020";
      }

      leaf allowed-lost-responses {
        type uint8;
        description
          "Number of Pdelay_Req messages for which a valid response
          is not received, above which a port is considered to not
          be exchanging peer delay messages with its neighbor.";
        reference
          "14.8.39 of IEEE Std 802.1AS-2020";
      }

      leaf allowed-faults {
        type uint8;
```

```
        description
          "Number of faults above which asCapable is set to false.";
        reference
          "14.8.40 of IEEE Std 802.1AS-2020";
      }

      leaf gptp-cap-receipt-timeout {
        type uint8;
        description
          "Number of transmission intervals that a port waits without
          receiving the gPTP capable TLV, before assuming that the
          neighbor port is no longer invoking the gPTP protocol.";
        reference
          "14.8.41 of IEEE Std 802.1AS-2020";
      }

      leaf nup {
        type float64;
        description
          "For an OLT port of an IEEE Std 802.3 EPON link, this value
          is the effective index of refraction for the EPON
          upstream wavelength light of the optical path";
        reference
          "14.8.43 of IEEE Std 802.1AS-2020";
      }

      leaf ndown {
        type float64;
        description
          "For an OLT port of an IEEE 802.3 EPON link, this value
          is the effective index of refraction for the EPON
          downstream wavelength light of the optical path";
        reference
          "14.8.44 of IEEE Std 802.1AS-2020";
      }

      leaf one-step-tx-oper {
        type boolean;
        config false;
        description
          "This value is true if the port is sending one-step
          Sync messages, and false if the port is sending
          two-step Sync and Follow-Up messages.";
        reference
          "14.8.45 of IEEE Std 802.1AS-2020";
      }

      leaf one-step-receive {
        type boolean;
        config false;
        description
          "This value is true if the port is capable of
          receiving and processing one-step Sync messages.";
        reference
          "14.8.46 of IEEE Std 802.1AS-2020";
      }

      leaf one-step-transmit {
        type boolean;
```

```
         config false;
         description
           "This value is true if the port is capable of
           transmitting one-step Sync messages.";
         reference
           "14.8.47 of IEEE Std 802.1AS-2020";
       }

       leaf initial-one-step-tx-oper {
         type int8;
         description
           "When use-mgt-one-step-tx-oper is false
           (i.e., change with Signaling message), this is the
           initial value of current-one-step-tx-oper.";
         reference
           "14.8.48 of IEEE Std 802.1AS-2020";
       }

       leaf current-one-step-tx-oper {
         type int8;
         config false;
         description
           "This value is true if the port is configured to
           transmit one-step Sync messages, either via management
           (mgt-one-step-tx-oper) or Signaling. If both
           current-one-step-tx-oper and one-step-transmit
           are true, the port transmits one-step Sync messages
           (i.e., one-step-tx-oper true).";
         reference
           "14.8.49 of IEEE Std 802.1AS-2020";
       }

       leaf use-mgt-one-step-tx-oper {
         type boolean;
         description
           "Boolean that determines the source of
           current-one-step-tx-oper.
           If the value is true, current-one-step-tx-oper
           is set equal to the value of mgt-one-step-tx-oper.
           If the value is false, current-one-step-tx-oper is
           determined by the OneStepTxOperSetting
           state machine (i.e., changed with Signaling message).";
         reference
           "14.8.50 of IEEE Std 802.1AS-2020";
       }

       leaf mgt-one-step-tx-oper {
         type int8;
         description
           "If use-mgt-one-step-tx-oper is true,
           current-one-step-tx-oper is set equal to this value.
           This value is not used if use-mgt-one-step-tx-oper
           is false.";
         reference
           "14.8.51 of IEEE Std 802.1AS-2020";
       }

       leaf sync-locked {
         type boolean;
```

```
        config false;
        description
          "This value is true if the port will transmit a Sync as
          soon as possible after the timeReceiver port receives a Sync
          message.";
        reference
          "14.8.52 of IEEE Std 802.1AS-2020";
      }

    leaf-list pdelay-truncated-timestamps {
      type uint64 {
        range "0..281474976710655";
      }
      config false;
      description
        "For full-duplex IEEE Std 802.3 media, and CSN media that use
        the peer-to-peer delay mechanism to measure path delay,
        the values of the four elements of this leaf-list correspond
        to the timestamps t1, t2, t3, and t4, listed in that order.
        Each timestamp is expressed in units of 2^-16 ns (i.e., the
        value of each array element is equal to the remainder obtained
        upon dividing the respective timestamp, expressed in units of
        2^-16 ns, by 2^48). At any given time, the timestamp values
        stored in the array are for the same, and most recently
        completed, peer delay message exchange. For each timestamp,
        only 48-bits are valid (the upper 16-bits are always zero).";
      reference
        "14.8.53 of IEEE Std 802.1AS-2020";
    }
  }

  augment "/ptp:ptp/ptp:instances/ptp:instance/ptp:ports/ptp:port" {
    description
      "Augment to add port-statistics-ds to IEEE Std 1588 PTP Port.";

    container port-statistics-ds {
      description
        "Provides counters associated with the port of the
        PTP Instance.";
      reference
        "14.10 of IEEE Std 802.1AS-2020";

      leaf rx-sync-count {
        type yang:counter32;
        config false;
        description
          "Counter that increments every time synchronization
          information is received.";
        reference
          "14.10.2 of IEEE Std 802.1AS-2020";
      }

      leaf rx-one-step-sync-count {
        type yang:counter32;
        config false;
        description
          "Counter that increments every time a one-step Sync
          message is received.";
        reference
```

```
            "14.10.3 of IEEE Std 802.1AS-2020";
          }

          leaf rx-follow-up-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time a Follow_Up
              message is received.";
            reference
              "14.10.4 of IEEE Std 802.1AS-2020";
          }

          leaf rx-pdelay-req-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time a Pdelay_Req
              message is received.";
            reference
              "14.10.5 of IEEE Std 802.1AS-2020";
          }

          leaf rx-pdelay-resp-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time a Pdelay_Resp
              message is received.";
            reference
              "14.10.6 of IEEE Std 802.1AS-2020";
          }

          leaf rx-pdelay-resp-follow-up-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time a Pdelay_Resp_Follow_Up
              message is received.";
            reference
              "14.10.7 of IEEE Std 802.1AS-2020";
          }

          leaf rx-announce-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time an Announce
              message is received.";
            reference
              "14.10.8 of IEEE Std 802.1AS-2020";
          }

          leaf rx-packet-discard-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time a PTP message
              of the respective PTP Instance is discarded.";
```

```
            reference
              "14.10.9 of IEEE Std 802.1AS-2020";
          }

          leaf sync-receipt-timeout-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time a sync receipt
              timeout occurs.";
            reference
              "14.10.10 of IEEE Std 802.1AS-2020";
          }

          leaf announce-receipt-timeout-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time an announce receipt
              timeout occurs.";
            reference
              "14.10.11 of IEEE Std 802.1AS-2020";
          }

          leaf pdelay-allowed-lost-exceeded-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time the value of the
              variable lostResponses exceeds the value of the variable
              allowedLostResponses, in the RESET state of the
              MDPdelayReq state machine.";
            reference
              "14.10.12 of IEEE Std 802.1AS-2020";
          }

          leaf tx-sync-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time synchronization
              information is transmitted.";
            reference
              "14.10.13 of IEEE Std 802.1AS-2020";
          }

          leaf tx-one-step-sync-count {
            type yang:counter32;
            config false;
            description
              "Counter that increments every time a one-step Sync
              message is transmitted.";
            reference
              "14.10.14 of IEEE Std 802.1AS-2020";
          }

          leaf tx-follow-up-count {
            type yang:counter32;
            config false;
```

```
        description
          "Counter that increments every time a Follow_Up
          message is transmitted.";
        reference
          "14.10.15 of IEEE Std 802.1AS-2020";
      }

      leaf tx-pdelay-req-count {
        type yang:counter32;
        config false;
        description
          "Counter that increments every time a Pdelay_Req
          message is transmitted.";
        reference
          "14.10.16 of IEEE Std 802.1AS-2020";
      }

      leaf tx-pdelay-resp-count {
        type yang:counter32;
        config false;
        description
          "Counter that increments every time a Pdelay_Resp
          message is transmitted.";
        reference
          "14.10.17 of IEEE Std 802.1AS-202014.10.17";
      }

      leaf tx-pdelay-resp-follow-up-count {
        type yang:counter32;
        config false;
        description
          "Counter that increments every time a Pdelay_Resp_Follow_Up
          message is transmitted.";
        reference
          "14.10.18 of IEEE Std 802.1AS-2020";
      }

      leaf tx-announce-count {
        type yang:counter32;
        config false;
        description
          "Counter that increments every time an Announce
          message is transmitted.";
        reference
          "14.10.19 of IEEE Std 802.1AS-2020";
      }
    }
  }

  augment "/ptp:ptp/ptp:instances/ptp:instance/ptp:ports/ptp:port" {
    description
      "Augment to add asymmetry-measurement-mode-ds to
      IEEE Std 1588 PTP Port.";

    container asymmetry-measurement-mode-ds {
      description
        "Represents the capability to enable/disable the Asymmetry
        Compensation Measurement Procedure on a PTP Port.
        This data set is used instead of the CMLDS
```

```
            asymmetry-measurement-mode-ds when only a single PTP
            Instance is present (i.e., CMLDS is not used).";
          reference
            "14.13 of IEEE Std 802.1AS-2020
            Annex G of IEEE Std 802.1AS-2020";

          leaf enabled {
            type boolean;
            description
              "For full-duplex IEEE Std 802.3 media, the value is true
               if an asymmetry measurement is being performed for the
               link attached to this PTP Port, and false otherwise.
               For all other media, the value shall be false.";
          }
        }
      }

    augment  "/ptp:ptp/ptp:common-services/ptp:cmlds/ptp:ports/ptp:port/ptp:link-
port-ds" {
        description
          "Augment IEEE Std 1588 cmldsLinkPortDS.

          14.16.9 of IEEE Std 802.1AS-2020 specifies neighborRateRatio
          (neighbor-rate-ratio), which is provided in YANG as the
          semantically equivalent node in ieee1588-ptp named
          scaled-neighbor-rate-ratio (in link-port-ds).";

      leaf cmlds-link-port-enabled {
        type boolean;
        config false;
        description
          "Boolean that is true if both delay-mechanism is common-p2p
           and the value of ptp-port-enabled is true, for at least one
           PTP Port that uses the CMLDS; otherwise, the value is false.";
        reference
          "11.2.18.1 of IEEE Std 802.1AS-2020
          14.16.3 of IEEE Std 802.1AS-2020";
      }

      leaf is-measuring-delay {
        type boolean;
        config false;
        description
          "This leaf is analogous to is-measuring-delay
          for a PTP Port, but applicable to this Link Port.";
        reference
          "14.16.4 of IEEE Std 802.1AS-2020";
      }

      leaf as-capable-across-domains {
        type boolean;
        config false;
        description
          "This leaf is true when all PTP Instances (domains)
          for this Link Port detect proper exchange of Pdelay
          messages.";
        reference
          "11.2.2 of IEEE Std 802.1AS-2020
          14.16.5 of IEEE Std 802.1AS-2020";
```

51

```
 1             }
 2
 3          leaf mean-link-delay-thresh {
 4            type ptp:time-interval;
 5            description
 6              "Propagation time threshold for mean-link-delay,
 7              above which a Link Port is not considered capable of
 8              participating in the IEEE Std 802.1AS protocol.";
 9            reference
10              "14.16.7 of IEEE Std 802.1AS-2020";
11          }
12          leaf initial-log-pdelay-req-interval {
13            type int8;
14            description
15              "This leaf is analogous to initial-log-pdelay-req-interval
16              for a PTP Port, but applicable to this Link Port.";
17            reference
18              "14.16.10 of IEEE Std 802.1AS-2020";
19          }
20          leaf current-log-pdelay-req-interval {
21            type int8;
22            config false;
23            description
24              "This leaf is analogous to current-log-pdelay-req-interval
25              for a PTP Port, but applicable to this Link Port.";
26            reference
27              "14.16.11 of IEEE Std 802.1AS-2020";
28          }
29          leaf use-mgt-log-pdelay-req-interval {
30            type boolean;
31            description
32              "This leaf is analogous to use-mgt-log-pdelay-req-interval
33              for a PTP Port, but applicable to this Link Port.";
34            reference
35              "14.16.12 of IEEE Std 802.1AS-2020";
36          }
37          leaf mgt-log-pdelay-req-interval {
38            type int8;
39            description
40              "This leaf is analogous to mgt-log-pdelay-req-interval
41              for a PTP Port, but applicable to this Link Port.";
42            reference
43              "14.16.13 of IEEE Std 802.1AS-2020";
44          }
45          leaf initial-compute-rate-ratio {
46            type int8;
47            description
48              "This leaf is analogous to initial-compute-rate-ratio
49              for a PTP Port, but applicable to this Link Port.";
50            reference
51              "14.16.14 of IEEE Std 802.1AS-2020";
52          }
53          leaf current-compute-rate-ratio {
54
```

```
 1          type int8;
 2          config false;
 3          description
 4            "This leaf is analogous to current-compute-rate-ratio
 5            for a PTP Port, but applicable to this Link Port.";
 6          reference
 7            "14.16.15 of IEEE Std 802.1AS-2020";
 8        }

 9        leaf use-mgt-compute-rate-ratio {
10          type boolean;
11          description
12            "This leaf is analogous to use-mgt-compute-rate-ratio
13            for a PTP Port, but applicable to this Link Port.";
14          reference
15            "14.16.16 of IEEE Std 802.1AS-2020";
16        }

17        leaf mgt-compute-rate-ratio {
18          type int8;
19          description
20            "This leaf is analogous to mgt-compute-rate-ratio
21            for a PTP Port, but applicable to this Link Port.";
22          reference
23            "14.16.17 of IEEE Std 802.1AS-2020";
24        }

25
26        leaf initial-compute-mean-link-delay {
27          type int8;
28          description
29            "This leaf is analogous to initial-compute-mean-link-delay
30            for a PTP Port, but applicable to this Link Port.";
31          reference
32            "14.16.18 of IEEE Std 802.1AS-2020";
33        }

34        leaf current-compute-mean-link-delay {
35          type int8;
36          config false;
37          description
38            "This leaf is analogous to current-compute-mean-link-delay
39            for a PTP Port, but applicable to this Link Port.";
40          reference
41            "14.16.19 of IEEE Std 802.1AS-2020";
42        }

43        leaf use-mgt-compute-mean-link-delay {
44          type boolean;
45          description
46            "This leaf is analogous to use-mgt-compute-mean-link-delay
47            for a PTP Port, but applicable to this Link Port.";
48          reference
49            "14.16.20 of IEEE Std 802.1AS-2020";
50        }

51        leaf mgt-compute-mean-link-delay {
52          type int8;
53          description
54            "This leaf is analogous to mgt-compute-mean-link-delay
```

53

```
              for a PTP Port, but applicable to this Link Port.";
            reference
              "14.16.21 of IEEE Std 802.1AS-2020";
          }

        leaf allowed-lost-responses {
          type uint8;
          description
            "This leaf is analogous to allowed-lost-responses
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.16.22 of IEEE Std 802.1AS-2020";
        }

        leaf allowed-faults {
          type uint8;
          description
            "This leaf is analogous to allowed-faults
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.16.23 of IEEE Std 802.1AS-2020";
        }

        leaf-list pdelay-truncated-timestamps {
          type uint64 {
            range "0..281474976710655";
          }
          config false;
          description
            "This leaf is analogous to pdelay-truncated-timestamps
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.16.25 of IEEE Std 802.1AS-2020";
        }
      }

    augment "/ptp:ptp/ptp:common-services/ptp:cmlds/ptp:ports/ptp:port" {
      description
        "Augment to add port-statistics-ds to IEEE Std 1588 Link Port.";

      container port-statistics-ds {
        description
          "This container is analogous to port-statistics-ds
          for a PTP Port, but applicable to this Link Port.";
        reference
          "14.17 of IEEE Std 802.1AS-2020";

        leaf rx-pdelay-req-count {
          type yang:counter32;
          config false;
          description
            "This leaf is analogous to rx-pdelay-req-count
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.17.2 of IEEE Std 802.1AS-2020";
        }

        leaf rx-pdelay-resp-count {
          type yang:counter32;
```

```
          config false;
          description
            "This leaf is analogous to rx-pdelay-resp-count
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.17.3 of IEEE Std 802.1AS-2020";
        }

        leaf rx-pdelay-resp-follow-up-count {
          type yang:counter32;
          config false;
          description
            "This leaf is analogous to rx-pdelay-resp-follow-up-count
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.17.4 of IEEE Std 802.1AS-2020";
        }

        leaf rx-packet-discard-count {
          type yang:counter32;
          config false;
          description
            "This leaf is analogous to rx-packet-discard-count
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.17.5 of IEEE Std 802.1AS-2020";
        }

        leaf pdelay-allowed-lost-exceeded-count {
          type yang:counter32;
          config false;
          description
            "This leaf is analogous to
            pdelay-allowed-lost-exceeded-count
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.17.6 of IEEE Std 802.1AS-2020";
        }

        leaf tx-pdelay-req-count {
          type yang:counter32;
          config false;
          description
            "This leaf is analogous to tx-pdelay-req-count
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.17.7 of IEEE Std 802.1AS-2020";
        }

        leaf tx-pdelay-resp-count {
          type yang:counter32;
          config false;
          description
            "This leaf is analogous to tx-pdelay-resp-count
            for a PTP Port, but applicable to this Link Port.";
          reference
            "14.17.8 of IEEE Std 802.1AS-2020";
        }
```

55

```
      leaf tx-pdelay-resp-follow-up-count {
        type yang:counter32;
        config false;
        description
          "This leaf is analogous to tx-pdelay-resp-follow-up-count
          for a PTP Port, but applicable to this Link Port.";
        reference
          "14.17.9 of IEEE Std 802.1AS-2020";
      }
    }
  }

  augment "/ptp:ptp/ptp:common-services/ptp:cmlds/ptp:ports/ptp:port" {
    description
      "Augment to add asymmetry-measurement-mode-ds to
      IEEE Std 1588 Link Port.";

    container asymmetry-measurement-mode-ds {
      description
        "This container is analogous to asymmetry-measurement-mode-ds
        for a PTP Port, but applicable to this Link Port.";
      reference
        "14.18 of IEEE Std 802.1AS-2020";

      leaf enabled {
        type boolean;
        description
          "This leaf is analogous to
          asymmetry-measurement-mode-ds.enabled
          for a PTP Port, but applicable to this Link Port.";
      }
    }
  }
}
```

Annex A

(normative)

Protocol Implementation Conformance Statement (PICS) proforma[3]

A.19 Remote management

Insert the following row at the end of the table in A.19:

Item	Feature	Status	References	Support
RMGT-4	If a remote management protocol that supports YANG is listed in RMGT-2, is the YANG data model of Clause 17 supported?	RMGT:O	item k) 4) of 5.4.2, Clause 17	Yes [ ] No [ ]

_____

[3] *Copyright release for PICS proformas:* Users of this standard may freely reproduce the PICS proforma in this annex so that it can be used for its intended purpose and may further publish the completed PICS.

Annex F

(informative)

PTP profile included in this standard

F.4 PTP options

Change F.4 c) as follows:

c) The management mechanism is the mechanism specified in Clause 14 ~~and~~, Clause 15, and Clause 17.

Annex H

(informative)

Bibliography

Insert the following bibliography references in alphanumeric order:

[B40] IETF RFC 6087, Guidelines for Authors and Reviewers of YANG Data Model Documents, January 2011.

[B41] IETF RFC 6241, Network Configuration Protocol (NETCONF), June 2011.

[B42] IETF RFC 6242, Using the NETCONF Protocol over Secure Shell (SSH), June 2011.

[B43] IETF RFC 8341, Network Configuration Access Control Model, March 2018.

[B44] IETF RFC 7589, Using the NETCONF Protocol over Transport Layer Security (TLS) with Mutual X.509 Authentication, June 2015.

[B45] IETF RFC 7950, The YANG 1.1 Data Modeling Language, August 2016.

[B46] IETF RFC 8040, RESTCONF Protocol, January 2017.

[B47] IETF RFC 8340, YANG Tree Diagrams, March 2018.

[B48] IETF RFC 8575, YANG Data Model for the Precision Time Protocol (PTP).

[B49] OMG Unified Modeling Language (OMG UML), Version 2.5, March 2015.