

IEEE P802f/D2.4

Draft Standard for Local and Metropolitan Area Networks: Overview and Architecture Amendment 3: YANG Data Model for EtherTypes

Prepared by the

Time-Sensitive Networking Task Group of IEEE 802.1 of the

LAN/MAN Standards Committee of the IEEE Computer Society

This page is not part of the draft.

Important Notice

This document is an unapproved draft of a proposed IEEE Standard. IEEE hereby grants the named IEEE SA Working Group or Standards Committee Chair permission to distribute this document to participants in the receiving IEEE SA Working Group or Standards Committee, for purposes of review for IEEE standardization activities. No further use, reproduction, or distribution of this document is permitted without the express written permission of IEEE Standards Association (IEEE SA). Prior to any review or use of this draft standard, in part or in whole, by another standards development organization, permission must first be obtained from IEEE SA (stds-copyright@ieee.org). This page is included as the cover of this draft, and shall not be modified or deleted.

IEEE Standards Association
445 Hoes Lane
Piscataway, NJ 08854, USA

1
2
3

IEEE P802f/D2.4

Draft Standard for Local and Metropolitan Area Networks: Overview and Architecture Amendment 3: YANG Data Model for EtherTypes

Prepared by the Time-Sensitive Networking Task Group of IEEE 802.1 of the
LAN/MAN Standards Committee of the IEEE Computer Society

12

Copyright © 2023 by the IEEE.
Three Park Avenue
New York, New York 10016-5997, USA
All rights reserved.

17

18

This document is an unapproved draft of a proposed IEEE Standard. As such, this document is subject to change. USE AT YOUR OWN RISK! IEEE copyright statements SHALL NOT BE REMOVED from draft or approved IEEE standards, or modified in any way. Because this is an unapproved draft, this document must not be utilized for any conformance/compliance purposes. Permission is hereby granted for officers from each IEEE Standards Working Group or Committee to reproduce the draft document developed by that Working Group for purposes of international standardization consideration. IEEE Standards Department must be informed of the submission for consideration prior to any reproduction for international standardization consideration (stds-ipr@ieee.org). Prior to adoption of this document, in whole or in part, by another standards development organization, permission must first be obtained from the IEEE Standards Department (stds-ipr@ieee.org). When requesting permission, IEEE Standards Department will require a copy of the standard development organization's document highlighting the use of IEEE content. Other entities seeking permission to reproduce this document, in whole or in part, must also obtain permission from the IEEE Standards Department.

32

IEEE Standards Activities Department
445 Hoes Lane
Piscataway, NJ 08854, USA

Abstract: This amendment specifies a YANG module containing the EtherType information, including a compact human-readable name and description, for a subset of EtherTypes taken from the IEEE Registration Authority EtherType public listing. This amendment also addresses errors and omissions in IEEE Std 802 description of existing functionality.

Keywords: BANs, body area networks, EtherTypes, IEEE 802®, IEEE 802 architecture, IEEE 802 reference model, LANs, local area networks, MANs, metropolitan area networks, object identifiers, PANs, personal area networks, RANs, regional area networks, protocol development, protocol types, YANG

The fields “Friendly Names” and “Short Descriptions” in Annex F may include trademarks that are owned by their respective trademark owners. The information in these fields is provided solely for the convenience of users of this standard and does not constitute an endorsement by IEEE of those products or the companies producing those products.

DRAFT STATUS:

3rd Standards Association recirculation ballot.

1 Important Notices and Disclaimers Concerning IEEE Standards Documents

2 IEEE Standards documents are made available for use subject to important notices and legal disclaimers.
3 These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>),
4 appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning
5 IEEE Standards Documents.”

6

7 Notice and Disclaimer of Liability Concerning the Use of IEEE Standards 8 Documents

9 IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating
10 Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards
11 through an accredited consensus development process, which brings together volunteers representing varied
12 viewpoints and interests to achieve the final product. IEEE Standards are documents developed by
13 volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers
14 are not necessarily members of IEEE or IEEE SA, and participate without compensation from IEEE. While
15 IEEE administers the process and establishes rules to promote fairness in the consensus development
16 process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the
17 soundness of any judgments contained in its standards.

18 IEEE makes no warranties or representations concerning its standards, and expressly disclaims all
19 warranties, express or implied, concerning this standard, including but not limited to the warranties of
20 merchantability, fitness for a particular purpose and non-infringement. In addition, IEEE does not warrant
21 or represent that the use of the material contained in its standards is free from patent infringement. IEEE
22 standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

23 Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there
24 are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to
25 the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and
26 issued is subject to change brought about through developments in the state of the art and comments
27 received from users of the standard.

28 In publishing and making its standards available, IEEE is not suggesting or rendering professional or other
29 services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any
30 other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his
31 or her own independent judgment in the exercise of reasonable care in any given circumstances or, as
32 appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE
33 standard.

34 IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
35 EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE
36 NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS;
37 OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
38 WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
39 OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE
40 UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND
41 REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

42

43 Translations

44 The IEEE consensus development process involves the review of documents in English only. In the event
45 that an IEEE standard is translated, only the English version published by IEEE is the approved IEEE
46 standard.

1 Official statements

2 A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board
3 Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its
4 committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures,
5 symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall
6 make it clear that the presenter's views should be considered the personal views of that individual rather than
7 the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group.

8

9 Comments on standards

10 Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of
11 membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations,**
12 **consulting information, or advice pertaining to IEEE Standards documents.**

13 Suggestions for changes in documents should be in the form of a proposed change of text, together with
14 appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is
15 important that any responses to comments and questions also receive the concurrence of a balance of
16 interests. For this reason, IEEE and the members of its Societies and Standards Coordinating Committees
17 are not able to provide an instant response to comments, or questions except in those cases where the matter
18 has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any
19 person who would like to participate in evaluating comments or in revisions to an IEEE standard is welcome
20 to join the relevant IEEE working group. You can indicate interest in a working group using the Interests tab
21 in the Manage Profile & Interests area of the [IEEE SA myProject system](#).¹

22 Comments on standards should be submitted using the [Contact Us](#) form.²

23

24 Laws and regulations

25 Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the
26 provisions of any IEEE Standards document does not constitute compliance to any applicable regulatory
27 requirements. Implementers of the standard are responsible for observing or referring to the applicable regu-
28 latory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in
29 compliance with applicable laws, and these documents may not be construed as doing so.

30

31 Data privacy

32 Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and
33 data ownership in the context of assessing and using the standards in compliance with applicable laws and
34 regulations.

35

36 Copyrights

37 IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws.
38 They are made available by IEEE and are adopted for a wide variety of both public and private uses. These
39 include both use, by reference, in laws and regulations, and use in private self-regulation, standardization,
40 and the promotion of engineering practices and methods. By making these documents available for use and
41 adoption by public authorities and private users, IEEE does not waive any rights in copyright to the
42 documents.

¹ Available at: <https://development.standards.ieee.org/myproject-web/public/view.html#landing>.

² Available at: <https://standards.ieee.org/content/ieee-standards/en/about/contact/index.html>.

Photocopies

Subject to payment of the appropriate licensing fees, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400; <https://www.copyright.com/>. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#).³ For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

Errata

Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#).⁴ Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to periodically check for errata.

Patents

IEEE Standards are developed in compliance with the [IEEE SA Patent Policy](#).⁵

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

³ Available at: <https://ieeexplore.ieee.org/browse/standards/collection/ieee>.

⁴ Available at: <https://standards.ieee.org/standard/index.html>.

⁵ Available at: <https://standards.ieee.org/about/sasb/patcom/materials.html>.

1 Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not
2 responsible for identifying Essential Patent Claims for which a license may be required, for conducting
3 inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or
4 conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing
5 agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determi-
6 nation of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own
7 responsibility. Further information may be obtained from the IEEE Standards Association.

8 **IMPORTANT NOTICE**

9 IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure
10 against interference with or from other devices or networks. IEEE Standards development activities consider
11 research and information presented to the standards development group in developing any safety recommen-
12 dations. Other information about safety practices, changes in technology or technology implementation, or
13 impact by peripheral systems also may be pertinent to safety considerations during implementation of the
14 standard. Implementers and users of IEEE Standards documents are responsible for determining and com-
15 plying with all appropriate safety, security, environmental, health, and interference protection practices and
16 all applicable laws and regulations.

17

1 Participants

2 The following is a list of participants in the IEEE 802.1 Working Group.

3 **Glenn Parsons**, *Chair*

4 **Jessy Rouyer**, *Vice-Chair*

5 **Janos Farkas**, *Chair, Time-Sensitive Networking Task Group*

6 **Marc Holness**, *Technical Editor*

7 The following members of the individual balloting committee voted on this standard. Balloters may have
8 voted for approval, disapproval, or abstention.

When the IEEE-SA Standards Board approved this standard on XX Month 20XX, it had the following membership:

Name, Chair
Name, Vice Chair
Name, Past Chair
Name, Secretary

SBMember1	SBMember9	SBMember17
SBMember2	SBMember10	SBMember18
SBMember3	SBMember11	SBMember19
SBMember4	SBMember12	SBMember20
SBMember5	SBMember13	SBMember21
SBMember6	SBMember14	SBMember22
SBMember7	SBMember15	SBMember23
SBMember8	SBMember16	

*Member Emeritus

8
9
10

¹ Introduction to IEEE P802f/D2.4

²

This introduction is not part of IEEE P802f/D2.4, Draft Standard for Local and Metropolitan Area Networks: Overview and Architecture Amendment 3: YANG Data Model for EtherTypes. Additionally, the Annex, containing the Tutorial, is not part of this Standard.

³ This amendment specifies a YANG module that contains the EtherType information, including a compact
⁴ human-readable name and description, for a subset of EtherTypes taken from the IEEE Registration
⁵ Authority EtherType public listing. This amendment also addresses errors and omissions in IEEE Std 802
⁶ description of existing functionality.

1	2.	Normative references	14
2	5.	Reference models (RMs)	15
3	7.	IEEE 802 network management	16
4	7.2.2	Management architecture.....	16
5	7.2.3	Managed object definitions.....	16
6	8.	MAC addresses	18
7	8.2.2	Assignment of universal addresses	18
8	8.3	Interworking with 48-bit and 64-bit MAC addresses	18
9	9.	Protocol identifiers and context-dependent identifiers	19
10	9.2	EtherTypes	19
11	9.2.1	Format, function, and administration.....	19
12	9.2.1a	Public EtherType assignments subset.....	19
13	Annex A	22
14	Bibliography	22
15	Annex D	23
16	List of IEEE 802 standards	23
17	Annex F	25
18	EtherType Listing Subset.....		25
19	F.1	Introduction.....	25
20	F.2	Tabular format	25
21	F.3	YANG module for EtherType subset	28
22	F.3.1	YANG Framework.....	28
23	F.3.2	Definition for ieee802-ethertype YANG module'	29
24	Annex G	39
25	Wake-on-LAN	39

1 IEEE P802f/D2.4

2

3 Draft Standard for Local and 4 Metropolitan Area Networks: 5 Overview and Architecture 6 Amendment 3: YANG Data Model for 7 EtherTypes

8 (This amendment is based on IEEE Std 802-2014, as previously amended by IEEE Std 802d-2017 and IEEE
9 Std 802c-2017.)

10 Editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace.
11 ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change
12 and describes what is being changed either by using ~~strikethrough~~ (to remove old material) and underscore (to add new
13 material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Insertions
14 may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make
15 changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing in-
16 structions, change markings, and this NOTE will not be carried over into future editions because the changes will be in-
17 corporated into the base standard.⁶

18

⁶Notes in text, tables, and figures are given for information only, and do not contain requirements needed to implement the standard.

2. Normative references

Change the text of Clause 2 as follows:

~~IEEE Std 802.1D™, IEEE Standard for Local and metropolitan area networks—Media Access Control (MAC) Bridges.~~^{1,2}

IEEE Std 802.1Q™, IEEE Standard for Local and metropolitan area networks—Virtual Bridged Local Area Networks.^{1,2}

5. Reference models (RMs)

5.3.2.1 Bridges and bridged IEEE 802 networks

Change the text of the 1st paragraph of 5.3.2.1 as follows:

Bridges are stations that interconnect multiple access domains. IEEE Std 802.1D⁷ provides the basic specification for bridge interworking among IEEE 802 networks. A bridged IEEE 802 network consists of one or more bridges together with the complete set of access domains that they interconnect. A bridged IEEE 802 network provides end stations belonging to any of its access domains with the connectivity of a network that contains the whole set of attached end stations. IEEE Std 802.1Q ~~adds additional capabilities to the bridge specification in IEEE Std 802.1D including virtual local area networks (VLANs), priorities, and provider bridging, as described in 5.3.2.5~~ includes provisions for MAC Bridging, virtual local area networks (VLANs), priorities and provider bridging.

Change the text of the last paragraph of 5.3.2.1 as follows:

The term *switch* is often used to refer to some classes of bridge. However, there is no consistent meaning applied to the distinction between the terms *bridge* and *switch*, and IEEE Std 802.1DQ does not make any such distinction. Hence, this standard only uses the term *bridge*.

5.3.2.3 Resolving topologies with multiple paths

Change the text of 5.3.2.3 as follows:

A key aspect of ~~IEEE Std 802.1D and~~ IEEE Std 802.1Q is the specification of the rapid spanning tree protocol (RSTP), which is used by bridges to configure their interconnections in order to prevent looping data paths in the bridged IEEE 802 network. If the basic interconnection topology of bridges and networks contains multiple possible paths between certain points, use of the RSTP blocks some paths in order to produce a simply connected active topology for the flow of MAC user traffic between end stations. For each point of attachment of a bridge to a network, the RSTP selects whether MAC user traffic is to be received and transmitted by the bridge at that point of attachment.

5.3.2.4 Transparent bridging

Change the text of 5.3.2.4 as follows:

~~IEEE Std 802.1D and~~ IEEE Std 802.1Q ~~specify~~ specifies transparent bridging operation, so called because the MAC bridging function does not require the MAC user frames transmitted and received to carry any additional information relating to the operation of the bridging functions; end-station operation is unchanged by the presence of bridges.

31

⁷ Information on normative references can be found in Clause 2.

1 7. IEEE 802 network management

2 7.2.2 Management architecture

3 *Change the text of 7.2.2 as follows:*

4 The Simple Network Management Protocol (SNMP), as described in IETF RFC 3411 [B5], [and Network](#)
5 [Configuration Protocol \(NETCONF\), as described in RFC 6241 \[B15\]](#), ~~are examples of~~ ~~provides a~~ general-
6 purpose management protocols that can be used for the management of IEEE 802 network equipment.

7 7.2.3 Managed object definitions

8 *Change the text of 7.2.3 as follows:*

9 In order for an IEEE 802 standard to specify management facilities, it is necessary for it to specify managed
10 objects that model the operations that can be performed on the communications resources specified in the
11 standard. The components of a managed object definition are as follows:

- 12 a) A definition of the functionality provided by the managed object, and the relationship between this
13 functionality and the resource to which it relates.
- 14 b) A definition of the syntax that is used to convey management operations, and their arguments and
15 results, in a management protocol.
- 16 c) An address that allows the management protocol to specifically communicate with the managed
17 object in question. In IEEE 802 this is done with an object identifier (OID), as described in
18 Clause 10, [or a Uniform Resource Name \(URN\), as described in Clause 11](#).

19 The functionality of a managed object can be described in a manner that is independent of the protocol that
20 is used; this abstract definition can then be used in conjunction with a definition of the syntactic elements
21 required in order to produce a complete definition of the object for use with specific management protocols.

22 SNMP is used in many cases together with the structure of management information known as SMIV2 (IETF
23 RFC 2578, IETF RFC 2579 [B3], and IETF RFC 2580 [B4]), which uses a set of macros based on a subset
24 of ASN.1 for defining managed objects. [YANG \(IETF RFC 7950\) is a data modeling language used to](#)
25 [model configuration data, state data, remote procedure calls, and notifications for network management](#)
26 [protocols](#).

27 The choice of notational tools for defining managed objects depends on ~~which of~~ the available management
28 protocols the standard supports.

8. MAC addresses

8.2.2 Assignment of universal addresses

Change the text of 8.2.2 as follows:

A universal address consists of two parts: the leading bits (24, 28, or 36) are assigned by the IEEE RA with the U/L bit set to zero and the remaining bits by that assignee. An example of an EUI-48 is shown in Figure 10. For MA-M and MA-S, the final 4 bits of the assigned number are in a nibble that is not adjacent to the other bits in the assigned number when displayed with LSB on the left and most significant bit (MSB) on the right. For example, when using an MA-S to create an EUI-48, the MA-S value is contained in octets 0, 1, 2, 3 and the **least most** significant **nibble four bits** of octet 4, and the value assigned by the assignee is contained in the **most least** significant **nibble four bits** of octet 4 and **in** octet 5.

Change the NOTE of 8.2.4 as follows:

NOTE—While some implementations have used a single EUI-48 or EUI-64 to identify all of the system's points of attachment to IEEE 802 networks, this approach does not inherently meet the requirements of IEEE 802.1DQ™ **MAC bridging**.

8.3 Interworking with 48-bit and 64-bit MAC addresses

Change the text of 8.3 as follows:

In response to concerns that the EUI-48 space could be exhausted by the breadth of products requiring unique identifiers, 64-bit MAC addresses were introduced. Initially, new IEEE standards projects that did not require backward compatibility with EUI-48 were requested to use 64-bit MAC addresses. This led to some IEEE 802 standards adopting 64-bit MAC addressing, which cannot be bridged onto IEEE 802 networks that use 48-bit MAC addressing. The reason is that the bridging function in **IEEE Std 802.1D and IEEE Std 802.1Q** assumes that 48-bit MAC addresses are unique among all the connected networks. Truncating **a** 64-bit MAC address into **a** 48-bit field can lead to two stations having the same 48-bit value. Instead, traffic between 64-bit and 48-bit MAC addressed networks needs to be routed at a layer above the DLL.

9. Protocol identifiers and context-dependent identifiers

9.2 EtherTypes

9.2.1 Format, function, and administration

Change the footnote in the first paragraph of 9.2.1:

EtherType protocol identification values are assigned by the IEEE RA⁸ and are used to identify the protocol that is to be invoked to process the user data in the frame. An EtherType is a sequence of 2 octets, interpreted as a 16-bit numeric value with the first octet containing the most significant 8 bits and the second octet containing the least significant 8 bits. Values in the 0–1535 range are not available for use in order to retain legacy compatibility with Length field based protocols, e.g., IEEE Std 802.3.

Change the second paragraph of 9.2.1 as follows:

Examples of EtherTypes are 0x08_00 and 0x86_DD, which are used to identify IPv4 and IPv6, respectively.

Insert a new sub-clause 9.2.1a, after 9.2.1, and renumber the following existing sub-clauses accordingly.

9.2.1a Public EtherType assignments subset

The IEEE Registration Authority (RA) provides a public listing of EtherType assignments⁹. Many of these are for private or proprietary purposes. However, others are incorporated into well-known standards. In some cases, the IEEE RA Public Listing for an EtherType identifies an assignee without explicitly identifying the standards in which the use of that EtherType is specified. For ready reference by users and developers of such standards, Annex F identifies some well-known EtherTypes and the protocols they identify. This subset is derived by combining the EtherTypes listed in the ietf-ethertypes YANG module specified in IETF RFC 8519 [B11] with the subset of EtherTypes defined by IEEE 802 Standards (e.g., IEEE 802.1Q, 802.3, etc.) and as provided by participants that developed this standard. Information on products released after that date can be found on the IEEE SA Registration Authority web site: <https://standards.ieee.org/products-programs/regauth/ethertype/> and <https://regauth.standards.ieee.org/standards-ra-web/pub/view.html#registries>. The subset in Table F.1 and in F.3 is provided solely for the convenience of users of this standard and does not constitute an endorsement by IEEE of the listed protocols.

The EtherType public listing includes the following fields, specified by the EtherType assignee:

- **Assignment** — The hexadecimal representation of the EtherType.
- **Assignment Type** — The type is EtherType¹⁰.
- **Company Name** — The registrant of the Assignment.
- **Company Address** — The address of the registrant.
- **Protocol** — A brief protocol description, as provided by the registrant.

This Standard includes the following fields in Table F.1 for use by the YANG module:

⁸More information on EtherTypes can be found at <http://standards.ieee.org/develop/regauth/4le> on the IEEE RA web site, <https://standards.ieee.org/products-programs/regauth/ethertype> and <https://regauth.standards.ieee.org/standards-ra-web/pub/view.html#registries>.

⁹The EtherType public listing is the public view of the EtherType registry managed by the Registration Authority (see <https://regauth.standards.ieee.org/>).

¹⁰EtherType is the only assignment type for the records in the EtherType public listing.

- 1 a) **Friendly Name** — A short alphanumeric name for the Assignment that is unique within the YANG
 - 2 module in Annex F.2 and is used to enumerate the entry.
 - 3 b) **Short Description** — A short description of the assigned protocol per its typical usage.
 - 4 c) **Reference** — A reference to a standard associated with the EtherType assignment.
- 5 A YANG model representation can be found in Annex F.3.2.

¹ **Annex A**

² (informative)

³ **Bibliography**

⁴ *Insert the following bibliography reference in the appropriate collating sequence:*

⁵ [B11] IETF RFC 8519, YANG Data Model for Network Access Control Lists (ACLs), March 2019.

⁶ [B15] IETF RFC 6241, Network Configuration Protocol (NETCONF), June 2011.

¹ **Annex D**

² (informative)

³ **List of IEEE 802 standards**

⁴ *Delete the following standard reference from the list.*

⁵ ~~IEEE Std 802.1D™, IEEE Standard for Local and metropolitan area networks: Media Access Control~~
⁶ ~~(MAC) Bridges.~~

⁷

Insert a new Annex as follows:

Annex F

(informative)

EtherType Listing Subset

F.1 Introduction

This Annex lists the subset of EtherType assignments described in 9.2.1 in tabular form (Table F.1) and in the form of a YANG module (F.2). This subset is provided solely for the convenience of the users of this standard and does not constitute an endorsement by IEEE of the listed protocols.

F.2 Tabular format

A subset of EtherType assignments by the IEEE RA is given in Table F.1. Each Friendly Name in Table F.1 is unique and is used as an identifier in the YANG module. The Short Description identifies the protocol, protocol message, or protocol field that uses the assignment as specified in the Reference, or the EtherType assignment itself as named in the Reference. Where the Reference specifies more than one name or use (distinguished for example by sub-type) these are included in the Short Description field.

15

Table F.1 — EtherType listing subset^a

EtherType Assignment (HEX)	Friendly Name	Short Description	Reference
08-00	ipv4	Internet Protocol version 4 (IPv4)	IETF RFC 894
08-06	arp	Address Resolution Protocol (ARP)	IETF RFC 826, IETF RFC 7042
08-42	wol	Wake-on-LAN	IEEE Std 802
22-E2	misp	MAC Status Protocol (MSP)	IEEE Std 802.1Q
22-E7	cnm	Congestion Notification Message (CNM)	IEEE Std 802.1Q
22-E9	cn-tag	Congestion Notification Tag (CN-TAG)	IEEE Std 802.1Q
22-EA	msrp	Multiple Stream Reservation Protocol (MSRP)	IEEE Std 802.1Q
22-F3	trill	Transparent Interconnection of Lots of Links	IETF RFC 6325

Table F.1 — EtherType listing subset^a (continued)

EtherType Assignment (HEX)	Friendly Name	Short Description	Reference
60-03	decnet	DECnet DNA Routing	DECnet DIGITAL Network Architecture - Ethernet Data Link Architectural Specification v1.0.0
80-35	rarp	Reverse Address Resolution Protocol	IETF RFC 903
80-9B	appletalk	Appletalk (Ethertalk)	Inside Appletalk, Second Edition
80-F3	aarp	Appletalk Address Resolution Protocol	Inside Appletalk, Second Edition
81-00	c-tag	Customer VLAN Tag (C-TAG)	IEEE Std 802.1Q
81-37	ipx	Internetwork Packet Exchange (IPX)	Internetwork Packet Exchange - Novell, Inc.
82-04	qnx	QNX Qnet	QNX - Quantum Software Systems, Ltd.
86-DD	ipv6	Internet Protocol Version 6 (IPv6)	IETF RFC 2464
88-08	efc	Multipoint Control Protocol (MPCP)	IEEE Std 802.3
88-09	esp	Ethernet Slow Protocol	IEEE Std 802.3
88-19	cobranet	CobraNet	CobraNet Programmer's Reference, Version 2.5
88-47	mpls-unicast	Multiprotocol Label Switching (MPLS) unicast traffic	IETF RFC 3031
88-48	mpls-multicast	Multiprotocol Label Switching (MPLS) multicast	IETF RFC 3031
88-63	pppoe-discovery	Point-to-Point Protocol over Ethernet (PPPoE) Discovery Stage	IETF RFC 2516
88-64	pppoe-session	Point-to-Point Protocol over Ethernet (PPPoE) Session Stage	IETF RFC 2516
88-6D	intel-ans	Intel Advanced Networking Services Probe Packets	Intel® Advanced Network Services (Intel® ANS) Advanced Settings for Teams
88-70	llc-encaps	LLC Encapsulation	IEEE Std 802.1AC
88-7B	homeplug	Homeplug	INT51X1 datasheet
88-8E	eapol	Port Access Entity (PAE) EtherType, Extensible Authentication Protocol over LANs (EAPOL)	IEEE Std 802.1X
88-92	profinet	PROFINET	IEC 61158-6-10

Table F.1 — EtherType listing subset^a (continued)

EtherType Assignment (HEX)	Friendly Name	Short Description	Reference
88-9A	hyperscsi	Small Computer System Interface (SCSI) over Ethernet.	An Ethernet Based Data Storage Protocol for Home Network
88-A2	aoe	Advanced Technology Attachment (ATA) over Ethernet.	AoE (ATA over Ethernet)
88-A4	ethercat	Ethernet for Control Automation Technology (EtherCAT)	IEC 61158-4-12
88-A8	s-tag	Service VLAN Tag (S-TAG) or Backbone VLAN Tag (B-TAG)	IEEE Std 802.1Q
88-AB	ethernet-powerlink	Ethernet Powerlink	IEC 61158-4-13
88-B5	exp1	Local experimental EtherType 1	IEEE Std 802
88-B6	exp2	Local experimental EtherType 2	IEEE Std 802
88-B7	oui-ext	OUI Extended EtherType	IEEE Std 802
88-B8	goose	IEC 61850 Generic Object Oriented Substation Event (GOOSE)	IEC 61850-8-1
88-B9	gse	IEC 61850 Generic Substation Events (GSE) management services	IEC 61850-8-1
88-BA	sv	IEC 61850 Sampled Value Transmission (SV)	IEC 61850-8-2
88-C7	pre-auth	RSNA Pre-Authentication	IEEE Std 802.11
88-CC	lldp	Link Layer Discovery Protocol (LLDP)	IEEE Std 802.1AB
88-CD	sercos	Sercos Interface	IEC 61158-4-19
88-DC	wsmpp	WAVE Short Message Protocol (WSMP)	IEEE Std 1609
88-E1	homeplug-av-mme	HomePlug AV Mobile Management Entity (MME)	HomePlug AV Specification
88-E3	mrp	Media Redundancy Protocol	IEC 62439-2
88-E5	macsec	MACsec EtherType	IEEE Std 802.1AE
88-E7	i-tag	Backbone Service Instance Tag	IEEE Std 802.1Q
88-F5	mvrp	Multiple VLAN Registration Protocol (MVRP)	IEEE Std 802.1Q
88-F6	mmrp	Multiple MAC Registration Protocol (MMRP)	IEEE Std 802.1Q
88-F7	ptp	Precision Time Protocol	IEEE Std 1588
89-02	cfm	IEEE 802.1Q Connectivity Fault Management (CFM) PDU Encapsulation EtherType	IEEE Std 802.1Q

Table F.1 — EtherType listing subset^a (continued)

EtherType Assignment (HEX)	Friendly Name	Short Description	Reference
89-06	fcoe	Fibre Channel over Ethernet (FCoE)	T11 FC-BB-5
89-0D	wlan-mgmt	802.11 Management Protocol	IEEE Std 802.11
89-10	encap	Backbone Service Encapsulated Addresses	IEEE Std 802.1Q
89-14	fip	FCoE Initialization Protocol	T11 FC-BB-5
89-15	roce	Remote Direct Memory Access (RDMA) over Converged Ethernet (RoCEv1)	InfiniBand™ Architecture Specification
89-17	mis	Media Independent Service (MIS) Protocol	IEEE Std 802.21
89-1D	tte	Time-Triggered Ethernet (TTE) Protocol Control Frame	SAE AS6802
89-29	mirp	Multiple I-SID Registration Protocol (MIRP)	IEEE Std 802.1Q
89-2F	hsr	High-availability Seamless Redundancy (HSR)	IEC 62439-3
89-3F	e-tag	Bridge Port Extension Tag (E-TAG)	IEEE Std 802.1BR
89-40	ecp	Edge Control Protocol	IEEE Std 802.1Q
89-4B	f-tag	Flow Filtering Tag (F-TAG)	IEEE Std 802.1Q
89-52	drcep	Distributed Relay Control Protocol (DRCP)	IEEE Std 802.1AX
89-A2	cim	Congestion Isolation Message (CIM)	IEEE Std 802.1Q
C9-D1	llc-legacy	LLC Encapsulation (obsolete)	IEEE Std 802.1AC
E2-3B	mpp	MAC Privacy protection Protocol	IEEE Std 802.1AE
F1-C1	r-tag	Frame Replication and Elimination for Reliability (FRER) Redundancy Tag (R-TAG)	IEEE Std 802.1CB

^aHexadecimal values in the Assignment field are provided from the public listing, while the information in the other fields (i.e., Friendly Name, Short Description, and Reference) is specified herein.

¹ F.3 YANG module for EtherType subset

² F.3.1 YANG Framework

³ The YANG module representation of the EtherType subset (as defined in Table F.1) is provided in this Annex.

1 Changes to the `ieee802-ethertypes.yang` module, adding or revising entries, are made by amending or revising this
2 standard and will add a new revision statement to the module. YANG augmentation should not be used to extend the
3 module.

4 NOTE — The `ietf-ethertypes.yang` module (as defined in `rfc8519`) is currently used by the
5 `ietf-packet-fields.yang` module (as defined in `rfc8519`) and the `ietf-detnet.yang` module. Moving forward it is
6 anticipated that the YANG module (`ieee802-ethertype.yang`) defined in Annex F.3.2 will supersede
7 `ietf-ethertypes.yang`, which would result in `ietf-ethertypes.yang` being deprecated.



8 F.3.2 Definition for `ieee802-ethertype` YANG module^{11,12}

```
9 module ieee802-ethertype {
10
11   namespace "urn:ieee:std:802.1Q:yang:ieee802-ethertype";
12   prefix "ieee-ethertype";
13
14   organization
15     "IEEE 802.1 Working Group";
16
17   contact
18     "WG-URL: http://ieee802.org/1/
19     WG-EMail: stds-802-1@ieee.org
20
21     Contact: IEEE 802.1 Working Group Chair
22     Postal: C/O IEEE 802.1 Working Group
23             IEEE Standards Association
24             445 Hoes Lane
25             Piscataway
26             NJ 08854
27             USA
28
29     E-mail: stds-802-1-chairs@ieee.org";
30
31   description
32     "This module contains a subset of commonly used 802 network EtherTypes.
33
34     Copyright (C) IEEE (2023).
35
36     This version of this YANG module is part of the IEEE Std 802;
37     see the standard itself for full legal notices.";
38
39   revision "2023-04-17" {
40     description
41       "Initial revision.";
42     reference
43       "IEEE Std 802f, Overview and Architecture -
44       YANG Data Model for EtherTypes";
45   }
46
47   typedef ethertype {
48     type enumeration {
49       enum ipv4 {
50         value 2048;
51         description
52           "08-00 Internet Protocol version 4 (IPv4)";
53         reference
```

¹¹Copyright release for YANG: Users of this standard may freely reproduce the YANG modules contained in this standard so that they can be used for their intended purpose.

¹²An ASCII version of the YANG module is attached to the PDF of this standard and can also be obtained from the IEEE 802.1 Website at <https://1.ieee802.org/yang-modules/>.

```
1         "Organization: Xerox, US
2         Reference: IETF RFC 894";
3     }
4     enum arp {
5         value 2054;
6         description
7             "08-06 Address Resolution Protocol (ARP)";
8         reference
9             "Organization: Symbolics, Inc.
10            Reference: IETF RFC 826, IETF RFC 7042";
11    }
12    enum wol {
13        value 2114;
14        description
15            "08-42 Wake-on-LAN";
16        reference
17            "Organization: None
18            Reference: IEEE Std 802";
19    }
20    enum msp {
21        value 8930;
22        description
23            "22-E2 MAC Status Protocol (MSP)";
24        reference
25            "Organization: IEEE 802.1 Working Group
26            Reference: IEEE Std 802.1Q";
27    }
28    enum cnm {
29        value 8935;
30        description
31            "22-E7 Congestion Notification Message (CNM)";
32        reference
33            "Organization: IEEE 802.1 Working Group
34            Reference: IEEE Std 802.1Q";
35    }
36    enum cn-tag {
37        value 8937;
38        description
39            "22-E9 Congestion Notification Tag (CN-TAG)";
40        reference
41            "Organization: IEEE 802.1 Working Group
42            Reference: IEEE Std 802.1Q";
43    }
44    enum msrp {
45        value 8938;
46        description
47            "22-EA Multiple Stream Reservation Protocol (MSRP)";
48        reference
49            "Organization: IEEE 802.1 Working Group
50            Reference: IEEE Std 802.1Q";
51    }
52    enum trill {
53        value 8947;
54        description
55            "22-F3 Transparent Interconnection of Lots of Links";
56        reference
57            "Organization: IETF TRILL Working Group
58            Reference: IETF RFC 6325";
59    }
60    enum decnet {
61        value 24579;
62        description
63            "60-03 DECnet DNA Routing";
64        reference
```

```
1      "Organization: DEC
2      Reference: DECnet DIGITAL Network Architecture - Ethernet
3      Data Link Architectural Specification v1.0.0";
4  }
5  enum rarp {
6      value 32821;
7      description
8          "80-35 Reverse Address Resolution Protocol";
9      reference
10         "Organization: Private
11         Reference: IETF RFC 903";
12  }
13  enum appletalk {
14      value 32923;
15      description
16          "80-9B Appletalk (Ethertalk)";
17      reference
18          "Organization: Private
19          Reference: Inside Appletalk, Second Edition";
20  }
21  enum aarp {
22      value 33011;
23      description
24          "80-F3 Appletalk Address Resolution Protocol";
25      reference
26          "Organization: Private
27          Reference: Inside Appletalk, Second Edition";
28  }
29  enum c-tag {
30      value 33024;
31      description
32          "81-00 Customer VLAN Tag (C-TAG)";
33      reference
34          "Organization: IEEE 802.1 Working Group
35          Reference: IEEE Std 802.1Q";
36  }
37  enum ipx {
38      value 33079;
39      description
40          "81-37 Internetwork Packet Exchange (IPX)";
41      reference
42          "Organization: Novell, Inc.
43          Reference: Internetwork Packet Exchange - Novell, Inc.";
44  }
45  enum qnx {
46      value 33284;
47      description
48          "82-04 QNX Qnet";
49      reference
50          "Organization: Quantum Software Systems, Ltd.
51          Reference: QNX - Quantum Software Systems, Ltd.";
52  }
53  enum ipv6 {
54      value 34525;
55      description
56          "86-DD Internet Protocol Version 6 (IPv6)";
57      reference
58          "Organization: USC/ISI
59          Reference: IETF RFC 2464";
60  }
61  enum efc {
62      value 34824;
63      description
64          "88-08 Multipoint Control Protocol (MPCP)";
```



```

1      reference
2      "Organization: IEEE 802.3 Working Group
3      Reference: IEEE Std 802.3";
4  }
5  enum esp {
6      value 34825;
7      description
8      "88-09 Ethernet Slow Protocol";
9      reference
10     "Organization: IEEE 802.3 Working Group
11     Reference: IEEE Std 802.3";
12 }
13 enum cobranet {
14     value 34841;
15     description
16     "88-19 CobraNet";
17     reference
18     "Organization: Peak Audio
19     Reference: CobraNet Programmer's Reference, Version 2.5";
20 }
21 enum mpls-unicast {
22     value 34887;
23     description
24     "88-47 Multiprotocol Label Switching (MPLS) unicast
25     traffic";
26     reference
27     "Organization: Cisco Systems
28     Reference: IETF RFC 3031";
29 }
30 enum mpls-multicast {
31     value 34888;
32     description
33     "88-48 Multiprotocol Label Switching (MPLS) multicast";
34     reference
35     "Organization: Cisco Systems
36     Reference: IETF RFC 3031";
37 }
38 enum pppoe-discovery {
39     value 34915;
40     description
41     "88-63 Point-to-Point Protocol over Ethernet (PPPoE)
42     Discovery Stage";
43     reference
44     "Organization: UUNET Technologies, Inc.
45     Reference: IETF RFC 2516";
46 }
47 enum pppoe-session {
48     value 34916;
49     description
50     "88-64 Point-to-Point Protocol over Ethernet (PPPoE)
51     Session Stage";
52     reference
53     "Organization: UUNET Technologies, Inc.
54     Reference: IETF RFC 2516";
55 }
56 enum intel-ans {
57     value 34925;
58     description
59     "88-6D Intel Advanced Networking Services Probe Packets";
60     reference
61     "Organization: Intel Corporation
62     Reference: Intel(R) Advanced Network Services (Intel(R) ANS)
63     Advanced Settings for Teams";
64 }

```

```
1      enum llc-encaps {
2          value 34928;
3          description
4              "88-70 LLC Encapsulation";
5          reference
6              "Organization: IEEE 802.1 Working Group
7              Reference: IEEE Std 802.1AC";
8      }
9      enum homeplug {
10         value 34939;
11         description
12             "88-7B Homeplug";
13         reference
14             "Organization: Intellon Corporation
15             Reference: INT51X1 datasheet";
16     }
17     enum eapol {
18         value 34958;
19         description
20             "88-8E Port Access Entity (PAE) EtherType, Extensible
21             Authentication Protocol over LANs (EAPOL)";
22         reference
23             "Organization: IEEE 802.1 Working Group
24             Reference: IEEE Std 802.1X";
25     }
26     enum profinet {
27         value 34962;
28         description
29             "88-92 PROFINET";
30         reference
31             "Organization: PROFIBUS International
32             Reference: IEC 61158-6-10";
33     }
34     enum hyperscsi {
35         value 34970;
36         description
37             "88-9A Small Computer System Interface (SCSI) over
38             Ethernet.";
39         reference
40             "Organization: Data Storage Institute
41             Reference: An Ethernet Based Data Storage Protocol for Home
42             Network";
43     }
44     enum aoe {
45         value 34978;
46         description
47             "88-A2 Advanced Technology Attachment (ATA) over Ethernet.";
48         reference
49             "Organization: Coraid Inc
50             Reference: AoE (ATA over Ethernet)";
51     }
52     enum ethercat {
53         value 34980;
54         description
55             "88-A4 Ethernet for Control Automation Technology
56             (EtherCAT)";
57         reference
58             "Organization: Beckhoff Automation GmbH & Co KG
59             Reference: IEC 61158-4-12";
60     }
61     enum s-tag {
62         value 34984;
63         description
64             "88-A8 Service VLAN Tag (S-TAG) or Backbone VLAN Tag
```

```

1      (B-TAG)";
2      reference
3      "Organization: IEEE 802.1 Working Group
4      Reference: IEEE Std 802.1Q";
5  }
6  enum ethernet-powerlink {
7      value 34987;
8      description
9      "88-AB Ethernet Powerlink";
10     reference
11     "Organization: Ethernet Powerlink Standardization Group
12     (EPSG)
13     Reference: IEC 61158-4-13";
14 }
15 enum expl {
16     value 34997;
17     description
18     "88-B5 Local experimental EtherType 1";
19     reference
20     "Organization: IEEE 802.1 Working Group
21     Reference: IEEE Std 802";
22 }
23 enum exp2 {
24     value 34998;
25     description
26     "88-B6 Local experimental EtherType 2";
27     reference
28     "Organization: IEEE 802.1 Working Group
29     Reference: IEEE Std 802";
30 }
31 enum oui-ext {
32     value 34999;
33     description
34     "88-B7 OUI Extended EtherType";
35     reference
36     "Organization: IEEE 802.1 Working Group
37     Reference: IEEE Std 802";
38 }
39 enum goose {
40     value 35000;
41     description
42     "88-B8 IEC 61850 Generic Object Oriented Substation Event
43     (GOOSE)";
44     reference
45     "Organization: IEC TC57
46     Reference: IEC 61850-8-1";
47 }
48 enum gse {
49     value 35001;
50     description
51     "88-B9 IEC 61850 Generic Substation Events (GSE) management
52     services";
53     reference
54     "Organization: IEC TC57
55     Reference: IEC 61850-8-1";
56 }
57 enum sv {
58     value 35002;
59     description
60     "88-BA IEC 61850 Sampled Value Transmission (SV)";
61     reference
62     "Organization: IEC TC57
63     Reference: IEC 61850-8-2";
64 }

```

```
1      enum pre-auth {
2          value 35015;
3          description
4              "88-C7  RSNA Pre-Authentication";
5          reference
6              "Organization: IEEE 802.11 Working Group
7              Reference: IEEE Std 802.11";
8      }
9      enum lldp {
10         value 35020;
11         description
12             "88-CC  Link Layer Discovery Protocol (LLDP)";
13         reference
14             "Organization: IEEE 802.1 Working Group
15             Reference: IEEE Std 802.1AB";
16     }
17     enum sercos {
18         value 35021;
19         description
20             "88-CD  Sercos Interface";
21         reference
22             "Organization: sercos international e.V.
23             Reference: IEC 61158-4-19";
24     }
25     enum wsmp {
26         value 35036;
27         description
28             "88-DC  WAVE Short Message Protocol (WSMP)";
29         reference
30             "Organization: IEEE P1609 WG
31             Reference: IEEE Std 1609";
32     }
33     enum homeplug-av-mme {
34         value 35041;
35         description
36             "88-E1  HomePlug AV Mobile Management Entity (MME)";
37         reference
38             "Organization: HomePlug Powerline Alliance, Inc.
39             Reference: HomePlug AV Specification";
40     }
41     enum mrp {
42         value 35043;
43         description
44             "88-E3  Media Redundancy Protocol";
45         reference
46             "Organization: Siemens AG
47             Reference: IEC 62439-2";
48     }
49     enum macsec {
50         value 35045;
51         description
52             "88-E5  MACsec EtherType";
53         reference
54             "Organization: IEEE 802 LAN/MAN Standards Committee
55             Reference: IEEE Std 802.1AE";
56     }
57     enum i-tag {
58         value 35047;
59         description
60             "88-E7  Backbone Service Instance Tag";
61         reference
62             "Organization: IEEE 802.1 Working Group
63             Reference: IEEE Std 802.1Q";
64     }
```

```

1      enum mvrp {
2          value 35061;
3          description
4              "88-F5 Multiple VLAN Registration Protocol (MVRP)";
5          reference
6              "Organization: IEEE 802.1 Working Group
7              Reference: IEEE Std 802.1Q";
8      }
9      enum mmrp {
10         value 35062;
11         description
12             "88-F6 Multiple MAC Registration Protocol (MMRP)";
13         reference
14             "Organization: IEEE 802.1 Working Group
15             Reference: IEEE Std 802.1Q";
16     }
17     enum ptp {
18         value 35063;
19         description
20             "88-F7 Precision Time Protocol";
21         reference
22             "Organization: IEEE I&M Society TC9
23             Reference: IEEE Std 1588";
24     }
25     enum cfm {
26         value 35074;
27         description
28             "89-02 IEEE 802.1Q Connectivity Fault Management (CFM) PDU
29             Encapsulation EtherType";
30         reference
31             "Organization: IEEE 802.1 Working Group
32             Reference: IEEE Std 802.1Q";
33     }
34     enum fcoe {
35         value 35078;
36         description
37             "89-06 Fibre Channel over Ethernet (FCoE)";
38         reference
39             "Organization: Cisco Systems, Inc
40             Reference: T11 FC-BB-5";
41     }
42     enum wlan-mgmt {
43         value 35085;
44         description
45             "89-0D 802.11 Management Protocol";
46         reference
47             "Organization: IEEE 802.11 Working Group
48             Reference: IEEE Std 802.11";
49     }
50     enum encap {
51         value 35088;
52         description
53             "89-10 Backbone Service Encapsulated Addresses";
54         reference
55             "Organization: IEEE 802.1 Working Group
56             Reference: IEEE Std 802.1Q";
57     }
58     enum fip {
59         value 35092;
60         description
61             "89-14 FCoE Initialization Protocol";
62         reference
63             "Organization: Brocade Communications Systems LLC
64             Reference: T11 FC-BB-5";

```

```
1      }
2      enum roce {
3          value 35093;
4          description
5              "89-15 Remote Direct Memory Access (RDMA) over Converged
6              Ethernet (RoCEv1)";
7          reference
8              "Organization: Mellanox Technologies, Inc.
9              Reference: InfiniBand(TM) Architecture Specification";
10     }
11     enum mis {
12         value 35095;
13         description
14             "89-17 Media Independent Service (MIS) Protocol";
15         reference
16             "Organization: IEEE 802.21 Working Group
17             Reference: IEEE Std 802.21";
18     }
19     enum tte {
20         value 35101;
21         description
22             "89-1D Time-Triggered Ethernet (TTE) Protocol Control
23             Frame";
24         reference
25             "Organization: TTTech Computertechnik AG
26             Reference: SAE AS6802";
27     }
28     enum mirp {
29         value 35113;
30         description
31             "89-29 Multiple I-SID Registration Protocol (MIRP)";
32         reference
33             "Organization: IEEE 802.1 Working Group
34             Reference: IEEE Std 802.1Q";
35     }
36     enum hsr {
37         value 35119;
38         description
39             "89-2F High-availability Seamless Redundancy (HSR)";
40         reference
41             "Organization: International Electrotechnical Commission
42             Reference: IEC 62439-3";
43     }
44     enum e-tag {
45         value 35135;
46         description
47             "89-3F Bridge Port Extension Tag (E-TAG)";
48         reference
49             "Organization: IEEE 802.1 Working Group
50             Reference: IEEE Std 802.1BR";
51     }
52     enum ecp {
53         value 35136;
54         description
55             "89-40 Edge Control Protocol";
56         reference
57             "Organization: IEEE 802.1 Working Group
58             Reference: IEEE Std 802.1Q";
59     }
60     enum f-tag {
61         value 35147;
62         description
63             "89-4B Flow Filtering Tag (F-TAG)";
64         reference
```

```
1      "Organization: IEEE 802.1 Working Group
2      Reference: IEEE Std 802.1Q";
3  }
4  enum drcp {
5      value 35154;
6      description
7          "89-52 Distributed Relay Control Protocol (DRCP)";
8      reference
9          "Organization: IEEE 802.1 Working Group
10         Reference: IEEE Std 802.1AX";
11  }
12  enum cim {
13      value 35234;
14      description
15          "89-A2 Congestion Isolation Message (CIM)";
16      reference
17          "Organization: IEEE 802.1 Working Group
18         Reference: IEEE Std 802.1Q";
19  }
20  enum llc-legacy {
21      value 51665;
22      description
23          "C9-D1 LLC Encapsulation (obsolete)";
24      reference
25          "Organization: IEEE 802.1 Working Group
26         Reference: IEEE Std 802.1AC";
27  }
28  enum mpp {
29      value 57915;
30      description
31          "E2-3B MAC Privacy protection Protocol";
32      reference
33          "Organization:
34         Reference: IEEE Std 802.1AE";
35  }
36  enum r-tag {
37      value 61889;
38      description
39          "F1-C1 Frame Replication and Elimination for Reliability
40         (FRER) Redundancy Tag (R-TAG)";
41      reference
42          "Organization: IEEE 802.1 Working Group
43         Reference: IEEE Std 802.1CB";
44  }
45  }
46  description
47      "IEEE Std 802 EtherTypes subset.";
48  }
49
50 }
51
52
```

Insert a new Annex as follows:

Annex G

(informative)

Wake-on-LAN

Wake-on-LAN (WoL) is a common protocol to wake up devices from a very low power mode remotely. It can be implemented over IEEE 802 networks as a frame using the EtherType 08-42. The payload of a WoL packet following the EtherType is shown in Figure G.1.

Figure G.1— Wake-on-LAN packet payload fields

6 octets	96 octets	0, 4 or 6 octets
Synchronization Stream	Target MAC	Password (optional)

The Synchronization Stream contains the all-stations broadcast MAC address, as specified in 8.2.2. The Target MAC contains 16 duplications of the destination MAC address. The Password field is optional, but if present, contains either 4 octets (for an IPv4 address) or 6 octets (for a MAC address).