

**Draft IEEE Standard for
Local and Metropolitan Area Networks—**

**Port-Based Network Access
Control—Corrigendum 1**

Prepared by the
IEEE 802.1 Maintenance Task Group

Developed by the
LAN/MAN Standards Committee
of the IEEE Computer Society

This and the following cover pages are not part of the draft. They provide revision and other information for IEEE 802.1 Working Group members and participants in the IEEE Standards Association ballot process, and will be updated as convenient. The text proper of this draft begins with the [Title page](#).

Current draft

The text of this draft, following these cover pages, is that of P802.1X-2020/Cor1 as of the final Working Group Recirculation Ballot with the omission of change bars showing changes from prior drafts.

Important Notice

This document is an unapproved draft of a proposed IEEE Standard. IEEE hereby grants the named IEEE SA Working Group or Standards Committee Chair permission to distribute this document to participants in the receiving IEEE SA Working Group or Standards Committee, for purposes of review for IEEE standardization activities. No further use, reproduction, or distribution of this document is permitted without the express written permission of IEEE Standards Association (IEEE SA). Prior to any review or use of this draft standard, in part or in whole, by another standards development organization, permission must first be obtained from IEEE SA (stds-copyright@ieee.org). This page is included as the cover of this draft, and shall not be modified or deleted.

IEEE Standards Association
445 Hoes Lane
Piscataway, NJ 08854, USA

Base standard

1

This draft is being submitted to SA Ballot as a corrigendum to IEEE Std 802.1X-2020 in order to update the
2 attached YANG modules to support the ability to extend the interfaces used.

3

MIB and YANG modules

4

The YANG modules specified by this standard are attached to the draft pdf as plain text (UTF-8) .yang files.

5

6

**Draft IEEE Standard for
Local and Metropolitan Area Networks—
Port-Based Network Access
Control—Corrigendum 1**

IEEE Computer Society

Developed by the
LAN/MAN Standards Committee

Copyright © 2026 by the IEEE.
Three Park Avenue
New York, New York 10016-5997, USA
All rights reserved.

This document is an unapproved draft of a proposed IEEE Standard. As such, this document is subject to change. USE AT YOUR OWN RISK! IEEE copyright statements SHALL NOT BE REMOVED from draft or approved IEEE standards, or modified in any way. Because this is an unapproved draft, this document must not be utilized for any conformance/compliance purposes. Permission is hereby granted for officers from each IEEE Standards Working Group or Committee to reproduce the draft document developed by that Working Group for purposes of international standardization consideration. IEEE Standards Department must be informed of the submission for consideration prior to any reproduction for international standardization consideration (stds.ipr@ieee.org). Prior to adoption of this document, in whole or in part, by another standards development organization, permission must first be obtained from the IEEE Standards Department (stds.ipr@ieee.org). When requesting permission, IEEE Standards Department will require a copy of the standard development organization's document highlighting the use of IEEE content. Other entities seeking permission to reproduce this document, in whole or in part, must also obtain permission from the IEEE Standards Department.

IEEE Standards Department
445 Hoes Lane
Piscataway, NJ 08854, USA

Abstract: This corrigendum to IEEE Std 802.1X-2020 corrects the when statement for the augment of the interfaces container in the ieee802-dot1x YANG module to avoid limiting the latter's applicability..

Keywords: access control, authentication, authorization, controlled port, EAP, EAPOL, IEEE 802.1X, key agreement, LANs, local area networks, MACsec, MACsec Key Agreement, MAC security, MAC Service, MANs, metropolitan area networks, MKA, port-based network access control, secure association, security, service access point, uncontrolled port.

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2026 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Unapproved draft.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-X-XXX-XXX-X STDXXXXX
Print: ISBN 978-X-XXX-XXX-X STDPDXXXXX

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

1 Important Notices and Disclaimers Concerning IEEE Standards Documents

3 IEEE Standards documents are made available for use subject to important notices and legal disclaimers.
4 These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>),
5 appear in all IEEE standards and may be found under the heading “Important Notices and Disclaimers
6 Concerning IEEE Standards Documents.”

7 Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

9 IEEE Standards documents are developed within IEEE Societies and subcommittees of IEEE Standards
10 Association (IEEE SA) Board of Governors. IEEE develops its standards through an accredited consensus
11 development process, which brings together volunteers representing varied viewpoints and interests to
12 achieve the final product. IEEE Standards are documents developed by volunteers with scientific, academic,
13 and industry-based expertise in technical working groups. Volunteers involved in technical working groups
14 are not necessarily members of IEEE or IEEE SA and participate without compensation from IEEE. While
15 IEEE administers the process and establishes rules to promote fairness in the consensus development
16 process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the
17 soundness of any judgments contained in its standards.

18 IEEE makes no warranties or representations concerning its standards, and expressly disclaims all
19 warranties, express or implied, concerning all standards, including but not limited to the warranties of
20 merchantability, fitness for a particular purpose and non-infringement. IEEE Standards documents do not
21 guarantee safety, security, health, or environmental protection, or compliance with law, or guarantee against
22 interference with or from other devices or networks. In addition, IEEE does not warrant or represent that the
23 use of the material contained in its standards is free from patent infringement. IEEE standards documents are
24 supplied “AS IS” and “WITH ALL FAULTS.”

25 Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there
26 are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to
27 the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and
28 issued is subject to change brought about through developments in the state of the art and comments
29 received from users of the standard.

30 In publishing and making its standards available, IEEE is not suggesting or rendering professional or other
31 services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any
32 other person or entity to another. Any person utilizing any IEEE Standards document should rely upon their
33 own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate,
34 seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

35 IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
36 EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE
37 NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
38 BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
39 WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
40 OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON
41 ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND
42 REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

43 Translations

44 The IEEE consensus balloting process involves the review of documents in English only. In the event that an
45 IEEE standard is translated, only the English language version published by IEEE is the approved IEEE
46 standard.

1 Use by artificial intelligence systems

2 In no event shall material in any IEEE Standards documents be used for the purpose of creating, training,
3 enhancing, developing, maintaining, or contributing to any artificial intelligence systems without the
4 express, written consent of the IEEE SA in advance. “Artificial intelligence” refers to any software,
5 application, or other system that uses artificial intelligence, machine learning, or similar technologies, to
6 analyze, train, process, or generate content. Requests for consent can be submitted using the [Contact Us](#)
7 form.¹

8 Official statements

9 A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board
10 Operations Manual is not, and shall not be considered or inferred to be, the official position of IEEE or any
11 of its committees and shall not be considered to be or be relied upon as, a formal position of IEEE or IEEE
12 SA. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE
13 standards shall make it clear that the presenter’s views should be considered the personal views of that
14 individual rather than the formal position of IEEE, IEEE SA, the Standards Committee, or the Working
15 Group. Statements made by volunteers may not represent the formal position of their employer(s) or
16 affiliation(s). News releases about IEEE standards issued by entities other than IEEE SA should be
17 considered the view of the entity issuing the release rather than the formal position of IEEE or IEEE SA.

18 Comments on standards

19 Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of
20 membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations,**
21 **consulting information, or advice pertaining to IEEE Standards documents.**

22 Suggestions for changes in documents should be in the form of a proposed change of text, together with
23 appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is
24 important that any responses to comments and questions also receive the concurrence of a balance of interests.
25 For this reason, IEEE and the members of its Societies and subcommittees of the IEEE SA Board of
26 Governors are not able to provide an instant response to comments or questions except in those cases where
27 the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation
28 requests. Any person who would like to participate in evaluating comments or revisions to an IEEE standard is
29 welcome to join the relevant IEEE SA working group. You can indicate interest in a working group using the
30 Interests tab in the Manage Profile & Interests area of the [IEEE SA myProject system](#).² An IEEE Account is
31 needed to access the application.

32 Comments on standards should be submitted using the [Contact Us](#) form.¹

33 Laws and regulations

34 Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the
35 provisions of any IEEE Standards document does not constitute compliance to any applicable regulatory
36 requirements. Implementers of the standard are responsible for observing or referring to the applicable
37 regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not
38 in compliance with applicable laws, and these documents may not be construed as doing so.

39 Data privacy

40 Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and
41 data ownership in the context of assessing and using the standards in compliance with applicable laws and
42 regulations.

¹ Available at: <https://standards.ieee.org/content/ieee-standards/en/about/contact/>.

² Available at: <https://development.standards.ieee.org/myproject-web/public/view.html#landing>.

1 Copyrights

2 IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws.
3 They are made available by IEEE and are adopted for a wide variety of both public and private uses. These
4 include both use, by reference, in laws and regulations, and use in private self-regulation, standardization,
5 and the promotion of engineering practices and methods. By making these documents available for use and
6 adoption by public authorities and private users, neither IEEE nor its licensors waive any rights in copyright
7 to the documents.

8 Photocopies

9 Subject to payment of the appropriate licensing fees, IEEE will grant users a limited, non-exclusive license
10 to photocopy portions of any individual standard for company or organizational internal use or individual,
11 non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance
12 Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400;
13 <https://www.copyright.com/>. Permission to photocopy portions of any individual standard for educational
14 classroom use can also be obtained through the Copyright Clearance Center.

15 Updating of IEEE Standards documents

16 Users of IEEE Standards documents should be aware that these documents may be superseded at any time
17 by the issuance of new editions or may be amended from time to time through the issuance of amendments,
18 corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the
19 document together with any amendments, corrigenda, or errata then in effect.

20 Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years
21 old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of
22 some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that
23 they have the latest edition of any IEEE standard.

24 In order to determine whether a given document is the current edition and whether it has been amended
25 through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#).³ For more
26 information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

27 Errata

28 Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#).⁴ Search for standard number
29 and year of approval to access the web page of the published standard. Errata links are located under the
30 Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to
31 periodically check for errata.

32 Patents

33 IEEE Standards are developed in compliance with the [IEEE SA Patent Policy](#).⁵

34 Attention is called to the possibility that implementation of this standard may require use of subject matter
35 covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the
36 existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has
37 filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the
38 IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may
39 indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without
40 compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of
41 any unfair discrimination to applicants desiring to obtain such licenses.

³ Available at: <https://ieeexplore.ieee.org/browse/standards/collection/ieee>.

⁴ Available at: <https://standards.ieee.org/standard/index.html>.

⁵ Available at: <https://standards.ieee.org/about/sasb/patcom/materials.html>.

1 Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not
2 responsible for identifying Essential Patent Claims for which a license may be required, for conducting
3 inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or
4 conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing
5 agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that
6 determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their
7 own responsibility. Further information may be obtained from the IEEE Standards Association.

8 **IMPORTANT NOTICE**

9 IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure
10 against interference with or from other devices or networks. Technologies, application of technologies, and
11 recommended procedures in various industries evolve over time. The IEEE standards development process
12 allows participants to review developments in industries, technologies, and practices, and to determine what,
13 if any, updates should be made to the IEEE standard. During this evolution, the technologies and
14 recommendations in IEEE standards may be implemented in ways not foreseen during the standards
15 development. IEEE Standards development activities consider research and information presented to the
16 standards development group in developing any safety recommendations. Other information about safety
17 practices, changes in technology or technology implementation, or impact by peripheral systems also may
18 be pertinent to safety considerations during implementation of the standard. Implementers and users of IEEE
19 Standards documents are responsible for determining and complying with all appropriate safety, security,
20 environmental, health, data privacy, and interference protection practices and all applicable laws and
21 regulations.

1 Participants

2 <<The following lists will be updated in the usual way prior to publication>>

3 At the time this standard was submitted to the IEEE-SA Standards Board for approval, the IEEE 802.1
4 working group had the following membership:

5
6
7
8
9

Glenn Parsons, *Chair*
Jessy V. Rouyer, *Vice Chair*
Mick Seaman, *Chair, Security Task Group, Editor*
Karen Randall, *Vice Chair, Security Task Group*

SeoYoung Baek
Shenghua Bao
Jens Bierschenk
Steinar Bjornstad
Christian Boiger
Paul Bottorff
David Chen
Feng Chen
Weiying Cheng
Rodney Cummings
János Farkas
Norman Finn
Geoffrey Garner
Eric W. Gray
Craig Gunther
Marina Gutierrez
Stephen Haddock
Mark Hantel
Patrick Heffernan

Marc Holness
Lu Huang
Tony Jeffree
Michael Johas Teener
Hal Keen
Stephan Kehler
Philippe Klein
Jouni Korhonen
Yizhou Li
Christophe Mangin
Tom McBeath
James McIntosh
Tero Mustala
Hiroki Nakano
Bob Noseworthy
Donald R. Pannell
Walter Pienciak
Michael Potts

Karen Randall
Maximilian Riegel
Dan Romascanu
Jessy V. Rouyer
Eero Ryytty
Soheil Samii
Behcet Sarikaya
Frank Schewe
Johannes Specht
Wilfried Steiner
Patricia Thaler
Paul Unbehagen
Hao Wang
Karl Weber
Brian Weis
Jordon Woods
Nader Zein
Helge Zinner
Juan Carlos Zuniga

10 The following members of the individual balloting committee voted on this standard. Balloters may have
11 voted for approval, disapproval, or abstention.

A.N. Other

12 <<The above lists will be updated in the usual way prior to publication>>

13

1

2 When the IEEE-SA Standards Board approved this standard on <dd> <month> <year>, it had the following
3 membership:

4

Jean-Philippe Faure, *Chair*

5

Vacant Position, *Vice-Chair*

6

John D. Kulick, *Past Chair*

7

Konstantinos Karachalios, *Secretary*

Chuck Adams

Michael Janezic

Robby Robson

Masayuki Ariyoshi

Thomas Koshy

Dorothy Stanley

Ted Burse

Joseph L. Koepfinger1

Adrian Stephens

Stephen Dukes

Kevin Lu

Mehmet Ulema

Doug Edwards

Daleep Mohla

Phil Wennblom

J. Travis Griffith

Damir Novosel

Howard Wolfman

Gary Hoffman

Ronald C. Petersen

Yu Yuan

Annette D. Reilly

8

*Member Emeritus

9

<<The above lists will be updated in the usual way prior to publication>>

10

¹ Introduction

²

This introduction is not part of IEEE Std 802.1X™-2020X/Cor1, IEEE Standard for Local and metropolitan area networks—Port-Based Network Access Control — Corrigendum 1.

³ This corrigendum to IEEE Std 802.1X™ corrects the when statement for the augment of the interfaces
⁴ container in the ieee802-dot1x YANG module to avoid limiting the latter's applicability.

1 Contents

2	14.	YANG Data Model	14
3	14.5	Definition of the IEEE 802.1X YANG data model	14
4	14.5.2	ieee802-dot1x-types YANG module definition	14
5	14.5.3	ieee802-dot1x YANG module definition	17

1

2 Draft IEEE Standard for Local and Metropolitan Area Networks— 4 Port-Based Network Access 5 Control—Corrigendum 1

6 [This corrigendum is based on IEEE Std 802.1X™-2020]

7 NOTE—The editing instructions contained in this corrigendum define how to merge the material contained
8 therein into the existing base standard to form the comprehensive standard.

9 The editing instructions are shown in ***bold italics***. Four editing instructions are used: change, delete, insert,
10 and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies
11 the location of the change and describes what is being changed by using ~~strikethrough~~ (to remove old
12 material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material
13 without disturbing the existing material. Deletions and insertions may require renumbering. If so,
14 renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or
15 equations by removing the existing figure or equation and replacing it with a new one. Editing instructions,
16 change markings, and this note will not be carried over into future editions because the changes will be
17 incorporated into the base standard.

1 14. YANG Data Model

2 14.5 Definition of the IEEE 802.1X YANG data model ^{1, 2, 3}

3 14.5.2 ieee802-dot1x-types YANG module definition

4 *Delete the YANG module in 14.5.2.*

5 *Insert the following YANG module in 14.5.2:*

```
6 module ieee802-dot1x-types {
7   yang-version "1.1";
8   namespace "urn:ieee:std:802.1X:yang:ieee802-dot1x-types";
9   prefix "dot1x-types";
10
11   organization
12     "Institute of Electrical and Electronics Engineers";
13
14   contact
15     "WG-URL: http://www.ieee802.org/1
16     WG-EMail: stds-802-1-L@ieee.org
17
18     Contact: IEEE 802.1 Working Group Chair
19     Postal: C/O IEEE 802.1 Working Group
20             IEEE Standards Association
21             445 Hoes Lane
22             Piscataway
23             NJ 08854
24             USA
25
26     E-mail: STDS-802-1-L@LISTSERV.IEEE.ORG";
27
28   description
29     "Port-based network access control allows a network administrator
30     to restrict the use of IEEE 802 LAN service access points (ports)
31     to secure communication between authenticated and authorized
32     devices. IEEE Std 802.1X specifies an architecture, functional
33     elements, and protocols that support mutual authentication
34     between the clients of ports attached to the same LAN and secure
35     communication between the ports. The following control allows a
36     port to be reinitialized, terminating (and potentially
37     restarting) authentication exchanges and MKA operation, based on
38     a data model described in a set of YANG modules.";
39
40   revision 2025-11-20 {
41     description
42       "Added statement to indicate YANG version 1.1";
43     reference
44       "IEEE Std 802.1X-2020, Port-Based Network Access Control.";
45   }
46
47   revision 2020-02-18 {
48     description
49       "Updated Contact information.";
50     reference
51       "IEEE Std 802.1X-2020, Port-Based Network Access Control.";
52   }
53
54   revision 2019-05-28 {
55     description
56       "Updates based upon comment resolution on draft
```

¹ Copyright release for YANG: Users of this standard may freely reproduce the YANG modules contained in this clause so that they can be used for their intended purpose.

² An ASCII version of each YANG module is attached to the PDF of this standard and can also be obtained from the IEEE 802.1 Website at <https://1.ieee802.org/yang-modules/>.

³ References in this standard's YANG module definitions are not clickable, as each module has been incorporated unchanged after development and verification using YANG tools.

```
1      D1.0 of P802.1X-Rev.";
2      reference
3      "IEEE Std 802.1X-2020, Port-Based Network Access Control.";
4  }
5
6  /* -----
7   * Type definitions used by dot1X YANG module
8   * -----
9   */
10
11  typedef pae-nid {
12      type string {
13          length "0..100";
14      }
15      description
16          "Network Identity, which is a UTF-8 string identifying a
17           network or network service.";
18      reference
19          "IEEE 802.1X-2020 Clause 3, Clause 10.1, Clause 12.6";
20  }
21
22  typedef pae-session-user-name {
23      type string {
24          length "0..253";
25      }
26      description
27          "Session user name, which is a UTF-8 string, representing the
28           identity of the peer Supplicant.";
29      reference
30          "IEEE 802.1X-2020 Clause 12.5.1";
31  }
32
33  typedef pae-session-id {
34      type string {
35          length "3..253";
36      }
37      description
38          "Session Identifier, which is a UTF-8 string, uniquely
39           identifying the session within the context of the PAE's
40           system.";
41      reference
42          "IEEE 802.1X-2020 Clause 12.5.1";
43  }
44
45  typedef pae-nid-capabilities {
46      type bits {
47          bit eap {
48              position 0;
49              description
50                  "EAP";
51          }
52          bit eapMka {
53              position 1;
54              description
55                  "EAP + MKA";
56          }
57          bit eapMkaMacSec {
58              position 2;
59              description
60                  "EAP + MKA + MACsec";
61          }
62          bit mka {
63              position 3;
64              description
65                  "MKA";
66          }
67          bit mkaMacSec {
68              position 4;
69              description
70                  "MKA + MACsec";
71          }
72          bit higherLayer {
```

```

1      position 5;
2      description
3          "Higher Layer (WebAuth)";
4      }
5      bit higherLayerFallback {
6          position 6;
7          description
8              "Higher Layer Fallback (WebAuth)";
9      }
10     bit vendorSpecific {
11         position 7;
12         description
13             "Vendor specific authentication mechanisms";
14     }
15 }
16 description
17     "Authentication and protection capabilities supported for the
18     NID. Indicates the combinations of authentication and
19     protection capabilities supported for the NID. Any set of these
20     combinations can be supported.";
21 reference
22     "IEEE 802.1X-2020 Clause 10.1, Clause 11.12.3";
23 }
24
25 typedef pae-access-status {
26     type enumeration {
27         enum no-access {
28             description
29                 "Other than to authentication services, and to services
30                 announced as available in the absence of authentication
31                 (unauthenticated).";
32         }
33         enum remedial-access {
34             description
35                 "The access granted is severely limited, possibly to
36                 remedial services.";
37         }
38         enum restricted-access {
39             description
40                 "The Controlled Port is operational, but restrictions have
41                 been applied by the network that can limit access to some
42                 resources.";
43         }
44         enum expected-access {
45             description
46                 "The Controlled Port is operational, and access provided is
47                 as expected for successful authentication and authorization
48                 for the NID.";
49         }
50     }
51     description
52         "Indicates the transmitter's Controlled Port operational status
53         and current level of access resulting from authentication and
54         the consequent authorization controls applied by that port's
55         clients.";
56     reference
57         "IEEE 802.1X-2020 Clause 10.4, Clause 12.5";
58 }
59
60 typedef mka-kn {
61     type uint32;
62     description
63         "Indicates a Key Number (KN) used in MKA. It is assigned by
64         the Key Server (sequentially beginning with 1).";
65     reference
66         "IEEE 802.1X-2020 Clause 9.8, Clause 9.16";
67 }
68
69 typedef mka-an {
70     type uint32;
71     description
72         "A number that is concatenated with a MACsec Secure Channel

```

```

1     Identifier to identify a Secure Association. Indicates an
2     Association Number (AN) assigned by the Key Server for use with
3     the key number for transmission.";
4     reference
5         "IEEE 802.1X-2020 Clause 9.8, Clause 9.16";
6 }
7
8 typedef pae-ckn {
9     type string {
10         length "1..32";
11     }
12     description
13         "Indicates the CAK name to identify the Connectivity
14         Association Key (CAK) which is the root key in the MACsec Key
15         Agreement key hierarchy. All potential members of the CA use
16         the same CKN.";
17     reference
18         "IEEE 802.1X-2020 Clause 9.3.1, Clause 6.2";
19 }
20
21 typedef pae-kmd {
22     type string {
23         length "0..253";
24     }
25     description
26         "A Key Management Domain (KMD). A string of up to 253 UTF-8
27         characters that names the transmitting authenticator's key
28         management domain.";
29     reference
30         "IEEE Clause 12.6";
31 }
32
33 typedef pae-auth-data {
34     type string;
35     description
36         "Authorization data associated with the CAK.";
37     reference
38         "IEEE 802.1X-2020 Clause 9.16";
39 }
40
41 typedef sci-list-entry {
42     type string {
43         length "8";
44     }
45     description
46         "8 octet string, where the first 6 octets represents the MAC
47         Address (in canonical format), and the next 2 octets represents
48         the Port Identifier.";
49     reference
50         "IEEE 802.1AE Clause 7.1.2, Clause 10.7.1";
51 }
52
53 typedef pae-if-index {
54     type int32 {
55         range "1..2147483647";
56     }
57     description
58         "The interface index value represented by this interface.";
59 }
60
61 } // ieee802-dot1x-types
62
63

```

64 14.5.3 ieee802-dot1x YANG module definition

65 *Delete the YANG module in 14.5.3.*

66 *Insert the following YANG module in 14.5.3:*

```

67 module ieee802-dot1x {
68     yang-version "1.1";

```

```
1 namespace "urn:ieee:std:802.1X:yang:ieee802-dot1x";
2 prefix "dot1x";
3
4 import ieee802-types { prefix "ieee"; }
5 import ietf-yang-types { prefix "yang"; }
6 import ietf-interfaces { prefix "if"; }
7 import ietf-system { prefix "sys"; }
8 import iana-if-type { prefix "ianaift"; }
9 import ieee802-dot1x-types { prefix "dot1x-types"; }
10
11 organization
12   "Institute of Electrical and Electronics Engineers";
13
14 contact
15   "WG-URL: http://www.ieee802.org/1
16   WG-EMail: stds-802-1-L@ieee.org
17
18   Contact: IEEE 802.1 Working Group Chair
19   Postal: C/O IEEE 802.1 Working Group
20           IEEE Standards Association
21           445 Hoes Lane
22           Piscataway
23           NJ 08854
24           USA
25
26   E-mail: STDS-802-1-L@LISTSERV.IEEE.ORG";
27
28 description
29   "Port-based network access control allows a network administrator
30   to restrict the use of IEEE 802 LAN service access points (ports)
31   to secure communication between authenticated and authorized
32   devices. IEEE Std 802.1X specifies an architecture, functional
33   elements, and protocols that support mutual authentication
34   between the clients of ports attached to the same LAN and secure
35   communication between the ports. The following control allows a
36   port to be reinitialized, terminating (and potentially
37   restarting) authentication exchanges and MKA operation, based on
38   a data model described in a set of YANG modules.";
39
40 revision 2025-11-20 {
41   description
42     "Added derived-from-or-self function to the when statement
43     for the augment of the interfaces container.";
44   reference
45     "IEEE Std 802.1X-2020, Port-Based Network Access Control.";
46 }
47
48 revision 2020-02-18 {
49   description
50     "Updated Contact information.";
51   reference
52     "IEEE Std 802.1X-2020, Port-Based Network Access Control.";
53 }
54
55 revision 2019-06-12 {
56   description
57     "Updates based on comment resolution of the WG ballot of
58     P802.1X-Rev/D1.0.";
59   reference
60     "IEEE Std 802.1X-2020, Port-Based Network Access Control.";
61 }
62
63 grouping nid-group {
64   description
65     "The PAE NID Group configuration and operational information.";
66   list pae-nid-group {
67     key "nid";
68     description
69       "A list that contains the configuration and operational
70       nodes for the network announcement information for the
71       Logon Process.";
72     leaf nid {
```

```

1      type dot1x-types:pae-nid;
2      description
3          "Identification of the network or network service.";
4      reference
5          "IEEE 802.1X-2020 Clause 12.5";
6  }
7  leaf use-eap {
8      type enumeration {
9          enum never {
10             description
11                 "Never.";
12             }
13          enum immediate {
14             description
15                 "Immediately, concurrently with the use of MKA with any
16                 cached CAK(s).";
17             }
18          enum mka-fail {
19             description
20                 "Not until MKA has failed, if a prior CAK has been
21                 cached.";
22             }
23          }
24      default "immediate";
25      description
26          "Determines when the Logon Process will initiate EAP, if
27          the Supplicant and or Authenticator are enabled, and takes
28          one of the above values.";
29      reference
30          "IEEE 802.1X-2020 Clause 12.5";
31  }
32  leaf unauth-allowed {
33      type enumeration {
34          enum never {
35             description
36                 "Never.";
37             }
38          enum immediate {
39             description
40                 "Immediately, independently of any current or future
41                 attempts to authenticate using the PAE or MKA.";
42             }
43          enum auth-fail {
44             description
45                 "Not until an attempt has been made to authenticate
46                 using EAP, unless neither the supplicant nor the
47                 authenticator is enabled, and MKA has attempted to use
48                 any cached CAK (unless the KaY is not enabled).";
49             }
50          }
51      default "immediate";
52      description
53          "Determines when the Logon Process will tell the CP state
54          machine to provide unauthenticated connectivity, and takes
55          one of the above values.";
56      reference
57          "IEEE 802.1X-2020 Clause 12.5";
58  }
59  leaf unsecure-allowed {
60      type enumeration {
61          enum never {
62             description
63                 "Never.";
64             }
65          enum immediate {
66             description
67                 "Immediately, to provide connectivity concurrently with
68                 the use of MKA with any CAK acquired through EAP.";
69             }
70          enum mka-fail {
71             description
72                 "Not until MKA has failed, or is not enabled.";

```

```

1      }
2      enum mka-server {
3          description
4              "Only if directed by the MKA server.";
5      }
6  }
7  default "immediate";
8  description
9      "Determines when the Logon Process will tell the CP state
10     machine to provide authenticated but unsecured
11     connectivity, takes one of the above values.";
12  reference
13      "IEEE 802.1X-2020 Clause 12.5";
14  }
15  leaf unauthenticated-access {
16      type enumeration {
17          enum no-access {
18              description
19                  "Other than to authentication services.";
20          }
21          enum fallback-access {
22              description
23                  "Limited access can be provided after authentication
24                  failure.";
25          }
26          enum limited-access {
27              description
28                  "Immediate limited access is available without
29                  authentication.";
30          }
31          enum open-access {
32              description
33                  "Immediate access is available without
34                  authentication.";
35          }
36      }
37      default "no-access";
38      description
39          "Unauthenticated access capabilities provided by the NID.";
40      reference
41          "IEEE 802.1X-2020 Clause 10.1";
42  }
43  leaf access-capabilities {
44      type dot1x-types:pae-nid-capabilities;
45      description
46          "Authentication and protection capabilities supported for
47          the NID.";
48      reference
49          "IEEE 802.1X-2020 Clause 10.1";
50  }
51
52  leaf kmd {
53      type dot1x-types:pae-kmd;
54      config false;
55      description
56          "The Key Management Domain for the NID.";
57      reference
58          "IEEE 802.1X-2020 Clause 10.4";
59  }
60  }
61  }
62
63  grouping port-capabilities {
64      description
65          "Per port PAE feature capabilities.";
66      leaf supp {
67          type boolean;
68          description
69              "Indicates if PACP EAP Supplicant is supported.";
70          reference
71              "IEEE 802.1X-2020 Clause 12.9.2";
72      }

```

```

1   leaf auth {
2       type boolean;
3       description
4           "Indicates if PACP EAP Authenticator is supported.";
5       reference
6           "IEEE 802.1X-2020 Clause 12.9.2";
7   }
8   leaf mka {
9       type boolean;
10      description
11          "Indicates if MKA is supported.";
12      reference
13          "IEEE 802.1X-2020 Clause 12.9.2";
14  }
15  leaf macsec {
16      type boolean;
17      description
18          "Indicates if MACsec on the Controlled port is supported.";
19      reference
20          "IEEE 802.1X-2020 Clause 12.9.2";
21  }
22  leaf announcements {
23      type boolean;
24      description
25          "Indicates if the ability to send EAPOL announcements is
26          supported.";
27      reference
28          "IEEE 802.1X-2020 Clause 12.9.2";
29  }
30  leaf listener {
31      type boolean;
32      description
33          "Indicates if the ability to use received EAPOL
34          announcements is supported.";
35      reference
36          "IEEE 802.1X-2020 Clause 12.9.2";
37  }
38  leaf virtual-ports {
39      type boolean;
40      description
41          "Indicates if virtual ports for a real port is supported.";
42      reference
43          "IEEE 802.1X-2020 Clause 12.9.2";
44  }
45  leaf in-service-upgrades {
46      type boolean;
47      description
48          "Indicates if MKA in-service upgrades is supported.";
49      reference
50          "IEEE 802.1X-2020 Clause 12.9.2";
51  }
52  }
53
54  /* -----
55  * Configuration objects used by 802.1X YANG module
56  * -----
57  */
58  augment "/sys:system" {
59      description
60          "Augment system with 802.1X PAE System specific configuration
61          nodes.";
62      container pae-system {
63          description
64              "Contains all 802.1X PAE System specific related
65              configuration and operational data.";
66          leaf name {
67              type string {
68                  length "1..255";
69              }
70          description
71              "The name which uniquely identifies the PAE System.";
72      }

```

```

1     leaf system-access-control {
2         type enumeration {
3             enum disabled {
4                 description
5                     "Deletes any virtual ports previously instantiated, and
6                     terminates authentication exchanges and MKA
7                     operation."";
8             }
9             enum enabled {
10                description
11                    "Enables PAE system access control."";
12            }
13        }
14        description
15            "Setting this control to disabled deletes any virtual ports
16            previously instantiated, and terminates authentication
17            exchanges and MKA operation. Each real port PAE behaves as
18            if enabledVirtualPorts was clear, the PAEs Supplicant,
19            Authenticator, and KaY as if their enabled controls were
20            clear, and Logon Process(es) as if unauthAllowed was
21            Immediate. Announcements can be transmitted (subject to
22            other controls), both periodically and in response to
23            announcement requests (conveyed by EAPOL-Starts or
24            EAPOL-Announcement-Reqs) but are sent with a single NID
25            Set, with a null NID, and the Access Information TLV (and
26            no other) with an pae-access-status of No Access,
27            accessRequested false, OpenAccess, and no
28            accessCapabilities. The control variable settings for each
29            real port PAE are unaffected, and will be used once
30            systemAccessControl is set to enabled."";
31        reference
32            "IEEE 802.1X-2020 Clause 12.9.1";
33    }
34    leaf system-announcements {
35        type enumeration {
36            enum disabled {
37                description
38                    "Causes each PAE to behave as if enabled were clear
39                    for the PAE's Announcement functionality."";
40            }
41            enum enabled {
42                description
43                    "Enables PAE system announcements."";
44            }
45        }
46        description
47            "Setting this control to Disabled causes each PAE to behave
48            as if enabled were clear for the PAE's Announcement
49            functionality. The independent controls for each PAE apply
50            if systemAnnouncements is Enabled."";
51        reference
52            "IEEE 802.1X-2020 Clause 12.9.1";
53    }
54    leaf eapol-protocol-version {
55        type uint8;
56        config false;
57        description
58            "The EAPOL protocol version for this system."";
59        reference
60            "IEEE 802.1X-2020 Clause 12.9.1, Clause 11.3";
61    }
62    leaf mka-version {
63        type uint8;
64        config false;
65        description
66            "The MKA protocol version for this system."";
67        reference
68            "IEEE 802.1X-2020 Clause 12.9.1, Clause 11.3";
69    }
70    leaf-list pae {
71        type if:interface-ref;
72        config false;

```

```

1      description
2        "List of PAE references.";
3    }
4  }
5  }
6
7  /*
8   * Port Authentication Entity (PAE) Nodes
9   */
10 augment "/if:interfaces/if:interface" {
11   when "derived-from-or-self(if:type,'ianaift:ethernetCsmacd') or " +
12     "derived-from-or-self(if:type,'ianaift:ilan') or " +
13     "derived-from-or-self(if:type,'ianaift:macSecControlledIF') or " +
14     "derived-from-or-self(if:type,'ianaift:ptm') or " +
15     "derived-from-or-self(if:type,'ianaift:bridge')" {
16     description
17       "Applies to the Controlled Port of SecY or PAC shim or
18       Ethernet related Interface.";
19   }
20   description
21     "Augment interface model with PAE configuration and
22     operational nodes.";
23   reference
24     "IEEE 802.1AE Clause 11.7 and IEEE 802.1X-2020 Clause 6.5 and
25     Clause 13.3.2";
26   container pae {
27     description
28       "Contains PAE configuration and operational related nodes.";
29     leaf pae-system {
30       type leafref {
31         path "/sys:system/dot1x:pae-system/dot1x:name";
32       }
33       description
34         "The PAE system that this PAE is a member of.";
35     }
36     leaf vp-enable {
37       when "../port-type = 'real-port' and
38         ../port-capabilities/virtual-ports = 'true'" {
39         description
40           "Applies when port is Real Port and virtual port
41           capabilities are supported.";
42       }
43       type boolean;
44       default "false";
45       description
46         "A real port's PAE may be configured to create virtual
47         ports to support multi-access LANs provided that MKA and
48         MACsec operation is enabled for that port.";
49       reference
50         "IEEE 802.1X-2020 Clause 12.7";
51     }
52     container port-capabilities {
53       description
54         "Per port PAE feature capabilities.";
55       uses port-capabilities;
56     }
57
58     leaf port-name {
59       type if:interface-ref;
60       config false;
61       description
62         "Each PAE is uniquely identified by a port name.";
63     }
64     leaf port-number {
65       type dot1x-types:pae-if-index;
66       config false;
67       description
68         "Each PAE is uniquely identified by a port number. The
69         port number used is unique amongst all port names for the
70         system, and directly or indirectly identifies the
71         Uncontrolled Port that supports the PAE. If the PAE has
72         been dynamically instantiated to support an existing or

```

```

1      potential virtual port, this portNumber, the
2      uncontrolledPortNumber and the controlledPortNumber are
3      allocated by the real ports PAE, and this portNumber is the
4      uncontrolledPortNumber. If the PAE supports a real port,
5      this portNumber is the commonPortNumber for the associated
6      PAC or SecY."";
7      reference
8      "IEEE 802.1X-2020 Clause 12.9.2";
9  }
10 leaf controlled-port-name {
11     type if:interface-ref;
12     config false;
13     description
14         "Each PAE is uniquely identified by a port name.";
15 }
16 leaf controlled-port-number {
17     type dot1x-types:paef-if-index;
18     config false;
19     description
20         "The port for the associated PAC or SecYs Controlled
21         Port.";
22     reference
23         "IEEE 802.1X-2020 Clause 12.9.2";
24 }
25 leaf uncontrolled-port-name {
26     type if:interface-ref;
27     config false;
28     description
29         "The uncontrolled port name reference.";
30 }
31 leaf uncontrolled-port-number {
32     type dot1x-types:paef-if-index;
33     config false;
34     description
35         "The port for the associated PAC or SecYs Uncontrolled
36         Port.";
37     reference
38         "IEEE 802.1X-2020 Clause 12.9.2";
39 }
40 leaf common-port-name {
41     type if:interface-ref;
42     config false;
43     description
44         "The common port name reference.";
45 }
46 leaf common-port-number {
47     type dot1x-types:paef-if-index;
48     config false;
49     description
50         "The port for the associated PAC or SecYs Common Port. All
51         the virtual ports created for a given real port share the
52         same Common Port and commonPortNumber.";
53     reference
54         "IEEE 802.1X-2020 Clause 12.9.2";
55 }
56 leaf port-type {
57     type enumeration {
58         enum real-port {
59             description
60                 "Real Port type.";
61         }
62         enum virtual-port {
63             description
64                 "Virtual Port type.";
65         }
66     }
67     //config false;
68     description
69         "The port type of the PAE.";
70     reference
71         "IEEE 802.1X-2020 Clause 12.9.2";
72 }

```

```

1     container virtual-port {
2         when "../port-capabilities/virtual-ports = 'true'" {
3             description
4                 "Applies when the virtual ports port capability is
5                 supported.";
6         }
7         config false;
8         description
9             "Contains Virtual Port operational state information.";
10        leaf max {
11            when "../port-type = 'real-port'" {
12                description
13                    "Applies when Port is a Real Port.";
14            }
15            type uint32;
16            description
17                "The guaranteed maximum number of virtual ports.";
18            reference
19                "IEEE 802.1X-2020 Clause 12.9.2";
20        }
21        leaf current {
22            when "../port-type = 'real-port'" {
23                description
24                    "Applies when Port is a Real Port.";
25            }
26            type yang:gauge32;
27            description
28                "The current number of virtual ports.";
29            reference
30                "IEEE 802.1X-2020 Clause 12.9.2";
31        }
32        leaf start {
33            when "../port-type = 'virtual-port'" {
34                description
35                    "Applies when Port is a Virtual Port.";
36            }
37            type boolean;
38            description
39                "Set if the virtual port was created by receipt of an
40                EAPOL-Start frame.";
41            reference
42                "IEEE 802.1X-2020 Clause 12.9.7";
43        }
44        leaf peer-address {
45            when "../port-type = 'virtual-port'" {
46                description
47                    "Applies when Port is a Virtual Port.";
48            }
49            type ieee:mac-address;
50            description
51                "The source MAC Address of the EAPOL-Start (if vpStart is
52                set).";
53            reference
54                "IEEE 802.1X-2020 Clause 12.9.7";
55        }
56    }
57
58    container supplicant {
59        when "../port-type = 'real-port' and
60            ../port-capabilities/supp = 'true'" {
61            description
62                "Applies to Real Port when supplicant port capabilities
63                are supported.";
64        }
65        description
66            "Contains the configuration nodes for the Supplicant PAE
67            associated with each port.";
68        leaf held-period {
69            type uint16;
70            units seconds;
71            default "60";
72            description

```

```

1         "The initial value of the timer used to impose a wait
2         period after a failed authentication attempt, before
3         another attempt is permitted.";
4     reference
5         "IEEE 802.1X-2020 Clause 8.6";
6 }
7 leaf retry-max {
8     type uint32;
9     default "2";
10    description
11        "Specifies the maximum number of re-authentication
12        attempts on an authenticator port before port is
13        unauthorized.";
14    reference
15        "IEEE 802.1X-2020 Clause 8.7";
16 }
17
18 leaf enabled {
19     type boolean;
20     config false;
21     description
22         "Set by PACP if the PAE can provide authentication. Will
23         be FALSE if the Port is not enabled, if the functionality
24         provided by the PAE is not available, or not implemented,
25         or the control variable enable has been cleared by
26         management, e.g. because the application scenario
27         authenticates a user and there is no user logged on.";
28     reference
29         "IEEE 802.1X-2020 Clause 8.4";
30 }
31 leaf authenticate {
32     type boolean;
33     config false;
34     description
35         "Set by the PAE client to request authentication, and
36         allows reauthentication while set. Cleared by the client
37         to revoke authentication. To enable authentication the
38         client also needs to clear failed (if set).";
39     reference
40         "IEEE 802.1X-2020 Clause 8.4";
41 }
42 leaf authenticated {
43     type boolean;
44     config false;
45     description
46         "Set by PACP if the PAE is currently authenticated, and
47         cleared if the authentication fails or is revoked.";
48     reference
49         "IEEE 802.1X-2020 Clause 8.4";
50 }
51 leaf failed {
52     type boolean;
53     config false;
54     description
55         "Set by PACP if the authentication has failed or has been
56         terminated. The cause could be a Fail returned by EAP,
57         either immediately or following a reauthentication, an
58         excessive number of attempts to authenticate (either
59         immediately or upon reauthentication), or the client
60         deasserting authenticate. The PACP will clear
61         authenticated as well as setting failed. Any ongoing
62         authentication exchange will be terminated (by the state
63         machines) if enable becomes FALSE and enabled will be
64         cleared, but failed will not be set.";
65     reference
66         "IEEE 802.1X-2020 Clause 8.4";
67 }
68 }
69
70 container authenticator {
71     when "../port-capabilities/auth = 'true'" {
72         description

```

```

1         "Applies when the Authenticator is supported.";
2     }
3     description
4         "Contains configuration nodes for the Authenticator PAE
5         associated with each port.";
6     leaf quiet-period {
7         type uint16;
8         units seconds;
9         default "60";
10        description
11            "Number of seconds that the authenticator remains in the quiet
12            state following a failed authentication exchange with the
13            supplicant.";
14        reference
15            "IEEE 802.1X-2020 Clause 8.6, Figure 12-3";
16    }
17    leaf reauth-period {
18        type uint32;
19        units seconds;
20        default "3600";
21        description
22            "This object indicates the time period of the
23            reauthentication to the supplicant.";
24        reference
25            "IEEE 802.1X-2020 Clause 8.6, Figure 12-3";
26    }
27    leaf reauth-enable {
28        type boolean;
29        default "false";
30        description
31            "Re-authentication is enabled or not.";
32        reference
33            "IEEE 802.1X-2020 Clause 5.8 and 8.9";
34    }
35    leaf retry-max {
36        type uint32;
37        default "2";
38        description
39            "Specifies the maximum number of re-authentication
40            attempts on an authenticator port before port is
41            unauthorized.";
42        reference
43            "IEEE 802.1X-2020 Clause 8.9";
44    }
45
46    leaf enabled {
47        type boolean;
48        config false;
49        description
50            "Set by PACP if the PAE can provide authentication. Will
51            be FALSE if the Port is not enabled, if the functionality
52            provided by the PAE is not available, or not implemented,
53            or the control variable enable has been cleared by
54            management, e.g. because the application scenario
55            authenticates a user and there is no user logged on.";
56        reference
57            "IEEE 802.1X-2020 Clause 8.4";
58    }
59    leaf authenticate {
60        type boolean;
61        config false;
62        description
63            "Set by the PAE client to request authentication, and
64            allows reauthentication while set. Cleared by the client
65            to revoke authentication. To enable authentication the
66            client also needs to clear failed (if set).";
67        reference
68            "IEEE 802.1X-2020 Clause 8.4";
69    }
70    leaf authenticated {
71        type boolean;
72        config false;

```

```

1      description
2          "Set by PACP if the PAE is currently authenticated, and
3          cleared if the authentication fails or is revoked.";
4      reference
5          "IEEE 802.1X-2020 Clause 8.4";
6  }
7  leaf failed {
8      type boolean;
9      config false;
10     description
11         "Set by PACP if the authentication has failed or has been
12         terminated. The cause could be a Fail returned by EAP,
13         either immediately or following a reauthentication, an
14         excessive number of attempts to authenticate (either
15         immediately or upon reauthentication), or the client
16         deasserting authenticate. The PACP will clear
17         authenticated as well as setting failed. Any ongoing
18         authentication exchange will be terminated (by the state
19         machines) if enable becomes FALSE and enabled will be
20         cleared, but failed will not be set.";
21     reference
22         "IEEE 802.1X-2020 Clause 8.4";
23 }
24 }
25
26 container kay {
27     when "../port-capabilities/mka = 'true'" {
28         description
29             "Applies when the MKA port capability is supported.";
30     }
31     description
32         "Contains configuration system level information for each
33         Interface supported by the KaY (Key Agreement Entity).";
34     leaf enable {
35         type boolean;
36         default "false";
37         description
38             "Set by management to enable (clear to disable) the use
39             of MKA.";
40         reference
41             "IEEE 802.1X-2020 Clause 9.16";
42     }
43     container actor {
44         description
45             "Contains configuration and operational nodes
46             associated with the actor";
47         leaf priority {
48             type uint8;
49             description
50                 "The Key Server Priority for all the ports actors.";
51             reference
52                 "IEEE 802.1X-2020 Clause 9.16";
53         }
54         leaf sci {
55             type dot1x-types:sci-list-entry;
56             config false;
57             description
58                 "The SCI assigned by the system to the port (applies
59                 to all the ports actors).";
60             reference
61                 "IEEE 802.1X-2020 Clause 9.16";
62         }
63     }
64     container key-server {
65         description
66             "Contains configuration and operational nodes
67             associated with the key
68             server.";
69         leaf priority {
70             type uint8;
71             description
72                 "The Key Server Priority for the Key Server for the

```

```

1         principal actor. Matches the actorPriority if the
2         actor is the Key Server";
3     reference
4         "IEEE 802.1X-2020 Clause 9.16";
5 }
6 leaf sci {
7     type dot1x-types:sci-list-entry;
8     config false;
9     description
10        "The SCI for Key Server for the principal actor. Null
11        if there is no principal actor, or that actor has no
12        live peers. Matches the actorSCI if the actor is the
13        Key Server.";
14    reference
15        "IEEE 802.1X-2020 Clause 9.16";
16 }
17 }
18 container group {
19     description
20        "Contains configuration nodes associated with the
21        group.";
22     leaf join {
23         type boolean;
24         default "true";
25         description
26            "Set if the KaY will accept Group CAKs distributed by
27            MKA.";
28         reference
29            "IEEE 802.1X-2020 Clause 9.16";
30     }
31     leaf form {
32         type boolean;
33         default "false";
34         description
35            "Set if the KaY will attempt to use point-to-point CAs
36            to distribute a Group CAK, if its principal actor is
37            the Key Server for all the point-to-point CAs.";
38         reference
39            "IEEE 802.1X-2020 Clause 9.16";
40     }
41     leaf new {
42         type boolean;
43         default "false";
44         description
45            "Set by management if a new Group CAK is to be
46            distributed, if the principal actor is the Key Server
47            for all point-to-point CAs. Cleared by the KaY when
48            distribution is complete.";
49         reference
50            "IEEE 802.1X-2020 Clause 9.16";
51     }
52 }
53
54 container macsec {
55     when "../port-capabilities/macsec = 'true'" {
56         description
57            "Applies when the MACsec port capability is
58            supported.";
59     }
60     description
61        "Contains configuration and operational nodes
62        associated with macsec.";
63     leaf capable {
64         type boolean;
65         description
66            "Set if MACsec is implemented.";
67         reference
68            "IEEE 802.1X-2020 Clause 9.16";
69     }
70     leaf desired {
71         type boolean;
72         default "true";

```

```

1      description
2      "Set if the participant desires MACsec frame protection.";
3      reference
4      "IEEE 802.1X-2020 Clause 9.16";
5  }
6
7  leaf protect {
8      type boolean;
9      config false;
10     description
11     "As used by the CP state machine, see 12.4.";
12     reference
13     "IEEE 802.1X-2020 Clause 9.16";
14 }
15 leaf validate {
16     type boolean;
17     config false;
18     description
19     "As used by the CP state machine, see 12.4.";
20     reference
21     "IEEE 802.1X-2020 Clause 9.16";
22 }
23 leaf replay-protect {
24     type boolean;
25     config false;
26     description
27     "As used by the CP state machine, see 12.4.";
28     reference
29     "IEEE 802.1X-2020 Clause 9.16";
30 }
31 }
32 leaf suspend-on-request {
33     type boolean;
34     default "true";
35     description
36     "Set by management to allow the KaYs principal actor to
37     initiate a suspension if it is the Key Server and another
38     participant has requested a suspension.";
39 }
40 leaf suspend-for {
41     type uint8;
42     default "0";
43     description
44     "Set by management to a non-zero number of seconds
45     between 1 and MKA Suspension Limit to initiate a
46     suspension (9.18) of that duration (if the KaYs principal
47     actor is the Key Server) or to request a suspension
48     (otherwise).";
49     reference
50     "IEEE 802.1X-2020 Clause 9.18";
51 }
52
53 leaf suspended-while {
54     type uint8;
55     config false;
56     description
57     "Read by management to determine if a suspension is in
58     progress and (when available) to discover the remaining
59     duration of that suspension";
60     reference
61     "IEEE 802.1X-2020 Clause 9.18";
62 }
63 leaf active {
64     type boolean;
65     config false;
66     description
67     "Set if there is at least one active actor, transmitting
68     MKPDUs.";
69     reference
70     "IEEE 802.1X-2020 Clause 9.16";
71 }
72 leaf authenticated {

```

```

1      type boolean;
2      config false;
3      description
4          "Set if the principal actor, i.e. the participant that
5          has the highest priority Key Server and one or more live
6          peers, has determined that Controlled Port communication
7          should proceed without MACsec.";
8      reference
9          "IEEE 802.1X-2020 Clause 9.16";
10     }
11     leaf secured {
12         type boolean;
13         config false;
14         description
15             "Set if the principal actor has determined that
16             communication should use MACsec.";
17         reference
18             "IEEE 802.1X-2020 Clause 9.16";
19     }
20     leaf failed {
21         type boolean;
22         config false;
23         description
24             "Cleared when authenticated or secured are set, set if
25             the latter are clear and MKA Life Time has elapsed since
26             an MKA participant was last created.";
27         reference
28             "IEEE 802.1X-2020 Clause 9.16";
29     }
30     container key-number {
31         config false;
32         description
33             "Contains operation state nodes for Key Numbers.";
34         leaf tx {
35             type dot1x-types:mka-kn;
36             description
37                 "The Key Number assigned by the Key Server to the SAK
38                 currently being used for transmission. Null if MACsec
39                 is not being used.";
40             reference
41                 "IEEE 802.1X-2020 Clause 9.16";
42         }
43         leaf rx {
44             type dot1x-types:mka-kn;
45             description
46                 "The Key Number assigned by the Key Server to the
47                 oldest SAK currently being used for reception. The same
48                 as txKN if a single SAK is currently in use (as will
49                 most often be the case). Null if MACsec is not being
50                 used.";
51             reference
52                 "IEEE 802.1X-2020 Clause 9.16";
53         }
54     }
55     container association-number {
56         config false;
57         description
58             "Contains operation state nodes for Association
59             Numbers.";
60         leaf tx {
61             type dot1x-types:mka-an;
62             description
63                 "The Association Number assigned by the Key Server for
64                 use with txKN. Zero if MACsec is not in use.";
65             reference
66                 "IEEE 802.1X-2020 Clause 9.16";
67         }
68         leaf rx {
69             type dot1x-types:mka-an;
70             description
71                 "The Association Number assigned by the Key Server for
72                 use with rxKN. The same as txAN if a single SAK is

```

```

1         currently in use. Zero if MACsec is not in use.";
2     reference
3         "IEEE 802.1X-2020 Clause 9.16";
4     }
5 }
6
7 list participants {
8     key "participant";
9     description
10        "Contains list of configuration and operational nodes
11        for each MKA participant supported by the KaY MKA
12        entity.";
13     leaf participant {
14         type uint32;
15         description
16             "Key into Participants list.";
17     }
18     leaf cached {
19         type boolean;
20         description
21             "Set by the KaY if the participants parameters are
22             cached. If set, cached can be cleared by management to
23             remove the participant from the cache.";
24     }
25     leaf active {
26         type boolean;
27         default "false";
28         description
29             "Set if the participant is active, i.e., is currently
30             transmitting periodic MKPDUs.";
31         reference
32             "IEEE 802.1X-2020 Clause 9.16";
33     }
34     leaf retain {
35         type boolean;
36         default "false";
37         description
38             "Set by management to retain the participant in the
39             cache, even if the KaY would normally remove it (due to
40             lack of use for example).";
41         reference
42             "IEEE 802.1X-2020 Clause 9.16";
43     }
44     leaf activate {
45         type enumeration {
46             enum default {
47                 description
48                     "The participant is from cached entries created by
49                     the KaY as part of normal operation, without
50                     explicit management, and is activated according to
51                     the implementation dependent policies of the KaY.";
52             }
53             enum disabled {
54                 description
55                     "The participant allows the cache information to be
56                     retained, but disabled for indefinite period.";
57             }
58             enum on-oper-up {
59                 description
60                     "Causing the participant to be activated when the
61                     PAEs part is activated, and therefore when the SecY
62                     or PACs Common Port becomes operational.";
63             }
64             enum always {
65                 description
66                     "Causing the participant to remain active all the
67                     time, even in the continued absence of partners.";
68             }
69         }
70         default "default";
71         description
72             "Controls when the participant is activated. Cached

```

```

1         entries created by the KaY as part of normal operation,
2         without explicit management, have the value Default,
3         and are activated according to the implementation
4         dependent policies of the KaY. This variable can be
5         set to any of its values by management. Disabled allows
6         the cache entry to be retained, but disabled for an
7         indefinite period. OnOperUp causes the participant to
8         be activated when the PAEs port (and therefore when the
9         SecY or PACs Common Port becomes MAC_Operational).
10        Always causes the participant to remain active all the
11        time, even in the continued absence of partners. If the
12        value is changed to Disabled or OnOperUp, the
13        participant ceases operation immediately and receipt of
14        MKPDUs with a matching CKN during a subsequent period
15        of twice MKA Life Time will not cause the participant
16        to become active once more.";
17        reference
18        "IEEE 802.1X-2020 Clause 9.16";
19    }
20
21    container peers {
22        config false;
23        description
24        "Contains operational state nodes associated with the
25        Peers.";
26        leaf-list live {
27            type dot1x-types:sci-list-entry;
28            description
29            "A list of the SCIs of the participants live
30            peers.";
31            reference
32            "IEEE 802.1X-2020 Clause 9.16";
33        }
34        leaf-list potential {
35            type dot1x-types:sci-list-entry;
36            description
37            "A list of the SCIs of the participants potential
38            peers.";
39            reference
40            "IEEE 802.1X-2020 Clause 9.16";
41        }
42    }
43    leaf ckn {
44        type dot1x-types:pae-ckn;
45        config false;
46        description
47        "The secure Connectivity Association Key Name for the
48        participant.";
49        reference
50        "IEEE 802.1X-2020 Clause 9.16";
51    }
52    leaf kmd {
53        type dot1x-types:pae-kmd;
54        config false;
55        description
56        "The Key Management Domain for the participant.";
57        reference
58        "IEEE 802.1X-2020 Clause 9.16";
59    }
60    leaf nid {
61        type dot1x-types:pae-nid;
62        config false;
63        description
64        "The NID for the participant.";
65        reference
66        "IEEE 802.1X-2020 Clause 9.16";
67    }
68    leaf auth-data {
69        type dot1x-types:pae-auth-data;
70        config false;
71        description
72        "Authorization data associated with the secure

```

```

1         Connectivity Association Key.";
2     reference
3         "IEEE 802.1X-2020 Clause 9.16";
4     }
5     leaf principal {
6         type boolean;
7         config false;
8         description
9             "Set if the participant is currently the principal
10            actor.";
11        reference
12            "IEEE 802.1X-2020 Clause 9.16";
13    }
14    leaf dist-ckn {
15        type dot1x-types:pae-ckn;
16        config false;
17        description
18            "The CKN for the last CAK distributed (either by the
19            actor or one of its partners). Null if this participant
20            has not been used to distribute a CAK.";
21        reference
22            "IEEE 802.1X-2020 Clause 9.16";
23    }
24    }
25    }
26
27    container logon-nid {
28        description
29            "Contains the configuration and operational related NID
30            information for the Logon Process. The Logon Process may
31            use Network Identifiers (NIDs) to manage its use of
32            authentication credentials, cached CAKs, and
33            announcements.";
34        leaf selected {
35            type dot1x-types:pae-nid;
36            description
37                "The NID currently configured for use by an access
38                controlled port when transmitting EAPOL-Start frames.
39                Defaults to the null NID.";
40            reference
41                "IEEE 802.1X-2020 Clause 12.5";
42        }
43        uses nid-group;
44
45        leaf connected {
46            type dot1x-types:pae-nid;
47            config false;
48            description
49                "The NID associated with the current connectivity
50                (possibly unauthenticated) provided by the operation of
51                the CP state machine.";
52            reference
53                "IEEE 802.1X-2020 Clause 12.5";
54        }
55        leaf requested {
56            type dot1x-types:pae-nid;
57            config false;
58            description
59                "The NID marked as Access requested in announcements, as
60                determined from EAPOL-Start frames. Defaults to the
61                selectedNID.";
62            reference
63                "IEEE 802.1X-2020 Clause 12.5";
64        }
65    }
66
67    container announcer {
68        when "../port-capabilities/announcements = 'true'" {
69            description
70                "Applies when the Announcements port capabilities are
71                supported.";
72        }

```

```

1      description
2          "Contains the configuration related Announcer
3          information.";
4      leaf enable {
5          type boolean;
6          default "false";
7          description
8              "A boolean indicating if the announcer is enabled or
9              not.";
10         reference
11             "IEEE 802.1X-2020 Clause 10.4";
12     }
13     list announce {
14         key "announces";
15         description
16             "Contains the configuration related status information
17             that the Announcers announce in the network announcement
18             of the PAE system.";
19         leaf announces {
20             type uint32;
21             description
22                 "Key into Announce list.";
23         }
24         uses nid-group;
25
26         leaf nid {
27             type dot1x-types:paе-nid;
28             config false;
29             description
30                 "The NID information to identify a received network
31                 announcement for the PAE.";
32             reference
33                 "IEEE 802.1X-2020 Clause 10.4";
34         }
35         leaf access-status {
36             type dot1x-types:paе-access-status;
37             config false;
38             description
39                 "Access Status reflects connectivity as a result of
40                 authentication attempts, and might be set directly by
41                 the system or configured by AAA protocols.";
42             reference
43                 "IEEE 802.1X-2020 Clause 10.4, Clause 12.5";
44         }
45     }
46 }
47
48 container listener {
49     when "../port-capabilities/listener = 'true'" {
50         description
51             "Applies when the Listener port capability is
52             supported.";
53     }
54     description
55         "Contains the configuration and operational Listener
56         node related information.";
57     leaf enable {
58         type boolean;
59         default "false";
60         description
61             "A boolean indicating if the listener is enabled or
62             not.";
63         reference
64             "IEEE 802.1X-2020 Clause 10.4";
65     }
66
67     list announcement {
68         key "announcements";
69         config false;
70         description
71             "A list containing the operational status information
72             that the Listeners receive in the network announcement of

```

```

1         the PAE system.";
2     leaf announcements {
3         type uint32;
4         description
5             "The key into the list of Announce nodes.";
6     }
7     leaf nid {
8         type dot1x-types:paе-nid;
9         description
10            "The NID information to identify a received network
11             announcement for the PAE.";
12         reference
13            "IEEE 802.1X-2020 Clause 10.4";
14     }
15     leaf kmd {
16         type dot1x-types:paе-kmd;
17         description
18            "The KMD information for this received network
19             announcement of the PAE.";
20         reference
21            "IEEE 802.1X-2020 Clause 10.4";
22     }
23     leaf specific {
24         type boolean;
25         description
26            "This object indicates the received announcement
27             information was specific to the receiving PAE, not
28             generic for all systems attached to the LAN.";
29         reference
30            "IEEE 802.1X-2020 Clause 10.4";
31     }
32     leaf access-status {
33         type dot1x-types:paе-access-status;
34         description
35            "The object information reflects connectivity as a
36             result of authentication attempts for this received
37             network announcement of the PAE.";
38         reference
39            "IEEE 802.1X-2020 Clause 10.4";
40     }
41     leaf requested-nid {
42         type boolean;
43         description
44            "The authenticated access has been requested for this
45             particular NID or not.";
46         reference
47            "IEEE 802.1X-2020 Clause 10.4";
48     }
49     leaf unauthenticated-access {
50         type dot1x-types:paе-access-status;
51         description
52            "The access capability of the ports clients without
53             authentication in this received network announcement of
54             the PAE";
55         reference
56            "IEEE 802.1X-2020 Clause 10.4";
57     }
58     leaf access-capabilities {
59         type dot1x-types:paе-nid-capabilities;
60         description
61            "The authentication and protection capabilities
62             supported for the NID.";
63         reference
64            "IEEE 802.1X-2020 Clause 10.4";
65     }
66     list cipher-suites {
67         key "index";
68         description
69            "A table contains the Cipher Suites information that
70             the Listeners receive in the network announcement of
71             the PAE system.";
72         reference

```

```

1         "IEEE 802.1X-2020 Clause 10.4";
2     leaf index {
3         type uint16;
4         description
5             "Key into cipher suite entry.";
6     }
7     leaf cipherSuite {
8         type string;
9         description
10            "cipher Suite identifier.";
11    }
12    leaf cipherSuiteCapability {
13        type uint32;
14        description
15            "Cipher Suite capability.";
16    }
17    }
18    }
19    }
20
21    container eapol-statistics {
22        config false;
23        description
24            "Contains operational EAPOL statistics.";
25        leaf invalid-eapol-frame-rx {
26            when "../../../port-type = 'real-port'" {
27                description
28                    "Applies when port is Real Port.";
29            }
30            type yang:counter32;
31            description
32                "The number of invalid EAPOL frames of any type that
33                have been received by this PAE.";
34            reference
35                "IEEE 802.1X-2020 Clause 12.8.1";
36        }
37        leaf eap-length-error-frames-rx {
38            when "../../../port-type = 'real-port'" {
39                description
40                    "Applies when port is Real Port.";
41            }
42            type yang:counter32;
43            description
44                "The number of EAPOL frames that the Packet Body Length
45                does not match a Packet Body that is contained within the
46                octets of the received EAPOL MPDU in this PAE.";
47            reference
48                "IEEE 802.1X-2020 Clause 12.8.1";
49        }
50        leaf eapol-announcements-rx {
51            when "../../../port-type = 'real-port'" {
52                description
53                    "Applies when port is Real Port.";
54            }
55            type yang:counter32;
56            description
57                "The number of EAPOL-Announcement frames that have been
58                received by this PAE";
59            reference
60                "IEEE 802.1X-2020 Clause 12.8.1";
61        }
62        leaf eapol-announce-reqs-rx {
63            when "../../../port-type = 'real-port'" {
64                description
65                    "Applies when port is Real Port.";
66            }
67            type yang:counter32;
68            description
69                "The number of EAPOL-Announcement-Req frames that have
70                been received by this PAE.";
71            reference
72                "IEEE 802.1X-2020 Clause 12.8.1";

```

```

1      }
2      leaf eapol-port-unavailable {
3          when "../port-type = 'real-port' and
4              ../port-capabilities/virtual-ports = 'true'" {
5              description
6                  "Applies when port is Real Port and when the virtual
7                  ports capability is supported.";
8          }
9          type yang:counter32;
10         description
11             "The number of EAPOL frames that are discarded because
12             their processing would require the creation of a virtual
13             port, for which there are inadequate or constrained
14             resources, or an existing virtual port and no such port
15             currently exists. If virtual port is not supported, this
16             object should be always 0.";
17         reference
18             "IEEE 802.1X-2020 Clause 12.8.1";
19     }
20     leaf eapol-start-frames-rx {
21         type yang:counter32;
22         description
23             "The number of EAPOL-Start frames that have been received
24             by this PAE.";
25         reference
26             "IEEE 802.1X-2020 Clause 12.8.1";
27     }
28     leaf eapol-eap-frames-rx {
29         type yang:counter32;
30         description
31             "The number of EAPOL-EAP frames that have been received
32             by this PAE.";
33         reference
34             "IEEE 802.1X-2020 Clause 12.8.1";
35     }
36     leaf eapol-logoff-frames-rx {
37         type yang:counter32;
38         description
39             "The number of EAPOL-Logoff frames that have been
40             received by this PAE.";
41         reference
42             "IEEE 802.1X-2020 Clause 12.8.1";
43     }
44     leaf eapol-mk-no-cfn {
45         type yang:counter32;
46         description
47             "The number of MKPDUs received with MKA not enabled or
48             CKN not recognized in this PAE.";
49         reference
50             "IEEE 802.1X-2020 Clause 12.8.1";
51     }
52     leaf eapol-mk-invalid-frames-rx {
53         type yang:counter32;
54         description
55             "The number of MKPDUs failing in message authentication
56             on receipt process in this PAE.";
57         reference
58             "IEEE 802.1X-2020 Clause 12.8.1";
59     }
60     leaf last-eapol-frame-source {
61         when "../port-type = 'real-port'" {
62             description
63                 "Applies when port is Real Port.";
64         }
65         type ieee:mac-address;
66         description
67             "The source MAC address of last received EAPOL frame by
68             this PAE.";
69         reference
70             "IEEE 802.1X-2020 Clause 12.8.2";
71     }
72     leaf last-eapol-frame-version {

```

```

1      type uint8;
2      description
3          "The version of last received EAPOL frame by this PAE.";
4      reference
5          "IEEE 802.1X-2020 Clause 12.8.2";
6  }
7  leaf eapol-supp-eap-frames-tx {
8      when "../port-type = 'real-port'" {
9          description
10             "Applies when port is Real Port.";
11         }
12         type yang:counter32;
13         description
14             "The number of EAPOL-EAP frames that have been
15             transmitted by the supplicant of this PAE.";
16         reference
17             "IEEE 802.1X-2020 Clause 12.8.3";
18     }
19     leaf eapol-logoff-frames-tx {
20         when "../port-type = 'real-port'" {
21             description
22                 "Applies when port is Real Port.";
23         }
24         type yang:counter32;
25         description
26             "The number of EAPOL-Logoff frames that have been
27             transmitted by this PAE.";
28         reference
29             "IEEE 802.1X-2020 Clause 12.8.3";
30     }
31     leaf eapol-announcements-tx {
32         when "../port-type = 'real-port'" {
33             description
34                 "Applies when port is Real Port.";
35         }
36         type yang:counter32;
37         description
38             "The number of EAPOL-Announcement frames that have been
39             transmitted by this PAE.";
40         reference
41             "IEEE 802.1X-2020 Clause 12.8.3";
42     }
43     leaf eapol-announce-reqs-tx {
44         when "../port-type = 'real-port'" {
45             description
46                 "Applies when port is Real Port.";
47         }
48         type yang:counter32;
49         description
50             "The number of EAPOL-Announcement-Req frames that have
51             been transmitted by this PAE.";
52         reference
53             "IEEE 802.1X-2020 Clause 12.8.3";
54     }
55     leaf eapol-start-frames-tx {
56         type yang:counter32;
57         description
58             "The number of EAPOL-Start frames that have been
59             transmitted by this PAE.";
60         reference
61             "IEEE 802.1X-2020 Clause 12.8.3";
62     }
63     leaf eapol-auth-eap-frames-tx {
64         type yang:counter32;
65         description
66             "The number of EAPOL-EAP frames that have been
67             transmitted by the authenticator of this PAE.";
68         reference
69             "IEEE 802.1X-2020 Clause 12.8.3";
70     }
71     leaf eapol-mka-frames-tx {
72         type yang:counter32;

```

```

1      description
2      "The number of EAPOL-MKA frames with no CKN information
3      that have been transmitted by this PAE.";
4      reference
5      "IEEE 802.1X-2020 Clause 12.8.3";
6    }
7  }
8
9  container logon-process {
10    description
11    "Contains configuration and operational system level
12    information for each port to support the Logon Process(es)
13    status information.";
14    leaf logon {
15      type boolean;
16      default "false";
17      description
18      "A boolean indicating if the logon-process is enabled or
19      not.";
20      reference
21      "IEEE 802.1X-2020 Clause 12.5";
22    }
23
24    leaf connect {
25      type enumeration {
26        enum pending {
27          description
28          "Prevent connectivity by clearing the
29          controlledPortEnabled parameter.";
30        }
31        enum unauthenticated {
32          description
33          "Provide unsecured connectivity, setting
34          controlledPortEnabled.";
35        }
36        enum authenticated {
37          description
38          "Provide unsecured connectivity with authorization
39          data, setting controlledPortEnabled.";
40        }
41        enum secure {
42          description
43          "Provide secure connectivity, using SAKs provided by
44          the KaY (when available) and setting
45          controlledPortEnabled when those keys are installed
46          and in use, as specified in detail by the CP state
47          machine.";
48        }
49      }
50      config false;
51      description
52      "The Logon Process sets this variable to one of the
53      above values.";
54      reference
55      "IEEE 802.1X-2020 Clause 12.3";
56    }
57    leaf port-valid {
58      type boolean;
59      config false;
60      description
61      "Set if Controlled Port communication is secured as
62      specified by the MACsec control macsecProtect.";
63      reference
64      "IEEE 802.1X-2020 Clause 12.3";
65    }
66    list session-statistics {
67      key "session-id";
68      config false;
69      description
70      "Contains operational state nodes associated with the
71      session statistics.";
72      leaf session-id {

```

```

1      type dot1x-types:pae-session-id;
2      description
3          "Key into list of session statistics.";
4      reference
5          "IEEE 802.1X-2020 Clause 12.5.1";
6  }
7  leaf user-name {
8      type dot1x-types:pae-session-user-name;
9      description
10         "User name of the session.";
11     reference
12         "IEEE 802.1X-2020 Clause 12.5.1";
13 }
14 leaf octets-rx {
15     type yang:counter64;
16     description
17         "The number of octets received in this session of this
18         PAE.";
19     reference
20         "IEEE 802.1X-2020 Clause 12.5.1";
21 }
22 leaf octets-tx {
23     type yang:counter64;
24     description
25         "The number of octets transmitted in this session of
26         this PAE.";
27     reference
28         "IEEE 802.1X-2020 Clause 12.5.1";
29 }
30 leaf frames-rx {
31     type yang:counter64;
32     description
33         "The number of packets received in this session of
34         this PAE.";
35     reference
36         "IEEE 802.1X-2020 Clause 12.5.1";
37 }
38 leaf frames-tx {
39     type yang:counter64;
40     description
41         "The number of packets transmitted in this session of
42         this PAE.";
43     reference
44         "IEEE 802.1X-2020 Clause 12.5.1";
45 }
46 leaf time {
47     type uint32;
48     units "seconds";
49     description
50         "Session Time. The duration of the session in
51         seconds.";
52     reference
53         "IEEE 802.1X-2020 Clause 12.5.1";
54 }
55 leaf terminate-cause {
56     type enumeration {
57         enum common_port_MAC_operational_false {
58             description
59                 "Common Port for this PAE is not operational.";
60         }
61         enum system_access_control_disabled {
62             description
63                 "The system-access-control node of the pae-system
64                 is disabled or initialization process of this PAE
65                 is invoked.";
66         }
67         enum eapol_logoff_rx {
68             description
69                 "The PAE has received EAPOL-Logoff frame.";
70         }
71         enum eap_reauthentication_failure {
72             description

```

```
1         "EAP reauthentication has failed.";
2     }
3     enum mka-failure_termination {
4         description
5             "MKA failure or other MKA termination.";
6     }
7     enum new_session-beginning {
8         description
9             "New session beginning.";
10    }
11    enum not_terminated_yet {
12        description
13            "Not Terminated Yet.";
14    }
15    }
16    description
17        "The reason for the session termination.";
18    reference
19        "IEEE 802.1X-2020 Clause 12.5.1";
20 }
21 }
22 }
23 }
24 }
25
26 container nid-group {
27     description
28         "Contains both configuration and operational state nodes
29         associated with the PAE NID group.";
30     uses nid-group;
31 }
32
33 }
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
```