

**IEEE Standard for
Local and Metropolitan Area Networks—
Link Aggregation
Amendment 1:
YANG for Link Aggregation**

Developed by the
LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved 10 September 2025
IEEE SA Standards Board

Abstract: This amendment to IEEE Std 802.1AX-2020 specifies a Unified Modeling Language (UML)-based model and YANG modules for Link Aggregation configuration and status reporting.

Keywords: Aggregated Link, Aggregator, amendment, Distributed Resilient Network Interconnect, DRNI, IEEE 802.1AX, IEEE 802.1AXdz, interconnect, Link Aggregation, Link Aggregation Group, local area network, management, Network-Network Interface, NNI, YANG

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2025 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published dd month year. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.
OMG®, UML®, and Unified Modeling Language™ are either registered trademarks or trademarks of Object Management Group, Inc. in the United States and/or other countries.

PDF: ISBN 979-8-8557-2660-2 STD28293
Print: ISBN 979-8-8557-2661-9 STDPD28293

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE Standards documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>), appear in all IEEE standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents are developed within IEEE Societies and subcommittees of IEEE Standards Association (IEEE SA) Board of Governors. IEEE develops its standards through an accredited consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE standards are documents developed by volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers involved in technical working groups are not necessarily members of IEEE or IEEE SA and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE makes no warranties or representations concerning its standards, and expressly disclaims all warranties, express or implied, concerning all standards, including but not limited to the warranties of merchantability, fitness for a particular purpose and non-infringement. IEEE Standards documents do not guarantee safety, security, health, or environmental protection, or compliance with law, or guarantee against interference with or from other devices or networks. In addition, IEEE does not warrant or represent that the use of the material contained in its standards is free from patent infringement. IEEE Standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document should rely upon their own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus balloting process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English language version published by IEEE is the approved IEEE standard.

Use by artificial intelligence systems

In no event shall material in any IEEE Standards documents be used for the purpose of creating, training, enhancing, developing, maintaining, or contributing to any artificial intelligence systems without the express, written consent of the IEEE SA in advance. “Artificial intelligence” refers to any software, application, or other system that uses artificial intelligence, machine learning, or similar technologies, to analyze, train, process, or generate content. Requests for consent can be submitted using the [Contact Us](#) form.¹

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual is not, and shall not be considered or inferred to be, the official position of IEEE or any of its committees and shall not be considered to be or be relied upon as, a formal position of IEEE or IEEE SA. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that the presenter’s views should be considered the personal views of that individual rather than the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group. Statements made by volunteers may not represent the formal position of their employer(s) or affiliation(s). News releases about IEEE standards issued by entities other than IEEE SA should be considered the view of the entity issuing the release rather than the formal position of IEEE or IEEE SA.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations, consulting information, or advice pertaining to IEEE Standards documents.**

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its Societies and subcommittees of the IEEE SA Board of Governors are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in evaluating comments or revisions to an IEEE standard is welcome to join the relevant IEEE SA working group. You can indicate interest in a working group using the Interests tab in the Manage Profile & Interests area of the [IEEE SA myProject system](#).² An IEEE Account is needed to access the application.

Comments on standards should be submitted using the [Contact Us](#) form.¹

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not constitute compliance to any applicable regulatory

¹ Available at: <https://standards.ieee.org/about/contact/>.

² Available at: <https://development.standards.ieee.org/myproject-web/public/view.html#landing>.

requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Data privacy

Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and data ownership in the context of assessing and using the standards in compliance with applicable laws and regulations.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, neither IEEE nor its licensors waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate licensing fees, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400; <https://www.copyright.com/>. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#).³ For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

Errata

Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#).⁴ Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the

³ Available at: <https://ieeexplore.ieee.org/browse/standards/collection/ieee>.

⁴ Available at: <https://standards.ieee.org/standard/index.html>.

Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to periodically check for errata.

Patents

IEEE standards are developed in compliance with the [IEEE SA Patent Policy](#).⁵

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

IMPORTANT NOTICE

Technologies, application of technologies, and recommended procedures in various industries evolve over time. The IEEE standards development process allows participants to review developments in industries, technologies, and practices, and to determine what, if any, updates should be made to the IEEE standard. During this evolution, the technologies and recommendations in IEEE standards may be implemented in ways not foreseen during the standard's development. IEEE standards development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, data privacy, and interference protection practices and all applicable laws and regulations.

⁵ Available at: <https://standards.ieee.org/about/sasb/patcom/materials.html>.

Participants

At the time this standard was submitted to the IEEE SA Standards Board for approval, the IEEE 802.1 Working Group had the following membership:

Glenn Parsons, *Chair*
Jessy V. Rouyer, *Vice Chair*
János Farkas, *Chair, Time-Sensitive Networking Task Group*
David McCall, *Vice Chair, Time-Sensitive Networking Task Group*
Stephen Haddock, *Editor*

Mahin Ahmed	Woojung Huh	Karen Randal
Venkat Arunarthi	Satoko Itaya	Maximilian Riegel
Ralf Assmann	Yoshihiro Ito	Silvana Rodrigues
Rudy Belliardi	Abdul Jabbar	Rajeev Roy
Christian Boiger	Michael Karl	Atsushi Sato
Paul Bottorff	Stephan Kehrer	Mick Seaman
Radhakrishna Canchi	Marcel Kiessling	Maik Seewald
Feng Chen	Gavin Lai	Ramesh Sivakolundu
Lihao Chen	Yunping (Lily) Lyu	Johannes Specht
Abhijit Choudhury	Christophe Mangin	Marius Stanica
Donald Fedyk	Scott Mansfield	Max Turner
Norman Finn	Olaf Mater	Ganesh Venkatesan
Geoffrey Garner	Martin Mittelberger	Tongtong Wang
Fumihide Goto	Hiroki Nakano	Leon Wessels
Mark Hantel	Takumi Nomura	Ludwig Winkel
Marc Holness	Richie Pearn	Jordon Woods
Daniel Hopf	Dieter Proell	Takahiro Yamaura
		Nader Zein

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Mahin Ahmed	Werner Hoelzl	Richard Mellitz
Boon Chong Ang	Oliver Holland	Martin Mittelberger
Butch Anton	Raj Jain	Rajesh Murthy
Murugan Balraj	Sangkwon Jeong	N. Kishor Narang
William Byrd	Pranav Jha	Satoshi Obara
Paul Cardinal	Stanley Johnson	Glenn Parsons
Pin Chang	Lokesh Kabra	Dieter Proell
Xiandong Dong	Ruslan Karmanov	Maximilian Riegel
Marc Emmelmann	Piotr Karocki	Jessy V. Rouyer
János Farkas	Stephan Kehrer	Rajeev Roy
Donald Fedyk	Stuart Kerry	Mick Seaman
Devon Gayle	Yongbum Kim	Ishita Shukla
Stephen Haddock	Hitesh Kumar	Max Turner
Akram Hakiri	Gavin Lai	John Vergis
Marco Hernandez	Christophe Mangin	Stephen Webb

When the IEEE SA Standards Board approved this standard on 10 September 2025, it had the following membership:

Lei Wang, *Chair*
Jon W. Rosdahl, *Vice Chair*
David J. Law, *Past Chair*
Alpesh Shah, *Secretary*

Edward Au
Ted Burse
Xiaofeng (Alfred) Chen
Doug Edwards
Nehad El-Sherif
J. Travis Griffith
Deborah Hagar

Guido R. Hiertz
Ronald W. Hotchkiss
Tyler Jaynes
Thomas Koshy
Howard Li
Xiaohui Liu
Kevin W. Lu
Hiroshi Mano

Daleep Mohla
Annette Reilly
Robby Robson
Dan Sabin
F. Keith Waters
Sha Wei
Luyang (Eric) Zhang

Introduction

This introduction is not part of IEEE Std 802.1AXdz-2025, IEEE Standard for Local and Metropolitan Area Networks—Link Aggregation—Amendment 1: YANG for Link Aggregation.

IEEE Std 802.1AXdz-2025: YANG for Link Aggregation specifies a Unified Modeling Language (UML)-based model and YANG modules for Link Aggregation configuration and status reporting.

This standard contains state-of-the-art material. The area covered by this standard is undergoing evolution. Revisions are anticipated within the next few years to clarify existing material, to correct possible errors, and to incorporate new related material. Information on the current revision state of this and other IEEE 802 standards may be obtained from:

Secretary, IEEE SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Contents

2.	Normative references	14
4.	Acronyms and abbreviations	15
5.	Conformance.....	16
5.3	Link Aggregation.....	16
5.3.2	Link Aggregation options	16
10.	YANG data model	17
10.1	YANG framework	17
10.2	Information model for Link Aggregation management.....	17
10.2.1	Link Aggregation model.....	18
10.2.2	DRNI model.....	20
10.3	Structure of the Link Aggregation YANG data model.....	21
10.4	Relationship to other YANG modules.....	21
10.4.1	IEEE 802.1AX Types module	21
10.4.2	IETF YANG Types module.....	21
10.4.3	IETF Interfaces YANG module.....	21
10.4.4	IEEE 802 Types module	21
10.5	Security considerations	22
10.5.1	Security considerations of the ieee802-dot1ax YANG modules	22
10.6	YANG schema tree definitions	22
10.6.1	Schema for the ieee802-dot1ax-linkagg YANG module.....	23
10.6.2	Schema for the ieee802-dot1ax-drni YANG module	24
10.7	YANG modules,,	25
10.7.1	The ieee802-dot1ax-types YANG module	25
10.7.2	The ieee802-dot1ax-linkagg YANG module.....	32
10.7.3	The ieee802-dot1ax-drni YANG module	45
Annex A (normative)	Protocol implementation conformance statement (PICS) proforma	55
A.2	PICS proforma for Clause 6.....	55
A.2.1	Major capabilities/options.....	55
Annex G (informative)	Bibliography	56

Figures

Figure 10-1	YANG root hierarchy with Link Aggregation YANG modules.....	18
Figure 10-2	Link Aggregation configuration and monitoring objects.....	19
Figure 10-3	DRNI configuration and monitoring objects	20

Tables

Table 10-1	Structure of the YANG modules	21
------------	-------------------------------------	----

IEEE Standard for Local and Metropolitan Area Networks— Link Aggregation Amendment 1: YANG for Link Aggregation

(This amendment is based on IEEE Std 802.1AX-2020.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.⁶

⁶ Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

2. Normative references

Insert the following references into Clause 2 in alphanumeric order:

IETF RFC 6241, Network Configuration Protocol (NETCONF), Enns, R., M. Bjorklund, J. Schoenwaelder, and A. Bierman, editors, Jun. 2011.⁷

IETF RFC 6991, Common YANG Data Types, Schoenwaelder, J., Jul. 2013.

IETF RFC 7950, The YANG 1.1 Data Modeling Language, Bjorklund, M., Aug. 2016.

IETF RFC 8343, A YANG Data Model for Interface Management, Bjorklund, M., Mar. 2018.

⁷ IETF RFCs are available from the Internet Engineering Task Force (<https://www.ietf.org/>).

4. Acronyms and abbreviations

Insert the following acronyms into Clause 4 in alphabetical order:

NETCONF Network Configuration Protocol

UML® Unified Modeling Language™⁸

⁸ UML® is a registered trademark of the Object Management Group, Inc., and Unified Modeling Language™ is a trademark of the Object Management Group, Inc.

5. Conformance

5.3 Link Aggregation

5.3.2 Link Aggregation options

Insert new list items j) and k) after item i) in the lettered list of 5.3.2, as follows:

- j) Support YANG modules for the management of Link Aggregation capabilities (Clause 10).
- k) Support YANG modules for the management of DRNI capabilities (Clause 10).

Insert new Clause 10 after Clause 9 as follows:

10. YANG data model

This clause specifies the YANG (IETF RFC 7950) data model that provides control and status monitoring of systems and system components that implement functionality specified in this standard.

This clause:

- a) Introduces the YANG framework that governs the naming and hierarchy of configuration and operational data structures in the data models, and the modeling of network interfaces (10.1).
- b) Describes the information data model and its relationship to the operational processes and managed objects specified in the other clauses of this standard, and provides a representation, similar to the Unified Modeling Language (UML), of relevant objects (10.2).
- c) Describes the structure of the YANG data model, which comprises three YANG modules (10.3).
- d) Includes a relationship description of other modules imported in YANG modules (10.4)
- e) Reviews security considerations applicable to each of the modules, with specific reference to data nodes in the YANG modules that compose the YANG data model (10.5).
- f) Includes each of the YANG modules (10.7) and its data schema (10.6).

10.1 YANG framework

The YANG framework applies hierarchy in the following areas:

- a) The uniform resource name (URN), as specified in IEEE Std 802 for the IEEE 802 series of standards.
- b) The YANG objects form a hierarchy of configuration and operational data structures that specify the YANG data model.

10.2 Information model for Link Aggregation management

The YANG objects are based on the managed objects in Clause 7. A UML-like representation of the management model is provided in the following subclauses.

NOTE—OMG® UML2.5⁹ [B11] conventions together with C++ language constructs are used in this clause as a representation to convey model structure and relationships.

The purpose of a UML-like¹⁰ diagram is to express the model design on a single piece of paper. The structure of the UML-like representation shows the name of the object followed by a list of properties for the object. The properties indicate its type and accessibility. The UML-like representation is meant to express simplified semantics for the properties. It is not meant to provide the specific datatype as used to encode the object in either MIB or YANG. In the UML-like representation, a box with a white background represents information that comes from sources outside of the IEEE. A box with a gray background represents objects that are specified by this IEEE Standard.

The YANG hierarchical structure that incorporates the Link Aggregation YANG modules supported by this standard is represented by Figure 10-1. In the figures in this clause, items that are shaded gray are described in this document, items with no background shading are specified elsewhere. The YANG data model is

⁹ OMG® is a registered trademark of the Object Management Group, Inc.

¹⁰ A description of the UML-like diagrams used in this clause is provided at <https://1.ieee802.org/uml-like-diagrams>.

realized in three YANG modules. One module *ieee802-dot1ax-types* provides data types that are needed by the Link Aggregation configuration and monitoring objects. The *ieee802-dot1ax-linkagg* module provides the Link Aggregation, Aggregation Port, and Aggregator configuration and monitoring objects. The *ieee802-dot1ax-drni* module provides the Distributed Resilient Network Interface (DRNI) configuration and monitoring objects. The Link Aggregation and DRNI capabilities are not only applicable to IEEE Std 802.1Q Bridges, but also (for example) end stations and routers.




Figure 10-1—YANG root hierarchy with Link Aggregation YANG modules

10.2.1 Link Aggregation model

The Link Aggregation configuration and monitoring objects in Figure 10-2 show the objects that are applicable on a system supporting Link Aggregation, and the interfaces supporting Link Aggregation.

The objects on the system consist of a list of Aggregation Systems, and a list of key groups. A key group is the set of Aggregators and Aggregation Ports that share the same System Priority, System MAC Address, and Aggregation Key, and therefore can potentially form a Link Aggregation Group. Each key group has a unique combination of actor-admin-key and actor-system, and includes parameters that have the same value for any Aggregator and/or Aggregation Port that have the same actor-admin-key and actor-system.

NOTE—See 6.3.5 and 6.3.6 for a description of the identification of Aggregation Ports that can potentially form a Link Aggregation Group, and Figure 6-15 for examples.

Each Aggregation Port is an interface (e.g., of type ethernetCsmacd) augmented with an “aggport” presence container as shown on the right side of Figure 10-2. Each Aggregator is an interface to the entire Link Aggregation Group (using type *ieee8023adlag*¹¹) augmented with a “lag” container as shown on the left side of Figure 10-2. The binding of Aggregation Ports to Aggregators is a dynamic function of the Link Aggregation Control Protocol. The Aggregation Ports attached to an Aggregator can be read from the *lower-layer-if* attribute of the Aggregator interface. The Aggregator to which an Aggregation Port is attached can be read through the *higher-layer-if* attribute of the Aggregation Port interface. An Aggregation Port only transmits and responds to LACPDU when the interface “enabled” leaf is true, and only attaches to an Aggregator when the Aggregator interface “enabled” leaf is true. The interface “oper-status” leaf of an Aggregation Port is “up” when the Aggregation Port is attached to an Aggregator and the “collecting” and “distributing” bits of the “actor-oper-state” leaf are both true. The interface “oper-status” leaf of an Aggregator is “up” when it has at least one attached Aggregation Port that is “up”.

¹¹ This type reflects the fact that the Link Aggregation specification was originally standardized in IEEE Std 802.3ad-2000. Further development has taken place in the IEEE 802.1 Working Group since 2008. Subsequent revisions have been published as IEEE Std 802.1AX.




Figure 10-2—Link Aggregation configuration and monitoring objects

10.2.2 DRNI model

The DRNI configuration and monitoring objects in Figure 10-3 show the objects that are applicable to an Aggregator augmented with a “drni” container.




Figure 10-3—DRNI configuration and monitoring objects

10.3 Structure of the Link Aggregation YANG data model

The YANG data model specified in this standard is composed of three YANG modules. A summary of the modules contained in this clause is represented in Table 10-1.

Table 10-1—Structure of the YANG modules

Module	Subclause	Notes
ieee802-dot1ax-types	10.7.1	Type definitions used for Link Aggregation YANG.
ieee802-dot1ax-linkagg	10.7.2	Link Aggregation Management
ieee802-dot1ax-drni	10.7.3	DRNI Management

In the YANG modules below, if any discrepancy between the DESCRIPTION text and the corresponding specification in any other part of this standard occurs, the specifications outside this clause take precedence.

10.4 Relationship to other YANG modules

This clause describes how the *ieee802-dot1ax-linkagg* and *ieee802-dot1ax-drni* YANG modules are related to the YANG modules that are imported.

10.4.1 IEEE 802.1AX Types module

The *ieee802-dot1ax-types* module provides reusable types that are used by the *ieee802-dot1ax-linkagg* and *ieee802-dot1ax-drni* modules.

10.4.2 IETF YANG Types module

The *ietf-yang-types* YANG module (IETF RFC 6991) contains a set of derived YANG types. This document leverages counter64.

10.4.3 IETF Interfaces YANG module

The *ietf-interfaces* YANG module (IETF RFC 8343) contains a set of YANG definitions for managing network interfaces. This document augments an *ietf-interfaces:interface* with aggregation-port or aggregator data nodes.

10.4.4 IEEE 802 Types module

The *ieee802-types* module provides reusable types that are used in IEEE 802 standards.

NOTE—The type for mac-addresses defined in *ieee802-types* has a pattern that allows upper and lower case letters. To avoid issues with string comparison, it is suggested to only use upper case for the letters in the hexadecimal numbers. Implementers using code comparing MAC addresses are advised that there is still an issue with a difference between the IETF mac-address definition and the IEEE mac-address definition.

10.5 Security considerations

The YANG modules specified in this clause are designed to be accessed via a network configuration protocol (e.g., the NETCONF protocol). In the case of NETCONF, the lowest NETCONF layer is the secure transport layer and the mandatory to implement secure transport is SSH. The NETCONF access control model provides the means to restrict access for particular NETCONF users to a pre-configured subset of all available NETCONF protocol operations and content.

It is the responsibility of a system's implementor and administrator to ensure that the protocol entities in the system that support NETCONF, and any other remote configuration protocols that make use of these YANG modules, are properly configured to allow access only to those users who have legitimate rights to read or write data nodes. This standard does not specify how the credentials of those users are to be stored or validated.

10.5.1 Security considerations of the *ieee802-dot1ax* YANG modules

There are several management objects specified in the *ieee802-dot1ax-linkagg* and *ieee802-dot1ax-drni* YANG modules that are configurable (i.e., read-write) and/or operational (i.e., read-only). Such objects could be considered sensitive or vulnerable in some network environments. A network configuration protocol, such as NETCONF (IETF RFC 6241), can support protocol operations that can edit or delete YANG module configuration data (e.g., edit-config, delete-config, copy-config). If this is done in a non-secure environment without proper protection, then negative effects on the network operation are possible.

The following containers, and the objects in these containers, of the *ieee802-dot1ax-linkagg* and *ieee802-dot1ax-drni* YANG modules can be manipulated to interfere with the operation of the Link Aggregation Control Protocol (LACP) or the Distributed Relay Control Protocol (DRCP). This could, for example, cause network instability and result in the loss of service for a large number of end users.

```
dot1ax-linkagg/linkagg/key-group  
dot1ax-linkagg/linkagg/key-group/cscd  
dot1ax-linkagg/linkagg/key-group/cscd/admin-conv-service-map  
dot1ax-linkagg/linkagg/key-group/cscd/admin-conv-link-map  
dot1ax-linkagg/aggport  
dot1ax-linkagg/aggport/cscd/admin-link-number  
dot1ax-linkagg/lag  
dot1ax-drni/lag/drni  
dot1ax-drni/lag/drni/home-gateway-conv-service-map
```

Some of the readable data in this YANG module could be considered sensitive or vulnerable in some network environments. It is important to control all types of access (e.g., including NETCONF get, get-config operations) to these objects and possibly to even encrypt the values of these objects when sending them over the network. For example, the system name and other information about the remote systems could provide information about the configuration and topology of the network and could be considered a privacy threat.

10.6 YANG schema tree definitions

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in these diagrams is as follows:

- Brackets “[” and “]” enclose list keys.

- Abbreviations before data node names: “rw” means configuration (read-write) and “ro” means state data (read-only).
- Symbols after data node names: “?” means an optional node, “!” means a presence container, and “*” denotes a list and leaf-list.
- Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (“:”).
- Ellipses (“...”) stand for contents of subtrees that are not shown.

10.6.1 Schema for the *ieee802-dot1ax-linkagg* YANG module

```

module: ieee802-dot1ax-linkagg
  +--rw linkagg
    +--rw agg-system* [name]
      | +--rw name string
      | +--rw actor-system? ieee:mac-address
      | +--rw actor-system-priority? uint16
    +--rw key-group* [name]
      +--rw name string
      +--rw actor-admin-key uint16
      +--rw agg-system-name agg-system-ref
      +--rw actor-protocol-da? ax:bridge-reserved-addresses
      +--rw collector-max-delay? uint16
      +--rw actor-admin-state? ax:lacp-state
      +--rw partner-admin-system? ieee:mac-address
      +--rw partner-admin-system-priority? uint16
      +--rw port-algorithm? identityref
      +--ro lags* if:interface-ref
      +--ro aggports* if:interface-ref
    +--rw cscd {ax:cscd}?
      +--rw admin-conv-service-map {ax:sid-map}?
        | +--rw (method)?
        | | +--:(pattern)
        | | | +--rw pattern? identityref
        | | +--:(cid-list)
        | | | +--rw cid-list* [cid]
        | | | | +--rw cid uint16
        | | | | +--rw service-ids* uint32
        +--ro admin-conv-service-digest? binary
      +--rw admin-conv-link-map
        | +--rw (method)?
        | | +--:(pattern)
        | | | +--rw pattern? identityref
        | | +--:(cid-list)
        | | | +--rw cid-list* [cid]
        | | | | +--rw cid uint16
        | | | | +--rw link-numbers* uint16
        +--ro admin-conv-link-digest? binary
      +--rw admin-discard-wrong-conv? enumeration {ax:dwc}?

  augment /if:interfaces/if:interface:
    +--rw lag
      +--rw key-group-name key-group-ref
      +--ro mac-address? ieee:mac-address
    +--ro lacp
      | +--ro actor-oper-key? uint16
      | +--ro partner-system? ieee:mac-address
      | +--ro partner-system-priority? uint16
      | +--ro partner-oper-key? uint16
      | +--ro aggregate-or-individual? boolean
    +--ro cscd {ax:cscd}?
      +--ro partner-port-algorithm? identityref
      +--ro partner-conv-service-digest? binary
      +--ro partner-conv-link-digest? binary
      +--ro discard-wrong-conversation? boolean
      +--ro active-lag-links* uint16
  augment /if:interfaces/if:interface/if:statistics:
    +--ro lag-stats
      +--ro unknown-protocol-frames? yang:counter64
  augment /if:interfaces/if:interface:
    +--rw aggport!

```

```

+--rw key-group-name          key-group-ref
+--rw actor-port-number?     uint16
+--rw actor-port-priority?   uint16
+--rw partner-admin-key?     uint16
+--rw partner-admin-port?    uint16
+--rw partner-admin-port-priority? uint16
+--rw partner-admin-state?   ax:lacp-state
+--rw wtr-time?              uint16
+--rw wtr-revertive?         boolean
+--ro lacp
|  +--ro actor-lacp-version?   uint8
|  +--ro actor-oper-key?      uint16
|  +--ro actor-oper-state?    ax:lacp-state
|  +--ro partner-lacp-version? uint8
|  +--ro partner-oper-system-priority? uint16
|  +--ro partner-oper-system? ieee:mac-address
|  +--ro partner-oper-key?    uint16
|  +--ro partner-oper-port?   uint16
|  +--ro partner-oper-port-priority? uint16
|  +--ro partner-oper-state?  ax:lacp-state
|  +--ro aggregate-or-individual? boolean
|  +--ro wtr-waiting?         boolean
+--rw cscd {ax:cscd}?
   +--rw admin-link-number?   uint16
   +--ro partner-link-number? uint16
   +--ro link-number?         uint16
augment /if:interfaces/if:interface/if:statistics:
+--ro aggpport-stats
+--ro lacp-pdu-rx?            yang:counter64
+--ro marker-pdu-rx?         yang:counter64
+--ro marker-response-pdu-rx? yang:counter64
+--ro unknown-rx?            yang:counter64
+--ro illegal-rx?            yang:counter64
+--ro lacp-pdu-tx?           yang:counter64
+--ro marker-pdu-tx?         yang:counter64
+--ro marker-response-pdu-tx? yang:counter64

```

10.6.2 Schema for the *ieee802-dot1ax-drni* YANG module

module: ieee802-dot1ax-drni

```

augment /if:interfaces/if:interface/dotlax:lag:
+--rw drni!
+--rw irp-name                if:interface-ref
+--rw drni-aggregator-key?    uint16
+--rw drni-aggregator-system? ieee:mac-address
+--rw drni-aggregator-system-priority? uint16
+--rw drcp-protocol-da?       ax:bridge-reserved-addresses
+--rw home-admin-irp-state?   irp-state
+--ro home-oper-irp-state?    irp-state
+--rw home-cscd-gateway-control? boolean
+--rw home-dr-client-gateway-control? boolean
+--rw home-gateway-algorithm? identityref
+--rw home-gateway-conv-service-map {ax:sid-map}?
|  +--rw (method)?
|  +--:(pattern)
|  |  +--rw pattern?         identityref
|  +--:(cid-list)
|  |  +--rw cid-list* [cid]
|  |  |  +--rw cid          uint16
|  |  |  +--rw service-ids* uint32
+--ro home-gateway-conv-service-digest? binary
+--rw gateway-enable-mask
|  +--rw cid-str*            string
|  +--rw invert-mask?       boolean
+--rw gateway-preference-mask
|  +--rw cid-str*            string
|  +--rw invert-mask?       boolean
+--ro gateway-available-mask
|  +--ro cid-str*            string

```



```

| +--ro invert-mask?    boolean
+--ro neighbor
  +--ro oper-irp-state?      irp-state
  +--ro system?              ieee:mac-address
  +--ro system-priority?     uint16
  +--ro drni-key?            uint16
  +--ro aggregator-algorithm? identityref
  +--ro aggregator-conv-service-digest? binary
  +--ro aggregator-conv-link-digest? binary
  +--ro partner-system-priority? uint16
  +--ro partner-system?      ieee:mac-address
  +--ro partner-aggregator-key? uint16
  +--ro cscd-state?          bits
  +--ro active-links*        uint16
  +--ro gateway-algorithm?   identityref
  +--ro gateway-conv-service-digest? binary
  +--ro gateway-available-mask
    | +--ro cid-str*        string
    | +--ro invert-mask?    boolean
  +--ro gateway-preference-mask
    +--ro cid-str*        string
    +--ro invert-mask?    boolean
augment /if:interfaces/if:interface/if:statistics/dot1ax:lag-stats:
+--ro drni-stats
  +--ro drcpdus-rx?      yang:counter64
  +--ro illegal-rx?      yang:counter64
  +--ro drcpdus-tx?      yang:counter64

```

10.7 YANG modules^{12,13,14}

10.7.1 The *ieee802-dot1ax-types* YANG module

```

module ieee802-dot1ax-types {
  yang-version 1.1;
  namespace "urn:ieee:std:802.1AX:yang:ieee802-dot1ax-types";
  prefix dot1ax-types;

  organization
    "IEEE 802.1 Working Group";
  contact
    "WG-URL: http://www.ieee802.org/1/
    WG-Email: stds-802-1-1@ieee.org

    Contact: IEEE 802.1 Working Group Chair
    Postal: C/O IEEE 802.1 Working Group
            IEEE Standards Association
            45 Hoes Lane
            Piscataway, NJ 08854
            USA
    E-mail: stds-802-1-chairs@ieee.org";
  description
    "Common types used within 802.1AX Link Aggregation modules.

    Copyright (C) IEEE (2025).

    This version of this YANG module is part of IEEE Std 802.1AX;
    see the standard itself for full legal notices.";

  revision 2025-09-30 {
    description

```

¹² *Copyright release for YANG modules:* Users of this standard may freely reproduce the YANG modules contained in this subclause so that they can be used for their intended purpose.

¹³ An ASCII version of the YANG module(s) can be obtained by Web browser from the IEEE 802.1 Website at <https://1.ieee802.org/yang-modules/>.

¹⁴ References in this standard's YANG module definitions are not clickable, as each module has been incorporated unchanged after development and verification using YANG tools.

IEEE Std 802.1AXdz™-2025
IEEE Standard for Local and Metropolitan Area Networks—Link Aggregation—
Amendment 1: YANG for Link Aggregation

```
"Published as part of IEEE Std 802.1AXdz-2025.
The following reference statement identifies each referenced
IEEE Standard as updated by applicable amendments.";
reference
  "IEEE Std 802.1AX-2020 Link Aggregation:
  IEEE Std 802.1AXdz-2025.";
}

feature csdc {
  description
    "Conversation-Sensitive Collection and Distribution (CSCD)
    is supported.";
  reference
    "5.3.2, 6.6 of IEEE Std 802.1AX";
}

feature dwc {
  description
    "The Discard Wrong Conversation option in CSCD is
    supported.";
  reference
    "5.3.2, 6.6 of IEEE Std 802.1AX";
}

feature sid-map {
  description
    "The Service ID to Conversation ID map is supported for
    use by distribution algorithms.";
}

feature c-vid-dist-alg {
  description
    "Supports distribution based on C-VIDs.";
}

feature s-vid-dist-alg {
  description
    "Supports distribution based on S-VIDs.";
}

feature i-sid-dist-alg {
  description
    "Supports distribution based on I-SIDs.";
}

feature te-sid-dist-alg {
  description
    "Supports distribution based on TE-SIDs.";
}

feature flow-hash-dist-alg {
  description
    "Supports distribution based on Flow Hash.";
}

feature basic-link-maps {
  description
    "Pre-defined admin-conv-link-map configurations to distribute
    packets on either one or two active links, with any
    remaining links available as standby.";
}

identity distribution-algorithm {
  description
    "Each distribution algorithm is identified by a sequence of
    4 octets, structured as shown in Figure 8-1. Distribution
    algorithm identifiers are used by network administrators to
    select between algorithms and, in Conversation-sensitive
    LACP and (if supported) Distributed Resilient Network
    Interconnect (DRNI) operation, to check whether partners
    and neighbors are using the same algorithm.
```

This identity is intended to serve as base identity, not to be directly referenced.

Vendor specific, combination (ex: multi-layer), and other customized distribution algorithms can be created as their own identities in their own YANG files, derived from this imported base type. When the identity description specifies a 4-octet value, this value is used for CSCD purposes, and included in LACPDUs. Otherwise the identity is used purely for local selection of a distribution algorithm, and the unspecified distribution algorithm is used for CSCD purposes.";

```
reference
  "8.1, 8.2 of IEEE Std 802.1AX";
}

identity unspecified {
  base distribution-algorithm;
  description
    "The 'Unspecified distribution algorithm' identifier has
    been reserved for use when the algorithm is unknown (or
    is not advertised).
    The algorithm identifier is 00-80-C2-00.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity c-vids-nomap {
  if-feature "c-vid-dist-alg";
  base distribution-algorithm;
  description
    "Distribution based on C-VIDs (8.2.1). No Service ID
    mapping table is used.
    The algorithm identifier is 00-80-C2-01.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity c-vids-map {
  if-feature "c-vid-dist-alg and sid-map";
  base distribution-algorithm;
  description
    "Distribution based on C-VIDs (8.2.1). A Service ID
    mapping table is used.
    The algorithm identifier is 00-80-C2-81.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity s-vids-nomap {
  if-feature "s-vid-dist-alg";
  base distribution-algorithm;
  description
    "Distribution based on S-VIDs (8.2.2). No Service ID
    mapping table is used.
    The algorithm identifier is 00-80-C2-02.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity s-vids-map {
  if-feature "s-vid-dist-alg and sid-map";
  base distribution-algorithm;
  description
    "Distribution based on S-VIDs (8.2.2). A Service ID
    mapping table is used.
    The algorithm identifier is 00-80-C2-82.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity i-sids-nomap {
```

```
if-feature "i-sid-dist-alg";
base distribution-algorithm;
description
  "Distribution based on I-SIDs (8.2.3). No Service ID
  mapping table is used.
  The algorithm identifier is 00-80-C2-03.";
reference
  "Table 8-1 of IEEE Std 802.1AX";
}

identity i-sids-map {
  if-feature "i-sid-dist-alg and sid-map";
  base distribution-algorithm;
  description
    "Distribution based on I-SIDs (8.2.3). A Service ID
    mapping table is used.
    The algorithm identifier is 00-80-C2-83.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity te-sids-nomap {
  if-feature "te-sid-dist-alg";
  base distribution-algorithm;
  description
    "Distribution based on TE-SIDs (8.2.4). No Service ID
    mapping table is used.
    The algorithm identifier is 00-80-C2-04.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity te-sids-map {
  if-feature "te-sid-dist-alg and sid-map";
  base distribution-algorithm;
  description
    "Distribution based on TE-SIDs (8.2.4). A Service ID
    mapping table is used.
    The algorithm identifier is 00-80-C2-84.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity flow-hash-nomap {
  if-feature "flow-hash-dist-alg";
  base distribution-algorithm;
  description
    "Distribution based on Flow Hash (8.2.5). No Service ID
    mapping table is used.
    The algorithm identifier is 00-80-C2-05.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity flow-hash-map {
  if-feature "flow-hash-dist-alg and sid-map";
  base distribution-algorithm;
  description
    "Distribution based on Flow Hash (8.2.5). A Service ID
    mapping table is used.
    The algorithm identifier is 00-80-C2-85.";
  reference
    "Table 8-1 of IEEE Std 802.1AX";
}

identity link-map-patterns {
  description
    "Base identity for patterns filling the admin-conv-link-map.
    This identity is intended to serve as base identity, not
    to be directly referenced. Use of the identity allows vendors
    to augment the module with vendor specified patterns.";
  reference
```

```
"7.3.1.1.34, 6.6.3.1 of IEEE Std 802.1AX";
}

identity one-plus-n {
  if-feature "basic-link-maps";
  base link-map-patterns;
  description
    "Provides active/standby behavior with one link carrying
    all traffic and any other links in the LAG are standby.
    All packets are mapped to the lowest link number that is
    active in the aggregation. This is updated whenever a link
    becomes active or inactive in the aggregation. The pattern
    supports any number of links with link numbers between 1
    and 4095. Any links in the aggregation with a link number
    greater than 4095 are not used.
    The map consists of an identical entry for each CID, with
    a list of numbers from 1 to 4095, followed by the number 0.
    The MD5 digest calculated for this map is
    0xd2dc4cf241740239408945bd87391286 (hex) or
    0txM8kF0AjlAiUW9hzkShg== (base64).";
}

identity two-plus-n {
  if-feature "basic-link-maps";
  base link-map-patterns;
  description
    "Provides basic load-balancing on two links and any other
    links in the aggregation are standby. All packets with an
    even CID value are mapped to the link with the lowest link
    number that is active in the aggregation, and all packets
    with an odd CID value are mapped to the link with the
    highest link number that is active in the aggregation.
    This is updated whenever a link becomes active or inactive
    in the aggregation. The pattern supports any number of
    links with link numbers between 1 and 4095. Any links in
    the aggregation with a link number greater than 4095 are
    not used.
    The map consists of an identical entry for each even CID
    containing a list of numbers from 1 to 4095, followed by
    the number 0, and an identical entry for each odd CID
    containing a list of numbers from 4095 to 1, followed by
    the number 0.
    The MD5 digest calculated for this map is
    0xfe8fec2effe6cd1cbd78c2a968aa5d20 (hex) or
    /o/sLv/mzRy9eMKpaKpdIA== (base64).";
}

identity service-map-patterns {
  description
    "Base identity for patterns filling the
    admin-conv-service-map. This identity is intended to serve
    as base identity, not to be directly referenced. Use of the
    identity allows vendors to augment the module with vendor
    specified patterns.";
  reference
    "7.3.1.1.36, 6.6.3.1 of IEEE Std 802.1AX";
}

typedef lacp-state {
  type bits {
    bit lacp-activity {
      position 1;
      description
        "Provides administrative control over when LACPDUs are
        transmitted. A value of '1' indicates Active mode where
        LACPDUs are sent regardless of partner's lacp-activity
        value. A value of '0' indicates Passive mode where
        LACPDUs are sent only when the partner's lacp-activity
        value is '1' (partner is in Active mode).";
    }
    bit lacp-timeout {
      position 2;
    }
  }
}
```

```
    description
      "Provides administrative control over the frequency of
      received LACPDUs. A value of '1' indicates Short Timeout
      (so partner uses frequent transmission). A value of '0'
      indicates Long Timeout (so partner can use infrequent
      transmission).";
  }
  bit aggregation {
    position 3;
    description
      "Provides administrative control over whether this
      Aggregation Port can be in a LAG with more than one
      member. A value of '1' indicates the port can be
      aggregated with other ports. A value of '0' indicates
      the port can only be a solitary link.";
  }
  bit synchronization {
    position 4;
    description
      "The Synchronization state of the MUX state machine.";
  }
  bit collecting {
    position 5;
    description
      "The Collecting state of the MUX state machine.";
  }
  bit distributing {
    position 6;
    description
      "The Distributing state of the MUX state machine.";
  }
  bit defaulted {
    position 7;
    description
      "Indicates the port is using the partner-admin values
      to select an Aggregator.";
  }
  bit expired {
    position 8;
    description
      "The Expired state of the Receive state machine.";
  }
}
description
  "LACP state values as transmitted in LACPDUs.
  Administrative control over the values of lacp-activity,
  lacp-timeout, aggregation, and (in partner-admin-lACP-state)
  synchronization is allowed.
  The remaining bits are read-only.";
reference
  "6.4.1, 6.4.2.3 of IEEE Std 802.1AX";
}

typedef bridge-reserved-addresses {
  type enumeration {
    enum nearest-customer-bridge {
      description
        "Reserved MAC address 01-80-C2-00-00-00";
    }
    enum slow-protocols-multicast {
      description
        "Reserved MAC address 01-80-C2-00-00-02";
    }
    enum nearest-non-tpmr-bridge {
      description
        "Reserved MAC address 01-80-C2-00-00-03";
    }
    enum nearest-bridge {
      description
        "Reserved MAC address 01-80-C2-00-00-0E";
    }
  }
}
```

```
description
  "Group addresses that are filtered by some or all types of
  Bridges in order to limit the scope of propagation of PDUs
  in a Bridged Network.";
reference
  "8.6.3 of IEEE Std 802.1Q";
}

grouping link-map {
  description
    "Specifies the contents of the admin-conv-link-map.";
  reference
    "7.3.1.1.34, 6.6.3.1 of IEEE Std 802.1AX";
  choice method {
    default "cid-list";
    description
      "Provides two ways to specify the map contents.";
    leaf pattern {
      type identityref {
        base link-map-patterns;
      }
      description
        "Use a predefined pattern to fill the map.";
    }
    list cid-list {
      key "cid";
      description
        "Data structure to map a Conversation Identifier
        (CID) to a Link Number. Each entry consists of a CID
        and a list of link numbers that can potentially be
        selected for that CID. An empty list of link-numbers
        means that no links are selected for the CID.";
      leaf cid {
        type uint16 {
          range "0..4095";
        }
        description
          "Port Conversation Identifier";
      }
      leaf-list link-numbers {
        type uint16;
        description
          "List of zero or more Link Numbers that can
          potentially be selected for distribution of frames
          with this CID.";
      }
    }
  }
}
```

```
grouping service-map {
  description
    "Specifies the contents of the admin-conv-service-map.";
  reference
    "7.3.1.1.36, 6.6.3.1 of IEEE Std 802.1AX";
  choice method {
    default "cid-list";
    description
      "Provides two ways to specify the map contents.";
    leaf pattern {
      type identityref {
        base service-map-patterns;
      }
      description
        "Use a predefined pattern to fill the map.";
    }
    list cid-list {
      key "cid";
      description
        "Data structure to map Service Identifiers to
        Conversation Identifiers. Each entry consists of a
        Conversation ID (CID) and a list of zero or more
```

```
Service Identifiers (SIDs) that map to it. An empty
list of SIDs means there are no SIDs that map to this
CID, and results in the same behavior as not having an
entry for this CID.";
leaf cid {
  type uint16 {
    range "0..4095";
  }
  description
    "Port Conversation Identifier";
}
leaf-list service-ids {
  type uint32;
  description
    "List of zero or more SIDs that map to the CID.";
}
}
}
}
```

10.7.2 The *ieee802-dot1ax-linkagg* YANG module

```
module ieee802-dot1ax-linkagg {
  yang-version 1.1;
  namespace "urn:ieee:std:802.1AX:yang:ieee802-dot1ax-linkagg";
  prefix dot1ax;

  import ieee802-dot1ax-types {
    prefix ax;
  }
  import ieee802-types {
    prefix ieee;
  }
  import ietf-yang-types {
    prefix yang;
  }
  import ietf-interfaces {
    prefix if;
  }
  import iana-if-type {
    prefix ianaif;
  }

  organization
    "IEEE 802.1 Working Group";
  contact
    "WG-URL: http://www.ieee802.org/1/
    WG-Email: stds-802-1-l@ieee.org

    Contact: IEEE 802.1 Working Group Chair
    Postal: C/O IEEE 802.1 Working Group
           IEEE Standards Association
           45 Hoes Lane
           Piscataway, NJ 08854
           USA
    E-mail: stds-802-1-chairs@ieee.org";
  description
    "This YANG module describes the configuration model for Link
    Aggregation, as specified in IEEE Std 802.1AX, including Link
    Aggregation Control Protocol (LACP) and Conversation-Sensitive
    Collection and Distribution.

    Copyright (C) IEEE (2025).

    This version of this YANG module is part of IEEE Std 802.1AX;
    see the standard itself for full legal notices.";

  revision 2025-09-30 {
```



```
description
  "Published as part of IEEE Std 802.1AXdz-2025.
  The following reference statement identifies each referenced
  IEEE Standard as updated by applicable amendments.";
reference
  "IEEE Std 802.1AX-2020 Link Aggregation:
  IEEE Std 802.1AXdz-2025.";
}

typedef key-group-ref {
  type leafref {
    path "/dotlax:linkagg/dotlax:key-group/dotlax:name";
  }
  description
    "This type is used by Aggregators and Aggregation Ports to
    reference an entry in the key-group list.";
}

typedef agg-system-ref {
  type leafref {
    path "/dotlax:linkagg/dotlax:agg-system/dotlax:name";
  }
  description
    "This type is used in the key-group list entries to
    reference an entry in the agg-system list.";
}

augment "/if:interfaces/if:interface" {
  when "derived-from-or-self(if:type,'ianaif:ieee8023adLag')" {
    description
      "Applies to interfaces representing a LAG.";
  }
  description
    "Augment Interface with Aggregator parameters.";
  container lag {
    description
      "Contains the configuration and status information that
      allows an instance of an Aggregator to be managed.";
    leaf key-group-name {
      type key-group-ref;
      mandatory true;
      description
        "Specifies the entry in the link-aggregation key-group
        list to which this Aggregator is assigned.";
    }
    leaf mac-address {
      type ieee:mac-address;
      config false;
      description
        "The MAC address assigned to the Aggregator.";
      reference
        "7.3.1.1.9 of IEEE Std 802.1AX";
    }
    container lacp {
      config false;
      description
        "Contains Aggregator LACP operational data.";
      leaf actor-oper-key {
        type uint16;
        description
          "The current operational value of the Key for the
          Aggregator. The meaning of particular Key
          values is of local significance.";
        reference
          "7.3.1.1.8 of IEEE Std 802.1AX";
      }
    }
    leaf partner-system {
      type ieee:mac-address;
      description
        "The value of the MAC address portion of the
        System Identifier for the current
        protocol partner of this Aggregator. A value
```

```
        of zero indicates that there is no known partner.
        If the aggregation is manually configured, this
        System Identifier value is assigned by the
        local System.";
    reference
        "7.3.1.1.10 of IEEE Std 802.1AX";
}
leaf partner-system-priority {
    type uint16;
    description
        "Indicates the priority value portion of the current
        Partner's System Identifier. If the aggregation is
        manually configured, this System Priority value is
        assigned by the local System.";
    reference
        "7.3.1.1.11 of IEEE Std 802.1AX";
}
leaf partner-oper-key {
    type uint16;
    description
        "The current operational value of the Key for the
        Aggregator's current protocol Partner. If the
        aggregation is manually configured, this Key value
        is assigned by the local System.";
    reference
        "7.3.1.1.12 of IEEE Std 802.1AX";
}
leaf aggregate-or-individual {
    type boolean;
    description
        "Indicates whether the Aggregator represents an
        Aggregate (TRUE) or an Individual link (FALSE).";
    reference
        "7.3.1.1.6 of IEEE Std 802.1AX";
}
}
container cscd {
    if-feature "ax:cscd";
    config false;
    description
        "Aggregator parameters obtained by the operation of LACP
        supporting CSCD.";
    leaf partner-port-algorithm {
        type identityref {
            base ax:distribution-algorithm;
        }
        description
            "Operational value of the distribution algorithm in
            use by the LACP Partner.";
        reference
            "7.3.1.1.40 of IEEE Std 802.1AX";
    }
    leaf partner-conv-service-digest {
        type binary;
        description
            "The MD5 Digest of the admin-conv-service-map in use
            by the LACP Partner.";
        reference
            "7.3.1.1.42, 6.6.3.1 of IEEE Std 802.1AX";
    }
    leaf partner-conv-link-digest {
        type binary;
        description
            "The MD5 Digest of the admin-conv-link-map in use
            by the LACP Partner.";
        reference
            "7.3.1.1.41, 6.6.3.1 of IEEE Std 802.1AX";
    }
}
leaf discard-wrong-conversation {
    type boolean;
    description
        "The operational value that determines whether an
```

```

    description
      "Aggregator discards a frame that is collected
      from an Aggregation Port that is different from the
      Aggregation Port to which the Aggregator would
      distribute a frame with the same Port Conversation
      ID.";
    reference
      "7.3.1.1.37, 6.6 of IEEE Std 802.1AX";
  }
  leaf-list active-lag-links {
    type uint16;
    description
      "A list, possibly empty, of the operational
      link-number of each Aggregation Port active
      (i.e., Collecting) on this Aggregator.";
    reference
      "7.3.1.1.43 of IEEE Std 802.1AX";
  }
}
}
}

augment "/if:interfaces/if:interface/if:statistics" {
  when '../dot1ax:lag' {
    description
      "Applies to Aggregators.";
  }
  description
    "Augment interface statistics with Aggregator statistics.";
  container lag-stats {
    config false;
    description
      "Contains the set of stats associated with the
      Aggregator.";
    leaf unknown-protocol-frames {
      type yang:counter64;
      description
        "A count of data frames discarded on reception by all
        ports that are (or have been) members of the
        aggregation, due to the detection of an unknown Slow
        Protocols PDU (7.3.3.1.5)";
      reference
        "7.3.1.1.29 of IEEE Std 802.1AX";
    }
  }
}

augment "/if:interfaces/if:interface" {
  description
    "Augment interface model with Aggregation Port
    configuration nodes.";
  container aggport {
    presence
      "When present, this interface supports Link Aggregation";
    description
      "Contains Aggregation Port configuration related nodes,
      which provides the basic management controls necessary
      to allow an instance of an Aggregation Port to be managed,
      for the purposes of Link Aggregation.";
    leaf key-group-name {
      type key-group-ref;
      mandatory true;
      description
        "Specifies the entry in the link-aggregation key-group
        list to which this aggregation-port is assigned.";
    }
    leaf actor-port-number {
      type uint16 {
        range "1..65535";
      }
      description
        "The port number assigned to the Aggregation Port.
        The port number is communicated in LACPDUs as the

```

```
    Actor Port.
    This leaf provides the ability to administratively
    override the initial value provided by the system.";
  reference
    "7.3.2.1.14, 6.4.6 of IEEE Std 802.1AX";
}
leaf actor-port-priority {
  type uint16;
  default "0x8000";
  description
    "The priority value assigned to this Aggregation Port.";
  reference
    "7.3.2.1.15, 6.4.6 of IEEE Std 802.1AX";
}
leaf partner-admin-key {
  type uint16 {
    range "1..65535";
  }
  description
    "The current administrative value of the Key for the
    protocol Partner. The assigned value is used, along
    with the value of port-partner-admin-system-priority,
    partner-admin-system, partner-admin-port, and
    partner-admin-port-priority, in order to achieve
    manually configured aggregation.
    The default value is the initial value of actor-port-
    number provided by the system.";
  reference
    "7.3.2.1.10 of IEEE Std 802.1AX";
}
leaf partner-admin-port {
  type uint16 {
    range "1..65535";
  }
  description
    "The current administrative value of the port number for
    the protocol Partner. The assigned value is used, along
    with the value of partner-admin-system-priority,
    partner-admin-system, port-partner-admin-key, and
    partner-admin-port-priority, in order to achieve
    manually configured aggregation.
    The default value is the initial value of actor-port-
    number provided by the system.";
  reference
    "7.3.2.1.16 of IEEE Std 802.1AX";
}
leaf partner-admin-port-priority {
  type uint16;
  default "0";
  description
    "The current administrative value of the port priority
    for the protocol Partner. The assigned value is used,
    along with the value of partner-admin-system-priority,
    partner-admin-system, partner-admin-key, and
    partner-admin-port, in order to achieve manually
    configured aggregation.";
  reference
    "7.3.2.1.18 of IEEE Std 802.1AX";
}
leaf partner-admin-state {
  type ax:lacp-state {
    bit lacp-activity {
      position 1;
      description
        "When the LACP_Activity state is set to '0', the
        transmission of LACPDUs is controlled by the
        actor-admin-state.LACP_Activity.";
    }
    bit lacp-timeout {
      position 2;
      description
        "When the LACP_Timeout is set to '0', LACPDUs
```

```
        are transmitted at the Slow_Periodic_Time.";
    }
    bit aggregation {
        position 3;
        description
            "When the Aggregation state is set to '0', this
            port cannot be aggregated with any other port.";
    }
    bit synchronization {
        position 4;
        description
            "When the Synchronization state is set to '0', this
            port cannot become active.";
    }
}
default "synchronization";
description
    "Provides administrative control over the partner's
    LACP_Activity, LACP_Timeout, Aggregation, and
    Synchronization state when the partner's information
    is unknown (i.e., no LACPDUs are received from the
    partner).";
reference
    "7.3.2.1.22, 6.4.1, 6.4.2.3, 6.4.6 of IEEE Std 802.1AX";
}
leaf wtr-time {
    type uint16 {
        range "0..32767";
    }
    default "0";
    description
        "The wait-to-restore (WTR) period, in seconds, that
        needs to elapse between an Aggregation Port on a LAG
        coming up (Port_Operational becoming TRUE) and being
        permitted to become active (transmitting and
        receiving frames) on the LAG.";
    reference
        "7.3.2.1.30 of IEEE Std 802.1AX";
}
leaf wtr-revertive {
    type boolean;
    default "true";
    description
        "Controls revertive or non-revertive mode of operation.
        When TRUE, the Aggregation Port can become active as
        soon as the wait-to-restore timer expires regardless of
        the state of other links in the LAG.
        When FALSE, the Aggregation Port cannot become active
        unless there are no other links that can become active
        in the LAG. The default value is TRUE.";
    reference
        "7.3.2.1.31 of IEEE Std 802.1AX";
}
container lacp {
    config false;
    description
        "Contains Aggregation Port LACP operational related
        nodes.";
    leaf actor-lacp-version {
        type uint8;
        description
            "The version number transmitted in LACPDUs on this
            Aggregation Port";
        reference
            "7.3.2.1.33 of IEEE Std 802.1AX";
    }
    leaf actor-oper-key {
        type uint16;
        description
            "The current operational value of the Key for the
            Aggregation Port. The meaning of particular Key values
            is of local significance.";
```

```
reference
  "7.3.2.1.5 of IEEE Std 802.1AX";
}
leaf actor-oper-state {
  type ax:lacp-state;
  description
    "The operational value of the Actor_State as
    transmitted in LACPDUs.";
  reference
    "7.3.2.1.21, 6.4.1, 6.4.2.3, 6.4.6 of IEEE Std 802.1AX";
}
leaf partner-lacp-version {
  type uint8;
  description
    "The version number in the LACPDU most recently
    received on this Aggregation Port.";
  reference
    "7.3.2.1.34 of IEEE Std 802.1AX";
}
leaf partner-oper-system-priority {
  type uint16;
  description
    "Indicates the operational value of priority associated
    with the Partners System ID. The value of this
    attribute can contain the manually configured value
    carried in partner-admin-system-priority if there is
    no protocol Partner.";
  reference
    "7.3.2.1.7 of IEEE Std 802.1AX";
}
leaf partner-oper-system {
  type ieee:mac-address;
  description
    "Represents the MAC address portion of the Aggregation
    Port's current protocol partner's System Identifier.
    A value of zero indicates that there is no known
    protocol Partner.
    The value of this attribute can contain the manually
    configured value carried in partner-admin-system if
    there is no protocol Partner.";
  reference
    "7.3.2.1.9 of IEEE Std 802.1AX";
}
leaf partner-oper-key {
  type uint16;
  description
    "The current operational value of the Key for the
    protocol Partner. The value of this attribute can
    contain the manually configured value carried in
    partner-admin-key if there is no protocol Partner.";
  reference
    "7.3.2.1.11 of IEEE Std 802.1AX";
}
leaf partner-oper-port {
  type uint16;
  description
    "The operational port number assigned by the
    Aggregation Port's protocol Partner. The value of this
    attribute can contain the administratively configured
    value carried in partner-admin-port if there is no
    protocol Partner.";
  reference
    "7.3.2.1.17 of IEEE Std 802.1AX";
}
leaf partner-oper-port-priority {
  type uint16;
  description
    "The operational priority value assigned by the
    Aggregation Port's protocol Partner. The value of this
    attribute can contain the administratively configured
    value carried in partner-admin-port-priority if there
    is no protocol Partner.";
```

```
reference
  "7.3.2.1.19 of IEEE Std 802.1AX";
}
leaf partner-oper-state {
  type ax:lacp-state;
  description
    "The operational value of the partner's LACP state
    derived from received LACPDUs or, when Defaulted is
    true, from the partner-admin-state.";
  reference
    "7.3.2.1.23, 6.4.1, 6.4.2.3, 6.4.6 of IEEE Std 802.1AX";
}
leaf aggregate-or-individual {
  type boolean;
  description
    "When true indicates the Aggregation Port can join a
    LAG consisting of multiple Aggregation Ports.
    When false, indicates that the Aggregation Port can
    only operate as an Solitary link because the
    Aggregation bit is false in either
    actor-oper-port-state or partner-oper-port-state.";
  reference
    "7.3.2.1.24 of IEEE Std 802.1AX";
}
leaf wtr-waiting {
  type boolean;
  description
    "Indicates the Aggregation Port is inhibited from
    becoming active for an interval (determined by
    wtr-time) after becoming operational or while
    non-revertive operation is being enforced by the
    Selection Logic.";
  reference
    "7.3.2.1.32 of IEEE Std 802.1AX";
}
}
container cscd {
  if-feature "ax:cscd";
  description
    "Aggregation Port parameters for support of CSCD.";
  leaf admin-link-number {
    type uint16;
    description
      "The Link_Number value for the Aggregation Port,
      that is unique among all Aggregation Ports in the same
      key group. This leaf provides the ability to
      administratively override the initial value provided
      by the system. A value of 0 is allowed, but
      results in no frames being distributed to this
      Aggregation Port.
      The default value is the initial value of actor-port-
      number provided by the system.";
    reference
      "7.3.2.1.27, 6.6.3.2 of IEEE Std 802.1AX";
  }
  leaf partner-link-number {
    type uint16;
    config false;
    description
      "The last received value of the Partner_Link_Number,
      or zero if the Aggregation Port is using default
      values for the Partner or the Partner LACP Version
      is 1.";
    reference
      "7.3.2.1.29 of IEEE Std 802.1AX";
  }
}
leaf link-number {
  type uint16;
  config false;
  description
    "The operational link number for this Aggregation Port.
    The value is either the same as the admin-link-number,
```

```
        or the corresponding value of the LACP partner.";
      reference
        "7.3.2.1.28 of IEEE Std 802.1AX";
    }
  }
}

augment "/if:interfaces/if:interface/if:statistics" {
  when '../dotlax:aggport' {
    description
      "Applies to Aggregation Ports.";
  }
  description
    "Augment interface statistics with aggport statistics.";
  container aggport-stats {
    config false;
    description
      "Contains stats associated with the Aggregation Port.";
    leaf lacp-pdu-rx {
      type yang:counter64;
      description
        "The number of valid LACPDUs received on this
        Aggregation Port.";
      reference
        "7.3.3.1.2 of IEEE Std 802.1AX";
    }
    leaf marker-pdu-rx {
      type yang:counter64;
      description
        "The number of valid Marker PDUs received on this
        Aggregation Port.";
      reference
        "7.3.3.1.3 of IEEE Std 802.1AX";
    }
    leaf marker-response-pdu-rx {
      type yang:counter64;
      description
        "The number of valid Marker Response PDUs received on
        this Aggregation Port.";
      reference
        "7.3.3.1.4 of IEEE Std 802.1AX";
    }
    leaf unknown-rx {
      type yang:counter64;
      description
        "The number of frames received that either:
        a) Carry the Slow Protocols Ethernet Type value,
        but contain an unknown PDU, or
        b) Are addressed to the Slow Protocols group MAC
        Address, but do not carry the Slow Protocols
        Ethernet Type.";
      reference
        "7.3.3.1.5 of IEEE Std 802.1AX";
    }
    leaf illegal-rx {
      type yang:counter64;
      description
        "The number of frames received that carry the Slow
        Protocols Ethernet Type value, but contain a badly
        formed PDU or an illegal value of Protocol Subtype.";
      reference
        "7.3.3.1.6 of IEEE Std 802.1AX";
    }
    leaf lacp-pdu-tx {
      type yang:counter64;
      description
        "The number of LACPDUs transmitted on this
        Aggregation Port.";
      reference
        "7.3.3.1.7 of IEEE Std 802.1AX";
    }
  }
}
```



```
leaf marker-pdu-tx {
  type yang:counter64;
  description
    "The number of Marker PDUs transmitted on this
    Aggregation Port.";
  reference
    "7.3.3.1.8 of IEEE Std 802.1AX";
}
leaf marker-response-pdu-tx {
  type yang:counter64;
  description
    "The number of Marker Response PDUs transmitted on
    this Aggregation Port.";
  reference
    "7.3.3.1.9 of IEEE Std 802.1AX";
}
}
}

container linkagg {
  description
    "Link Aggregation System specific configuration nodes.";
  list agg-system {
    key "name";
    description
      "List of Aggregation Systems.";
    leaf name {
      type string;
      description
        "Name for the Aggregation System.";
    }
    leaf actor-system {
      type ieee:mac-address;
      description
        "The part of the System Identifier that is a globally
        unique MAC address. This leaf provides the ability to
        administratively override the initial value provided
        by the system.";
      reference
        "7.3.1.1.4, 7.3.2.1.3 of IEEE Std 802.1AX";
    }
    leaf actor-system-priority {
      type uint16;
      default "0x8000";
      description
        "The part of the System Identifier that is the
        priority of the system.";
      reference
        "7.3.1.1.5, 7.3.2.1.2 of IEEE Std 802.1AX";
    }
  }
}
list key-group {
  key "name";
  unique "actor-admin-key";
  description
    "List of key groups. A key group is the set of Aggregators
    and Aggregation Ports that share the same system priority,
    system identifier, and aggregation key, and therefore can
    potentially form a Link Aggregation Group. Each entry in
    the key group list contains the parameters common to all
    Aggregation Ports and/or Aggregators in the key group.";
  reference
    "6.3.5, 6.4.12 of IEEE Std 802.1AX";
  leaf name {
    type string;
    description
      "Name for the key group.";
  }
  leaf actor-admin-key {
    type uint16 {
      range "1..65535";
    }
  }
}
```

```
mandatory true;
description
  "The administrative value of the key used by the
   Aggregators and Aggregation Ports in this key-group.";
reference
  "7.3.1.1.7, 7.3.2.1.4 of IEEE Std 802.1AX";
}
leaf agg-system-name {
  type agg-system-ref;
  mandatory true;
  description
    "Specifies the Aggregation System for this key
     group.";
}
leaf actor-protocol-da {
  type ax:bridge-reserved-addresses;
  must ". = 'nearest-customer-bridge' or
        . = 'slow-protocols-multicast' or
        . = 'nearest-non-tpmr-bridge'" {
    error-message "Invalid protocol address";
  }
  default "slow-protocols-multicast";
  description
    "A 6-octet read-write MAC Address value specifying the DA
     to be used when sending Link Aggregation Control and
     Marker PDUs. Valid addresses are the
     nearest-customer-bridge, slow-protocols-multicast,
     and nearest-non-tpmr-bridge group addresses. The
     default value is the slow-protocols-multicast address.";
  reference
    "7.3.2.2.1, 6.2.10.2 of IEEE Std 802.1AX";
}
leaf collector-max-delay {
  type uint16;
  description
    "Specifies the maximum delay, in tens of microseconds,
     between receiving a frame from an Aggregator Port, and
     either delivering the frame to the Aggregator Client or
     discarding the frame. A value of zero means the delay
     is less than the minimum increment (< 10us).
     This leaf provides the ability to administratively
     override the initial value provided by the system.";
  reference
    "7.3.1.1.32, 6.2.3.1.1, B.3 of IEEE Std 802.1AX";
}
leaf actor-admin-state {
  type ax:lacp-state {
    bit lacp-activity {
      position 1;
      description
        "Setting the LACP_Activity state to '0' means that the
         transmission of LACPDUs is controlled by the value of
         partner-oper-state.LACP_Activity.";
    }
    bit lacp-timeout {
      position 2;
      description
        "Setting the LACP_Timeout to '0' means that actor uses
         the Long_Timeout value, allowing the partner to
         transmit LACPDUs at the Slow_Periodic_Time.";
    }
    bit aggregation {
      position 3;
      description
        "Setting the Aggregation state to '0' prevents this
         port from being aggregated with any other ports.";
    }
  }
  default "lacp-activity lacp-timeout aggregation";
  description
    "Provides administrative control over the values of the
     LACP_Activity, LACP_Timeout, and Aggregation state.";
```

```
reference
  "7.3.2.1.20, 6.4.1, 6.4.2.3, 6.4.6 of IEEE Std 802.1AX";
}
leaf partner-admin-system {
  type ieee:mac-address;
  default "00-00-00-00-00-00";
  description
    "The administrative value of the MAC address portion of
    the Partner's System Identifier.
    The assigned value is used, along with the value of
    port-partner-admin-system, partner-admin-key,
    partner-admin-port, and partner-admin-port-priority,
    to achieve administratively configured Link
    Aggregation Groups with a partner that does not run
    LACP.";
  reference
    "7.3.2.1.8 of IEEE Std 802.1AX";
}
leaf partner-admin-system-priority {
  type uint16;
  default "0";
  description
    "The administrative value of priority portion of the
    the Partner's System Identifier. The assigned
    value is used, along with the value of
    port-partner-admin-system, partner-admin-key,
    partner-admin-port, and partner-admin-port-priority,
    to achieve administratively configured Link
    Aggregation Groups with a partner that does not run
    LACP.";
  reference
    "7.3.2.1.6 of IEEE Std 802.1AX";
}
leaf port-algorithm {
  type identityref {
    base ax:distribution-algorithm;
  }
  default "ax:unspecified";
  description
    "Identifies the algorithm used by the Aggregator to
    assign frames to a Port Conversation ID. Default is
    the value for an unspecified distribution algorithm.
    When the identity description specifies a 4-octet value,
    this value will be used for CSCD purposes, and included
    in LACPDUs. Otherwise this leaf is used purely for
    local selection of a distribution algorithm, and the
    unspecified distribution algorithm is used for CSCD
    purposes.";
  reference
    "7.3.1.1.33, Table 8-1 of IEEE Std 802.1AX";
}
leaf-list lags {
  type if:interface-ref;
  config false;
  description
    "A list of the if:name of Aggregators assigned to this
    key group.";
  reference
    "linkagg:key-group";
}
leaf-list aggports {
  type if:interface-ref;
  config false;
  description
    "A list of the if:name of Aggregation Ports assigned to
    this key group.";
  reference
    "linkagg:key-group";
}
container cscd {
  if-feature "ax:cscd";
  description
```

IEEE Std 802.1AXdz™-2025
IEEE Standard for Local and Metropolitan Area Networks—Link Aggregation—
Amendment 1: YANG for Link Aggregation

```
"Contains CSCD parameters that need to be consistent for
all Aggregation Ports and Aggregators in the key group.";
container admin-conv-service-map {
  if-feature "ax:sid-map";
  description
    "Data structure to map Service Identifiers to
    Conversation Identifiers. Each entry consists of a
    Conversation ID (CID) and a list of zero or more
    Service Identifiers (SIDs) that map to it. An empty
    list of SIDs means there are no SIDs that map to this
    CID, and results in the same behavior as not having an
    entry for this CID.";
  reference
    "7.3.1.1.36, 6.6.3.1 of IEEE Std 802.1AX";
  uses ax:service-map;
}
leaf admin-conv-service-digest {
  type binary;
  config false;
  description
    "The MD5 Digest of the admin-conv-service-map. The
    value is NULL (AAAAAAAAAAAAAAAAAAAAAA== in base64)
    when the distribution algorithm specified by
    agg-port-algorithm does not use the
    admin-conv-service-map.";
  reference
    "7.3.1.1.39, 6.6.3.1 of IEEE Std 802.1AX";
}
container admin-conv-link-map {
  description
    "Data structure to map a Conversation Identifier
    (CID) to a Link Number. Each entry consists of a CID
    and a list of link numbers that can potentially be
    selected for that CID. An empty list of link-numbers
    means that no links are selected for the CID.";
  reference
    "7.3.1.1.34, 6.6.3.1 of IEEE Std 802.1AX";
  uses ax:link-map;
}
leaf admin-conv-link-digest {
  type binary;
  config false;
  description
    "The MD5 Digest of the admin-conv-link-map. The
    value is NULL (AAAAAAAAAAAAAAAAAAAAAA== in base64)
    when the distribution algorithm specified by
    agg-port-algorithm does not use the
    admin-conv-link-map.";
  reference
    "7.3.1.1.38, 6.6.3.1 of IEEE Std 802.1AX";
}
leaf admin-discard-wrong-conv {
  if-feature "ax:dwc";
  type enumeration {
    enum force-true {
      value 1;
      description
        "Indicates that an Aggregator discards a
        frame that is collected from an Aggregation Port
        that is different from the Aggregation Port to
        which the Aggregator would distribute a frame
        with the same Port Conversation ID.";
    }
    enum force-false {
      value 2;
      description
        "Indicates that an Aggregator does not discard
        a frame that is collected from an Aggregation Port
        that is different from the Aggregation Port to
        which the Aggregator would distribute a frame with
        the same Port Conversation ID. This is the behavior
        of the Aggregator when DWC is not supported";
    }
  }
}
```

```

    }
    enum auto {
      value 3;
      description
        "Indicates that the Aggregator behaves as
         if the value was force-true only when the actor
         and partner agree on the algorithms (other than
         unspecified) and mapping tables used to map frames
         to Aggregation Ports, and behaves as if the value
         was force-false otherwise.";
    }
  }
  default "force-false";
  description
    "Indicates whether an Aggregator discards a
     frame that is collected from an Aggregation Port
     that is different from the Aggregation Port to which
     the Aggregator would distribute a frame with the
     same Port Conversation ID.";
  reference
    "7.3.1.1.35, 6.6 of IEEE Std 802.1AX";
}
}
}
}
}

```

10.7.3 The *ieee802-dot1ax-drni* YANG module

```

module ieee802-dot1ax-drni {
  yang-version 1.1;
  namespace "urn:ieee:std:802.1AX:yang:ieee802-dot1ax-drni";
  prefix dot1ax-drni;

  import ieee802-dot1ax-types {
    prefix ax;
  }
  import ieee802-dot1ax-linkagg {
    prefix dot1ax;
  }
  import ieee802-types {
    prefix ieee;
  }
  import ietf-yang-types {
    prefix yang;
  }
  import ietf-interfaces {
    prefix if;
  }

  organization
    "IEEE 802.1 Working Group";
  contact
    "WG-URL: http://www.ieee802.org/1/
     WG-Email: stds-802-1-1@ieee.org

    Contact: IEEE 802.1 Working Group Chair
    Postal: C/O IEEE 802.1 Working Group
           IEEE Standards Association
           45 Hoes Lane
           Piscataway, NJ 08854
           USA
    E-mail: stds-802-1-chairs@ieee.org";
  description
    "This YANG module describes the configuration model for a
     Distributed Resilient Network Interface (DRNI) as specified
     in 802.1AX.

    Copyright (C) IEEE (2025).

```

IEEE Std 802.1AXdz™-2025
IEEE Standard for Local and Metropolitan Area Networks—Link Aggregation—
Amendment 1: YANG for Link Aggregation

This version of this YANG module is part of IEEE Std 802.1AX;
see the standard itself for full legal notices.";

```
revision 2025-09-30 {
  description
    "Published as part of IEEE Std 802.1AXdz-2025.
    The following reference statement identifies each referenced
    IEEE Standard as updated by applicable amendments.";
  reference
    "IEEE Std 802.1AX-2020 Link Aggregation:
    IEEE Std 802.1AXdz-2025.";
}

typedef irp-state {
  type bits {
    bit reserved-1 {
      position 1;
      description
        "Reserved for future use. It is set to 0 on
        transmit and ignored on receipt.";
    }
    bit reserved-2 {
      position 2;
      description
        "Reserved for future use. It is set to 0 on
        transmit and ignored on receipt.";
    }
    bit short-timeout {
      position 3;
      description
        "The Short_Timeout flag indicates the Timeout control
        value in use by the DRCP Receive machine on this IRP.
        Short Timeout is encoded as a 1; Long Timeout is encoded
        as a 0.";
    }
    bit synchronization {
      position 4;
      description
        "When the Sync flag is TRUE (1), the DRCP Receive machine
        has determined the Neighbor DRNI System has a compatible
        configuration for forming a DRNI.";
    }
    bit irc-data {
      position 5;
      description
        "When the IRC_Data flag is TRUE (1), the transfer of Up
        and Down frames is permitted on the IRC.";
    }
    bit drni {
      position 6;
      description
        "The DRNI flag is TRUE (1) when this DRNI System is paired
        with another DRNI System and FALSE (0) otherwise.";
    }
    bit defaulted {
      position 7;
      description
        "When the Defaulted flag is TRUE (1), the DRCP Receive
        machine is using default operational Neighbor
        information. When FALSE (0), the operational Neighbor
        information in use has been received in a DRCPDU.";
    }
    bit expired {
      position 8;
      description
        "When the Expired flag is TRUE (1), the DRCP Receive
        machine is in the EXPIRED state.";
    }
  }
  description
    "IRP state values as transmitted in DRCPDUs.
```

```
        Administrative control over the values of Short_Timeout
        and IRC_Data is allowed. The remaining bits are read-only.";
    reference
        "7.4.1.1.24, 9.6.2.3, Figure 9-13 of IEEE Std 802.1AX";
}

grouping drni-mask {
    description
        "Specifies the contents of a bit mask indexed by CID.";
    leaf-list cid-str {
        type string {
            pattern '(0|[1-9][0-9]{0,3})'
                + '((-0|[1-9][0-9]{0,3})'
                + '(%0|[1-9][0-9]{0,3}))?)?'
                + '(',
            pattern '(0|[1-9][0-9]{0,3})'
                + '((-0|[1-9][0-9]{0,3})'
                + '(%0|[1-9][0-9]{0,3}))?)?'
                + ')*';
        }
        default "0-4095";
        description
            "A comma separated list of single CID values (x),
            CID ranges (x-y), or ranges with an increment (x-y%z).
            For example, the string '0,10-13,100-110%4' sets the
            bits in the mask corresponding to CIDs
            0,10,11,12,13,100,104,108.
            Some special cases are:
            'x-y%z' where x+z>y is the same as 'x'.
            'x-y%0' is the same as 'x'.
            'x-y%1' is the same as 'x-y'.
            'x-y%2' sets the bit for all even CIDs in the range
            when x is even, and for all odd CIDs when x is odd.
            Although the pattern allows values of x, y, and z in the
            range 0-9999, resulting CID values greater than 4095
            have no effect on the mask.
            Specified as a list of strings, so that long strings
            can be broken into several shorter strings.
            The default sets all bits in the mask.";
    }
    leaf invert-mask {
        type boolean;
        default "false";
        description
            "When true the specified mask is inverted:
            each zero replaced with a one,
            and each one replaced with a zero.";
    }
}

augment "/if:interfaces/if:interface/dot1ax:lag" {
    description
        "Augmentation parameters only for Aggregators with
        DRNI enabled.";
    container drni {
        presence "When present, this Aggregator is enabled for DRNI";
        description
            "Aggregator parameters to support a Distributed
            Resilient Network Interface";
        leaf irp-name {
            type if:interface-ref;
            mandatory true;
            description
                "Interface Name (if:name) of the Port supporting the
                Intra-Relay Port (IRP) of this DRNI Gateway.";
            reference
                "7.4.1.1.23 of IEEE Std 802.1AX";
        }
        leaf drni-aggregator-key {
            type uint16 {
                range "1..65535";
            }
        }
    }
}
```

```
description
  "The Aggregator Key value to be used by the Aggregator
  supporting this DRNI Gateway (and the Aggregation Ports
  assigned to this DRNI Gateway) when paired with a
  neighbor DRNI System via the IRC. The default value is
  the Aggregator's Actor_Admin_Aggregator_Key value.";
reference
  "7.4.1.1.15 of IEEE Std 802.1AX";
}
leaf drni-aggregator-system {
  type ieee:mac-address;
  default "00-00-00-00-00-00";
  description
    "The Aggregator System value to be used by the
    Aggregator supporting this DRNI Gateway (and the
    Aggregation Ports assigned to this DRNI Gateway)
    when paired with a neighbor DRNI System via the
    Intra-Relay Connection (IRC).";
  reference
    "7.4.1.1.13 of IEEE Std 802.1AX";
}
leaf drni-aggregator-system-priority {
  type uint16;
  default "0";
  description
    "The Aggregator System Priority value to be used by the
    Aggregator supporting this DRNI Gateway (and the
    Aggregation Ports assigned to this DRNI Gateway) when
    paired with a neighbor DRNI System via the IRC.";
  reference
    "7.4.1.1.14 of IEEE Std 802.1AX";
}
leaf drcp-protocol-da {
  type ax:bridge-reserved-addresses;
  must "." = 'nearest-customer-bridge' or
    . = 'nearest-bridge' or
    . = 'nearest-non-tpmr-bridge' {
    error-message "Invalid protocol address";
  }
  default "nearest-non-tpmr-bridge";
  description
    "A 6-octet read-write MAC Address value specifying the
    Destination Address for Distributed Relay Control PDUs
    transmitted on the Intra-Relay Port. Valid addresses are
    the nearest-customer-bridge, nearest-bridge, and
    nearest-non-tpmr-bridge group addresses. The default
    value is the nearest-non-tpmr-bridge group
    address.";
  reference
    "7.4.1.1.12, 9.6.1.1 of IEEE Std 802.1AX";
}
leaf home-admin-irp-state {
  type irp-state {
    bit short-timeout {
      position 3;
      description
        "The Short_Timeout flag indicates the Timeout control
        value in use by the DRCP Receive machine on this
        IRP. Short Timeout is encoded as a 1; Long Timeout
        is encoded as a 0.";
    }
    bit irc-data {
      position 5;
      description
        "When the IRC_Data flag is TRUE (1), the transfer of
        Up and Down frames is permitted on the IRC.";
    }
  }
  default "short-timeout irc-data";
  description
    "Provides administrative control over the values of the
    Short_Timeout and IRC-Data state.";
```



```
reference
  "7.4.1.1.24, 9.6.2.3, Figure 9-13 of IEEE Std 802.1AX";
}
leaf home-oper-irp-state {
  type irp-state;
  config false;
  description
    "A string of 8 bits, corresponding to the current
    operational value of IRP_State as transmitted in
    DRCPDUs.";
  reference
    "7.4.1.1.25, 9.6.2.3, Figure 9-13 of IEEE Std 802.1AX";
}
leaf home-cscd-gateway-control {
  type boolean;
  default "true";
  description
    "When TRUE, allows the DRNI Gateway Port selection to
    be based on the CSCD parameters that control the
    Aggregator Port selection.";
  reference
    "7.4.1.1.16 of IEEE Std 802.1AX";
}
leaf home-dr-client-gateway-control {
  type boolean;
  default "true";
  description
    "When TRUE, allows the Distributed Relay Client to
    determine whether to forward frames through the DRNI
    Gateway Port.";
  reference
    "7.4.1.1.17 of IEEE Std 802.1AX";
}
leaf home-gateway-algorithm {
  type identityref {
    base ax:distribution-algorithm;
  }
  default "ax:unspecified";
  description
    "Identifies the algorithm used by the DRNI Gateway to
    assign frames to a Gateway Conversation ID. 8.2 provides
    the IEEE 802.1 OUI (00-80-C2) Gateway Algorithm
    encodings. Default is the value for an unspecified
    distribution algorithm.";
  reference
    "7.4.1.1.6 of IEEE Std 802.1AX";
}
container home-gateway-conv-service-map {
  if-feature "ax:sid-map";
  description
    "Data structure to map Service Identifiers to
    Conversation Identifiers. Each entry consists of a
    Conversation ID (CID) and a list of zero or more Service
    Identifiers (SIDs) that map to it. Frames with Service
    IDs not contained in the map are not mapped to any
    Gateway Conversation ID and are discarded.";
  reference
    "7.4.1.1.20, 6.6.3.1 of IEEE Std 802.1AX";
  uses ax:service-map;
}
leaf home-gateway-conv-service-digest {
  type binary;
  config false;
  description
    "The MD5 Digest of the home-gateway-conv-service-map. The
    value is NULL (AAAAAAAAAAAAAAAAAAAAAA== in base64) when
    the distribution algorithm specified
    by agg-port-algorithm does not use the
    home-gateway-conv-service-map.";
  reference
    "7.4.1.1.21 of IEEE Std 802.1AX";
}
```

```
container gateway-enable-mask {
  description
    "A vector of Boolean values, with one value for each
    possible Gateway Conversation ID. A 1 indicates that
    frames associated with that Gateway Conversation ID
    are allowed to pass through this Gateway Port, and a
    0 indicates that such frames are not allowed to pass.
    Default value is all bits set to 1.";
  reference
    "7.4.1.1.18, 9.5.3.5, 9.6.5 of IEEE Std 802.1AX";
  uses drni-mask;
}
container gateway-preference-mask {
  description
    "A vector of Boolean values, with one value for each
    possible Gateway Conversation ID. A 1 indicates that
    this Gateway Port is the preferred Gateway when both
    DRNI Gateways have the Gateway Conversation ID enabled
    in the gateway-available-mask, and a 0 indicates that
    it is not preferred.
    Default value is all bits set to 1.";
  reference
    "7.4.1.1.19, 9.5.3.5, 9.6.5 of IEEE Std 802.1AX";
  uses drni-mask;
}
container gateway-available-mask {
  config false;
  description
    "A vector of Boolean values, with one value for each
    possible Gateway Conversation ID. A 1 indicates that
    this Gateway Port is eligible to be selected to pass
    that Gateway Conversation ID, and a 0 indicates that
    it is not eligible.";
  reference
    "7.4.1.1.22, 9.5.3.5, 9.6.5 of IEEE Std 802.1AX";
  uses drni-mask;
}
container neighbor {
  config false;
  description
    "Operational values for the DRNI neighbor obtained
    from DRCPDUs.";
  leaf oper-irp-state {
    type irp-state;
    description
      "A string of 8 bits, corresponding to the current
      operational value of IRP_State as transmitted in
      DRCPDUs.";
    reference
      "7.4.1.1.26, 9.6.2.3, Figure 9-13 of IEEE Std 802.1AX";
  }
  leaf system {
    type ieee:mac-address;
    description
      "The MAC Address portion of the System Identifier of
      the Neighbor DRNI System (connected via the
      Intra-Relay Port). ";
    reference
      "7.4.1.1.29 of IEEE Std 802.1AX";
  }
  leaf system-priority {
    type uint16;
    description
      "The priority portion of the System Identifier of the
      Neighbor DRNI System (connected via the Intra-Relay
      Port). ";
    reference
      "7.4.1.1.30 of IEEE Std 802.1AX";
  }
  leaf drni-key {
    type uint16;
    description
```

```

    "The DRNI key value received from the Neighbor DRNI
    System (connected via the Intra-Relay Port).";
  reference
    "7.4.1.1.31 of IEEE Std 802.1AX";
}
leaf aggregator-algorithm {
  type identityref {
    base ax:distribution-algorithm;
  }
  description
    "The Port algorithm used by the Neighbor Aggregator to
    assign frames to Port Conversation IDs.";
  reference
    "7.4.1.1.33 of IEEE Std 802.1AX";
}
leaf aggregator-conv-service-digest {
  type binary;
  description
    "The MD5 Digest of the Neighbor Aggregator's
    Admin_Conv_Service_Map. Obtained from the Home
    Aggregator State TLV last received from the Neighbor
    DRNI System.";
  reference
    "7.4.1.1.34 of IEEE Std 802.1AX";
}
leaf aggregator-conv-link-digest {
  type binary;
  description
    "The MD5 Digest of the Neighbor Aggregator's
    Admin_Conv_Link_Map. Obtained from the Home Aggregator
    State TLV (9.6.2.4) last received from the Neighbor
    DRNI System.";
  reference
    "7.4.1.1.35 of IEEE Std 802.1AX";
}
leaf partner-system-priority {
  type uint16;
  description
    "The priority portion of the System Identifier of the
    Neighbor Aggregator's Partner.";
  reference
    "7.4.1.1.36 of IEEE Std 802.1AX";
}
leaf partner-system {
  type ieee:mac-address;
  description
    "The MAC Address portion of the System Identifier of
    the Neighbor Aggregator's Partner.";
  reference
    "7.4.1.1.37 of IEEE Std 802.1AX";
}
leaf partner-aggregator-key {
  type uint16;
  description
    "The operational key value of the Neighbor
    Aggregator's Partner.";
  reference
    "7.4.1.1.38 of IEEE Std 802.1AX";
}
leaf cscd-state {
  type bits {
    bit reserved-1 {
      position 0;
      description
        "Bit 1 is reserved for future use. It is set to 0
        and ignored on receipt.";
    }
    bit reserved-2 {
      position 1;
      description
        "Bit 2 is reserved for future use. It is set to 0
        and ignored on receipt.";
    }
  }
}
```

```
}
bit reserved-3 {
  position 2;
  description
    "Bit 3 is reserved for future use. It is set to 0
    and ignored on receipt.";
}
bit cscd_gateway_control {
  position 3;
  description
    "CSCD_Gateway_Control is encoded in bit 4. When
    this flag is TRUE, the DRNI Gateway is configured
    to minimize forwarding data frames on the IRC by
    selecting the DRNI Gateway and Aggregator Ports
    for forwarding any given Conversation ID to be in
    the same DRNI System.";
}
bit discard_wrong_conversation {
  position 4;
  description
    "Discard_Wrong_Conversation is encoded in bit 5.
    The Aggregator's Discard_Wrong_Conversation
    value.";
}
bit differ_conv_link_digests {
  position 5;
  description
    "Differ_Conv_Link_Digests is encoded in bit 6.
    This flag is TRUE when the Aggregator's
    Actor_Conv_Link_Digest matches the Aggregator's
    Partner_Conv_Link_Digest.";
}
bit differ_conv_service_digests {
  position 6;
  description
    "Differ_Conv_Service_Digests is encoded in bit 7.
    This flag is TRUE when the Aggregator's
    Actor_Conv_Service_Digest matches the Aggregator's
    Partner_Conv_Service_Digest.";
}
bit differ_port_algorithms {
  position 7;
  description
    "Differ_Port_Algorithms is encoded in bit 8. The
    Aggregator's differPortAlgorithms flag is TRUE
    when the Aggregator's Actor_Port_Algorithm matches
    the Aggregator's Partner_Port_Algorithm.";
}
}
description
  "8 bits, corresponding to the Aggregator_CSCD_State
  in the Neighbor_Aggregator_State variable. The first
  three bits (the least significant bits of CSCD_State)
  are reserved; the fourth bit corresponds to the
  Neighbor's value for Home_Admin_CSCD_Gateway_Control;
  the fifth bit corresponds to the Neighbor Aggregator's
  operational value for Discard_Wrong_Conversation; and
  the sixth, seventh, and eighth bits correspond to the
  Neighbor Aggregator's operational value for
  differConvLinkDigests, differConvServiceDigests, and
  differPortAlgorithms, respectively, (the most
  significant bits of CSCD_State).";
reference
  "7.4.1.1.39 of IEEE Std 802.1AX";
}
leaf-list active-links {
  type uint16;
  description
    "A list of the operational Link_Numbers of Aggregation
    Ports that are currently active (i.e., collecting) on
    the Neighbor's Aggregator. An empty list indicates that
    there are no Aggregation Ports active. Each integer
```

```
        value in the list carries an aAggPortOperLinkNumber
        attribute value.";
    reference
        "7.4.1.1.40 of IEEE Std 802.1AX";
}
leaf gateway-algorithm {
    type identityref {
        base ax:distribution-algorithm;
    }
    description
        "The gateway algorithm used by the Neighbor DRNI
        Gateway to assign frames to Gateway Conversation IDs.";
    reference
        "7.4.1.1.41 of IEEE Std 802.1AX";
}
leaf gateway-conv-service-digest {
    type binary;
    description
        "The MD5 Digest of the Neighbor DRNI Gateway's
        the Home_Admin_Gateway_Conv_Service_Map. Obtained
        from Gateway_Conv_Service_Digest in the
        Neighbor_Gateway_State_TLV last received from the
        Neighbor DRNI System.";
    reference
        "7.4.1.1.42 of IEEE Std 802.1AX";
}
container gateway-available-mask {
    description
        "A vector of Boolean values, with one value for each
        possible Gateway Conversation ID. A 1 indicates that
        the Neighbor DRNI Gateway Port is eligible to be
        selected to pass that Gateway Conversation ID, and
        a 0 indicates that it is not eligible.";
    reference
        "7.4.1.1.43 of IEEE Std 802.1AX";
    uses drni-mask;
}
container gateway-preference-mask {
    description
        "A vector of Boolean values, with one value for each
        possible Gateway Conversation ID. A 1 indicates that
        the Neighbor DRNI Gateway Port is the preferred
        Gateway when both DRNI Gateways have the Gateway
        Conversation ID enabled in the gateway-available-mask,
        and a 0 indicates that it is not preferred.";
    reference
        "7.4.1.1.44 of IEEE Std 802.1AX";
    uses drni-mask;
}
}
}
}

augment "/if:interfaces/if:interface/if:statistics"
+ "/dotlax:lag-stats" {
    when '../dotlax:lag/dotlax-drni:drni' {
        description
            "Applies to Aggregators with DRNI present.";
    }
    description
        "Augment interface statistics with DRNI statistics.";
    container drni-stats {
        description
            "Contains DRNI specific statistics.";
        leaf drcpdus-rx {
            type yang:counter64;
            description
                "The number of valid DRCPDUs received on this
                Intra-Relay Port.";
            reference
                "7.4.1.1.45 of IEEE Std 802.1AX";
        }
    }
}
```

```
leaf illegal-rx {  
  type yang:counter64;  
  description  
    "The number of frames received on this Intra-Relay  
    Port that carry the DRCP EtherType value,  
    but contain a badly formed PDU.";  
  reference  
    "7.4.1.1.46, 9.6.1.4 of IEEE Std 802.1AX";  
}  
leaf drcpdus-tx {  
  type yang:counter64;  
  description  
    "The number of valid DRCPDUs transmitted on this  
    Intra-Relay Port.";  
  reference  
    "7.4.1.1.47 of IEEE Std 802.1AX";  
}  
}  
}
```

Annex A

(normative)

Protocol implementation conformance statement (PICS) proforma¹⁵

A.2 PICS proforma for Clause 6

A.2.1 Major capabilities/options

Insert two new rows at the end of the table in A.2.1 as follows:

Item	Feature	Subclause	Value/Comment	Status	Support
...					
YANG	Does the implementation support management operations using YANG modules?	10.6		O	Yes [] No []
YANG modules	Is the ieee802-dot1ax-types module supported?	10.7.1		YANG:M	N/A [] Yes []
	Is the ieee802-dot1ax-linkagg module supported?	10.7.2		YANG:M	N/A [] Yes []
	Is the ieee802-dot1ax-drni module supported?	10.7.3		DRNI AND YANG:M	N/A [] Yes []

¹⁵ Copyright release for PICS proformas: Users of this standard may freely reproduce the PICS proforma in this subclause so that it can be used for its intended purpose and may further publish the completed PICS.

Annex G

(informative)

Bibliography

Insert the following three bibliography entries after [B8] in Annex G:

[B9] IETF RFC 7803, Changing the Registration Policy for the NETCONF Capability URNs Registry, Leiba, B., February 2016.¹⁶

[B10] IETF RFC 8040, RESTCONF Protocol, Bierman, A., M. Bjorklund, and K. Watsen, January 2017.

[B11] OMG Unified Modeling Language (OMG UML), Version 2.5, March 2015.¹⁷

¹⁶ IETF RFCs are available from the Internet Engineering Task Force (<https://www.ietf.org/>).

¹⁷ OMG documents are available from the Object Management Group (<https://www.omg.org/>).