

1

2

3

4 June 26, 2025

IEEE P802.1DP/Draft 3.3
SAE AS6675™-2025

5 IEEE P802.1DP/SAE AS6675™-2025/D3.3

6 Draft Standard for
Local and metropolitan area networks—

8 Time-Sensitive Networking for Aerospace
Onboard Ethernet Communications

10 Unapproved draft, prepared by the

11 Time-Sensitive Networking (TSN) Task Group of IEEE 802.1

12 Developed by the

13 LAN/MAN Standards Committee

14 of the

15 IEEE Computer Society

16 Copyright ©2025 by The Institute of Electrical and Electronics Engineers, Inc. and SAE International

17

18

19

20 All rights reserved.

Important Notice

This document is an unapproved draft of a proposed IEEE Standard. IEEE hereby grants the named IEEE SA Working Group or Standards Committee Chair permission to distribute this document to participants in the receiving IEEE SA Working Group or Standards Committee, for purposes of review for IEEE standardization activities. No further use, reproduction, or distribution of this document is permitted without the express written permission of IEEE Standards Association (IEEE SA). Prior to any review or use of this draft standard, in part or in whole, by another standards development organization, permission must first be obtained from IEEE SA (stds-copyright@ieee.org). This page is included as the cover of this draft, and shall not be modified or deleted.

IEEE Standards Association
445 Hoes Lane
Piscataway, NJ 08854, USA

1 This document is an unapproved draft of a proposed IEEE Standard. As such, this document is subject to
2 change. USE AT YOUR OWN RISK! IEEE copyright statements SHALL NOT BE REMOVED from draft
3 or approved IEEE standards, or modified in any way. Because this is an unapproved draft, this document
4 must not be utilized for any conformance/compliance purposes. Permission is hereby granted for officers
5 from each IEEE Standards Working Group or Committee to reproduce the draft document developed by that
6 Working Group for purposes of international standardization consideration. IEEE Standards Department
7 must be informed of the submission for consideration prior to any reproduction for international
8 standardization consideration (stds.ipr@ieee.org). Prior to adoption of this document, in whole or in part, by
9 another standards development organization, permission must first be obtained from the IEEE Standards
10 Department (stds.ipr@ieee.org). Permission can be requested from either IEEE or SAE International at the
11 respective address below.

12 IEEE Standards Activities Department
13 445 Hoes Lane
14 Piscataway, NJ 08854, USA

15 400 Commonwealth Drive
16 Warrendale, PA 15096, USA

17

¹ **Abstract:** This standard specifies profiles of IEEE 802.1 Time-Sensitive Networking (TSN) for
² aerospace onboard bridged IEEE 802.3 Ethernet networks. The profiles select features, options,
³ configurations, defaults, protocols, and procedures of bridges, end stations, and Local Area
⁴ Networks to build deterministic networks for aerospace onboard communications.

⁵ **Keywords:** Bridged Network, IEEE 802.1Q™, LAN, local area network, MAC security, MACsec,
⁶ privacy, Virtual Bridged Network, virtual LAN, VLAN Bridge

1 Important Notices and Disclaimers Concerning IEEE Standards Documents

2 IEEE Standards documents are made available for use subject to important notices and legal disclaimers.
3 These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>),
4 appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning
5 IEEE Standards Documents.”

6 Notice and Disclaimer of Liability Concerning the Use of IEEE Standards 7 Documents

8 IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating
9 Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards
10 through an accredited consensus development process, which brings together volunteers representing varied
11 viewpoints and interests to achieve the final product. IEEE Standards are documents developed by
12 volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers
13 are not necessarily members of IEEE or IEEE SA, and participate without compensation from IEEE. While
14 IEEE administers the process and establishes rules to promote fairness in the consensus development
15 process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the
16 soundness of any judgments contained in its standards.

17 IEEE makes no warranties or representations concerning its standards, and expressly disclaims all
18 warranties, express or implied, concerning this standard, including but not limited to the warranties of
19 merchantability, fitness for a particular purpose and non-infringement. In addition, IEEE does not warrant or
20 represent that the use of the material contained in its standards is free from patent infringement. IEEE
21 standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

22 Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there
23 are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to
24 the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and
25 issued is subject to change brought about through developments in the state of the art and comments
26 received from users of the standard.

27 In publishing and making its standards available, IEEE is not suggesting or rendering professional or other
28 services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any
29 other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his
30 or her own independent judgment in the exercise of reasonable care in any given circumstances or, as
31 appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE
32 standard.

33 IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
34 EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE
35 NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
36 BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
37 WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
38 OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON
39 ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND
40 REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

1 Translations

2 The IEEE consensus development process involves the review of documents in English only. In the event
3 that an IEEE standard is translated, only the English version published by IEEE is the approved IEEE
4 standard.

5 Official statements

6 A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board
7 Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its
8 committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures,
9 symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall
10 make it clear that the presenter's views should be considered the personal views of that individual rather than
11 the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group.

12 Comments on standards

13 Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of
14 membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations,
15 consulting information, or advice pertaining to IEEE Standards documents.**

16 Suggestions for changes in documents should be in the form of a proposed change of text, together with
17 appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is
18 important that any responses to comments and questions also receive the concurrence of a balance of
19 interests. For this reason, IEEE and the members of its Societies and Standards Coordinating Committees
20 are not able to provide an instant response to comments, or questions except in those cases where the matter
21 has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any
22 person who would like to participate in evaluating comments or in revisions to an IEEE standard is welcome
23 to join the relevant IEEE working group. You can indicate interest in a working group using the Interests tab
24 in the Manage Profile & Interests area of the [IEEE SA myProject system](#).¹ An IEEE Account is needed to
25 access the application.

26 Comments on standards should be submitted using the [Contact Us](#) form.²

27 Laws and regulations

28 Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the
29 provisions of any IEEE Standards document does not imply compliance to any applicable regulatory
30 requirements. Implementers of the standard are responsible for observing or referring to the applicable
31 regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not
32 in compliance with applicable laws, and these documents may not be construed as doing so.

33 Data privacy

34 Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and
35 data ownership in the context of assessing and using the standards in compliance with applicable laws and
36 regulations.

1. Available at: <https://development.standards.ieee.org/myproject-web/public/view.html#landing>.

2. Available at: <https://standards.ieee.org/content/ieee-standards/en/about/contact/index.html>.

1 Copyrights

2 IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws.
3 They are made available by IEEE and are adopted for a wide variety of both public and private uses. These
4 include both use, by reference, in laws and regulations, and use in private self-regulation, standardization,
5 and the promotion of engineering practices and methods. By making these documents available for use and
6 adoption by public authorities and private users, IEEE does not waive any rights in copyright to the
7 documents.

8 Photocopies

9 Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to
10 photocopy portions of any individual standard for company or organizational internal use or individual, non-
11 commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center,
12 Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to
13 photocopy portions of any individual standard for educational classroom use can also be obtained through
14 the Copyright Clearance Center.

15 Updating of IEEE Standards documents

16 Users of IEEE Standards documents should be aware that these documents may be superseded at any time
17 by the issuance of new editions or may be amended from time to time through the issuance of amendments,
18 corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the
19 document together with any amendments, corrigenda, or errata then in effect.

20 Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years
21 old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of
22 some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that
23 they have the latest edition of any IEEE standard.

24 In order to determine whether a given document is the current edition and whether it has been amended
25 through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#).³ For more
26 information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

27 Errata

28 Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#).⁴ Search for standard number
29 and year of approval to access the web page of the published standard. Errata links are located under the
30 Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to
31 periodically check for errata.

32 Patents

33 IEEE Standards are developed in compliance with the [IEEE SA Patent Policy](#).⁵

34 Attention is called to the possibility that implementation of this standard may require use of subject matter
35 covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the
36 existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has
37 filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the

3. Available at: <https://ieeexplore.ieee.org/browse/standards/collection/ieee>.

4. Available at: <https://standards.ieee.org/standard/index.html>.

5. Available at: <https://standards.ieee.org/about/sasb/patcom/materials.html>.

1 IEEE SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may
2 indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without
3 compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of
4 any unfair discrimination to applicants desiring to obtain such licenses.

5 Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not
6 responsible for identifying Essential Patent Claims for which a license may be required, for conducting
7 inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or
8 conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing
9 agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that
10 determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their
11 own responsibility. Further information may be obtained from the IEEE Standards Association.

12 **IMPORTANT NOTICE**

13 IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure
14 against interference with or from other devices or networks. IEEE Standards development activities consider
15 research and information presented to the standards development group in developing any safety
16 recommendations. Other information about safety practices, changes in technology or technology
17 implementation, or impact by peripheral systems also may be pertinent to safety considerations during
18 implementation of the standard. Implementers and users of IEEE Standards documents are responsible for
19 determining and complying with all appropriate safety, security, environmental, health, and interference
20 protection practices and all applicable laws and regulations.

¹ Participants

² <<The following lists will be updated in the usual way prior to publication>>

³ At the time this standard was completed, the IEEE 802.1 working group had the following membership:

⁴

Glenn Parsons, *Chair*

⁵

Jessy Rouyer, *Vice Chair*

⁶

Janos Farkas, *Chair, Time-Sensitive Networking Task Group*

⁷

Abdul Jabbar, *Editor*

⁸

⁹ The following members of the individual balloting committee voted on this standard. Balloters may have
¹⁰ voted for approval, disapproval, or abstention.

A.N. Other

¹¹ <<The above lists will be updated in the usual way prior to publication>>

¹²

¹³

¹⁴ When the IEEE-SA Standards Board approved this standard on <dd> <month> <year>, it had the following
¹⁵ membership:

¹⁶

Chair

¹⁷

Vice-Chair

¹⁸

Past Chair

1

Secretary

2 *Member Emeritus

3 <<The above lists will be updated in the usual way prior to publication>>

4

1 Introduction

2

This introduction is not part of IEEE P802.1DP-20XX/SAE AS6675, Draft Standard for Local and metropolitan area networks—Time-Sensitive Networking for Aerospace Onboard Ethernet Communications.

3 This standard specifies profiles of IEEE 802.1 Time-Sensitive Networking (TSN) and IEEE 802.1 Security
4 standards for aerospace onboard bridged IEEE 802.3 Ethernet networks.

5 This standard was first published as IEEE Std 802.1DP-20XX.

6 This standard contains state-of-the-art material. The area covered by this standard is undergoing evolution.
7 Revisions are anticipated within the next few years to clarify existing material, to correct possible errors, and
8 to incorporate new related material. Information on the current revision state of this and other IEEE 802
9 standards may be obtained from

10 Secretary, IEEE SA Standards Board
11 445 Hoes Lane
12 Piscataway, NJ 08854
13 USA

14

7 Contents

2	1.	Overview.....	16
3	1.1	Scope.....	16
4	1.2	Purpose.....	17
5	1.3	Introduction.....	17
6	2.	Normative references	18
7	3.	Definitions	20
8	4.	Abbreviations and acronyms	21
9	5.	Conformance.....	22
10	5.1	Requirements terminology.....	22
11	5.2	Profile Conformance Statement (PCS).....	22
12	5.3	Conformance Classes.....	22
13	5.3.1	Type1 Conformance Class	23
14	5.3.2	Type2 Conformance Class	23
15	5.4	Bridge component requirements.....	23
16	5.4.1	Common Bridge component requirements	23
17	5.4.2	Asynchronous Type1 Bridge component requirements	23
18	5.4.3	Asynchronous Type2 Bridge component requirements	24
19	5.4.4	Synchronous Type1 Bridge component requirements	24
20	5.4.5	Synchronous Type2 Bridge component requirements	24
21	5.5	Bridge component options.....	24
22	5.5.1	Common Bridge component options	24
23	5.5.2	Asynchronous Type1 Bridge component options	25
24	5.5.3	Asynchronous Type2 Bridge component options	25
25	5.5.4	Synchronous Type1 Bridge component options	25
26	5.5.5	Synchronous Type2 Bridge component options	25
27	5.6	End station component requirements.....	25
28	5.6.1	Common end station component requirements	25
29	5.6.2	Asynchronous Type1 end station component requirements	26
30	5.6.3	Asynchronous Type2 end station component requirements	26
31	5.6.4	Synchronous Type1 end station component requirements	26
32	5.6.5	Synchronous Type2 end station component requirements	26
33	5.7	End station component options.....	27
34	5.7.1	Common end station component options	27
35	5.7.2	Asynchronous Type1 end station component options	27
36	5.7.3	Asynchronous Type2 end station component options	27
37	5.7.4	Synchronous Type1 end station component options	28
38	5.7.5	Synchronous Type2 end station component options	28
39	6.	Overview of Aerospace Onboard Networks.....	29
40	6.1	Introduction to Aerospace Networks	29
41	6.1.1	Current Network Architectures	29
42	6.1.2	New Network Architectures	31
43	6.2	Network Design Constraints.....	31
44	6.2.1	Performance & Technology	31
45	6.2.2	Industry Adoption	32
46	6.2.3	Regulatory Considerations	33

1	6.3	Network topologies.....	33
2	6.3.1	Number of Nodes	36
3	6.3.2	Physical Topology	36
4	6.3.3	Number of Switch Hops	37
5	6.3.4	Max Number of Streams per Switch	37
6	6.3.5	Network Redundancy	37
7	6.3.6	Redundancy Mode	37
8	6.3.7	Data Rates	37
9	6.3.8	Media type	37
10	6.3.9	Worst Case Link Utilization	38
11	6.3.10	Dissimilarity, Integrity, Maintenance, Monitoring, Security [DIMMS]	38
12	6.3.11	Certification Requirements	38
13	6.3.12	Supported Traffic types	38
14	6.4	Application and traffic characteristics	39
15	6.4.1	Traffic Type Characteristics	39
16	6.4.2	Traffic Type Analysis Summary	40
17	7.	Required functions for aerospace networks.....	42
18	7.1	Time synchronization	42
19	7.2	Traffic shaping.....	42
20	7.2.1	Per-Stream queuing and shaping at end stations	43
21	7.2.2	Per-Class queuing and shaping at end stations	43
22	7.3	Stream isolation	44
23	7.4	Active topology enforcement.....	45
24	7.5	Network redundancy.....	45
25	7.5.1	Coordination between FRER components on a network	46
26	7.6	Configuration	46
27	7.6.1	Aerospace configuration model overview	46
28	7.6.2	YANG Data Models	48
29	7.7	Management and Monitoring.....	48
30	7.7.1	Overview	48
31	7.7.2	TSN feature specific monitoring objects	49
32	Annex A	(normative) PCS proforma—IEEE Std 802.1DP Aerospace TSN Networking	53
33	A.1	Introduction.....	53
34	A.2	Abbreviations and special symbols.....	53
35	A.2.1	Status symbols	53
36	A.2.2	General abbreviations	54
37	A.3	Instructions for completing the PCS proforma	54
38	A.3.1	General structure of the PCS proforma	54
39	A.3.2	Additional information	54
40	A.3.3	Exception information	55
41	A.3.4	Conditional status	55
42	A.4	PCS proforma for IEEE Std 802.1DP—Aerospace TSN Networking	56
43	A.4.1	Implementation identification	56
44	A.4.2	Profile summary	56
45	A.4.3	Implementation summary	57
46	A.5	Bridge component implementations	58
47	A.5.1	Common Bridge component capabilities	58
48	A.5.2	Asynchronous Type1 Bridge component capabilities	59
49	A.5.3	Asynchronous Type2 Bridge component capabilities	59
50	A.5.4	Synchronous Type1 Bridge component capabilities	59
51	A.5.5	Synchronous Type2 Bridge component capabilities	60

1	A.6	End station component implementations	61
2	A.6.1	Common end station component capabilities	61
3	A.6.2	Asynchronous Type1 end station component capabilities	61
4	A.6.4	Synchronous Type1 end station component capabilities	62
5	A.6.3	Asynchronous Type2 end station component capabilities	62
6	A.6.5	Synchronous Type2 end station component capabilities	63
7	Annex B (informative)	Bibliography	64
8	Annex C (informative)	Example Aerospace Configuration	65
9	C.1	Introduction.....	65
10	C.2	Fully Centralized Aerospace Configuration	65

7 Figures

2	Figure 6-1	Commercial Aircraft Network Domains.....	29
3	Figure 6-2	Commercial Integrated Modular Avionics Depiction.....	30
4	Figure 7-1	Aerospace Stream Isolation	44
5	Figure 7-2	Aerospace Configuration Model.....	47
6	Figure C-1	Aerospace Configuration Model Example.....	66

7 Tables

2	Table 6-1	Use Case Characteristics.....	34
3	Table 6-2	Summary of Aerospace Use Cases	35
4	Table 6-3	Aerospace Traffic Type Characteristics	39
5	Table 6-4	Summary of Aerospace Traffic Types.....	40
6	Table 7-1	Number of supported streams for low stream-count Bridges	44
7	Table 7-2	Number of supported streams for high stream-count Bridges	45
8	Table 7-3	YANG data models.....	48
9	Table 7-4	Time synchronization managed objects.....	49
10	Table 7-5	Scheduled traffic managed objects	50
11	Table 7-6	PSFP stream filter managed objects	50
12	Table 7-7	PSFP stream gate managed objects	50
13	Table 7-8	PSFP flow meter managed objects	51
14	Table 7-9	FRER, per-port managed objects.....	51
15	Table 7-10	IEEE Std 802.1CB, FRER, per-stream, per-port managed objects	52
16	Table 7-11	FTT managed objects.....	52

1

2 Draft Standard for 3 Local and Metropolitan Networks — 4 Time-Sensitive Networking for 5 Aerospace Onboard Ethernet 6 Communications

7 1. Overview

8 The standardization of Ethernet communication technology in IEEE Std 802.3™, specifying transmission
9 over the physical media of individual Local Area Networks (LANs), and in IEEE Std 802.1Q™, specifying
10 Bridges that interconnect IEEE 802® LANs,¹ has facilitated widespread deployment of networks that
11 connect significantly more end stations, with significantly greater bandwidth, and at significantly reduced
12 cost compared to prior technology. All these metrics have been improved by several orders of magnitude—
13 reducing costs through the multi-vendor provision of common components (bridges, end station interfaces,
14 integrated circuit and circuit designs, connectors, and software) for a wide range of network applications.

15 The use of Ethernet communication technology in networks with high-reliability and deterministic latency
16 requirements is further supported by Time-Sensitive Networking (TSN) provisions in IEEE Std 802.1Q,
17 IEEE Std 802.1AS, IEEE Std 802.1CB, and the security provisions in IEEE Std 802.1AE and
18 IEEE Std 802.1X. The provisions in these standards can be used in various ways, and include options that
19 address different network requirements and parameters that vary by network and application scale. Network
20 design, time to deploy, component development, component selection, component validation, and
21 component configuration for a particular network can all benefit from consistent choices across similar
22 networks and network applications of the provisions, parameters, and options specified in the relevant
23 standards. A set of such choices comprises a *profile* of those standards and target networks.

24 This standard specifies profiles for use in Ethernet networks supporting aerospace onboard communications.
25 These networks and their network components have stringent verification requirements, so the profiles
26 emphasize not just what capabilities are to be available, but also what optional capabilities are not used. All
27 available capabilities can be subject to time-consuming and expensive verification, so omission of unused
28 capabilities is desirable and can be required.

29 1.1 Scope

30 This standard specifies profiles of IEEE 802.1 Time-Sensitive Networking (TSN) and IEEE 802.1 Security
31 standards for aerospace onboard bridged IEEE 802.3 Ethernet networks. The profiles select features,

¹ IEEE and IEEE 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

options, configurations, defaults, protocols, and procedures of bridges, end stations, and Local Area Networks to build deterministic networks for aerospace onboard communications.

1.2 Purpose

This standard specifies profiles for designers, implementers, integrators, and certification agencies of deterministic IEEE 802.3 Ethernet networks that support a broad range of aerospace onboard applications including those requiring security, high availability and reliability, maintainability, and bounded latency.

1.3 Introduction

The TSN suite of standards are broad ranging, and intended for use in a variety of environments that require bounded latency, synchronization, reliability, isolation, and high availability. This standard selects the TSN features that are directly applicable to Aerospace Onboard Ethernet Communications and explains how the associated TSN standards are used. This standard narrows the focus from the broad set of available TSN features to those that are applicable to aerospace onboard networks.

The standard describes use cases and functional requirements pertinent to the use of TSN in aerospace platforms. The conformance clause, Clause 5, specifies mandatory and optional features that are expected to be provided by conformant implementations of systems, system components, and system functions used in aerospace onboard Ethernet networks.

Consistent with the purpose of this standard, Aerospace OEMs and suppliers at all tiers are able to use this standard to specify and design the network and network components required to implement the systems and functions on aerospace platforms. Component and technology suppliers are expected to benefit by understanding which TSN features are required to allow OEMs and higher-tier suppliers to implement conformant aerospace onboard networks.

2. Normative references

The following referenced documents are indispensable for the application of this document (i.e., they must be understood and used, so each referenced document is cited in the text and its relationship to this document is explained). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments or corrigenda) applies.

IEEE Std 802.1AS™-2020, IEEE Standard for Local and metropolitan area networks—Timing and Synchronization for Time-Sensitive Applications.^{2,3}

IEEE Std 802.1ASdm™-2024, IEEE Standard for Local and Metropolitan Area Networks—Timing and Synchronization for Time-Sensitive Applications—Amendment 3: Hot Standby and Clock Drift Error Reduction.

IEEE Std 802.1ASdn™-2024, IEEE Standard for Local and Metropolitan Area Networks—Timing and Synchronization for Time-Sensitive Applications—Amendment 2: YANG Data Model

IEEE Std 802.1ASdr™-2024, IEEE Standard for Local and Metropolitan Area Networks—Timing and Synchronization for Time-Sensitive Applications—Amendment 1: Inclusive Terminology.

IEEE P802.1ASed Draft 2.1, IEEE Draft Standard for Local and metropolitan area networks—Timing and Synchronization for Time-Sensitive Applications—Amendment: Fault Tolerant Timing with Time Integrity, June 2025.

IEEE Std 802.1CB™-2017, IEEE Standard for Local and metropolitan area networks—Frame Replication and Elimination for Reliability.

IEEE Std 802.1CBcv™-2021, IEEE Standard for Local and metropolitan area networks—Frame Replication and Elimination for Reliability—Amendment 1: Information Model, YANG Data Model and Management Information Base Module.

IEEE Std 802.1CBdb™-2021, IEEE Standard for Local and metropolitan area networks—Frame Replication and Elimination for Reliability—Amendment 2: Extended Stream Identification Functions.

IEEE Std 802.1DCT™-2024, IEEE Standard for Local and Metropolitan Area Networks—Quality of Service Provision by Network Systems.

IEEE Std 802.1Q™-2022, IEEE Standard for Local and metropolitan area networks—Bridges and Bridged Networks.

IEEE Std 802.1Qcw™-2023, IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing.

IEEE Std 802.1Qdj™-2024, IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—Amendment 38: Configuration Enhancements for Time-Sensitive Networking.

IEEE Std 802.1Qdx™-2024, IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—Amendment 39: YANG Data Models for the Credit-Based Shaper.

² IEEE publications are available from The Institute of Electrical and Electronics Engineers (<https://standards.ieee.org/>).

³ The IEEE standards or products referred to in this clause are trademarks of The Institute of Electrical and Electronics Engineers, Inc.

¹IEEE Std 1588e™-2024, IEEE Standard for Precision Clock Synchronization Protocol for Networked
²Measurement and Control Systems—Amendment 5: MIB and YANG Modules

3

3. Definitions

For the purposes of this document, the following terms and definitions apply. The *IEEE Standards Dictionary Online* should be consulted for terms not defined in this clause.⁴

This standard makes use of the following terms defined in IEEE Std 802[®] [B4].

— end station

— frame

This standard makes use of the following terms defined in IEEE Std 802.1Q.

— Centralized Network Configuration (CNC)

— Centralized User Configuration (CUC)

— Bridge

— packet

— policing

— Stream

— Tagged frame

— Talker

The following terms are specific to this standard:

Aerospace end system: A system attached to a network onboard an aerospace platform that is an initial source or a final destination of data transmitted across that network.

NOTE—The term “aerospace end system” is used in this document to refer to aerospace systems that encompass all layers of Open Systems Interconnection (OSI) reference basic model, ISO/IEC 7498-1:1994.

Bridged end station: A system with both end station and Bridge components.

end station: A functional unit in an IEEE 802[®] [B4] network that acts as a source of, and/or destination for, link layer data traffic carried on the network (from IEEE Std 802-2014)

onboard: A system, or a set of systems, that is permanently installed onboard an aerospace platform. This does not include test or instrumentation systems installed on the ground to support platform operation.

traffic: A sequence of frames forwarded in a network.

time-aware: An adjective to describe use of time that is synchronized with other stations using a protocol (e.g., IEEE Std 802.1AS).

⁴ *IEEE Standards Dictionary Online* is available at <https://dictionary.ieee.org>.

4. Abbreviations and acronyms

The following abbreviations and acronyms are used in this standard: ⁵

ACD	Aircraft Control Domain
BTCA	Best timeTransmitter Clock Algorithm
CBS	Credit Based Shaper
C-VLAN	Customer Virtual Local Area Network
CFM	Connectivity Fault Management
CNC	Centralized Network Configuration
CUC	Centralized User Configuration
DAL	Design/Development Assurance Level
FRER	Frame Replication and Elimination for Reliability
FTT	Fault-Tolerant Timing
GM	Grandmaster
ICD	Interface Control Document
IMA	Integrated Modular Avionics
LAN	Local Area Network (IEEE Std 802® [B4])
MAC	Medium Access Control
MS	Mission System
PCS	Profile Conformance Statement
PICS	Protocol Implementation Conformance Statement
PIESD	Passenger Information and Entertainment Services Domain
PTP	Precision Time Protocol (IEEE Std. 1588)
TAS	Time Aware Shaper
TSN	Time-Sensitive Networking

⁵ The abbreviations listed include those defined in standards referenced by this standard and used in this standard.

5. Conformance

This clause specifies mandatory and optional capabilities provided by conformant implementations of systems, system components, and system functions for use in aerospace onboard Ethernet communications.

5.1 Requirements terminology

For consistency with existing IEEE and IEEE 802.1™ standards, requirements are expressed using the following terminology:

- a) **Shall** is used for mandatory requirements.
- b) **May** is used to describe implementation or administrative choices (“may” means “is permitted to,” and hence, “may” and “may not” mean precisely the same thing).
- c) **Should** is used for recommended choices (the behaviors described by “should” and “should not” are both permissible but not equally desirable choices).

Profile Conformance Statements (PCS) reflect the occurrences of the words “shall,” “may,” and “should” within the standard.

The standard avoids needless repetition and apparent duplication of its formal requirements by using **is**, **is not**, **are**, and **are not** for definitions and the logical consequences of conformant behavior. Behavior that is permitted but is neither always required nor directly controlled by an implementer or administrator, or whose conformance requirement is detailed elsewhere, is described by **can**. Behavior that never occurs in a conformant implementation or system of conformant implementations is described by **cannot**. The word **allow** is used as a replacement for the phrase “Support the ability for,” and the word **capability** means “can be configured to.”

5.2 Profile Conformance Statement (PCS)

A claim of conformance to a profile specified in this standard attests to the implementation of a system, system component, or system functionality specified in referenced standards with the profile’s selection of, and constraints upon, system parameters and options.

The supplier of an implementation that is claimed to conform to this standard shall provide the information necessary to identify both the supplier and the implementation, and shall complete a copy of the relevant PCS proforma provided in Annex A of this standard, together with the Protocol Implementation Conformance Statements (PICS) for the referenced standards, as identified in the PCS.

5.3 Conformance Classes

These profiles include conformance requirements and options for bridges and end stations that support a multitude of aerospace use cases. While some TSN features are required for certain use cases, the use of such features could be non-optimal in other use cases. Therefore, this standard defines two profiles applicable to end stations and Bridge components. The asynchronous profile defines the requirements for aerospace networks that do not require synchronous TSN features for operation. The synchronous profile defines the requirements for aerospace networks that require synchronous TSN features for operation. The synchronous profile is a superset of the asynchronous profile and includes all the requirements of the asynchronous profile. In this regard, a device conformant to the synchronous profile also supports requirements defined in the asynchronous profile. The asynchronous profile, is therefore a subset of the synchronous profile.

NOTE—The asynchronous profile implementations could use time synchronization (gPTP) to enable temporal integrity of application data.

In each profile, this standard recognizes two types of devices, herein defined as Type1 and Type2, to distinguish more capable devices with abundant resources from less capable devices that are often resource constrained. Both types of classes apply to the two profiles, resulting in total of 4 potential conformance classes for each conformant component: asynchronous Type1, asynchronous Type2, synchronous Type1, and synchronous Type2. Aerospace implementations could include a mixture of Type1 and Type2 conformant devices on an aerospace platform as needed to provide the required system capabilities.

5.3.1 Type1 Conformance Class

The Type1 conformance class imposes fewer requirements than the Type2 conformance class and is expected to be used for less performant systems. Requirements for Type1 devices are described for Bridges in 5.4.2, 5.4.4, 5.5.2 and 5.5.4; and for end stations in 5.6.2, 5.6.4, 5.7.2 and 5.7.4.

5.3.2 Type2 Conformance Class

The Type2 conformance class imposes more requirements than the Type1 conformance class and is expected to be used for more performant systems. Requirements for Type2 devices are described for Bridges in 5.4.3, 5.4.5, 5.5.3 and 5.5.5; and for end stations in 5.6.3, 5.6.5, 5.7.3 and 5.7.5.

5.4 Bridge component requirements

5.4.1 Common Bridge component requirements

A bridge component implementation claiming conformance to any conformance class in this document shall:

- a) Support VLAN Bridge component requirements according to 5.4 of IEEE Std 802.1Q-2022, except for items g), h), and o)
- b) Support active topology enforcement as specified in 7.4
- c) Support C-VLAN component requirements according to 5.5 of IEEE Std 802.1Q-2022, except for item d)
- d) Allow the FDB to contain Static and Dynamic VLAN Registration Entries for a minimum of 64 VIDs, according to 8.8 of IEEE Std 802.1Q-2022
- e) Support the strict priority algorithm for transmission selection on each port for each traffic class according to 8.6.8.1 of IEEE Std 802.1Q-2022
- f) Support the operation of the credit-based shaper algorithm according to 8.6.8.2 of IEEE Std 802.1Q-2022 on all ports as the transmission selection algorithm for at least 2 traffic classes
- g) Support stream identification components according to 5.3 of IEEE Std 802.1CB-2017 on all ports
- h) Support Per-Stream Filtering and Policing (PSFP) according to 8.6.5.2 and 8.6.6 of IEEE Std 802.1Q-2022
- i) Support minimum number of stream identification and filtering entries as defined in Table 7-1
- j) Support the management entities for configuration of bridge functions as specified in 7.6
- k) Support the monitoring of PSFP as specified in 7.7.2.4

NOTE—For asynchronous components, the state machines for stream gate control as specified in 8.6.10 of IEEE Std 802.1Q-2022 are not required to be supported. The default value of stream gate state is open.

5.4.2 Asynchronous Type1 Bridge component requirements

A bridge component claiming conformance to asynchronous Type1 class of this document, shall

- a) Support common bridge component requirements according to 5.4.1
- b) Support at least four queues according to 8.6.6 of IEEE Std 802.1Q-2022

1 5.4.3 Asynchronous Type2 Bridge component requirements

2 A bridge component claiming conformance to asynchronous Type2 class of this document, shall

- 3 a) Support asynchronous Type1 bridge component requirements according to 5.4.2
- 4 b) Support FRER according to 5.15 of IEEE Std 802.1CB-2017
- 5 c) Support monitoring for FRER as specified in 7.7.2.5

6 5.4.4 Synchronous Type1 Bridge component requirements

7 A bridge component claiming conformance to synchronous Type1 class of this document, shall

- 8 a) Support common bridge component requirements according to 5.4.1
- 9 b) Support eight queues according to 8.6.6 of IEEE Std 802.1Q-2022
- 10 c) Support at least 2 PTP Instances on all physical ports according to 5.4.1 items a) through f) and h) of
- 11 IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 12 d) Implement the PortSyncSyncSend state machine on all physical ports according to 10.2.12 of IEEE
- 13 Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 14 e) Support media-dependent timing and synchronization methods for full-duplex IEEE 802.3 links
- 15 according to 5.5 item a), b), and e) of IEEE Std 802.1AS-2020 as amended by IEEE Std
- 16 802.1ASdm-2024
- 17 f) Support a Fault-Tolerant Timing entity for all PTP Instances according to IEEE P802.1ASed
- 18 g) Implement specifications for externalPortConfigurationEnabled value of true for all ports according
- 19 to 10.3.1 of IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 20 h) Support the state machines for stream gate control as specified in 8.6.10 of IEEE Std 802.1Q-2022
- 21 i) Support the enhancements for scheduled traffic as specified in 8.6.8.4 of IEEE Std 802.1Q-2022 on
- 22 all ports
- 23 j) Support the state machines for scheduled traffic as specified in 8.6.9 of IEEE Std 802.1Q-2022
- 24 k) Support the monitoring requirements of scheduled traffic as specified in 7.7.2.2
- 25 l) Support the monitoring requirements of the Fault-Tolerant Timing entity as specified in 7.7.2.6
- 26 m) Support the monitoring requirements of time synchronization as specified in 7.7.2.1

27 5.4.5 Synchronous Type2 Bridge component requirements

28 A bridge component claiming conformance to synchronous Type2 class of this document, shall

- 29 a) Support synchronous Type1 bridge component requirements according to 5.4.4
- 30 b) Support at least 3 PTP Instances on all physical ports according to 5.4.1 items a) through f) and h) of
- 31 IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 32 c) Support FRER according to 5.15 of IEEE Std 802.1CB-2017
- 33 d) Support monitoring for FRER as specified in 7.7.2.5

34 5.5 Bridge component options

35 5.5.1 Common Bridge component options

36 A bridge component implementation claiming conformance to any conformance class in this document may:

- 37 a) Allow translation of VIDs through support of the VID Translation Table or through support of both
- 38 the VID Translation Table and Egress VID translation table on one or more Bridge Ports according
- 39 to 6.9 of IEEE Std 802.1Q-2022

40

1 5.5.2 Asynchronous Type1 Bridge component options

2 A bridge component implementation claiming conformance to asynchronous Type1 conformance class in
3 this document may:

- 4 a) Support any of the common Bridge component options according to 5.5.1
- 5 b) Support the operation of the credit-based shaper algorithm according to 8.6.8.2 of IEEE Std 802.1Q-
6 2022 on all ports as the transmission selection algorithm for all traffic classes
- 7 c) Support eight queues according to 8.6.6 of IEEE Std 802.1Q-2022

8 5.5.3 Asynchronous Type2 Bridge component options

9 A bridge component implementation claiming conformance to asynchronous Type2 conformance class in
10 this document may:

- 11 a) Support any of the common Bridge component options according to 5.5.1
- 12 b) Support any of the asynchronous Type1 Bridge component options according to 5.5.2
- 13 c) Support Active Destination MAC and VLAN Stream identification functions for encoding and
14 decoding packets according to 6.6 of IEEE Std 802.1CB-2017
- 15 d) Support minimum number of stream identification and filtering entries as defined in Table 7-2

16 5.5.4 Synchronous Type1 Bridge component options

17 A bridge component implementation claiming conformance to synchronous Type1 conformance class in this
18 document may:

- 19 a) Support any of the common Bridge component options according to 5.5.1
- 20 b) Support the operation of the credit-based shaper algorithm according to 8.6.8.2 of IEEE Std 802.1Q-
21 2022 on all ports as the transmission selection algorithm for all traffic classes
- 22 c) Support at least 3 PTP Instances on all physical ports according to 5.4.1 items a) through f) and h) of
23 IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 24 d) Support the Grandmaster PTP Instance capability according to 5.4.2 item c) of IEEE Std 802.1AS-
25 2020 as amended by IEEE Std 802.1ASdm-2024

26 5.5.5 Synchronous Type2 Bridge component options

27 A bridge component implementation claiming conformance to synchronous Type2 conformance class in this
28 document may:

- 29 a) Support any of the common Bridge component options according to 5.5.1
- 30 b) Support any of the synchronous Type1 Bridge component options according to 5.5.4
- 31 c) Support Active Destination MAC and VLAN Stream identification functions for encoding and
32 decoding packets according to 6.6 of IEEE Std 802.1CB-2017
- 33 d) Support minimum number of stream identification and filtering entries as defined in Table 7-2

34 5.6 End station component requirements

35 5.6.1 Common end station component requirements

36 An end station component claiming conformance to any conformance class in this document shall

- 37 a) Support a minimum of two traffic classes on all ports
- 38 b) Support the strict priority transmission selection algorithm according to 8.6.8.1 of IEEE Std 802.1Q-
39 2022 on all ports for all traffic classes

- 1 c) Support the operation of the credit-based shaper algorithm according to 8.6.8.2 of IEEE Std 802.1Q-
2 2022 on all ports as the transmission selection algorithm for at least two traffic classes
- 3 d) Support management entities for configuration of the end station as specified in 7.6
- 4 e) Support a minimum of 8 Per-Stream queues according to the talker queuing model according to
5 34.6.1.1 of IEEE Std 802.1Q-2022
- 6 f) Support the operation of the credit-based shaper algorithm according to 8.6.8.2 of IEEE Std 802.1Q-
7 2022 for at least two per-stream queues

8 5.6.2 Asynchronous Type1 end station component requirements

9 An asynchronous Type1 end station that conforms to the provisions of this standard shall:

- 10 a) Support the common end station component requirements of 5.6.1

11 5.6.3 Asynchronous Type2 end station component requirements

12 An asynchronous Type2 end station that conforms to the provisions of this standard shall:

- 13 a) Support the asynchronous Type1 end station requirements of 5.6.2
- 14 b) Support the FRER Talker end system required behaviors as specified in 5.6 of IEEE Std 802.1CB-
15 2017
- 16 c) Support the FRER Listener end system required behaviors as specified in 5.9 of IEEE Std 802.1CB-
17 2017
- 18 d) Support the monitoring requirements of FRER as specified in 7.7.2.5

19 5.6.4 Synchronous Type1 end station component requirements

20 A synchronous Type1 end station that conforms to the provisions of this standard shall:

- 21 a) Support the common end station component requirements of 5.6.1
- 22 b) Support at least 2 PTP Instances on all physical ports according to 5.4.1 items a) through f) and h) of
23 IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 24 c) Support media-dependent timing and synchronization methods for full-duplex IEEE 802.3 links
25 according to 5.5 item a), b), and e) of IEEE Std 802.1AS-2020 as amended by IEEE Std
26 802.1ASdm-2024
- 27 d) Support a Fault-Tolerant Timing entity for all PTP Instances according to IEEE P802.1ASed
- 28 e) Implement specifications for externalPortConfigurationEnabled value of true for all ports according
29 to 10.3.1 of IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 30 f) Support end station requirements for enhancements for scheduled traffic according to 5.25 of IEEE
31 Std 802.1Q-2022
- 32 g) Support the monitoring requirements of scheduled traffic as specified in 7.7.2.2
- 33 h) Support the monitoring requirements of the Fault-Tolerant Timing entity as specified in 7.7.2.6
- 34 i) Support the monitoring requirements of time synchronization as specified in 7.7.2.1

35 5.6.5 Synchronous Type2 end station component requirements

36 A synchronous Type2 end station that conforms to the provisions of this standard shall:

- 37 a) Support the synchronous Type1 end station component requirements of 5.6.4
- 38 b) Support at least 3 PTP Instances on all physical ports according to 5.4.1 items a) through f) and h) of
39 IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 40 c) Support a Fault-Tolerant Timing entity for all PTP Instances according to IEEE P802.1ASed

- 1 d) Support the FRER Talker end system required behaviors as specified in 5.6 of IEEE Std 802.1CB-
2 2017
- 3 e) Support the FRER Listener end system required behaviors as specified in 5.9 of IEEE Std 802.1CB-
4 2017
- 5 f) Support the monitoring requirements of FRER as specified in 7.7.2.5,

6 5.7 End station component options

7 5.7.1 Common end station component options

8 An end station component claiming conformance to any conformance class in this document may:

- 9 a) Support Customer VLAN tags
- 10 b) Support the assignment of different VID and PCP values to different streams
- 11 c) Support the assignment of different destination MAC address to different streams
- 12 d) Support eight queues according to 8.6.6 of IEEE Std 802.1Q-2022
- 13 e) Support a minimum of 16 Per-Stream queues according to the talker queuing model as specified in
14 34.6.1.1 of IEEE Std 802.1Q-2022
- 15 f) Support the operation of the credit-based shaper algorithm according to 8.6.8.2 of IEEE Std 802.1Q-
16 2022 for all per-stream queues

17 5.7.2 Asynchronous Type1 end station component options

18 An asynchronous Type1 end station that conforms to the provisions of this standard may:

- 19 a) Support any of the common end station component options according to 5.7.1

20 5.7.3 Asynchronous Type2 end station component options

21 An asynchronous Type2 end station that conforms to the provisions of this standard may:

- 22 a) Support any of the common end station component options according to 5.7.1
- 23 b) Support operation of the per-stream credit-based shaper algorithm for more than one stream
24 according to talker behavior as specified in 34.6.1.1 of IEEE Std 802.1Q-2022
- 25 c) Support FRER stream splitting function as specified in 7.7 of IEEE Std 802.1CB-2017 on more than
26 one port and for some number of Compound Streams greater than 1
- 27 d) Support FRER talker end system required as specified in 5.6 of IEEE Std 802.1CB-2017 on more
28 than one port
- 29 e) Support FRER talker end system required as specified in 5.6 of IEEE Std 802.1CB-2017 for some
30 number of Compound Streams greater than 1
- 31 f) Support FRER listener end system required behaviors as specified in 5.9 of IEEE Std 802.1CB-2017
32 on more than one port
- 33 g) Support FRER listener end system required behaviors as specified in 5.9 of IEEE Std 802.1CB-2017
34 for some number of Compound Streams greater than 1
- 35 h) Support a minimum of 64 Per-Stream queues according to the talker queuing model specified in
36 34.6.1.1 of IEEE Std 802.1Q-2022

1 5.7.4 Synchronous Type1 end station component options

2 A synchronous Type1 end station that conforms to the provisions of this standard may:

- 3 a) Support any of the common end station component options according to 5.7.1
- 4 b) Support at least 3 PTP Instances on all physical ports according to 5.4.1 items a) through f) and h) of
5 IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 6 c) Implement the PortSyncSyncSend state machine on all physical ports according to 10.2.12 of IEEE
7 Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024
- 8 d) Support the Grandmaster PTP Instance capability according to 5.4.2 item c) of IEEE Std 802.1AS-
9 2020 as amended by IEEE Std 802.1ASdm-2024

10 5.7.5 Synchronous Type2 end station component options

11 A synchronous Type2 end station that conforms to the provisions of this standard may:

- 12 a) Support any of the common end station component options according to 5.7.1
- 13 b) Support any of the synchronous Type1 end station component options according to 5.7.4
- 14 c) Support FRER stream splitting function as specified in 7.7 of IEEE Std 802.1CB-2017 on more than
15 one port and for some number of Compound Streams greater than 1
- 16 d) Support FRER talker end system required as specified in 5.6 of IEEE Std 802.1CB-2017 on more
17 than one port
- 18 e) Support FRER talker end system required as specified in 5.6 of IEEE Std 802.1CB-2017 for some
19 number of Compound Streams greater than 1
- 20 f) Support FRER listener end system required behaviors as specified in 5.9 of IEEE Std 802.1CB-2017
21 on more than one port
- 22 g) Support FRER listener end system required behaviors as specified in 5.9 of IEEE Std 802.1CB-2017
23 for some number of Compound Streams greater than 1
- 24 h) Support a minimum of 64 Per-Stream queues according to the talker queuing model specified in
25 34.6.1.1 of IEEE Std 802.1Q-2022

6. Overview of Aerospace Onboard Networks

This clause provides an overview of aerospace onboard networks (6.1), their design constraints (6.2), and a summary of use cases (6.3, 6.4). The objective of this clause is to support the selections made by profiles defined in this standard.

NOTE—This clause does not limit the aerospace profiles to the use cases described within the clause. The profiles defined by Clause 5 of this standard are expected to be used by industry for all relevant applications.

6.1 Introduction to Aerospace Networks

Aerospace network architectures can be broadly categorized by use cases from either a commercial or a military perspective and analyzed from either a current or a future perspective.

6.1.1 Current Network Architectures

In this document, “current” is used to describe the state of aerospace systems that existed at the time of writing this standard.

Current network architectures in aerospace are often domain based, wherein a domain defines a set of functional communication blocks (e.g. aircraft control domain, vehicle management domain, etc.). Domains are isolated by physically separate networks. Furthermore, within a given domain there could be sub-domains that are also segregated into physically separate networks. For example, in the aircraft control domain, the fly-by-wire (or flight control) network is a separate network from the avionics network.

The current aerospace use cases also limit the use of Ethernet to lower criticality communications, which are not necessarily flight critical. For example, fly-by-wire networks on existing aircraft are based on non-Ethernet data buses.

6.1.1.1 Commercial Aircraft

Networks are used in commercial aircraft to support varying levels of capabilities from supporting passenger entertainment to the actual control of the aircraft. Modern commercial aircraft can be subdivided into three networking domains: Aircraft Control Domain (ACD), Airline Information Services Domain (AISD), and the Passenger Information and Entertainment Services Domain (PIESD) as shown in Figure 6-1.




Figure 6-1—Commercial Aircraft Network Domains

The Aircraft Control Domain (ACD) networks host equipment that contribute to the safe flight of the aircraft. Functions typically hosted on the ACD network include electronic flight display systems, engine monitoring and alerting systems, flight management systems, flight controls, and other control systems that are housed outside of the passenger cabin. Due to the high criticality of the functions hosted, the ACD network has high safety requirements and deterministic⁶ behavior is required.

In the ACD, networks were initially brought on the aircraft in order to reduce size, weight, and power (SWaP). Before that, functions allocated to dedicated equipment were connected by low-bandwidth point to point data buses such as ARINC 429 or RS-485. Modern aircraft often employ Integrated Modular Avionics (IMA) that provides shared resources and reduces the amount of equipment and wiring on the aircraft. In an IMA system, a general purpose processor is used to host software applications from multiple systems and a high-speed network provides an interconnect between the IMA processing, other function-specific equipment and to data concentrators that provide connections to legacy interfaces. SWaP savings occur due to the reduced equipment count and a reduction in wiring due to consolidation. Figure 6-2 depicts a notional IMA system with processing elements, network switches and data concentrators.




Figure 6-2—Commercial Integrated Modular Avionics Depiction

The Airline Information Service Domain (AISD) supports non-essential airline operational activities. It typically provides a general purpose processing platform as well as connectivity off the aircraft and between the other domains on the network. The AISD has high security requirements, but limited safety and determinism requirements due to the non-essential functions supported.

The Passenger Information and Entertainment Services Domain (PIESD) provides passenger network and entertainment services. On large commercial aircraft, this includes supporting the needs of hundreds of passengers. This drives high performance requirements. Interestingly, the PIESD has high availability requirements based on customer expectations.

6.1.1.2 Military Aircraft

Military aircraft also use onboard networks to support functionality from the flight critical to mission oriented. A military aircraft can be subdivided into two domains: Air Vehicle System (AVS) and Mission System (MS). The AVS of the military aircraft is similar to the ACD of commercial aircraft. It encompasses the systems necessary for safe flight of the aircraft.

The Mission System of the military aircraft is responsible for supporting the varied missions of the aircraft. Depending on the type of aircraft, this could be delivering a weapon, search-and-rescue operations, and transport of equipment or personnel. The requirements for the MS network vary based on the mission

⁶ The meaning of determinism can vary with the use case and might range from microsecond timing control to bounded timing behavior in the milliseconds range.

1 equipment installed. The MS equipment can include one or more high performance mission computers and
2 typically has higher bandwidth needs than the AVS.

3 6.1.2 New Network Architectures

4 As described in 6.1, the current aerospace network architectures tend to be domain based with multiple sub-
5 domains in each domain. This poses a challenge to platforms that require significant inter-domain
6 communications coupled with more stringent size, weight and power, and cost (SWaP-C) requirements.
7 Zonal architectures provide one solution to address these challenges and reduce the cabling needs in the
8 aircraft while simultaneously converging the different data buses.

9 Traditional aerospace system architectures have evolved from a domain or functional approach where each
10 system was designed in isolation and overlaid onto the vehicle hardware in such a way that independent
11 interconnects were often provided in the same physical areas. However, more recent approaches in civil,
12 military, and also satellite platforms, have adopted a zonal approach where data is consolidated locally and
13 communicated over shared buses between zones, often involving shared I/O and processing components.
14 This zonal approach relies on logical separation of functions over a shared infrastructure rather than on
15 physical separation as has traditionally been the case and reduces the duplication of interconnect
16 infrastructure to provide the required level of fault-tolerance. By supporting the partitioning of traffic flows,
17 TSN supports the convergence of application functions onto a single physical network to reduce weight and
18 cost by eliminating separate physical networks. In an example of this approach, it might be possible to
19 envisage a flight control or weapon release function sharing network resources with a video distribution
20 system.

21 Time-sensitive networking enables features that are required for the full range of use cases and traffic types
22 to implement functions with a single network technology. Thus, adoption of TSN would allow for a
23 significant increase in the scale of onboard Ethernet networks (i.e., the number of end stations, Bridges, and
24 streams).

25 6.2 Network Design Constraints

26 Although there is considerable variability in the requirements and use cases of commercial and military
27 aircraft, the aerospace profiles of TSN attempt to balance the requirements of these use cases.

28 As in any system, the primary purpose of the network is to support the system and enable it to fulfill its
29 design objectives. The functional aspects of this are ultimately measured through technical performance
30 provided by the networking technology, typically interpreted as the ability to transport data from A to B in a
31 time T , however this performance needs to be measured against market factors as well as regulatory
32 constraints imposed on the aerospace industry. These factors are discussed here briefly to provide an
33 overview of the design constraints that frame the aerospace TSN profiles.

34 6.2.1 Performance & Technology

35 Performance is addressed here through quantifiable physical characteristics whereas technology is addressed
36 through qualitative measures related to the use of the technology in an avionics system.

37 Each unique use case has differing requirements related to the bandwidth needs of connected nodes, the
38 latency required for transmission of data through the network, and for the level of determinism needed to
39 support individual applications. Bandwidth needs for MS are often orders of magnitude greater than for
40 ACD and the aggregate bandwidth needs for PIEDS are increasing, as driven by passenger expectations and
41 demand.

Hand in hand with the increased bandwidth needs for mission or passenger networks, the need for tight control of latency and jitter to support streaming services, whether this be for sensor data or for audio and video streams, drives the need for quality-of-service provision. Commercial transport aircraft, and some military platforms, have been using the quality-of-service provisions of ARINC 664 Part 7 [B3] for many years to provide bounded latency determinism to support aircraft system functions and this is expected to be expanded by the addition of closed loop control functions that require strict delivery deadlines associated with mechanical and electronic control systems.

Determinism can also be considered to include the need for guaranteed delivery, and whilst true guaranteed delivery has typically been deferred to individual applications and aircraft functions, increased availability of data through provision of redundant data paths and redundant data sources are the predominant means of providing data delivery in the aerospace network.

Demonstration of determinism, or at least proof thereof, has been central to the regulatory framework for many years and widespread adoption of what is essentially an asynchronous communication medium places stringent requirements on aerospace system designers to show aviation safety authorities, either by demonstration or by mathematical analysis, that network latencies can meet the safety requirements of the systems hosted on the various aircraft networks.

Security is rapidly becoming a central theme for aerospace systems and security features common in modern infrastructure networks are expected to be adopted in aerospace networks. Whether this is through authenticated access mechanisms and secure networks, or secure partitioning of network domains, physical security is no longer going to be the default operating paradigm.

Central to the reason for adoption of Ethernet as the preferred networking technology for aerospace networks, as has been seen over the last 20-30 years, are the levels of standardization and interoperability seen amongst a wide range of suppliers, as well as the ability to accommodate physical as well as functional growth that this standardization has brought. The availability of integration and test equipment and tools brought over from telecommunications, industrial and automotive markets also plays a large part in the attractiveness of Ethernet based networks to the aerospace industry.

6.2.2 Industry Adoption

The adoption of networking technologies in the aerospace industry is driven by clear technical and economic advantages that are made more compelling by the development of profiles specifically targeting aerospace applications.

TSN is not a separate standard but comprises a set of amendments to the IEEE standard for Bridges and Bridged Networks to support time-aware functions. With the wide set of features that comprise TSN it is imperative that both operators and suppliers agree on a subset of the standards that are needed to avoid a situation where different components claim to support TSN but do not support the same set of TSN standards and are not inter-operable at the equipment level. The development of an industry profile to constrain the use of TSN standards is therefore a critical component that leads to a uniform supplier base to minimize the developmental and operating costs for aerospace networks.

Flexibility to support multiple traffic profiles with a single networking technology that is widely available and conforms to open standards, notwithstanding any dissimilarity needs, reduces the life-cycle costs of the aircraft by limiting variation in technology and equipment for maintenance and support tasks.

The larger industrial ecosystem that results from the use of open standards, and the natural evolution that arises from sharing these with wider industry, leads to more reliable supply chain options and longevity in that supply chain to support the long service life that is expected in the aerospace industry.

1 6.2.3 Regulatory Considerations

2 The use cases described in section 6.3 cover the full range of aviation functional hazard classifications
3 ranging from no functional effect through to catastrophic effect. An aerospace TSN network therefore needs
4 to be developed following processes agreed with safety authorities responsible for oversight of the selected
5 application. Enabling common profiles of TSN for use in aerospace industry makes it possible to gain
6 consensus between users of the technology and the applicable regulatory authorities. It is not in the scope of
7 this standard to provide support for demonstrating the compliance of a TSN implementation with the
8 appropriate regulations governing the particular application.

9 Central to the arguments for safety of the systems supported by the TSN network are established
10 mechanisms for analyzing the probability of faults that lead to impaired system functionality, whether this
11 relates to the equipment providing the network services or to the behavior of the functions implemented on
12 that equipment. With regard to the functions provided by TSN, defining the constraints within which these
13 functions operate greatly simplifies the effort required to demonstrate a level of determinism appropriate to
14 the intended scope of operation and to thereby analyze the effects of failures associated with each of the
15 performed functions.

16 Whether this relates to such failures as loss of synchronization and the methods needed to reduce the chance
17 of this to an acceptable level, or the failure of filtering mechanisms in equipment that forms a part of the
18 network, techniques can be agreed for the analysis of these failures and then reused across similar
19 applications.

20 Without involvement of industry or government safety authorities, or details of specific network
21 implementations, it is not possible or appropriate to propose or describe methods for achieving regulatory
22 approval for the application of TSN networks in aerospace applications. The purpose of the specified TSN
23 profiles is therefore limited to supporting commonality between applications and reducing the number of
24 analyses that need to be considered.

25 6.3 Network topologies

26 Network topologies for a range of aerospace platform use cases have been analyzed and are summarized
27 here to inform the reader of potential use cases that have been considered in the development of the TSN
28 profiles. The inclusion of a use case does not necessarily mean that a TSN profile supports the use case.
29 Similarly, the exclusion of a use case does not imply that it is not supported by a TSN profile.

30 The aerospace use cases examined to develop a summary of use cases are listed below. Abbreviations are
31 used as described in 6.1.1 above.

- 32 — Small Business Aircraft - ACD/AISD
- 33 — Large Passenger Aircraft - ACD/AISD
- 34 — Large Passenger Aircraft - PIESD
- 35 — Small and Combat Military Network - AVS
- 36 — Small and Combat Military Network - MS
- 37 — Large Military Network - MS
- 38 — Unmanned Military Network - AVS & MS
- 39 — Rotary Wing Aircraft - AVS
- 40 — Rotary Wing - MS
- 41 — Satellite Network
- 42 — Fibre Channel over TSN Backbone (AS6509)

¹The individual use cases can be analyzed from the perspective of various qualitative and quantitative
²characteristics to provide fair comparisons. The characteristics defined in Table 6-1 denote characteristics of
³the physical medium.

Table 6-1—Use Case Characteristics

Characteristic	Description
Number of Nodes	Denotes the total number of networking nodes in an instantiation of the use case. Includes both end stations and Bridges. Specified as a range or a maximum value.
Physical Topology	Denotes the type of physical topology in use, where “physical topology” represents the hardware level connectivity between devices. Examples include star, ring, mesh, and point-to-point/multipoint. One or more topologies can be specified.
Number of Switch Hops	Denotes the number of hops between source and destination. Specified as a range or a maximum value.
Max Number of Streams per Switch	Denotes the number of unique data streams traversing a Bridge in the network. Each unique stream requires the Bridge to perform stream identification, stream policing, and optionally stream shaping. These functions serve the overall aerospace requirement that the Bridge is able to maintain isolation between unique data streams and provide guaranteed quality of service for each data stream. Specified as a range or a maximum value.
Network Redundancy	Describes the network redundancy architecture in the current instantiations of the use case. One or more redundancy architectures can be specified.
Redundancy Mode	Denotes the mode of redundancy. Options include - standby: Transmitter-receiver pair is connected via multiple paths. Upon detection of failure in one path, transmissions are switched to another path. Also referred to as bus fail-over, - hot-active: data is transmitted on multiple paths. Receivers select one of the available copies. Also referred to as frame fail-over, - active-active with voting: data is transmitted on multiple paths. Receivers process all frames and vote on the content. One or more modes can be specified.
Data Rates	Denotes the data rate(s) of the physical media. Can be specified as one or more rates
Media type	Denotes the type of media, which can include the physical medium as well as MAC protocol. Examples include 100BASE-TX, Shielded Twisted Pair. Can be specified as one or more media types.
Worst Case Link Utilization	Denotes the link utilization of the most congested link in the network. Due to aerospace certification requirements, the worst case link utilization as designed/configured can be different from the worst case utilization as realized on the wire. This field can be used to specify both the “as configured” and “as realized on wire” variants of the link utilization. Specified as a range or maximum value.
Dissimilarity, Integrity, & Security	When applicable, denotes the use of dissimilarity, integrity, & security features. Additionally, the method by which such a feature is achieved in the current instantiation of the use case can be specified.
Maintenance and Monitoring	When applicable, denotes the use of maintenance and monitoring features. Additionally, the method by which such a feature is achieved in the current instantiation of the use case can be specified.

Table 6-1—Use Case Characteristics (continued)

Characteristic	Description
Certification Requirements	Specify if any certification requirements apply to this use case. Specify if it is Mandatory, Desired, Do Not Care.
Supported Traffic types	Listing of Traffic Types from section 6.4 that exist in this use case.

¹ NOTE—Aerospace uses the term "Switch" to refer to Layer-2 bridges. In this standard, all normative text uses the term "Bridge". Only the informative text describing the aerospace applications uses the term "Switch"

³ The use case characteristics presented during development of this standard [B5] are summarized in Table 6-
⁴ 2 and discussed in the following sub-sections. The list is not intended to be exhaustive, but provides typical
⁵ use cases considered sufficient to drive development of the standard.

Table 6-2—Summary of Aerospace Use Cases

Characteristic	Current Use		Known/ Desired New Use	Use case driving the most restrictive bound
	Lower Bound	Upper Bound		
Number of Nodes	5	100	500	Large Passenger Aircraft (ACD)
Physical Topology	Bus (command/response protocol), Point-to-point/ multipoint, Ring (daisy chained), switched star or combination		Hybrid - Ring and Star	N/A
Number of Switch Hops	0	5	15-30	Large Passenger Aircraft (PIESD)
Max Number of Streams per Switch	50	2000	4096	Large Passenger Aircraft (ACD)
Network Redundancy	Two independent networks (A,B). End systems are dual homed to redundant LANs (ARINC664 part 7); Fault- tolerant Ring; None on point-to-point links. Subsystem or full system level redundancy (dual, triple, or quad)		same as current use cases	All fault-tolerant use cases
Redundancy Mode	Bus Failover (Hot Standby), Frame Failover (Hot Active); Hot Active with voting		same as current use	DAL* A/B systems
Data Rates	10 Kbps	1 Gbps	100 Gbps	MIL-STD-1553 and Satellites on the low bound. Military MS on the high end.
Media type	Copper: 1394,1553, RS-485/422, ARINC 429/629, Ethernet. Multimode Fiber: Fibre Channel, 100BASE- SX and 1000BASE-SX		Optical fiber for higher data rates	All aircraft
Worst Case Link Utilization	95% (worst case-configured) 80% (realized on the wire); higher for deterministic buses		reduced to support application growth	Large passenger air- craft for configured, Military Flight Networks for realized

Table 6-2—Summary of Aerospace Use Cases (continued)

Characteristic	Current Use		Known/ Desired New Use	Use case driving the most restrictive bound
	Lower Bound	Upper Bound		
Dissimilarity, Integrity, & Security	No dissimilarity, integrity, or security features	Dissimilarity in design/implementation, high integrity additions, monitoring, security for isolation between assurance levels and cross-domain traffic	no change	Flight critical systems (e.g. ACD in large passenger aircraft, or AVS in military vehicles)
Maintenance and Monitoring	No maintenance or monitoring functions	Monitoring/Maintenance with SNMP or other means	Mandatory MIBs for TSN Network	Systems requiring high utilization.
Certification Requirements	None, self certified	HW/SW design and development assurance; IMA and Safety	no change	Passenger Aircraft (ACD)
Supported Traffic types	All traffic types		no change	All aircraft

*Design/Development Assurance Level according to SAE ARP4754 [B9]

6.3.1 Number of Nodes

Control domains (ACD or AVS) typically have between 10 and 100 nodes depending upon the size and extent of the network and this is expected to remain constant going forward in time. The lower bound represents smaller military vehicle and satellite applications but these are expected to increase as more systems are added to the main networks.

Going forward the main driver for expanding the network comes from large passenger aircraft where airline and passenger information and entertainment networks (AISD & PIESD) are expected to grow as airlines compete through provision of improved passenger experiences.

6.3.2 Physical Topology

Almost all conceivable network topologies can be found across the aerospace use cases examined, and this is expected to remain the case going forward.

The most common topology encountered is that of a switched star, with larger networks cascading switches so that traffic traverses a number of switch hops to reach its final destination. Ring networks are also important, particularly where switches are impractical or where bandwidth demands are high, providing one of the main drivers for Bridged end stations. Ring networks are most commonly found in military applications. Point to point links are also found where bandwidth requirements or weight restrictions make the use of switches impractical.

Redundancy and availability requirements complicate the network topology discussion. Civil passenger aircraft often employ redundant networks with dual-port end stations as typified by ARINC 664 Part 7 [B3] networks. Elsewhere, redundant paths can be seen to provide redundancy in a single unified network. Both of these examples further drive the need for Bridged end stations and frame redundancy mechanisms.

1 6.3.3 Number of Switch Hops

2 The number of switch hops is largely an outcome of the size of the network and a trade off between switch
3 size/capacity and wire-weight. Latency and determinism requirements have tended to put an upper bound on
4 the number of switch hops. However, the reduced latency available with time-sensitive networking is likely
5 to see the number of hops increase, particularly in larger cabin applications.

6 6.3.4 Max Number of Streams per Switch

7 The number of streams per switch is largely driven by the size and complexity of the network, and is usually
8 controlled by the system integrator as part of the network configuration. Whilst ARINC 664 Part 7 [B3]
9 specifies a minimum of 4096 streams, or Virtual Links, per switch this is not seen in current networks.
10 However, as networks become larger, particularly for large passenger aircraft and with the addition of small
11 devices to current networks, this number of streams is expected to be realized and could expand to as many
12 as 10,000 streams.

13 The number of streams per switch need also to be balanced against the practicalities of the technology and
14 whilst the majority of aerospace use cases are expected to be met through the use of commercial technology
15 the limits of that technology need also to be considered. The upper bound of 4096 streams is therefore
16 considered a reasonable compromise.

17 6.3.5 Network Redundancy

18 Where network redundancy is required, current use cases most commonly achieve this by implementing two
19 independent (A,B) networks and dual-homed end nodes (e.g. ARINC 664 Part 7 [B3]). TSN Ethernet offers
20 additional methods for achieving redundancy, including use of mesh or ring networks, and use of Bridged
21 end stations as well as dual-homed end nodes. Dual-homed end nodes refer to devices with two PHYs and
22 two MACs without a local Bridge component.

23 Point-to-point links do not by themselves provide redundancy unless this is managed at the system level
24 where dual, triple or sometimes quad redundancy can be encountered.

25 6.3.6 Redundancy Mode

26 A variety of redundancy mechanisms can be found, with bus fail-over (hot standby), frame fail-over (hot
27 active) and hot active with voting being the most common.

28 6.3.7 Data Rates

29 Data rates, particularly at the lower bound, are largely tied to the historical/legacy systems that are being
30 migrated to an Ethernet based network. At the upper bound, data rates have been limited by available
31 technologies with high bandwidth applications being migrated from older RF links and bespoke
32 transmission schemes. New use cases are expected to follow advances in commercial technology with 100
33 Gbps Ethernet seen as the most likely next step in performance.

34 6.3.8 Media type

35 Aerospace applications have traditionally relied on copper interconnects as there is a long established
36 acceptance of the technology and an understanding of how to install the technology in the specific
37 environment. This has led to the situation where lower speed Ethernet links also use copper media for lower
38 speeds (below 100 Mbps) and shorter distances.

39 The advent of higher aggregate data rates and high bandwidth data streams are however driving a need to
40 adopt optical fiber media for anything above 100 Mbps.

1 6.3.9 Worst Case Link Utilization

2 Driven by the desire to stay with copper media interfaces and the ability to statically configure networks for
3 determinism, link utilization has been pushed to the limit in the worst case analysis. Because this is very
4 much a worst-case analysis, to provide evidence of bounded latency determinism, the reality is that this level
5 of utilization is extremely rare and the reality is usually well below 50%.

6 However, in rare cases this level of utilization can also be encountered in practice when tight control of the
7 traffic is managed by a single function or application. In these cases, provided that the system integrator can
8 demonstrate control of the traffic loading, then 80% or even higher utilization might indeed be encountered.

9 6.3.10 Dissimilarity, Integrity, Maintenance, Monitoring, Security [DIMMS]

10 Dissimilarity and integrity tend to be associated with safety critical systems and are generally mandated by
11 the relevant aviation safety authorities, particularly with regard to dissimilarity. Both of these come at
12 considerable cost in an aerospace environment but are essential for certain systems.

13 Maintenance operations, whilst important to the end user, are often afforded a lower importance by the OEM
14 because they do not directly contribute to the aircraft function and are therefore harder to place a value on.
15 Monitoring however is crucial as this relates to the assessment of continued safe operation of the system and
16 falls within the purview of the aviation safety authorities.

17 Security in the realm of aerospace networks is not to be confused with cybersecurity, although there is some
18 limited commonality. Whereas cybersecurity addresses the activities performed by an organization to
19 safeguard its digital assets, security relates most simply to the protection of information from unauthorized
20 interaction. In the aerospace network security therefore relates to the physical and logical separation of
21 network domains. Most commonly mandated for military networks security is becoming more relevant to
22 civil aircraft networks, particularly where data is shared between network domains such as the AISD and
23 PIESD. Robust logical partitioning, through VLANs, and cross-domain security therefore become
24 increasingly important for aerospace networks.

25 6.3.11 Certification Requirements

26 Certification requirements are generally set by the safety authority responsible in the domain in which the
27 platform is intended to operate. For civil applications this is generally a national or regional organization,
28 whereas for military applications the acquisition organization is usually responsible, following guidelines
29 such as, but not limited to, DO-254 [B8], DO-178 [B7], ARP4754 [B9] and ARP4761 [B10], as set by one
30 or more of the civilian authorities. Satellite systems are regulated by the European Cooperation for Space
31 Standardization (ECSS) or similar organizations.

32 The responsible safety authority sets development design assurance standards for the safe operation of
33 equipment, systems and aircraft within a defined scope. In relation to time-sensitive networking this
34 includes oversight of activities intended to show that the network provides the intended behavior and
35 performance consistent with its intended application and can include test or mathematical analysis consistent
36 with acceptable means of compliance as outlined by the authority.

37 Specification of the certification requirements for a time-sensitive network is outside of the scope of this
38 standard.

39 6.3.12 Supported Traffic types

40 Traffic types are described in detail in 6.4 but a generic listing of current traffic types is provided here for
41 information.

- 1 — File Transfers - Mission Loading, Video Transfer, Image Transfer, Nav/Map data
- 2 — Asynchronous Parametric Data – sensors, displays,
- 3 — Synchronous Parametric Data – closed loop control and Inertial
- 4 — Command and Control – Weapons release authorization, commands
- 5 — Audio Streaming – Cockpit audio, cabin PA,
- 6 — Video Streaming – Uncompressed real-time video (ARINC818), compressed video streams
- 7 — Maintenance and Health Monitoring – fault reporting, testing
- 8 — Fiber Channel over TSN (FCoT) – HS1760 (weapons systems), and other FC based applications
- 9 — Extremely High BW Source - raw Radar data
- 10 — Raw IQ data and Raw Plot data
- 11 — Network control and infrastructure traffic

12 An aerospace network implementation could include one or more of these traffic types. The number of
13 streams per traffic type vary according to the use case.

14 6.4 Application and traffic characteristics

15 Aerospace applications have been analyzed here in terms of the traffic that they use to communicate. This
16 has been performed in a two-step process where first the characteristics used to define the traffic were
17 defined and second where example applications were analyzed using the defined characteristics to provide a
18 summary of the traffic types used in aerospace applications. The applications analyzed and their
19 characteristics are not exhaustive but illustrate the complete range of traffic types that are encountered in
20 typical aerospace applications on an aerospace network.

21 6.4.1 Traffic Type Characteristics

22 Traffic type characteristics are listed in Table 6-3 that enable a comparison of the most common traffic types
23 encountered in the aircraft applications that are described in Table 6-1 and Table 6-2.

Table 6-3—Aerospace Traffic Type Characteristics

Characteristic	Description
Periodicity	Traffic types comprise data streams that can either be Periodic : transmitted in a cyclic/periodic (e.g. signal transmission) or Aperiodic : transmitted in a acyclic/sporadic (e.g. event-driven) manner
Typical Period	Period denotes the planned data transmission interval (often also called “cycle”) at the application layer. #: Specify period for cyclic traffic N/A: for aperiodic/acyclic traffic
Application Synchronized to Network	Is the application producing traffic type synchronized to the network time at the application layer? YES or NO
Data Delivery Guarantee Mode	Packet(s) are delivered to all receivers: Deadline : before a specified time, relative to cycle time (applies to periodic data) Latency : within a predictable timespan from the start of the transmission Bandwidth : if bandwidth utilization is within in the resources reserved by the sender None : no special delivery requirements
Delivery Guarantee Value	#: Typical quantification of the data delivery guarantee for 80% of the use cases. For “deadline” mode, specifies if the data is delivered in the same period or not.

Table 6-3—Aerospace Traffic Type Characteristics (continued)

Characteristic	Description
Application Tolerant to Jitter	Application’s tolerance of a certain amount of latency variation of the packet’s transmission (a.k.a Jitter) yes: application can tolerate jitter as specified (always yes for “Bandwidth” and “none” delivery modes) no: highly sensitive application requires negligible jitter
Tolerable Jitter Value	#: Value of acceptable jitter for periodic applications NEG: Jitter needs to be negligible N/A: if data delivery guarantee mode is “bandwidth” or “none”
Application Tolerant to Packet Loss	An application’s tolerance to a certain amount of consecutive packet loss Yes: app can tolerate loss due to recovery mechanism in upper layer protocols or basic redundancy No: app cannot tolerate a single packet loss
Tolerable Packet Loss Value	#: Num of consecutive packet loss tolerable to app. 0: if application is not tolerant to packet loss
Application Payload Size Variability	fixed: application payload size remains fixed variable: app payload varies from one packet to packet
Payload Value (Bytes)	#: size/range of application data (payload) to be transmitted in the Ethernet frames.
Data Criticality	Criticality of this data for operation of the critical parts of the system: high: highly critical for the operation (DAL A, B), medium: relevant but not continuously needed for the operation (DAL C, D), low: not relevant for operation (DAL E).

7 6.4.2 Traffic Type Analysis Summary

2 The traffic use case analysis in tables 6-1 and 6-2 separated traffic types broadly into Military Aircraft and
3 Commercial Aircraft groupings [B6]. The bounds of these traffic types are summarized here in Table 6-4.

Table 6-4—Summary of Aerospace Traffic Types

Traffic Characteristic	Current Use (range)		Known/ Desired New Use Bound	Use Case Driving the Most Restrictive (right) Bound
	Left Bound (loosest)	Right Bound (tightest)		
Synchronism	Asynchronous	Synchronous	no change	Ultra-low latency and/or jitter (right bound)
Application synchronized to network?	No	Yes	no change	Ultra-low latency and/or jitter
Periodicity or Cycle Time	Aperiodic	<1 ms	100 μs	Flight critical controls, sensors, and weapon systems
Latency Mode Guarantee Value	100 ms	1 ms	100 μs	high criticality asynchronous events

Table 6-4—Summary of Aerospace Traffic Types (*continued*)

Traffic Characteristic	Current Use (range)		Known/ Desired New Use Bound	Use Case Driving the Most Restrictive (right) Bound
	Left Bound (loosest)	Right Bound (tightest)		
Tolerance to interference (delay variation/jitter)	up to latency limit	< 1 μ s	no change	fly-by-wire, synchronous sensors
Tolerance to Loss*	3 consecutive frames	zero	no change	Parametric data (left bound), Flight control or weapon release (right bound)
Payload size	8 bytes	2112 bytes	no change	Sensor data (left bound) Fibre Channel over TSN (right bound)
Data Criticality	no safety effect	DAL A	no change	Safety critical and flight control

* All aerospace systems are robust to losses and failures. This entry therefore indicates desirable behavior.

¹ Synchronism and whether the application is synchronized to the network are used here to capture how traffic
² synchronization relates to the application behavior. In most cases, applications are not synchronized to the
³ network. However, where ultra-low latency is necessary, and an asynchronous boundary between the
⁴ network and the application cannot be tolerated then it is reasonable, even necessary, to synchronize the
⁵ application to the network. Examples of this would be fly-by-wire or safety-critical closed-loop control
⁶ functions.

⁷ Two categories of traffic are generally considered candidates for migration to TSN, namely Ethernet based
⁸ traffic (ARINC 664 Part 7 [B3] or COTS), and non-Ethernet traffic (ARINC 429/629, Fibre Channel, MIL-
⁹ STD-1553, IEEE 1394). Current Ethernet systems are asynchronous and have cycle times of 50 ms or higher
¹⁰ and use bounded latency to support safety requirements. Current non-Ethernet systems are often physically
¹¹ partitioned/segmented, can have cycle times of 1 ms or higher, are sensitive to both latency and delay
¹² variation and require determinism. As mentioned above, whether these tight latency/jitter requirements are
¹³ needed on all signals isn't clear, but there are certainly functions that do require this.

¹⁴ Aerospace systems are inherently designed to be tolerant to network frame loss, but eliminating congestion
¹⁵ loss remains an objective. TSN-based systems need to address the requirements of both Ethernet and non-
¹⁶ Ethernet traffic with the potential evolution to use cases requiring sub-millisecond latency.

¹⁷

7. Required functions for aerospace networks

This clause provides requirements specific to this document and the aerospace use case.

7.1 Time synchronization

Time synchronization is used in aerospace networks to support time-aware functions on end stations and Bridges including enhancements to scheduled traffic and per-stream filtering and policing functions. Synchronized time can be used in aerospace end systems for operation of synchronous applications and timestamping of application payloads to protect and maintain data integrity. This standard specifies time synchronization according to IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024 for conformant components.

Due to the static nature of engineered aerospace networks the Grandmaster(s) and time distribution tree(s) are predetermined. As a result, aerospace components do not use the best timeTransmitter clock selection algorithm (BTCA). Instead, aerospace applications use external port configuration for setting the Grandmaster PTP Instance and time-synchronization spanning tree for each of the supported gPTP domains.

It is important for aerospace applications to consider fault-tolerance, including availability and integrity of the synchronizing function, to provide reliable and trustworthy time. Synchronous aerospace systems, i.e. those conforming to the synchronous aerospace profiles, are expected to tolerate multiple (typically 2) simultaneous arbitrary faults in end stations, Bridges, links, and GMs to maintain availability and integrity of time synchronization. Fault-tolerant time synchronization enables reliable and accurate transmission of time values and the associated Sync and Follow_Up messages in the presence of arbitrary faults.

This standard specifies the use of fault-tolerance mechanisms according to IEEE P802.1ASed. These mechanisms include provisions for multiple time domains, multiple Grandmasters (GM), multiple time distribution trees, multiple PTP Instances per physical port in Bridges and end stations, and time selection functions. The Fault-Tolerant Timing (FTT) entity as specified in IEEE P802.1ASed is used to enhance both the availability and integrity of time distribution in an aerospace onboard network. The FTT entity manages the selection of a time source from two or more gPTP times and corresponding PTP Instances. The selected time is provided to target applications in accordance with Clause 9 of IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024. The fault-tolerance mechanisms supported by components conformant to synchronous profiles of this standard are specified in Clause 5.

NOTE—The use of fault-tolerance features needs to be carefully considered by the system designer to meet the availability and integrity targets of the specific aerospace system. For example, additional consideration beyond those addressed by the FTT entity could be needed to enable sufficient fault-tolerance of time synchronization at the system level.

7.2 Traffic shaping

The use cases defined in Clause 6 require shaping of the traffic at egress ports of Bridges or end stations to meet the latency and packet delay variation (jitter) requirements defined in Table 6-4. Traffic shaping is specified according to the profile being used.

Two traffic shaping methods are applicable to the aerospace use cases:

- a) Credit-based shaper algorithm as defined in 8.6.8.2 of IEEE Std 802.1Q-2022 and
- b) Enhancements for scheduled traffic as defined in 8.6.8.4 of IEEE Std 802.1Q-2022

The credit-based shaper algorithm (CBSA) is used by asynchronous implementations to shape the transmissions of a stream on the basis of the aggregate rate or bandwidth. CBSA does not require network-

1 wide time synchronizations and can be used in aerospace scenarios that do not support time synchronization.
2 CBSA can also be configured in Bridges to shape the flow of unregulated traffic arriving at the Bridge.

3 The enhancements for scheduled traffic are used by synchronous component implementations to schedule
4 the transmissions of a stream across the network to achieve required latency and jitter. A device supporting
5 scheduled traffic is required to also support time synchronization as defined in 7.1 since scheduling requires
6 all devices to have the same notion of time. Scheduled traffic can be configured in Bridges to shape and time
7 align asynchronous flows that arrive at the Bridge from non-time-aware components.

8 Bridge and end station implementations could support both CBSA and scheduled traffic on the same port.
9 The interaction between the two shapers needs to be considered when evaluating the performance of such an
10 implementation. For example, as described in 8.6.8 of IEEE Std 802.1Q-2022, the credit for CBSA
11 accumulates only during the time that the gate assigned to the credit-based flow is open, so the CBSA idle
12 slope is calculated based on the requested operIdleSlope and the duty cycle of the schedule for the assigned
13 output queue.

14 Implementations need to consider the queuing of frames at end stations and Bridges to achieve the latency
15 and jitter requirements for aerospace applications. Additionally, queuing could be used to separate frames
16 from different sources for isolation purposes. 8.6.6 of IEEE Std 802.1Q-2022 provides recommendations for
17 mapping priority to traffic classes depending upon the number of priorities and queues supported by
18 components of the platform. IEEE 802.1Q-2022 specifies up to 8 traffic classes. In addition to per-class
19 shaping, aerospace implementations could utilize per-stream shaping as described in 7.2.1.

20 7.2.1 Per-Stream queuing and shaping at end stations

21 An aerospace end system could have multiple applications, each of which could generate multiple streams.
22 An aerospace talker end station is expected to queue and shape each stream individually according to the
23 talker queuing model specified in 34.6.1.1 of IEEE Std 802.1Q-2022.

24 In the case of asynchronous end stations, each stream would be shaped individually using a per-stream
25 queue and a credit-based shaper algorithm (CBSA) as defined in 8.6.8.2 of IEEE Std 802.1Q-2022.

26 In the case of a synchronous end station, each stream could either be shaped individually with CBSA or
27 enhancements for scheduled traffic. If the application is operating in a synchronous mode, it can be expected
28 to produce data at the correct transmit offset. However, in cases where the application is not synchronous,
29 but the end station is synchronous, per stream queuing and shaping allows for the scheduling of frames from
30 the asynchronous application.

31 NOTE—the delay introduced by the per-stream queuing and shaping at the end stations needs to be accounted for in the
32 end-to-end latency analysis by the system integrator.

33 The number of Per-Stream queues supported is dependent on the end station implementation. Across
34 aerospace use cases, the number of streams required per end station range from 2 to 256. The mapping of the
35 per-stream queues to the per-class queues is implementation dependent. Clause 5 provides the requirements
36 for the minimum number of streams to be supported by conformant end stations.

37 NOTE—For example, in an implementation supporting 8 per-stream queues and 2 traffic classes could map all 8 per-
38 stream queues to a one class or distribute them in an arbitrary manner.

39 7.2.2 Per-Class queuing and shaping at end stations

40 An aerospace end system could produce the streams described in 7.2.1 using one or more traffic classes
41 assigned to different output queues according to the system requirements. The frame queuing described in
42 8.6.6 of IEEE Std 802.1Q-2022 for bridges outlines the use of one or more queues, each corresponding to a
43 distinct traffic class. Aerospace end systems are expected to use the same approach with streams assigned to

output queues according to the allocated traffic class. The number of supported queues depends on the complexity of the device and is expected to range between 2 and 8.

7.3 Stream isolation

Aerospace use cases require strict isolation between streams to support independence between system functions and to prevent faults and failures in one device or application from impacting other devices or applications. This is especially important in a scenario where the network converges traffic from sources that are certified to different design assurance levels (mixed-DAL). For example, a Bridge can have two streams that originate from different data sources (talkers), operate at different assurance levels, and arrive at different ingress ports, but are forwarded to the same egress port. This is illustrated in Figure 7-1 where




Figure 7-1—Aerospace Stream Isolation

stream 1 and stream 2 originating from end stations #1 and #2, respectively, are forwarded by a Bridge to end station #3. If the Bridge does not identify, filter, police, and monitor each stream individually, faults in one stream could negatively affect the other streams at the output of the Bridge. To support aerospace use cases, this standard requires stream isolation at all conformant Bridges.

This standard specifies the use of Per-Stream Filtering and Policing (PSFP), defined in 8.6.5 of IEEE Std 802.1Q-2022, in Bridges to filter and police streams. PSFP can be used in combination with traffic shaping mechanism to meet the latency and jitter requirements of asynchronous streams. The default behavior for aerospace use cases is to discard frames that do not meet the PSFP criteria assigned to the corresponding stream filter. PSFP requirements for Bridges belonging to the different conformance classes defined in this standard are provided in Clause 5.

Depending on the size, complexity, and design of aerospace network implementations, Bridges can have different requirements for stream isolation, particularly with regards to the supported stream count. While some use cases require very large stream counts per Bridge port, other aerospace use cases involving constrained hardware require low stream count per Bridge port. This standard defines minimum stream counts to be supported on both low and high stream count Bridge implementations as shown in Table 7-1 and Table 7-2.

Table 7-1—Number of supported streams for low stream-count Bridges

Number of Ports	Minimum Stream Count
≤4	128
5-9	192
>9	256

7

Table 7-2—Number of supported streams for high stream-count Bridges

Number of Ports	Minimum Stream Count
<=4	256
5-8	512
9-12	1024
13-18	2048
>18	>4095

2 NOTE—The queuing of frames at an egress port, as described in IEEE Std 802.1Q-2022, 8.6.6, can be used to further
3 isolate streams. For example, the priority value of a frame and the mapping of priorities to traffic classes provide
4 additional means of stream isolation. The specific solution for queuing frames to maximize stream isolation is
5 implementation dependent.

6 7.4 Active topology enforcement

7 The Learning Process according to 8.7 of IEEE Std 802.1Q-2022 can be configured by management action.
8 By default learning is disabled for all Bridge ports, thereby disabling the creation of dynamic filtering
9 entries. The managed objects to disable learning are not specified in this standard.

10 A loop-free network is provided through configuration. Support for the Rapid Spanning Tree Algorithm and
11 Protocol (RSTP) is not required.

12 By default the forwarding of any frames to one or more port(s) is determined by static filtering entries as
13 defined in 8.8.1 of IEEE Std 802.1Q-2022. Forwarding is FALSE (i.e. drop) for all other frames.

14 7.5 Network redundancy

15 Most aerospace use cases require network redundancy to overcome link and node failures. The standard
16 specifies the use of Frame Replication and Elimination for Reliability (FRER), as defined in IEEE Std
17 802.1CB-2017 for network redundancy. FRER provides a flexible solution that supports different
18 redundancy patterns as described in Annex C of IEEE Std 802.1CB-2017. FRER can be used to implement
19 the commonly used aerospace redundancy pattern of dual redundant paths over physically separate networks
20 (e.g. A/B network pattern). Bridge and end station requirements for FRER are described in Clause 5.

21 FRER enables an application to transmit a single copy of a frame that is replicated by the talker end station
22 or subsequent Bridge for transmission over multiple disjoint paths. At the receiving end station or a
23 preceding Bridge all but one of the copies are discarded, thereby providing seamless redundancy for
24 applications that cannot tolerate packet loss.

25 NOTE 1—FRER can be configured to pass all redundant frames to the receiving application at an end station for
26 integrity checks if the use case imposes such a requirement on an implementation.

27 NOTE 2—If an aerospace end system includes an end station and a Bridge, the FRER functions can be implemented in
28 either the end station or the Bridge. In some cases, the FRER functions could be split between the end station and the
29 Bridge.

7.5.1 Coordination between FRER components on a network

When a stream is split into two or more member streams, the resulting member streams can be either distinct with different VLAN IDs or identical with same VLAN ID. The stream identification and recovery functions on the FRER component responsible to recover the stream and eliminate the redundant frames need to support both the distinct and identical member streams.

If the stream is VLAN tagged at the talker ahead of the FRER component responsible for splitting the stream, the resulting member streams after splitting can be:

- a) Distinct member streams with different VLAN IDs wherein the VLAN ID of one of the member streams is identical to the VLAN ID used by the talker
- b) Distinct member streams with different VLAN IDs; none of the member streams are tagged with a VLAN ID used by the talker
- c) Identical member streams with same VLAN IDs, where the VLAN ID is the same as the one used by the talker
- d) Identical member streams with same VLAN IDs, where the VLAN ID is distinct from the one used by the talker

The stream identification and recovery functions on the FRER component responsible to recover the stream and eliminate the redundant frames need to support one or more items from the list above in coordination with the FRER component responsible for splitting the stream.

Implementations need to consider this interoperability between devices in a given network to enable compatibility between the replication and elimination of redundant streams.

7.6 Configuration

7.6.1 Aerospace configuration model overview

Due to the safety and assurance requirements, aerospace networks are designed to be engineered networks with static topology best suited for fully centralized configuration model as specified in Clause 46 of IEEE Std 802.1Q-2022. The topology and stream requirements are derived from higher level system requirements. Therefore, the input data for centralized user configuration (CUC) entity and the centralized network configuration (CNC) component is derived from higher level system interface control documents (ICDs). Aerospace regulatory requirements do not allow direct communication channels between configuration tool entities (CUC, CNC) and network components (Bridges and end stations). Therefore, this standard specifies an offline file-based configuration approach.

Figure 7-2 depicts the configuration model as specified by this standard. The CUC and the CNC get the information required to generate network and user configuration in the form of static files. And similarly, the CUC and the CNC generate individual file-based device configurations that are loaded into equipment during manufacture or at major service events following an industry or implementation specific process. Aerospace qualified tools are used at each stage of configuration development to verify that configurations are accurate representations of the user requirements with configuration control maintained for individually identifiable items.

NOTE—The format of input files to CUC and CNC is implementation dependent and out of scope of this standard.

The YANG modules for talker, bridge, and listener configurations at conformant end stations and Bridges are listed in clause 7.6.2.

NOTE—Aerospace implementations typically utilize industry standards like ARINC 665-3 [B2] and ARINC 615A [B1] and convert configuration instance data, that is generated and tested off-line, to binary representation and load this into equipment prior to use. This approach is further discussed in Annex C.




Figure 7-2—Aerospace Configuration Model

¹ Configuration of the end station talkers and listeners requires additional stream centric information (e.g.,
² stream identification, stream tagging and stream shaping parameters) in addition to interface configuration.
³ This standard specifies the use of UNI YANG model as defined in IEEE Std 802.1Qdj to provide the talker
⁴ and listener configuration data to end stations.

⁵ NOTE—For talker and listener configuration, this standard only specifies the data model with which the instance data is
⁶ provided to respective end stations. Instantiation of the talker/listener configuration on end stations is implementation
⁷ dependent and out of scope of this standard.

7.6.2 YANG Data Models

This standard selects and specifies the use of YANG data models in aerospace applications from the list of YANG models defined in existing IEEE standards. Table 7-3 lists the YANG modules required for conformance of Bridges and end stations to this standard.

Table 7-3—YANG data models

Function	Initial YANG specification	Bridge and/or end station	YANG modules
Time synchronization	IEEE Std 802.1ASdn-2024 IEEE Std 1588e-2024	Bridge and end station	ietf-yang-types ieee1588-ptp ieee802-dot1as-gptp
Scheduled traffic	IEEE Std 802.1Qcw-2023	Bridge and end station	ieee802-dot1q-sched ieee802-dot1q-sched-bridge
Credit-based shaper (CBS)	IEEE Std 802.1Qdx-2024 IEEE Std 802.1DC-2024	Bridge and end station	ieee802-dot1q-cbsa ieee802-dot1q-cbsa-bridge ieee802-dot1q-cbsa-if
Per-Stream Filtering & Policing (PSFP)	IEEE Std 802.1Qcw-2023	Bridge only	ieee802-dot1q-psfp ieee802-dot1q-psfp-bridge
Frame Replications and Elimination for Reliability (FRER)	IEEE Std 802.1CBcv-2021	Bridge and end station	ieee802-dot1cb-frer
Stream identification (Bridge)	IEEE Std 802.1CBcv-2021 IEEE Std 802.1CBdb-2021	Bridge only	ieee802-dot1cb-stream-identification ieee802-dot1q-bridge
End station Configuration (Interface/Stream configuration)	IEEE Std 802.1Qdj-2024	End station only	ieee802-dot1q-cnc-config
Explicit static forwarding	IEEE Std 802.1Qcp-2018	Bridge only	ieee802-dot1q-bridge
Fault-Tolerant Timing	IEEE P802.1ASed	Bridge and end station	ieee802-dot1as-fft

NOTE 1—Dependencies of the YANG modules in Table 7-3 are not explicitly listed.

7.7 Management and Monitoring

7.7.1 Overview

Management and monitoring of network equipment and functions is necessary for safe operation of aerospace systems. Clause 7.6 describes a static configuration model wherein the TSN functions are managed via static configuration files that are loaded on conformant Bridges and end stations prior to the operation of the system. This standard further selects a set of monitoring objects that are required to be maintained and made available by conformant components during operation (flight) for a certifiable solution.

NOTE 1—While all management objects for selected TSN features are to be supported as required by Clause 5 of IEEE Std 802.1Q-2022, the management objects for configuration (r/w objects) might not be exposed during runtime for

1 safety reasons and might only be accessible via the static configuration files. The management objects defined in 7.7 are
2 monitoring objects (counters) that are to be made available during runtime.
3 NOTE 2—The protocol to access management objects by aircraft management function is outside the scope of this
4 standard.

5 7.7.2 TSN feature specific monitoring objects

6 The following sections outline the monitoring objects of the functions outlined in Table 7-3.

7 7.7.2.1 Required monitoring objects for time synchronization

8 Managed objects to monitor time synchronization in conformant components are listed in Table 7-4. These
9 objects are defined for each PTP Instance supported by the component.

Table 7-4—Time synchronization managed objects

Name	Data Type	Operations Supported*	Reference (IEEE Std 802.1AS-2020 as amended by IEEE Std 802.1ASdm-2024)
clockIdentity	Octet[8]	R	8.5.2.2
domainNumber	UInteger8	R	10.2.2.1.2
offsetFromTimeTransmitter	UInteger16	R	10.2.10
gmTimebaseIndicator	UInteger16	R	9.2.2.3, 9.6.2.3
cumulativeRateRatio	UInteger16	R	14.4.3
grandmasterIdentity	Octet[8]	R	8.5.2.2, 14.2.2
portIdentity	UInteger16	R	8.5.2.3
asCapable	Boolean	R	10.2.5.1
meanLinkDelay	UScaledNs	R	10.2.5.8
neighborRateRatio	UInteger32	R	10.2.5.7
rxPTPPacketDiscardCount	UInteger32	R	14.10.9
syncReceiptTimeoutCount	UInteger32	R	14.10.10
pdelayAllowedLostResponsesExceededCount	UInteger32	R	14.10.12
cmlDsLinkPortNumber	UInteger32	R	14.16.2

*R = read-only access

7.7.2.2 Required monitoring objects for Scheduled Traffic

Managed objects required to monitor the operation of scheduled traffic in conformant components are listed in Table 7-5. The objects are defined per queue and per port.

Table 7-5—Scheduled traffic managed objects

Name	Data Type	Operations Supported*	Reference (IEEE Std 802.1Q-2022)
TransmissionOverrun	counter	R	12.29.1.1.2

*R = read-only access

7.7.2.3 Required monitoring objects for credit-based shaper

No objects are defined to monitor the operation of the credit-based shaper.

7.7.2.4 Required monitoring objects for PSFP

Managed objects required to monitor PSFP stream filtering in conformant components are listed Table 7-6. The objects are defined per stream.

Table 7-6—PSFP stream filter managed objects

Name	Data type	Operations supported*	Reference (IEEE Std 802.1Q-2022)
MatchingFramesCount	counter	R	8.6.5.3
PassingSDUCount	counter	R	8.6.5.3.1
NotPassingSDUCount	counter	R	8.6.5.3.1
PassingFrameCount	counter	R	8.6.5.4
NotPassingFrameCount	counter	R	8.6.5.4
RedFramesCount	counter	R	8.6.5.5

*R = read-only access

Managed objects required to monitor PSFP stream gates in conformant components are listed in Table 7-7. These objects are defined for each stream gate.

Table 7-7—PSFP stream gate managed objects

Name	Data type	Operations supported*	Reference (IEEE Std 802.1Q-2022)
StreamGateClosedDueToInvalidRx	boolean	RW	8.6.5.4
StreamGateClosedDueToOctetsExceeded	boolean	RW	8.6.5.4

*RW = Read/Write access.

⁷ Managed objects required to monitor PSFP flow meters traffic in conformant components are listed in ² Table 7-8. These objects are defined per flow meter.

Table 7-8—PSFP flow meter managed objects

Name	Data type	Operations supported*	Reference (IEEE Std 802.1Q-2022)
MarkAllFramesRed	boolean	RW	8.6.5.5

*RW = Read/Write access.

³ 7.7.2.5 Required monitoring objects for FRER

⁴ Managed objects required to monitor the operation of FRER in conformant components are listed in Table 7-⁵ 9 and in Table 7-10. These objects are defined per-port and per-stream per-port respectively.

Table 7-9—FRER, per-port managed objects

Name	Data type	Operations supported*	Reference (IEEE Std 802.1CB)
frerCpSeqRcvyPassedPackets	counter	R	10.9.1
frerCpSeqRcvyDiscardPackets	counter	R	10.9.2
frerCpSeqEncErroredPackets	counter	R	10.9.3

*R = read-only access.

7

Table 7-10—IEEE Std 802.1CB, FRER, per-stream, per-port managed objects

Name	Data type	Operations supported*	Reference (IEEE Std 802.1CB)
frerCpsSeqGenResets	counter	R	10.8.2
frerCpsSeqRcvyOutOfOrderPackets	counter	R	10.8.3
frerCpsSeqRcvyRoguePackets	counter	R	10.8.4
frerCpsSeqRcvyPassedPackets	counter	R	10.8.5
frerCpsSeqRcvyDiscardedPackets	counter	R	10.8.6
frerCpsSeqRcvyLostPackets	counter	R	10.8.7
frerCpsSeqRcvyTaglessPackets	counter	R	10.8.8
frerCpsSeqRcvyResets	counter	R	10.8.9
frerCpsSeqRcvyLatentErrorResets	counter	R	10.8.10
frerCpsSeqEncErroredPackets	counter	R	10.8.11

*R = read-only access.

2 7.7.2.6 Required monitoring objects for FTT

3 Managed objects required to monitor the operation of a Fault-Tolerant Timing entity in conformant
4 components are listed in.

Table 7-11—FTT managed objects

Name	Data type	Operations supported*	Reference (IEEE P802.1ASed)
fttTrustState	Enumeration2	R	14.23.20
fttSelInstance	UInteger32	R	14.23.17

*R = read-only access.

1 Annex A

2

3 (normative)

4 PCS proforma—IEEE Std 802.1DP Aerospace TSN Networking⁷

5 A.1 Introduction

6 The supplier of a protocol implementation that is claimed to conform to this standard shall complete the
7 following Profile Conformance Statement (PCS) proforma, which is presented in a tabular format based on
8 the format used for Protocol Implementation Conformance Statement (PICS) proformas.

9 The tables do not contain an exhaustive list of all requirements that are stated in the referenced standards; for
10 example, if a row in a table asks whether the implementation is conformant to Standard X, and the answer
11 “Yes” is chosen, then it is assumed that it is possible, for that implementation, to fill out the PCS proforma
12 specified in Standard X to show that the implementation is conformant; however, the tables in this document
13 will only further refine those elements of conformance to Standard X where particular answers are required
14 for the profiles specified here.

15 A completed PCS proforma is the PCS for the implementation in question. The PCS is a statement of which
16 capabilities and options of the protocol have been implemented. The PCS can have a number of uses,
17 including use

- 18 a) By the protocol implementer, as a checklist to reduce the risk of failure to conform to the standard
19 through oversight.
- 20 b) By the supplier and acquirer—or potential acquirer—of the implementation, as a detailed indication
21 of the capabilities of the implementation, stated relative to the common basis for understanding
22 provided by the standard PCS proforma.
- 23 c) By the user—or potential user—of the implementation, as a basis for initially checking the
24 possibility of interworking with another implementation (note that, while interworking can never be
25 guaranteed, failure to interwork can often be predicted from incompatible PCSs).
- 26 d) By a protocol tester, as the basis for selecting appropriate tests against which to assess the claim for
27 conformance of the implementation.

28 A.2 Abbreviations and special symbols

29 A.2.1 Status symbols

30	M	mandatory
31	O	optional
32	O.n	optional, but support of at least one of the group of options labeled by the same numeral n
33		is required
34	X	prohibited
35	pred:	conditional-item symbol, including predicate identification: see A.3.4
36	¬	logical negation, applied to a conditional item’s predicate

⁷ Copyright release for PCS proformas: Users of this standard may freely reproduce the PCS proforma in this annex so that it can be used for its intended purpose and may further publish the completed PCS.

1

2 A.2.2 General abbreviations

3	N/A	not applicable
4	PCS	Profile Conformance Statement

5 A.3 Instructions for completing the PCS proforma

6 A.3.1 General structure of the PCS proforma

7 The first part of the PCS proforma, implementation identification and protocol summary, is to be completed
8 as indicated with the information necessary to identify fully both the supplier and the implementation.

9 The main part of the PCS proforma is a fixed-format questionnaire, divided into several subclauses, each
10 containing a number of individual items. Answers to the questionnaire items are to be provided in the
11 rightmost column, either by simply marking an answer to indicate a restricted choice (usually Yes or No) or
12 by entering a value or a set or range of values. (Note that there are some items where two or more choices
13 from a set of possible answers can apply; all relevant choices are to be marked.)

14 Each item is identified by an item reference in the first column. The second column contains the question to
15 be answered with reference or references to the material that specifies the item in the main body of this
16 standard in the third column. The fourth column provides additional values or comments to support the
17 conformance questions. The fifth column records the status of the item—whether support is mandatory,
18 optional, or conditional: see also A.3.4. The sixth column provides the space for the answers.

19 A supplier may also provide (or be required to provide) further information, categorized as either Additional
20 Information or Exception Information. When present, each kind of further information is to be provided in a
21 further subclause of items labeled Ai or Xi, respectively, for cross-referencing purposes, where i is any
22 unambiguous identification for the item (e.g., simply a numeral). There are no other restrictions on its format
23 and presentation.

24 A completed PCS proforma, including any Additional Information and Exception Information, is the
25 Protocol Implementation Conformation Statement for the implementation in question.

26 NOTE—Where an implementation is capable of being configured in more than one way, a single PCS may be able to
27 describe all such configurations. However, the supplier has the choice of providing more than one PCS, each covering
28 some subset of the implementation's configuration capabilities, in case that makes for easier and clearer presentation of
29 the information.

30 A.3.2 Additional information

31 Items of Additional Information allow a supplier to provide further information intended to assist the
32 interpretation of the PCS. It is not intended or expected that a large quantity will be supplied, and a PCS can
33 be considered complete without any such information. Examples might be an outline of the ways in which a
34 (single) implementation can be set up to operate in a variety of environments and configurations, or
35 information about aspects of the implementation that are outside the scope of this standard but that have a
36 bearing on the answers to some items.

37 References to items of Additional Information may be entered next to any answer in the questionnaire and
38 may be included in items of Exception Information.

1 A.3.3 Exception information

2 It may occasionally happen that a supplier will wish to answer an item with mandatory status (after any
3 conditions have been applied) in a way that conflicts with the indicated requirement. No preprinted answer
4 will be found in the Support column for this item. Instead, the supplier shall write the missing answer into
5 the Support column, together with an *Xi* reference to an item of Exception Information, and shall provide the
6 appropriate rationale in the Exception item itself.

7 An implementation for which an Exception item is required in this way does not conform to this standard.

8 NOTE—A possible reason for the situation described previously is that a defect in this standard has been reported, a
9 correction for which is expected to change the requirement not met by the implementation.

10 A.3.4 Conditional status

11 A.3.4.1 Conditional items

12 The PCS proforma contains a number of conditional items. These are items for which both the applicability
13 of the item itself, and its status if it does apply—mandatory or optional—are dependent on whether certain
14 other items are supported.

15 Where a group of items is subject to the same condition for applicability, a separate preliminary question
16 about the condition appears at the head of the group, with an instruction to skip to a later point in the
17 questionnaire if the “Not Applicable” answer is selected. Otherwise, individual conditional items are
18 indicated by a conditional symbol in the Status column.

19 A conditional symbol is of the form “**pred:** S” where **pred** is a predicate as described in A.3.4.2 below, and
20 S is a status symbol, M or O.

21 If the value of the predicate is true (see A.3.4.2), the conditional item is applicable, and its status is indicated
22 by the status symbol following the predicate: The answer column is to be marked in the usual way. If the
23 value of the predicate is false, the “Not Applicable” (N/A) answer is to be marked.

24 A.3.4.2 Predicates

25 A predicate is one of the following:

- 26 a) An item-reference for an item in the PCS proforma: The value of the predicate is true if the item is
27 marked as supported and is false otherwise.
- 28 b) A predicate-name, for a predicate defined as a boolean expression constructed by combining
29 item-references using the boolean operator OR: The value of the predicate is true if one or more of
30 the items is marked as supported.
- 31 c) The logical negation symbol “¬” prefixed to an item-reference or predicate-name: The value of the
32 predicate is true if the value of the predicate formed by omitting the “¬” symbol is false, and vice
33 versa.

34 Each item whose reference is used in a predicate or predicate definition, or in a preliminary question for
35 grouped conditional items, is indicated by an asterisk in the Item column.

1 **A.4 PCS proforma for IEEE Std 802.1DP—Aerospace TSN**

2 **Networking**

A.4.1 Implementation identification

Supplier	
Contact point for queries about the PCS	
Implementation Name(s) and Version(s)	
Other information necessary for full identification, e.g., name(s) and version(s) of machines and/or operating system names	
NOTE 1—Only the first three items are required for all implementations; other information may be completed as appropriate in meeting the requirement for full identification. NOTE 2—The terms “Name” and “Version” should be interpreted appropriately to correspond with a supplier’s terminology (e.g., Type, Series, Model).	

A.4.2 Profile summary

Identification of protocol specification	IEEE Std 802.1DP-<year>, IEEE Standard for Time-Sensitive Networking for Aerospace Ethernet Communications
Identification of amendments and corrigenda to the PCS proforma that have been completed as part of the PCS	Amd. : Corr. : Amd. : Corr. :
Have any Exception items been required? (See A.3.3: the answer “Yes” means that the implementation is not conformant).	No [] Yes []

Date of Statement	
-------------------	--

3

4

5

A.4.3 Implementation summary

The following table is used to indicate the type of component that the PCS describes. A component may support multiple profiles, either simultaneously or independently, and this table should be used to indicate all profiles supported by the component.

Item	Feature	Subclause	Value/Comment	Status	Support
AT1-BC	If the implementation supports asynchronous Type1 Bridge component functions, mark “Yes” and complete Annex A.5.1* and Annex A.5.2	5.4.1, 5.5.1, 5.4.2, 5.5.2		O	Yes [] No []
AT2-BC	If the implementation supports asynchronous Type2 Bridge component functions, mark “Yes” and complete Annex A.5.1* and Annex A.5.3	5.4.1, 5.5.1, 5.4.3, 5.5.3		O	Yes [] No []
ST1-BC	If the implementation supports synchronous Type1 Bridge component functions, mark “Yes” and complete Annex A.5.1* and Annex A.5.4	5.4.1, 5.5.1, 5.4.4, 5.5.4		O	Yes [] No []
ST2-BC	If the implementation supports synchronous Type2 Bridge component functions, mark “Yes” and complete Annex A.5.1* and Annex A.5.5	5.4.1, 5.5.1, 5.4.5, 5.5.5		O	Yes [] No []
AT1-EC	If the implementation supports asynchronous Type1 end station component functions, mark “Yes” and complete Annex A.6.1* and Annex A.6.2	5.6.1, 5.7.1, 5.6.2, 5.7.2		O	Yes [] No []
AT2-EC	If the implementation supports asynchronous Type2 end station component functions, mark “Yes” and complete Annex A.6.1* and Annex A.6.3	5.6.1, 5.7.1, 5.6.3, 5.7.3		O	Yes [] No []
ST1-EC	If the implementation supports synchronous Type1 end station component functions, mark “Yes” and complete Annex A.6.1* and Annex A.6.4	5.6.1, 5.7.1, 5.6.4, 5.7.4		O	Yes [] No []
ST2-EC	If the implementation supports synchronous Type2 end station component functions, mark “Yes” and complete Annex A.6.1* and Annex A.6.5	5.6.1, 5.7.1, 5.6.5, 5.7.5		O	Yes [] No []

* If a component supports multiple profiles then the appropriate common component conformance statement need only be completed once.

¹Protocol implementations for aerospace onboard Ethernet communications may support either or both
²Bridge and end station protocol features with asynchronous and/or synchronous capabilities and Type1 or
³Type2 capability profiles. PCS proformas are provided here for all capabilities described in Clause 5, to be
⁴complete for each implementation supporting aerospace onboard Ethernet networks.

⁵A.5 Bridge component implementations

⁶A.5.1 Common Bridge component capabilities

The following table describes common bridge component requirements and options.

Item	Feature	Subclause	Comment	Status	Support
BC-1	Supports VLAN Bridge requirements?	5.4.1, a		M	Yes []
BC-2	Supports active topology enforcement as specified in 7.4?	5.4.1, b	per 7.4	M	Yes []
BC-3	Supports C-VLANs requirements?	5.4.1, c		M	Yes []
BC-4	FDB supports static and dynamic VLAN registration entries?	5.4.1, d	Indicate how many supported.	M	Yes [] Qty. []
BC-5	Supports the strict priority algorithm for transmission selection on each port for each traffic class?	5.4.1, e		M	Yes []
BC-6	Supports operation of the credit-based shaper algorithm on all ports for at least 2 traffic classes?	5.4.1, f	Indicate how many traffic classes supported.	M	Yes [] Qty. []
BC-7	Supports stream identification all ports?	5.4.1, g		M	Yes []
BC-8	Supports Per-Stream Filtering and Policing (PSFP)?	5.4.1, h	Supports maximum SDU size filtering, supports flow metering, supports monitoring for PSFP.	M	Yes []
BC-9	Supports minimum number of stream identification and filtering entries?	5.4.1, i	per Table 7-1 Indicate how many supported	M	Yes [] Qty. []
BC-10	Supports bridge management entities for configuration of Bridge functions?	5.4.1, j	per 7.6	M	Yes []
BC-11	Supports the monitoring of PSFP	5.4.1, k	per 7.7.2.4	M	Yes []
BC-12	Supports translation of VLAN identifiers	5.5.1, a	Using one or more of the suggested means.	O	Yes [] No []

⁷

A.5.2 Asynchronous Type1 Bridge component capabilities

Item	Feature	Subclause	Status	Support
AT1-BC-1	Supports all common Bridge component requirements?	5.4.2, a	AT1-BC:M	Yes []
AT1-BC-2	Supports at least four traffic queues? Indicate how many supported.	5.4.2, b	AT1-BC:M	Yes [] Qty. []
AT1-BC-3	Supports operation of the credit-based shaper algorithm for all traffic classes?	5.5.2, b	AT1-BC:O	Yes [] No []
AT1-BC-4	Supports eight traffic queues?	5.5.2, c	AT1-BC:O	Yes [] No []

A.5.3 Asynchronous Type2 Bridge component capabilities

Item	Feature	Subclause	Status	Support
AT2-BC-1	Supports all asynchronous Type1 Bridge component requirements?	5.4.3, a	AT2-BC:M	Yes []
AT2-BC-2	Supports FRER?	5.4.3, b	AT2-BC:M	Yes []
AT2-BC-3	Supports monitoring for FRER?	5.4.3, c	AT2-BC:M	Yes []
AT2-BC-4	Supports operation of the credit-based shaper algorithm for all traffic classes?	5.5.3, b	AT2-BC:O	Yes [] No []
AT2-BC-5	Supports eight traffic queues?	5.5.3, b	AT2-BC:O	Yes [] No []
AT2-BC-6	Supports active destination MAC and VLAN stream identification functions?	5.5.3, c	AT2-BC:O	Yes [] No []
AT2-BC-7	Support a minimum number of stream identification and filtering entries as defined in Table 7-2? Indicate how many supported	5.5.3, d	AT2-BC:O	Yes [] No [] Qty. []

A.5.4 Synchronous Type1 Bridge component capabilities

Item	Feature	Subclause	Status	Support
ST1-BC-1	Supports all common Bridge component requirements?	5.4.4, a	ST1-BC:M	Yes []
ST1-BC-2	Supports eight traffic queues?	5.4.4, b	ST1-BC:M	Yes []
ST1-BC-3	Supports at least 2 PTP Instances on all physical ports? Indicate how many supported.	5.4.4, c	ST1-BC:M	Yes [] Qty. []
ST1-BC-4	Implements the PortSyncSyncSend state machine on all physical ports?	5.4.4, d	ST1-BC:M	Yes []
ST1-BC-5	Supports media-dependent timing and synchronization methods?	5.4.4, e	ST1-BC:M	Yes []
ST1-BC-6	Support a Fault-Tolerant Timing entity for all PTP Instances?	5.4.4, f	ST1-BC:M	Yes []
ST1-BC-7	Supports external port configuration capability on all ports?	5.4.4, g	ST1-BC:M	Yes []
ST1-BC-8	Supports PSFP stream gating?	5.4.4, h	ST1-BC:M	Yes []
ST1-BC-9	Supports enhancements for scheduled traffic on all ports?	5.4.4, i	ST1-BC:M	Yes []
ST1-BC-10	Supports the state machines for scheduled traffic?	5.4.4, j	ST1-BC:M	Yes []

A.5.4 Synchronous Type1 Bridge component capabilities *(continued)*

Item	Feature	Subclause	Status	Support
ST1-BC-11	Supports monitoring for scheduled traffic?	5.4.4, k	ST1-BC:M	Yes []
ST1-BC-12	Support monitoring for the FTT entity?	5.4.4, l	ST1-BC:M	Yes []
ST1-BC-13	Supports the monitoring requirements of time synchronization?	5.4.4, m	ST1-BC:M	Yes []
ST1-BC-14	Supports operation of the credit-based shaper algorithm on all ports and for all traffic classes?	5.5.4, b	ST1-BC:O	Yes [] No []
ST1-BC-15	Supports at least 3 PTP Instances on all physical ports? Indicate how many supported.	5.5.4, c	ST1-BC:O	Yes [] No [] Qty. []
ST1-BC-16	Supports the Grandmaster PTP Instance capability?	5.5.4, d	ST1-BC:O	Yes [] No []

A.5.5 Synchronous Type2 Bridge component capabilities

Item	Feature	Subclause	Status	Support
ST2-BC-1	Supports all synchronous Type1 Bridge component requirements?	5.4.5, a	ST2-BC:M	Yes []
ST2-BC-2	Supports at least 3 PTP Instances on all physical ports? Indicate how many supported.	5.4.5, b	ST2-BC:M	Yes [] Qty. []
ST2-BC-3	Supports FRER functions?	5.4.5, c	ST2-BC:M	Yes []
ST2-BC-4	Supports monitoring for FRER?	5.4.5, d	ST2-BC:M	Yes []
ST2-BC-5	Supports active destination MAC and VLAN stream identification functions?	5.5.5, c	ST2-BC:O	Yes [] No []
ST2-BC-6	Support minimum number of stream identification and filtering entries as defined in Table 7-2 Indicate how many supported.	5.5.5, d	ST2-BC:O	Yes [] No [] Qty. []
ST2-BC-7	Supports the Grandmaster PTP Instance capability?	5.5.5, b	ST2-BC:O	Yes [] No []
ST2-BC-8	Supports operation of the credit-based shaper algorithm on all ports and for all traffic classes?	5.5.5, b	ST2-BC:O	Yes [] No []

1 A.6 End station component implementations

2

A.6.1 Common end station component capabilities

The following table describes common end station component requirements and options.

Item	Feature	Subclause	Comment	Status	Support
EC-1	Supports a minimum of two traffic classes on all Ports?	5.6.1, a	Indicate how many supported	M	Yes [] Qty. []
EC-2	Supports the strict priority transmission algorithm on all ports for all traffic classes?	5.6.1, b		M	Yes []
EC-3	Supports operation of the credit-based shaper algorithm on all ports for at least 2 traffic classes?	5.6.1, c	Indicate how many supported	M	Yes [] Qty. []
EC-4	Support management entities for configuration of the end station?	5.6.1, d		M	Yes []
EC-5	Supports a minimum of eight Per-Stream traffic queues?	5.6.1, e	Indicate how many supported.	M	Yes [] Qty. []
EC-6	Supports operation of the credit-based shaper algorithm for at least two per-stream queues	5.6.1, f	Indicate how many supported	M	Yes [] Qty. []
EC-7	Supports use of customer VLAN identifiers?	5.7.1, a		O	Yes [] No []
EC-8	Supports the use of per-stream VLAN identifiers and PCP?	5.7.1, b		O	Yes [] No []
EC-9	Support the assignment of different destination MAC address to different streams	5.7.1, c		O	Yes [] No []
EC-10	Supports eight traffic queues?	5.7.1, d		O	Yes [] No []
EC-11	Supports a minimum of sixteen Per-Stream traffic queues?	5.7.1, e	Indicate how many supported.	O	Yes [] No [] Qty. []
EC-12	Supports operation of the credit-based shaper algorithm for all per-stream queues	5.7.1, f		O	Yes [] No []

3 Separate tables are included for Asynchronous and Synchronous, Type1 and Type2 end station
4 implementations. Suppliers should complete the PCS tables appropriate to the implementation they are
5 supplying.

6

A.6.2 Asynchronous Type1 end station component capabilities

Item	Feature	Subclause	Status	Support
AT1-EC-1	Supports all common end station component requirements	5.6.2, a	AT1-EC:M	Yes []

7

A.6.3 Asynchronous Type2 end station component capabilities

Item	Feature	Subclause	Status	Support
AT2-EC-1	Supports all asynchronous Type1 end station component requirements	5.6.3, a	AT2-EC:M	Yes []
AT2-EC-2	Supports FRER talker behavior	5.6.3, b	AT2-EC:M	Yes []
AT2-EC-3	Supports FRER listener behavior	5.6.3, c	AT2-EC:M	Yes []
AT2-EC-4	Supports monitoring of FRER	5.6.3, d	AT2-EC:M	Yes []
AT2-EC-5	Supports operation of the per-stream credit-based shaper algorithm for more than one stream?	5.7.3, b	AT2-EC:O	Yes [] No []
AT2-EC-6	Supports the FRER stream splitting function on more than one port and for more than one compound stream?	5.7.3, c	AT2-EC:O	Yes [] No []
AT2-EC-7	Supports FRER talker behavior on more than one port?	5.7.3, d	AT2-EC:O	Yes [] No []
AT2-EC-8	Supports FRER talker behavior for more than one compound stream?	5.7.3, e	AT2-EC:O	Yes [] No []
AT2-EC-9	Supports FRER listener behavior on more than one port?	5.7.3, f	AT2-EC:O	Yes [] No []
AT2-EC-10	Supports FRER listener behavior for more than 1 compound stream?	5.7.3, g	AT2-EC:O	Yes [] No []
AT2-EC-11	Support a minimum of 64 Per-Stream queues Indicate how many supported.	5.7.3, h	AT2-EC:O	Yes [] No [] Qty. []

7

A.6.4 Synchronous Type1 end station component capabilities

Item	Feature	Subclause	Status	Support
ST1-EC-1	Supports all common end station component requirements?	5.6.4, a	ST1-EC:M	Yes []
ST1-EC-2	Supports at least 2 PTP Instances on all physical ports? Indicate how many supported.	5.6.4, b	ST1-EC:M	Yes [] Qty. []
ST1-EC-3	Supports media-dependent timing and synchronization methods?	5.6.4, c	ST1-EC:M	Yes []
ST1-EC-4	Supports a Fault-Tolerant Timing entity for all PTP Instances?	5.6.4, d	ST1-EC:M	Yes []
ST1-EC-5	Supports external port configuration capability on all ports?	5.6.4, e	ST1-EC:M	Yes []
ST1-EC-6	Supports end station enhancements for scheduled traffic?	5.6.4, f	ST1-EC:M	Yes []
ST1-EC-7	Supports the monitoring requirements of scheduled traffic?	5.6.4, g	ST1-EC:M	Yes []
ST1-EC-8	Support monitoring for the FTT entity?	5.6.4, h	ST1-EC:M	Yes []
ST1-EC-9	Supports the monitoring requirements of time synchronization?	5.6.4, i	ST1-EC:M	Yes []

A.6.4 Synchronous Type1 end station component capabilities *(continued)*

Item	Feature	Subclause	Status	Support
ST1-EC-10	Supports at least 3 PTP Instances on all physical ports? Indicate how many supported.	5.7.4, b	ST1-EC:O	Yes [] No [] Qty. []
ST1-EC-11	Implements the PortSyncSyncSend state machine on all physical ports?	5.7.4, c	ST1-EC:O	Yes [] No []
ST1-EC-12	Supports the Grandmaster PTP Instance capability?	5.7.4, d	ST1-EC:O	Yes [] No []

7

A.6.5 Synchronous Type2 end station component capabilities

Item	Feature	Subclause	Status	Support
ST2-EC-1	Supports all synchronous Type1 end station component requirements?	5.6.5, a	ST2-EC:M	Yes []
ST2-EC-2	Supports at least 3 PTP Instances on all physical ports? Indicate how many supported.	5.6.5, b	ST2-EC:M	Yes [] No [] Qty. []
ST2-EC-3	Supports a Fault-Tolerant Timing entity for all PTP Instances?	5.6.5, c	ST2-EC:M	Yes []
ST2-EC-4	Supports FRER talker behavior?	5.6.5, d	ST2-EC:M	Yes []
ST2-EC-5	Supports FRER listener behavior?	5.6.5, e	ST2-EC:M	Yes []
ST2-EC-6	Supports monitoring of FRER?	5.6.5, f	ST2-EC:M	Yes []
ST2-EC-7	Supports the FRER stream splitting function on more than one port and for more than one compound stream?	5.7.5, c	ST2-EC:O	Yes [] No []
ST2-EC-8	Supports FRER talker behavior on more than one port?	5.7.5, d	ST2-EC:O	Yes [] No []
ST2-EC-9	Supports FRER talker behavior for more than one compound stream?	5.7.5, e	ST2-EC:O	Yes [] No []
ST2-EC-10	Supports FRER listener behavior on more than one port?	5.7.5, f	ST2-EC:O	Yes [] No []
ST2-EC-11	Supports FRER listener behavior for more than 1 compound stream?	5.7.5, g	ST2-EC:O	Yes [] No []
ST2-EC-12	Support a minimum of 64 Per-Stream queues? Indicate how many entries.	5.7.5, h	ST2-EC:O	Yes [] No [] Qty. []
ST2-EC-13	Implements the PortSyncSyncSend state machine on all physical ports?	5.7.4, c	ST2-EC:O	Yes [] No []
ST2-EC-14	Supports the Grandmaster PTP Instance capability?	5.7.4, d	ST2-EC:O	Yes [] No []

¹ **Annex B**

² (informative)

³ **Bibliography**

⁴ Bibliographical references are resources that provide additional or helpful material but do not need to be
⁵ understood or used to implement this standard. Reference to these resources is made for informational use
⁶ only.

⁷ [B1] ARINC Report 615A, Software Loader Using Ethernet Interface

⁸ [B2] ARINC Report 665, Loadable Software Standards

⁹ [B3] ARINC Specification 664 part 7, Avionics Full-Duplex Switched Ethernet Network

¹⁰ [B4] IEEE Std 802[®], IEEE Standard for Local and metropolitan area networks: Overview and Architecture.

¹¹ [B5] Jabbar-et-al, Summary of Aerospace Use Cases,

¹² <https://www.ieee802.org/1/files/public/docs2021/dp-Jabbar-Aerospace-UseCase-Summary-0521-v01.pdf>

¹³ [B6] Jabbar-et-al, Aerospace Traffic Characterization,

¹⁴ [https://www.ieee802.org/1/files/public/docs2021/dp-Jabbar-et-all-Aerospace-Traffic-Characterization-0421](https://www.ieee802.org/1/files/public/docs2021/dp-Jabbar-et-all-Aerospace-Traffic-Characterization-0421-v02.pdf)

¹⁵ [-v02.pdf](https://www.ieee802.org/1/files/public/docs2021/dp-Jabbar-et-all-Aerospace-Traffic-Characterization-0421-v02.pdf).

¹⁶ [B7] RTCA DO-178C, Software Considerations in Airborne Systems and Equipment Certification

¹⁷ [B8] RTCA DO-254, Design Assurance Guidance for Airborne Electronic Hardware

¹⁸ [B9] SAE ARP4754A/B, Guidelines for Development of Civil Aircraft and Systems

¹⁹ [B10] ARP4761/A, Guidelines for Conducting the Safety Assessment Process on Civil Aircraft, Systems,
²⁰ and Equipment

Annex C

(informative)

Example Aerospace Configuration

C.1 Introduction

In the highly regulated aerospace industry, the generation of complex network configurations is required to be traceable to system level requirements to help ensure that the system behavior is that which was intended and that unintended behavior is eliminated. TSN network configurations are no exception to this and system integrators often rely on tooling to develop the configurations used in the equipment that makes up the system for which TSN is being used.

Aerospace applications use a fully centralized configuration model to define an engineered static network topology. The specified profiles for TSN aerospace communications do not specify the process by which configurations are loaded into the network but leaves that to the integrator to define. This Annex is intended to provide an example for how this might be achieved in a typical commercial aerospace application.

C.2 Fully Centralized Aerospace Configuration

An example of an aerospace configuration is provided in Figure C-1 and explained below. In this example, a modeling tool is used to design the network topology and streams required by the application. Depending on the complexity of the required system and the expectations for through-life support, this tool can range from a series of spreadsheets to a model-based engineering tool.

The topology and configurations are developed from requirements that represent the required system behavior. A design modeling tool is used to generate all input to centralized configuration models (CUC & CNC) from which individual device configurations are derived. Consistent with aerospace practice, no direct communications occur between the CUC/CNC and Bridges or end stations. Instead, individual file-based device configurations are created and loaded into equipment during manufacture or at major service events. Aerospace qualified tools are used at each stage of configuration development to verify that configurations are accurate representations of the user requirements with configuration control maintained for individually identifiable items. Figure C-1 depicts the configuration model specified by the aerospace profiles. Physical links are implied between talkers, listeners and bridges but are excluded from the figure for clarity.

Whilst TSN configurations will use YANG configuration models, 7.6.2, aerospace equipment is expected to use vendor-specific binary configurations that are generated from the YANG models. Vendor supplied configuration tools are therefore expected to be supplied with equipment that performs translation from YANG models to vendor-specific binary data and that performs verification on the output to show that it matches the configuration requirements described in the YANG model.

The vendor-specific binary configuration data is packaged as loadable software using the ARINC 665 [B2] standard and uploaded to Bridges and end stations using an ARINC 615-A [B1] compliant data loader.




Figure C-1—Aerospace Configuration Model Example