Alfa 21 Plus

Vishal Diagnostics



TECHNICAL SPECIFICATIONS

Throughput: 60 Tests/hour

Mode: Whole blood, Pre-diluted

Total Parameters: 21

WBC, RBC, PLT, HGB, HCT, MCV, MCH, MCHC, PCT, MPV, PDW, RDW-CV, RDW-SD,P-LCC, P-LCR

3-Part Diff: LYM#, MID#, NEU#, LYM%, MID%, NEU%

Principle of Measurement

RBC/PLT/WBC/Diff: Electrical Impedance
Hb: Cyanide free Colorimetry
MCV/MPV: Measured

Histogram: 3/WBC/RBC/PLT

Sample Volume

Whole Blood: 10 µí
Pre Diluted mode: 20 µl

Calibration

Manual and Auto Calibration
HQ-CAL (4.5ml)

Quality Control
L-J graph,X-Bar Analysis, X-Mean Analysis
CBC-3D L, N, H (3ml)

High Caliber Detection

Aperture size - 68µ (RBC/PLT) and 100µ (WBC)
Automatic clog detection & prevention
High pressure back flush

Data Storage
1,00,000 results with Histograms
Data back-up through USB mass storage device

3 Part Differential Hematology Analyzer

- Throughput of 60 Tests/hour with 21 parameters
- Precision counting through High resolution cylindrical Aperture
- Sweep flow, PHM and PWM technology for reliable results
- Intelligent fault diagnosticswith clog and bubble detection

User Interface

10.4" touch screen display
Built-in Thermal printer
USB support with HP printers
PS2 port for Mouse and Keyboard
RS232 for LIS interface
5 USB+1 LAN+1 PS2 port

Power Requirement

100V-240V AC
50/60 HZ
100VA-180VA

Operating Environment

Temperature: 15C-35C
Humidity :<90%RH

Dimension (mm): 530x330x460

Weight (Kg): 23

Reagents

Diluent
Lyser
Detergent





Alfa - 5 | Auto Hematology Analyzer

| Specifications |	WBC/DIFF: Flow Cytometry, Semi-conductor laser light multi-dimensional cell classification
34 Parameters	WBC, LYM%, MON%, NEU%, EOS%, BAS%, LYM#, MON#, NEU#, EOS#, BAS#, RBC, HGB, HCT, MCV, MCH, MCHC, RDW_CV, RDW SD, PLT, MPV, PDW, PCT, P_LCR, P_LCC, RETIC%, RETIC_ABS, IRF Research Parameters: ALY#, ALY%, LIC#, LIC%, NRBC#, NRBC% 2 Histograms for RBC and PLT 2 Scatter grams: 5-part differential scatter gram Eosinophils and Moutrophils scatter gram 23-D stereograms
Principles of Operation	WBC Analysis: Optical and impedance measurements WBC Analysis: Optical and impedance measurements RBC/PLT Analysis: Impedance method HGB test: Cyanide-free reagent colorimetry
Reagent	Diluent, Sheath, Detergent, Lyse
Sampling modes	Whole blood: 20µL Pre-diluent: 20µL
Aperture Diameter	WBC 100µm | RBC/PLT 68µm
Throughput	Whole blood: up to 60 samples per hour Pre-diluent: up to 60 samples per hour
Data storage	Up to 200,000 sample results with grams
Alarms	Error messages
Display	10.4 inch with touch screen
Size	L490mm x H332mm x W459mm
Power	250VA
Weight	35KG

Samarth Agency

'Moreshwar', Plot No.10,
Abhiyantanagar, Islampur
Pin -415 409 Tal.Walwa,
Dist. Sangli, Maharastra

ph-
+918329160577 +919699637355
+918412821206 +919699627366

email-
sharadmore7517@gmail.com