sysmex | Lighting the way with diagnostics

Simplifying coagulation testing

CA-104

Basic Specifications

	Instrument Type	Semi-automated optical analyser for clotting assays
	Light Source	LED
	Parameters	PT, APTT, TT, Fibrinogen, Extrinsic and intrinsic factors
	Sample Volume	PT, APTT 50µL | Fbg 100µL TT 50-100µL | Factors 5µL
	Throughput	PT approx. 60 tests/hr | APTT approx. 30 tests/hr
Measurement	Principle	Turbodensitometric measuring principle
Measurement	Measurement Channels	Four with light protection caps
Measurement	Incubation Channels	Four reagent positions, sixteen cuvette positions
Sample & reagent handling	Sample Type	Centrifuged citrated plasma
Sample & reagent handling	Sample & Reagent Handling	Manual pipette, auto-start function
Sample & reagent handling	Reaction Tube Type	Single-use cuvettes with stir bars
Operation	Access Mode	Batch testing
Operation	LCD Display	Two lines with 20 characters each
Operation	Calibration Curve	Up to 9 calibration points can be stored
Operation	Programmable Methods	Up to 15 assays
Operation	Reportable Units	Seconds, INR, Percent, mg/dL
Operation	Temperature Control	Measurement channels and incubation positions are kept at approx. 37.4°C+/- 0.3°C
Operation	Printer	Integrated thermal printer , external printer connection as option
Operation	Interfaces	For connection to external printer, RS 232C interface is available
Technical	Dimensions	270W x 95H x 310D mm
Technical	Weight	2.9 kg
Technical	Operating Voltage	100 - 240VAC
Technical	Power Consumption	90VA
Technical	Operating Temperature	10°C - 30°C
Technical	Relative Humidity	Less than 85%



Samarth Agency

'Moreshwar', Plot No.10,
Abhiyantanagar, Islampur
Pin -415 409 Tal.Walwa,
Dist. Sangli, Maharastra

ph-
+918329160577 +919699637355
+918412821206 +919699627366