

FREE SETUP GUIDE · 10 MINUTES

Talk to Google Tag Manager. Literally.

Connect Claude or Cursor straight to your GTM containers and GA4 — audit, explore, and document in plain English. Read-only by default, so it's safe for client work.

Samarth GTM MCP — open source, MIT licensed

Swipe for the full setup →

An MCP server with 107 GTM + GA4 tools

- **Full GTM API v2 surface**

Tags, triggers, variables, versions, server-side containers, zones, custom templates.

- **Read-only GA4 included**

Admin + reporting tools to reconcile what's configured vs. what's actually collected.

- **Built-in audits**

Including a Consent Mode v2 engine validated by a 170-case test suite.

- **Works with any MCP client**

Claude Desktop, Claude Code, Cursor — local stdio or team HTTP deployment.

You need four things

- **Node.js 18 or newer**
- **A Google Cloud project**
With the Tag Manager API enabled (free).
- **A Google account with GTM access**
Whatever containers you can see, the AI can see.
- **An MCP client**
Claude Desktop, Claude Code, or Cursor.

No anonymous access exists for the GTM API — someone has to own an OAuth app. This guide uses your own (5 extra minutes, full control).

STEP 1 OF 3

Install & build

```
git clone github.com/samarthanalytics-sj/samarth-analytics-mcp
cd samarth-analytics-mcp && npm install
cp .env.example .env
npm run build
```

Then create an OAuth 2.0 Client ID (type: Desktop app) in Google Cloud Console and drop it into .env:

```
GOOGLE_OAUTH_CLIENT_ID=...apps.googleusercontent.com
GOOGLE_OAUTH_CLIENT_SECRET=your-client-secret
```

Authorize with Google — once

```
npm run auth:google
```

- **Opens your browser to Google's consent screen**
- **Captures the redirect automatically**
A tiny local callback server does the token exchange.
- **Saves tokens to a local, gitignored file**
Nothing to copy-paste. Re-run any time access expires.

Connect your AI client

Claude Desktop — add to `claude_desktop_config.json`:

```
{ "mcpServers": { "samarth-gtm": {  
  "command": "node",  
  "args": ["/path/to/dist/index.js"]  
} } }
```

Same JSON works in Cursor (Settings → MCP) and Claude Code (`.claude/mcp_config.json`). Keep credentials in `.env` — it's loaded automatically. Restart the client and you're live.

TRY THESE FIRST

Your first five prompts

“ List my GTM accounts and containers.

“ Audit container GTM-XXXXXXX for common GA4 implementation issues.

“ Show me every tag that fires on All Pages, with its triggers.

“ Export this workspace as JSON.

“ Compare what GA4 actually collects vs. what GTM is configured to send.

Safe for client containers

It ships read-only. Three separate flags gate every kind of change:

```
GTM_MCP_ENABLE_WRITES=false  
GTM_MCP_ENABLE_PUBLISH=false  
GTM_MCP_ENABLE_DELETES=false  
DRY_RUN=false # simulate writes
```

- **Every mutation also requires confirm: true**

Per call. The AI proposes; you approve.

- **Agency posture: leave them all false**

AI does the reading and auditing. You make the changes.

Built for real workloads

- **Automatic pagination**

List tools follow every page transparently, with safety bounds.

- **Retry with backoff + jitter**

Rate limits and transient errors are absorbed — on reads only. Mutations never auto-retry.

- **Two transports**

stdio for local clients; Streamable HTTP for team and cloud deployments.

- **Validated inputs, surfaced errors**

Zod schemas on every tool; detailed Google API errors back to the client.

Stop clicking. Start asking.

Samarth GTM MCP is open source under the MIT license. Star it, fork it, or open an issue:

github.com/samarthanalytics-sj/samarth-analytics-mcp

Follow Samarth Analytics for the next post: 5 prompts that replace an hour of GTM clicking.