



Windows 10

Report generated by Nessus™

Fri, 25 Aug 2023 21:21:55 IST

TABLE OF CONTENTS

Vulnerabilities by Host

- 192.168.56.1.....4

Nessus Essentials

Vulnerabilities by Host

192.168.56.1



Scan Information

Start time: Fri Aug 25 21:12:20 2023
End time: Fri Aug 25 21:21:55 2023

Host Information

Netbios Name: LAPTOP-S4O7NPQB
IP: 192.168.56.1
OS: EthernetBoard OkiLAN 8100e

Vulnerabilities

69552 - Oracle TNS Listener Remote Poisoning

Synopsis

It was possible to register with a remote Oracle TNS listener.

Description

The remote Oracle TNS listener allows service registration from a remote host. An attacker can exploit this issue to divert data from a legitimate database server or client to an attacker-specified system.

Successful exploits will allow the attacker to manipulate database instances, potentially facilitating man-in-the-middle, session- hijacking, or denial of service attacks on a legitimate database server.

See Also

<http://www.nessus.org/u?8c8334e6>
<http://www.nessus.org/u?06d298e5>
<https://seclists.org/fulldisclosure/2012/Apr/204>

Solution

Apply the workaround in Oracle's advisory.

Risk Factor

High

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.8 (CVSS:3.0/E:F/RL:O/RC:C)

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.8 (CVSS2#E:F/RL:W/RC:C)

References

BID 53308
CVE CVE-2012-1675
XREF CERT:359816

Exploitable With

Core Impact (true)

Plugin Information

Published: 2013/08/26, Modified: 2023/07/17

Plugin Output

tcp/1521/oracle_tnslnr

The remote Oracle TNS listener returned the following response to a registration request :

0x0000:	00 00 02 64 24 08 FF 03 01 00 12 34 34 78 78 34	...d\$.44xx4
0x0010:	78 10 10 32 10 32 10 32 54 76 10 32 10 32 54 76	x..2.2Tv.2.2Tv
0x0020:	00 78 10 32 54 76 00 00 38 02 00 80 07 00 00 00	.x.2Tv..8.....
0x0030:	00 00 00 00 00 00 00 00 00 00 00 00 00 05 00 00
0x0040:	10 00 00 00 02 00 00 00 00 00 00 00 70 72 7C 64pr d
0x0050:	57 02 00 00 05 00 00 00 00 00 00 00 00 00 00 00	W.....
0x0060:	00 00 00 00 00 00 00 00 00 00 00 00 20 47 8B 64 G.d
0x0070:	57 02 00 00 BC 91 FB 9F E8 86 4B CB B6 3D C5 18	W.....K..=..
0x0080:	C5 E3 42 40 05 00 00 00 0A 00 00 00 01 00 00 00	..B@.....
0x0090:	00 00 00 00 F0 74 7C 64 57 02 00 00 06 00 00 00t dW.....
0x00A0:	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00

0x00B0:	00 00 00 00 E0 3E 8B 64 57 02 00 00 6E 65 73 73>.dW...ness
0x00C0:	75 73 58 44 42 00 05 00 00 00 07 00 00 00 01 00	usXDB.....
0x00D0:	00 00 00 00 00 00 10 1B 93 64 57 02 00 00 06 00dW.....
0x00E0:	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
0x00F0:	00 00 00 00 00 00 20 3F 8B 64 57 02 00 00 6E 65 ?.dW...ne
0x0100:	73 73 75 73 00 05 00 00 00 37 00 00 00 01 00 00	ssus.....7.....
0x0110:	00 00 00 00 00 00 60 3F 8B 64 57 02 00 00 07 00 00`.?.dW.....
0x0120:	00 00 00 00 00 00 50 6D 7C 64 57 02 00 00 00 00 00Pm dW.....
0x0130:	00 00 00 00 00 00 E0 3F 8B 64 57 02 00 00 28 41 44?.dW... (AD
0x0140:	44 52 45 53 53 3D 28 50 52 4F 54 4F 43 4F 4C 3D	DRESS=(PROTOCOL=
0x0150:	54 43 50 29 28 48 4F 53 54 3D 31 39 32 2E 31 36	TCP) (HOST=192.16
0x0160:	38 2E 35 36 2E 31 29 28 50 4F 52 54 3D 31 35 32	8.56.1) (PORT=152
0x0170:	31 29 29 00 48 00 00 00 00 00 00 00 10 DF 07 64	1)).H.....d
0x0180:	57 02 00 00 00 00 00 00 00 00 00 00 28 44 45 53	W..... (DES
0x0190:	43 52 49 50 54 49 4F 4 [...]	

57608 - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

<http://www.nessus.org/u?df39b8b3>

<http://technet.microsoft.com/en-us/library/cc731957.aspx>

<http://www.nessus.org/u?74b80723>

<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>

<http://www.nessus.org/u?a3cac4ea>

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

12218 - mDNS Detection (Remote Network)

Synopsis

It is possible to obtain information about the remote host.

Description

The remote service understands the Bonjour (also known as ZeroConf or mDNS) protocol, which allows anyone to uncover information from the remote host such as its operating system type and exact version, its hostname, and the list of services it is running.

This plugin attempts to discover mDNS used by hosts that are not on the network segment on which Nessus resides.

Solution

Filter incoming traffic to UDP port 5353, if desired.

Risk Factor

Medium

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2004/04/28, Modified: 2021/06/28

Plugin Output

udp/5353/mdns

```
Nessus was able to extract the following information :
```

```
- mDNS hostname      : LAPTOP-S407NPQB.local.  
- Advertised services :  
  o Service name     : LAPTOP-S407NPQB._ni-logos._tcp.local.  
    Port number      : 2343
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2023/07/27

Plugin Output

tcp/0

```
Following application CPE matched on the remote system :  
cpe:/a:oracle:database_server -> Oracle Database Server
```

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/135/epmap

The following DCERPC services are available locally :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : samss lpc

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : SidKey Local End Point

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : protected_storage

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service

```
Named pipe : lsasspirpc

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : lsapolicylookup

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : LSA_EAS_ENDPOINT

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : LSA_IDPEXT_ENDPOINT

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Local RPC service
Named pipe : lsacap

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc [...]
```

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/445/cifs

The following DCERPC services are available remotely :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 650a7e26-eab8-5533-ce43-9c1dfce11511, version 1.0
Description : Unknown RPC service
Annotation : Vpn APIs
Type : Remote RPC service
Named pipe : \PIPE\ROUTER
Netbios name : \\LAPTOP-S4O7NPQB

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 2f5f6521-cb55-1059-b446-00df0bce31db, version 1.0
Description : Telephony service
Windows process : svchost.exe
Annotation : Unimodem LRPC Endpoint
Type : Remote RPC service
Named pipe : \pipe\tapsrv
Netbios name : \\LAPTOP-S4O7NPQB

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 7f1343fe-50a9-4927-a778-0c5859517bac, version 1.0
Description : Unknown RPC service
Annotation : DfsDs service
Type : Remote RPC service
Named pipe : \PIPE\wkssvc
Netbios name : \\LAPTOP-S4O7NPQB

Object UUID : 00000000-0000-0000-0000-000000000000

UUID : f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1.0
Description : Unknown RPC service
Annotation : Event log TCPIP
Type : Remote RPC service
Named pipe : \pipe\eventlog
Netbios name : \\LAPTOP-S407NPQB

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 1ff70682-0a51-30e8-076d-740be8cee98b, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\LAPTOP-S407NPQB

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 378e52b0-c0a9-11cf-822d-00aa0051e40f, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\LAPTOP-S407NPQB

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 33d84484-3626-47ee-8c6f-e7e98b113be1, version 2.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\LAPTOP-S407NPQB

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 86d35949-83c9-4044-b424-db363231fd0c, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbio [...]

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49664/dce-rpc

The following DCERPC services are available on TCP port 49664 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1.0
Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Remote RPC service
TCP Port : 49664
IP : 192.168.56.1

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0
Description : Security Account Manager
Windows process : lsass.exe
Type : Remote RPC service
TCP Port : 49664
IP : 192.168.56.1

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2.0
Description : Unknown RPC service
Annotation : KeyIso
Type : Remote RPC service
TCP Port : 49664
IP : 192.168.56.1

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 8fb74744-b2ff-4c00-be0d-9ef9a191felb, version 1.0

Description : Unknown RPC service
Annotation : Ngc Pop Key Service
Type : Remote RPC service
TCP Port : 49664
IP : 192.168.56.1

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49665/dce-rpc

The following DCERPC services are available on TCP port 49665 :

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49665
IP : 192.168.56.1

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49666/dce-rpc

The following DCERPC services are available on TCP port 49666 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 86d35949-83c9-4044-b424-db363231fd0c, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49666
IP : 192.168.56.1

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 3a9ef155-691d-4449-8d05-09ad57031823, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49666
IP : 192.168.56.1

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49667/dce-rpc

The following DCERPC services are available on TCP port 49667 :

```
Object UUID : 00000000-0000-0000-0000-000000000000
UUID : f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1.0
Description : Unknown RPC service
Annotation : Event log TCPIP
Type : Remote RPC service
TCP Port : 49667
IP : 192.168.56.1
```

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49668/dce-rpc

The following DCERPC services are available on TCP port 49668 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345678-1234-abcd-ef00-0123456789ab, version 1.0
Description : IPsec Services (Windows XP & 2003)
Windows process : lsass.exe
Type : Remote RPC service
TCP Port : 49668
IP : 192.168.56.1

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 0b6edbf8-4a24-4fc6-8a23-942b1eca65d1, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49668
IP : 192.168.56.1

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : ae33069b-a2a8-46ee-a235-ddfd339be281, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49668
IP : 192.168.56.1

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 4a452661-8290-4b36-8f8e-7f4093a94978, version 1.0
Description : Unknown RPC service
Type : Remote RPC service

TCP Port : 49668
IP : 192.168.56.1

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 76f03f96-cdfd-44fc-a22c-64950a001209, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49668
IP : 192.168.56.1

10736 - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

tcp/49696/dce-rpc

The following DCERPC services are available on TCP port 49696 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 367abb81-9844-35f1-ad32-98f038001003, version 2.0
Description : Service Control Manager
Windows process : svchost.exe
Type : Remote RPC service
TCP Port : 49696
IP : 192.168.56.1

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2022/09/09

Plugin Output

tcp/0

```
Remote device type : switch  
Confidence level : 65
```

42410 - Microsoft Windows NTLMSSP Authentication Request Remote Network Name Disclosure

Synopsis

It is possible to obtain the network name of the remote host.

Description

The remote host listens on tcp port 445 and replies to SMB requests.

By sending an NTLMSSP authentication request it is possible to obtain the name of the remote system and the name of its domain.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/11/06, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The following 2 NetBIOS names have been gathered :
```

```
LAPTOP-S407NPQB = Computer name  
LAPTOP-S407NPQB = Workgroup / Domain name
```


Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

tcp/445/cifs

```
Nessus was able to obtain the following information about the host, by  
parsing the SMB2 Protocol's NTLM SSP message:
```

```
Target Name: LAPTOP-S4O7NPQB  
NetBIOS Domain Name: LAPTOP-S4O7NPQB  
NetBIOS Computer Name: LAPTOP-S4O7NPQB  
DNS Domain Name: LAPTOP-S4O7NPQB  
DNS Computer Name: LAPTOP-S4O7NPQB  
DNS Tree Name: unknown  
Product Version: 10.0.19041
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/139/smb

```
An SMB server is running on this port.
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

100871 - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :  
SMBv2
```

106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

tcp/445/cifs

```
The remote host supports the following SMB dialects :
_version_  _introduced in windows version_
2.0.2      Windows 2008
2.1        Windows 7
3.0        Windows 8
3.0.2      Windows 8.1
3.1.1      Windows 10

The remote host does NOT support the following SMB dialects :
_version_  _introduced in windows version_
2.2.2      Windows 8 Beta
2.2.4      Windows 8 Beta
3.1        Windows 10
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2023/06/20

Plugin Output

tcp/135/epmap

```
Port 135/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2023/06/20

Plugin Output

tcp/139/smb

```
Port 139/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2023/06/20

Plugin Output

tcp/445/cifs

```
Port 445/tcp was found to be open
```


Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2023/06/20

Plugin Output

tcp/1521/oracle_tnslnr

```
Port 1521/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2023/06/20

Plugin Output

tcp/2343

```
Port 2343/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2023/06/20

Plugin Output

tcp/3580/www

```
Port 3580/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2023/07/31

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.5.4
Nessus build : 20013
Plugin feed version : 202308251403
Scanner edition used : Nessus Home
Scanner OS : LINUX
Scanner distribution : ubuntu1404-x86-64
Scan type : Normal
Scan name : Windows 10
```

```
Scan policy used : Basic Network Scan
Scanner IP : 10.0.2.15
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 54.242 ms
Thorough tests : no
Experimental tests : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin launched)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2023/8/25 21:12 IST
Scan duration : 554 sec
Scan for malware : no
```

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2022/03/09

Plugin Output

tcp/0

```
Remote operating system : EthernetBoard OkiLAN 8100e  
Confidence level : 65  
Method : SinFP
```

```
The remote host is running EthernetBoard OkiLAN 8100e
```

22073 - Oracle Database Detection

Synopsis

A database service is listening on the remote host.

Description

The remote host is running an Oracle database server.

It may be possible to extract the version number of the remote TNS (Transparent Network Substrate) listener by sending a 'VERSION'

request to the TNS listener service operating on this port.

Note that the version of the TNS listener does not necessarily reflect the version of the Oracle database it provides access to.

Solution

Restrict access to the database to allowed IPs only.

Risk Factor

None

Plugin Information

Published: 2006/07/19, Modified: 2023/07/17

Plugin Output

tcp/1521/oracle_tnslnr

The banner of the remote Oracle TNS listener on port 1521 contains the following version :

TNSLSNR for : Version 21.0.0.0.0

Note: This banner can be read without authentication.

10658 - Oracle Database tnslnr Service Remote Version Disclosure

Synopsis

An Oracle tnslnr service is listening on the remote port.

Description

The remote host is running the Oracle tnslnr service, a network interface to Oracle databases. This product allows a remote user to determine the presence and version number of a given Oracle installation.

Solution

Filter incoming traffic to this port so that only authorized hosts can connect to it.

Risk Factor

None

Plugin Information

Published: 2001/05/01, Modified: 2022/10/12

Plugin Output

tcp/1521/oracle_tnslnr

```
A TNS service is running on this port but it
refused to honor an attempt to connect to it.
(The TNS reply code was 4)
```


Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2023/08/08

Plugin Output

tcp/0

```
. You need to take the following action :  
[ Oracle TNS Listener Remote Poisoning (69552) ]  
+ Action to take : Apply the workaround in Oracle's advisory.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2023/07/10

Plugin Output

tcp/3580/www

```
A web server is running on this port.
```

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/06/26

Plugin Output

udp/0

```
For your information, here is the traceroute from 10.0.2.15 to 192.168.56.1 :  
10.0.2.15  
192.168.56.1  
  
Hop Count: 1
```

135860 - WMI Not Available

Synopsis

WMI queries could not be made against the remote host.

Description

WMI (Windows Management Instrumentation) is not available on the remote host over DCOM. WMI queries are used to gather information about the remote host, such as its current state, network interface configuration, etc.

Without this information Nessus may not be able to identify installed software or security vulnerabilities that exist on the remote host.

See Also

<https://docs.microsoft.com/en-us/windows/win32/wmisdk/wmi-start-page>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/04/21, Modified: 2023/07/17

Plugin Output

tcp/445/cifs

```
Can't connect to the 'root\CIMV2' WMI namespace.
```

10150 - Windows NetBIOS / SMB Remote Host Information Disclosure

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

tcp/445/cifs

```
The following 2 NetBIOS names have been gathered :
```

```
LAPTOP-S407NPQB = Computer name  
LAPTOP-S407NPQB = Workgroup / Domain name
```