

RSA Public and Private Key Generation

Jason Pearson and Sam Demorest

April 21, 2015

Used the in beta programming language Rust
Two separate programs reuse-ability
Public and private key generation
Encryption and decryption of characters

Implimentation

Miller-Rabin instead of AKS for speed

Modular exponentiation

ASCII representation of character for encrypting

Used an inverse function instead of Extended Euclidean Algorithm

Output

```
C:\Users\BuckDich\Documents\GitHub\rsa_keygen>cargo run 8
    Running `target\rsa_keygen 8`
Value of p = 151
Value of q = 157
Value of n = 23707
Value of totient = 23400
Value of e = 181
Value of d = 224821
Please Insert Letter To Encrypt
C
You sent in C

Number before mod 67
Encryption Time = 15618
Decryption Time = C

C:\Users\BuckDich\Documents\GitHub\rsa_keygen>
```

Conclusion

Able to determine large prime numbers

Able to encrypt one character and decrypt it

BigInt library not fully ready for deployment yet

No use of bit twiddling operations for optimization

Demo Time!

AKS References:

http://www.cse.iitk.ac.in/users/manindra/algebra/primality_v6.pdf

<http://mathworld.wolfram.com/AKSPrimalityTest.html>

Rust References:

<https://doc.rust-lang.org/>

<http://rustbyexample.com/>

<https://github.com/rust-lang/rust>

RSA Cryptosystem References:

<http://mathworld.wolfram.com/RSAEncryption.html>

<https://engineering.purdue.edu/kak/compsec/NewLectures/Lecture12.pdf>