

Support Vector Machines and its Applications

Kris De Brabanter

Iowa State University

I. Support Vector Machines (SVM)

- 1 Linear SVM classifier: separable case
- 2 Linear SVM classifier: non-separable case
- 3 Nonlinear SVM classifier

II. Least Squares Support Vector Machines (LS-SVM)

- 4 Least Squares Support Vector Machines
 - Primal space (Classification)
 - Dual space (Classification)
 - Regression in dual space
 - Properties
 - Examples


III. Fixed-Size Least Squares Support Vector Machines (FS-LSSVM)

- 5 Fixed-Size Least Squares Support Vector Machines
 - Problem formulation
 - Approximation for the feature map
 - Solution in primal space
 - Selection of support vectors
 - Examples and Comparison with SVM & LS-SVM



Part I

Support Vector Machines


Linear SVM classifier: separable case




Linear SVM classifier: separable case



Linear SVM classifier: separable case




Separating hyperplane not unique



Unique hyperplane

Linear SVM classifier: separable case



- Classification task
- IID data $\mathcal{D} = \{(X_k, Y_k)\}_{i=1}^n \subset \mathbb{R}^d \times \{-1, +1\}$
- When data is separable

$$\begin{cases} w^T X_i + b \geq +1, & \text{if } Y_i = +1 \\ w^T X_i + b \leq -1 & \text{if } Y_i = -1. \end{cases}$$

Linear SVM classifier: separable case

Maximize the margin subject to the fact all training data need to be correctly classified (Vapnik & Lerner, 1963)

Linear SVM classifier: separable case

Maximize the margin subject to the fact all training data need to be correctly classified (Vapnik & Lerner, 1963)

Optimization problem (P)

$$\begin{aligned} \min_{w,b} \mathcal{J}_P(w) &= \frac{1}{2} w^T w \\ \text{s.t.} \quad Y_k [w^T X_k + b] &\geq 1, \quad k = 1, \dots, n. \end{aligned}$$

Linear SVM classifier: separable case

Maximize the margin subject to the fact all training data need to be correctly classified (Vapnik & Lerner, 1963)

Optimization problem (P)

$$\begin{aligned} \min_{w,b} \mathcal{J}_P(w) &= \frac{1}{2} w^T w \\ \text{s.t.} \quad Y_k [w^T X_k + b] &\geq 1, \quad k = 1, \dots, n. \end{aligned}$$

Using Lagrange multipliers α_k (dual problem)

Optimization problem (D)

$$\begin{aligned} \max_{\alpha} \mathcal{J}_D(\alpha) &= -\frac{1}{2} \sum_{k,l=1}^n Y_k Y_l X_k^T X_l \alpha_k \alpha_l + \sum_{k=1}^n \alpha_k \\ \text{s.t.} \quad \sum_{k=1}^n \alpha_k Y_k &= 0 \end{aligned}$$

Linear SVM classifier: separable case

- ① Solution is given by

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k X_k^T x + \hat{b} \right] \quad (1)$$

Linear SVM classifier: separable case

- ① Solution is given by

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k X_k^T x + \hat{b} \right] \quad (1)$$

- ② Properties
- Global and unique solution

Linear SVM classifier: separable case

- ① Solution is given by

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k X_k^T x + \hat{b} \right] \quad (1)$$

- ② Properties

- Global and unique solution
- Sparseness \Rightarrow many α_k are equal to zero

Linear SVM classifier: separable case

- ① Solution is given by

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k X_k^T x + \hat{b} \right] \quad (1)$$

- ② Properties

- Global and unique solution
- Sparseness \Rightarrow many α_k are equal to zero
- Eq (1) can be written as $\hat{y}(x) = \text{sign} \left[\sum_{k=1}^{\#SV} \hat{\alpha}_k Y_k X_k^T x + \hat{b} \right]$

Linear SVM classifier: separable case

- ① Solution is given by


$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k X_k^T x + \hat{b} \right] \quad (1)$$

- ② Properties


- Global and unique solution
- Sparseness \Rightarrow many α_k are equal to zero
- Eq (1) can be written as $\hat{y}(x) = \text{sign} \left[\sum_{k=1}^{\#SV} \hat{\alpha}_k Y_k X_k^T x + \hat{b} \right]$
- Geometrical meaning of the support vectors

Linear SVM classifier: separable case


Toy Example: 25 data points in each class



Linear SVM classifier: non-separable case



Linear SVM classifier: non-separable case



- Tolerate misclassifications
- Introduce slack variables $\xi_k > 0$ (Cortes & Vapnik, 1995)
- $Y_k[w^T X_k + b] \geq 1 \rightarrow Y_k[w^T X_k + b] \geq 1 - \xi_k, \quad k = 1, \dots, n$

Nonlinear SVM classifier


- Extension of linear classifier (non-separable case) to nonlinear classifier (Vapnik, 1995)

Nonlinear SVM classifier

- Extension of linear classifier (non-separable case) to nonlinear classifier (Vapnik, 1995)
- Input data mapped to a high dimensional feature space by nonlinear mapping φ


Nonlinear SVM classifier

- Extension of linear classifier (non-separable case) to nonlinear classifier (Vapnik, 1995)
- Input data mapped to a high dimensional feature space by nonlinear mapping φ



Nonlinear SVM classifier


- Extension of linear classifier (non-separable case) to nonlinear classifier (Vapnik, 1995)
- Input data mapped to a high dimensional feature space by nonlinear mapping φ



- No explicit construction of φ needed (Mercer, 1909)

Nonlinear SVM classifier

- Extension of linear classifier (non-separable case) to nonlinear classifier (Vapnik, 1995)
- Input data mapped to a high dimensional feature space by nonlinear mapping φ



- No explicit construction of φ needed (Mercer, 1909)
- Using Mercer's condition: $K(x, z) = \varphi(x)^T \varphi(z)$ (Courant & Hilbert, 1953)

Nonlinear SVM classifier

Optimization problem (P)

$$\begin{aligned} \min_{w, b, \xi} \mathcal{J}_P(w, \xi) &= \frac{1}{2} w^T w + c \sum_{k=1}^n \xi_k \\ \text{s.t.} \quad & Y_k [w^T \varphi(X_k) + b] \geq 1 - \xi_k, \quad k = 1, \dots, n. \\ & \xi_k \geq 0, \quad k = 1, \dots, n. \end{aligned}$$

Nonlinear SVM classifier

Optimization problem (P)

$$\begin{aligned} \min_{w, b, \xi} \mathcal{J}_P(w, \xi) &= \frac{1}{2} w^T w + c \sum_{k=1}^n \xi_k \\ \text{s.t.} \quad &Y_k [w^T \varphi(X_k) + b] \geq 1 - \xi_k, \quad k = 1, \dots, n. \\ &\xi_k \geq 0, \quad k = 1, \dots, n. \end{aligned}$$

Using Lagrange multipliers α_k (dual problem) +
 $K(X_k, X_l) = \varphi(X_k)^T \varphi(X_l)$

Optimization problem (D)

$$\begin{aligned} \max_{\alpha} \mathcal{J}_D(\alpha) &= -\frac{1}{2} \sum_{k, l=1}^n Y_k Y_l K(X_k, X_l) \alpha_k \alpha_l + \sum_{k=1}^n \alpha_k \\ \text{s.t.} \quad &\sum_{k=1}^n \alpha_k Y_k = 0 \\ &0 \leq \alpha_k \leq c, \quad k = 1, \dots, n. \end{aligned}$$

Nonlinear SVM classifier

- ① Solution is given by

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k K(X_k, x) + \hat{b} \right] \quad (2)$$

Nonlinear SVM classifier

- 1 Solution is given by

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k K(X_k, x) + \hat{b} \right] \quad (2)$$

- 2 Properties
 - Global and unique solution

Nonlinear SVM classifier

- 1 Solution is given by

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k K(X_k, x) + \hat{b} \right] \quad (2)$$

- 2 Properties

- Global and unique solution
- Sparseness \Rightarrow many α_k are equal to zero

Nonlinear SVM classifier

- 1 Solution is given by

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k K(X_k, x) + \hat{b} \right] \quad (2)$$

- 2 Properties

- Global and unique solution
- Sparseness \Rightarrow many α_k are equal to zero
- Eq (2) can be written as

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^{\#SV} \hat{\alpha}_k Y_k K(X_k, x) + \hat{b} \right]$$

Nonlinear SVM classifier

- 1 Solution is given by

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^n \hat{\alpha}_k Y_k K(X_k, x) + \hat{b} \right] \quad (2)$$

- 2 Properties



- Global and unique solution
- Sparseness \Rightarrow many α_k are equal to zero
- Eq (2) can be written as

$$\hat{y}(x) = \text{sign} \left[\sum_{k=1}^{\#SV} \hat{\alpha}_k Y_k K(X_k, x) + \hat{b} \right]$$

- Geometrical meaning of the support vectors

nonlinear SVM classifier

- 1 LibSVM software (Chang & Lin, 2001)
- 2 Toy Example:
 - Ripley data set (250 data points)
 - Regression: sinc data (500 data points)



Part II

Least Squares Support Vector Machines

LS-SVM formulation

- Proposed by Suykens *et al.*, 1999

LS-SVM formulation

- Proposed by Suykens *et al.*, 1999
- WHY? Simplify the SVM formulation

LS-SVM formulation

- Proposed by Suykens *et al.*, 1999
- WHY? Simplify the SVM formulation
- Recall SVM formulation

Optimization problem (P)

$$\begin{aligned} \min_{w, b, \xi} \mathcal{J}_P(w, \xi) &= \frac{1}{2} w^T w + c \sum_{k=1}^n \xi_k \\ \text{s.t.} \quad Y_k [w^T \varphi(X_k) + b] &\geq 1 - \xi_k, \quad k = 1, \dots, n. \\ \xi_k &\geq 0, \quad k = 1, \dots, n. \end{aligned}$$

- LS-SVM formulation

Optimization problem (P)

$$\begin{aligned} \min_{w, b, e} \mathcal{J}_P(w, e) &= \frac{1}{2} w^T w + \frac{\gamma}{2} \sum_{k=1}^n e_k^2 \\ \text{s.t.} \quad Y_k [w^T \varphi(X_k) + b] &= 1 - e_k, \quad k = 1, \dots, n. \end{aligned}$$

LS-SVM formulation

- Using Lagrange multipliers, the solution is given by the LINEAR SYSTEM

$$\left(\begin{array}{c|c} 0 & Y^T \\ \hline Y & \Omega + \frac{1}{\gamma} I_n \end{array} \right) \begin{pmatrix} b \\ \alpha \end{pmatrix} = \begin{pmatrix} 0 \\ 1_n \end{pmatrix} \quad (3)$$

- $\Omega = Y_k Y_l \varphi(X_k)^T \varphi(X_l) = Y_k Y_l K(X_k, X_l)$
- Classifier in dual space
$$\hat{y}(x) = \text{sign} \left(\sum_{k=1}^n \hat{\alpha}_k Y_k K(x, X_k) + \hat{b} \right)$$
- $K(\cdot, \cdot)$ has to be positive definite
- Extension to multiclass problems (Suykens *et al.*, 2002)

LS-SVM formulation for regression

- Analog to the classification case
- Using Lagrange multipliers, the solution is given by the LINEAR SYSTEM

$$\left(\begin{array}{c|c} 0 & 1_v^T \\ \hline 1_v & \Omega + \frac{1}{\gamma} I_n \end{array} \right) \begin{pmatrix} b \\ \alpha \end{pmatrix} = \begin{pmatrix} 0 \\ Y \end{pmatrix} \quad (4)$$

- $\Omega = \varphi(X_k)^T \varphi(X_l) = K(X_k, X_l)$
- Regressor in dual space $\hat{y}(x) = \sum_{k=1}^n \hat{\alpha}_k K(x, X_k) + \hat{b}$
- $K(\cdot, \cdot)$ has to be positive definite

Properties of the LS-SVM

- ① Advantages
 - Linear system instead of QP

Properties of the LS-SVM

① Advantages

- Linear system instead of QP
- Global and unique solution


Properties of the LS-SVM

1 Advantages

- Linear system instead of QP
- Global and unique solution

2 Drawbacks

- Lack of sparseness: $\alpha_k = \gamma e_k \Rightarrow$ Pruning techniques




Properties of the LS-SVM

1 Advantages

- Linear system instead of QP
- Global and unique solution

2 Drawbacks



- Lack of sparseness: $\alpha_k = \gamma e_k \Rightarrow$ Pruning techniques



- No geometrical interpretation of the support vectors

Examples

- 1 LS-SVMLab software (De Brabanter *et al.*, 2010)
- 2 Toy Example:
 - Ripley data set (250 data points)
 - Regression: sinc data (200 data points)



Part III

Fixed-Size Least Squares Support Vector Machines

Problem formulation

- ① Can we solve the LS-SVM in primal space instead of dual?
- ② Approximation of feature map φ needed
- ③ Is it possible to compute such a mapping?
- ④ What to do when data sets are large?
 - $N = 1000 \Rightarrow K \Rightarrow 8 \text{ MB}$
 - $N = 10000 \Rightarrow K \Rightarrow 763 \text{ MB}$
 - $N = 20000 \Rightarrow K \Rightarrow 3051 \text{ MB}$

Approximation for the feature map

(Nyström, 1930; Williams & Seeger, 2001)

- "big" matrix: $\Omega_{n,n} \in \mathbb{R}^{n \times n}$, "small" matrix: $\Omega_{m,m} \in \mathbb{R}^{m \times m}$
(based on e.g. random subsample, in practice often $m \ll n$)
- Eigenvalue decompositions: $\Omega_{n,n} \tilde{U} = \tilde{U} \tilde{\Lambda}$ and $\Omega_{m,m} \bar{U} = \bar{U} \bar{\Lambda}$
- Relation to eigenvalues and eigenfunctions of the integral equation

$$\int K(x, x') \phi_i(x) dF_X(x) = \lambda_i \phi_i(x')$$

with

$$\hat{\lambda}_i = \frac{1}{m} \bar{\lambda}_i, \quad \hat{\phi}_i(x_k) = \sqrt{m \bar{u}_{ki}}, \quad \hat{\phi}_i(x') = \frac{\sqrt{m}}{\bar{\lambda}_i} \sum_{k=1}^m \bar{u}_{ki} K(x_k, x')$$

Solution in primal space

- Feature map

$$\hat{\phi}_i(x') = \sqrt{\bar{\lambda}_i} \phi_i(x') = \frac{1}{\sqrt{\bar{\lambda}_i}} \sum_{k=1}^m \bar{u}_{ki} K(x_k, x'), i = 1, \dots, m$$

Solution in primal space

- Feature map

$$\hat{\phi}_i(x') = \sqrt{\lambda_i} \phi_i(x') = \frac{1}{\sqrt{\lambda_i}} \sum_{k=1}^m \bar{u}_{ki} K(x_k, x'), i = 1, \dots, m$$

- recall

Optimization problem (P)

$$\min_{w, b} \mathcal{J}_P(w, b) = \frac{1}{2} w^T w + \frac{\gamma}{2} \sum_{k=1}^n (Y_k - (w^T \varphi(X_k) + b))^2$$

- ridge regression in primal space (Suykens *et al.*, 2002)

Solution in primal space

- solution is given by

$$\begin{pmatrix} w \\ b \end{pmatrix} = \left(\hat{\Phi}_e^T \hat{\Phi}_e + \frac{I_{m+1}}{\gamma} \right)^{-1} \hat{\Phi}_e^T Y,$$

where $\hat{\Phi}_e$ is the $n \times (m+1)$ extended feature matrix

$$\hat{\Phi}_e = \begin{pmatrix} \hat{\varphi}_1(X_1) & \cdots & \hat{\varphi}_m(X_1) & 1 \\ \vdots & \ddots & \vdots & \vdots \\ \hat{\varphi}_1(X_n) & \cdots & \hat{\varphi}_m(X_n) & 1 \end{pmatrix}$$

- model has the form: $\hat{y}(x) = w^T \hat{\varphi}(x) + b$

Selection of support vectors

De Brabanter *et al.*, 2010

- Use entropy based criterion instead of random

Selection of support vectors

De Brabanter *et al.*, 2010

- Use entropy based criterion instead of random
- Quadratic Rényi entropy: $H_{R2}^m(x) = -\log \int f(x)^2 dx$

Selection of support vectors

De Brabanter *et al.*, 2010

- Use entropy based criterion instead of random
- Quadratic Rényi entropy: $H_{R2}^m(x) = -\log \int f(x)^2 dx$
- $H_{R2}^m(x) = -\log \frac{1}{m^2 |H|^2} \sum_{k=1}^m \sum_{l=1}^m K \left\{ (H\sqrt{2})^{-1} (X_k - X_l) \right\}$

Selection of support vectors

De Brabanter *et al.*, 2010

- Use entropy based criterion instead of random
- Quadratic Rényi entropy: $H_{R2}^m(x) = -\log \int f(x)^2 dx$
- $H_{R2}^m(x) = -\log \frac{1}{m^2 |H|^2} \sum_{k=1}^m \sum_{l=1}^m K \left\{ (H\sqrt{2})^{-1} (X_k - X_l) \right\}$
 - RBF Kernel: $K(u) = \frac{1}{\sqrt{2\pi}} e^{-\frac{u^2}{2}}$

Selection of support vectors

De Brabanter *et al.*, 2010

- Use entropy based criterion instead of random
- Quadratic Rényi entropy: $H_{R2}^m(x) = -\log \int f(x)^2 dx$
- $H_{R2}^m(x) = -\log \frac{1}{m^2 |H|^2} \sum_{k=1}^m \sum_{l=1}^m K \left\{ (H\sqrt{2})^{-1} (X_k - X_l) \right\}$
 - RBF Kernel: $K(u) = \frac{1}{\sqrt{2\pi}} e^{-\frac{u^2}{2}}$
 - H is called the bandwidth matrix, $H = \text{diag}(h_1, \dots, h_d)$

Selection of support vectors

De Brabanter *et al.*, 2010

- Use entropy based criterion instead of random
- Quadratic Rényi entropy: $H_{R2}^m(x) = -\log \int f(x)^2 dx$
- $H_{R2}^m(x) = -\log \frac{1}{m^2|H|^2} \sum_{k=1}^m \sum_{l=1}^m K \left\{ (H\sqrt{2})^{-1} (X_k - X_l) \right\}$
 - RBF Kernel: $K(u) = \frac{1}{\sqrt{2\pi}} e^{-\frac{u^2}{2}}$
 - H is called the bandwidth matrix, $H = \text{diag}(h_1, \dots, h_d)$
 - Bandwidth choice \rightarrow relation with density estimation: plug-in bandwidth selectors, solve-the-equation rules,...

Selection of support vectors

De Brabanter *et al.*, 2010

- Use entropy based criterion instead of random
- Quadratic Rényi entropy: $H_{R2}^m(x) = -\log \int f(x)^2 dx$
- $H_{R2}^m(x) = -\log \frac{1}{m^2|H|^2} \sum_{k=1}^m \sum_{l=1}^m K \left\{ (H\sqrt{2})^{-1} (X_k - X_l) \right\}$
 - RBF Kernel: $K(u) = \frac{1}{\sqrt{2\pi}} e^{-\frac{u^2}{2}}$
 - H is called the bandwidth matrix, $H = \text{diag}(h_1, \dots, h_d)$
 - Bandwidth choice \rightarrow relation with density estimation: plug-in bandwidth selectors, solve-the-equation rules,...
 - For large data sets: fast evaluations of sums of Gaussians \rightarrow Improved Fast Gauss Transform (Yang *et al.*, 2003), (Raykar & Duraiswami, 2006,2007)

Selection of support vectors


- Goal is to maximize this entropy criterion

Entropy Maximization

$$\begin{aligned} \max_f H_{R^2}^m(f) &= -\log \int f^2(x) dx \\ \text{s.t.} \quad &\int f(x) dx = 1 \\ &f(x) \geq 0. \end{aligned}$$


Selection of support vectors

- Maximizing the entropy: algorithm (Suykens *et al.*, 2002)



Selection of support vectors

- Maximizing the entropy: algorithm (Suykens *et al.*, 2002)




Examples

- Tuning parameters tuned with fast v -fold CV (De Brabanter *et al.*, 2010)
- Minimizing CV cost: CSA + gridsearch (Xavier de Souza *et al.*, 2006; De Brabanter *et al.*, 2010)
- Movie: regression, Motorcycle data set (133 data points)


Examples

- Tuning parameters tuned with fast v -fold CV (De Brabanter *et al.*, 2010)
- Minimizing CV cost: CSA + gridsearch (Xavier de Souza *et al.*, 2006; De Brabanter *et al.*, 2010)
- Movie: regression, Motorcycle data set (133 data points)
- Classification: Ripley data set (FS-LSSVM: 40 sv's)

FS-LSSVM^{RBF}
 $\gamma=1.4038, \sigma^2=2.5142$, with 2 different classes



LS-SVM^{RBF}
 $\gamma=3.0841, \sigma^2=1.4869$, with 2 different classes






Examples

- System identification: large scale application (De Brabanter *et al.*, 2008b)
- SYSID2009 Wiener-Hammerstein Benchmark (188.000 data points, SISO system)
- Task: Given 100.000 training samples, simulate (iterative prediction) the following 88.000 samples
- Total of 2000 support vectors
- Selected kernel: RBF
- Tuning parameters tuned with fast v -fold CV
- Performance criteria: RMSE and fit percentage

$$f = 100 \left(1 - \frac{\|y - \hat{y}\|}{\|y - \bar{y}\|} \right)$$

Examples



Examples

- Results

Method	lags	RMSE _{test}	fit (%)
ARX	10	5.6×10^{-2}	76.47
MLP-NARX	11	2.3×10^{-2}	86.06
FS-LSSVM (Lin)	10	4.3×10^{-2}	81.93
FS-LSSVM (Poly)	10	6.0×10^{-3}	96.86
FS-LSSVM (RBF)	10	5.2×10^{-3}	97.78

Comparison with SVM & LS-SVM

- UCI data sets: Binary classification (misclassifications on test in %)

	spa	mgt	adu	ftc
N_{test}	1533	6020	12222	50000
n	57	11	14	54
# SV FS-LSSVM	200	1000	500	500
# SV C-SVC	800	7000	11085	185000
RBFS FS-LSSVM	92.5(0.67)	86.6(0.51)	85.21(0.21)	81.8(0.52)
Lin FS-LSSVM	90.9(0.75)	77.8(0.23)	83.9(0.17)	75.61(0.35)
RBFS C-SVC	92.6(0.76)	85.6(1.46)	84.81(0.20)	81.5(*)
Lin C-SVC	91.9(0.82)	77.3(0.53)	83.5(0.28)	75.24(*)
Maj. Rule	60.6(0.58)	65.8(0.28)	83.4(0.1)	51.23(0.20)

Comparison with SVM & LS-SVM

- UCI data sets: Binary classification (Computational time)

Av. Time (s)	spa	mgt	adu	ftc
RBF FS-LSSVM	44(5)	2103(64)	1601(208)	25160(523)
Lin FS-LSSVM	15(0.8)	276(3.8)	304(12)	1114(15)
RBF C-SVC	1010(53)	20603(396)	139730(5556)	58962(*)
Lin C-SVC	785(22)	13901(189)	130590(4771)	53478(*)

(*): no CV was performed. Timing is given for fixed tuning parameters

Comparison with SVM & LS-SVM

- UCI data sets: Regression

		bho	ccs
N_{test}		168	343
n		506	1030
# SV FS-LSSVM		135	120
# SV ε -SVR		226	670
RBF FS-LSSVM	L_2	0.13(0.02)	37.26(4.1)
	L_1	0.24(0.02)	4.47(0.26)
	L_∞	1.90(0.50)	27.78(5.43)
RBF ε -SVC	L_2	0.16(0.05)	62.24(5.8)
	L_1	0.24(0.03)	5.8(0.2)
	L_∞	2.20(0.54)	31.20(4.35)

Thanks for listening...

Questions???

References



Vapnik, V. and Lerner, A. (1963). Pattern Recognition using Generalized Portrait Method, *Automation and Remote Control* 24:774–780.



Cortes, C. and Vapnik, V. (1995), Support vector networks, *Machine Learning*, 20:273–297.



Vapnik, V. (1995), *The Nature of Statistical Learning*, Springer-Verlag, New York.



Mercer, J. (1909), Functions of positive and negative type and their connection with the theory of integral equations, *Philos. trans. Roy. Soc. London*, pp. 415–446.



Courant, R. and Hilbert, D. (1953), *Methods of Mathematical Physics*, International Science Publishers, New York.



Chang, C and Lin, C. (2001), LIBSVM: a library for support vector machines, Software available at <http://www.csie.ntu.edu.tw/~cjlin/libsvm>



Suykens, J. A. K. and Vandewalle, J. (1999), Least squares support vector machine classifiers, *Neural Processing Letters*, 9(3): 293–300.



Suykens, J. A. K., Van Gestel, T., De Brabanter, J., De Moor, B. and Vandewalle, J. (2002), *Least Squares Support Vector Machines*. World Scientific, Singapore.



De Brabanter K., Karsmakers P., Ojeda F., Alzate C., De Brabanter J., Pelckmans K., De Moor B., Vandewalle J. and Suykens J.A.K., *LS-SVMlab Toolbox User's Guide version 1.8*, Internal Report 10-146, ESAT-SISTA, K.U.Leuven (Leuven, Belgium).

References



Nyström, E. J. (1930), *Über die praktische Auflösung von Integralgleichungen mit Anwendungen auf Randwertaufgaben*, Acta Mathematica 54: 185–204.



Williams, C. K. I. and Seeger, M. (2001), *Using the Nyström method to speed up kernel machines*, Advances in Neural Information Processing Systems.



Girolami, M. (2002), *Orthogonal Series Density Estimation and the Kernel Eigenvalue Problem*, Neural Computation 14: 669–688.



De Brabanter, K., De Brabanter, J., Suykens, J.A.K. and De Moor, B., *Optimized Fixed-Size Least Squares Support Vector Machines for Large Datasets*, Computational Statistics & Data Analysis, vol. 54, no. 6, Jun. 2010, pp. 1484–1504.



Yang, C., Duraiswami, R., Gumerov, N. and Davis, L., (2003), *Improved fast Gauss transform and efficient kernel density estimation*. IEEE International Conference on Computer Vision 1, 464–471.



Raykar, V. C. and Duraiswami, R., (2006). *Fast optimal bandwidth selection for kernel density estimation*. Proc. of the 2006 SIAM International Conference on Data Mining, Bethesda, Maryland.



Raykar, V. C. and Duraiswami, R., (2007). Large-Scale Kernel Machines. MIT Press, Ch. The Improved Fast Gauss Transform with Applications to Machine Learning, pp. 175–202.



Xavier de Souza, S., Suykens, J. A. K., Vandewalle, J. and Bollé, D. (2006), *Cooperative Behavior in Coupled Simulated Annealing Processes with Variance Control*, Proc. of the International Symposium on Nonlinear Theory and its Applications (NOLTA2006), pp. 114–119.

References



De Brabanter K., Dreesen P., Karsmakers P., Pelckmans K., De Brabanter J., Suykens J.A.K. and De Moor B. (2008), *Fixed-Size LS-SVM Applied to the Wiener-Hammerstein Benchmark*, Internal Report 08-196, ESAT-SISTA, K.U.Leuven (Leuven, Belgium).