

CONTROLLED TECHNICAL DOCUMENT

NAWI TEST REPORT

Type evaluation and verification record

FINAL REPORT

TR-2026-000042

PASS

DEMONSTRATION / SYNTHETIC DATA

Synthetic observations are identified as such; reported results are the persisted application calculations.

INSTRUMENT IDENTIFICATION

Field	Recorded information
Manufacturer	gym
Applicant	meril
Model / type designation	gym
Serial number	asdasd
Accuracy class	Class II
Indication type	Self-indicating
Capacity	200 - 1,000 g
Verification interval e	10 g
Scale interval d	5 g

DOCUMENT CONTROL

Field	Recorded information
Report number	TR-2026-000042
Revision	01
Document status	FINAL REPORT
Issue date	24 Sept 2026, 19:34
Workflow status	Approved / completed

Field	Recorded information
Applicable standard	OIML R 76-1:2006
Laboratory	dr jhatka
Tester	samarth dubey
Reviewer	samarth dubey

APPLICANT AND MANUFACTURER

Field	Recorded information
Applicant	meril
Contact person	mrp
Email	meril@gmail.com
Telephone	+91 4234234234
Address	dasdasd
Manufacturer	gym
Manufacturer address	dasdasd

INSTRUMENT TECHNICAL SPECIFICATIONS

Field	Recorded information
Instrument type	gym
Manufacturer	gym
Serial number	asdasd
Accuracy class	Class II
Indication type	Self-indicating
Mass unit	g
Minimum capacity	200 g
Maximum capacity	1,000 g
Verification interval (e)	10 g
Scale interval (d)	5 g
Verification intervals (n)	100
Range / interval configuration	Single-Range / Single-Interval
Power source	AC Mains
Nominal voltage	230 V
Software version	eweqw
Load cell information	qweqw
Tare configuration	Subtractive - Semi-automatic

Field	Recorded information
Maximum tare effect	500 g
Stable equilibrium function	No
Multiple indicating devices	Yes
Printing capability	No
Data storage capability	No

TEST CONDITIONS

Parameter	Recorded start	Recorded end	Unit
Temperature	34	20	deg C
Relative humidity	34	50	%
Atmospheric pressure	41	1,013.25	hPa

Field	Recorded information
Evaluation started	24 Sept 2026, 00:04
Evaluation completed	24 Sept 2026, 18:04
Environmental notes	Synthetic Prototype / Regression Data - simulated end-of-session conditions for workflow verification; not a physical laboratory observation.

TEST EQUIPMENT AND CALIBRATION REFERENCES

No test equipment or calibration reference information is recorded.

APPLICABLE TEST SUMMARY

Test ID	Test description	Status	Result	Non-applicability reason
A.4.2	Checking of zero	Completed	PASS	
A.4.3	Setting to zero before loading	Completed	PASS	
A.4.4	Determination of weighing performance	Completed	PASS	
A.4.5	Multiple indicating devices	Completed	PASS	
A.4.6	Tare	Completed	PASS	
A.4.7	Eccentricity	Completed	PASS	
A.4.8	Discrimination	Completed	PASS	
A.4.9	Sensitivity of non-self-indicating instrument	NOT APPLICABLE	NOT APPLICABLE	Not applicable: A.4.9 is the sensitivity test for a non-self-indicating instrument.

Test ID	Test description	Status	Result	Non-applicability reason
A.4.10	Repeatability	Completed	PASS	
A.4.11	Variation of indication with time	Completed	PASS	
A.4.12	Stability of equilibrium	NOT APPLICABLE	NOT APPLICABLE	The instrument does not have a configured stable-equilibrium function.
A.4.13	Portable weighbridge tests	NOT APPLICABLE	NOT APPLICABLE	The instrument is not a portable road-vehicle weighbridge.
A.5	Influence Factors	Completed	PASS	
A.6	Endurance test	Completed	PASS	

DETAILED TEST RESULTS

A.4.2 - CHECKING OF ZERO

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A4.2-1.0
Technical reference	OIML R 76-1:2006 Annex A A.4.2
Started	24 Sept 2026, 00:04
Completed	24 Sept 2026, 03:16
Support / applicability reason	The instrument has a configured zero-setting function, so the A.4.2 checking-of-zero module applies.

Field	Recorded information
Test procedure version	R76-A4.2-1.0
Workflow status	COMPLETED
Result	PASS

Phases

Code	Name	Applicability	Workflow status	Result	Reason
A.4.2.1	Zero-setting Range	APPLICABLE	COMPLETED	OBSERVED	Use the non-automatic zero-setting-range procedure.
A.4.2.2	Zero Indicator	APPLICABLE	COMPLETED	OBSERVED	The instrument has a digital zero-indicating device.

Code	Name	Applicability	Workflow status	Result	Reason
A.4.2.3	Accuracy of Zero-setting	APPLICABLE	COMPLETED	PASS	Use the non-automatic or semi-automatic accuracy procedure (A.4.2.3.1).

Observations

Field	Recorded information
Starting Zero State	0
Applied Load	5
Zero Restored	Yes
Observed Positive Range	5
Observed Negative Range	5
Notes	Synthetic Prototype / Regression Data - zero range within the configured profile.
Unit	g
Input Applied Load	5
Input Observed Positive Range	5
Input Observed Negative Range	5

Observations

Field	Recorded information
Unit	g
Input Unit	g
Starting Indication	-5
Increment	0.5
Observed Lower Range	-5
Observed Upper Range	5
Input Starting Indication	-5
Input Observed Lower Range	-5
Input Observed Upper Range	5

Indication Observations

Sequence	Unit	Value	Input Value	Input Unit	Observed At
1	g	-5 g	-5 g	g	24 Sept 2026, 03:13

Sequence	Unit	Value	Input Value	Input Unit	Observed At
2	g	-4.5 g	-4.5 g	g	24 Sept 2026, 03:13
3	g	-4 g	-4 g	g	24 Sept 2026, 03:13
4	g	-3.5 g	-3.5 g	g	24 Sept 2026, 03:13
5	g	-3 g	-3 g	g	24 Sept 2026, 03:13
6	g	-2.5 g	-2.5 g	g	24 Sept 2026, 03:13
7	g	-2 g	-2 g	g	24 Sept 2026, 03:13
8	g	-1.5 g	-1.5 g	g	24 Sept 2026, 03:13
9	g	-1 g	-1 g	g	24 Sept 2026, 03:13
10	g	-0.5 g	-0.5 g	g	24 Sept 2026, 03:13
11	g	0 g	0 g	g	24 Sept 2026, 03:13
12	g	0.5 g	0.5 g	g	24 Sept 2026, 03:13
13	g	1 g	1 g	g	24 Sept 2026, 03:13
14	g	1.5 g	1.5 g	g	24 Sept 2026, 03:13
15	g	2 g	2 g	g	24 Sept 2026, 03:13
16	g	2.5 g	2.5 g	g	24 Sept 2026, 03:13
17	g	3 g	3 g	g	24 Sept 2026, 03:13
18	g	3.5 g	3.5 g	g	24 Sept 2026, 03:13
19	g	4 g	4 g	g	24 Sept 2026, 03:13
20	g	4.5 g	4.5 g	g	24 Sept 2026, 03:13
21	g	5 g	5 g	g	24 Sept 2026, 03:13

Calculations

Field	Recorded information
Calculated indication	500
Error	0
Corrected error	0
Calculated E0	0
Accuracy Class	II
Verification scale interval (e)	10
M	50

Field	Recorded information
Mpe Multiplier	0.5
Maximum permissible error	5
MPE unit	g
Technical reference	OIML R 76-1:2006 Section 3.5.1 Table 6
Reference edition	R76-1:2006
Range Label	>=0e to <=5000e
Compliance Result	PASS
Result	PASS

Observations

Field	Recorded information
Zero Indication I0	0
Additional load (Delta L0)	5
Load L	500
Indication I	500
Additional load (Delta L)	5
Notes	Synthetic Prototype / Regression Data - zero error and changeover readings are coherent with the configured Class II profile; values are simulated, not physical measurements.
Unit	g
Input Zero Indication I0	0
Input Delta L0	5
Input Load L	500
Input Indication I	500
Input Delta L	5

A.4.3 - SETTING TO ZERO BEFORE LOADING

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A4.3-1.0

Field	Recorded information
Method	Automatic zero-setting / zero-tracking
Technical reference	OIML R 76-1:2006 Annex A A.4.3(b)
Started	24 Sept 2026, 03:16
Completed	24 Sept 2026, 03:16
Test notes	Synthetic Prototype / Regression Data - A.4.3(b) carries the completed A.4.2.3 zero deviation into subsequent weighing; simulation only.
Support / applicability reason	For semi-automatic or automatic zero-setting, or zero-tracking, the deviation from zero is determined according to A.4.2.3.

Field	Recorded information
Test procedure version	R76-A4.3-1.0
Workflow status	COMPLETED
Result	PASS
Method Used	A.4.3(b)
Method Label	Automatic zero-setting / zero-tracking
Source Phase	A.4.2.3
Zero Reference Established	Yes
Zero Deviation	0
Zero Deviation Unit	g
Execution Mode	Synthetic Simulation
Operator Notes	Synthetic Prototype / Regression Data - A.4.3(b) carries the completed A.4.2.3 zero deviation into subsequent weighing; simulation only.

Source Evidence

Field	Recorded information
Result	PASS
Completed	24 Sept 2026, 03:16

Observations

Field	Recorded information
Zero Indication I0	0
Additional load (Delta L0)	5
Load L	500

Field	Recorded information
Indication I	500
Additional load (Delta L)	5
Notes	Synthetic Prototype / Regression Data - zero error and changeover readings are coherent with the configured Class II profile; values are simulated, not physical measurements.
Unit	g
Input Zero Indication I0	0
Input Delta L0	5
Input Load L	500
Input Indication I	500
Input Delta L	5

Calculations

Field	Recorded information
Calculated indication	500
Error	0
Corrected error	0
Calculated E0	0
Accuracy Class	II
Verification scale interval (e)	10
M	50
Mpe Multiplier	0.5
Maximum permissible error	5
MPE unit	g
Technical reference	OIML R 76-1:2006 Section 3.5.1 Table 6
Reference edition	R76-1:2006
Range Label	>=0e to <=5000e
Compliance Result	PASS
Result	PASS

A.4.4 - DETERMINATION OF WEIGHING PERFORMANCE

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Technical reference	OIML R 76-1:2006 Annex A A.4.4
Started	24 Sept 2026, 03:23
Completed	24 Sept 2026, 03:24
Support / applicability reason	The weighing-performance procedure is available for a configured single-range, single-interval NAWI.

Weighing observations

No.	Applied load / indication / Delta L	P / Error Ec	MPE	Result
1	200 / 200 / 5 g	200 / 0 g	+/-5 g	PASS
2	250 / 250 / 5 g	250 / 0 g	+/-5 g	PASS
3	300 / 300 / 5 g	300 / 0 g	+/-5 g	PASS
4	500 / 500 / 5 g	500 / 0 g	+/-5 g	PASS
5	600 / 600 / 5 g	600 / 0 g	+/-5 g	PASS
6	1,000 / 1,000 / 5 g	1,000 / 0 g	+/-5 g	PASS
7	950 / 950 / 5 g	950 / 0 g	+/-5 g	PASS
8	900 / 900 / 5 g	900 / 0 g	+/-5 g	PASS
9	750 / 750 / 5 g	750 / 0 g	+/-5 g	PASS
10	210 / 210 / 5 g	210 / 0 g	+/-5 g	PASS

Field	Recorded information
Workflow status	COMPLETED
Result	PASS
Reference edition	R76-1:2006
Supported	Yes
Observation Unit	g

Zero reference

Field	Recorded information
Unit	g
Zero Indication	0

Field	Recorded information
Additional load (Delta L0)	5
Input Zero Indication	0
Input Delta L0	5
Calculated E0	0
Recorded	24 Sept 2026, 03:23

A.4.5 - MULTIPLE INDICATING DEVICES

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A4.5-1.0
Technical reference	OIML R 76-1:2006 Section 3.6.3; comparison during Annex A A.4.4
Completed	24 Sept 2026, 17:03
Support / applicability reason	The instrument has multiple indicating devices.

Field	Recorded information
Test procedure version	R76-A4.5-1.0
Method / reference	OIML R 76-1:2006 Section 3.6.3; comparison during Annex A A.4.4
Workflow status	PASS
Result	PASS

Comparisons

Sequence	Result	Load	Unit	Direction	Difference
1	PASS	200 g	g	INCREASING	0
2	PASS	250 g	g	INCREASING	0
3	PASS	300 g	g	INCREASING	0
4	PASS	500 g	g	INCREASING	0
5	PASS	600 g	g	INCREASING	0
6	PASS	1,000 g	g	INCREASING	0
7	PASS	950 g	g	DECREASING	0

Sequence	Result	Load	Unit	Direction	Difference
8	PASS	900 g	g	DECREASING	0
9	PASS	750 g	g	DECREASING	0
10	PASS	210 g	g	DECREASING	0

Devices

Label	Indication	Unit	Device Id	Type
Device 1	200 g	g	Device 1	DISPLAY
Device 2	200 g	g	Device 2	DISPLAY

Devices

Label	Indication	Unit	Device Id	Type
Device 1	250 g	g	Device 1	DISPLAY
Device 2	250 g	g	Device 2	DISPLAY

Devices

Label	Indication	Unit	Device Id	Type
Device 1	300 g	g	Device 1	DISPLAY
Device 2	300 g	g	Device 2	DISPLAY

Devices

Label	Indication	Unit	Device Id	Type
Device 1	500 g	g	Device 1	DISPLAY
Device 2	500 g	g	Device 2	DISPLAY

Devices

Label	Indication	Unit	Device Id	Type
Device 1	600 g	g	Device 1	DISPLAY
Device 2	600 g	g	Device 2	DISPLAY

Devices

Label	Indication	Unit	Device Id	Type
Device 1	1,000 g	g	Device 1	DISPLAY

Label	Indication	Unit	Device Id	Type
Device 2	1,000 g	g	Device 2	DISPLAY

Devices

Label	Indication	Unit	Device Id	Type
Device 1	950 g	g	Device 1	DISPLAY
Device 2	950 g	g	Device 2	DISPLAY

Devices

Label	Indication	Unit	Device Id	Type
Device 1	900 g	g	Device 1	DISPLAY
Device 2	900 g	g	Device 2	DISPLAY

Devices

Label	Indication	Unit	Device Id	Type
Device 1	750 g	g	Device 1	DISPLAY
Device 2	750 g	g	Device 2	DISPLAY

Devices

Label	Indication	Unit	Device Id	Type
Device 1	210 g	g	Device 1	DISPLAY
Device 2	210 g	g	Device 2	DISPLAY

A.4.6 - TARE

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A4.6-1.0
Technical reference	OIML R 76-1:2006 Annex A A.4.6
Started	24 Sept 2026, 17:21
Completed	24 Sept 2026, 17:23

Field	Recorded information
Support / applicability reason	A tare device and the characteristics needed for the tare procedures are configured.

Field	Recorded information
Test procedure version	R76-A4.6-1.0
Method / reference	OIML R 76-1:2006 Annex A A.4.6
Workflow status	COMPLETED
Result	PASS

Tare Configuration Snapshot

Field	Recorded information
Tare Device Present	Yes
Tare Type	SUBTRACTIVE
Tare Operation Mode	Semi-automatic
Tare Weighing Device Present	No
Preset Tare Device Present	No

Maximum Tare Effect

Field	Recorded information
Value	500
Unit	g

Phases

Code	Name	Applicability	Workflow status	Result	Reason
A.4.6.1	Tare weighing test	APPLICABLE	LOCKED	PASS	Perform loading and unloading with the configured tare arrangement.
A.4.6.2	Accuracy of tare setting	APPLICABLE	COMPLETED	PASS	Establish tare-setting accuracy with the indication set to zero by the tare device.
A.4.6.3	Tare weighing device	Not applicable	Not applicable	Not recorded	Not applicable - the instrument has no separate tare-weighing device.

Observations

Sequence	Result	Indication I	Additional load (Delta L)	Corrected error	Maximum permissible error
----------	--------	--------------	---------------------------	-----------------	---------------------------

Sequence	Result	Indication I	Additional load (Delta L)	Corrected error	Maximum permissible error
1	PASS	200 g	5 g	0 g	5 g
2	PASS	338 g	5 g	0 g	5 g
3	PASS	475 g	5 g	0 g	5 g
4	PASS	613 g	5 g	0 g	5 g
5	PASS	750 g	5 g	0 g	5 g

Observations

Sequence	Result	Additional load (Delta L)	Unit	Notes	Input Delta L
1	PASS	5 g	g	Synthetic Prototype / Regression Data - simulated tare-setting observation.	5 g
2	PASS	5 g	g	Synthetic Prototype / Regression Data - simulated tare-setting observation.	5 g
3	PASS	5 g	g	Synthetic Prototype / Regression Data - simulated tare-setting observation.	5 g
4	PASS	5 g	g	Synthetic Prototype / Regression Data - simulated tare-setting observation.	5 g
5	PASS	5 g	g	Synthetic Prototype / Regression Data - simulated tare-setting observation.	5 g

Calculations

Field	Recorded information
Last Error E0	0
Accuracy Limit	2.5
Result	PASS
Source Phase	A.4.2.3

Procedure

Field	Recorded information
Tare Load Fraction	0.3
Recommended Tare Load	300
Load L0	100
Load L0 Is Applied	Yes

Field	Recorded information
Accuracy Limit	2.5
Repetitions	5

Completion

Field	Recorded information
Required Repetitions	5
Valid Repetitions	5
Complete	Yes
Result	PASS
Reason	All 5 tare-setting repetitions are recorded.

A.4.7 - ECCENTRICITY**TEST RESULT: PASS**

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A4.7-1.0
Method	Mobile instrument - applicable four-quarter platform positions
Technical reference	OIML R 76-1:2006 Annex A A.4.7; calculation A.4.4.3
Started	24 Sept 2026, 17:26
Completed	24 Sept 2026, 17:27
Support / applicability reason	The instrument configuration determines the applicable eccentricity method and loading positions. For this mobile instrument, A.4.7.5 applies the configured normal-platform A.4.7.1 four-quarter procedure as applicable.

Field	Recorded information
Test procedure version	R76-A4.7-1.0
Method / reference	OIML R 76-1:2006 Annex A A.4.7; calculation A.4.4.3
Method	A.4.7.1
Method Label	Mobile instrument - applicable four-quarter platform positions
Execution Supported	Yes
Support Point Count	4

Field	Recorded information
Position Count	4
Workflow status	COMPLETED
Result	PASS
Zero Condition Confirmed	Yes

Test Load

Field	Recorded information
Value	330
Unit	g

Sketch

Field	Recorded information
Type	four-quarter-normal-platform
Method / reference	OIML R 76-1:2006 Annex A A.4.7.1

Position Ids

Position 1 - Position 2 - Position 3 - Position 4

Positions

Label	Workflow status	Result	Completed	Position Id	Loading Area
Quarter 1	COMPLETED	PASS	24 Sept 2026, 17:26	Position 1	Approximately one quarter of the load-receptor surface.
Quarter 2	COMPLETED	PASS	24 Sept 2026, 17:26	Position 2	Approximately one quarter of the load-receptor surface.
Quarter 3	COMPLETED	PASS	24 Sept 2026, 17:27	Position 3	Approximately one quarter of the load-receptor surface.
Quarter 4	COMPLETED	PASS	24 Sept 2026, 17:27	Position 4	Approximately one quarter of the load-receptor surface.

Observations

Load L	Indication I	Additional load (Delta L)	Corrected error	Maximum permissible error	Unit
330 g	330 g	5 g	0 g	5 g	g

Observations

Load L	Indication I	Additional load (Delta L)	Corrected error	Maximum permissible error	Unit
330 g	330 g	5 g	0 g	5 g	g

Observations

Load L	Indication I	Additional load (Delta L)	Corrected error	Maximum permissible error	Unit
330 g	330 g	5 g	0 g	5 g	g

Observations

Load L	Indication I	Additional load (Delta L)	Corrected error	Maximum permissible error	Unit
330 g	330 g	5 g	0 g	5 g	g

A.4.8 - DISCRIMINATION

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A4.8-1.0
Method	A.4.8.2
Technical reference	OIML R 76-1:2006 Annex A A.4.8.2
Started	24 Sept 2026, 17:27
Completed	24 Sept 2026, 17:28
Support / applicability reason	The digital discrimination procedure is applicable for this configured instrument.

Field	Recorded information
Test procedure version	R76-A4.8-1.0
Method / reference	OIML R 76-1:2006 Annex A A.4.8.2
Method	A.4.8.2
Workflow status	COMPLETED
Result	PASS

Stages

Label	Workflow status	Result	Completed	Order	Recommended Increment Count
Min	COMPLETED	PASS	24 Sept 2026, 17:27	1	10
½ Max	COMPLETED	PASS	24 Sept 2026, 17:28	2	10
Max	COMPLETED	PASS	24 Sept 2026, 17:28	3	10

Target Load

Field	Recorded information
Value	200
Unit	g

One Tenth D

Field	Recorded information
Value	0.5
Unit	g

One Point Four D

Field	Recorded information
Value	7
Unit	g

Observation

Field	Recorded information
Unit	g
Input Base Load	200
Input Starting Indication	200
Input Removed Additional Load	5
Input Lower Indication	195
Input Restored Increment	0.5
Input Applied Additional Load	7
Input Upper Indication	205
Base Load	200
Starting Indication	200

Field	Recorded information
Additional Increment Count	10
Removed Additional Load	5
Lower Indication	195
Restored Increment	0.5
Applied Additional Load	7
Upper Indication	205
One Tenth D	0.5
One Point Four D	7
Expected Lower Indication	195
Expected Upper Indication	205
Actual Lower Difference	5
Actual Upper Difference	5
Lower Pass	Yes
Upper Pass	Yes
Result	PASS
Technical reference	OIML R 76-1:2006 Annex A A.4.8.2
Reference edition	R76-A4.8-1.0
Notes	Synthetic Prototype / Regression Data - nominal digital transition at Min.
Recorded	24 Sept 2026, 17:27

Target Load

Field	Recorded information
Value	500
Unit	g

One Tenth D

Field	Recorded information
Value	0.5
Unit	g

One Point Four D

Field	Recorded information
Value	7
Unit	g

Observation

Field	Recorded information
Unit	g
Input Base Load	500
Input Starting Indication	500
Input Removed Additional Load	5
Input Lower Indication	495
Input Restored Increment	0.5
Input Applied Additional Load	7
Input Upper Indication	505
Base Load	500
Starting Indication	500
Additional Increment Count	10
Removed Additional Load	5
Lower Indication	495
Restored Increment	0.5
Applied Additional Load	7
Upper Indication	505
One Tenth D	0.5
One Point Four D	7
Expected Lower Indication	495
Expected Upper Indication	505
Actual Lower Difference	5
Actual Upper Difference	5
Lower Pass	Yes
Upper Pass	Yes
Result	PASS

Field	Recorded information
Technical reference	OIML R 76-1:2006 Annex A A.4.8.2
Reference edition	R76-A4.8-1.0
Notes	Synthetic Prototype / Regression Data - nominal digital transition at half maximum.
Recorded	24 Sept 2026, 17:28

Target Load

Field	Recorded information
Value	1,000
Unit	g

One Tenth D

Field	Recorded information
Value	0.5
Unit	g

One Point Four D

Field	Recorded information
Value	7
Unit	g

Observation

Field	Recorded information
Unit	g
Input Base Load	1,000
Input Starting Indication	1,000
Input Removed Additional Load	5
Input Lower Indication	995
Input Restored Increment	0.5
Input Applied Additional Load	7
Input Upper Indication	1,005
Base Load	1,000

Field	Recorded information
Starting Indication	1,000
Additional Increment Count	10
Removed Additional Load	5
Lower Indication	995
Restored Increment	0.5
Applied Additional Load	7
Upper Indication	1,005
One Tenth D	0.5
One Point Four D	7
Expected Lower Indication	995
Expected Upper Indication	1,005
Actual Lower Difference	5
Actual Upper Difference	5
Lower Pass	Yes
Upper Pass	Yes
Result	PASS
Technical reference	OIML R 76-1:2006 Annex A A.4.8.2
Reference edition	R76-A4.8-1.0
Notes	Synthetic Prototype / Regression Data - nominal digital transition at maximum.
Recorded	24 Sept 2026, 17:28

A.4.9 - SENSITIVITY OF NON-SELF-INDICATING INSTRUMENT

TEST RESULT: NOT APPLICABLE

Field	Recorded information
Status	NOT APPLICABLE
Reason	Not applicable: A.4.9 is the sensitivity test for a non-self-indicating instrument.

A.4.10 - REPEATABILITY

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A4.10-1.0
Method	Same Load Repeat Weighings
Technical reference	OIML R 76-1:2006 Section 3.6.1 / Annex A A.4.10
Started	24 Sept 2026, 17:28
Completed	24 Sept 2026, 17:29
Support / applicability reason	The repeatability procedure is included for the configured NAWI test route.

Field	Recorded information
Test procedure version	R76-A4.10-1.0
Method / reference	OIML R 76-1:2006 Section 3.6.1 / Annex A A.4.10
Control Stage	VERIFICATION
Method	Same Load Repeat Weighings
Workflow status	COMPLETED
Result	PASS
Zero Reference E0	0
Observation Unit	g

Procedure Confirmation

Field	Recorded information
Automatic Zero On Confirmed	Yes
Unloaded Instrument Rest Confirmed	Yes
Confirmed At	24 Sept 2026, 17:28
Tester Name Snapshot	samarth dubey

Series

Label	Workflow status	Result	Completed	Series Id	Order
Approximately 80% of Max	COMPLETED	PASS	24 Sept 2026, 17:29	Series 1	1

Target Load

Field	Recorded information
Value	800
Unit	g

Observations

Indication	Additional load (Delta L)	Corrected error	Maximum permissible error	Unit	Notes
800 g	5 g	0 g	5 g	g	Synthetic Prototype / Regression Data - repeatability weighing 1 of 6 at the derived 80% Max target.
800 g	5 g	0 g	5 g	g	Synthetic Prototype / Regression Data - repeatability weighing 2 of 6 at the derived 80% Max target.
800 g	5 g	0 g	5 g	g	Synthetic Prototype / Regression Data - repeatability weighing 3 of 6 at the derived 80% Max target.
800 g	5 g	0 g	5 g	g	Synthetic Prototype / Regression Data - repeatability weighing 4 of 6 at the derived 80% Max target.
800 g	5 g	0 g	5 g	g	Synthetic Prototype / Regression Data - repeatability weighing 5 of 6 at the derived 80% Max target.
800 g	5 g	0 g	5 g	g	Synthetic Prototype / Regression Data - repeatability weighing 6 of 6 at the derived 80% Max target.

Summary

Field	Recorded information
Target Mpe Rule	OIML R 76-1:2006 Section 3.5.1 Table 6
Minimum Result	800
Maximum Result	800
Repeatability Range	0
Absolute Mpe	5
Result	PASS

Target Mpe

Field	Recorded information
Value	5
Unit	g

Maximum permissible error

Field	Recorded information
Value	5
Unit	g

A.4.11 - VARIATION OF INDICATION WITH TIME

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A4.11-1.0
Method	A.4.11.1 + A.4.11.2
Technical reference	OIML R 76-1:2006 Section 3.9.4 / Annex A A.4.11
Started	24 Sept 2026, 17:29
Completed	24 Sept 2026, 18:31
Support / applicability reason	The creep and zero-return procedures apply to accuracy Classes II, III and IIII.

Field	Recorded information
Test procedure version	R76-A4.11-1.0
Method / reference	OIML R 76-1:2006 Section 3.9.4 / Annex A A.4.11
Method	A.4.11.1 + A.4.11.2
Workflow status	COMPLETED
Result	PASS
Observation Unit	g

Plan

Field	Recorded information
Method	A.4.11.1 + A.4.11.2
Execution Supported	Yes
Method / reference	OIML R 76-1:2006 Section 3.9.4 / Annex A A.4.11

Recommended Load

Field	Recorded information
-------	----------------------

Field	Recorded information
Value	1,000
Unit	g

Creep Checkpoints

Checkpoint	Minutes
T0	0
T5	5
T15	15
T30	30
T60	60
T120	120
T180	180
T240	240

Zero Return Limit

Field	Recorded information
Value	5
Unit	g
Rule	0.5e for a single-range, single-interval instrument.

Procedure Confirmation

Field	Recorded information
Normal Oscillation Confirmed	Yes
Confirmed At	24 Sept 2026, 17:30
Tester Name Snapshot	samarth dubey

Environmental Readings

20 - 20 - 20 - 20

Creep

Field	Recorded information
Workflow status	COMPLETED

Field	Recorded information
Result	PASS
Started	24 Sept 2026, 17:30
Completed	24 Sept 2026, 18:00

Observation

Field	Recorded information
Actual Load	950
Input Actual Load	950
Unit	g
Indication	950
Indication Unit	g
Initial Delta L	5
Initial P	950
P0	950
P5	950
P15	950
P30	950
Maximum permissible error	5
MPE unit	g
Mpe Rule Reference	OIML R 76-1:2006 Section 3.5.1 Table 6
Mpe Rule Set Id	R76-1:2006:TABLE-6:INITIAL-VERIFICATION
Mpe Rule Version	R76-1:2006
Source Clause	OIML R 76-1:2006 Section 3.9.4 / Annex A A.4.11
Delta30	0
Delta15 30	0
Early Termination Limit	5
Stability Limit	2
Temperature Variation	0 deg C
Temperature Condition	SATISFIED
Early Termination Allowed	Yes

Field	Recorded information
Required Checkpoint	T30
Result	PASS
Recorded	24 Sept 2026, 18:00
Tester Name Snapshot	samarth dubey
Notes	Synthetic Prototype / Regression Data - close-to-Max stable baseline. Continuous load intended for 30-minute early-termination criteria.

Checkpoints

Indication	Additional load (Delta L)	Unit	Checkpoint	Minutes	P
950 g	5 g	g	T0	0	950
950 g	5 g	g	T5	5	950
950 g	5 g	g	T15	15	950
950 g	5 g	g	T30	30	950

Zero Return

Field	Recorded information
Workflow status	COMPLETED
Result	PASS
Started	24 Sept 2026, 18:00
Completed	24 Sept 2026, 18:31

Observation

Field	Recorded information
Actual Load	950
Input Actual Load	950
Unit	g
Zero Before	0
Zero After	0
Input Zero After	0
Zero After Unit	g
Zero Return Deviation	0

Field	Recorded information
Allowed Limit	5
Zero Tracking Off Confirmed	Yes
Stabilized Before	Yes
Stabilized After	Yes
Result	PASS
Recorded	24 Sept 2026, 18:31
Tester Name Snapshot	samarth dubey

A.4.12 - STABILITY OF EQUILIBRIUM

TEST RESULT: NOT APPLICABLE

Field	Recorded information
Status	NOT APPLICABLE
Reason	The instrument does not have a configured stable-equilibrium function.

A.4.13 - PORTABLE WEIGHBRIDGE TESTS

TEST RESULT: NOT APPLICABLE

Field	Recorded information
Status	NOT APPLICABLE
Reason	The instrument is not a portable road-vehicle weighbridge.

A.5 - INFLUENCE FACTORS

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A5-1.0
Technical reference	OIML R 76-1:2006 Annex A A.5
Started	24 Sept 2026, 18:31
Completed	24 Sept 2026, 18:35

Field	Recorded information
Support / applicability reason	The generated A.5 branch set is derived from the persisted instrument configuration.

Field	Recorded information
Test procedure version	R76-A5-1.0
Method / reference	OIML R 76-1:2006 Annex A A.5
Workflow status	COMPLETED
Result	PASS

Plan

Field	Recorded information
Method / reference	OIML R 76-1:2006 Annex A A.5

Target Load

Field	Recorded information
Value	500
Unit	g
Label	0.50 x Max

Voltage

Field	Recorded information
Supported	Yes
Branch	A.5.4.1
Reference	230
Lower	195.5
Upper	253
Formula	0.85 Unom to 1.10 Unom
Three Phase	No

Temperature

Field	Recorded information
Supported	Yes
Reference Temperature	20 deg C

Field	Recorded information
Two Hour Stabilization Minutes	120
Maximum Change Rate Celsius Per Minute	1
High Temperature Absolute Humidity Limit GPer M3	20 deg C

Targets

Label	Value
Reference temperature	20
Specified high temperature	40
Specified low temperature	-10
5 deg C	5
Reference temperature	20

Warm Up Checkpoints

5 - 15 - 30

Tilt

Field	Recorded information
Workflow status	APPLICABLE
Reason	Use the 50/1000 tilt procedure because no level indicator or automatic tilt sensor is configured.
Method	A.5.1.2
Execution Supported	Yes
Tilt Ratio	50/1000

Directions

LONGITUDINAL - TRANSVERSE

Test Loads

Label	Unit	Value
10e	g	100 g
Between 1/2 Max and Max	g	500 g

Phases

Code	Name	Applicability	Workflow status	Result	Reason
A.5.1	Tilting	APPLICABLE	COMPLETED	PASS	Use the 50/1000 tilt procedure because no level indicator or automatic tilt sensor is configured.
A.5.2	Warm-up time	APPLICABLE	COMPLETED	PASS	The instrument uses electric power and is in scope for the warm-up test.
A.5.3	Temperature tests	APPLICABLE	COMPLETED	PASS	The specified operating-temperature range is available for the A.5.3 procedure.
A.5.4	Voltage variations	APPLICABLE	COMPLETED	PASS	The configured power-source branch determines the A.5.4 voltage limits.

Setup

Field	Recorded information
Environmental Conditions Stable Confirmed	Yes
Notes	Synthetic Prototype / Regression Data; stable controlled setup conditions recorded for this report.
Recorded	24 Sept 2026, 18:31
Tester Name Snapshot	samarth dubey

Tilting

Field	Recorded information
Zero Setting Off Confirmed	Yes
Result	PASS
Recorded	24 Sept 2026, 18:33
Tester Name Snapshot	samarth dubey

Observations

Load	Indication	Additional load (Delta L)	Corrected error	Maximum permissible error	Calculated indication
0	0	0	5	5	5
200	195	0	0	5	200
980	975	0	0	5	980
0	0	0	5	5	5
200	195	0	0	5	200
980	975	0	0	5	980

Raw

Field	Recorded information
Direction	LONGITUDINAL
Position	No Load
Actual Tilt	2.9
Load	0
Indication	0
Additional load (Delta L)	0
Zero Error	0
Unit	g

Raw

Field	Recorded information
Direction	LONGITUDINAL
Position	Low Load
Actual Tilt	2.9
Load	200
Indication	195
Additional load (Delta L)	0
Zero Error	0
Unit	g

Raw

Field	Recorded information
Direction	LONGITUDINAL
Position	Max Load
Actual Tilt	2.9
Load	980
Indication	975
Additional load (Delta L)	0
Zero Error	0

Field	Recorded information
Unit	g

Raw

Field	Recorded information
Direction	TRANSVERSE
Position	No Load
Actual Tilt	2.9
Load	0
Indication	0
Additional load (Delta L)	0
Zero Error	0
Unit	g

Raw

Field	Recorded information
Direction	TRANSVERSE
Position	Low Load
Actual Tilt	2.9
Load	200
Indication	195
Additional load (Delta L)	0
Zero Error	0
Unit	g

Raw

Field	Recorded information
Direction	TRANSVERSE
Position	Max Load
Actual Tilt	2.9
Load	980
Indication	975

Field	Recorded information
Additional load (Delta L)	0
Zero Error	0
Unit	g

Warm Up

Field	Recorded information
Disconnected At	22 Sept 2026, 08:00
Connected At	22 Sept 2026, 16:00
Stabilization At	22 Sept 2026, 16:00
Eight Hour Precondition Confirmed	Yes
Result	PASS

Observations

Result	Load	Indication	Additional load (Delta L)	Corrected error	Maximum permissible error
PASS	950 g	945 g	0 g	0 g	5 g
PASS	950 g	945 g	0 g	0 g	5 g
PASS	950 g	945 g	0 g	0 g	5 g

Temperature

Field	Recorded information
Result	PASS
Recorded	24 Sept 2026, 18:34

Points

Load	Indication	Additional load (Delta L)	Corrected error	Maximum permissible error	Unit
950 g	945 g	0 g	0 g	5 g	g
950 g	945 g	0 g	0 g	5 g	g
950 g	945 g	0 g	0 g	5 g	g
950 g	945 g	0 g	0 g	5 g	g
950 g	945 g	0 g	0 g	5 g	g

Voltage

Field	Recorded information
Result	PASS
Recorded	24 Sept 2026, 18:35

Observations

Label	Load	Indication	Additional load (Delta L)	Corrected error	Maximum permissible error
Reference Start	100 g	95 g	0 g	0 g	5 g
LOWER	100 g	95 g	0 g	0 g	5 g
UPPER	100 g	95 g	0 g	0 g	5 g
Reference End	100 g	95 g	0 g	0 g	5 g
Reference Start	700 g	695 g	0 g	0 g	5 g
LOWER	700 g	695 g	0 g	0 g	5 g
UPPER	700 g	695 g	0 g	0 g	5 g
Reference End	700 g	695 g	0 g	0 g	5 g

A.6 - ENDURANCE TEST

TEST RESULT: PASS

Field	Recorded information
Workflow status	Completed
Applicability	APPLICABLE
Test version	R76-A6-1.0
Technical reference	OIML R 76-1:2006 Section 3.9.4.3 / Annex A A.6
Started	24 Sept 2026, 18:35
Completed	24 Sept 2026, 18:38
Support / applicability reason	The instrument is Class II, III or IIII with Max not exceeding 100 kg.

Recovery checkpoints

Applications	Checkpoint time	Actual load	Recorded by	Notes
0	24 Sept 2026, 18:35	Not recorded	samarth dubey	Session created; software checkpoint only.
10,000	24 Sept 2026, 18:36	Not recorded g	samarth dubey	Software recovery checkpoint; not an additional OIML interval.

Applications	Checkpoint time	Actual load	Recorded by	Notes
25,000	24 Sept 2026, 18:36	Not recorded g	samarth dubey	Software recovery checkpoint; not an additional OIML interval.
50,000	24 Sept 2026, 18:36	Not recorded g	samarth dubey	Software recovery checkpoint; not an additional OIML interval.
75,000	24 Sept 2026, 18:36	Not recorded g	samarth dubey	Software recovery checkpoint; not an additional OIML interval.
100,000	24 Sept 2026, 18:37	Not recorded g	samarth dubey	Software recovery checkpoint; not an additional OIML interval.

Endurance calculation

Field	Recorded information
Required applications	100,000
Recorded applications	100,000
Synthetic applications	99,990
Pre-endurance baseline error	0 g
Post-endurance corrected error	0 g
Durability error	0 g
Abnormal events	0
Cycle state	COMPLETED

Field	Recorded information
Test procedure version	R76-A6-1.0
Method / reference	OIML R 76-1:2006 Section 3.9.4.3 / Annex A A.6
Workflow status	COMPLETED
Result	PASS
Required loading applications	100,000
Recorded loading applications	100,000
Synthetic loading applications	99,990
Cycle State	COMPLETED
Resumed At	24 Sept 2026, 18:35

Applicability

Field	Recorded information
Code	A.6

Field	Recorded information
Name	Endurance test
Order	14
Route	A.6
Method / reference	OIML R 76-1:2006 Section 3.9.4.3 / Annex A A.6
Workflow status	APPLICABLE
Reason	The instrument is Class II, III or IIII with Max not exceeding 100 kg.
Method	ENDURANCE
Method Label	Endurance after all other tests
Execution Supported	Yes
Clause	A.6
Accuracy Class	II
Maximum capacity	1,000
Unit	g

Target Load

Field	Recorded information
Value	500
Unit	g
Label	Approximately 50% of Max

Checkpoints

Timestamp	Notes	Cycle Number	Operator
24 Sept 2026, 18:35	Session created; software checkpoint only.	0	samarth dubey
24 Sept 2026, 18:36	Software recovery checkpoint; not an additional OIML interval.	10,000	samarth dubey
24 Sept 2026, 18:36	Software recovery checkpoint; not an additional OIML interval.	25,000	samarth dubey
24 Sept 2026, 18:36	Software recovery checkpoint; not an additional OIML interval.	50,000	samarth dubey
24 Sept 2026, 18:36	Software recovery checkpoint; not an additional OIML interval.	75,000	samarth dubey
24 Sept 2026, 18:37	Software recovery checkpoint; not an additional OIML interval.	100,000	samarth dubey

Actual Load

Field	Recorded information
Value	500
Unit	g
Input Value	500
Input Unit	g

Actual Load

Field	Recorded information
Value	500
Unit	g
Input Value	500
Input Unit	g

Actual Load

Field	Recorded information
Value	500
Unit	g
Input Value	500
Input Unit	g

Actual Load

Field	Recorded information
Value	500
Unit	g
Input Value	500
Input Unit	g

Actual Load

Field	Recorded information
Value	500
Unit	g
Input Value	500

Field	Recorded information
Input Unit	g

Phases

Code	Name	Workflow status	Result	Completed	Method / reference
A.6.1	Pre-endurance weighing	COMPLETED	PASS	24 Sept 2026, 18:35	OIML R 76-1:2006 Section 3.9.4.3 / Annex A A.6
A.6.2	Endurance loading applications	COMPLETED	PASS	24 Sept 2026, 18:37	OIML R 76-1:2006 Section 3.9.4.3 / Annex A A.6
A.6.3	Post-endurance weighing	COMPLETED	PASS	24 Sept 2026, 18:37	OIML R 76-1:2006 Section 3.9.4.3 / Annex A A.6
A.6.4	Durability assessment	COMPLETED	PASS	24 Sept 2026, 18:38	OIML R 76-1:2006 Section 3.9.4.3 / Annex A A.6

Pre Weighing

Field	Recorded information
Source Test Id	6ab44a4e482192ede98fdd3e
Source Sequence	4
Load	500
Unit	g
Calculated indication	500
Error	0
Corrected error	0
Maximum permissible error	5
Recorded	24 Sept 2026, 18:35
Tester Name Snapshot	samarth dubey
Method / reference	OIML R 76-1:2006 A.4.4.1 / A.4.4.3

Actual Load

Field	Recorded information
Value	500
Unit	g
Input Value	500

Field	Recorded information
Input Unit	g

Loading Conditions

Field	Recorded information
Actual Load	500
Unit	g
Loading Method	MANUAL
Loading Frequency	Synthetic prototype batch representation; load target 500 g; 100,000 aggregate applications.
Loading Behavior	Synthetic Prototype / Regression Data. Each batch represents repeated load/unload applications under the configured test conditions.
Loaded Equilibrium Confirmed	Yes
Unloaded Equilibrium Confirmed	Yes
Applied Force Within Normal Operation	Yes
Normal Conditions Confirmed	Yes
Supporting Evidence	Synthetic Prototype / Regression Data; batch mechanism used for a practical prototype run, not a claim of physical endurance testing.
Normalized Unit	g
Recorded	24 Sept 2026, 18:35
Tester Name Snapshot	samarth dubey

Durability Assessment

Field	Recorded information
Supported	Yes
Durability error	0
Maximum permissible error	5
MPE unit	g
Result	PASS
Technical reference	OIML R 76-1:2006 Section 3.9.4.3
Mpe Reference	OIML R 76-1:2006 Section 3.5.1 Table 6

Post Weighing

Field	Recorded information
Load	500
Indication	495
Additional load (Delta L)	0
Zero Error	0
Unit	g
Notes	Synthetic Prototype / Regression Data; post-endurance observation linked to A.4.4 baseline load 500 g.
Calculated indication	500
Error	0
Corrected error	0
P	500
E	0
E0	0
Ec	0
Recorded	24 Sept 2026, 18:37
Tester Name Snapshot	samarth dubey
Method / reference	OIML R 76-1:2006 A.4.4.1 / A.4.4.3

Maximum permissible error

Field	Recorded information
Supported	Yes
Accuracy Class	II
Load	500
Verification scale interval (e)	10
M	50
Mpe Multiplier	0.5
Maximum permissible error	5
Maximum permissible error	5
MPE unit	g
Display Mpe	+/-5 g
Technical reference	OIML R 76-1:2006 Section 3.5.1 Table 6

Field	Recorded information
Reference edition	R76-1:2006
Range Label	>=0e to <=5000e
Load Type	GROSS

REMARKS, DEVIATIONS AND NON-CONFORMITIES

Synthetic Prototype / Regression Data - simulated end-of-session conditions for workflow verification; not a physical laboratory observation.

Reviewed synthetic regression record: all applicable tests and persisted calculations PASS.

OVERALL CONCLUSION

Overall evaluation result: PASS

The persisted evaluation record indicates that all applicable completed tests satisfy their recorded acceptance criteria.

REVIEW AND APPROVAL

Role	Name	Action / decision	Date
Tester	samarth dubey	Submitted for review	24 Sept 2026, 18:40
Reviewer	samarth dubey	Approved	24 Sept 2026, 18:42

Reviewer note

Reviewed synthetic regression record: all applicable tests and persisted calculations PASS.

Review history

Action	Recorded by	Date
Submitted for reviewer assessment	samarth dubey	24 Sept 2026, 18:40
Approved by reviewer	samarth dubey	24 Sept 2026, 18:42

TRACEABILITY AND REVISION

Field	Recorded information
Applicable standard	OIML R 76-1:2006
Report structure reference	OIML R 76-2, where applicable to the stored report structure
Data source	Persisted test report and test records
Revision	01
Issue / generation date	24 Sept 2026, 19:34

Field	Recorded information
Finalization date	24 Sept 2026, 18:42

EVIDENCE APPENDIX

1 persisted supporting record

Evidence 01 - Instrument · Nameplate

Field	Recorded information
Linked test	Report-level evidence
Description	download (2).png
Captured	24 Sept 2026, 00:03
Captured by	samarth dubey
Evidence type	nameplate

