Ideation Phase

Empathize & Discover

Date	23 September 2026
Team ID	SWTID-2026-5076
Project Name	Script-Controlled ACL – Restrict Record Access Based on Field Value
Maximum Marks	4 Marks

Empathy Map Canvas

Primary user: EEE branch user who needs access to Institution Details records. The map focuses on the user's experience with role-based, field-value-controlled access.

SAYS	THINKS
• "I need to view the records relevant to my EEE branch." • "I should be able to access records only when I have the required role." • "I need clear access rules for viewing and modifying records."	• "My branch-specific records should be protected from unauthorized users." • "The ACL should check my role and the record's Branch value." • "Administrators should retain full access when required."
DOES	**FEELS**
• Logs in and opens the Student/Institution Details records. • Attempts to view records with different Branch values such as ECE, EEE and CSE. • Uses the available permissions to view, create, edit or delete records.	• Concerned about unauthorized access to records. • Confident when access is limited to the intended branch and role. • Frustrated when a required record or action is blocked unexpectedly. • Reassured when administrators can retain full access.

USER NEEDS / PAINS / GAINS

PAINS	• Unauthorized users may see sensitive records if access rules are not enforced. • Users may be unable to perform actions when required roles are missing. • Different permissions for read, create, write and delete can be confusing.
NEEDS	• Branch-based record visibility. • Role-based permissions for each operation. • Consistent and understandable access behaviour. • Administrator access for overall management.
GAINS	• Only EEE branch records are visible to the intended role in the read scenario. • Permissions can be extended step-by-step using bb1, bb2, bb3 and bb4. • Sensitive data is protected from unauthorized viewing, modification, creation and deletion.

Empathy Insight

The user needs secure, predictable access to Institution Details records. The project addresses this by combining user roles with record-level ACL rules and, for the read scenario, a Branch = EEE data condition. The project documentation states that the overall ACL setup is intended to control READ, CREATE, WRITE and DELETE operations.

Source basis: Project document and the provided Empathy Map Canvas template.