Loanwalle Integration API Documentation

Table of Contents

1. Overview
2. Authentication
3. Base URL
4. Endpoints
5. Error Handling
6. Examples
7. Troubleshooting

Overview

The Loanwalle API integration allows partners to programmatically create and manage loan leads. The API supports two authentication methods: **API Keys** and **Partner Bearer Tokens**.

Key Features

- ✅ Create new loan leads
- ✅ Retrieve lead status and details
- ✅ Multi-authentication support (API Key + Bearer Token)
- ✅ Real-time lead tracking
- ✅ Comprehensive error handling

Supported Loan Types

- `PERSONAL_LOAN` - Personal loans
- `HOME_LOAN` - Home/mortgage loans
- `AUTO_LOAN` - Automobile loans
- `EDUCATION_LOAN` - Education loans
- `BUSINESS_LOAN` - Business loans

Authentication

Method 1: API Key (Recommended)

Best for: Server-to-server integrations, applications

How to Get:

1. Go to Partner Dashboard → Settings → API Keys
2. Click "Create New API Key"
3. Copy the key and store it securely

Usage:

```
-H "x-api-key: lw_your_secret_key_here"
```

Method 2: Bearer Token

Best for: User-initiated operations, web applications

How to Get:

1. Authenticate with partner credentials
2. Token is returned in login response
3. Use token in Authorization header

Usage:

```
-H "Authorization: Bearer eyJhbGciOiJIUzI1NiIs..."
```

Security Best Practices

⚠️ **IMPORTANT**:

- Never commit API keys to version control
- Rotate API keys every 90 days
- Use environment variables for storing keys
- Monitor API key usage in dashboard
- Revoke compromised keys immediately

Base URL

```
Production: https://api.loanwalle.com/v1
Staging: https://staging-api.loanwalle.com/v1
Development: http://localhost:4002/api/v1
Local Testing: http://localhost:4002/api/v1
```

Endpoints

1. Create Lead

Creates a new loan application lead in the system.

Request

```
POST /loanwalle/leads HTTP/1.1
Host: localhost:4002
Content-Type: application/json
x-api-key: your_api_key_here
```

Method: `POST`
Path: `/loanwalle/leads`
Status Code: `201 Created`

Headers

Header	Required	Value
`Content-Type`	✅ Yes	`application/json`
`x-api-key`	✅ Yes*	Your API key
`Authorization`	✅ Yes*	`Bearer token` (alternative)

*Either x-api-key or Authorization header is required

Request Body

```
{
  "lead": {
    "first_name": "string",
    "last_name": "string",
    "email": "string",
    "mobile": "string",
    "pan": "string",
    "loan_type": "string",
    "loan_amount": "number"
  }
}
```

Parameters

Parameter	Type	Required	Length	Description	Example
first_name	string	✅ Yes	1-100	Applicant's first name	"John"
last_name	string	✅ Yes	1-100	Applicant's last name	"Doe"
email	email	✅ Yes	-	Valid email address	"john.doe@example.com"
mobile	string	✅ Yes	10	10-digit mobile number	"9876543210"
pan	string	✅ Yes	10	PAN card number (uppercase)	"ABCDE1234F"
loan_type	string	✅ Yes	-	Type of loan	"PERSONAL_LOAN"
loan_amount	number	✅ Yes	-	Loan amount in INR	500000

Success Response

```
{
  "success": true,
```

```
  "message": "Lead created successfully",
  "data": {
    "loanId": "268c1d92-16a2-4e41-a011-2aa6b7b80500"
  }
}
```

Error Responses

400 - Bad Request (Missing Field)

```
{
  "statusCode": 400,
  "error": "Bad Request",
  "message": "PAN number is required",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

400 - Invalid Email

```
{
  "statusCode": 400,
  "error": "Bad Request",
  "message": "Invalid email format",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

400 - Duplicate PAN

```
{
  "statusCode": 400,
  "error": "Bad Request",
  "message": "PAN number already exists",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

400 - Duplicate Mobile

```
{
  "statusCode": 400,
  "error": "Bad Request",
  "message": "Mobile number already exists for this brand",
```

```
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

401 - Unauthorized

```
{
  "statusCode": 401,
  "error": "Unauthorized",
  "message": "Invalid or expired API key",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

422 - Unprocessable Entity

```
{
  "statusCode": 422,
  "error": "Unprocessable Entity",
  "message": "Invalid loan type",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

429 - Rate Limited

```
{
  "statusCode": 429,
  "error": "Too Many Requests",
  "message": "Rate limit exceeded. Try again after 60 seconds",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

500 - Server Error

```
{
  "statusCode": 500,
  "error": "Internal Server Error",
  "message": "An unexpected error occurred",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

cURL Examples

Basic Request

```
curl --location 'http://localhost:4002/api/v1/loanwalle/leads' \
  --header 'Content-Type: application/json' \
  --header 'x-api-key: lw_your_api_key_here' \
  --data-raw '{
    "lead": {
      "first_name": "John",
      "last_name": "Doe",
      "email": "john.doe@example.com",
      "mobile": "9876543210",
      "pan": "ABCDE1234F",
      "loan_type": "PERSONAL_LOAN",
      "loan_amount": 500000
    }
  }'
```

With Bearer Token

```
curl --location 'http://localhost:4002/api/v1/loanwalle/leads' \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer your_partner_token_here' \
  --data-raw '{
    "lead": {
      "first_name": "Jane",
      "last_name": "Smith",
      "email": "jane.smith@example.com",
      "mobile": "9876543211",
      "pan": "XYZAB5678C",
      "loan_type": "HOME_LOAN",
      "loan_amount": 2500000
    }
  }'
```

With Formatted Output (jq)

```
curl --location 'http://localhost:4002/api/v1/loanwalle/leads' \
  --header 'Content-Type: application/json' \
  --header 'x-api-key: lw_your_api_key_here' \
  --data-raw '{
    "lead": {
      "first_name": "Rajesh",
      "last_name": "Kumar",
```

```
      "email": "rajesh.kumar@example.com",
      "mobile": "9123456789",
      "pan": "ABCD1234E",
      "loan_type": "PERSONAL_LOAN",
      "loan_amount": 750000
    }
  }' | jq '.data'
```

---

2. Get Lead Status

Retrieve current status and details of a specific lead.

Request

```
GET /loanwalle/leads/:leadId HTTP/1.1
Host: localhost:4002
x-api-key: your_api_key_here
```

Method: `GET`
Path: `/loanwalle/leads/:leadId`
Status Code: `200 OK`

Headers

Header	Required	Value
`x-api-key`	✅ Yes*	Your API key
`Authorization`	✅ Yes*	`Bearer token` (alternative)

*Either x-api-key or Authorization header is required

Path Parameters

Parameter	Type	Required	Description	Example
leadId	string	✅ Yes	Lead ID from create response	"loan_6c7d8e9f0g1h2i3j4k"

Success Response

```
{
  "success": true,
  "message": "Lead status retrieved successfully",
  "data": {
    "id": "268c1d92-16a2-4e41-a011-2aa6b7b80500",
    "status": "ONBOARDING",
    "amount": 500000,
    "loanType": "PERSONAL_LOAN",
    "applicationDate": "2026-02-07T00:00:00.000Z",
    "approvalDate": null,
    "disbursementDate": null,
    "closureDate": null,
    "createdAt": "2026-02-07T20:25:03.405Z",
    "updatedAt": "2026-02-07T20:25:03.405Z"
  }
}
```

Lead Status Values

Status	Description
`ONBOARDING`	Application submitted, in progress
`UNDER_REVIEW`	Application under review
`APPROVED`	Loan approved
`REJECTED`	Application rejected
`DISBURSED`	Funds disbursed to applicant
`CLOSED`	Loan closed/repaid
`DEFAULTED`	Loan defaulted

Error Responses

404 - Lead Not Found

```
{
  "statusCode": 404,
  "error": "Not Found",
  "message": "Lead not found",
  "timestamp": "2026-02-08T10:30:45.123Z",
```

```
  "path": "/api/v1/loanwalle/leads/invalid_id"
}
```

401 - Unauthorized

```
{
  "statusCode": 401,
  "error": "Unauthorized",
  "message": "Invalid or expired API key",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads/loan_id"
}
```

400 - Invalid Lead ID

```
{
  "statusCode": 400,
  "error": "Bad Request",
  "message": "Invalid lead ID format",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

cURL Examples

Basic Request

```
curl --location 'http://localhost:4002/api/v1/loanwalle/leads/268c1d92-
16a2-4e41-a011-2aa6b7b80500' \
  --header 'x-api-key: lw_your_api_key_here'
```

With Formatted Output

```
curl --location 'http://localhost:4002/api/v1/loanwalle/leads/268c1d92-
16a2-4e41-a011-2aa6b7b80500' \
  --header 'x-api-key: lw_your_api_key_here' | jq '.data'
```

Extract Status Only

```
curl --location 'http://localhost:4002/api/v1/loanwalle/leads/268c1d92-
16a2-4e41-a011-2aa6b7b80500' \
  --header 'x-api-key: lw_your_api_key_here' | jq '.data.status'
```

Extract Amount

```
curl --location 'http://localhost:4002/api/v1/loanwalle/leads/268c1d92-
16a2-4e41-a011-2aa6b7b80500' \
  --header 'x-api-key: lw_your_api_key_here' | jq '.data.amount'
```

With Bearer Token

```
curl --location 'http://localhost:4002/api/v1/loanwalle/leads/268c1d92-
16a2-4e41-a011-2aa6b7b80500' \
  --header 'Authorization: Bearer your_partner_token_here'
```

---

3. Test API Key

Verify that your API key is valid and authentication is working correctly.

Request

```
GET /loanwalle/test HTTP/1.1
Host: localhost:4002
x-api-key: your_api_key_here
```

Method: `GET`
Path: `/loanwalle/test`
Status Code: `200 OK`

Success Response

```
{
  "success": true,
  "message": "API Key authentication is working correctly",
  "timestamp": "2026-02-07T20:16:37.658Z",
  "data": {
    "apiName": "Loanwalle Test Endpoint",
    "description": "This endpoint confirms that your API key is valid and
authenticated",
    "version": "1.0.0"
  }
}
```

cURL Example

```
curl --location 'http://localhost:4002/api/v1/loanwalle/test' \
  -H 'x-api-key: lw_your_api_key_here'
```

Error Handling

Common HTTP Status Codes

Status Code	Meaning	Action
`200`	OK	Request successful
`201`	Created	Resource created successfully
`400`	Bad Request	Invalid parameters or format
`401`	Unauthorized	Invalid/missing authentication
`404`	Not Found	Resource not found
`422`	Unprocessable Entity	Validation error
`429`	Too Many Requests	Rate limit exceeded
`500`	Server Error	Unexpected server error
`503`	Service Unavailable	Server temporarily unavailable

Error Response Structure

```
{
  "statusCode": 400,
  "error": "Bad Request",
  "message": "Descriptive error message",
  "timestamp": "2026-02-08T10:30:45.123Z",
  "path": "/api/v1/loanwalle/leads"
}
```

Retry Strategy

Implement exponential backoff for retries:

```
async function retryRequest(fn, maxRetries = 3) {
  for (let i = 0; i < maxRetries; i++) {
    try {
      return await fn();
    } catch (error) {
      if (error.statusCode >= 500 && i < maxRetries - 1) {
        const delay = Math.pow(2, i) * 1000; // 1s, 2s, 4s
        await new Promise((resolve) => setTimeout(resolve, delay));
        continue;
      }
      throw error;
    }
  }
}
```

Examples

JavaScript/Node.js Example

```
const axios = require("axios");

const API_KEY = process.env.LOANWALLE_API_KEY;
const BASE_URL = "https://api.loanwalle.com/v1";

const client = axios.create({
  baseURL: BASE_URL,
  headers: {
    "x-api-key": API_KEY,
    "Content-Type": "application/json",
  },
});

// Create Lead
async function createLead(leadData) {
  try {
    const response = await client.post("/loanwalle/leads", {
      lead: leadData,
    });
    console.log("Lead created:", response.data.data);
    return response.data.data;
  } catch (error) {
```

```
    console.error("Error creating lead:", error.response.data);
    throw error;
  }
}

// Get Lead Status
async function getLeadStatus(leadId) {
  try {
    const response = await client.get(`/loanwalle/leads/${leadId}`);
    console.log("Lead status:", response.data.data);
    return response.data.data;
  } catch (error) {
    console.error("Error fetching lead:", error.response.data);
    throw error;
  }
}

// Usage
const newLead = await createLead({
  first_name: "John",
  last_name: "Doe",
  email: "john.doe@example.com",
  mobile: "9876543210",
  pan: "ABCDE1234F",
  loan_type: "PERSONAL_LOAN",
  loan_amount: 500000,
});

const status = await getLeadStatus(newLead.loanId);
```

Python Example

```
import requests
import os

API_KEY = os.getenv('LOANWALLE_API_KEY')
BASE_URL = 'https://api.loanwalle.com/v1'

headers = {
    'x-api-key': API_KEY,
    'Content-Type': 'application/json'
}

def create_lead(lead_data):
    response = requests.post(
```

```
        f'{BASE_URL}/loanwalle/leads',
        json={'lead': lead_data},
        headers=headers
    )
    response.raise_for_status()
    return response.json()

def get_lead_status(lead_id):
    response = requests.get(
        f'{BASE_URL}/loanwalle/leads/{lead_id}',
        headers=headers
    )
    response.raise_for_status()
    return response.json()

# Usage
lead_data = {
    'first_name': 'John',
    'last_name': 'Doe',
    'email': 'john.doe@example.com',
    'mobile': '9876543210',
    'pan': 'ABCDE1234F',
    'loan_type': 'PERSONAL_LOAN',
    'loan_amount': 500000
}

response = create_lead(lead_data)
print('Lead created:', response['data'])

status = get_lead_status(response['data']['loanId'])
print('Lead status:', status['data'])
```

cURL Workflow Example

```
#!/bin/bash

API_KEY="your_api_key_here"
BASE_URL="https://api.loanwalle.com/v1"

# Test API Key
echo "Testing API Key..."
curl -X GET $BASE_URL/loanwalle/test \
  -H "x-api-key: $API_KEY"

echo "\n\nCreating Lead..."
```

```
LEAD_RESPONSE=$(curl -s -X POST $BASE_URL/loanwalle/leads \
  -H "Content-Type: application/json" \
  -H "x-api-key: $API_KEY" \
  -d '{
    "lead": {
      "first_name": "John",
      "last_name": "Doe",
      "email": "john.doe@example.com",
      "mobile": "9876543210",
      "pan": "ABCDE1234F",
      "loan_type": "PERSONAL_LOAN",
      "loan_amount": 500000
    }
  }')

LOAN_ID=$(echo $LEAD_RESPONSE | jq -r '.data.loanId')
echo "Lead created with ID: $LOAN_ID"

echo "\n\nFetching Lead Status..."
curl -s -X GET $BASE_URL/loanwalle/leads/$LOAN_ID \
  -H "x-api-key: $API_KEY" | jq '.data'
```

Troubleshooting

Issue: “Invalid API Key”

Cause: API key is incorrect, expired, or revoked

Solutions:

1. Verify API key is correct and copied completely
2. Check if API key has been revoked in dashboard
3. Create a new API key if necessary
4. Ensure API key is for correct brand/organization

Issue: “PAN number already exists”

Cause: PAN number is already registered in the system

Solutions:

1. Verify PAN number is correct

2. Use unique PAN for each application
3. Contact support if duplicate was created in error

Issue: “Mobile number already exists for this brand”

Cause: Mobile number is already associated with another lead

Solutions:

1. Use a different mobile number
2. Contact support if duplicate needs to be resolved
3. Verify the mobile number belongs to the correct person

Issue: “Lead not found” (404)

Cause: Invalid lead ID or lead has been deleted

Solutions:

1. Verify lead ID is correct (from create response)
2. Check if lead ID has correct format
3. Ensure lead was successfully created

Issue: Rate Limit Exceeded (429)

Cause: Too many requests in a short time period

Solutions:

1. Implement exponential backoff in retry logic
2. Space out API requests
3. Contact support for rate limit increase
4. Use batch endpoints if available

Issue: Validation Errors (400)

Cause: Invalid data format or missing required fields

Solutions:

1. Validate all required fields are provided
2. Check data types match requirements (e.g., email format)
3. Ensure PAN is 10 characters, mobile is 10 digits

4. Verify enum values (loan_type) are valid

Issue: Server Error (500)

Cause: Unexpected server error

Solutions:

1. Retry request after a few seconds
2. Implement exponential backoff
3. Check system status page
4. Contact support with error timestamp and path

FAQ

Q: How do I get an API Key?
A: Go to Partner Dashboard → Settings → API Keys → Create New API Key

Q: How often should I rotate API Keys?
A: It's recommended to rotate keys every 90 days for security

Q: Can I use both API Key and Bearer Token?
A: Yes, either one works. Use whichever fits your use case better

Q: What's the maximum loan amount?
A: There's no hard limit, but verify with your lender for business rules

Q: How long does a lead take to process?
A: Processing time varies by lender, typically 1-3 business days

Q: Can I update a lead after creation?
A: Currently, leads cannot be updated. Create a new lead if changes needed

Q: Is there a rate limit?
A: Yes, standard is 1000 requests/hour. Contact support for higher limits

---

Support & Resources

- **API Status**: https://status.loanwalle.com
- **Documentation**: https://docs.loanwalle.com

- **Support Email**: api-support@loanwalle.com
- **Support Chat**: Available in Partner Dashboard
- **Issue Tracker**: https://github.com/loanwalle/api-issues

Version History

Version	Date	Changes
1.0.0	2026-02-08	Initial API release

Last Updated: February 8, 2026
API Version: 1.0.0
Documentation Version: 1.0