

Week 1 Practice Programming Assignment

Week 1 Practice Programming Assignment

Problem 1

Solution

Problem 2

Solution

Problem 1

Twin primes are pairs of prime numbers that differ by 2. For example (3, 5), (5, 7), and (11,13) are twin primes.

Write a function **Twin_Primes(n, m)** where **n** and **m** are positive integers and **n < m**, that returns all unique twin primes between n and m (both inclusive). The function returns a list of tuples and each tuple **(a,b)** represents one unique twin prime where **n <= a < b <= m**.

Sample Input 1

```
1 | 1
2 | 15
```

Output

```
1 | [(3, 5), (5, 7), (11, 13)]
```

Sample Input 2

```
1 | 11
2 | 25
```

Output

```
1 | [(11, 13), (17, 19)]
```

Solution

```
1 | def prime(n):
2 |     if n < 2:
3 |         return False
4 |     for i in range(2,n//2+1):
5 |         if n%i==0:
6 |             return False
7 |     return True
8 |
9 | def Twin_Primes(n, m):
10 |     Res=[]
11 |     for i in range(n,m-1):
12 |         if prime(i)==True:
13 |             if prime(i+2)==True:
14 |                 Res.append((i,i+2))
15 |     return(Res)
```

Suffix Code(Visible)

```
1 | n=int(input())
2 | m=int(input())
3 | print(sorted(Twin_Primes(n, m)))
```

Public Test Cases

Input 1

1	1
2	15

Output

1	[(3, 5), (5, 7), (11, 13)]
---	----------------------------

Input 2

1	11
2	25

Output

1	[(11, 13), (17, 19)]
---	----------------------

Input 3

1	5
2	50

Output

1	[(5, 7), (11, 13), (17, 19), (29, 31), (41, 43)]
---	--

Private Test Cases

Input 1

1	1
2	100

Output

1	[(3, 5), (5, 7), (11, 13), (17, 19), (29, 31), (41, 43), (59, 61), (71, 73)]
---	--

Input 2

1	1
2	10

Output

1	[(3, 5), (5, 7)]
---	------------------

Input 3

1	60
2	200

Output

1	[(71, 73), (101, 103), (107, 109), (137, 139), (149, 151), (179, 181), (191, 193), (197, 199)]
---	--

Input 4

1	50
2	73

Output

1	[(59, 61), (71, 73)]
---	----------------------

Input 5

1	17
2	19

Output

1	[(17, 19)]
---	------------

Problem 2

Create a **Triangle** class that accepts three side-lengths of the triangle as `a`, `b` and `c` as parameters at the time of object creation. Class **Triangle** should have the following methods:

- **Is_valid()** :- Returns `valid` if triangle is valid otherwise returns `Invalid`.
 - A triangle is valid when the sum of its two side-length are greater than the third one. That means the triangle is valid if all three condition are satisfied:
 - $a + b > c$
 - $a + c > b$
 - $b + c > a$
- **Side_Classification()** :- If the triangle is invalid then return `Invalid`. Otherwise, it returns the type of triangle according to the sides of the triangle as follows:
 - Return `Equilateral` if all sides are of equal length.
 - Return `Isosceles` if any two sides are of equal length and third is different.
 - Return `scalene` if all sides are of different lengths.
- **Angle_Classification()** :- If the triangle is invalid then return `Invalid`. Otherwise, return type of triangle using Pythagoras theorem.

Assume $a \leq b \leq c$. then

- If $a^2 + b^2 > c^2$ return `Acute`
 - If $a^2 + b^2 = c^2$ return `Right`
 - If $a^2 + b^2 < c^2$ return `obtuse`
- **Area()** :- If the triangle is invalid then return `Invalid`. Otherwise, return the area of the triangle.
 - $Area = \sqrt{s(s-a)(s-b)(s-c)}$
Where $s = (a + b + c)/2$

Sample Input 1

```
1 | 2
2 | 3
3 | 4
```

Output

```
1 | valid
2 | Scalene
3 | obtuse
4 | 2.9047375096555625
```

Sample Input 2

```
1 | 10
2 | 3
3 | 5
```

Output

```
1 Invalid
2 Invalid
3 Invalid
4 Invalid
```

Solution

```
1 class Triangle:
2     def __init__(self,a,b,c):
3         self.a = a
4         self.b = b
5         self.c = c
6     def is_valid(self):
7         if self.a >= self.b + self.c:
8             return 'Invalid'
9         if self.b >= self.a + self.c:
10            return 'Invalid'
11        if self.c >= self.b + self.a:
12            return 'Invalid'
13        return 'Valid'
14    def Side_Classification(self):
15        if self.is_valid() == 'Valid':
16            if self.a == self.b == self.c:
17                return 'Equilateral'
18            elif (self.a == self.b) or (self.b == self.c) or (self.a ==
self.c):
19                return 'Isosceles'
20            else:
21                return 'Scalene'
22        else:
23            return 'Invalid'
24    def Angle_Classification(self):
25        if self.is_valid() == 'Valid':
26            l = [self.a**2, self.b**2, self.c**2]
27            l.sort()
28            if l[0] + l[1] > l[2]:
29                return "Acute"
30            elif l[0] + l[1] == l[2]:
31                return "Right"
32            elif l[0] + l[1] < l[2]:
33                return "Obtuse"
34        else:
35            return 'Invalid'
36    def Area(self):
37        if self.is_valid() == 'Valid':
38            s = (self.a + self.b + self.c)/2
39            return (s*(s-self.a)*(s-self.b)*(s-self.c)) ** 0.5
40        else:
41            return 'Invalid'
```

Suffix code(visible)

```
1 a=int(input())
2 b=int(input())
3 c=int(input())
4 T=Triangle(a,b,c)
5 print(T.is_valid())
6 print(T.Side_Classification())
7 print(T.Angle_Classification())
8 print(T.Area())
```

Public Test Cases

Input 1

```
1 2
2 3
3 4
```

Output

```
1 valid
2 Scalene
3 obtuse
4 2.9047375096555625
```

Input 2

```
1 10
2 3
3 5
```

Output

```
1 Invalid
2 Invalid
3 Invalid
4 Invalid
```

Input 3

```
1 5
2 5
3 5
```

Output

```
1 valid
2 Equilateral
3 Acute
4 10.825317547305483
```

Private Test Cases

Input 1

1	2
2	12
3	3

Output

1	Invalid
2	Invalid
3	Invalid
4	Invalid

Input 2

1	14
2	5
3	12

Output

1	valid
2	Scalene
3	Obtuse
4	29.230762904857617

Input 3

1	32
2	12
3	21

Output

1	valid
2	Scalene
3	Obtuse
4	61.89456761299815

Input 4

1	10
2	10
3	5

Output

1	valid
2	Isosceles
3	Acute
4	24.206145913796355

Input 5

1	3
2	4
3	5

Output

1	valid
2	scalene
3	right
4	6.0