

▼ Divide and Conquer: Counting Inversions

Divide and Conquer

- Break the problem into disjoint sub-problems
- Combine these sub-problem solutions efficiently

Examples

- Merge sort
 - Split into left and right half and sort each half separately
 - Merge the sorted halves
- Quicksort
 - Re-arrange into lower and upper partitions, sort each partition separately
 - Place pivot between sorted lower and upper partitions

Recommender systems

- Online services recommend items to you
- Compare your profile with other customers
- Identify people who share your likes and dislikes
- Recommend items that they like
- Comparing profiles: How similar are your rankings to those of others?

Comparing rankings

- You and your friend rank 5 movies $\{A, B, C, D, E\}$
 - Your ranking: D, B, C, A, E
 - Your friend's ranking: B, A, C, D, E
- How to measure how similar these rankings are?
- For each pair of movies, compare preferences
 - You rank B above C , so does your friend
 - You rank D above B , your friend ranks B above D

Compare based on inversions

Inversions

- Pair of movies ranked in opposite order
 - You rank D above B , your friend ranks B above D

- No inversion \implies rankings identical
- Every pair inverted \implies maximally dissimilar
- Number of inversions range from 0 to $n(n-1)/2 \rightarrow$ measure of dissimilarity

Permutations


- Fix the order of one ranking as a sorted sequence $1, 2, \dots, n$
- The other ranking is a permutation of $1, 2, \dots, n$
- An inversion is a pair $(i, j), i < j$, where j appears before i

Counting inversions

- Number of inversions ranges from 0 to $n(n-1)/2 \rightarrow$ measure of dissimilarity
- Your ranking: D, B, C, A, E
 - D = 1, B = 2, C = 3, A = 4, E = 5
- Your friend's ranking: B, A, C, D, E
 - 2, 4, 3, 1, 5
- Inversions in 2, 4, 3, 1, 5?
- $(1, 2), (1, 3), (1, 4), (3, 4)$

Graphically

- Write the 2 permutations as 2 rows of nodes
- Connect every pair (j, j) between the two rows



- Every crossing is an inversion
- Brute force - check every $(i, j), O(n^2)$

▼ Divide and Conquer

- Friend's permutation is i_1, i_2, \dots, i_n
- Divide into 2 lists
 - $L = [i_1, i_2, \dots, i_{n/2}]$

- $R = [i_{n/2+1}, i_{n/2+2}, \dots, i_n]$
- Recursively count inversions in L and R
- Add inversions across the boundary between L and R
 - $i \in L, j \in R, i > j$
 - How many elements in L are bigger than elements in R ?
- How to count inversions across the boundary?
- Adapt merge sort
- Recursively **sort and count** inversions in L and R
- Count inversions while merging - **merge and count**

Merge and Count

- Merge $L = [i_1, i_2, \dots, i_{n/2}]$ and $R = [i_{n/2+1}, i_{n/2+2}, \dots, i_n]$, sorted
- Count inversions while merging
 - If we add i_m from R to the output, i_m is smaller than elements currently in L
 - i_m is hence inverted w.r.t. elements currently in L
 - Add current size (total size - current pointer index) of L to the inversion count

```
def merge_and_count(A, B):
    m = len(A)
    n = len(b)
    C = []
    i, j, k, count = 0, 0, 0, 0

    while k < m + n:
        if i == m:
            C.append(B[j])
            j += 1
            k += 1
        elif j == n:
            C.append(A[i])
            i += 1
            k += 1
        elif A[i] < B[j]:
            C.append(A[i])
            i += 1
            k += 1
        else:
            C.append(B[j])
            j += 1
            k += 1
            count = count + (m - i) # m - i is the current length of L

    return (C, count)
```

- `sort_and_count` is merge sort with `merge_and_count`

```
def sort_and_count(A):
    n = len(A)
    if n <= 1:
        return (A, 0)

    (L, countL) = sort_and_count(A[:n//2])
    (R, countR) = sort_and_count(A[n//2:])
    (B, countB) = merge_and_count(L, R) # countB is cross inversions

    return (B, countL + countR + countB)
```

Analysis


- Recurrence is similar to merge sort
 - $T(0) = T(1) = 1$
 - $T(n) = 2T(n/2) + n$
- Solve to get $T(n) = O(n \log n)$
- Note that the number of inversions can still be $O(n^2)$
 - Number ranges from 0 to $n(n - 1)/2$
- We are counting them efficiently without enumerating each one

▼ Divide and Conquer: Closest pair of points

Recall: Video game

- Several objects on the screen
- Basic step: Find the closest pair of objects
- n objects - naive algorithm is n^2
 - For each pair of objects, compute their distance
 - Report minimum distance across all pairs
- There is a clever algorithm that takes time $n \log_2 n$
- Uses divide and conquer

The problem statement

- Points p in $2D$ - $p = (x, y)$
- Usual Euclidean distance between $p_1 = (x_1, y_1)$ and $p_2 = (x_2, y_2)$
 - $d(p_1, p_2) = \sqrt{(y_2 - y_1)^2 + (x_2 - x_1)^2}$
- Given n points p_1, p_2, \dots, p_n find the closest pair
 - Assume no two points have same x or y coordinate
 - We can always rotate the points slightly to ensure this
 - or we can modify the algorithm slightly 
- Brute force
 - Compute $d(p_i, p_j)$ for every pair of points
 - $O(n^2)$

Finding the closest pair of points

In 1 dimension

- Given n 1D points x_1, x_2, \dots, x_n , find the closest pair
 - $d(p_i, p_j) = |x_j - x_i|$
- Sort the points - $O(n \log n)$
- In sorted order, nearest points to p are its neighbours
 - $O(n)$ scan to find the minimum separation between adjacent points


In 2 dimensions

- Divide and Conquer

- Split the points in 2 halves by a vertical line
- Recursively compute closest pair in each half
- Compare shortest distance in each half to shortest distance across the dividing line
- How to do this efficiently?

Dividing Points

- Given n points $P = \{p_1, p_2, \dots, p_n\}$ compute
 - P_x, P sorted by x -coordinate
 - P_y, P sorted by y -coordinate
- Divide P by a vertical line into equal size Q, R
- How to compute Q_x, Q_y, R_x, R_y efficiently?
- Q_x is the first half of P_x, R_x is the second half of P_x
- Let x_R be the smallest x coordinate in R
- For $p \in P_y$, if x -coordinate of p is less than x_R , move p to Q_y , else R_y
- All of this can be done in $O(n)$




Divide and Conquer

- Want to compute $ClosestPair(P_x, P_y)$
- Split (P_x, P_y) as $(Q_x, Q_y), (R_x, R_y)$
- Recursively compute $ClosestPair(Q_x, Q_y)$ and $ClosestPair(R_x, R_y)$
- How to combine these recursive solutions?

Combining Solutions


- Let d_Q, d_R be the closest distances in Q, R , respectively
- Set $\delta = \min(d_Q, d_R)$

- Only need to consider points within distance δ on either side of the separator
- No pair outside this band can be closer than δ



Combining Solutions

- Divide the distance δ band into boxes of side $\delta/2$
- We cannot have 2 points inside the same box
 - Box diagonal is $\delta/\sqrt{2}$
- Any point within the distance δ must lie in a 4×4 neighbourhood of boxes
 - Check each point against 15 others
- From Q_y, R_y , extract S_y , points in δ band sorted by y
- Scan S_y from bottom to top, comparing each p with next 15 points in S_y
- Linear scan



▼ Algorithm and Analysis

Pseudocode

```
def ClosestPair(Px, Py):
    if len(Px) <= 3:
        compute pairwise distances
        return closest pair and distance

    Construct (Qx, Qy), (Rx, Ry)

    (q1, q2, dQ) = ClosestPair(Qx, Qy)
```

```
(r1, r2, dR) = ClosestPair(Rx, Ry)
```

```
Construct Sy from Qy, Ry
```

```
Scan Sy, find (s1, s2, dS)
```

```
return (q1, q2, dQ), (r1, r2, dR), (s1, s2, dS)
```

```
depending on which of dQ, dR, dS is minimum
```

Analysis

- Sort P to get P_x, P_y - $O(n \log n)$
- Recursive algorithm
 - Construct $(Q_x, Q_y), (R_x, R_y)$ - $O(n)$
 - Construct S_y from Q_y, R_y - $O(n)$
 - Scan S_y - $O(n)$
- Recurrence: $T(n) = 2T(n/2) + O(n)$ like merge sort
- Overall, $O(n \log n)$

▼ Divide and Conquer: Integer Multiplication

Integer Multiplication

- How do we multiply two integers x, y ?
- Form **partial products** - multiply each digit of y separately by x
- Add up all the partial products
- Works the same in any base - e.g. Binary
- To multiply 2 n -bit numbers
 - n partial products
 - Adding each partial product to cumulative sum is $O(n)$
 - Overall $O(n^2)$
- Can we improve on this?
 - Each partial product seems "necessary"

12	1100
x 13	x 1101
---	-----
36	1100
12	0000
---	1100
156	1100

	10011100

Divide and Conquer

- Split the n bits into 2 groups of $n/2$

$$\begin{array}{rcl}
 & x_1 & x_0 \\
 \times & b_{n-1} b_{n-2} \cdots b_{\frac{n}{2}} & b_{\frac{n}{2}-1} b_{\frac{n}{2}-2} \cdots b_0 \\
 \\
 & y_1 & y_0 \\
 y & b'_{n-1} b'_{n-2} \cdots b'_{\frac{n}{2}} & b'_{\frac{n}{2}-1} b'_{\frac{n}{2}-2} \cdots b'_0
 \end{array}$$

- Rewrite xy as $(x_1 \cdot 2^{n/2} + x_0)(y_1 \cdot 2^{n/2} + y_0)$
- Regroup as $x_1 y_1 \cdot 2^n + (x_1 y_0 + x_0 y_1) \cdot 2^{n/2} + x_0 y_0$
- Four $n/2$ -bit multiplications
- $T(1) = 1, T(n) = 4T(n/2) + n$
 - Combining the partial products requires adding $O(n)$ bit numbers

$$\begin{aligned}
 T(n) &= 4T(n/2) + n \\
 &= 4(4T(n/4) + n/2) + n \\
 &= 4^2 T(n/2^2) + (2 + 1)n \\
 &= 4^2(4T(n/2^3) + n/2^2) \\
 &\quad + (2^1 + 2^0)n \\
 &= 4^3 T(n/2^3) + (2^2 + 2^1 + 2^0)n \\
 &= \dots \\
 &= 4^{\log n} T(n/2^{\log n}) \\
 &\quad + (2^{\log n - 1} + \dots + 2^1 + 2^0)n \\
 &= O(n^2)
 \end{aligned}$$

Karatsuba's algorithm

- Rewrite xy as $x_1y_1 \cdot 2^n + (x_1y_0 + x_0y_1) \cdot 2^{n/2} + x_0y_0$
- $T(n) = 4T(n/2) + n$ is $O(n^2)$
- Divide and Conquer has not helped!
- $(x_1 - x_0)(y_1 - y_0) = x_1y_1 - x_1y_0 - x_0y_1 + x_0y_0$
 - $O(n/2)$ bit multiplication
- Compute x_1y_1, x_0y_0
 - $O(n/2)$ bit multiplications
- $(x_1y_1 + x_0y_0) - (x_1 - x_0)(y_1 - y_0)$ leaves $x_1y_0 + x_0y_1$
 - 3 $O(n/2)$ bit multiplications

The Algorithm

Fast-Multiply(x, y, n)

if $n = 1$

return $x \cdot y$

else

$m = n/2$

$(x_1, x_0) = (x/2^m, x \bmod 2^m)$ Bit shifting

$(y_1, y_0) = (y/2^m, y \bmod 2^m)$ Bit shifting

$(a, b) = (x_1 - x_0, y_1 - y_0)$

$p = \text{Fast-Multiply}(x_1, y_1, m)$

$q = \text{Fast-Multiply}(x_0, y_0, m)$

$r = \text{Fast-Multiply}(a, b, m)$

return $p \cdot 2^n + (p + q - r) \cdot 2^{n/2} + q$

Karatsuba's algorithm - Analysis

$$\blacksquare T(1) = 1, T(n) = 3T(n/2) + n$$

$$\begin{aligned} \blacksquare T(n) &= 3T(n/2) + n \\ &= 3(3T(n/4) + n/2) + n \\ &= 3^2 T(n/2^2) + (3/2 + 1)n \\ &= 3^2(3T(n/2^3) + n/2^2) + ((3/2)^1 + 1)n \\ &= 3^3 T(n/2^3) + ((3/2)^2 + (3/2)^1 + 1)n \\ &= \dots \\ &= 3^{\log n} T(n/2^{\log_2 n}) + ((3/2)^{\log n - 1} + \dots + (3/2)^1 + 1)n \\ &= 3^{\log n} + [((3/2)^{\log n - 1} - 1)/((3/2) - 1)]n \end{aligned}$$

$$\blacksquare a^{\log n} = n^{\log a}$$

$$\blacksquare 3^{\log n} = n^{\log 3}$$

$$\begin{aligned} \blacksquare n \cdot (3/2)^{\log n} &= n \cdot n^{\log(3/2)} \\ &= n \cdot n^{\log 3 - \log 2} \\ &= n^1 \cdot n^{\log 3 - 1} \\ &= n^{1 + \log 3 - 1} \\ &= n^{\log 3} \end{aligned}$$

$$\blacksquare \log 3 \approx 1.59$$

■ Divide and conquer reduces the complexity of integer multiplication from $O(n^2)$ to $O(n^{1.59})$

Historical note

- In the 1950s, Andrei Kolmogorov, one of the giants of 20th century mathematics, publicly conjectured that multiplication could not be done in subquadratic time
- Kolmogorov mentioned this conjecture at a seminar in Moscow University in 1960
- Anatolii Karatsuba, a 23 year old student, came back 2 weeks later to Kolmogorov with this divide and conquer algorithm
- Karatsuba's original proposal was slightly different
 - Instead of $r = (x_1 - x_0)(y_1 - y_0)$, he used $r = (x_1 + x_0)(y_1 + y_0)$
 - Then, $x_0 y_1 + x_1 y_0 = r - (x_1 y_1 + x_0 y_0)$
 - Difficulty is that $x_1 + x_0, y_1 + y_0$ could have $n + 1$ bits, complicates the analysis
- Using $r = (x_1 - x_0)(y_1 - y_0)$ to simplify the analysis is due to Donald Knuth
- Karatsuba's algorithm can be used in any base, not just for binary multiplication

▼ Divide and Conquer: Recursion Trees


Solving recurrences

- Divide and conquer involves breaking up a problem into disjoint subproblems and combining the solutions efficiently
- Complexity $T(n)$ is expressed as a recurrence
- For searching and sorting, we solved simple recurrence by repeated substitution
 - Binary search: $T(n) = T(n/2) + 1$, $T(n)$ is $O(\log n)$
 - Merge sort: $T(n) = 2T(n/2) + n$, $T(n)$ is $O(n \log n)$
- For integer multiplication, the analysis became more complicated
 - Naive divide and conquer: $T(n) = 4T(n/2) + n$, $T(n)$ is $O(n^2)$
 - Karatsuba's algorithm: $T(n) = 3T(n/2) + n$ is $O(n^{\log_2 3})$
- Is there a uniform way to compute the asymptotic expression for $T(n)$?

Recursion Trees

- **Recursion tree** Rooted tree with one node for each recursive subproblem
- **Value** of each node is time spent on that subproblem **excluding** recursive calls
- Concretely, on an input of size n
 - $f(n)$ is the time spent on non-recursive work
 - r is the number of recursive calls
 - Each recursive call works on a subproblem of size n/c
- Resulting recurrence: $T(n) = rT(n/c) + f(n)$
- Root of recursion tree for $T(n)$ has value of $f(n)$
- Root has r children, each (recursively) the root of a tree for $T(n/c)$
- Each node at level d has value $f(n/c^d)$
 - Assume, for simplicity, that n was a power of c

Recursion tree for $T(n) = rT(n/c) + f(n)$



▼ Recursion Trees

- Leaves correspond to the base case $T(1)$
 - Safe to assume $T(1) = 1$, asymptotic complexity ignores constants
- Level i has r^i nodes, each with value $f(n/c^i)$
- Tree has L levels, $L = \log_c n$
- Total cost is $T(n) = \sum_{i=0}^L r^i \cdot f(n/c^i)$
- Number of leaves is r^L
 - Last term in the level by level sum is $r^L \cdot f(1) = r^{\log_c n} \cdot 1 = n^{\log_c r}$
 - Recall that $a^{\log_b c} = c^{\log_b a}$
- Tree has $\log_c n$ levels, last level has the cost $n^{\log_c r}$
- Total cost is $T(n) = \sum_{i=0}^L r^i \cdot f(n/c^i)$
- Think of the total cost as a series. Three common cases
- **Decreasing** Each term is a constant factor smaller than the previous term
 - Root dominates the sum, $T(n) = O(f(n))$
- **Equal** All terms in the series are equal
 - $T(n) = O(f(n) \cdot L) = O(f(n) \log n)$ – $\log_c n$ is asymptotically the same as $\log n$
- **Increasing** Series grows exponentially, each term a constant factor larger than the previous term
 - Leaves dominate the sum, $T(n) = O(n^{\log_c r})$

▼ Divide and Conquer: Quick Select

Selection

- Find the k^{th} largest value in a sequence of length n
- Sort in descending order and look at position k - $O(n \log n)$
- Can we do better than this?
 - $k = 1$ - maximum, $O(n)$
 - $k = n$ - minimum, $O(n)$
- For any fixed k , k passes, $O(kn)$
- Median - $k = n/2$
 - If we can find median $O(n)$, quicksort becomes $O(n \log n)$

▼ Divide and Conquer

- Recall partitioning for quicksort
 - Pivot partitions sequence as `lower` and `upper`
- Let `m = len(lower)`. 3 cases:
 - `k <= m` - answer lies in `lower`
 - `k == m + 1` - answer lies in `pivot`
 - `k > m + 1` - answer lies in `upper`
- Recursive strategy
 - Case 1: `select(lower, k)`
 - Case 2: `return(pivot)`
 - Case 3: `select(upper, k - (m + 1))`

```
# To find the k-th largest element in L[l:r]
def quick_select(L, l, r, k):
    if (k < 1) or (k > r - 1):
        return None

    pivot, lower, upper = L[l], l + 1, l + 1

    for i in range(l + 1, r):
        if L[i] > pivot:      # Extend the upper segment
            upper += 1
        else:                # Exchange L[i] with the start of upper segment
            L[i], L[lower] = L[lower], L[i]
            lower += 1
```

```

    upper += 1

# Move the pivot
L[l], L[lower - 1] = L[lower - 1], L[l]
lower - 1

# Recursive calls
lower_len = lower - 1

if k <= lower_len:
    return quick_select(L, l, lower, k)
elif k == lower_len + 1:
    return L[lower]
else:
    return quick_select(L, lower + 1, r, k - (lower_len + 1))

```

Analysis

- Recurrence is similar to quick sort
- $T(1) = 1$
- $T(n) = \max(T(m), T(n - (m + 1))) + n$, where $m = \text{len}(\text{lower})$
- Worst case: m is always 0 or $n - 1$
 - $T(n) = T(n - 1) + n$
 - $T(n)$ is $O(n^2)$
- Recall: if the pivot is within a fixed fraction, quick sort is $O(n \log n)$
 - E.g. pivot in middle third of values
 - $T(n) = T(n/3) + T(2n/3) + n$
- Can we find a good pivot quickly?

▼ Median of medians

- Divide L into blocks of 5
- Find the median of each block (brute force)
- Let M be the list of block medians
- Recursively apply the process to M
- What can we guarantee about $\text{MoM}(L)$?

```

def MoM(L):    # Median of medians
    if len(L) <= 5:
        L.sort()
        return L[len(L)//2]

# Construct list of block medians

```

```


M = []

for i in range(0, len(L), 5):
    X = L[i : i + 5]
    X.sort()
    M.append(X[len(X)//2])


return MoM(M)

```

- We can visualize the blocks as follows
- Each block of 5 is arranged in ascending order, top to bottom
- Block medians are the middle row



- We can visualize the blocks as follows
- Each block of 5 is arranged in ascending order, top to bottom
- Block medians are the middle row
- The median of block medians lies between $3\text{len}(L)/10$ and $7\text{len}(L)/10$



▼ Analysis

- Use median of block medians to locate the pivot for `quick_select`
- `MoM` is $O(n)$
 - $T(1) = 1$

- $T(n) = T(n/5) + n$
- Recurrence for `fast_select` is now
 - $T(1) = 1$
 - $T(n) = \max(T(3m/10), T(7m/10) + n)$, where $m = \text{len}(\text{lower})$
- $T(n)$ is $O(n)$
- Can also use MoM to make quick sort $O(n \log n)$

```
# Find the k-th largest element in L[l:r]
def fast_select(L, l, r, k):
    if (k < 1) or (k > r - 1):
        return None

    # Find MoM pivot and move to L[l]
    pivot = MoM(L[l:r])
    pivot_pos = min([i for i in range(l, r) if L[i] == pivot])
    L[l], L[pivot_pos] = L[pivot_pos], L[l]

    # Partition as before
    pivot, lower, upper = L[l], l + 1, l + 1
    for i in range(l + 1, r):
        ...

    # Recursive calls
    lower_len = lower - l

    if k <= lower_len:
        return fast_select(L, l, lower, k)
    elif k == lower_len + 1:
        return L[lower]
    else:
        return fast_select(L, lower + 1, r, k - (lower_len + 1))
```

Summary

- Median of block medians helps find a good pivot in $O(n)$
- Selection becomes $O(n)$, *quicksort becomes* $O(n \log n)$
**Notice that 'fast_select' with 'k = len(L)/2' finds median in time $O(n)$*

Historical note

- C.A.R. Hoare described `quick_select` in the same paper that introduced `quick_sort`, 1962
- The median of medians algorithm is due to Manuel Blum, Robert Floyd, Vaughn Pratt, Ron Rivest and Robert Tarjan, 1973

Acknowledgement

▼ Implementation of Quick Select and Fast Select Algorithms

```
def quick_select(L, l, r, k):    # k-th largest in L[l:r]
    if (k < 1) or (k > r - 1):
        return None

    pivot, lower, upper = L[l], l + 1, l + 1

    for i in range(l + 1, r):
        if L[i] > pivot:        # Extend the upper segment
            upper += 1
        else:                  # Exchange L[i] with start of upper segment
            L[i], L[lower] = L[lower], L[i]
            lower += 1
            upper += 1


    L[l], L[lower - 1] = L[lower - 1], L[l]
    lower -= 1

    # Recursive calls
    lower_len = lower - l

    if k <= lower_len:
        return quick_select(L, l, lower, k)
    elif k == lower_len + 1:
        return L[lower]
    else:
        return quick_select(L, lower + 1, r, k - (lower_len + 1))
```

```
from random import *
A = [randrange(1000) for i in range(200)]
print(A)
```

[459, 622, 418, 938, 112, 602, 681, 763, 566, 859, 949, 917, 181, 168, 147, 530, 661,



```
for i in range(0, len(A) + 2):
    print(quick_select(A, 0, len(A), i))
```



None

1
5
5
12
17
19
25



25
29
37
44
53
57
63
64
68
72
73
74
77
79
85
89
94
95
96
97
97
112
117
129
133
140
145
147
147
149
149
151
151
155
168
168
168
181
183
188
198
199
206
208
212
213
226
231
235
240
244
248

```
def MoM(L):          # Median of medians
    if len(L) <= 5:
        L.sort()
        return L[len(L)//2]

# Construct list of block medians
M = []
```

```

for i in range(0, len(L), 5):
    X = L[i:i + 5]
    X.sort()
    M.append(X[len(X)//2])

return MoM(M)


from random import *
A = [randrange(1000) for i in range(200)]
print(A)

```

```

[923, 690, 370, 838, 519, 572, 18, 772, 414, 800, 444, 458, 487, 353, 561, 128, 668,

```

◀  ▶

```

B = sorted(A)
(B[(3 * len(B))//10], B[len(B)//2], B[(7 * len(B))//10], MoM(A))

(342, 480, 677, 459)

```

```

import sys
sys.setrecursionlimit(2 ** 31 - 1)

```

```

import time

class TimeError(Exception):
    """A custom exception used to report error in the use of Timer class"""

class Timer:
    def __init__(self):
        self._start = 0
        self._elapsed = 0

    def start(self):
        if self._start is not None:
            raise TimeError('Timer is running. Use .stop()')

        self._start = time.perf_counter()

    def stop(self):
        if self._start is None:
            raise TimeError('Timer is not running. Use .start()')

        self._elapsed = time.perf_counter() - self._start
        self._start = None

    def elapsed(self):
        if self._elapsed is None:
            raise TimeError('Timer has not been run yet. Use .start()')

```

```

    return self._elapsed

def __str__(self):
    return str(self._elapsed)

```

```

t = Timer()
t.stop()
t.start()

A = [i for i in range(10000)]
print(quick_select(A, 0, len(A), 10000))
t.stop()

print(t)

```

```

9999
6.074782084999697

```

```

# Find the k-th largest element in L[l:r]
def fast_select(L, l, r, k):
    if (k < 1) or (k > r - 1):
        return None

    # Find MoM pivot and move to L[l]
    pivot = MoM(L[l:r])
    pivot_pos = min([i for i in range(l, r) if L[i] == pivot])
    L[l], L[pivot_pos] = L[pivot_pos], L[l]

    # Partition as before
    pivot, lower, upper = L[l], l + 1, l + 1
    for i in range(l + 1, r):
        if L[i] > pivot: # Extend the upper segment
            upper += 1
        else:           # Exchange L[i] with the start of the upper segment
            L[i], L[lower] = L[lower], L[i]
            lower += 1
            upper += 1

    L[l], L[lower - 1] = L[lower - 1], L[l]
    lower -= 1

    # Recursive calls
    lower_len = lower - l

    if k <= lower_len:
        return fast_select(L, l, lower, k)
    elif k == lower_len + 1:
        return L[lower]

```



```
else:  
    return fast_select(L, lower + 1, r, k - (lower_len + 1))
```

```
t = Timer()  
t.stop()  
t.start()  
  
A = [i for i in range(10000)]  
print(fast_select(A, 0, len(A), 10000))  
t.stop()  
print(t)
```

```
None  
0.0011042640003324777
```