

Notes on Anomaly Detection

Sameer Kesava PhD

April 26, 2020

Contents

1	Supervised Learning Algorithms	1
1.1	Univariate Data	1
1.2	Multivariate Data	1
1.3	Random Cut Forest	1
1.4	XGBoost	1
2	Unsupervised Learning Algorithms	2
2.1	MeanShift Clustering	2
2.2	DBSCAN	2
3	Improving the Accuracy	3
3.1	Hyperparameter Tuning	3

Supervised Learning Algorithms

1.1 Univariate Data

- Boxplot
- Grubbs test

1.2 Multivariate Data

1.3 Random Cut Forest

From Amazon SageMaker

1.4 XGBoost

- Gradient boosting method
- Absolute loss and Huber loss more robust to outliers.
- Hyperparameters
 1. Max_depth
 2. Colsample_bytree
 3. Eta
 4. train-test split: 60-40/70-30/80-20.

Unsupervised Learning Algorithms

2.1 MeanShift Clustering

2.2 DBSCAN

Improving the Accuracy

3.1 Hyperparameter Tuning

- Hyperparameter optimization based on Gaussian Process Regression and Bayesian Optimization
- keras tuner in keras
- GridSearchCV or RandomSearchCV in scikit-learn
- RandomSearch can be used as the baseline against which optimization algorithms can be evaluated.

Bibliography

- [1] Pankaj Malhotra et al., Long Short Term Memory Networks for Anomaly Detection in Time Series, 2015.