A Synchronization Critic for Video-to-Audio Generation Works as a Reward on Samples Rather than as a Training Loss

Samer Aslan
Johns Hopkins University

Abstract

Video-to-audio (V2A) generators usually produce the right kind of sound for a scene, but often at the wrong moment. We study how a synchronization critic can improve the timing of a codebook V2A generator (SpecVQGAN). The critic is a small audio-visual model, trained contrastively on real clips to find the true offset between audio and video and then frozen. Its score, the Perceptual Alignment Loss (PAL), is the share of the critic's offset distribution that falls inside a window around zero offset, a simplified stand-in for the human audio-visual temporal binding window. We compare two ways to use PAL. As a differentiable training loss, passed to the transformer's logits through straight-through codebook decoding, PAL does not improve timing on FlashDot, a synthetic benchmark of flashing dots and tones with frame-exact labels: tone-activity F1 is 0.23 to 0.30 with PAL and 0.41 with cross-entropy alone. Two diagnostics explain this. Teacher-forced predictions inherit their alignment from the ground-truth prefix, so they look aligned without using the video, and the frozen critic can be fooled: optimizing free logits against PAL reaches the PAL of the ground-truth codes while the decoded audio has tone F1 of 0.28 (0.20 for random codes, 0.98 for the ground truth). As a reward on the generator's own free-running samples, the same critic helps: keeping the best of eight samples raises tone F1 from 0.50 to 0.54 and held-out synchronization accuracy from 0.25 to 0.65 on the FlashDot development split. PAL-filtered self-training, which fine-tunes the generator on its own lowest-PAL samples, [one-sentence VAS and FlashDot test result against random selection and ground-truth-only fine-tuning]. A check of timing metrics against known delays shows that envelope lag recovers a delay exactly, while DTW distance mostly measures spectral content. For discrete-token V2A models, a synchronization critic is far more useful as a reward on the generator's own samples than as a differentiable loss. Code and FlashDot: `https://github.com/sameraslan/PerceptAlign`.

1 Introduction

Video-to-audio (V2A) generation produces a soundtrack that fits the frames of a silent clip, for uses such as Foley for film and sound for generated video. Codebook-transformer models (Iashin and Rahtu, 2021) and their successors usually get the kind of sound right. Timing is harder: a hammer clip can receive convincing hammer sounds whose impacts land between the visible strikes. Part of the reason is the training objective. Cross-entropy over discrete spectrogram tokens has no notion of temporal distance, so an onset placed slightly early costs about as much as one placed a second early.

Human perception handles timing with some tolerance. Light and sound from one event arrive at slightly different times, and observers still bind them into one event when the asynchrony falls inside the temporal binding window (Wallace and Stevenson, 2014). The window is wider when audio lags than when it leads (Dixon and Spitz, 1980; van Wassenhove et al., 2007; Vroomen and Keetels, 2010), varies between people (Stevenson et al., 2012), and shifts after exposure to a constant lag (Fujisaki et al., 2004). We take one design principle from this literature: a timing score should accept small offsets around zero and penalize large ones, rather than treating every non-zero offset as equally wrong. Calling the score "perceptual" is an analogy; we do not model the perceptual system.

We build such a score from a frozen, contrastively pretrained synchronization critic. For each short segment of a clip, the critic compares audio and video embeddings at every offset in a small range and turns the comparisons into a distribution over offsets; the Perceptual Alignment Loss (PAL) is the negative log of the mass inside a window around zero. The form follows the self-synchronization loss of Niu and Mak (2023), with a soft window over near-zero offsets in place of their one-hot target, an optional asymmetric window, and computation per segment.

A frozen critic can enter a generator in two ways. It can be a differentiable training loss, as the sync expert of Wav2Lip (Prajwal et al., 2020) is for lip generation; for a discrete-token generator this needs a path from the logits to

a spectrogram, which we provide with straight-through decoding through the frozen codebook decoder. Or it can be a reward on whole samples from the generator, as in re-ranking (Du et al., 2023) and preference optimization (Chan et al., 2026; Cheng et al., 2026). We study both on SpecVQGAN and find a clear difference. As a loss, PAL does not improve timing, for two reasons we isolate with simple probes. Teacher-forced predictions are conditioned on the aligned ground-truth prefix, so they look aligned to the critic whether or not the model uses the video (exposure bias, Bengio et al., 2015; Ranzato et al., 2016). And when the gradient path is opened up so that only the video can explain the timing, the generator finds spectrograms that the frozen critic scores as well aligned but that do not follow the video. As a reward on free-running samples, the critic avoids both problems: candidates are realistic outputs of the generator, so the critic only has to rank them. Because a timing metric that compares spectrograms can be dominated by spectral content, we also test candidate metrics against known delays on a benchmark where the correct timing is known exactly.

Contributions.

- **PAL**, a windowed, per-segment synchronization score from a frozen critic, used as a loss and as a reward (Section 3).
- **An analysis of why PAL fails as a loss** for a codebook generator, with two reusable diagnostics: a wrong-video cross-entropy probe for exposure bias and a free-logit attack that tests whether a critic can be exploited (Sections 3.6 and 5.2).
- **PAL-filtered self-training**, which fine-tunes the generator on its own lowest-PAL samples, with random-selection and ground-truth-only controls, alongside best-of-N re-ranking (Sections 3.5 and 5.3).
- **FlashDot**, a synthetic benchmark of flashing dots and synchronous tones with frame-exact timing labels, and **a metric check** of how timing metrics respond to known delays (Sections 4.1 and 5.1).

2 Related work

Video-to-audio generation. Early systems include example-based synthesis on Greatest Hits (Owens et al., 2016), waveform generation on VEGAS (Zhou et al., 2018) and RegNet on VAS (Chen et al., 2020). SpecVQGAN (Iashin and Rahtu, 2021), our base model, adapts VQGAN (Esser et al., 2021) to spectrograms and predicts codes from visual features with a transformer. Other systems improve alignment through architecture or visual features (Mei et al., 2024; Wang et al., 2024c; Viertola et al., 2025; Cheng et al., 2025; Mo and Song, 2025), or condition on a timing signal predicted from video such as onsets, energy or a coarse layout (Comunità et al., 2024; Zhang et al., 2026; Ton et al., 2025; Jeong et al., 2025; Wang et al., 2024b). Semantic conditioning without a timing mechanism is also common (Sheffer and Adi, 2023; Wang et al., 2024a).

Synchronization signals for V2A. Several systems use a synchronization model on whole outputs. CondFoley (Du et al., 2023) re-ranks samples from a code model with a synchronization model at test time. Diff-Foley (Luo et al., 2023) guides diffusion sampling with an alignment classifier, and Seeing and Hearing (Xing et al., 2024) steers pretrained generators with a frozen multimodal aligner. V2A-DPO (Chan et al., 2026) and SyncDPO (Cheng et al., 2026) post-train with preference pairs that reward synchronization. Our self-training is in the same family of sample-level rewards, with a binding-window critic as the reward and supervised fine-tuning on selected samples in place of a preference objective.

Synchronization models and losses. SyncNet (Chung and Zisserman, 2017) learned a two-stream embedding for lip sync. Owens and Efros (2018) learned audio-visual features by detecting shifted audio, the supervision our critic uses, and Chung et al. (2019) trained with a softmax over many candidate offsets, the form of our critic objective. Later models cover lips and voices (Kadandale et al., 2022; Chen et al., 2024), localization (Afouras et al., 2020; Arandjelović and Zisserman, 2018) and open-domain video (Iashin et al., 2022, 2024). Inside generators, Wav2Lip (Prajwal et al., 2020) trains a face generator against a frozen sync expert, VCA-GAN (Kim et al., 2021) adds a contrastive synchronization term to lip-to-speech, Niu and Mak (2023) use the negative log probability of zero offset from a cross-correlation over offsets, and LatentSync (Li et al., 2024) carries SyncNet supervision into latent diffusion. These methods produce continuous outputs for lips and speech; we ask whether the same kind of loss transfers to a discrete-token sound-effect generator, and find that it does not.




Figure 1: Two uses of one frozen critic. (a) Stage 1: the critic embeds a real spectrogram (ground truth or its VQGAN reconstruction) and the clip's visual features and is trained so that zero offset wins the softmax over offsets. (b) PAL as a loss (Section 3.4): a window of the transformer's logits is decoded with a straight-through estimator, scored by the critic, and PAL is added to the cross-entropy loss. (c) PAL as a reward (Section 3.5): free-running samples are decoded and scored, and the lowest-PAL sample is kept for output or for fine-tuning.

Exposure bias, self-training and reward over-optimization. Teacher forcing conditions each prediction on the ground-truth prefix, so training never sees the model's own errors; scheduled sampling feeds model predictions back during training (Bengio et al., 2015), and sequence-level training scores whole generated sequences (Ranzato et al., 2016). Training on a model's own filtered outputs appears in expert iteration (Anthony et al., 2017) and in ReST (Gulcehre et al., 2023), which alternate sampling from the current policy, filtering by a reward and fine-tuning on the kept samples; our self-training follows that loop with a synchronization critic as the filter. A learned reward that is optimized hard drifts away from the quantity it stands for (Gao et al., 2023); our free-logit attack measures the extreme case, with no generator between the optimizer and the critic.

Human audio-visual timing. Observers perceive auditory and visual signals as one event over a range of asynchronies, the temporal binding window (Wallace and Stevenson, 2014). Audio lead is detected at smaller asynchronies than audio lag (Dixon and Spitz, 1980), and the window for audio-visual speech is wider on the audio-lag side (van Wassenhove et al., 2007; Vroomen and Keetels, 2010). Its width differs across individuals (Stevenson et al., 2012), and perceived simultaneity recalibrates after exposure to a constant lag (Fujisaki et al., 2004; Takeshima, 2021). We use these findings only to motivate the shape of the target over offsets.

3 Method

3.1 Base generator: SpecVQGAN

We follow SpecVQGAN (Iashin and Rahtu, 2021). Audio is an 80-bin log-mel spectrogram (86.1 frames per second) of 848 frames, about 9.8 s, with values in $[0, 1]$. A VQGAN (Esser et al., 2021) encodes it into a 5×53 grid of codes from a codebook $E \in \mathbb{R}^{|V| \times 256}$, $|V| = 128$; one code column covers 16 mel frames. The transformer reads codes in column-major order (the five codes of a column, then the next column), so a sequence has $N = 265$ tokens. It is a GPT whose input starts with the clip's 212 visual feature frames (2048-dimensional, 21.5 per second, four per code column), followed by the token embeddings. It is trained by teacher-forced cross-entropy, $\mathcal{L}_{\text{CE}} = -\frac{1}{N}\sum_j \log q_j(z_j)$ with $q_j = \text{softmax}(\ell_j)$, where z_j is the ground-truth code and $\ell_j \in \mathbb{R}^{|V|}$ the logits at position j, computed from the visual features and the ground-truth prefix $z_{<j}$. At test time codes are sampled autoregressively (top-k with $k = 100$, temperature 1) and decoded by the VQGAN decoder.

3.2 Synchronization critic

The critic has an audio encoder and a video encoder of the same structure: two blocks of a temporal one-dimensional convolution (kernel 5, 256 channels), group normalization (8 groups) and GELU, then a 1×1 convolution to 128 dimensions and L2 normalization at every frame. The audio input is the spectrogram mapped to $[-1, 1]$ and average-pooled by four along time, which brings it to the 212-frame rate of the visual features. In a band variant the audio encoder sees only $B \in \{8, 4, 1\}$ band energies, the means over equal groups of mel bins, so it can judge when energy changes but sees little of the spectral content. The design follows the local feature extractors of Niu and Mak (2023). For a clip the critic gives unit-norm embeddings $a_1, \ldots, a_T$ and $v_1, \ldots, v_T$.

3.3 Perceptual Alignment Loss

For offsets $o \in \{-K, \ldots, K\}$ (in video frames), PAL compares audio frame i with video frame $i+o$, so a negative offset means the audio event comes after the visual one (audio late). The central frames $i \in [K, T-K)$ are split into S equal consecutive segments $I_1, \ldots, I_S$, so every offset compares the same number of real frames. For segment s,

$$C_{s,o} = \frac{1}{|I_s|} \sum_{i \in I_s} \langle a_i, v_{i+o} \rangle, \qquad p_{s,o} = \frac{\exp(C_{s,o}/\tau)}{\sum_{o'=-K}^{K} \exp(C_{s,o'}/\tau)}. \tag{1}$$

The target is a window over offsets with weight one at zero,

$$w_o = \exp\left(-\frac{o^2}{2\sigma_o^2}\right), \quad \sigma_o = \begin{cases} \sigma_{\text{late}} & o < 0 \text{ (audio late)}, \\ \sigma & o \geq 0, \end{cases} \qquad W_s = \sum_{o=-K}^{K} w_o \, p_{s,o} \in (0, 1]. \tag{2}$$

The symmetric window has $\sigma_{\text{late}} = \sigma$; the asymmetric option sets $\sigma_{\text{late}} > \sigma$, widening the window on the audio-late side in the direction of the human asymmetry. With $\sigma = 0$ the window is the indicator of zero offset. PAL averages the windowed mass over segments and takes the negative logarithm:

$$\mathcal{L}_{\text{PAL}} = -\log\left(\frac{1}{S} \sum_{s=1}^{S} W_s\right). \tag{3}$$

With $\sigma = 0$ and $S = 1$, Equation (3) is $-\log p_{1,0}$, the self-synchronization loss of Niu and Mak (2023). The window gives partial credit for mass one or two frames from zero, and segmentation keeps one well-aligned stretch from hiding a badly aligned one. Stage 1 uses the per-segment reduction $-\frac{1}{S} \sum_s \log W_s$.

Stage 1: training the critic. The critic is trained on real clips with $\sigma = 0$, $K = 10$, $\tau = 0.1$ and the per-segment log reduction ($S = 8$ on VAS, $S = 4$ on FlashDot), so the negatives are the other offsets of the same clip (Owens and Efros, 2018; Chung et al., 2019) and the objective is a cross-entropy over offsets with zero offset as the target in every segment. The audio input is the VQGAN reconstruction of the ground truth (the ground truth itself with probability 0.3), since every spectrogram the critic scores later comes out of the same decoder. The critic is then frozen.

3.4 PAL as a training loss

The critic needs a spectrogram, while the transformer outputs a distribution over codes. With $q_j = \text{softmax}(\ell_j)$, the decoded code vector is

$$\hat{e}_j = \left(\text{onehot}\left(\arg\max_k q_{j,k}\right) + q_j - \text{sg}(q_j)\right)^{\top} E, \tag{4}$$

where sg stops the gradient (Bengio et al., 2013). The forward value is the codebook entry of the most likely code, so the decoder only receives real codebook entries, and the backward pass uses the gradient of the expected code vector $q_j^{\top} E$. The code vectors are decoded by the frozen decoder and scored by the critic. To bound memory, PAL is computed on a random window of 12 code columns (about 2.2 s, decoded with one extra column of context on each side) for four examples per batch, with $K = 8$, $S = 4$, $\tau = 0.1$ and $\sigma = 1$. The loss is $\mathcal{L} = \mathcal{L}_{\text{CE}} + \beta \, \mathcal{L}_{\text{PAL}}$.

Algorithm 1 PAL-filtered self-training

Require: generator G, frozen decoder D and critic, training clips $\{(x_i, z_i)\}$, rounds R, clips per round M, candidates N, steps per round U

for $r = 1, \ldots, R$ **do**
  draw M training clips $\mathcal{I}$
  for $i \in \mathcal{I}$ **do**
    sample $\tilde{z}_i^{(1)}, \ldots, \tilde{z}_i^{(N)} \sim G(\cdot \mid x_i)$ ▷ free-running, top-k
    $k^\star \leftarrow \arg\min_k \mathcal{L}_{\text{PAL}}\big(D(\tilde{z}_i^{(k)}), x_i\big)$ ▷ random control: $k^\star \leftarrow 1$
    $\hat{z}_i \leftarrow \tilde{z}_i^{(k^\star)}$
  end for
  for U steps **do**
    batch: half $(x_i, \hat{z}_i)$ with $i \in \mathcal{I}$, half (x_j, z_j) from all training clips
    update G (or its LoRA adapters) by teacher-forced $\mathcal{L}_{\text{CE}}$ on the batch
  end for
end for

Corrupted-prefix PAL. If the logits come from the teacher-forced pass, PAL scores the most likely codes given the ground-truth prefix. In column-major order the prefix contains the codes of every earlier column, which already show whether a sound is on, so these predictions can look aligned without any use of the video. We therefore also compute PAL on a second forward pass in which each input token is replaced by a uniformly random code with probability $1 - p_{\text{keep}}^{\text{PAL}}$. With $p_{\text{keep}}^{\text{PAL}} = 0$ the prefix carries no information, and the video is the only source of timing. Cross-entropy can use the same corruption on its own pass ($p_{\text{keep}} < 1$), a simple form of training on imperfect prefixes in the spirit of scheduled sampling (Bengio et al., 2015).

3.5 PAL as a reward on samples

Best-of-N re-ranking. For each clip we draw N free-running samples, score each with PAL under the training critic, and output the lowest-PAL sample. This needs no training and multiplies test-time cost by N.

PAL-filtered self-training. Self-training moves the selection into training (Algorithm 1). Each round draws N samples for a random subset of training clips, keeps the lowest-PAL sample per clip, and fine-tunes the generator with cross-entropy on batches that mix kept samples and ground truth half and half. The critic only ranks realistic outputs of the generator and is never differentiated. Two controls share every setting: *random selection* keeps an arbitrary candidate (the one drawn first) in place of the lowest-PAL one, so any difference comes from the critic's choice; *ground-truth-only* fine-tuning runs the same number of steps on ground truth alone, so any difference from it comes from training on the model's own samples. On VAS only LoRA adapters (Hu et al., 2022) on the frozen SpecVQGAN transformer are trained.

3.6 Diagnostics

Two cheap probes tell, before a long training run, whether a critic-based loss can work for a given autoregressive code model and frozen critic.

Wrong-video cross-entropy. We compute development cross-entropy twice, once with each clip's own visual features and once with the features of a different development clip, and repeat both with a fully corrupted prefix ($p_{\text{keep}} = 0$). The first gap shows whether the model uses the video at all; the second, and its level against uniform ($\log |V| \approx 4.85$), whether the video alone can carry its predictions. If it cannot, a loss that needs the model to use the video has little to work with.

Free-logit attack. We replace the generator with free logits for eight development clips, initialized at random and optimized by Adam (learning rate 0.1, 200 steps) to minimize PAL through the same straight-through decoding and window as in training. If the PAL reached matches that of the ground-truth codes while the timing metrics (Section 4.3)

of the decoded optimum stay near those of random codes, the critic can be satisfied by audio that does not follow the video, and a generator trained against it can learn the same shortcut.

4 Experimental setup

4.1 Datasets

FlashDot. FlashDot is a synthetic benchmark in which the correct timing is known exactly (example in Figure 5). Each 10 s clip shows a red dot on a white background during 1–6 "on" intervals of 0.15–1.5 s and plays a 1 kHz tone during exactly the same intervals; video runs at 21.5 frames per second, and clips are generated from a seed. Spectrograms follow the SpecVQGAN VAS pipeline, and visual features are the 2048-dimensional pooled outputs of an ImageNet-trained ResNet-50 (He et al., 2016), one per frame. We generate 2000 clips, split 1600/200/200 into train, development and test.

VAS. VAS (Chen et al., 2020) has eight classes (baby, cough, dog, drum, fireworks, gun, hammer, sneeze). We use the spectrograms and features released with SpecVQGAN (Iashin and Rahtu, 2021): BN-Inception (Ioffe and Szegedy, 2015) RGB and optical-flow features, flow from denseflow (Wang et al., 2020), concatenated to 2048 dimensions, 212 frames per clip. The test set is SpecVQGAN's `vas_valid` list (768 clips). A class-stratified 5% of `vas_train` is held out as a development split (589 clips), and the remaining 11,184 clips are used for training.

4.2 Models

On FlashDot we train a GPT with 6 layers, 6 heads and width 384 from scratch on codes from the public SpecVQGAN VAS codebook, which is not retrained (batch 8, 2000 steps unless stated). On VAS we start from the public SpecVQGAN VAS transformer (24 layers, 16 heads, width 1024). To fit training on a laptop GPU, its weights are frozen in half precision and only LoRA adapters (Hu et al., 2022) are trained, on the key, query, value and output projections and both MLP layers of every block (rank 16, $\alpha = 16$, initialized so that training starts from the public model). All training uses AdamW (Loshchilov and Hutter, 2019). Table 5 lists all hyperparameters.

4.3 Metrics

Timing metrics compare a generated spectrogram with the ground-truth spectrogram of the same clip. The onset envelope is the spectral flux of the log-mel spectrogram (the sum over bins of positive frame-to-frame differences). *Onset F1* matches generated and ground-truth onsets one to one within ±100 ms (Raffel et al., 2014). *Onset AP* ranks generated onsets by strength and counts a hit when one falls within ±100 ms of an unmatched ground-truth onset, as in Du et al. (2023). For the envelope metrics both envelopes are smoothed and mean-centred: *envelope correlation* is their Pearson correlation at zero lag, and *lag* is the shift within ±1 s that maximizes their cross-correlation, reported as mean absolute value in ms and as the share of clips *within one video frame* ($|\text{lag}| \leq 46.5$ ms).

On FlashDot, *tone F1* is the frame-level F1 between the ground-truth on/off label and a tone detector that thresholds the mean of the three mel bins with the largest on-minus-off difference. Bins and threshold are chosen on VQGAN reconstructions of training clips. Random codes score about 0.20.

Scoring a model with the critic it was selected against invites reward hacking, so *held-out sync accuracy* uses a separate evaluation critic trained with the stage-1 recipe, a different seed and a different architecture (kernel 3, three blocks, width 384; on VAS its audio input is 8 band energies). It scores the whole clip ($S = 1$, $\sigma = 0$) over 21 offsets; we report the fraction of clips whose most likely offset is zero (tolerance 0) or within one frame of zero (tolerance 1). Chance is about $1/21$ and $3/21$. The critics are weak on VAS: development offset accuracy is 0.116 (0.288 within one frame) for the training critic and 0.124 (0.311) for the held-out critic. On FlashDot the training critic reaches 0.77 (0.81), limited by silent segments, which have no offset to find. On VAS we also report Melception FID and mean KL divergence (MKL) as in SpecVQGAN (Iashin and Rahtu, 2021). The metric check (Section 5.1) adds DTW distance on per-clip standardized mel frames (Salvador and Chan, 2007) and mean absolute mel difference (mel L1).




Figure 2: Metric response to injected delays on FlashDot (development, 200 clips). Dashed lines: an unrelated clip. Only |lag| grows in proportion to the delay; DTW and mel L1 rank every delay as closer to the truth than an unrelated clip.

4.4 Protocol

All settings are chosen on the development split, and each final configuration is run on the test split once. The FlashDot loss experiments and the preliminary re-ranking result are single runs (seed 0) on the development split; they are diagnostic. Main FlashDot results use three seeds (0, 1, 2) on the test split and report the mean and standard deviation over seeds; VAS results use one seed, because each fine-tuning arm takes several hours on our hardware. Comparisons between two systems on the same clips use a paired bootstrap over clips (10,000 resamples) of the per-clip difference, reported as a 95% percentile interval and a two-sided p value, checked against a paired sign-flip permutation test.

5 Results

5.1 Which metrics respond to known delays

A timing metric should worsen steadily as a known delay grows and should rank a clip with the right kind of sound but unrelated timing as badly aligned. We delay each of 200 FlashDot development spectrograms by 2 to 64 mel frames (23 to 743 ms), filling the start with the clip's quietest frame, and compare it with the original; as a second reference we compare each clip with a different clip (Figure 2; values in Table 4).

The envelope lag recovers the injected delay exactly. Onset F1 is flat up to 93 ms, inside its tolerance, and drops to the level of an unrelated clip (about 0.14) or below from 186 ms. Envelope correlation falls from 0.75 at 23 ms to about zero by 93 ms, so it cannot tell 100 ms from a second. DTW grows with delay, from 69 at 23 ms to 1968 at 743 ms, but an unrelated clip scores 10582: a large delay looks five times closer to the truth than a clip with different content, so DTW mostly measures content. Mel L1 jumps at the smallest delay and then barely separates a 743 ms delay (0.052) from an unrelated clip (0.054). We therefore use |lag|, within-one-frame, onset F1 and, on FlashDot, tone F1 as timing metrics, and leave DTW out.

5.2 PAL as a training loss does not improve timing

On FlashDot, every way of adding PAL to the loss lowers timing quality (Table 1, middle). With teacher-forced logits, tone F1 falls from 0.414 to 0.297 and held-out sync accuracy from 0.165 to 0.090, below chance, even with 1000 more training steps. Computing PAL from a half or fully corrupted prefix, so that the video is the only source of timing, does no better (tone F1 0.228 and 0.279). Corrupting the prefix of the cross-entropy pass alone, with no critic, helps instead: tone F1 0.499, |lag| 306 ms. The two diagnostics of Section 3.6 show why the loss fails.

Exposure bias. The CE model does use the video under teacher forcing: development cross-entropy is 1.56 with each clip's own visual features and 1.95 with another clip's. With a fully corrupted prefix it is 4.38 against 4.57, close to the uniform level of 4.85, so the video alone tells the model little about which code comes next. Teacher-forced

Table 1: FlashDot. Top: references. Middle: PAL as a loss and the CE baselines, trained from scratch (development split, 2000 steps unless stated). Bottom: PAL as a reward. Sync acc. is the held-out critic at tolerance 1 (chance ≈ 0.14); within 1 frame is the share of clips with |lag| within one video frame. † single training seed. Best of 8 on the development split uses training seed 0.

Model	Split	Tone F1 ↑	|Lag| (ms) ↓	Within 1 frame ↑	Sync acc. ↑
VQGAN reconstruction	dev	0.970	2.7	1.000	1.000
VQGAN reconstruction	test	[]	[]	[]	[]
CE (teacher forcing)†	dev	0.414	423	0.120	0.165
CE, corrupted prefix ($p_{\text{keep}} = 0.5$)†	dev	0.499	306	0.170	0.245
CE + PAL, teacher-forced (3000 steps)†	dev	0.297	474	0.035	0.090
CE + PAL, half-corrupted PAL prefix†	dev	0.228	484	0.035	0.120
CE + PAL, fully corrupted PAL prefix†	dev	0.279	491	0.060	0.125
CE, corrupted prefix, best of 8†	dev	0.535	228	0.480	0.645
CE, corrupted prefix	test	[]	[]	[]	[]
best of 8	test	[]	[]	[]	[]
self-training, random selection	test	[]	[]	[]	[]
self-training, PAL selection	test	[]	[]	[]	[]

predictions therefore inherit their timing from the aligned prefix, and they look aligned to the critic whatever the model does with the video, while the model's free-running samples are close to chance timing (held-out sync accuracy 0.165 against a chance level of about 0.14). A PAL gradient on teacher-forced logits rewards copying the prefix, which the model already does.

The critic can be exploited. Corrupting the PAL prefix removes the shortcut through the prefix but opens another one. In the free-logit attack (Figure 3), optimizing logits directly against the mel critic reaches a PAL of 0.98, about that of the ground-truth codes (0.95; random codes 2.12). The decoded spectrograms are broadband texture with tone F1 0.28, barely above random codes (0.20) and far from the ground truth (0.98). Critics that see only 8, 4 or 1 band energies are fooled the same way. Coarser critics do align energy changes better at the optimum, with |lag| of 151 ms (mel), 147 ms (8 bands), 48 ms (4 bands) and 15 ms (1 band) against 644 ms for random codes, but none of them produces the tone: tone F1 at the optimum is 0.28, 0.28, 0.11 and 0.05. A critic trained only on real audio has never seen spectrograms like these, and it scores them as aligned.

5.3 PAL as a reward on samples

Used to choose among the generator's own samples, the same critic helps. Keeping the best of eight free-running samples from the corruption-trained CE model (candidates scored with $\sigma = 0$) raises tone F1 from 0.499 to 0.535, the share of clips within one video frame from 0.17 to 0.48, and held-out sync accuracy from 0.245 to 0.645 on the FlashDot development split (Table 1). The tone F1 gain is modest; the larger held-out gain partly reflects that the two critics share features and model family. Figure 4 shows one development clip: the clip whose |lag| gain from re-ranking is the median over clips, so it shows a typical case rather than the best one.

[Paragraph: FlashDot test results for best-of-8 and self-training against random selection.]

On VAS (Table 2), the VQGAN reconstruction reaches FID 6.0 and MKL 1.03, matching the published codebook numbers (6.0 and 1.0), which checks our port of the evaluation. The pretrained SpecVQGAN transformer (top-k 100, one sample per clip) gives FID 27.8 and MKL 5.81 (published 25.4 and 5.9). Its timing is close to chance: envelope correlation 0.003, |lag| 502 ms, 5.6% of clips within one frame, and held-out sync accuracy 0.061 / 0.167 against chance levels of about 0.05 / 0.14. The ground truth itself reaches only 0.285 / 0.536 under the held-out critic, which bounds what that metric can show.

Keeping the best of four samples per clip by PAL improves the timing measures that follow the envelope: |lag| falls by 46 ms (95% interval 16 to 74 ms, $p = 0.002$, paired bootstrap over the 768 clips), envelope correlation rises from 0.003 to 0.015 ($p < 0.001$) and held-out sync accuracy at tolerance 1 from 0.167 to 0.375, at four times the sampling cost. Onset F1 (+0.008, $p = 0.10$) and the share of clips within one frame ($p = 0.41$) do not change significantly, and




Figure 3: Free-logit attack on four FlashDot critics (eight development clips). Optimizing logits against PAL (orange) reaches the PAL of the ground-truth codes (blue) for every critic, while tone F1 stays near or below that of random logits (grey). Coarser critics bring the envelope lag down, but none recovers the tone.

Table 2: VAS test results (768 clips of the SpecVQGAN `vas_valid` list), one sample per clip unless stated. Sync acc. is the held-out critic at tolerance 0 / 1 (chance ≈ 0.05 / 0.14). On.: onset; Env.: envelope correlation; |Lag| in ms; 1 fr.: share of clips with |lag| within one video frame. Fine-tuned rows train LoRA adapters with the same budget. Fine-tuned rows are single training runs (seed 0).

Model	On. F1 ↑	On. AP ↑	Env. ↑	|Lag| ↓	1 fr. ↑	Sync acc. ↑	FID ↓	MKL ↓
Ground truth	–	–	–	–	–	0.285 / 0.536	–	–
VQGAN reconstruction	0.813	0.778	0.918	0.2	100%	0.277 / 0.518	6.0	1.03
Pretrained SpecVQGAN	0.368	0.206	0.003	502	5.6%	0.061 / 0.167	27.8	5.81
best of 4	0.376	0.215	0.015	456	6.6%	0.151 / 0.375	26.7	5.92
GT-only fine-tune	0.346	0.188	0.006	481	5.3%	0.055 / 0.167	20.4	5.58
self-train, random	0.344	0.185	0.006	467	6.5%	0.060 / 0.165	25.1	5.95
self-train, PAL	0.347	0.186	0.004	488	6.5%	0.062 / 0.167	24.1	5.75

FID and MKL stay close to the single-sample values. The held-out gain is the largest, and it is the one most open to shared bias between the two critics (Section 7).

Self-training does not carry this gain into the generator. With the same LoRA budget (two rounds of 256 clips, four candidates, 150 steps each), self-training with PAL selection, self-training with random selection and fine-tuning on ground truth alone give the same timing: no two of the three differ significantly on any timing measure (all $p > 0.1$). For PAL against random selection, onset F1 differs by +0.003 ($p = 0.50$), |lag| by +22 ms ($p = 0.13$) and sync accuracy by +0.001 ($p = 0.98$). All three lower onset F1 by about 0.02 against the pretrained model ($p < 0.001$), and only random selection lowers |lag| significantly (−35 ms, $p = 0.01$). All three also lower FID, and ground-truth-only fine-tuning lowers it most (20.4, against 24.1 with PAL selection and 25.1 with random selection). On VAS the FID gain therefore comes from fine-tuning on in-domain audio, and at this budget PAL selection adds nothing measurable to timing or quality.

Binding window. Table 3 scores the same eight candidates per clip under different windows. Every window improves on a single sample by a similar amount, and the shape of the window matters little. On FlashDot the narrowest window ($\sigma = 0$, exact zero offset) puts more clips within one frame than $\sigma = 1$ (0.49 against 0.415, $p = 0.01$), while $\sigma = 1$ gives higher held-out sync accuracy at tolerance 1, the tolerance that window matches (0.68 against 0.58, $p < 0.001$); tone F1 does not differ ($p = 0.30$). On VAS, $\sigma = 0$ and $\sigma = 1$ do not differ significantly on any measure. Neither




Figure 4: One FlashDot development clip (the clip with the median |lag| gain from best-of-8 re-ranking). The bottom row marks when the tone is on. The PAL-trained model (teacher-forced PAL) adds tones that are not in the video; the corruption-trained CE model misses some tones; keeping the best of eight of its samples by PAL lines the onsets up more closely with the ground truth.

asymmetric window improves on the symmetric $\sigma = 1$ window on either dataset, and the window with a wide audio-late side ($\sigma = 0.5$, $\sigma_{\text{late}} = 2$) lowers held-out sync accuracy on both (FlashDot -0.065, $p = 0.008$; VAS -0.066, $p = 0.003$). The oracle rows show how far any PAL choice is from the best available candidate: on VAS, choosing by true lag puts 40% of clips within one frame, against 7 to 9% for every PAL window.

6 Discussion

The same frozen critic hurts timing as a loss and helps as a reward, and the two diagnostics locate the difference. A differentiable loss scores whatever the gradient path produces: under teacher forcing that is a prediction already aligned by its prefix, and with the prefix removed it is a point the generator can move toward freely, including spectrograms outside anything the critic was trained on. A reward on free-running samples scores only what the generator actually produces, so the critic works inside the region where its ranking means something, and the generator learns from real audio-like samples through ordinary cross-entropy. This matches what is known about optimizing learned rewards (Gao et al., 2023): the less freely the optimizer can move against the reward model, the more the reward keeps its meaning. For discrete-token V2A models, we recommend running the wrong-video probe and the free-logit attack before training against any critic, and using the critic to select samples. Our results give no support to the perceptual motivation for the window: scoring exact zero offset selects samples as well as any window we tried, and the asymmetric windows that follow the human tolerance for late audio bring no gain. We keep the window as a parameter of PAL rather than as a claim about perception.

Table 3: Candidate selection on the test split: every row chooses among the same 8 free-running samples per clip. FlashDot: corruption-trained CE generator, 200 clips, one generator seed. VAS: pretrained SpecVQGAN, 256 clips, one run; its FID uses these clips only and is not comparable with Table 2. σ: width of the binding window on the audio-early side, σ_{late} on the audio-late side (Equation (2)). Sync: held-out critic at tolerance 1. The oracle keeps the candidate with the best true tone F1 (FlashDot) or smallest |lag| (VAS).

	FlashDot			VAS			
Selection	Tone F1 ↑	1 fr. ↑	Sync ↑	1 fr. ↑	|Lag| ↓	Sync ↑	FID ↓
One sample	0.510	0.270	0.285	5.5%	525	0.164	37.0
Best of 8, $\sigma = 0$	0.539	0.490	0.580	7.0%	439	0.465	35.7
Best of 8, $\sigma = 0.5$	0.550	0.475	0.625	7.8%	432	0.465	35.9
Best of 8, $\sigma = 1$	0.549	0.415	0.680	7.4%	436	0.449	35.4
Best of 8, $\sigma = 2$	0.553	0.365	0.645	7.4%	425	0.426	35.7
Best of 8, $\sigma = 0.5$, $\sigma_{\text{late}} = 2$	0.549	0.340	0.615	7.8%	423	0.383	34.1
Best of 8, $\sigma = 2$, $\sigma_{\text{late}} = 0.5$	0.548	0.380	0.585	9.4%	422	0.426	35.2
Oracle (upper bound)	0.689	0.275	0.345	39.8%	97	0.227	34.2

7 Limitations

- **Base model.** SpecVQGAN is far from current V2A systems such as MMAudio (Cheng et al., 2025). Our results concern a codebook transformer with a frozen decoder; we make no claim about flow or diffusion models and no state-of-the-art comparison.
- **Scope of the negative result.** We show that PAL fails as a loss for this generator with straight-through decoding, teacher-forced or corrupted prefixes, and our critics. Other gradient estimators, critics trained on generated audio, or losses on free-running samples could behave differently.
- **Compute.** All training ran on one laptop GPU, so on VAS we fine-tune LoRA adapters rather than the full transformer, and self-training uses two rounds with few candidates per clip. Larger budgets could change the size of the effect in either direction.
- **Feature-based critics and evaluation.** The critics see precomputed visual features at about 21.5 frames per second, so one offset step is about 46 ms and finer errors are invisible to them. On VAS their development offset accuracy is only about 0.12. The held-out critic uses the same features and model family as the training critic, so it is not fully independent of it. We did not compute a score from a stronger synchronization model such as Synchformer (Iashin et al., 2024), which needs raw video frames rather than the precomputed features we have; such a score would be a more independent check.
- **Binding window.** The Gaussian window, symmetric or wider on the audio-late side, simplifies a human window whose width and shape vary with stimulus, task and observer (Stevenson et al., 2012; Takeshima, 2021); it is not fitted to human data.

References

Triantafyllos Afouras, Andrew Owens, Joon Son Chung, and Andrew Zisserman. Self-supervised learning of audio-visual objects from video. In *Computer Vision – ECCV 2020*, Lecture Notes in Computer Science, pages 208–224. Springer, 2020. doi: 10.1007/978-3-030-58523-5_13.

Thomas Anthony, Zheng Tian, and David Barber. Thinking fast and slow with deep learning and tree search. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 5360–5370, 2017.

Relja Arandjelović and Andrew Zisserman. Objects that sound. In *Computer Vision – ECCV 2018*, Lecture Notes in Computer Science, pages 451–466. Springer, 2018. doi: 10.1007/978-3-030-01246-5_27.

Samy Bengio, Oriol Vinyals, Navdeep Jaitly, and Noam Shazeer. Scheduled sampling for sequence prediction with recurrent neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 1171–1179, 2015.

Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation, 2013. URL https://arxiv.org/abs/1308.3432.

Nolan Chan, Timmy Gang, Yongqian Wang, Yuzhe Liang, and Dingdong Wang. V2A-DPO: Omni-preference optimization for video-to-audio generation. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2026. URL https://arxiv.org/abs/2603.11089.

Peihao Chen, Yang Zhang, Mingkui Tan, Hongdong Xiao, Deng Huang, and Chuang Gan. Generating visually aligned sound from videos. *IEEE Transactions on Image Processing*, 29:8292–8302, 2020. doi: 10.1109/TIP.2020.3009820.

Xuanjun Chen, Haibin Wu, Chung-Che Wang, Hung-yi Lee, and Jyh-Shing Roger Jang. Multimodal transformer distillation for audio-visual synchronization. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 7755–7759, 2024. doi: 10.1109/ICASSP48485.2024.10446372.

Ho Kei Cheng, Masato Ishii, Akio Hayakawa, Takashi Shibuya, Alexander Schwing, and Yuki Mitsufuji. MMAudio: Taming multimodal joint training for high-quality video-to-audio synthesis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 28901–28911, 2025. doi: 10.1109/CVPR52734.2025.02691.

Xin Cheng, Xihua Wang, Ying Ba, Yuyue Wang, Kaisi Guan, Yinbo Wang, Wenpu Li, and Ruihua Song. SyncDPO: Enhancing temporal synchronization in video-audio joint generation via preference learning, 2026. URL https://arxiv.org/abs/2605.12179.

Joon Son Chung and Andrew Zisserman. Out of time: Automated lip sync in the wild. In *Computer Vision – ACCV 2016 Workshops*, volume 10117 of *Lecture Notes in Computer Science*, pages 251–263. Springer, 2017. doi: 10.1007/978-3-319-54427-4_19.

Soo-Whan Chung, Joon Son Chung, and Hong-Goo Kang. Perfect match: Improved cross-modal embeddings for audio-visual synchronisation. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3965–3969, 2019. doi: 10.1109/ICASSP.2019.8682524.

Marco Comunità, Riccardo F. Gramaccioni, Emilian Postolache, Emanuele Rodolà, Danilo Comminiello, and Joshua D. Reiss. SyncFusion: Multimodal onset-synchronized video-to-audio foley synthesis. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 936–940, 2024. doi: 10.1109/ICASSP48485.2024.10447063.

N. F. Dixon and L. Spitz. The detection of auditory visual desynchrony. *Perception*, 9(6):719–721, 1980. doi: 10.1068/p090719.

Yuexi Du, Ziyang Chen, Justin Salamon, Bryan Russell, and Andrew Owens. Conditional generation of audio from video via foley analogies. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2426–2436, 2023. doi: 10.1109/CVPR52729.2023.00240.

Patrick Esser, Robin Rombach, and Björn Ommer. Taming transformers for high-resolution image synthesis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 12868–12878, 2021. doi: 10.1109/CVPR46437.2021.01268.

Waka Fujisaki, Shinsuke Shimojo, Makio Kashino, and Shin'ya Nishida. Recalibration of audiovisual simultaneity. *Nature Neuroscience*, 7(7):773–778, 2004. doi: 10.1038/nn1268.

Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 202 of *PMLR*, pages 10835–10866, 2023.

Caglar Gulcehre, Tom Le Paine, Srivatsan Srinivasan, Ksenia Konyushkova, Lotte Weerts, Abhishek Sharma, Aditya Siddhant, Alex Ahern, Miaosen Wang, Chenjie Gu, Wolfgang Macherey, Arnaud Doucet, Orhan Firat, and Nando de Freitas. Reinforced self-training (ReST) for language modeling, 2023. URL https://arxiv.org/abs/2308.08998.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016. doi: 10.1109/CVPR.2016.90.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022. URL https://openreview.net/forum?id=nZeVKeeFYf9.

Vladimir Iashin and Esa Rahtu. Taming visually guided sound generation. In *British Machine Vision Conference (BMVC)*, 2021. URL https://arxiv.org/abs/2110.08791.

Vladimir Iashin, Weidi Xie, Esa Rahtu, and Andrew Zisserman. Sparse in space and time: Audio-visual synchronisation with trainable selectors. In *British Machine Vision Conference (BMVC)*, 2022. URL https://arxiv.org/abs/2210.07055.

Vladimir Iashin, Weidi Xie, Esa Rahtu, and Andrew Zisserman. Synchformer: Efficient synchronization from sparse cues. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 5325–5329, 2024. doi: 10.1109/ICASSP48485.2024.10448489.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *Proceedings of the 32nd International Conference on Machine Learning (ICML)*, volume 37 of *PMLR*, pages 448–456, 2015.

Yujin Jeong, Yunji Kim, Sanghyuk Chun, and Jiyoung Lee. Read, watch and scream! sound generation from text and video. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 17590–17598, 2025. doi: 10.1609/aaai.v39i17.33934.

Venkatesh Shenoy Kadandale, Juan F. Montesinos, and Gloria Haro. VocaLiST: An audio-visual synchronisation model for lips and voices. In *Interspeech*, pages 3128–3132, 2022. doi: 10.21437/Interspeech.2022-10861.

Minsu Kim, Joanna Hong, and Yong Man Ro. Lip to speech synthesis with visual context attentional GAN. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 34, pages 2758–2770, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/16437d40c29a1a7b1e78143c9c38f289-Abstract.html.

Chunyu Li, Chao Zhang, Weikai Xu, Jingyu Lin, Jinghui Xie, Weiguo Feng, Bingyue Peng, Cunjian Chen, and Weiwei Xing. LatentSync: Taming audio-conditioned latent diffusion models for lip sync with SyncNet supervision, 2024. URL https://arxiv.org/abs/2412.09262.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations (ICLR)*, 2019. URL https://arxiv.org/abs/1711.05101.

Simian Luo, Chuanhao Yan, Chenxu Hu, and Hang Zhao. Diff-Foley: Synchronized video-to-audio synthesis with latent diffusion models. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 36, pages 48855–48876, 2023. doi: 10.52202/075280-2121.

Xinhao Mei, Varun Nagaraja, Gael Le Lan, Zhaoheng Ni, Ernie Chang, Yangyang Shi, and Vikas Chandra. FoleyGen: Visually-guided audio generation. In *IEEE 34th International Workshop on Machine Learning for Signal Processing (MLSP)*, 2024. doi: 10.1109/MLSP58920.2024.10734721.

Shentong Mo and Yibing Song. Foley-Flow: Coordinated video-to-audio generation with masked audio-visual alignment and dynamic conditional flows. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 28912–28921, 2025. doi: 10.1109/CVPR52734.2025.02692.

Zhe Niu and Brian Mak. On the audio-visual synchronization for lip-to-speech synthesis. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 7809–7818, 2023. doi: 10.1109/ICCV51070.2023.00721.

Andrew Owens and Alexei A. Efros. Audio-visual scene analysis with self-supervised multisensory features. In *Computer Vision – ECCV 2018*, Lecture Notes in Computer Science, pages 639–658. Springer, 2018. doi: 10.1007/978-3-030-01231-1_39.

Andrew Owens, Phillip Isola, Josh McDermott, Antonio Torralba, Edward H. Adelson, and William T. Freeman. Visually indicated sounds. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2405–2413, 2016. doi: 10.1109/CVPR.2016.264.

K R Prajwal, Rudrabha Mukhopadhyay, Vinay P. Namboodiri, and C. V. Jawahar. A lip sync expert is all you need for speech to lip generation in the wild. In *Proceedings of the 28th ACM International Conference on Multimedia (MM)*, pages 484–492, 2020. doi: 10.1145/3394171.3413532.

Colin Raffel, Brian McFee, Eric J. Humphrey, Justin Salamon, Oriol Nieto, Dawen Liang, and Daniel P. W. Ellis. mir_eval: A transparent implementation of common MIR metrics. In *Proceedings of the 15th International Society for Music Information Retrieval Conference (ISMIR)*, pages 367–372, 2014.

Marc'Aurelio Ranzato, Sumit Chopra, Michael Auli, and Wojciech Zaremba. Sequence level training with recurrent neural networks. In *International Conference on Learning Representations (ICLR)*, 2016. URL https://arxiv.org/abs/1511.06732.

Stan Salvador and Philip Chan. Toward accurate dynamic time warping in linear time and space. *Intelligent Data Analysis*, 11(5):561–580, 2007. doi: 10.3233/IDA-2007-11508.

Roy Sheffer and Yossi Adi. I hear your true colors: Image guided audio generation. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2023. doi: 10.1109/ICASSP49357.2023.10096023.

Ryan A. Stevenson, Raquel K. Zemtsov, and Mark T. Wallace. Individual differences in the multisensory temporal binding window predict susceptibility to audiovisual illusions. *Journal of Experimental Psychology: Human Perception and Performance*, 38(6):1517–1529, 2012. doi: 10.1037/a0027339.

Yasuhiro Takeshima. Visual field differences in temporal synchrony processing for audio-visual stimuli. *PLoS ONE*, 16(12):e0261129, 2021. doi: 10.1371/journal.pone.0261129.

Tri Ton, Ji Woo Hong, and Chang D. Yoo. TARO: Timestep-adaptive representation alignment with onset-aware conditioning for synchronized video-to-audio synthesis. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 14228–14237, 2025. doi: 10.1109/ICCV51701.2025.01320.

Virginie van Wassenhove, Ken W. Grant, and David Poeppel. Temporal window of integration in auditory-visual speech perception. *Neuropsychologia*, 45(3):598–607, 2007. doi: 10.1016/j.neuropsychologia.2006.01.001.

Ilpo Viertola, Vladimir Iashin, and Esa Rahtu. Temporally aligned audio for video with autoregression. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2025. doi: 10.1109/ICASSP49660.2025.10890587.

Jean Vroomen and Mirjam Keetels. Perception of intersensory synchrony: A tutorial review. *Attention, Perception, & Psychophysics*, 72(4):871–884, 2010. doi: 10.3758/APP.72.4.871.

Mark T. Wallace and Ryan A. Stevenson. The construct of the multisensory temporal binding window and its dysregulation in developmental disabilities. *Neuropsychologia*, 64:105–123, 2014. doi: 10.1016/j.neuropsychologia.2014.08.005.

Heng Wang, Jianbo Ma, Santiago Pascual, Richard Cartwright, and Weidong Cai. V2A-Mapper: A lightweight solution for vision-to-audio generation by connecting foundation models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 15492–15501, 2024a. doi: 10.1609/aaai.v38i14.29475.

Shiguang Wang, Zhizhong Li, Yue Zhao, Yuanjun Xiong, Limin Wang, and Dahua Lin. denseflow. https://github.com/open-mmlab/denseflow, 2020. Software.

Xihua Wang, Yuyue Wang, Yihan Wu, Ruihua Song, Xu Tan, Zehua Chen, Hongteng Xu, and Guodong Sui. TiVA: Time-aligned video-to-audio generation. In *Proceedings of the 32nd ACM International Conference on Multimedia (MM)*, pages 573–582, 2024b. doi: 10.1145/3664647.3681027.

Yongqi Wang, Wenxiang Guo, Rongjie Huang, Jiawei Huang, Zehan Wang, Fuming You, Ruiqi Li, and Zhou Zhao. Frieren: Efficient video-to-audio generation network with rectified flow matching. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 37, pages 128118–128138, 2024c. doi: 10.52202/079017-4068.

Yazhou Xing, Yingqing He, Zeyue Tian, Xintao Wang, and Qifeng Chen. Seeing and hearing: Open-domain visual-audio generation with diffusion latent aligners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7151–7161, 2024. doi: 10.1109/CVPR52733.2024.00683.

Yiming Zhang, Yicheng Gu, Yanhong Zeng, Zhening Xing, Yuancheng Wang, Zhizheng Wu, Bin Liu, and Kai Chen. FoleyCrafter: Bring silent videos to life with lifelike and synchronized sounds. *International Journal of Computer Vision*, 2026. doi: 10.1007/s11263-025-02649-3. arXiv:2407.01494 (2024).

Yipin Zhou, Zhaowen Wang, Chen Fang, Trung Bui, and Tamara L. Berg. Visual to sound: Generating natural sound for videos in the wild. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3550–3558, 2018. doi: 10.1109/CVPR.2018.00374.

A Relation to an earlier draft

An unpublished 2023 draft of this work reported results for an earlier implementation of the alignment loss. In that implementation the loss could not influence the generator: the predicted spectrogram was decoded from the argmax of the transformer's logits inside a function that ran without gradient tracking, so no gradient reached the transformer, and the only parameters the loss touched, those of its two feature extractors, were not in the optimizer. All numbers in that draft are superseded by this paper. The experiments reported here were rerun with a new implementation in which the gradient does reach the transformer (Section 3.4); with that path in place, the loss the draft intended does not improve timing (Section 5.2).

B FlashDot example and metric check values




Figure 5: A FlashDot clip: ground-truth spectrogram, its VQGAN reconstruction with the public VAS codebook, and the tone label. The reconstruction keeps the timing (tone F1 0.970 over the development split) and adds codebook texture, so it bounds what any code model with this decoder can reach.

Table 4: Response of candidate metrics to known delays, mean over 200 FlashDot development clips. Arrows give the direction of a better score.

Comparison	DTW ↓	Mel L1 ↓	Onset F1 ↑	Env. corr. ↑	|Lag| (ms) ↓
Delay 0 ms	0	0.000	1.00	1.00	0
Delay 23 ms	69	0.032	1.00	0.75	23
Delay 46 ms	138	0.035	1.00	0.32	46
Delay 93 ms	271	0.036	1.00	0.01	93
Delay 186 ms	527	0.040	0.05	0.02	186
Delay 372 ms	1034	0.045	0.13	−0.01	372
Delay 743 ms	1968	0.052	0.14	−0.04	743
Other clip	10582	0.054	0.14	0.01	470

C Hyperparameters

Table 5: Hyperparameters. Values are those of the reported runs; red entries are not yet fixed.

Component	Setting	Value
Training critic	encoder blocks / kernel / channels	2 / 5 / 256
	embedding dimension, normalization	128, L2 per frame
	group norm groups, mel pooling	8, ×4
Held-out critic	blocks / kernel / channels, seed	3 / 3 / 384, 1
	audio input (FlashDot / VAS)	mel / 8 bands
Stage 1	K, τ, σ	10, 0.1, 0
	S (FlashDot / VAS)	4 / 8
	reduction	$-\frac{1}{S}\sum_s \log W_s$
	probability of ground-truth audio	0.3
	optimizer	AdamW, lr 10^{-3}, wd 10^{-4}
	steps (FlashDot / VAS), batch	2000 / 3000, 32
	selection	lowest dev loss
PAL as a loss (FlashDot)	K, S, τ, σ	8, 4, 0.1, 1
	reduction	$-\log \frac{1}{S}\sum_s W_s$
	decoding	straight-through
	window columns c, margin m	12, 1
	examples with PAL per batch	4 of 8
	PAL weight β	1
	p_{keep} (CE pass), $p^{\text{PAL}}_{\text{keep}}$	$\{1, 0.5\}$, $\{1, 0.5, 0\}$
	optimizer	AdamW, lr 3×10^{-4}, $\beta = (0.9, 0.95)$, wd 0.01
	schedule, gradient clipping	200 warm-up steps, cosine decay; 1.0
	steps, batch	2000 (3000 teacher-forced PAL), 8
FlashDot GPT	layers / width / heads	6 / 384 / 6
Self-training	rounds, steps per round	2, 300 (FlashDot) / 150 (VAS)
	clips per round, candidates N	400, 8 (FlashDot) / 256, 4 (VAS)
	batch, ground-truth share	8 (FlashDot) / 4 (VAS), 0.5
	trained parameters	all (FlashDot) / LoRA $r = 16$, $\alpha = 16$ (VAS)
	initialization	CE, corrupted prefix (FlashDot) / public model (VAS)
	optimizer	AdamW, lr 10^{-4}, $\beta = (0.9, 0.95)$, wd 0.01
	candidate scoring	training critic, $\sigma = 1$
Sampling	top-k, temperature	100, 1.0
	re-ranking samples N (FlashDot / VAS)	8 / 4
Seeds	FlashDot / VAS	3 (test) / 1

D VAS sample




Figure 6: One VAS test clip (the clip with the median |lag| gain from best-of-4 re-ranking). Its |lag| is 116 ms for the single sample and 81 ms for the best of four. VAS audio is dense, and timing differences of this size are hard to see in a spectrogram, which is why we report onset and envelope measures.