XorMon Public API (1.0.0)

Download OpenAPI specification: Download

This is a public API to demonstrate features of XorMon API

Authorization
API requests require authorization header with a valid Public API Key
You can create a Public API Key in XorMon UI or create a temporary Public API Key with `/api/public/v1/auth` API.

Auth request
POST `https://{host}/api/public/v1/auth`

```
{
  "username": "xormon",
  "password": "xormon"
}
```

Response:

```
{
  "statusCode":200,
  "data": {
    "apiKey":"3b766bcdb5e6afd1bdde2eaf13a5a5b0",
    "expiration":"2023-07-26T07:43:53.763Z"
  }
}
```

Public API Key in other requests
GET `https://{host}/api/public/v1/architecture/classes`
Header: `'apiKey: 3b766bcdb5e6afd1bdde2eaf13a5a5b0'`

Auth

Public API Key generation

Generates API based on username and password

REQUEST BODY SCHEMA: application/json
required

`username` required	string
`password` required	string

Responses

> **201** Public API Key

> **400** Error

> **401** Unauthorized

POST /api/public/v1/auth

Request samples

Payload

Content type
application/json

Copy

```
{
    "username": "string",
    "password": "string"
}
```

Response samples

201 400 401

Content type
application/json

Copy Expand all Collapse all


```
{
    "statusCode": 0,
    "message": "string",
    "error": "string",
  - "data": {
        "apiKey": "string",
        "expiration": "string"
    }
}
```

ACL

Fetches rules

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

`group_id` required	number Example: `2` The group ID

QUERY PARAMETERS

`rule_id`	Array of strings Example: `rule_id=123e4567-e89b-12d3-a456-426614174000` rules to fetch

Responses

> **200** Rules has been successfully fetched

GET /api/public/v1/acl/rules/{group_id}

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
    "error": "string",
    "message": "string",
    "statusCode": 0
}
```

Creates or updates a rule and returns it

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

group_id required	number Example: 2 The group ID

REQUEST BODY SCHEMA: application/json
required

Rule definition. `class`, `hwType` and `itemId` may be used on their own. `subsystem` must be used with `hwType`. `classes`, `hwTypes` and `itemIds` are shorthands for multiple rules. They may appear

in combination (eg. `classes` and `hwTypes` in the same object). Multiple-rule shorthands and single rule definition may not be mixed.

One of ACLRuleDTO ACLRuleDTO

Array [

class	string or null The allowed class
classes	Array of any or null The allowed classes
hwType	string or null The allowed hardware type
hwTypes	Array of any or null The allowed hardware types
itemId	string or null The allowed item
itemIds	Array of any or null The allowed items
rule_id	string or null <uuid> The UUID of the existing rule
subsystem	string or null The allowed subsystem (hwType must be also present)

]

Responses

200

- Rule has been successfully created or updated
- Rule already exists

201

400 Invalid rule syntax

> **422** Attempting to update a non-existent rule or rule target doesn't exist

POST /api/public/v1/acl/rules/{group_id}

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all


```
{
    "class": "virtualization",
  - "classes": [
        "virtualization",
        "san"
    ],
    "hwType": "vmware",
  - "hwTypes": [
        "vmware",
        "proxmox"
    ],
    "itemId": "3FC43EEA-4489-40FB-8BDD-4FD4FA53BF3D",
  - "itemIds": [
        "A1B2C3D4-E5F6-7A8B-9C0D-E1F2G3H4I5J6",
        "1A2B3C4D-5E6F-7A8B-9C0D-E1F2G3H4I5J6"
    ],
    "rule_id": "123e4567-e89b-12d3-a456-426614174000",
    "subsystem": "vm"
}
```


Response samples

200 201 400 422

Content type
application/json

Copy Expand all Collapse all


```
{
  - "data": [
      + { … }
    ],
    "error": "string",
    "message": "string",
    "statusCode": 0
}
```

Deletes rules and returns them

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

group_id required	number Example: 2 The group ID

REQUEST BODY SCHEMA: application/json
required

rule_id > required	Array of strings or string The UUID(s) of the existing rule(s)

Responses

> **200** Rules have been successfully deleted

DELETE /api/public/v1/acl/rules/{group_id}

Request samples

Payload

Content type
application/json

Copy

```
{
    "rule_id": "123e4567-e89b-12d3-a456-426614174000"
}
```

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
    "error": "string",
    "message": "string",
    "statusCode": 0
}
```

Alias

Fetches all items with aliases

Responses

> **200** List of items with aliases

> **400** Error

> **401** Unauthorized

GET /api/public/v1/alias

https://192.168.1.103/api/public/v1/alias

200 400 401

Content type
application/json

Copy Expand all Collapse all


```
{
    "statusCode": 200,
  - "data": [
      - {
            "item_id": "string",
            "label": "string",
            "alias": "string"
        }
    ]
}
```


Creates or updates aliases for items

REQUEST BODY SCHEMA: application/json
required

List of alias definitions
Array [

item_id required	string
alias required	string

]

Responses

> **201** Aliases created

> **400** Error

> **401** Unauthorized

POST /api/public/v1/alias

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
      "item_id": "string",
      "alias": "string"
    }
]
```

Response samples

201 **400** **401**

Content type
application/json

Copy Expand all Collapse all

```
{
    "statusCode": 201,
  - "data": [
      + { … }
    ]
}
```

Deletes aliases by item IDs

REQUEST BODY SCHEMA: application/json
required

Array of item IDs whose aliases should be deleted
Array [
  string
]

Responses

> **200** Aliases successfully deleted

> **400** An error occurred while deleting aliases

> **401** Unauthorized

DELETE /api/public/v1/alias/multiple

Request samples

Payload

Content type
application/json

Copy

```
[
    "7C7E6AE1-3825-46DD-924E-606B75DF635A",
    "6D2E726A-8050-4E93-885A-4E7FA6F9C03B"
]
```

Response samples

200 400 401

Content type
application/json

Copy

```
{
    "statusCode": 200,
    "message": "string"
}
```

Architecture

List of all classes

Returns a list of all classes that are needed for further filtering of hw_types

AUTHORIZATIONS: > *apiKey*

Responses

> **200** List of all classes

> **400** Error

> **401** Unauthorized

GET /api/public/v1/architecture/classes

https://192.168.1.103/api/public/v1/architecture/classes

200 400 401

Content type
application/json

Copy Expand all Collapse all


```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

List of hw_types

Returns a list of hw_types under the specified class, which are then needed for further subsystem filtering

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

class required	string

QUERY PARAMETERS

list_models	boolean If true list hw_types with matching system models.

Responses

> **200** List of hw_types under the given class

> **400** Error

> **401** Unauthorized

GET /api/public/v1/architecture/class/{class}/hw_types

https://192.168.1.103/api/public/v1/architecture/class/{class}/hw_types

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

List of subsystems

Returns a list of subsystems that are further needed for filtering items and metrics

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

class required	string
hw_type required	string

Responses

> **200** List of subsystems

> **400** Error

> **401** Unauthorized

GET /api/public/v1/architecture/class/{class}/hw_type/{hw_type}/subsyste…

https://192.168.1.103/api/public/v1/architecture/class/{class}/hw_type/{hw_type}/subsystems

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
```

```
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

List of metrics

Returns a list of metrics that are used to export timeseries data

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

class required	string
hw_type required	string
subsystem required	string

Responses

> **200** List of metrics

> **400** Error

> **401** Unauthorized

GET /api/public/v1/architecture/class/{class}/hw_type/{hw_type}/subsyste…

https://192.168.1.103/api/public/v1/architecture/class/{class}/hw_type/{hw_type}/subsystem/{subsystem}/metrics

Content type
application/json

Copy Expand all Collapse all


```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```


List of items

Returns a list of items that are used to export timeseries data

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

class required	string
hw_type required	string
subsystem required	string

Responses

> **200** List of metrics

> **400** Error

> **401** Unauthorized

GET /api/public/v1/architecture/class/{class}/hw_type/{hw_type}/subsyste…

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

List of properties

Returns a list of properties that are used to export configuration data

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

class required	string
hw_type required	string
subsystem required	string

Responses

> **200** List of properties

> **400** Error

> **401** Unauthorized

GET /api/public/v1/architecture/class/{class}/hw_type/{hw_type}/subsyste…

https://192.168.1.103/api/public/v1/architecture/class/{class}/hw_type/{hw_type}/subsystem/{subsystem}/properties

Content type
application/json

Copy Expand all Collapse all


```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```


Item searching

Searching for items based on parameters: hw_type, subsystem, label. The number of records returned and the page number can be defined.

AUTHORIZATIONS: > *apiKey*

QUERY PARAMETERS

subsystem	string
hw_type	string
class	string
parents	string Example: `parents=id1,id2,id3` Comma separated list of parent item ids
search	string
page	number Page indexing starts at 0
limit	number

Responses

> **200** Item searching

> **400** Error

> **401** Unauthorized

GET /api/public/v1/architecture/search

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all


```
{
  - "data": {
      + "metadata": { … },
      + "items": [ … ]
    },
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

List of all devices (root level items)

Returns a list of all devices - root items. (Server at Powers, vCenter at VMware, Device at storages)

AUTHORIZATIONS:

apiKey

API Key: apiKey

Header parameter name: `apiKey`

Responses

200 List of all devices

RESPONSE SCHEMA: application/json

data required	Array of objects (Item)

Array [

item_id required	string

label required	string
hw_type	string
subsystem	string
subsystem_detail >	object (Subsystem)
parents >	Array of objects (_ItemProxy)

]

statusCode	number
message	string
error	string

> **400** Error

> **401** Unauthorized

GET /api/public/v1/architecture/devices

https://192.168.1.103/api/public/v1/architecture/devices

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
```

```
}
```

Audit

Get audit items by time range

Returns a list of audit items between `start` and `end` timestamps.

QUERY PARAMETERS

`start` required	integer Start timestamp (seconds since epoch)
`end` required	integer End timestamp (seconds since epoch)

Responses

- **200** Successful response with audit items
- **400** Error
- **401** Unauthorized

```
GET /api/public/v1/audit
```

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all


```
{
    "statusCode": 0,
  - "data": [
      + { … }
    ]
}
```

Certificate

Get current certificate info

Returns full paths to certificate files and expiration date.

Responses

- **200** Current certificate info
- **401** Unauthorized
- **404** Certificate not found
- **500** Unable to read certificate

GET /api/public/v1/certificate

Response samples

200 401 404 500

Content type
application/json

Copy Expand all Collapse all


```
{
    "statusCode": 200,
  - "data": {
        "crtFile": "/home/xormon/nextgen/server-nest/files/cert/xormon.crt",
        "keyFile": "/home/xormon/nextgen/server-nest/files/cert/xormon.key",
        "expiresAt": "2026-04-01T12:00:00.000Z"
    }
}
```

Upload SSL certificate and private key

Uploads a certificate (`.crt`) and private key (`.key`) in multipart/form-data format. Certificates must be valid and match the private key.

REQUEST BODY SCHEMA: multipart/form-data
required

crt required	string <binary> Public X.509 certificate (.crt)
key required	string <binary> Private key file (.key)

Responses

> **201** Certificate uploaded successfully

> **400** Error

> **401** Unauthorized

POST /api/public/v1/certificate

Response samples

201 400 401

Content type
application/json

Copy

```
{
    "statusCode": 201,
    "message": "Certificate successfully uploaded"
}
```

CMDB

List of all CMDB types

Returns a list of all CMDB types that are needed for getting lists of CMDB specific tables

AUTHORIZATIONS: > *apiKey*

Responses

> **200** List of all CMDB types

> **400** Error

> **401** Unauthorized

GET /api/public/v1/cmdb/types

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
        "string"
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

List of CMDB tables

Returns a list of CMDB tables under the specified CMDB type, which are then needed for further data export

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

cmdb_type required	string

Responses

> **200** List of CMDB tables under the given CMDB type

> **400** Error

> **401** Unauthorized

GET /api/public/v1/cmdb/tables/{cmdb_type}

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
        "string"
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Export CMDB table

Returns CMDB table data in csv format. (The export is in base values, no transformations are applied like in GUI, eg. data is in bytes and not in GBs and so on. If you are confused, just check the table in GUI)

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

cmdb_type required	string
cmdb_table required	string

Responses

> **201** Export CMDB data

> **400** Error

> **401** Unauthorized

GET /api/public/v1/cmdb/table/{cmdb_type}/{cmdb_table}

Response samples

201 400 401

Content type
application/json

Copy

```
{
    "data": "string",
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Exporter

List of exports

Returns a list of exports created from the GUI

AUTHORIZATIONS: > *apiKey*

Responses

> **200** List of exports

> **400** Error

> **401** Unauthorized

GET /api/public/v1/exporter/exports

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Export

Returns the export result

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

`export_id` required	string

Responses

> **200** Export result

> **400** Error

> **401** Unauthorized

GET /api/public/v1/exporter/export/{export_id}

Response samples

200 400 401

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Export data

Returns data export based on set parameters

AUTHORIZATIONS: > *apiKey*

REQUEST BODY SCHEMA: application/json
required

start required	number Time in UNIX millisecond format
end required	number Time in UNIX millisecond format
metric required	Array of strings
uuids required	Array of strings
format	string Default: `"json"` Enum: `"csv"` `"json"` `"xlsx"`

Responses

> **201** Export data

> **400** Error

> **401** Unauthorized

POST /api/public/v1/exporter/timeseries

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
    "start": 0,
    "end": 0,
  - "metric": [
        "string"
    ],
  - "uuids": [
        "string"
    ],
    "format": "csv"
}
```

Response samples

201 **400** **401**

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
```

```
}
```

Export data Aggregated

Returns aggregated data export based on set parameters, specify start and end to get specific range or get last range interval by specifying valuesInterval

AUTHORIZATIONS: > *apiKey*

REQUEST BODY SCHEMA: application/json
required

`metric` required	Array of strings
`uuids` required	Array of strings
`values` required	string Enum: `"avg"` `"max"` `"last"`
`format`	string Default: `"json"` Enum: `"csv"` `"json"` `"xlsx"`
`valuesInterval`	string Enum: `"lastHour"` `"lastDay"` `"lastWeek"` `"lastMonth"` `"lastYear"`
`start`	number Time in UNIX millisecond format
`end`	number Time in UNIX millisecond format

Responses

> **201** Export data

> **400** Error

> **401** Unauthorized

POST /api/public/v1/exporter/timeseries/aggregate

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "metric": [
        "string"
    ],
  - "uuids": [
        "string"
    ],
    "values": "avg",
    "format": "csv",
    "valuesInterval": "lastHour",
    "start": 0,
    "end": 0
}
```

Response samples

201 **400** **401**

Content type
application/json

Copy

```
{
    "statusCode": 0,
```

```
    "message": "string",
    "error": "string"
}
```

Export mapping

Exports the mapping for the given uuids

AUTHORIZATIONS: > *apiKey*

REQUEST BODY SCHEMA: application/json
required

`uuids` required	Array of strings
`format`	string Default: `"json"` Enum: `"csv"` `"json"` `"xlsx"`

Responses

> **200** Export mapping success

> **400** Error

> **401** Unauthorized

POST `/api/public/v1/exporter/mapping`

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "uuids": [
        "string"
    ],
    "format": "csv"
}
```

Response samples

200 400 401

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Export configuration

Exports the configuration for the given uuids of device, volume or host. Storage-only feature

AUTHORIZATIONS: > *apiKey*

REQUEST BODY SCHEMA: application/json
required

uuids required	Array of strings
properties	Array of strings List of properties to export. If left empty, all properties are exported

`format`	string Default: `"json"` Enum: `"csv"` `"json"` `"xlsx"`

Responses

> **200** Export configuration success

> **400** Error

> **401** Unauthorized

POST /api/public/v1/exporter/configuration

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "uuids": [
        "string"
    ],
  - "properties": [
        "string"
    ],
    "format": "csv"
}
```

Response samples

200 **400** **401**

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Export capacity

Exports the capacity for the given uuids or subsystem. Storage-only feature

AUTHORIZATIONS: > *apiKey*

REQUEST BODY SCHEMA: application/json
required

`uuids`	Array of strings
`subsystem`	string
`format`	string Default: `"json"` Enum: `"csv"` `"json"` `"xlsx"`

Responses

> **200** Export capacity success

> **400** Error

> **401** Unauthorized

POST /api/public/v1/exporter/capacity

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "uuids": [
        "string"
    ],
    "subsystem": "pool",
    "format": "csv"
}
```

Response samples

200 **400** **401**

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Device configuration

List all host configurations

Returns a list of all device (hostcfg) configurations

AUTHORIZATIONS: > *apiKey*

QUERY PARAMETERS

`class`	string Class type for devices ex. storage
`hw_type`	string Hw type for devices ex. swiz

Responses

> **200** List of host configurations

> **400** Error

> **401** Unauthorized

> **403** Forbidden

GET /api/public/v1/hostcfg

Response samples

200 400 401 403

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```


Add host configurations

Add a new device (host configuration)

AUTHORIZATIONS: > *apiKey*

REQUEST BODY SCHEMA: application/json
required

`label`	string Custom name assigned to the device and displayed throughout the user interface.
`hw_type`	string Device type or model. See Architecture APIs: List of all classes and List of hw_types for available values.
`disabled`	boolean Device disabled for monitoring if set to "true".
`ignore_health_status`	boolean Device health status is not reported.
`ignore_health_status_reason`	string or null Reason for ignoring device health status.
`data`	object Settings specific to the selected HW type. See "List host configuration data properties for specific technology" or "List host configuration data properties for specific device type"

Responses

> **200** Added host configuration

> **400** Error

> **401** Unauthorized

> **403** Forbidden

POST /api/public/v1/hostcfg

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
    "label": "string",
    "hw_type": "string",
    "disabled": true,
    "ignore_health_status": true,
    "ignore_health_status_reason": "string",
    "data": { }
}
```

Response samples

200 **400** **401** **403**

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
        "hostcfg_id": "string",
        "label": "string",
        "hw_type": "string",
        "disabled": true,
        "target": true,
        "ignore_health_status": true,
        "ignore_health_status_reason": "string",
        "data": { },
        "hw_type_label": "string",
        "limited": true
    },
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Update host configurations

Update device (host configuration)

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

`hostcfg_id` required	string

REQUEST BODY SCHEMA: application/json
optional

`label`	string Custom name assigned to the device and displayed throughout the user interface.
`disabled`	boolean Device disabled for monitoring if set to "true".

`ignore_health_status`	boolean Device health status is not reported.
`ignore_health_status_reason`	string or null Reason for ignoring device health status.
`data`	object Settings specific to the selected HW type. See "List host configuration data properties for specific technology" or "List host configuration data properties for specific device type"

Responses

- **200** Successfuly updated host configuration
- **400** Error
- **401** Unauthorized
- **403** Forbidden

PUT /api/public/v1/hostcfg/{hostcfg_id}

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
    "label": "string",
    "disabled": true,
    "ignore_health_status": true,
    "ignore_health_status_reason": "string",
    "data": { }
```

```
}
```

Response samples

200 400 401 403

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Delete host configurations

Delete device (host configuration)

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

hostcfg_id required	string

Responses

> 200 Successfuly deleted host configuration

> 400 Error

> 401 Unauthorized

> **403** Forbidden

DELETE /api/public/v1/hostcfg/{hostcfg_id}

Response samples

200 400 401 403

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

List all host configurations data types

Returns a list of all device data property keys, what types they are and if they are required or not. This information is used when creating new hostconfigurations.

AUTHORIZATIONS: > *apiKey*

Responses

> **200** List of all host configuration data types

> **400** Error

> **401** Unauthorized

> **403** Forbidden

GET /api/public/v1/hostcfg/definitions

https://192.168.1.103/api/public/v1/hostcfg/definitions

200 400 401 403

Content type
application/json

Copy Expand all Collapse all


```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

List host configuration data properties for specific technology.

Returns definition of specific technology configuration data properties.

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

hw_type required	string

Responses

> **200** Technology data properties.

> **400** Error

> **401** Unauthorized

> **403** Forbidden

GET /api/public/v1/hostcfg/definitions/{hw_type}

https://192.168.1.103/api/public/v1/hostcfg/definitions/{hw_type}

200 400 401 403

Content type
application/json

Copy Expand all Collapse all


```
{
  - "data": {
      + "exampleDataKey": { … }
    },
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Health Status

Health status

Returns a list of health statuses

AUTHORIZATIONS: > *apiKey*

Responses

> **201** Health status data

> **400** Error

> **401** Unauthorized

GET /api/public/v1/health_status

Response samples

201 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string",
  - "data": [
      + { … }
    ]
}
```

Health status by severity

Returns a list of health statuses by severity

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

severity required	string Enum: `"error"` `"warning"` `"ok"` Example: `error`

Responses

> **201** Health status data

> **400** Error

> **401** Unauthorized

GET /api/public/v1/health_status/{severity}

Response samples

201 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string",
```

```
  - "data": [
      + { … }
    ]
}
```

Tags

List of all tags

Returns a list of all tags

AUTHORIZATIONS: > *apiKey*

Responses

> **200** List of all tags

> **400** Error

> **401** Unauthorized

GET /api/public/v1/tags

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ]
}
```

Create new tag

Create new tag

AUTHORIZATIONS: > *apiKey*

REQUEST BODY SCHEMA: application/json
required

One of object object

`label` required	string The label of the tag

Responses

> **201** New tag created

> **400** Error

> **401** Unauthorized

POST /api/public/v1/tags

Request samples

Payload

Content type
application/json

Example
Request with only label

Copy

```
{
    "label": "string"
}
```

Response samples

201 **400** **401**

Content type
application/json

Example
Response for only "label" provided

Copy Expand all Collapse all

```
{
    "statusCode": 201,
    "message": "Tag created successfully",
  - "data": {
        "tag_id": "string",
        "label": "string"
    }
}
```

Search items by tag and category

Retrieve items filtered by tag and category query parameters

AUTHORIZATIONS: > *apiKey*

QUERY PARAMETERS

`tag`	string Search items by tag
`category`	string Search items by category

Responses

> **200** List of items matching the query filters

> **400** Bad request

> **401** Unauthorized

GET /api/public/v1/tags/search-items

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
    "statusCode": 200,
  - "data": [
      + { … }
    ]
}
```

List of all items by tag id

Returns a list of all items by tag id

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

tag_id required	string

Responses

> **200** List of all items of a tag

> **401** Unauthorized

> **404** tag_id does not exist

GET /api/public/1/tags/{tag_id}/items

Response samples

200 401 404

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
        "tag_id": "string",
        "label": "string",
        "category": "string",
    + "items": [ … ]
    },
    "statusCode": 0,
    "error": "string",
    "message": "string"
```

```
}
```

List of all categories

Returns a list of all categories

AUTHORIZATIONS: > *apiKey*

Responses

> **200** List of all categories

> **400** Error

> **401** Unauthorized

GET /api/public/v1/tags/categories

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "message": "string",
    "error": "string"
```

```
}
```

Create new category

Creates new category with the specified label.

REQUEST BODY SCHEMA: application/json
required

`category_label` required	string The label of the category to be created

Responses

> **201** Tag category successfully created

> **400** Error

> **401** Unauthorized

POST `/api/public/v1/tags/categories`

Request samples

Payload

Content type
application/json

Copy

```
{
    "category_label": "string"
}
```

Response samples

201 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
    "statusCode": 0,
    "message": "string",
  - "data": {
        "category_id": "string",
        "category_label": "string"
    }
}
```

Add items to tag

Adds one or more items to a specified tag

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

tag_id required	string ID of the tag to which items will be added

REQUEST BODY SCHEMA: application/json
required

item_ids required	Array of strings Array of item IDs to be added to the tag

Responses

> **201** Items successfully added to the tag

> **400** Invalid input

> **401** Unauthorized

POST /api/public/v1/tags/{tag_id}/items

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "item_ids": [
        "string"
    ]
}
```

Response samples

201 **400** **401**

Content type
application/json

Copy Expand all Collapse all

```
{
    "tag_id": "string",
  - "item_ids": [
        "string"
    ]
}
```

Delete items from tag

Deletes specified items from a tag by its ID

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

`tag_id` required	string ID of the tag from which items will be deleted

REQUEST BODY SCHEMA: application/json
required

`item_ids` required	Array of strings Array of item IDs to be deleted from the tag

Responses

> **200** Items successfully deleted from the tag

> **204** No items were deleted

> **400** Tag or items not found

> **401** Unauthorized

DELETE /api/public/v1/tags/{tag_id}/items

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "item_ids": [
        "string"
    ]
}
```

Response samples

200 **204** **400** **401**

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Delete tag

Deletes a tag specified by its ID

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

tag_id required	string ID of the tag to be deleted

Responses

- **200** Tag successfully deleted
- **400** Invalid tag ID
- **401** Unauthorized
- **404** Tag not found

DELETE /api/public/v1/tags/{tag_id}

Response samples

200 400 401 404

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Delete tag category

Deletes tag category specified by its ID

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

`category_id` required	string ID of the tag category to be deleted

Responses

> **200** Tag category successfully deleted'

> **400** Invalid tag category ID

> **401** Unauthorized

> **404** Tag category not found

DELETE `/api/public/v1/tags/categories/{category_id}`

Response samples

200 | 400 | 401 | 404

Content type
application/json

Copy

```
{
    "statusCode": 0,
    "message": "string",
    "error": "string"
}
```

Alerting

Fetches all alerting configurations

Returns a list of all alerting configurations

AUTHORIZATIONS: > *apiKey*

Responses

> **200** List of alerting configurations

> **400** Error

> **401** Unauthorized

GET /api/public/v1/alerting/groups

Response samples

200 400 401

Content type
application/json

Copy Expand all Collapse all

```
{
    "message": "string",
  - "data": [
      + { … }
    ],
```

```
    "statusCode": 0,
    "error": "string"
}
```

Get alerts by group

Returns alerts for a specific alerting group

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

`alertingGroupId` required	string

Responses

> **200** Alerts fetched successfully

> **400** Error

> **401** Unauthorized

> **404** Alert group not found

GET `/api/public/v1/alerting/alerts/{alertingGroupId}`

Response samples

200 | 400 | 401 | 404

Content type
application/json

Copy Expand all Collapse all


```
{
    "message": "string",
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "error": "string"
}
```


Get alert status

Returns the status of a specific alert

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

alertId required	string

Responses

> **200** Alert status fetched successfully

> **400** Error

> **401** Unauthorized

> **404** Alert not found

GET /api/public/v1/alerting/alerts/status/{alertId}

Response samples

200 400 401 404

Content type
application/json

Copy Expand all Collapse all


```
{
    "message": "string",
  - "data": {
        "alerting_id": "047b7bc9-daae-4f26-a0fe-b7ddee6a1b9f",
        "alerting_group_id": "b65e7a82-e650-4894-8fd8-9863299cdd9f",
        "peak": null,
        "limit": 0,
        "repeat": null,
        "metric": "cpu_util",
        "isAlertActive": true,
        "lastCheck": "2025-09-12T12:55:00.000Z"
    },
    "statusCode": 0,
    "error": "string"
}
```

Get alert group status

Returns the status of a specific alert group

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

`alertingGroupId` required	string

Responses

> **200** Alert group status fetched successfully

> **400** Error

> **401** Unauthorized

> **404** Alert group not found

GET /api/public/v1/alerting/alerts/group/status/{alertingGroupId}

Response samples

200 400 401 404

Content type
application/json

Copy Expand all Collapse all


```
{
    "message": "string",
  - "data": {
        "alerting_id": "047b7bc9-daae-4f26-a0fe-b7ddee6a1b9f",
        "alerting_group_id": "b65e7a82-e650-4894-8fd8-9863299cdd9f",
        "peak": null,
        "limit": 0,
        "repeat": null,
        "metric": "cpu_util",
        "isAlertActive": true,
        "lastCheck": "2025-09-12T12:55:00.000Z"
    },
    "statusCode": 0,
    "error": "string"
}
```

Get alerting group with alerts activity

Returns alerting group with active alerts

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

`alertingGroupId` required	string

Responses

> **200** Alerting group with alerts activity fetched successfully

> **400** Error

> **401** Unauthorized

> **404** Alert group not found

GET `/api/public/v1/alerting/groups/alerts/{alertingGroupId}`

Response samples

200 | 400 | 401 | 404

Content type
application/json

Copy Expand all Collapse all


```
{
    "message": "string",
  - "data": {
        "alerting_group_id": "string",
        "label": "string",
        "description": "string",
        "enabled": true,
    + "alerts": [ … ],
    + "active_items": [ … ]
    },
```

```
    "statusCode": 0,
    "error": "string"
}
```

Get alert with items

Returns alert with active items

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

alertId required	string

Responses

> **200** Alert with items fetched successfully

> **400** Error

> **401** Unauthorized

> **404** Alert not found

GET /api/public/v1/alerting/alerts/items/{alertId}

Response samples

200 400 401 404

Content type
application/json

Copy Expand all Collapse all


```
{
    "message": "string",
  - "data": {
        "alerting_group_id": "string",
        "alerting_id": "string",
        "metric": "string",
        "limit": 0,
        "peak": 0,
        "repeat": 0,
        "isAlertActive": true,
        "active_items_count": 0,
    + "items": [ … ]
    },
    "statusCode": 0,
    "error": "string"
}
```

Get alert items

Returns active items for a specific alert

AUTHORIZATIONS: > *apiKey*

PATH PARAMETERS

alertId required	string

Responses

> **200** Alert items fetched successfully

> **400** Error

> **401** Unauthorized

> **404** Alert not found

GET /api/public/v1/alerting/items/alert/{alertId}

Response samples

200 400 401 404

Content type
application/json

Copy Expand all Collapse all

```
{
    "message": "string",
  - "data": [
      + { … }
    ],
    "statusCode": 0,
    "error": "string"
}
```