Blur fade

---
title: Blur Fade
date: 2024-07-07
description: Blur fade in and out animation. Used to smoothly fade in and out content.
author: dillionverma
published: true

<ComponentPreview name="blur-fade-demo" />

Installation

<Tabs defaultValue="cli">

<TabsList>
  <TabsTrigger value="cli">CLI</TabsTrigger>
  <TabsTrigger value="manual">Manual</TabsTrigger>
</TabsList>
<TabsContent value="cli">

```bash
npx shadcn@latest add @magicui/blur-fade
```

</TabsContent>

<TabsContent value="manual">

<Steps>

<Step>Copy and paste the following code into your project.</Step>

```tsx
"use client"

import { useRef } from "react"
import {
  AnimatePresence,
  motion,
  useInView,
  type MotionProps,
  type UseInViewOptions,
  type Variants,
} from "motion/react"

type MarginType = UseInViewOptions["margin"]

interface BlurFadeProps extends MotionProps {
  children: React.ReactNode
  className?: string
  variant?: {
    hidden: { y: number }
    visible: { y: number }
  }
  duration?: number
  delay?: number
  offset?: number
  direction?: "up" | "down" | "left" | "right"
```

```
  inView?: boolean
  inViewMargin?: MarginType
  blur?: string
}

const getFilter = (v: Variants[string]) =>
  typeof v === "function" ? undefined : v.filter

export function BlurFade({
  children,
  className,
  variant,
  duration = 0.4,
  delay = 0,
  offset = 6,
  direction = "down",
  inView = false,
  inViewMargin = "-50px",
  blur = "6px",
  ...props
}: BlurFadeProps) {
  const ref = useRef(null)
  const inViewResult = useInView(ref, { once: true, margin: inViewMargin })
  const isInView = !inView || inViewResult
  const defaultVariants: Variants = {
    hidden: {
      [direction === "left" || direction === "right" ? "x" : "y"]:
        direction === "right" || direction === "down" ? -offset : offset,
      opacity: 0,
      filter: `blur(${blur})`,
    },
    visible: {
      [direction === "left" || direction === "right" ? "x" : "y"]: 0,
      opacity: 1,
      filter: `blur(0px)`,
    },
  }
  const combinedVariants = variant ?? defaultVariants

  const hiddenFilter = getFilter(combinedVariants.hidden)
  const visibleFilter = getFilter(combinedVariants.visible)

  const shouldTransitionFilter =
    hiddenFilter != null &&
    visibleFilter != null &&
    hiddenFilter !== visibleFilter

  return (
    <AnimatePresence>
      <motion.div
        ref={ref}
        initial="hidden"
        animate={isInView ? "visible" : "hidden"}
        exit="hidden"
        variants={combinedVariants}
        transition={{
          delay: 0.04 + delay,
          duration,
```

```
        ease: "easeOut",
        ...(shouldTransitionFilter ? { filter: { duration } } : {}),
      }}
      className={className}
      {...props}
    >
      {children}
    </motion.div>
  </AnimatePresence>
 )
}
```

<Step>Update the import paths to match your project setup.</Step>

</Steps>

</TabsContent>

</Tabs>

Examples

<ComponentPreview name="blur-fade-text-demo" />

Usage

```tsx showLineNumbers
import { BlurFade } from "@/components/ui/blur-fade"
```

```tsx showLineNumbers
<BlurFade>
  <img src="https://picsum.photos/300/200?random=1" alt="Sample 1" />
  <img src="https://picsum.photos/300/200?random=2" alt="Sample 2" />
  <img src="https://picsum.photos/300/200?random=3" alt="Sample 3" />
</BlurFade>
```

Props

Prop	Type	Default	Description
`children`	`React.ReactNode`	`-`	The content to be animated
`className`	`string`	`-`	The class name to be applied to the component
`variant`	`object`	`-`	Custom animation variants for motion component
`duration`	`number`	`0.4`	Duration (seconds) for the animation
`delay`	`number`	`0`	Delay (seconds) before the animation starts
`offset`	`number`	`6`	Offset for the animation
`direction`	`string`	`"down"`	Direction for the animation (`up`, `down`, `left`, `right`)
`inView`	`boolean`	`false`	Whether to trigger animation when component is in view
`inViewMargin`	`MarginType`	`"-50px"`	Margin for triggering the in-view animation
`blur`	`string`	`"6px"`	Amount of blur to apply during the animation