File upload

File Upload

A 2-file React component from Aceternity UI. Add it to this project so it works and looks exactly like the source below.

Fastest path

If this project has a `components.json` (shadcn), run `npx shadcn@latest add @aceternity/file-upload-demo`.
If the command succeeds, only fix import paths to match this project and skip to **Check**. If it fails or there is no `components.json`, build it by hand as below.

Build it

- Stack: React with TypeScript and Tailwind CSS v4.
- Install: `motion`, `@tabler/icons-react`, `react-dropzone`, `clsx`, `tailwind-merge`. Use this project's package manager.
- Create this file, in this project's usual place for components:
  - `components/ui/file-upload.tsx`
- Keep these exports and their names: `FileUpload`, `GridPattern`. Other code imports them.
- It imports `cn` from `@/lib/utils` (clsx + tailwind-merge, so a caller's `className` overrides the defaults). Use the project's helper if it has one; otherwise create it: `export function cn(...inputs: ClassValue[]) { return twMerge(clsx(inputs)); }`.
- Imports that start with `@/` use the shadcn alias. Rewrite them to this project's alias, and keep the file layout consistent with its conventions (location, naming, formatting).
- Keep `"use client"` at the top in Next.js App Router projects (it uses state, effects or browser APIs). In other setups it is harmless.
- Style with the Tailwind utilities exactly as written. They are the design: do not swap them for other values, inline styles or a CSS file.
- Animation uses Motion. Keep the timings, easings and the reduced-motion handling as they are.

Use it

The example below shows how to render it. Put it on a page to see it working:
- `components/file-upload-demo.tsx`

Check

- It type-checks and the page renders with no console errors.
- It looks and behaves like the source in light and dark mode.
- With `prefers-reduced-motion: reduce`, motion is reduced as the source intends.
- Tell me every place where you had to do something differently from the source, and why.

Source

The reference implementation. Copy it as-is, then apply only the changes listed above.

`components/file-upload-demo.tsx`

```tsx
"use client";
import React, { useState } from "react";
import { FileUpload } from "@/components/ui/file-upload";

export default function FileUploadDemo() {
  const [files, setFiles] = useState<File[]>([]);
  const handleFileUpload = (files: File[]) => {
    setFiles(files);
    console.log(files);
  };

  return (
    <div className="w-full max-w-4xl mx-auto min-h-96 border border-dashed bg-white dark:bg-black border-neutral-200 dark:border-neutral-800 rounded-lg">
      <FileUpload onChange={handleFileUpload} />
```

```
    </div>
  );
}
```

`components/ui/file-upload.tsx`

```tsx
"use client";
import { cn } from "@/lib/utils";
import React, { useRef, useState } from "react";
import { motion } from "motion/react";
import { IconUpload } from "@tabler/icons-react";
import { useDropzone } from "react-dropzone";

const mainVariant = {
  initial: {
    x: 0,
    y: 0,
  },
  animate: {
    x: 20,
    y: -20,
    opacity: 0.9,
  },
};

const secondaryVariant = {
  initial: {
    opacity: 0,
  },
  animate: {
    opacity: 1,
  },
};

export const FileUpload = ({
  onChange,
}: {
  onChange?: (files: File[]) => void;
}) => {
  const [files, setFiles] = useState<File[]>([]);
  const fileInputRef = useRef<HTMLInputElement>(null);

  const handleFileChange = (newFiles: File[]) => {
    setFiles((prevFiles) => [...prevFiles, ...newFiles]);
    onChange && onChange(newFiles);
  };

  const handleClick = () => {
    fileInputRef.current?.click();
  };

  const { getRootProps, isDragActive } = useDropzone({
    multiple: false,
    noClick: true,
    onDrop: handleFileChange,
    onDropRejected: (error) => {
      console.log(error);
```

```
  },
 });

 return (
  <div className="w-full" {...getRootProps()}>
   <motion.div
    onClick={handleClick}
    whileHover="animate"
    className="group/file relative block w-full cursor-pointer overflow-hidden rounded-lg p-10"
   >
    <input
     ref={fileInputRef}
     id="file-upload-handle"
     type="file"
     onChange={(e) => handleFileChange(Array.from(e.target.files || []))}
     className="hidden"
    />
    <div className="absolute inset-0 [mask-image:radial-gradient(ellipse_at_center,white,transparent)]">
     <GridPattern />
    </div>
    <div className="flex flex-col items-center justify-center">
     <p className="relative z-20 font-sans text-base font-bold text-neutral-700 dark:text-neutral-300">
      Upload file
     </p>
     <p className="relative z-20 mt-2 font-sans text-base font-normal text-neutral-400 dark:text-neutral-400">
      Drag or drop your files here or click to upload
     </p>
     <div className="relative mx-auto mt-10 w-full max-w-xl">
      {files.length > 0 &&
       files.map((file, idx) => (
        <motion.div
         key={"file" + idx}
         layoutId={idx === 0 ? "file-upload" : "file-upload-" + idx}
         className={cn(
          "relative z-40 mx-auto mt-4 flex w-full flex-col items-start justify-start overflow-hidden rounded-md bg-white p-4 md:h-24
dark:bg-neutral-900",
          "shadow-sm",
         )}
        >
         <div className="flex w-full items-center justify-between gap-4">
          <motion.p
           initial={{ opacity: 0 }}
           animate={{ opacity: 1 }}
           layout
           className="max-w-xs truncate text-base text-neutral-700 dark:text-neutral-300"
          >
           {file.name}
          </motion.p>
          <motion.p
           initial={{ opacity: 0 }}
           animate={{ opacity: 1 }}
           layout
           className="shadow-input w-fit shrink-0 rounded-lg px-2 py-1 text-sm text-neutral-600 dark:bg-neutral-800 dark:text-white"
          >
           {(file.size / (1024 * 1024)).toFixed(2)} MB
          </motion.p>
         </div>
```

```
            <div className="mt-2 flex w-full flex-col items-start justify-between text-sm text-neutral-600 md:flex-row md:items-center
dark:text-neutral-400">
              <motion.p
                initial={{ opacity: 0 }}
                animate={{ opacity: 1 }}
                layout
                className="rounded-md bg-gray-100 px-1 py-0.5 dark:bg-neutral-800"
              >
                {file.type}
              </motion.p>

              <motion.p
                initial={{ opacity: 0 }}
                animate={{ opacity: 1 }}
                layout
              >
                modified{" "}
                {new Date(file.lastModified).toLocaleDateString()}
              </motion.p>
            </div>
          </motion.div>
        ))}
        {!files.length && (
          <motion.div
            layoutId="file-upload"
            variants={mainVariant}
            transition={{
              type: "spring",
              stiffness: 300,
              damping: 20,
            }}
            className={cn(
              "relative z-40 mx-auto mt-4 flex h-32 w-full max-w-[8rem] items-center justify-center rounded-md bg-white group-hover/file:shadow-2xl
dark:bg-neutral-900",
              "shadow-[0px_10px_50px_rgba(0,0,0,0.1)]",
            )}
          >
            {isDragActive ? (
              <motion.p
                initial={{ opacity: 0 }}
                animate={{ opacity: 1 }}
                className="flex flex-col items-center text-neutral-600"
              >
                Drop it
                <IconUpload className="h-4 w-4 text-neutral-600 dark:text-neutral-400" />
              </motion.p>
            ) : (
              <IconUpload className="h-4 w-4 text-neutral-600 dark:text-neutral-300" />
            )}
          </motion.div>
        )}

        {!files.length && (
          <motion.div
            variants={secondaryVariant}
            className="absolute inset-0 z-30 mx-auto mt-4 flex h-32 w-full max-w-[8rem] items-center justify-center rounded-md border
border-dashed border-sky-400 bg-transparent opacity-0"
          ></motion.div>
```

```
          )}
        </div>
      </div>
    </motion.div>
  </div>
 );
};

export function GridPattern() {
 const columns = 41;
 const rows = 11;
 return (
  <div className="flex shrink-0 scale-105 flex-wrap items-center justify-center gap-x-px gap-y-px bg-gray-100 dark:bg-neutral-900">
   {Array.from({ length: rows }).map((_, row) =>
    Array.from({ length: columns }).map((_, col) => {
     const index = row * columns + col;
     return (
      <div
       key={`col -{row}`}
       className={`flex h-10 w-10 shrink-0 rounded-[2px] ${
        index % 2 === 0
         ? "bg-gray-50 dark:bg-neutral-950"
         : "bg-gray-50 shadow-[0px_0px_1px_3px_rgba(255,255,255,1)_inset] dark:bg-neutral-950
dark:shadow-[0px_0px_1px_3px_rgba(0,0,0,1)_inset]"
       }`}
      />
     );
    }),
   )}
  </div>
 );
}
```