



## **Release notes**

### **E-Series Systems**

NetApp  
April 02, 2023

This PDF was generated from <https://docs.netapp.com/us-en/e-series/whats-new.html> on April 02, 2023.  
Always check [docs.netapp.com](https://docs.netapp.com) for the latest.

# Table of Contents

Release notes .....	1
What's new in SANtricity OS .....	1
Release notes .....	4

# Release notes

## What's new in SANtricity OS

The following tables describe new features in SANtricity OS 11.7 for embedded management of EF300, EF600, E2800/EF280, and E5700/EF570 controllers.

### New features in Version 11.74

New feature	Description
Support for FIPS 140-3	FIPS 140-3 is now supported on certain drives for both SAS and NVMe-based SSDs. FIPS 140-3 level SSD drives can co-exist with FIPS 140-2 level SSD drives, provided that the drives are either all NVMe-based or all SAS-based. When using a mixture of these levels in volume groups and disk pools, be aware that the group or pool will then operate at the lower level of security (140-2).
MFA and SSH support	For SANtricity versions 11.74 and later, the Remote Login feature allows you to configure multifactor authorization (MFA) by requiring users to enter an SSH key and/or SSH password. The menu option in the Hardware section has changed from <b>Change remote login</b> to <b>Configure remote login (SSH)</b> .
Access tokens	This release includes a new feature for creating access tokens. These tokens allow you to authenticate with the REST API or command line interface (CLI), without exposing user names and passwords. This feature is provided in the Access Management section.

### New features in Version 11.73

New feature	Description
Resource Provisioning and DULBE support	Resource Provisioning capabilities and DULBE drive capabilities are now fully supported in this release. This support includes making host-directed UNMAP on Resource-Provisioned volumes more widely usable.
EF600 SAS (512e) expansion	This release provides support for expansion to SAS-3 enclosures for the EF600 storage system. With this expansion, the 4KiB-block NVMe SSDs can coexist with 512e SAS SSDs and HDDs. However, drives with different block sizes cannot be configured in the same pool or volume group.

New feature	Description
QLC SSD support	This release supports the current generation of QLC SSDs that have ONTAP feature set in the drive firmware but do not have the full E-Series-specific feature set. QLC drives (NVMe only) are lower cost, but have lower write performance and a lower endurance rating so they should not be used with write-intensive workloads.
TLS 1.3 support	TLS 1.3 is now supported for embedded management. This support applies to System Manager and embedded Web Services, with the ability to enable or disable it. (TLS 1.3 support was added in a previous release for the Web Services Proxy and Unified Manager.)
RAID 1 DDP with 8-drive minimum	With this release, RAID 1 DDP no longer requires a minimum of 11 SSDs in a pool. The minimum now allows 8-drive SSD pools if only RAID 1 volumes are created in the pool.
EKMS key deletion	A storage admin can now request an external key management server (EKMS) to delete an old key. The key deletion only takes place during a re-key process after the installed drives have the new key.

## New features in Version 11.72

New feature	Description
SNMPv3 support	SNMPv3 is now supported for alert notifications, configurable in <b>Settings &gt; Alerts</b> . SNMPv3 provides security through strong authentication and data encryption.
Support replicating keys to multiple key servers	For external key management for self-encrypting drives, the Create External Key Management dialog includes a new option for adding multiple key servers.
Updated browser versions	System Manager minimum browser versions have been updated.

## New features in Version 11.71

New feature	Description
EF300 expansion	This release provides support for expansion to SAS-3 enclosures for the EF300 storage system. With this expansion, the 4KiB-block NVMe SSDs can coexist with 512e SAS SSDs and HDDs. However, drives with different block sizes cannot be configured in the same pool or volume group.
FEC mode option in iSCSI configuration	For storage arrays using the 25Gb iSCSI host interface card, a new option is available for setting the Forward Error Correction (FEC) mode when you configure iSCSI ports.

New feature	Description
Remote Storage Volumes	The optional Remote Storage Volumes feature allows you to import volumes from a remote storage system to a local E- Series storage system using an iSCSI connection. The remote storage may be the same brand as your E-Series system or from a different storage vendor, as long as it is accessible via iSCSI.
Sanitize (erase) capability added for non-FDE drives	The drive sanitize feature now includes non-FDE drives in the procedure. From the Hardware page, you can open the Drive's context menu and select "Erase" (previously, this selection was "Secure Erase").
Secure connection for email alerts	To enable encrypted email notifications, you can optionally configure outgoing emails (alerts, ASUP dispatches) to supply authentication credentials. Encryption types include SMTPS and STARTTLS.
AutoSupport additions	An alert now appears in the Notifications area when AutoSupport is not enabled.
Syslog alert format change	The Syslog alert format now supports RFC 5424.

## New features in Version 11.70

New feature	Description
New storage system model – EF300	This release introduces the EF300 low-cost all-NVMe-flash storage system. The EF300 includes 24 NVME SSD drives and a single host interface card (HIC) per controller. The supported NVMe over Fabrics host interfaces include NVMe over IB, NVMe over RoCE, and NVMe over FC. The supported SCSI interfaces include FC, IB over iSER, and IB over SRP. Multiple EF300 storage systems and other E- Series storage systems can be viewed and managed in Unified Manager.
New Resource Provisioning feature (EF300 and EF600 only)	The Resource Provisioning feature is new for the EF300 and EF600 storage systems. Resource-provisioned volumes can be put in use immediately with no background initialization process.
Add 512e block size option (EF300 and EF600 only)	For EF300 and EF600 storage systems, a volume can be set to support a 512-byte or a 4KiB block size. The 512e capability has been added to allow support of the iSCSI host interface and the VMware OS. If possible, System Manager suggests the appropriate default value.
New option for sending AutoSupport dispatches on demand	A new Send AutoSupport Dispatch feature allows you to send data to technical support without waiting for a scheduled dispatch. This option is available in the AutoSupport tab of the Support Center.

New feature	Description
External Key Management Server enhancements	<p>The feature for connecting to an external key management server includes the following enhancements:</p> <ul style="list-style-type: none"> <li>• Bypass the function for creating a backup key.</li> <li>• Choose an intermediate certificate for the key management server, in addition to the client and server certificates.</li> </ul>
Certificate enhancements	This release allows for using an external tool such as OpenSSL to generate a Certificate Signing Request (CSR), which also requires you to import a private key file along with the signed certificate.
New Offline Initialization feature for Volume Groups	For volume creation, System Manager provides a method for skipping the host assignment step so that newly created volumes are initialized offline. This capability is applicable only to RAID volume groups on SAS drives (i.e., not to dynamic disk pools or to the NVMe SSDs included in the EF300 and EF600 storage systems). This feature is for workloads that need to have the volumes at full performance when usage begins, rather than having initialization run in the background.
New Collect Configuration Data feature	This new feature saves RAID configuration data from the controller, which includes all data for volume groups and disk pools (the same information as the CLI command for <code>save storageArray dbmDatabase</code> ). This capability has been added to aid technical support and is located in the Diagnostics tab of the Support Center.
Change default preservation capacity for disk pools in 12 drive case	Previously, a 12-drive disk pool was created with enough preservation (spare) capacity to cover two drives. The default is now changed to handle a single drive failure to offer a more cost-effective small pool default.

## Release notes

Release Notes are available outside this site. You will be prompted to log in using your NetApp Support Site credentials.

- [11.70 Release notes](#)
- [11.60 Release notes](#)
- [11.50 Release notes](#)

## Copyright information

Copyright © 2023 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.