

Creating a Secure Software Development Lifecycle (SSDLC) Plan

Internet and Web Application Security 3e - Lab 3


Student: Samuel Guardado
Email: sguar5@brockport.edu
Report Generated: Thursday, July 30, 2026 at 6:10 PM

Time on Task: 7 hours, 51 minutes
Progress: 100%


Section 1: Hands-On Demonstration

Part 1: Identify the Roles Required During Development


29. Make a screen capture showing the page with the new title.




35. Make a screen capture showing the lines for the Fetch stage.




37. Make a screen capture showing the lines for the Build stage.



39. Make a screen capture showing the lines for the Push stage.




41. Make a screen capture showing the lines for the Run stage.




Part 2: Configure the Roles to Use Separate Credentials


4. Make a screen capture showing the directory tree.




36. Make a screen capture showing the application with the updated title.




47. Make a screen capture showing the failed build log.



52. Make a screen capture showing the directory tree.




55. Make a screen capture showing the build list with a success after the failure.




Part 3: Integrate Testing into the Pipeline

8. Make a screen capture showing the SAST output in the log.



24. Make a screen capture showing the log details of the input step.




Section 2: Challenge and Analysis

Part 1: Implement the Push to Production

1. **Document the required steps** to create the new SSH key, **install it on the Jenkins server**, and **update the Pipeline**.

Step 1: Created an exclusive key for todo-prod \ Step 2: Moved it to the authorized keys folder and gave it proper permissions(.ssh = 700, and authorized_keys = 600) \ Step 3: Edited the pipeline to match the new key I just created.

2. **Make a screen capture** showing a log from running the new Pipeline configuration that shows the new key being used.



Part 2: Restrict Jenkins SCM Access

1. **Document the changes** to the SSH configuration file ~/.ssh/authorized_keys for the user scm to ensure that the *jenkins_key* can clone only the git repository.

For the scm user, I changed the Jenkins key to: "command+"git-upload-pack '/home/repos/todolist.git'", not-port-forwarding,no-agent-forwarding,no-pty ssh-rsa AAAAB3... j_prod_key. These configurations force least privilege to the Jenkins SSH key by cloning the repository, which protects it from being modified.