



## Incident report analysis

|          |                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Summary  | The company experienced a Denial-of-Service attack (DoS) caused by an ICMP flood. A malicious actor sent a large amount of ICMP packets through a misconfigured firewall, overwhelming the company's network, and preventing normal traffic from accessing network resources. The security team responded by blocking incoming ICMP packets, stopping non-critical network services, and restoring critical network services. |
| Identify | The organization's network services and network resources were affected by an ICMP flood attack. The misconfigured firewall was involved in the incident because it allowed the malicious ICMP traffic to reach the internal network. Normal internal network traffic was unable to access network resources. Critical network services were affected and non-critical services were taken offline.                           |
| Protect  | To remedy that security incident, the security team has implemented a new firewall rule to limit the incoming ICMP packets rate and an IDS/IPS system to filter part of the ICMP traffic based on suspicious characteristics. The firewall should also verify source IP addresses to help detect and block spoofed source addresses incoming ICMP packets.                                                                    |
| Detect   | The security team will continuously monitor network traffic using a network analyzer and IDS/IPS. The firewall will verify source IP addresses to detect IP spoofing. Security logs and alerts can be collected and analyzed using a SIEM to identify abnormal ICMP traffic patterns and other suspicious activity.                                                                                                           |
| Respond  | For future security incidents, the security team will isolate affected systems and block malicious or suspicious ICMP traffic to contain the attack. The team will analyze firewall and network logs to determine the source and characteristics                                                                                                                                                                              |

|         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|         | of the attack and identify any abnormal activity. The team will also report all incidents to upper management and appropriate legal authorities, if applicable and review the response procedures and implement improvements to prevent similar incidents.                                                                                                                                                                                                                                                  |
| Recover | To recover from an ICMP flood attack, critical network services should first be restored and verified to ensure that they are functioning normally. Non-critical services can then be brought back online gradually. Network system and traffic performance should be monitored during the restoration process to ensure that the attack has been contained and that services remain stable. The company should also review and improve its recovery procedures based on lessons learned from the incident. |

---

Reflections/Notes: