



DIAGRAMMI DI CARICO

LOAD CHART


TABELLE DI CARICO PER CONFIGURAZIONI MONOANTA
LOAD CHARTS FOR ONE SASH CONFIGURATIONS

130 kg - 180°



Obbligatorio A3310.50 con soglie ribassate
Mandatory A3310.50 with low threshold

Consigliato A3310.50 per portate > 110 kg
Recommended A3310.50 with weight > 100kg




2500	50	42	35	30	26	23	21	19	17
2400	50	43	36	31	27	24	22	20	18
2300	50	45	38	32	28	25	23	21	19
2200	50	47	39	34	30	26	24	21	20
2100	50	50	41	35	31	28	25	23	21
2000	50	50	43	37	33	29	26	24	22
1900	50	50	46	39	34	30	27	25	23
1800	50	50	48	41	36	32	29	26	24
1700	50	50	50	44	38	34	31	28	25
1600	50	50	50	46	41	36	33	30	27
1500	50	50	50	50	43	39	35	32	29
1400	50	50	50	50	46	41	37	34	28
1300	50	50	50	50	50	44	40	33	30
1200	50	50	50	50	50	48	39	35	33
1100	50	50	50	50	50	47	43	39	30
1000	50	50	50	50	50	50	47	35	26
900	50	50	50	50	50	50	35	32	19
800	50	50	50	50	50	43	39	24	11
700	50	50	50	50	50	50	15	N.D.	N.D.
600	50	50	50	50	43	19	N.D.	N.D.	N.D.
500	50	50	50	50	N.D.	N.D.	N.D.	N.D.	N.D.
	430	500	600	700	800	900	1000	1100	1200





150 kg - 90°



Obbligatorio A3310.50 con soglie ribassate
Mandatory A3310.50 with low threshold



2700	50	44	37	32	28	25	22	20	19
2600	50	46	38	33	29	26	23	21	19
2500	50	48	40	34	30	27	24	22	20
2400	50	50	42	36	31	28	25	23	21
2300	50	50	43	37	33	29	26	24	22
2200	50	50	45	39	34	30	27	25	23
2100	50	50	48	41	36	32	29	26	24
2000	50	50	50	43	38	33	30	27	25
1900	50	50	50	45	39	35	32	29	26
1800	50	50	50	48	42	37	33	30	28
1700	50	50	50	50	44	39	35	32	29
1600	50	50	50	50	47	42	38	34	31
1500	50	50	50	50	50	44	40	36	33
1400	50	50	50	50	50	48	43	39	32
1300	50	50	50	50	50	50	46	38	35
1200	50	50	50	50	50	50	45	41	38
1100	50	50	50	50	50	50	49	45	27
1000	50	50	50	50	50	50	50	33	30
900	50	50	50	50	50	50	40	36	22
800	50	50	50	50	50	50	45	27	11
700	50	50	50	50	50	50	17	N.D.	N.D.
600	50	50	50	50	50	19	N.D.	N.D.	N.D.
550	50	50	50	50	N.D.	N.D.	N.D.	N.D.	N.D.
	470	500	600	700	800	900	1000	1100	1200



Per apertura
impedita a 180°
è obbligatorio
braccio limitatore
For windows
with 180°
restricted opening
mandatory use a
limiter arm

A1215.1 (L>570)

