```
Last login: Mon Mar 30 16:13:04 on ttys018
hs11@SAs-MacBook-Air bin % ./mysql -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 37
Server version: 8.0.44 Source distribution
Copyright (c) 2000, 2023, Oracle and/or its affiliates.
Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.
Type 'help;' or '\h' for help. Type '\c' to clear the current input
statement.
mysql> show databases;
+--------------------+
| Database           |
+--------------------+
| information_schema |
| mysql              |
| performance_schema |
| sys                |
+--------------------+
4 rows in set (0.00 sec)
mysql> CREATE DATABASE;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near '' at line 1
mysql> CREATE DATABASE DAE;
Query OK, 1 row affected (0.01 sec)
mysql> show database;
```

```
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'database' at line 1
mysql> SHOW DATABASE;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'DATABASE' at line 1
mysql> SHOW DATABASES;
+--------------------+
| Database           |
+--------------------+
| DAE                |
| information_schema |
| mysql              |
| performance_schema |
| sys                |
+--------------------+
5 rows in set (0.00 sec)
mysql> USE DAE;
Database changed
mysql> CREATE TABLE DAETABLE (id INT PRIMARY KEY,
FName VARCHAR(15), LName VARCHAR(15),AGE INT);
Query OK, 0 rows affected (0.02 sec)
mysql> SHOW TABLES;
+---------------+
| Tables_in_dae |
+---------------+
| DAETABLE      |
+---------------+
1 row in set (0.00 sec)
```

```
mysql> INSERT INTO DATATABLE (id, FName, Age) VALUES (1,
"SAMI","DHANAPAL","15"
    -> ;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near '' at line 1
mysql> INSERT INTO DATATABLE (id, FName, Age) VALUES (2,
"IDA","YOHANNES","16"
    -> ;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near '' at line 1
mysql> INSERT INTO DATATABLE (id, FName, Age) VALUES (1,
"SAMI","DHANAPAL","15");
ERROR 1146 (42S02): Table 'dae.datatable' doesn't exist
mysql>
mysql> SELECT * FROM DAETABLE;
Empty set (0.00 sec)
mysql> INSERT INTO DAETABLE (id, FName, LName, Age)
VALUES (1, "SAMI", "DHANAPAL", 15);
Query OK, 1 row affected (0.00 sec)
mysql> INSERT INTO DAETABLE (id, FName, LName, Age)
VALUES (2, "IDA", "YOHANNES", 16);
Query OK, 1 row affected (0.00 sec)
mysql> SELECT * FROM DAETABLE
    -> ;
+----+-------+----------+------+
| id | FName | LName    | AGE  |
+----+-------+----------+------+
|  1 | SAMI  | DHANAPAL |   15 |
```

```
|  2 | IDA   | YOHANNES |   16 |
+----+-------+----------+------+
2 rows in set (0.00 sec)
mysql> ALTER TABLE DAETABLE ADD COLUMN emailId
VARCHAR(30);
Query OK, 0 rows affected (0.01 sec)
Records: 0  Duplicates: 0  Warnings: 0
mysql> SELECT * FROM DAETABLE;
+----+-------+----------+------+---------+
| id | FName | LName    | AGE  | emailId |
+----+-------+----------+------+---------+
|  1 | SAMI  | DHANAPAL |   15 | NULL    |
|  2 | IDA   | YOHANNES |   16 | NULL    |
+----+-------+----------+------+---------+
2 rows in set (0.01 sec)
mysql> show tables;
+---------------+
| Tables_in_dae |
+---------------+
| DAETABLE      |
+---------------+
1 row in set (0.03 sec)
mysql> desc daetable
    -> ;
+---------+-------------+------+-----+---------+-------+
| Field   | Type        | Null | Key | Default | Extra |
+---------+-------------+------+-----+---------+-------+
| id      | int         | NO   | PRI | NULL    |       |
| FName   | varchar(15) | YES  |     | NULL    |       |
| LName   | varchar(15) | YES  |     | NULL    |       |
```

```
| AGE     | int         | YES  |     | NULL    |       |
| emailId | varchar(30) | YES  |     | NULL    |       |
+---------+-------------+------+-----+---------+-------+
5 rows in set (0.03 sec)
mysql> select * from daetable
    -> ;
+----+-------+----------+------+---------+
| id | FName | LName    | AGE  | emailId |
+----+-------+----------+------+---------+
|  1 | SAMI  | DHANAPAL |   15 | NULL    |
|  2 | IDA   | YOHANNES |   16 | NULL    |
+----+-------+----------+------+---------+
2 rows in set (0.01 sec)
mysql> update daetable set emailid =
'samiksha.dhanapal777@gmail.com' where id = 7
    -> ;
Query OK, 0 rows affected (0.00 sec)
Rows matched: 0  Changed: 0  Warnings: 0
mysql> select * from daetable;
+----+-------+----------+------+---------+
| id | FName | LName    | AGE  | emailId |
+----+-------+----------+------+---------+
|  1 | SAMI  | DHANAPAL |   15 | NULL    |
|  2 | IDA   | YOHANNES |   16 | NULL    |
+----+-------+----------+------+---------+
2 rows in set (0.00 sec)
mysql>
mysql> create table animal;
ERROR 4028 (HY000): A table must have at least one visible
column.
```

```
mysql> create table animal
    -> (Reptile Primary Key, Mammal Primary Key, Ancient Primary
Key, Fantasy Primary Key);
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'Primary Key, Mammal Primary
Key, Ancient Primary Key, Fantasy Primary Key)' at line 2
mysql> (Reptile Primary Key, Mammal Primary Key, Ancient
Primary Key, Fantasy Primary Key);                ERROR 1064
(42000): You have an error in your SQL syntax; check the manual
that corresponds to your MySQL server version for the right
syntax to use near 'Reptile Primary Key, Mammal Primary Key,
Ancient Primary Key, Fantasy Primary Ke' at line 1
mysql> create table animal
    -> (Reptile, Mammal, Ancient, Fantasy);
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near ', Mammal, Ancient, Fantasy)' at
line 2
mysql> create table animal (Reptile VARCHAR(20) PRIMARY
KEY , Mammal VARCHAR(20) PRIMARY KEY, Ancient
VARCHAR(20) PRIMARY KEY, Fantasy VARCHAR(20)
PRIMARY KEY);
ERROR 1068 (42000): Multiple primary key defined
mysql> create table animal (Reptile VARCHAR(20)PRIMARY
KEY, Mammal VARCHAR(20), Ancient VARCHAR(20), Fantasy
VARCHAR(20);
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near '' at line 1
```

```
mysql> create table animal (Reptile VARCHAR(20)PRIMARY
KEY, Mammal VARCHAR(20), Ancient VARCHAR(20), Fantasy
VARCHAR(20);
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near '' at line 1
mysql> SHOW TABLES;
+---------------+
| Tables_in_dae |
+---------------+
| DAETABLE      |
+---------------+
1 row in set (0.01 sec)
mysql> create table animal (mammals varchar(30) primary key,
reptiles varchar(20), ancient_dinasours varchar(25), fantasy
varchar(15));
Query OK, 0 rows affected (0.03 sec)
mysql> INSERT INTO ANIMAL (Reptiles, Mammals, Ancient,
Fantasy);
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near '' at line 1
mysql> INSERT INTO ANIMAL (Reptiles, Mammals, Ancient,
Fantasy ) VALUES ("Snake", "Human", "Dinosaur", "Unicorn" )
    -> INSERT INTO ANIMAL (Reptiles, Mammals, Ancient,
Fantasy ) VALUES ("Snake", "Human", "Dinosaur", "Unicorn" );
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'INSERT INTO ANIMAL (Reptiles,
Mammals, Ancient, Fantasy ) VALUES ("Snake", "Huma' at line 2
```

```
mysql> INSERT INTO ANIMAL (Reptiles, Mammals, Ancient,
Fantasy ) VALUES ("Snake", "Human", "Dinosaur", "Unicorn" )
INSERT INTO ANIMAL (Reptiles, Mammals, Ancient, Fantasy )
VALUES ("Snake", "Human", "Dinosaur", "Unicorn" );
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'INSERT INTO ANIMAL (Reptiles,
Mammals, Ancient, Fantasy ) VALUES ("Snake", "Huma' at line 1
mysql> select * from animal;
Empty set (0.01 sec)
mysql> select * from ANIMAL;
Empty set (0.00 sec)
mysql> select * from  animal;;
Empty set (0.00 sec)
ERROR:
No query specified
mysql> INSERT INTO animal (Reptiles, Mammals, Ancient,
Fantasy ) VALUES ("Snake", "Human", "Dinosaur", "Unicorn" );
ERROR 1054 (42S22): Unknown column 'Ancient' in 'field list'
mysql> INSERT INTO animal (reptiles, mammals,
ancient_dinosaurs, fantasy ) VALUES ("Snake", "Human",
"Dinosaur", "Unicorn" );
ERROR 1054 (42S22): Unknown column 'ancient_dinosaurs' in
'field list'
mysql> create table animal (mammals varchar(30) primary key,
reptiles varchar(20), ancient_dinasours varchar(25), fantasy
varchar(15));
ERROR 1050 (42S01): Table 'animal' already exists
```

```
mysql> INSERT INTO animal (reptiles, mammals,
ancient_dinosaurs, fantasy ) VALUES ("Snake", "Human",
"Dinosaur", "Unicorn" );
ERROR 1054 (42S22): Unknown column 'ancient_dinosaurs' in
'field list'
mysql> select * from animal
    ->
    ->
    ->
Display all 763 possibilities? (y or n)
?                       ENGINES                 MASTER
RTREE
ABS                     ENUM
MASTER_CONNECT_RETRY    RTRIM
ACOS                    ENVELOPE                MASTER_HOST
SAVEPOINT
ACTION                  EQUALS                  MASTER_LOG_FILE
SCHEMA
ADD                     ERRORS                  MASTER_LOG_POS
SCHEMAS
ADDDATE                 ESCAPE
MASTER_PASSWORD         SEC_TO_TIME
ADDTIME                 ESCAPED                 MASTER_PORT
SECOND
AES_DECRYPT             EVENTS
MASTER_POS_WAIT         SECOND_MICROSECOND
AES_ENCRYPT             EXECUTE
MASTER_SERVER_ID        SECURITY
AFTER                   EXISTS                  MASTER_SSL
SELECT
```

AGAINST exit MASTER_SSL_CA
SENSITIVE
AGGREGATE EXIT
MASTER_SSL_CAPATH SEPARATOR
ALGORITHM EXP
MASTER_SSL_CERT SERIAL
ALL EXPANSION
MASTER_SSL_CIPHER SERIALIZABLE
ALTER EXPLAIN MASTER_SSL_KEY
SESSION
alter table EXPORT_SET
MASTER_TLS_VERSION SESSION_USER
ANALYZE EXTENDED MASTER_USER
SET
AND EXTERIORRING MATCH
set option
ANY EXTRACT MAX
SHA
AREA FALSE
MAX_CONNECTIONS_PER_HOUR SHA1
AS FAST
MAX_QUERIES_PER_HOUR SHARE
ASBINARY FETCH MAX_ROWS
SHOW
ASC FIELD
MAX_UPDATES_PER_HOUR show databases
ASCII FIELDS
MAX_USER_CONNECTIONS show fields from
ASENSITIVE FILE MBRCONTAINS
show keys from

ASIN FIND_IN_SET MBRDISJOINT
show tables
ASTEXT FIRST MBREQUAL
SHUTDOWN
ASWKB FIXED MBRINTERSECTS
SIGN
ASWKT FLOAT MBROVERLAPS
SIGNED
ATAN FLOAT4 MBRTOUCHES
SIMPLE
ATAN2 FLOAT8 MBRWITHIN
SIN
AUTO_INCREMENT FLOOR MD5
SLAVE
AVG FLUSH MEDIUM
SLEEP
AVG_ROW_LENGTH FOR MEDIUMBLOB
SMALLINT
BACKUP FORCE MEDIUMINT
SNAPSHOT
BDB FOREIGN MEDIUMTEXT
SOME
BEFORE FORMAT MERGE
SONAME
BEGIN FOUND MICROSECOND
SOUNDEX
BENCHMARK FOUND_ROWS MID
SOUNDS
BERKELEYDB FROM MIDDLEINT
source

BETWEEN FROM_DAYS MIGRATE
SPACE
BIGINT FROM_UNIXTIME MIN
SPATIAL
BIN FULL MIN_ROWS
SPECIFIC
BINARY FULLTEXT MINUTE
SQL
BINLOG FUNCTION
MINUTE_MICROSECOND SQL_BIG_RESULT
BIT GEOMCOLLFROMTEXT
MINUTE_SECOND SQL_BUFFER_RESULT
BIT_AND GEOMCOLLFROMWKB
MLINEFROMTEXT SQL_CACHE
BIT_COUNT GEOMETRY
MLINEFROMWKB SQL_CALC_FOUND_ROWS
BIT_LENGTH GEOMETRYCOLLECTION MOD
SQL_NO_CACHE
BIT_OR GEOMETRYCOLLECTIONFROMTEXT
MODE SQL_SMALL_RESULT
BIT_XOR GEOMETRYCOLLECTIONFROMWKB
MODIFIES SQL_THREAD
BLOB GEOMETRYFROMTEXT MODIFY
SQL_TSI_DAY
BOOL GEOMETRYFROMWKB MONTH
SQL_TSI_HOUR
BOOLEAN GEOMETRYN MONTHNAME
SQL_TSI_MINUTE
BOTH GEOMETRYTYPE
MPOINTFROMTEXT SQL_TSI_MONTH

BTREE GEOMFROMTEXT MPOINTFROMWKB SQL_TSI_QUARTER
BY GEOMFROMWKB MPOLYFROMTEXT SQL_TSI_SECOND
BYTE GET_FORMAT MPOLYFROMWKB SQL_TSI_WEEK
CACHE GET_LOCK MULTILINESTRING SQL_TSI_YEAR
CALL GLENGTH MULTILINESTRINGFROMTEXT SQLEXCEPTION
CASCADE GLOBAL MULTILINESTRINGFROMWKB SQLSTATE
CASCADED go MULTIPOINT SQLWARNING
CASE GRANT MULTIPOINTFROMTEXT SQRT
CAST GRANTS MULTIPOINTFROMWKB SRID
CEIL GREATEST MULTIPOLYGON SSL
CEILING GROUP MULTIPOLYGONFROMTEXT START
CENTROID GROUP_CONCAT MULTIPOLYGONFROMWKB STARTING
CHAIN GROUP_UNIQUE_USERS MUTEX STARTPOINT
CHANGE HANDLER mysql status
CHANGED HASH NAME STATUS

CHAR HAVING NAME_CONST STD
CHAR_LENGTH help NAMES STDDEV
CHARACTER HELP NATIONAL STDDEV_POP
CHARACTER_LENGTH HEX NATURAL STDDEV_SAMP
CHARSET HIGH_PRIORITY NCHAR STOP
charset HOSTS NDB STORAGE
CHECK HOUR NDBCLUSTER STR_TO_DATE
CHECKSUM HOUR_MICROSECOND NEW STRAIGHT_JOIN
CIPHER HOUR_MINUTE NEXT STRCMP
clear HOUR_SECOND NO STRING
CLIENT IDENTIFIED NO_WRITE_TO_BINLOG STRIPED
CLOSE IF NONE SUBDATE
COALESCE IFNULL nopager SUBJECT
CODE IGNORE NOT SUBSTR
COERCIBILITY IMPORT notee SUBSTRING

COLLATE IN NOW SUBSTRING_INDEX
COLLATION INDEX nowarning SUBTIME
COLUMN INDEXES NULL SUM
COLUMNS INET_ATON NULLIF SUPER
COMMENT INET_NTOA NUMERIC SUSPEND
COMMIT INFILE NUMGEOMETRIES sys
COMMITTED information_schema NUMINTERIORRINGS SYSDATE
COMPACT INNER NUMPOINTS system
COMPRESS INNOBASE NVARCHAR SYSTEM_USER
COMPRESSED INNODB OCT TABLE
CONCAT INOUT OCTET_LENGTH TABLES
CONCAT_WS INSENSITIVE OFFSET TABLESPACE
CONCURRENT INSERT ON TAN
CONDITION INSERT_METHOD ONE tee
connect INSTR ONE_SHOT TEMPORARY

CONNECTION INT OPEN TEMPTABLE
CONNECTION_ID INT1 OPTIMIZE TERMINATED
CONSISTENT INT2 OPTION TEXT
CONSTRAINT INT3 OPTIONALLY THEN
CONTAINS INT4 OR TIME
CONTINUE INT8 ORD TIME_FORMAT
CONV INTEGER ORDER TIME_TO_SEC
CONVERT INTERIORRINGN OUT TIMEDIFF
CONVERT_TZ INTERSECTS OUTER TIMESTAMP
COS INTERVAL OUTFILE TIMESTAMPADD
COT INTO OVERLAPS TIMESTAMPDIFF
COUNT INVOKER PACK_KEYS TINYBLOB
CRC32 IO_THREAD pager TINYINT
CREATE IS PARTIAL TINYTEXT
create database IS_FREE_LOCK PASSWORD TO

create table IS_USED_LOCK
performance_schema TO_DAYS
CROSS ISCLOSED PERIOD_ADD
TOUCHES
CROSSES ISEMPTY PERIOD_DIFF
TRAILING
CUBE ISNULL PHASE
TRANSACTION
CURDATE ISOLATION PI
TRIGGER
CURRENT_DATE ISSIMPLE POINT
TRIGGERS
CURRENT_TIME ISSUER
POINTFROMTEXT TRIM
CURRENT_TIMESTAMP ITERATE
POINTFROMWKB TRUE
CURRENT_USER JOIN POINTN
TRUNCATE
CURSOR JSON_ARRAY
POLYFROMTEXT TYPE
CURTIME JSON_ARRAY_APPEND
POLYFROMWKB TYPES
DAE JSON_CONTAINS POLYGON
UCASE
DATA JSON_CONTAINS_PATH
POLYGONFROMTEXT UNCOMMITTED
DATABASE JSON_DEPTH
POLYGONFROMWKB UNCOMPRESS
DATABASES JSON_EXTRACT POSITION
UNCOMPRESSED_LENGTH

DATE JSON_INSERT POW UNDEFINED
DATE_ADD JSON_KEYS POWER UNDO
DATE_FORMAT JSON_LENGTH PRECISION UNHEX
DATE_SUB JSON_MERGE PREPARE UNICODE
DATEDIFF JSON_QUOTE PREV UNION
DATETIME JSON_REPLACE PRIMARY UNIQUE
DAY JSON_ROWOBJECT print UNIQUE_USERS
DAY_HOUR JSON_SEARCH PRIVILEGES UNIX_TIMESTAMP
DAY_MICROSECOND JSON_SET PROCEDURE UNKNOWN
DAY_MINUTE JSON_TYPE PROCESS UNLOCK
DAY_SECOND JSON_UNQUOTE PROCESSLIST unlock tables
DAYNAME JSON_VALID prompt UNSIGNED
DAYOFMONTH KEY PURGE UNTIL
DAYOFWEEK KEYS QUARTER UPDATE
DAYOFYEAR KILL QUERY UPGRADE

DEALLOCATE LANGUAGE QUICK
UPPER
DEC LAST quit USAGE
DECIMAL LAST_DAY QUOTE
use
DECLARE LAST_INSERT_ID RADIANS
USE
DECODE LCASE RAND
USE_FRM
DEFAULT LEADING READ
USER
DEFINER LEAST READS
USER_RESOURCES
DEGREES LEAVE REAL
USING
DELAY_KEY_WRITE LEAVES RECOVER
UTC_DATE
DELAYED LEFT REDUNDANT
UTC_TIME
DELETE LENGTH REFERENCES
UTC_TIMESTAMP
delimiter LEVEL REGEXP
UUID
DES_DECRYPT LIKE rehash
VALUE
DES_ENCRYPT LIMIT RELAY_LOG_FILE
VALUES
DES_KEY_FILE LINEFROMTEXT
RELAY_LOG_POS VAR_POP

DESC LINEFROMWKB RELAY_THREAD VAR_SAMP
DESCRIBE LINES RELEASE VARBINARY
DETERMINISTIC LINESTRING RELEASE_LOCK VARCHAR
DIMENSION LINESTRINGFROMTEXT RELOAD VARCHARACTER
DIRECTORY LINESTRINGFROMWKB RENAME VARIABLES
DISABLE LN REPAIR VARIANCE
DISCARD LOAD REPEAT VARYING
DISJOINT load data from REPEATABLE VERSION
DISTINCT LOAD_FILE REPLACE VIEW
DISTINCTROW LOCAL REPLICATION warnings
DIV LOCALTIME REQUIRE WARNINGS
DO LOCALTIMESTAMP RESET WEEK
DOUBLE LOCATE resetconnection WEEKDAY
DROP LOCK RESTORE WEEKOFYEAR
DUAL lock tables RESTRICT WHEN

DUMPFILE LOCKS RESUME WHERE
DUPLICATE LOG RETURN WHILE
DYNAMIC LOG10 RETURNS WITH
EACH LOG2 REVERSE WITHIN
edit LOGS REVOKE WORK
ego LONG RIGHT WRITE
ELSE LONGBLOB RLIKE X
ELSEIF LONGTEXT ROLLBACK X509
ELT LOOP ROLLUP XA
ENABLE LOW_PRIORITY ROUND XOR
ENCLOSED LOWER ROUTINE Y
ENCODE LPAD ROW YEAR
ENCRYPT LTRIM ROW_COUNT YEAR_MONTH
END MAKE_SET ROW_FORMAT YEARWEEK
ENDPOINT MAKEDATE ROWS ZEROFILL
ENGINE MAKETIME RPAD

```
    -> ;
Empty set (0.00 sec)
mysql> show databases;
+--------------------+
| Database           |
+--------------------+
| DAE                |
| information_schema |
| mysql              |
| performance_schema |
| sys                |
+--------------------+
5 rows in set (0.01 sec)
mysql> use dae;
Database changed
mysql> select * from animal;
Empty set (0.00 sec)
mysql> INSERT INTO animal (reptiles, mammals,
ancient_dinosaurs, fantasy ) VALUES ("Snake", "Human",
"Dinosaur", "Unicorn" );
ERROR 1054 (42S22): Unknown column 'ancient_dinosaurs' in
'field list'
mysql> desc animal
-> ;
+------------------+-------------+------+-----+---------+-------+
| Field            | Type        | Null | Key | Default | Extra |
+------------------+-------------+------+-----+---------+-------+
| mammals          | varchar(30) | NO   | PRI | NULL    |       |
| reptiles         | varchar(20) | YES  |     | NULL    |       |
| ancient_dinasours | varchar(25) | YES  |     | NULL    |       |
```

```
| fantasy           | varchar(15) | YES  |     | NULL    |       |
+------------------+------------+------+-----+---------+-------+
4 rows in set (0.01 sec)
mysql> INSERT INTO animal (reptiles, mammals,
ancient_dinosours, fantasy ) VALUES ("Snake", "Human",
"Dinosaur", "Unicorn" );
ERROR 1054 (42S22): Unknown column 'ancient_dinosours' in
'field list'
mysql> INSERT INTO animal (reptiles, mammals,
ancient_dinasours, fantasy ) VALUES ("Snake", "Human",
"Dinosaur", "Unicorn" );
Query OK, 1 row affected (0.00 sec)
mysql> INSERT INTO animal (reptiles, mammals,
ancient_dinasours, fantasy ) VALUES ("Snake", "Human", "Dino",
"Shark" );
ERROR 1062 (23000): Duplicate entry 'Human' for key
'animal.PRIMARY'
mysql> INSERT INTO animal (reptiles, mammals,
ancient_dinasours, fantasy ) VALUES ("Snake", "Sami", "Dino",
"Shark" );
Query OK, 1 row affected (0.00 sec)
mysql> select * from animal
    -> ;
+---------+----------+------------------+---------+
| mammals | reptiles | ancient_dinasours | fantasy |
+---------+----------+------------------+---------+
| Human   | Snake    | Dinosaur         | Unicorn |
| Sami    | Snake    | Dino             | Shark   |
+---------+----------+------------------+---------+
2 rows in set (0.01 sec)
```

```
mysql> desc animal
    -> ;
+------------------+------------+------+-----+---------+-------+
| Field            | Type       | Null | Key | Default | Extra |
+------------------+------------+------+-----+---------+-------+
| mammals          | varchar(30) | NO   | PRI | NULL    |       |
| reptiles         | varchar(20) | YES  |     | NULL    |       |
| ancient_dinasours | varchar(25) | YES  |     | NULL    |       |
| fantasy          | varchar(15) | YES  |     | NULL    |       |
+------------------+------------+------+-----+---------+-------+
4 rows in set (0.01 sec)
mysql> desc daetable
    -> ;
ERROR 2006 (HY000): MySQL server has gone away
No connection. Trying to reconnect...
ERROR 2002 (HY000): Can't connect to local MySQL server
through socket '/Applications/MAMP/tmp/mysql/mysql.sock' (2)
ERROR:
Can't connect to the server
mysql> desc daetable
    -> ;
No connection. Trying to reconnect...
ERROR 2002 (HY000): Can't connect to local MySQL server
through socket '/Applications/MAMP/tmp/mysql/mysql.sock' (2)
ERROR:
Can't connect to the server
mysql> desc DAETABLE
    -> ;
No connection. Trying to reconnect...
Connection id:    9
```

```
Current database: dae
+---------+------------+------+-----+---------+-------+
| Field   | Type       | Null | Key | Default | Extra |
+---------+------------+------+-----+---------+-------+
| id      | int        | NO   | PRI | NULL    |       |
| FName   | varchar(15) | YES  |     | NULL    |       |
| LName   | varchar(15) | YES  |     | NULL    |       |
| AGE     | int        | YES  |     | NULL    |       |
| emailId | varchar(30) | YES  |     | NULL    |       |
+---------+------------+------+-----+---------+-------+
5 rows in set (0.01 sec)
mysql> show daetable;
ERROR 2006 (HY000): MySQL server has gone away
No connection. Trying to reconnect...
Connection id:    390
Current database: dae
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'daetable' at line 1
mysql> show databases;
+--------------------+
| Database           |
+--------------------+
| DAE                |
| information_schema |
| mysql              |
| performance_schema |
| studyplanner       |
| sys                |
+--------------------+
```

```
6 rows in set (0.00 sec)
mysql> use DAE
Reading table information for completion of table and column
names
You can turn off this feature to get a quicker startup with -A
Database changed
mysql> select * from animal;
+---------+----------+------------------+---------+
| mammals | reptiles | ancient_dinasours | fantasy |
+---------+----------+------------------+---------+
| Human   | Snake    | Dinosaur         | Unicorn |
| Sami    | Snake    | Dino             | Shark   |
+---------+----------+------------------+---------+
2 rows in set (0.00 sec)
mysql> select * from daetable;
+----+-------+----------+------+---------+
| id | FName | LName    | AGE  | emailId |
+----+-------+----------+------+---------+
|  1 | SAMI  | DHANAPAL |   15 | NULL    |
|  2 | IDA   | YOHANNES |   16 | NULL    |
+----+-------+----------+------+---------+
2 rows in set (0.00 sec)
mysql> INSERT INTO daetable (id, FName, LName, AGE,
emailId) VALUES ("3", "ABHINAV", "PIRATLA", "18",
abhinav@gmail.com");
    "> :wq
:wq
^C
```

```
mysql> INSERT INTO daetable (id, FName, LName, AGE,
emailId) VALUES ("3", "ABHINAV", "PIRATLA", "18",
"abhinav@gmail.com");
Query OK, 1 row affected (0.01 sec)
mysql> select * from daetable;
+----+---------+----------+------+------------------+
| id | FName   | LName    | AGE  | emailId          |
+----+---------+----------+------+------------------+
|  1 | SAMI    | DHANAPAL |   15 | NULL             |
|  2 | IDA     | YOHANNES |   16 | NULL             |
|  3 | ABHINAV | PIRATLA  |   18 | abhinav@gmail.com |
+----+---------+----------+------+------------------+
3 rows in set (0.00 sec)
mysql> select * from animals;
ERROR 1146 (42S02): Table 'dae.animals' doesn't exist
mysql> show databases;
+--------------------+
| Database           |
+--------------------+
| DAE                |
| information_schema |
| mysql              |
| performance_schema |
| studyplanner       |
| sys                |
+--------------------+
6 rows in set (0.00 sec)
mysql> use DAE;
Reading table information for completion of table and column
names
```

```
You can turn off this feature to get a quicker startup with -A
Database changed
mysql> select * from animals;
ERROR 1146 (42S02): Table 'dae.animals' doesn't exist
mysql> select * from animal;
+---------+----------+------------------+---------+
| mammals | reptiles | ancient_dinasours | fantasy |
+---------+----------+------------------+---------+
| Human   | Snake    | Dinosaur         | Unicorn |
| Sami    | Snake    | Dino             | Shark   |
+---------+----------+------------------+---------+
2 rows in set (0.00 sec)
mysql> INSERT INTO animal (reptiles, mammals,
ancient_dinasours, fantasy ) VALUES ("lizard", "goat", "T-rex",
"Dragon" );
Query OK, 1 row affected (0.00 sec)
mysql> select * from animal;
+---------+----------+------------------+---------+
| mammals | reptiles | ancient_dinasours | fantasy |
+---------+----------+------------------+---------+
| goat    | lizard   | T-rex            | Dragon  |
| Human   | Snake    | Dinosaur         | Unicorn |
| Sami    | Snake    | Dino             | Shark   |
+---------+----------+------------------+---------+
3 rows in set (0.01 sec)
mysql> show databases;
+-------------------+
| Database          |
+-------------------+
| DAE               |
```

```
| information_schema |
| mysql              |
| performance_schema |
| studyplanner       |
| sys                |
+--------------------+
6 rows in set (0.00 sec)
mysql> select * from about-friends;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near '-friends' at line 1
mysql> create table friends;
ERROR 4028 (HY000): A table must have at least one visible
column.
mysql> create table
    -> ;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near '' at line 1
mysql> create table animal (ID int primary key, FName
varchar(20), age varchar(25), grade varchar(15));
ERROR 1050 (42S01): Table 'animal' already exists
mysql> CREATE TABLE DAETABLE (id INT PRIMARY KEY,
FName VARCHAR(15), LName VARCHAR(15),AGE INT);
ERROR 1050 (42S01): Table 'daetable' already exists
mysql> Query OK, 0 rows affected (0.02 sec)
    -> hjk
    -> ;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
```

```
for the right syntax to use near 'Query OK, 0 rows affected (0.02
sec)
hjk' at line 1
mysql> CREATE TABLE FRIENDS (id INT PRIMARY KEY,
FName VARCHAR(15), LName VARCHAR(15),AGE INT);
Query OK, 0 rows affected (0.03 sec)
mysql> SHOW TABLE;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near '' at line 1
mysql> SHOW TABLES;
+---------------+
| Tables_in_dae |
+---------------+
| animal        |
| DAETABLE      |
| FRIENDS       |
+---------------+
3 rows in set (0.00 sec)
mysql> INSERT INTO FRIENDS (id, FName, LName, AGE )
VALUES ("1", "Sami", "Dhanapal", "14" );
Query OK, 1 row affected (0.01 sec)
mysql> INSERT INTO FRIENDS (id, FName, LName, AGE )
VALUES ("2", "IDA", "YOHANNES", "16" );
Query OK, 1 row affected (0.00 sec)
mysql> select * from FRIENDS
    -> ;
+----+-------+----------+------+
| id | FName | LName    | AGE  |
+----+-------+----------+------+
```

```
|  1 | Sami  | Dhanapal |   14 |
|  2 | IDA   | YOHANNES |   16 |
+----+-------+----------+------+
2 rows in set (0.00 sec)
mysql> INSERT INTO FRIENDS (id, FName, LName, AGE )
VALUES ("3", "MANVITHA", "PEELA", "15" );
Query OK, 1 row affected (0.01 sec)
mysql> INSERT INTO FRIENDS (id, FName, LName, AGE )
VALUES ("4", "PRISHA", "JILHEWAR", "15" );
Query OK, 1 row affected (0.01 sec)
mysql> INSERT INTO FRIENDS (id, FName, LName, AGE )
VALUES ("5", "ABI", "ESQUIVEL", "15" );
Query OK, 1 row affected (0.01 sec)
mysql> SELELCT * FROM FRIENDS
    -> ;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'SELELCT * FROM FRIENDS' at
line 1
mysql> select * from FRIENDS;
+----+----------+----------+------+
| id | FName    | LName    | AGE  |
+----+----------+----------+------+
|  1 | Sami     | Dhanapal |   14 |
|  2 | IDA      | YOHANNES |   16 |
|  3 | MANVITHA | PEELA    |   15 |
|  4 | PRISHA   | JILHEWAR |   15 |
|  5 | ABI      | ESQUIVEL |   15 |
+----+----------+----------+------+
5 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE FRIENDS (id INT PRIMARY KEY, NAME
VARCHAR(15), VEGE OR FRUIT VARCHAR(15), YUMMY
VARCHAR(3));
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'OR FRUIT VARCHAR(15),
YUMMY VARCHAR(3))' at line 1
mysql> CREATE TABLE FRIENDS (id INT PRIMARY KEY, NAME
VARCHAR(15), VEGE OR FRUIT VARCHAR(15), YUMMY
VARCHAR(3));
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'OR FRUIT VARCHAR(15),
YUMMY VARCHAR(3))' at line 1
mysql> CREATE TABLE FRIENDS (id INT PRIMARY KEY, NAME
VARCHAR(15), VEGE_OR_FRUIT VARCHAR(15), YUMMY
VARCHAR(3))
    -> ;
ERROR 1050 (42S01): Table 'friends' already exists
mysql> CREATE TABLE FOOD (id INT PRIMARY KEY, NAME
VARCHAR(15), VEGE OR FRUIT VARCHAR(15), YUMMY
VARCHAR(3))
    -> ;
ERROR 1064 (42000): You have an error in your SQL syntax;
check the manual that corresponds to your MySQL server version
for the right syntax to use near 'OR FRUIT VARCHAR(15),
YUMMY VARCHAR(3))' at line 1
mysql> CREATE TABLE FRIENDS (id INT PRIMARY KEY, NAME
VARCHAR(15), VEGE_OR_FRUIT VARCHAR(15), YUMMY
VARCHAR(3))
```

```
    -> ;
ERROR 1050 (42S01): Table 'friends' already exists
mysql> CREATE TABLE FOOD (id INT PRIMARY KEY, NAME
VARCHAR(15), VEGE_OR_FRUIT VARCHAR(15), YUMMY
VARCHAR(3))
    -> ;
Query OK, 0 rows affected (0.01 sec)
mysql> INSERT INTO FRIENDS (id, NAME, VEGE_OR_FRUIT,
YUMMY ) VALUES ("1", "TOMAMTO", "FRUIT", "NO" );
ERROR 1054 (42S22): Unknown column 'NAME' in 'field list'
mysql> INSERT INTO FOOD (id, NAME, VEGE_OR_FRUIT,
YUMMY ) VALUES ("1", "TOMAMTO", "FRUIT", "NO" );
Query OK, 1 row affected (0.01 sec)
mysql> INSERT INTO FOOD (id, NAME, VEGE_OR_FRUIT,
YUMMY ) VALUES ("2", "APPLE", "FRUIT", "YES" );
Query OK, 1 row affected (0.01 sec)
mysql> INSERT INTO FOOD (id, NAME, VEGE_OR_FRUIT,
YUMMY ) VALUES ("3", "POTATO", "VEGE", "YES" );
Query OK, 1 row affected (0.00 sec)
mysql> select * from food;
+----+---------+---------------+-------+
| id | NAME    | VEGE_OR_FRUIT | YUMMY |
+----+---------+---------------+-------+
|  1 | TOMAMTO | FRUIT         | NO    |
|  2 | APPLE   | FRUIT         | YES   |
|  3 | POTATO  | VEGE          | YES   |
+----+---------+---------------+-------+
3 rows in set (0.00 sec)
mysql>
```