SPRINGBOOT

COMPONENT

BankAccount.java × BankAccountManagementApplication.java application.prop

```java
package com.example.BankAccountManagement;

import org.springframework.stereotype.Component;

@Component
public class BankAccount {

    public int account_number;  2 usages
    public String account_holder;  2 usages
    public String account_type;  2 usages
    public double account_balance;  2 usages

    public void display_details() {  1 usage

        System.out.println("Account Number: " + account_number);
        System.out.println("Account Holder: " + account_holder);
        System.out.println("Account Type: " + account_type);
        System.out.println("Account Balance: " + account_balance);
    }
}
```

BankAccount.java | BankAccountManagementApplication.java | application.properties

```java
package com.example.BankAccountManagement;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;

@SpringBootApplication
public class BankAccountManagementApplication {

    public static void main(String[] args) {

        ApplicationContext context =
                SpringApplication.run(BankAccountManagementApplication.class, args);

        BankAccount b = context.getBean(BankAccount.class);

        b.account_number = 10001;
        b.account_holder = "Samin";
        b.account_type = "Savings";
        b.account_balance = 25000.50;

        b.display_details();
    }
}
```

OUTPUT

```
Account Number: 10001
Account Holder: Samin
Account Type: Savings
Account Balance: 25000.5
```