SCOPE

SINGLETON

Student.java | TasksingletonApplication.java

```java
package com.example.Tasksingleton;
import org.springframework.context.annotation.Scope;
import org.springframework.stereotype.Component;
@Component
@Scope("singleton")
public class Student {
    int Student_id;  4 usages
    int roll_no;  4 usages
    String student_name;  4 usages
    String student_department;  4 usages

    public void display_details() {  2 usages
        System.out.println();
        System.out.println("Student id: " + Student_id);
        System.out.println("Roll no: " + roll_no);
        System.out.println("Student name: " + student_name);
        System.out.println("Department: " + student_department);

    }

}
```

```java
package com.example.Tasksingleton;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;

@SpringBootApplication
public class TasksingletonApplication {

    public static void main(String[] args) {

        ApplicationContext context =
                SpringApplication.run(TasksingletonApplication.class, args);

        Student s = context.getBean(Student.class);

        s.Student_id = 1001;
        s.roll_no = 220002;
        s.student_name = "SaminSathik";
        s.student_department = "BCA";

        Student s1 = context.getBean(Student.class);
```

```java
        Student s = context.getBean(Student.class);

        s.Student_id = 1001;
        s.roll_no = 220002;
        s.student_name = "SaminSathik";
        s.student_department = "BCA";

        Student s1 = context.getBean(Student.class);

        s1.Student_id = 1002;
        s1.roll_no = 220003;
        s1.student_name = "Kuthubudeen";
        s1.student_department = "IT";

        s1.display_details();
        s.display_details();
    }
}
```

TasksingletonApplication ×

OUTPUT

```
Student id: 1002
Roll no: 220003
Student name: Kuthubudeen
Department: IT
```