LANDLORDLEDGER · BUILD IT · EP. 2 · FREE CHECKLIST

ATTIC MOISTURE CHECK

Stop shower steam from rotting your roof deck.

BATHROOM FANS

- [ ] Turn the fan on: it holds a square of toilet paper against the grille
- [ ] Fan runs quietly; no rattles, no dust-clogged grille
- [ ] Run the fan about 20 minutes after every shower (a timer switch helps)

IN THE ATTIC

- [ ] Follow each fan duct: it must END at a roof or wall vent, not in the insulation
- [ ] Duct is connected, not crushed, sagging, or torn
- [ ] Roof boards above bathrooms: no dark stains, no mold spots
- [ ] In winter: no frost on nail tips or roof boards
- [ ] Insulation dry, not packed against eave (soffit) vents

OUTSIDE

- [ ] Vent cap/flap opens when the fan runs and closes when off
- [ ] Roof and soffit vents clear of nests and debris

CALL A PRO IF

- [ ] Mold patches bigger than a small spot, soft wood, or a musty attic smell
- [ ] **BONUS: the 2-inch ceiling gap that leaks heat: revealed in Build It · Ep. 3**

General information only, not legal, tax, financial, or professional advice. Rules vary by state and city.
Free to use and share · Build It · Ep. 2