



Order Management

[Back to Order Management](#)

How to link wsh_delivery_details table with doo_fulfill_lines_all



Received Response 218 Views 9 Comments



Andrej Toth Vano-Oracle Member

Jun 8, 2022 2:34PM 9 comments

Summary: what is correct join between wsh_delivery_details table and doo_fulfill_lines_all

Content (required):

I have one order line with 3 fulfillment lines.

Select dfl.fulfill_line_number

from wsh_delivery_details wdd

join doo_fulfill_lines_all dfl on (

dfl.fulfill_line_id = wdd.source_shipment_id

)

where

is always pointing to dfl.fulfill_line_number = 1

Version (include the version you are using, if applicable):

22B

Code Snippet (add any code snippets that support your topic, if applicable):Tagged: [Order Management](#)

Flag

Quote

Like

Answers

**Vinod Arramalla-Oracle** Bronze Medal**Jun 8, 2022 2:59PM**

Since you did not pass the order number / header id to the query it is getting fulfillment lines from all the orders and thus showing the result. Please check the below query and see if you are getting the desired result.

```
Select dfl.fulfill_line_number , dha.header_id , dha.order_number
```

```
from wsh_delivery_details wdd
```

```
, doo_fulfill_lines_all dfl
```

```
, doo_headers_all dha
```

```
where dfl.fulfill_line_id = wdd.source_shipment_id
```

```
and dha.header_id = dfl.header_id
```

```
and dha.order_number = <order_number>
```

Flag

Quote

Like

**Andrej Toth Vano-Oracle** Member**Jun 8, 2022 3:56PM**

Thank You Vinod.

Your query is returning always fulfill_line_number = 1

```
Select dfl. fulfill_line_number dfl_ fulfill_line_number
```

```
, dha.header_id dha_header_id
```

```
, dha.order_number dha_order_number
```

```
, dfl.shipped_qty dfl_shipped_qty
```

```
, wdd.shipped_quantity wdd_shipped_quantity
```

```
from wsh_delivery_details wdd
```

```
, doo_ fulfill_lines_all dfl
```

```
, doo_headers_all dha
```

```
where dfl. fulfill_line_id = wdd.source_shipment_id
```

```
and dha.header_id = dfl.header_id
```

```
and dha.order_number = '10000238'
```

```
and wdd.source_line_number = 5
```

```
;
```

DFL_FULFILL_LINE_NUMBER	DHA_HEADER_ID	DHA_ORDER_NUMBER	DFL_SHIPPED_QTY	WDD_SHIPPED_QUANTITY
1	300000049438369	10000238	500	500
1	300000049438369	10000238	500	500
1	300000049438369	10000238	500	500
1	300000049438369	10000238	500	1000
1	300000049438369	10000238	500	500
1	300000049438369	10000238	500	500
1	300000049438369	10000238	500	500

There are 3 fulfillment lines

1- qty 500

2- qty 2500

3- qty 1000

Following SQL is showing the issue.

```
select dha.order_number dha_order_number
```

```
, dla.line_number dla_line_number
```

```
, dfl. fulfill_line_number dfl_ fulfill_line_number
```

```
, dfl.shipped_qty dfl_shipped_qty

, wdd.delivery_detail_id wdd_delivery_detail_id

, wdd.shipped_quantity wdd_shipped_quantity

from doo_headers_all dha

, doo_lines_all dla

, doo_fulfill_lines_all dfl

, wsh_delivery_details wdd

where 1=1

and dha.order_number = '10000238'

AND dha.status_code <> 'DOO_REFERENCE'

AND dha.Submitted_Flag = 'Y'

and dla.header_id = dha.header_id

and dla.line_number = 5

and dfl.line_id = dla.line_id

and wdd.source_shipment_id(+) = dfl.fulfill_line_id
```

order by dfl.fulfill_line_number

DHA_ORDER..	DLA_LINE_NUMBER	DFL_FULFILL_LINE_NUMBER	DFL_SHIPPED_QTY	WDD_DELIVERY_DETAIL_ID	WDD_SHIPPED_QUANTITY
10000238	5	1	500	24010	500
10000238	5	1	500	96002	500
10000238	5	1	500	630034	500
10000238	5	1	500	630038	1000
10000238	5	1	500	630039	500
10000238	5	1	500	630040	500
10000238	5	1	500	1111065	500
10000238	5	2	2500		
10000238	5	3	1000		

Thank You,

Andrej

Flag

 Quote

Like

**Vinod Arramalla-Oracle** Bronze Medal**Jun 9, 2022 11:29AM**

Ok Andrej, I understand you have a requirement to fetch all fulfillment lines for which delivery lines have not been created as well

In that case yes, we need to put outer join.

and wdd.source_shipment_id(+) = dfl.fulfill_line_id

I hope your issue is resolved.

Flag

Quote

Like

**Shyam_Patel** Gold Crown**Jun 9, 2022 11:27PM**

```
SELECT DISTINCT doh.order_number,  
  
               wnd.delivery_id,  
  
               wnd.delivery_name,  
  
               dfla.fulfill_line_id,  
  
               dfla.status_code  
  
FROM   fusion.doo_headers_all doh,  
  
       fusion.doo_fulfill_lines_all dfla,  
  
       fusion.wsh_delivery_details wdd,  
  
       fusion.wsh_delivery_assignments WDA,  
  
       fusion.wsh_new_deliveries WND  
  
WHERE  wdd.delivery_detail_id = WDA.delivery_detail_id  
  
       AND WDA.delivery_id = WND.delivery_id  
  
       AND doh.header_id = dfla.header_id
```

```

AND Nvl(dfla.fulfillment_split_ref_id, dfla.fulfill_line_id) =

    wdd.source_shipment_id

AND shipment_advice_status IS NULL

AND wdd.wms_interfaced_flag = 'CONFIRMED'

AND wdd.released_status = 'C'

AND dfla.status_code IN ( 'BACKORDERED', 'AWAIT_SHIP' )

AND doh.submitted_flag = 'Y'

AND NOT EXISTS (SELECT *

                FROM  fusion.doo_fulfill_line_details FLD

                WHERE  FLD.delivery_name = WND.delivery_name);

```

=====

```

SELECT dha.source_order_number,

    wnd.delivery_id,

    dfla.status_code,

    wnd.status_code,

    Decode (wdd.released_status, 'B', 'Backordered',

        'C', 'Shipped',

        'D', 'Cancelled',

        'N', 'Not Ready for Release',

        'R', 'Ready to Release',

        'S', 'Released to Warehouse',

        'X', 'Not Applicable',

        'Y', 'Staged')  "Shipping Status",

```

dfla.source_line_number,

dog.group_id,

Decode (dog.is_group_editable, 'Y', 'For Order '

|| dha.source_order_number

||

' Run shipment Advice for Delivery for '

||

wnd.delivery_id,

'Support will work to Recover from EM for group_id : '

|| dog.group_id) "Resolution",

dog.is_group_editable,

dog.status,

wnd.ultimate_dropoff_date,

wnd.confirmed_by,

wnd.confirm_date,

wnd.actual_ship_date

FROM fusion.doo_headers_all dha,

fusion.doo_fulfill_lines_all dfla,

fusion.wsh_delivery_assignments wda,

fusion.wsh_new_deliveries wnd,

fusion.wsh_delivery_details wdd,

fusion.doo_orchestration_groups dog

WHERE DHA.header_id = DFLA.header_id

AND DFLA.fulfill_line_id = WDD.source_shipment_id

AND Wdd.delivery_detail_id = wda.delivery_detail_id

AND wda.delivery_id = wnd.delivery_id

AND wdd.released_status = 'C'

AND dfla.status_code = 'PICKED'

AND DHA.submitted_flag = 'Y'

AND dog.fulfillment_line_id = DFLA.fulfill_line_id

--and IS_GROUP_EDITABLE = 'N'

AND status = 'ACTIVE'

ORDER BY dha.source_order_number,

wnd.delivery_id,

dfla.source_line_number

Flag

Quote

1 Like



Chandrajit Bronze Trophy

Mar 15, 2023 7:13AM

EVEN with this below condition, we will not know which line in the delivery detail table is connected with which line in the fulfill detail table for partial shipment cases . So we need another join to ascertain rows from delivery details table to fulfillment details table

AND **Nvl**(dfla.fulfillment_split_ref_id, dfla.fulfill_line_id) =

wdd.source_shipment_id

Flag

Quote

Like

**Anuradha - User352 -Oracle** Gold Trophy**Mar 15, 2023 8:19AM**

Hi Chandrajit,

Split Shipment Lines created for partial shipments would still continue to point to the original fulfillment line and hence the below predicate is correct

```
AND Nvl(dfla.fulfillment_split_ref_id, dfla.fulfill_line_id) =  
      wdd.source_shipment_id
```

Kind Regards,

Anuradha

Flag



Quote

Like

**Chandrajit** Bronze Trophy**Mar 22, 2023 7:32PM**

Hi Anuradha

But if you need to select fulfillment line order qty for that split line, this join will not help. With this join also, you get the fulfillment line qty of original line.

thanks

Chandrajit

Flag



Quote

Like

**Anuradha - User352 -Oracle** Gold Trophy**Mar 24, 2023 8:13AM**

Hi Chandrajit,

Please consider using the case or decode function to get the ordered quantity on the split fulfillment line for split lines and the quantity from the original line if no splits.

```
SELECT  dfla.source_order_number          ,
        dfla.fulfillment_split_ref_id "split line",
        wdd.src_requested_quantity,
        dfla.fulfill_line_id "original line"      ,
        dfla.ordered_qty "original line qty"      ,
        dflasplit.ordered_qty "split line qty"     ,
        DECODE(dfla.fulfillment_split_ref_id , NULL,dfla.ordered_qty,dflaspl
FROM      fusion.doo_fulfill_lines_all dfla      ,
        fusion.doo_fulfill_lines_all dflasplit,
        fusion.wsh_delivery_details wdd          ,
        fusion.doo_headers_all dha
WHERE     dfla.fulfillment_split_ref_id          = dflas
        AND NVL(dfla.fulfillment_split_ref_id, dfla.fulfill_line_id) = wdd.s
        AND dfla.fulfillment_split_ref_id        IS NOT N
        AND dha.header_id                        = dfla.
        AND dha.submitted_flag                   = 'Y'

ORDER BY dfla.creation_date DESC
```



Kind Regards,

Anuradha

Flag

Quote

2 Like

**Michal Shaked** Green Ribbon**Jul 20, 2023 2:01PM**

Hi Chandrajit,

did you get any solution for the above issue?

We also have the need for each shipment line to bring some data from the relevant fulfilment line in the order and as you mentioned, all shipping lines are mapped to the original fulfillment id..

Did you find any way to connect to the new fulfillment lines after the split?

Michal.

Flag

Quote

Like

Leave a Comment

Type your comment



Save Draft

Post Comment

Search this Category

Keywords

Updated From

yyyy-mm-dd

To

yyyy-mm-dd

Authors

Tags

Search

English 日本語