



# CSE3103 : Database FALL 2020

Nazmus Sakib
Assistant Professor
Department of Computer Science and Engineering
Ahsanullah University of Science and Technology

# Classification of Physical Storage Media


- Speed with which data can be accessed
- Cost per unit of data
- Reliability
  - data loss on power failure or system crash
  - physical failure of the storage device
- Can differentiate storage into:
  - volatile storage: loses contents when power is switched off
  - non-volatile storage:
    - Contents persist even when power is switched off.
    - Includes secondary and tertiary storage, as well as batter- backed up mainmemory.

# **Physical Storage Media**

• **Cache** – fastest and most costly form of storage; volatile; managed by the computer system hardware.

#### Main memory:

- fast access (10s to 100s of nanoseconds; 1 nanosecond =  $10^{-9}$  seconds)
- generally too small (or too expensive) to store the entire database
  - capacities of up to a few Gigabytes widely used currently
  - Capacities have gone up and per-byte costs have decreased steadily and rapidly (roughly factor of 2 every 2 to 3 years)
- **Volatile** contents of main memory are usually lost if a power failure or system crash occurs.



# **Storage Hierarchy (Cont.)**


- Primary storage: Fastest media but volatile (cache, main memory).
- **Secondary storage:** next level in hierarchy, non-volatile, moderately fast access time
  - also called on-line storage
  - E.g. flash memory, magnetic disks
- **Tertiary storage:** lowest level in hierarchy, non-volatile, slow access time
  - also called off-line storage
  - E.g. magnetic tape, optical storage

# Disk Subsystem

- Disks usually connected directly to computer system
- In **Storage Area Networks (SAN)**, a large number of disks are connected by a high-speed network to a number of servers
- In **Network Attached Storage (NAS)** networked storage provides a file system interface using networked file system protocol, instead of providing a disk system interface

### **Storage Area Network**

- Common in large storage environments
- Multiple hosts attached to multiple storage arrays flexible




# Storage Area Network (Cont.)

- SAN is one or more storage arrays
  - Connected to one or more Fibre Channel switches
- Hosts also attach to the switches
- Storage made available via **LUN Masking** from specific arrays to specific servers
- Easy to add or remove storage, add new host and allocate it storage
  - Over low-latency Fibre Channel fabric
- Why have separate storage networks and communications networks?
  - Consider iSCSI, FCOE

### **Network-Attached Storage**

- Network-attached storage (NAS) is storage made available over a network rather than over a local connection (such as a bus)
  - Remotely attaching to file systems



# **Network-Attached Storage**

- NFS and CIFS are common protocols
- Implemented via remote procedure calls (RPCs) between host and storage over typically TCP or UDP on IP network
- iSCSI protocol uses IP network to carry the SCSI protocol
  - Remotely attaching to devices (blocks)

