

CMP_SC 3050: Heaps

Rohit Chadha

September 4, 2014

Heaps

A heap is a **nearly complete** binary tree:

- The tree is completely filled except at the lowest level
- At the lowest level, the tree must be filled from the left upto a point


In addition, a heap must satisfy one of the following properties

- 1 **Max-heap property:** The value stored at every node must be **greater** than the value stored in its children

OR


- 2 **Min-heap property:** The value stored at every node must be **less** than the value stored in its children

Example




Convert a nearly complete binary tree to a max-heap

- First consider the case that at only one node the value stored is less than its children




Convert a nearly complete binary tree to a max-heap

- First consider the case that at only one node the value stored is less than its children
- Swap the value at this node with the larger value of its children




Convert a nearly complete binary tree to a max-heap

- First consider the case that at only one node the value stored is less than its children
- Swap the value at this node with the larger value of its children




Convert a nearly complete binary tree to a max-heap

- First consider the case that at only one node the value stored is less than its children
- Swap the value at this node with the larger value of its children
- The resulting tree may not be a heap, but the error occurs at a **lower** level




Convert a nearly complete binary tree to a max-heap

- First consider the case that at only one node the value stored is less than its children
- Swap the value at this node with the larger value of its children
- The resulting tree may not be a heap, but the error occurs at a **lower** level
- Continue until you get a proper heap




Convert a nearly complete binary tree to a max-heap

- First consider the case that at only one node the value stored is less than its children
- Swap the value at this node with the larger value of its children
- The resulting tree may not be a heap, but the error occurs at a **lower** level
- Continue until you get a proper heap




Convert a nearly complete binary tree to a max-heap

- First consider the case that at only one node the value stored is less than its children
- Swap the value at this node with the larger value of its children
- The resulting tree may not be a heap, but the error occurs at a **lower** level
- Continue until you get a proper heap
- This procedure is called **MAX-HEAPIFY**



Convert a nearly complete binary tree to a max-heap

- First consider the case that at only one node the value stored is less than its children
- Swap the value at this node with the larger value of its children
- The resulting tree may not be a heap, but the error occurs at a **lower** level
- Continue until you get a proper heap
- This procedure is called **MAX-HEAPIFY**
- What is the time complexity of Max-Heapify?
 - ▶ At each level the procedure spends a constant amount of time
 - ▶ Hence the running time is $O(h)$ if h is the height of the error



Convert a nearly complete binary tree to a max-heap continued

- Now, there might be more than one errors

Convert a nearly complete binary tree to a max-heap continued

- Now, there might be more than one errors
- Start at the bottom of the tree

Convert a nearly complete binary tree to a max-heap continued

- Now, there might be more than one errors
- Start at the bottom of the tree
- There are no errors there


Convert a nearly complete binary tree to a max-heap continued

- Now, there might be more than one errors
- Start at the bottom of the tree
- There are no errors there
- Go one level up, fix the errors at this height starting from right to left

Convert a nearly complete binary tree to a max-heap continued







- Now, there might be more than one errors
- Start at the bottom of the tree
- There are no errors there
- Go one level up, fix the errors at this height starting from right to left
- Keep going up..
- This procedure is called **BUILD-MAX-HEAP**

Example: Build-Max-Heap



(a)

Example: Build-Max-Heap



*Time complexity of BUILD-MAX-HEAP

- MAX-HEAPIFY takes $O(h)$ times on nodes at height h

*Time complexity of BUILD-MAX-HEAP

- MAX-HEAPIFY takes $O(h)$ times on nodes at height h
- There are $\lceil \frac{n}{2^{h+1}} \rceil$ nodes of height h

*Time complexity of BUILD-MAX-HEAP

- MAX-HEAPIFY takes $O(h)$ times on nodes at height h
- There are $\lceil \frac{n}{2^{h+1}} \rceil$ nodes of height h
- Therefore, the total cost of BUILD-MAX-HEAP is

$$\sum_{h=0}^{\lfloor \log n \rfloor} \lceil \frac{n}{2^{h+1}} \rceil O(h) = O(n) \sum_{h=0}^{\lfloor \log n \rfloor} O(\frac{h}{2^h})$$

*Time complexity of BUILD-MAX-HEAP

- MAX-HEAPIFY takes $O(h)$ times on nodes at height h
- There are $\lceil \frac{n}{2^{h+1}} \rceil$ nodes of height h
- Therefore, the total cost of BUILD-MAX-HEAP is

$$\sum_{h=0}^{\lfloor \log n \rfloor} \lceil \frac{n}{2^{h+1}} \rceil O(h) = O(n) \sum_{h=0}^{\lfloor \log n \rfloor} O(\frac{h}{2^h})$$

- But

$$\sum_{h=0}^{\lfloor \log n \rfloor} \frac{h}{2^h} < 2$$

*Time complexity of BUILD-MAX-HEAP

- MAX-HEAPIFY takes $O(h)$ times on nodes at height h
- There are $\lceil \frac{n}{2^{h+1}} \rceil$ nodes of height h
- Therefore, the total cost of BUILD-MAX-HEAP is

$$\sum_{h=0}^{\lfloor \log n \rfloor} \lceil \frac{n}{2^{h+1}} \rceil O(h) = O(n) \sum_{h=0}^{\lfloor \log n \rfloor} O(\frac{h}{2^h})$$

- But

$$\sum_{h=0}^{\lfloor \log n \rfloor} \frac{h}{2^h} < 2$$

- Thus MAX-HEAPIFY takes $O(n)$ time

*Time complexity of BUILD-MAX-HEAP

- MAX-HEAPIFY takes $O(h)$ times on nodes at height h
- There are $\lceil \frac{n}{2^{h+1}} \rceil$ nodes of height h
- Therefore, the total cost of BUILD-MAX-HEAP is

$$\sum_{h=0}^{\lfloor \log n \rfloor} \lceil \frac{n}{2^{h+1}} \rceil O(h) = O(n) \sum_{h=0}^{\lfloor \log n \rfloor} O(\frac{h}{2^h})$$


- But

$$\sum_{h=0}^{\lfloor \log n \rfloor} \frac{h}{2^h} < 2$$

- Thus MAX-HEAPIFY takes $O(n)$ time
- You should know the result


But how do we implement heaps?

- A heap of size n can be implemented as an **array** of size n




But how do we implement heaps?

- A heap of size n can be implemented as an **array** of size n
- We will traverse the whole heap from top level to bottom level, going from left to right at each individual level




But how do we implement heaps?

- A heap of size n can be implemented as an **array** of size n
- We will traverse the whole heap from top level to bottom level, going from left to right at each individual level
- The node visited at the i -th step will be stored at the i -th location




But how do we implement heaps?

- A heap of size n can be implemented as an **array** of size n
- We will traverse the whole heap from top level to bottom level, going from left to right at each individual level
- The node visited at the i -th step will be stored at the i -th location




But how do we implement heaps?

- A heap of size n can be implemented as an **array** of size n
- We will traverse the whole heap from top level to bottom level, going from left to right at each individual level
- The node visited at the i -th step will be stored at the i -th location
- We did this for heaps, but we can do the same thing for every nearly complete binary tree




But how do we implement heaps?

- A heap of size n can be implemented as an **array** of size n
- We will traverse the whole heap from top level to bottom level, going from left to right at each individual level
- The node visited at the i -th step will be stored at the i -th location
- We did this for heaps, but we can do the same thing for every nearly complete binary tree
 - ▶ Infact, we can consider any array as a nearly complete binary tree!




Arrays as nearly complete binary trees




Root of the tree = $A[1]$
Left child of $A[i]$ = $A[2i]$
Right child of $A[i]$ = $A[2i + 1]$
Parent of $A[i]$ = $A[\lfloor \frac{i}{2} \rfloor]$


Arrays as nearly complete binary trees



Root of the tree $= A[1]$
Left child of $A[i]$ $= A[2i]$
Right child of $A[i]$ $= A[2i + 1]$
Parent of $A[i]$ $= A[\lfloor \frac{i}{2} \rfloor]$




Arrays as nearly complete binary trees



Root of the tree = $A[1]$
Left child of $A[i]$ = $A[2i]$
Right child of $A[i]$ = $A[2i + 1]$
Parent of $A[i]$ = $A[\lfloor \frac{i}{2} \rfloor]$

LEFT[i] = $2i$
RIGHT[i] = $2i + 1$
PARENT[i] = $\lfloor \frac{i}{2} \rfloor$



Pseudocode for MAX-HEAPIFY

```
MAX-HEAPIFY( $A, i, n$ )  
   $l = \text{LEFT}(i)$   
   $r = \text{RIGHT}(i)$   
  if  $l \leq n$  and  $A[l] > A[i]$   
     $largest = l$   
  else  $largest = i$   
  if  $r \leq n$  and  $A[r] > A[largest]$   
     $largest = r$   
  if  $largest \neq i$   
    exchange  $A[i]$  with  $A[largest]$   
    MAX-HEAPIFY( $A, largest, n$ )
```

Makes the subtree rooted at $A[i]$ a heap if the subtrees rooted at $A[\text{LEFT}(i)]$ and $A[\text{RIGHT}(i)]$ are heaps

Pseudocode for BUILD-MAX-HEAP

```
BUILD-MAX-HEAP( $A, n$ )  
  for  $i = \lfloor n/2 \rfloor$  downto 1  
    MAX-HEAPIFY( $A, i, n$ )
```

Makes the nearly complete binary tree stored in $A[1..n]$ a heap

An application of Heaps: Sorting

Given an array, the Heapsort algorithm on an array A of size n acts as follows:

- Convert array A into a heap A (use BUILD-MAX-HEAPIFY)

An application of Heaps: Sorting

Given an array, the Heapsort algorithm on an array A of size n acts as follows:

- Convert array A into a heap A (use BUILD-MAX-HEAPIFY)
- The root is the maximum element. Swap it with the element in the last position in the array.

An application of Heaps: Sorting

Given an array, the Heapsort algorithm on an array A of size n acts as follows:

- Convert array A into a heap A (use BUILD-MAX-HEAPIFY)
- The root is the maximum element. Swap it with the element in the last position in the array.
- The maximum is in the correct place

An application of Heaps: Sorting

Given an array, the Heapsort algorithm on an array A of size n acts as follows:

- Convert array A into a heap A (use BUILD-MAX-HEAPIFY)
- The root is the maximum element. Swap it with the element in the last position in the array.
- The maximum is in the correct place
- The new $A[1 \dots n - 1]$ is a nearly complete binary tree

An application of Heaps: Sorting

Given an array, the Heapsort algorithm on an array A of size n acts as follows:

- Convert array A into a heap A (use BUILD-MAX-HEAPIFY)
- The root is the maximum element. Swap it with the element in the last position in the array.
- The maximum is in the correct place
- The new $A[1 \dots n - 1]$ is a nearly complete binary tree
- The $A[1 \dots n - 1]$ is also almost a heap except that the root may be smaller than its children

An application of Heaps: Sorting

Given an array, the Heapsort algorithm on an array A of size n acts as follows:

- Convert array A into a heap A (use BUILD-MAX-HEAPIFY)
- The root is the maximum element. Swap it with the element in the last position in the array.
- The maximum is in the correct place
- The new $A[1 \dots n - 1]$ is a nearly complete binary tree
- The $A[1 \dots n - 1]$ is also almost a heap except that the root may be smaller than its children
- Call MAX-HEAPIFY to make $A[1 \dots n - 1]$ a heap

An application of Heaps: Sorting

Given an array, the Heapsort algorithm on an array A of size n acts as follows:

- Convert array A into a heap A (use BUILD-MAX-HEAPIFY)
- The root is the maximum element. Swap it with the element in the last position in the array.
- The maximum is in the correct place
- The new $A[1 \dots n - 1]$ is a nearly complete binary tree
- The $A[1 \dots n - 1]$ is also almost a heap except that the root may be smaller than its children
- Call MAX-HEAPIFY to make $A[1 \dots n - 1]$ a heap
- Repeat until only one node remains

Pseudocode and analysis of heap sort

HEAPSORT(A, n)

cost

times

```
1  BUILD-MAX-HEAP( $A, n$ )
2  for  $i = n$  downto 2
3      exchange  $A[1]$  with  $A[i]$ 
4      MAX-HEAPIFY( $A, 1, i - 1$ )
```

Pseudocode and analysis of heap sort

HEAPSORT(A, n)	cost	times
1 BUILD-MAX-HEAP(A, n)	$O(n)$	1
2 for $i = n$ downto 2		
3 exchange $A[1]$ with $A[i]$		
4 MAX-HEAPIFY($A, 1, i - 1$)		

Pseudocode and analysis of heap sort

HEAPSORT(A, n)		cost	times
1	BUILD-MAX-HEAP(A, n)	$O(n)$	1
2	for $i = n$ downto 2	$O(1)$	$n - 1$
3	exchange $A[1]$ with $A[i]$		
4	MAX-HEAPIFY($A, 1, i - 1$)		

Pseudocode and analysis of heap sort

	cost	times
HEAPSORT(A, n)		
1 BUILD-MAX-HEAP(A, n)	$O(n)$	1
2 for $i = n$ downto 2	$O(1)$	$n - 1$
3 exchange $A[1]$ with $A[i]$	$O(1)$	$n - 1$
4 MAX-HEAPIFY($A, 1, i - 1$)		

Pseudocode and analysis of heap sort

HEAPSORT(A, n)		cost	times
1	BUILD-MAX-HEAP(A, n)	$O(n)$	1
2	for $i = n$ downto 2	$O(1)$	$n - 1$
3	exchange $A[1]$ with $A[i]$	$O(1)$	$n - 1$
4	MAX-HEAPIFY($A, 1, i - 1$)	$O(\log n)$	$n - 1$

Pseudocode and analysis of heap sort

HEAPSORT(A, n)		cost	times
1	BUILD-MAX-HEAP(A, n)	$O(n)$	1
2	for $i = n$ downto 2	$O(1)$	$n - 1$
3	exchange $A[1]$ with $A[i]$	$O(1)$	$n - 1$
4	MAX-HEAPIFY($A, 1, i - 1$)	$O(\log n)$	$n - 1$

Heapsort takes $O(n \log n)$ time

A new data structure: Max Priority Queues

- Like stacks, queues and lists, maintains a dynamic set
- Each element has a *key*. May have other data

Operations

$\text{INSERT}(A, x)$: inserts element x into priority queue A

$\text{MAXIMUM}(A)$: returns element of A with largest key

$\text{EXTRACT-MAX}(A)$: removes and returns element of A with largest key

$\text{INCREASE-KEY}(A, x, k)$: increases value of element x 's key to k

A new data structure: Max Priority Queues

- Like stacks, queues and lists, maintains a dynamic set
- Each element has a *key*. May have other data

Operations

$\text{INSERT}(A, x)$: inserts element x into priority queue A


$\text{MAXIMUM}(A)$: returns element of A with largest key

$\text{EXTRACT-MAX}(A)$: removes and returns element of A with largest key


$\text{INCREASE-KEY}(A, x, k)$: increases value of element x 's key to k

Can be implemented using heaps


Example INCREASE-KEY(A, x, k): Increase key 4 to 15




(a)



(b)



(c)



(d)

INCREASE-KEY(S, x, k)

HEAP-INCREASE-KEY(A, i, key)

if $key < A[i]$

error “new key is smaller than current key”

$A[i] = key$

while $i > 1$ and $A[\text{PARENT}(i)] < A[i]$

exchange $A[i]$ with $A[\text{PARENT}(i)]$

$i = \text{PARENT}(i)$

- Make sure k is bigger than x 's current key
- Update x 's key value to k
- Traverse the heap upward comparing x to its parent and swapping keys until x 's key is smaller than its parent's key

INCREASE-KEY(S, x, k)

HEAP-INCREASE-KEY(A, i, key)

if $key < A[i]$

error “new key is smaller than current key”

$A[i] = key$

while $i > 1$ and $A[\text{PARENT}(i)] < A[i]$

exchange $A[i]$ with $A[\text{PARENT}(i)]$

$i = \text{PARENT}(i)$

- Make sure k is bigger than x 's current key
- Update x 's key value to k
- Traverse the heap upward comparing x to its parent and swapping keys until x 's key is smaller than its parent's key
- Time complexity is $O(\log n)$

Conclusion

- We learnt a new useful data structure: **Heaps**
- Heaps can be used to sort in $O(n \log n)$ time
- Heaps can implement Priority Queues with insertion, deletion and changing keys operations all taking $O(\log n)$ time
- We just finished Chapter 6 of the book

Next class: We start with graph algorithms (Chapter 22)