

# Distributed motion planning for multiple vehicles transporting a flexible payload\*

SKM<sup>1</sup>, RVP<sup>2</sup> and GP<sup>2</sup>

**Abstract**—This paper deals with the development of control strategies for cooperatively transporting a flexible payload with multiple vehicles. To this end, an algorithm is developed which generates optimal trajectories for the vehicles to follow. The trajectories are parameterized using splines, and the optimization algorithm used to solve for the spline coefficients is based on an Alternating Direction Method of Multipliers (ADMM) formulation. The algorithm instructs that the optimization problem be solved repeatedly in a receding horizon fashion, making it fit into a distributed model predictive control (DMPC) framework. One ADMM iteration is performed per one DMPC iteration, reducing the inter-agent communication rate. Numerical and experimental validation of the developed control scheme is performed and the results are presented.

## I. INTRODUCTION

Payload transportation tasks are ubiquitous in industrial environments. These payloads can vary greatly in weights, necessitating multiple transportation solutions of varying payload capacities be used within the same logistics structure. An alternative to this would be to use multiple vehicles to cooperatively tow a payload, with the number of vehicles chosen as per the towing requirements. To enable such a multi-agent system to work autonomously and transport the payload to a desired location, cooperative control strategies are required. This work presents one such strategy from a motion-planning perspective. The algorithms developed within this strategy design optimal trajectories for the vehicles to follow to achieve the goal of payload transportation. These trajectories are fed to a low level controller for tracking. The generated trajectories respect various constraints presented by the dynamics of the system, individual vehicle kinematics, and avoid collisions between the vehicles. To account for dynamic disturbances, these trajectories are generated repeatedly with current initial conditions.

The trajectories result from solving an optimization problem. Since the payload transportation problem at hand is composed of multiple agents and there is no central agent with access to the states of all the transportation vehicles, the formulated optimization problem is solved in a distributed fashion. This means that each vehicle solves a local optimization problem to generate its own trajectory, and is aided by communication with other vehicles. The usual procedures for distributing an optimization problem over

multiple agents are based on optimization decomposition techniques. One such technique, dual-decomposition, is used in [1] to generate trajectories for a flight formation problem in an offline manner. In order to make the motion planning-based control robust against plant-model mismatch, it is desirable to solve the motion planning problem repeatedly. This leads the problem into a distributed model predictive control (DMPC) framework.

The formation-control problem is solved in a DMPC framework in [2], in which the optimization problem is decomposed using the Alternating Direction Method of Multipliers (ADMM) algorithm. A major difference between formation control problems and the payload transportation problem is that in the latter, the agents are dynamically coupled. This means that a change in state of one of the agents results in a change in state of the others. These coupled dynamics act as constraints on the centralized optimization problem, and decomposing the centralized problem for DMPC purposes would require decomposing the coupling dynamics constraint. Decoupling of dynamics is done using primal decomposition in [3], in which, linear systems are considered, and an optimal consensus problem is solved. In optimal consensus problems, multiple optimization variables are driven to the same value over iterations. In other words, consensus is achieved between different states of the system. Another approach based on dual decomposition, is discussed in [4]. In this, the variable splitting method is employed [1], with the introduction of copies of states of neighboring vehicles which affect local states of a host vehicle. More robust methods based on the ADMM are formulated in [5], which consider coupled objective functions in addition to coupled nonlinear dynamics.

The issue with using ADMM for DMPC is that each ADMM iteration involves solving three optimization problems, and hence each MPC iteration requires solving three times the number of ADMM iterations per MPC cycle. The problem with using the techniques proposed in [5] is that the constraints are distributed over the first and second problems, leaving them without simple closed form solutions and hence making the algorithm slow. This makes practical implementation infeasible. This is overcome in [6], where the ADMM-consensus problem introduced in [7] is combined with the idea of introducing copies of neighboring states from [8]. The proposed formulation is the closest to what is used to solve the payload transport problem in this thesis, with a modification inspired by [2] to remove the need to have a centralized controller to perform the 2nd ADMM step.

The rest of the paper is organized as follows:

\*This work was not supported by any organization

<sup>1</sup>Albert Author is with Faculty of Electrical Engineering, Mathematics and Computer Science, University of Twente, 7500 AE Enschede, The Netherlands [albert.author@papercept.net](mailto:albert.author@papercept.net)

<sup>2</sup>Bernard D. Researcher is with the Department of Electrical Engineering, Wright State University, Dayton, OH 45435, USA [b.d.researcher@ieee.org](mailto:b.d.researcher@ieee.org)

Section II introduces the motion planning problem for cooperative payload transportation problem, and Section III describes how this problem can be solved in an online distributed manner. Results from simulations based on the proposed approach are presented in Section IV, and the results from an experimental validation in Section V.

## II. PROBLEM FORMULATION

### A. System model

The system is modeled as 3 holonomic vehicles attached through 1D spring-damper elements to a common payload. The payload and the holonomic vehicles are abstracted as point masses, and are constrained to move in a 2D plane. Dynamic spring-mass-damper models are used to describe the system in the optimization problem. Friction is ignored from the model. The free length of the flexible elements is assumed to be 0m, resulting in the vehicles only applying a pulling force on the payload. A schematic of this model is shown in 1.




Fig. 1. Dynamic model decoupling

### B. Centralized formulation

The payload position is represented by the vector  $X_0(t)$  and each vehicle  $i$ 's position by  $X_i(t)$ . The goal of the trajectory generation problem is to transport the payload to a location closest to the goal location respecting the various system constraints. The problem is solved for a horizon of  $T$ s. The complete optimization problem required to generate the trajectories  $X_0(t)$  and  $X_i(t)$  is shown in (1).

$$\begin{aligned}
 & \underset{\forall i: X_i(t), X_0(t)}{\text{minimize}} && \int_0^T \|X_0(t) - X_d\|_1 dt \\
 & \text{subject to} && f_i(X_0(t), X_i(t)) \leq 0 \\
 & && g(X_0(t), X_i(t), X_j(t)) = 0 \\
 & && \langle X_i(t) - X_0(t), X_j(t) - X_0(t) \rangle \leq 0 \quad (1) \\
 & && X_0(0) = x_0^i, X_i(0) = x_i^i \\
 & && \dot{X}_0(0) = u_0, \dot{X}_i(0) = u_i \\
 & && \forall t \in [0, T], \quad \forall i, j \in \{1, \dots, N\}, i \neq j
 \end{aligned}$$

The first constraint consists of individual vehicle  $i$ 's dynamics, bounds on vehicle velocities and accelerations, and flexible element  $i$ 's elongation limits. The second constraint represents the payload dynamics. Intra-vehicle collisions are avoided using the third constraint, which limits the angles

between the vehicles to lie at  $\geq 90$  deg when subtended at the payload. Initial conditions on the vehicle and payload position and velocity states are captured in the final two constraints.

### C. Spline parameterization

Problem (1) represents an infinite dimensional problem, since the optimization variables  $X_0(t)$  and  $X_i(t)$  are continuous variables in time. In order to make the problem numerically tractable, a spline-based parameterization of the optimization variables is used. The continuous optimization variables are hence represented as linear combinations of piecewise polynomial basis functions  $b_k(t)$ , as expressed in (2).

$$\begin{aligned}
 X_i(t) &= \sum_{k=1}^n x_{i,k} b_k(t) \quad \forall i \in \{1, \dots, N\} \\
 X_0(t) &= \sum_{k=1}^n x_{0,k} b_k(t)
 \end{aligned} \quad (2)$$

The trajectories of each vehicle  $i$  are consequently represented by the coefficient set  $\mathbf{X}_i = \{x_{i,k}\}_{k=1}^n$  and the those of the payload by  $\mathbf{X}_0 = \{x_{0,k}\}_{k=1}^n$ . Substituting these parameterizations in (1) results in an optimization problem with finite number of variables. This is seen in (3).

$$\begin{aligned}
 & \underset{\forall i: \mathbf{X}_i, \mathbf{X}_0}{\text{minimize}} && J(\mathbf{X}_0) \\
 & \text{subject to} && F_i(\mathbf{X}_0, \mathbf{X}_i) \leq 0 \\
 & && G(\mathbf{X}_0, \mathbf{X}_i, \mathbf{X}_j) = 0 \\
 & && H_{ij}(\mathbf{X}_0, \mathbf{X}_i, \mathbf{X}_j) \leq 0 \quad (3) \\
 & && \mathbf{X}_0(1) = x_0^i, \mathbf{X}_i(1) = x_i^i \\
 & && \text{Make velocity things here??} \\
 & && \forall i, j \in \{1, \dots, N\}, i \neq j
 \end{aligned}$$

The objective is now a linear function in payload coefficients. Substituting the parameterizations into the inequality constraints representing vehicle dynamics and intra-vehicle collision avoidance conditions results in functions which are in terms of the spline coefficients and time. These semi-infinite constraints (because of time dependence) can be converted to a finite number following the convex hull property [9] of splines. This property dictates that the constraints are conservatively satisfied if the inequality constraints are moved onto the coefficients of the combined function. These constraints are represented by  $F_i$  and  $H_{ij}$  respectively.

### D. Distributed formulation

The objective of this section is to split the optimization problem (3) into  $N$  separate problems, one for each vehicle. This means that each problem should contain optimization variables local to the vehicle it is assigned. The first step towards this is the introduction of copies of the payload variables  $\mathbf{X}_0$  on each vehicle. These variables are represented by  $\mathbf{X}_{i0}$ . This results in  $N$  copies of the payload dynamics constraint  $G$ , each one being  $G_i(\mathbf{X}_{i0}, \mathbf{X}_i, \mathbf{X}_j) = 0$ . This is further decoupled by borrowing ideas from [8], which dictates that the states  $\mathbf{X}_j$  of vehicle  $j$  which affect the

dynamics of vehicle  $i$  can be modeled as exogenous inputs  $\mathbf{X}_{ij}$  acting on vehicle  $i$ . The new variables  $\mathbf{X}_{ij}$  are hence local to vehicle  $i$ . The payload dynamics constraint is thus further modified as  $G_i(\mathbf{X}_{i0}, \mathbf{X}_i, \mathbf{X}_{ij}) = 0$ . This substitution should however be supported by consensus constraints between  $\mathbf{X}_j$  and  $\mathbf{X}_{ij}$ . Following a modification of the consensus constraints presented in [2], consensus variables  $\mathbf{Z}_{ij}$  are introduced which act as a balance between  $\mathbf{X}_j$  and  $\mathbf{X}_{ij}$ . The corresponding consensus constraints are shown in (4).

$$\begin{aligned}
& \underset{\forall i,j,i \neq j: \mathbf{X}_i, \mathbf{X}_{ij}, \mathbf{Z}_{ij}, \mathbf{X}_{i0}}{\text{minimize}} && \sum_{i=1}^N J_i(\mathbf{X}_{i0}) \\
& \text{subject to} && F_i(\mathbf{X}_0, \mathbf{X}_i) \leq 0 \\
& && G_i(\mathbf{X}_{i0}, \mathbf{X}_i, \mathbf{X}_{ij}) = 0 \\
& && H_{ij}(\mathbf{X}_{i0}, \mathbf{X}_i, \mathbf{X}_{ij}) \leq 0 \\
& && \mathbf{X}_j = \mathbf{Z}_{ij} \\
& && \mathbf{X}_{ij} = \mathbf{Z}_{ij} \\
& && \forall i, j \in \{1, \dots, N\}, i \neq j
\end{aligned} \tag{4}$$

The optimization problem (4) can now be decoupled using the Alternating Direction Method of Multipliers (ADMM), which is a popular technique used in DMPC formulations due to its superior convergence properties. According to this method, equality constraints are moved into the objective function forming a Lagrangian equivalent of the optimization problem, and the Lagrangian is augmented with a quadratic term to improve convergence properties. This appended objective function is seen in (5).

$$\mathcal{L} = \sum_{i=1}^N \left[ J_i(\mathbf{X}_{i0}) + \sum_{j \neq i} \left( \begin{aligned} & \lambda_{iji}^T (\mathbf{X}_{ij} - \mathbf{Z}_{ij}) + \frac{\rho}{2} \|\mathbf{X}_{ij} - \mathbf{Z}_{ij}\|_2^2 \\ & + \\ & \lambda_{ijj}^T (\mathbf{X}_j - \mathbf{Z}_{ij}) + \frac{\rho}{2} \|\mathbf{X}_j - \mathbf{Z}_{ij}\|_2^2 \end{aligned} \right) \right] \tag{5}$$

The dual variables introduced in the Lagrangian corresponding to the equality constraints are  $\lambda_{iji}$  and  $\lambda_{ijj}$ . The conventional methods dictate that the Lagrangian first be minimized with respect to the primal variables, resulting in the formulation of the dual problem in terms of the dual variables. Then, the (concave) dual problem is solved for the dual variables. According to the ADMM, this process is done iteratively in a 3-step procedure. In the first two steps, the primal variables are solved for keeping the dual variables constant. In the final step, the dual variables are updated by gradient ascent. The first step of solving for the primal variables involves keeping the dual variables  $\lambda_{iji}$  and  $\lambda_{ijj}$  and *other* set of primal variables  $\mathbf{Z}_{ij}$  constant from the previous ADMM iteration. This step is easily split amongst individual vehicles and is solved for in parallel on each of the vehicles. This splitting is possible because of the bi-directionality of interaction, meaning that the Lagrangian terms corresponding to the constraint  $\mathbf{X}_i = \mathbf{Z}_{ji}$  can be moved onto agent  $i$ , provided that the values of  $\mathbf{Z}_{ji}$  and  $\lambda_{jii}$ . This results in vehicle  $i$  solving an optimization problem with variables only local to it. This step is shown in (6).

### Step 1 : Primal X variables

$$\begin{aligned}
& \underset{\mathbf{x}_i, \mathbf{x}_{ij}, \mathbf{x}_{i0}}{\text{minimize}} && J_i(\mathbf{X}_{i0}) + \sum_{j \neq i} \left( \begin{aligned} & (\lambda_{iji}^T)^k (\mathbf{X}_{ij} - \mathbf{Z}_{ij}^k) + \frac{\rho}{2} \|\mathbf{X}_{ij} - \mathbf{Z}_{ij}^k\|_2^2 \\ & + \\ & (\lambda_{jii}^T)^k (\mathbf{X}_i - \mathbf{Z}_{ji}^k) + \frac{\rho}{2} \|\mathbf{X}_i - \mathbf{Z}_{ji}^k\|_2^2 \end{aligned} \right) \\
& \text{subject to} && F_i(\mathbf{X}_0, \mathbf{X}_i) \leq 0 \\
& && G_i(\mathbf{X}_{i0}, \mathbf{X}_i, \mathbf{X}_{ij}) = 0 \\
& && H_{ij}(\mathbf{X}_{i0}, \mathbf{X}_i, \mathbf{X}_{ij}) \leq 0
\end{aligned} \tag{6}$$

The superscript  $k$  indicates that these variables are from the previous iteration. This step is followed by the communication of coefficients  $\mathbf{X}_j$  belonging to vehicle  $j$  to vehicle  $i$ . Vehicle  $i$  uses these variables to calculate the primal variable set  $\mathbf{Z}_{ij}$ , according to the second ADMM step. This step is shown in (7).

### Step 2 : Primal Z variables

$$\underset{\mathbf{z}_{ij}}{\text{minimize}} \quad \sum_{j \neq i} \left( \begin{aligned} & (\lambda_{iji}^T)^k (\mathbf{X}_{ij}^{k+1} - \mathbf{Z}_{ij}) + \frac{\rho}{2} \|\mathbf{X}_{ij}^{k+1} - \mathbf{Z}_{ij}\|_2^2 \\ & + \\ & (\lambda_{jii}^T)^k (\mathbf{X}_j^{k+1} - \mathbf{Z}_{ij}) + \frac{\rho}{2} \|\mathbf{X}_j^{k+1} - \mathbf{Z}_{ij}\|_2^2 \end{aligned} \right) \tag{7}$$

The 2nd step is solved as a Least Squares problem, removing the need to call another optimization routine. This step can be seen as a balancing step, finding a  $\mathbf{Z}_{ij}$  trading off between the trajectory  $\mathbf{X}_{ij}$  which is expected of vehicle  $j$  by vehicle  $i$ , and trajectory  $\mathbf{X}_j$  which vehicle  $j$  can actually provide while respecting its constraints. and This step is followed by the communication of  $\mathbf{Z}_{ji}$  variables from vehicle  $j$  to vehicle  $i$ . These variables are used to update the  $\mathbf{X}$  variables on vehicle  $i$  in step 1 of the next ADMM iteration. In the final ADMM step, the dual variables  $\lambda_{iji}$  and  $\lambda_{ijj}$  belonging to vehicle  $i$  are updated through gradient ascent. It can easily be seen from the Lagrangian formulation (5) that the gradients with respect to  $\lambda_{iji}$  and  $\lambda_{ijj}$  are  $(\mathbf{X}_{ij} - \mathbf{Z}_{ij})$  and  $(\mathbf{X}_j - \mathbf{Z}_{ij})$  respectively. Choosing the optimal step length of  $\rho$  according to [7], the dual variables are updated according to (8).

### Step 3 : Dual variables

$$\begin{aligned}
\lambda_{iji}^{k+1} &= \lambda_{iji}^k + \rho(\mathbf{X}_{ij}^{k+1} - \mathbf{Z}_{ij}^{k+1}) \\
\lambda_{ijj}^{k+1} &= \lambda_{ijj}^k + \rho(\mathbf{X}_j^{k+1} - \mathbf{Z}_{ij}^{k+1})
\end{aligned} \tag{8}$$

The updated dual variables  $\lambda_{jii}$  on vehicle  $j$  are communicated to vehicle  $i$ , which are used to update the  $\mathbf{X}$  on vehicle  $i$  in step 1 of the next ADMM iteration. One sequence of these three ADMM steps are performing in one DMPC iteration, calculating a trajectory for the vehicles to follow for the next  $T_s$ . This is embedded in an online formulation according to the methodology described in [2].

### III. MATH

Before you begin to format your paper, first write and save the content as a separate text file. Keep your text and graphic files separate until after the text has been formatted and styled. Do not use hard tabs, and limit use of hard returns to only one return at the end of a paragraph. Do not add any kind of pagination anywhere in the paper. Do not number text heads-the template will do that for you.

Finally, complete content and organizational editing before formatting. Please take note of the following items when proofreading spelling and grammar:

#### A. Abbreviations and Acronyms

Define abbreviations and acronyms the first time they are used in the text, even after they have been defined in the abstract. Abbreviations such as IEEE, SI, MKS, CGS, sc, dc, and rms do not have to be defined. Do not use abbreviations in the title or heads unless they are unavoidable.

#### B. Units

- Use either SI (MKS) or CGS as primary units. (SI units are encouraged.) English units may be used as secondary units (in parentheses). An exception would be the use of English units as identifiers in trade, such as 3.5-inch disk drive.
- Avoid combining SI and CGS units, such as current in amperes and magnetic field in oersteds. This often leads to confusion because equations do not balance dimensionally. If you must use mixed units, clearly state the units for each quantity that you use in an equation.
- Do not mix complete spellings and abbreviations of units: Wb/m<sup>2</sup> or webers per square meter, not webers/m<sup>2</sup>. Spell out units when they appear in text: . . . a few henries, not . . . a few H.
- Use a zero before decimal points: 0.25, not .25. Use cm<sup>3</sup>, not cc. (bullet list)

#### C. Equations

The equations are an exception to the prescribed specifications of this template. You will need to determine whether or not your equation should be typed using either the Times New Roman or the Symbol font (please no other font). To create multileveled equations, it may be necessary to treat the equation as a graphic and insert it into the text after your paper is styled. Number equations consecutively. Equation numbers, within parentheses, are to position flush right, as in (1), using a right tab stop. To make your equations more compact, you may use the solidus ( / ), the exp function, or appropriate exponents. Italicize Roman symbols for quantities and variables, but not Greek symbols. Use a long dash rather than a hyphen for a minus sign. Punctuate equations with commas or periods when they are part of a sentence, as in

$$\alpha + \beta = \chi \quad (1)$$

Note that the equation is centered using a center tab stop. Be sure that the symbols in your equation have been defined

before or immediately following the equation. Use (1), not Eq. (1) or equation (1), except at the beginning of a sentence: Equation (1) is . . .

#### D. Some Common Mistakes

- The word data is plural, not singular.
- The subscript for the permeability of vacuum  $\mu_0$ , and other common scientific constants, is zero with subscript formatting, not a lowercase letter o.
- In American English, commas, semi-/colons, periods, question and exclamation marks are located within quotation marks only when a complete thought or name is cited, such as a title or full quotation. When quotation marks are used, instead of a bold or italic typeface, to highlight a word or phrase, punctuation should appear outside of the quotation marks. A parenthetical phrase or statement at the end of a sentence is punctuated outside of the closing parenthesis (like this). (A parenthetical sentence is punctuated within the parentheses.)
- A graph within a graph is an inset, not an insert. The word *alternatively* is preferred to the word *alternately* (unless you really mean something that alternates).
- Do not use the word *essentially* to mean *approximately* or *effectively*.
- In your paper title, if the words that uses can accurately replace the word using, capitalize the u; if not, keep using lower-cased.
- Be aware of the different meanings of the homophones *affect* and *effect*, *complement* and *compliment*, *discreet* and *discrete*, *principal* and *principle*.
- Do not confuse *imply* and *infer*.
- The prefix *non* is not a word; it should be joined to the word it modifies, usually without a hyphen.
- There is no period after the *et* in the Latin abbreviation *et al.*.
- The abbreviation *i.e.* means *that is*, and the abbreviation *e.g.* means *for example*.

### IV. USING THE TEMPLATE

Use this sample document as your LaTeX source file to create your document. Save this file as **root.tex**. You have to make sure to use the cls file that came with this distribution. If you use a different style file, you cannot expect to get required margins. Note also that when you are creating your out PDF file, the source file is only part of the equation. *Your  $\TeX$   $\rightarrow$  PDF filter determines the output file size. Even if you make all the specifications to output a letter file in the source - if your filter is set to produce A4, you will only get A4 output.*

It is impossible to account for all possible situation, one would encounter using  $\TeX$ . If you are using multiple  $\TeX$  files you must make sure that the “MAIN” source file is called root.tex - this is particularly important if your conference is using PaperPlaza’s built in  $\TeX$  to PDF conversion tool.

## A. Headings, etc

Text heads organize the topics on a relational, hierarchical basis. For example, the paper title is the primary text head because all subsequent material relates and elaborates on this one topic. If there are two or more sub-topics, the next level head (uppercase Roman numerals) should be used and, conversely, if there are not at least two sub-topics, then no subheads should be introduced. Styles named Heading 1, Heading 2, Heading 3, and Heading 4 are prescribed.

## B. Figures and Tables

Positioning Figures and Tables: Place figures and tables at the top and bottom of columns. Avoid placing them in the middle of columns. Large figures and tables may span across both columns. Figure captions should be below the figures; table heads should appear above the tables. Insert figures and tables after they are cited in the text. Use the abbreviation Fig. 1, even at the beginning of a sentence.

TABLE I  
AN EXAMPLE OF A TABLE

One	Two
Three	Four

We suggest that you use a text box to insert a graphic (which is ideally a 300 dpi TIFF or EPS file, with all fonts embedded) because, in an document, this method is somewhat more stable than directly inserting a picture.

Fig. 2. Inductance of oscillation winding on amorphous magnetic core versus DC bias magnetic field

Figure Labels: Use 8 point Times New Roman for Figure labels. Use words rather than symbols or abbreviations when writing Figure axis labels to avoid confusing the reader. As an example, write the quantity Magnetization, or Magnetization, M, not just M. If including units in the label, present them within parentheses. Do not label axes only with units. In the example, write Magnetization (A/m) or Magnetization A[m(1)], not just A/m. Do not label axes with a ratio of quantities and units. For example, write Temperature (K), not Temperature/K.

## V. CONCLUSIONS

A conclusion section is not required. Although a conclusion may review the main points of the paper, do not replicate the abstract as the conclusion. A conclusion might elaborate on the importance of the work or suggest applications and extensions.

## APPENDIX

Appendixes should appear before the acknowledgment.

## ACKNOWLEDGMENT

The preferred spelling of the word acknowledgment in America is without an e after the g. Avoid the stilted expression, One of us (R. B. G.) thanks . . . Instead, try R. B. G. thanks. Put sponsor acknowledgments in the unnumbered footnote on the first page.

References are important to the reader; therefore, each citation must be complete and correct. If at all possible, references should be commonly available publications.

## REFERENCES

- [1] G. O. Young, Synthetic structure of industrial plastics (Book style with paper title and editor), in *Plastics*, 2nd ed. vol. 3, J. Peters, Ed. New York: McGraw-Hill, 1964, pp. 1564.
- [2] W.-K. Chen, *Linear Networks and Systems* (Book style). Belmont, CA: Wadsworth, 1993, pp. 123135.
- [3] H. Poor, *An Introduction to Signal Detection and Estimation*. New York: Springer-Verlag, 1985, ch. 4.
- [4] B. Smith, An approach to graphs of linear forms (Unpublished work style), unpublished.
- [5] E. H. Miller, A note on reflector arrays (Periodical styleAccepted for publication), *IEEE Trans. Antennas Propagat.*, to be published.
- [6] J. Wang, Fundamentals of erbium-doped fiber amplifiers arrays (Periodical styleSubmitted for publication), *IEEE J. Quantum Electron.*, submitted for publication.
- [7] C. J. Kaufman, Rocky Mountain Research Lab., Boulder, CO, private communication, May 1995.
- [8] Y. Yorozu, M. Hirano, K. Oka, and Y. Tagawa, Electron spectroscopy studies on magneto-optical media and plastic substrate interfaces(Translation Journals style), *IEEE Transl. J. Magn.Jpn.*, vol. 2, Aug. 1987, pp. 740741 [Dig. 9th Annu. Conf. Magnetism Japan, 1982, p. 301].
- [9] M. Young, *The Techincal Writers Handbook*. Mill Valley, CA: University Science, 1989.
- [10] J. U. Duncombe, Infrared navigationPart I: An assessment of feasibility (Periodical style), *IEEE Trans. Electron Devices*, vol. ED-11, pp. 3439, Jan. 1959.
- [11] S. Chen, B. Mulgrew, and P. M. Grant, A clustering technique for digital communications channel equalization using radial basis function networks, *IEEE Trans. Neural Networks*, vol. 4, pp. 570578, July 1993.
- [12] R. W. Lucky, Automatic equalization for digital communication, *Bell Syst. Tech. J.*, vol. 44, no. 4, pp. 547588, Apr. 1965.
- [13] S. P. Bingulac, On the compatibility of adaptive controllers (Published Conference Proceedings style), in *Proc. 4th Annu. Allerton Conf. Circuits and Systems Theory*, New York, 1994, pp. 816.
- [14] G. R. Faulhaber, Design of service systems with priority reservation, in *Conf. Rec. 1995 IEEE Int. Conf. Communications*, pp. 38.
- [15] W. D. Doyle, Magnetization reversal in films with biaxial anisotropy, in *1987 Proc. INTERMAG Conf.*, pp. 2.2-12.2-6.
- [16] G. W. Juette and L. E. Zeffanella, Radio noise currents n short sections on bundle conductors (Presented Conference Paper style), presented at the IEEE Summer power Meeting, Dallas, TX, June 2227, 1990, Paper 90 SM 690-0 PWRS.
- [17] J. G. Kreifeldt, An analysis of surface-detected EMG as an amplitude-modulated noise, presented at the 1989 Int. Conf. Medicine and Biological Engineering, Chicago, IL.
- [18] J. Williams, Narrow-band analyzer (Thesis or Dissertation style), Ph.D. dissertation, Dept. Elect. Eng., Harvard Univ., Cambridge, MA, 1993.
- [19] N. Kawasaki, Parametric study of thermal and chemical nonequilibrium nozzle flow, M.S. thesis, Dept. Electron. Eng., Osaka Univ., Osaka, Japan, 1993.
- [20] J. P. Wilkinson, Nonlinear resonant circuit devices (Patent style), U.S. Patent 3 624 12, July 16, 1990.