

hw04

October 28, 2025

1 Sampling, Bias, and Community Structure in Real Networks

1.1 Part A — Sampling and Bias in Network Analysis (15 pts)

Goal: Investigate how different sampling methods can change the observed structure of a social network.

```
[45]: import networkx as nx
import random
from tabulate import tabulate
import matplotlib.pyplot as plt
```

```
[2]: G_fb = nx.read_edgelist("facebook_combined.txt", nodetype=int)
```

1.1.1 A1 – Create Two Samples (6 pts)

```
[72]: # 1. Random Sample - Randomly select 250 nodes.
nodes = random.sample(sorted(G_fb.nodes()), 250)
G_random = G_fb.subgraph(nodes).copy()

# 2. Ego-Centered Sample - Pick a node with degree > 50 and build its 1.
#    ↪ 5-degree ego network.
center = max(G_fb, key=lambda n: G_fb.degree(n))
G_ego = nx.ego_graph(G_fb, center, radius=1)
print(
    tabulate(
        [
            ["Random", G_random.number_of_nodes(), G_random.number_of_edges()],
            ["Ego", G_ego.number_of_nodes(), G_ego.number_of_edges()],
        ],
        headers=["Sample", "# Nodes", "# Edges"]
    )
)
```

Sample	# Nodes	# Edges
Random	250	376
Ego	1046	27795

1.2 A2 – Compute and Visualize Metrics (6 pts)

For each sample (G_random, G_ego):

- Compute Average Clustering Coefficient (C)
- Compute Average Shortest Path Length (L) (on largest component if needed)
- Find Maximum Degree (Max k)

1.2.1 1. Table of Metrics

```
[73]: print(
    tabulate(
        [
            [
                "Random",
                round(nx.average_clustering(G_random), 2),
                round(
                    nx.average_shortest_path_length(
                        G_random.subgraph(
                            max(nx.connected_components(G_random), key=len)
                        )
                    ),
                    2,
                ),
                max(G_random.degree, key=lambda x: x[1])[1],
            ],
            [
                "Ego",
                round(nx.average_clustering(G_ego), 2),
                round(
                    nx.average_shortest_path_length(
                        G_ego.subgraph(
                            max(nx.connected_components(G_ego), key=len)
                        )
                    ),
                    2,
                ),
                max(G_ego.degree, key=lambda x: x[1])[1],
            ],
        ],
        headers=["Sample", "Avg Clustering (C)", "Avg Path (L)", "Max Degree"]
    )
)
```

Sample	Avg Clustering (C)	Avg Path (L)	Max Degree
Random	0.35	1.93	14
Ego	0.58	1.95	1045

1.2.2 2. Two degree distribution plots (log-log axes)

Each plot must include a title, axis labels (“Degree (k)” and “Count of Nodes”)

```
[71]: fig, axes = plt.subplots(1, 2, figsize=(12, 4), sharex=True, sharey=True)

axes[0].set_title("Random Sample")
axes[0].set_xlabel("Degree")
axes[0].set_ylabel("Frequency")
degree_freq = nx.degree_histogram(G_random)
degrees = range(len(degree_freq))
axes[0].loglog(degrees, degree_freq, "o")

axes[1].set_title("Ego")
axes[1].set_xlabel("Degree")
axes[1].set_ylabel("Frequency")
degree_freq = nx.degree_histogram(G_ego)
degrees = range(len(degree_freq))
axes[1].loglog(degrees, degree_freq, "o")
plt.show()
```

