

HW 2

Sam Ly

February 5, 2026

Chapter 4

1. The lexical grammars of Python and Haskell are not regular. What does that mean, and why aren't they?

The lexical grammars of Python and Haskell are not regular because the levels of indentation are significant. Regular languages can not have “n-length string of characters” have significant semantic meaning.

2. Aside from separating tokens—distinguishing `print foo` from `printfoo`—spaces aren't used for much in most languages. However, in a couple of dark corners, a space does affect how code is parsed in CoffeeScript, Ruby, and the C preprocessor. Where and what effect does it have in each of those languages?

In C, the macro system places significance on the spaces, because C macros can either be a regular value (eg. number literal, string, etc.) or a “function” that gets substituted.

```
#define FOO(x) 2*x
#define BAR (x)
// Usage:
FOO(a); // changes to 2*a
BAR; // changes to (x), likely an error.
```

3. Our scanner here, like most, discards comments and whitespace since those aren't needed by the parser. Why might you want to write a scanner that does not discard those? What would it be useful for?

Many modern languages can actually make use of comments. For example, JavaDoc can turn comments into documentation. The JavaDoc can also inform the IDE's LSP, allowing for inline completions and context.

4. Add support to Lox's scanner for C-style `/* ... */` block comments. Make sure to handle newlines in them. Consider allowing them to nest. Is adding support for nesting more work than you expected? Why?