Section Overview

- Throughput, Arithmetic Intensity, and the Roofline Model

Driving Question

Hardware specification	Value
GPU	RTX 3090
Peak throughput	35.6 $\mathrm{TFLOP/s}$
DRAM bandwidth	935.8 $\mathrm{GB/s}$

Driving Question

Hardware specification	Value
GPU	RTX 3090
Peak throughput	$35.6\,\mathrm{TFLOP/s}$
DRAM bandwidth	$935.8\,\mathrm{GB/s}$

Is there a better performance metric?

We have been measuring our kernels with **latency**, but is there some other metric that better describes "performance"?

Driving Question

Hardware specification	Value
GPU	RTX 3090
Peak throughput	$35.6\,\mathrm{TFLOP/s}$
DRAM bandwidth	$935.8\,\mathrm{GB/s}$

Is there a better performance metric?


We have been measuring our kernels with **latency**, but is there some other metric that better describes "performance"?

How fast *can* we be?

Given that we can do 35.6×10^{12} floating point operations **per second**, how fast (theoretically) can we do our SGEMM operations?


Why latency alone isn't enough

- Latency tells us how long one kernel launch takes, but it depends on the problem size.




Why latency alone isn't enough

- To compare performance **across problem sizes**, we need to account for both the work completed and the time required. This gives us **achieved throughput**.



Why latency alone isn't enough

- Since hardware is characterized by its **peak throughput**, the two values provide a first gauge of how much compute capability our kernel realizes.



Why latency alone isn't enough

- Latency tells us how long one kernel launch takes, but it depends on the problem size.
- To compare performance **across problem sizes**, we need to account for both the work completed and the time required. This gives us **achieved throughput**.
- Since hardware is characterized by its **peak throughput**, the two values provide a first gauge of how much compute capability our kernel realizes.

Why throughput

Throughput tells us

1. A general performance metric, no matter the problem size
2. How well we are utilizing hardware

Throughput as a performance measure

Throughput

Throughput is the total useful work (FLOPs) done per unit time.

$$\text{Throughput} = \frac{\text{FLOPs}}{\text{time}}$$

Throughput as a performance measure

Throughput

Throughput is the total useful work (FLOPs) done per unit time.

$$\text{Throughput} = \frac{\text{FLOPs}}{\text{time}}$$

Example

Peak throughput of our RTX 3090 is 35.6 TFLOP/s. We observed 360ms or 0.36s of latency for $n = 8192$, where the total FLOPs required is 1.10 TFLOPs. Thus, we have an observed throughput of

$$\frac{1.10\text{TFLOPs}}{0.36\text{s}} \approx 3.05\text{TFLOP/s}.$$

Roughly 8.5% of peak throughput.

Characterizing our kernels data use

Hardware specification	Value
GPU	RTX 3090
Peak throughput	$35.6\,\mathrm{TFLOP/s}$
DRAM bandwidth	$935.8\,\mathrm{GB/s}$

1. Throughput characterizes how well our kernel utilizes the hardware
2. One factor that impacts final throughput is how efficiently our kernels use data

Arithmetic Intensity: Characterizing our kernels

Arithmetic Intensity

We define the **Arithmetic Intensity** (AI) of our kernel as the number of FLOPs done per bytes moved from DRAM.

$$\text{AI} = \frac{\text{FLOPs}}{\text{bytes moved}}$$

Arithmetic Intensity: Characterizing our kernels

Arithmetic Intensity

We define the **Arithmetic Intensity** (AI) of our kernel as the number of FLOPs done per bytes moved from DRAM.

$$\text{AI} = \frac{\text{FLOPs}}{\text{bytes moved}}$$

Example

For $n, k, m = 8192$, our tiled kernel moved a total of 137.7 GB of data from DRAM. With a total work count of 1.10 TFLOP, its arithmetic intensity is

$$\text{AI} = \frac{1.10 \times 10^{12} \text{ FLOP}}{137.7 \times 10^{9} \text{ bytes}} \approx \boxed{8.0 \text{ FLOP/byte}}.$$

Two Key Constraints of Hardware

Hardware specification	**Value**
GPU	RTX 3090
Peak throughput	$35.6\,\mathrm{TFLOP/s}$
DRAM bandwidth	$935.8\,\mathrm{GB/s}$

Two Key Constraints of Hardware

Hardware specification	Value
GPU	RTX 3090
Peak throughput	35.6 $\mathrm{TFLOP/s}$
DRAM bandwidth	935.8 $\mathrm{GB/s}$

Example

Our tiling kernel has AI of 8.0 FLOP/byte, meaning it does 8 floating point operations for every byte of data moved from DRAM.
At 935.8 $\mathrm{GB/s}$ of bandwidth, our **memory roof** is

$$935.8\,\mathrm{GB/s} \times 8.0\ \text{FLOP/byte} \approx 7.49\ \text{TFLOP/s}.$$

Two Key Constraints of Hardware

Hardware specification	Value
GPU	RTX 3090
Peak throughput	35.6 $\mathrm{TFLOP/s}$
DRAM bandwidth	935.8 $\mathrm{GB/s}$

Example

Our tiling kernel has AI of 8.0 FLOP/byte, meaning it does 8 floating point operations for every byte of data moved from DRAM.
At 935.8 $\mathrm{GB/s}$ of bandwidth, our **memory roof** is

$$935.8\,\mathrm{GB/s} \times 8.0\ \text{FLOP/byte} \approx 7.49\ \text{TFLOP/s}.$$

This is much lower than the peak throughput of 35.6 $\mathrm{TFLOP/s}$.

Two Key Constraints of Hardware

Hardware specification	Value
GPU	RTX 3090
Peak throughput	35.6 $\mathrm{TFLOP/s}$
DRAM bandwidth	935.8 $\mathrm{GB/s}$

Example

Our tiling kernel has AI of 8.0 FLOP/byte, meaning it does 8 floating point operations for every byte of data moved from DRAM.
At 935.8 $\mathrm{GB/s}$ of bandwidth, our **memory roof** is

$$935.8\,\mathrm{GB/s} \times 8.0\ \mathrm{FLOP/byte} \approx 7.49\ \mathrm{TFLOP/s}.$$

This is much lower than the peak throughput of 35.6 $\mathrm{TFLOP/s}$. **No matter how we optimize this kernel, without increasing AI, we will never achieve greater than 7.49 TFLOP/s**.

Hypothetical Kernel

Hardware specification	Value
GPU	RTX 3090
Peak throughput	35.6 $\mathrm{TFLOP/s}$
DRAM bandwidth	935.8 $\mathrm{GB/s}$

Example

Imagine we have some kernel that has double the AI at 16.0 FLOP/s.

Hypothetical Kernel

Hardware specification	Value
GPU	RTX 3090
Peak throughput	$35.6\,\mathrm{TFLOP/s}$
DRAM bandwidth	$935.8\,\mathrm{GB/s}$

Example

Imagine we have some kernel that has double the AI at 16.0 FLOP/s. Our memory roof is now

$$935.8\,\mathrm{GB/s} \times 16.0\ \mathrm{FLOP/byte} \approx 15.0\ \mathrm{TFLOP/s}.$$

Hypothetical Kernel

Hardware specification	Value
GPU	RTX 3090
Peak throughput	$35.6\,\mathrm{TFLOP/s}$
DRAM bandwidth	$935.8\,\mathrm{GB/s}$

Example

Imagine we have some kernel that has double the AI at 16.0 FLOP/s. Our memory roof is now

$$935.8\,\mathrm{GB/s} \times 16.0\ \mathrm{FLOP/byte} \approx 15.0\ \mathrm{TFLOP/s}.$$

Since $15.0\ \mathrm{TFLOP/s} < 35.6\,\mathrm{TFLOP/s}$, this kernel will still be memory bound.

Hypothetical Kernels

Hardware specification	**Value**
GPU	RTX 3090
Peak throughput	35.6 TFLOP/s
DRAM bandwidth	935.8 GB/s

AI (FLOP/byte)	Upper bound throughput (TFLOP/s)
8	7.49
16	14.97
32	29.95
36	33.69
38	35.56
40	37.43

Hypothetical Kernels

Hardware specification	**Value**
GPU	RTX 3090
Peak throughput	$35.6\,\mathrm{TFLOP/s}$
DRAM bandwidth	$935.8\,\mathrm{GB/s}$

AI (FLOP/byte)	Upper bound throughput (TFLOP/s)
8	7.49
16	14.97
32	29.95
36	33.69
38	35.56
40	37.43

Wait! Our peak throughput is $35.6\,\mathrm{TFLOP/s}$! At AI ≥ 38, we are **compute bound**. Our data can finally keep up with the CUDA Cores!

Ridge Point

Hardware specification	Value
GPU	RTX 3090
Peak throughput	$35.6\,\mathrm{TFLOP/s}$
DRAM bandwidth	$935.8\,\mathrm{GB/s}$

AI $= 38$ FLOP/byte is known as the **ridge point** *RP*, and can be found by solving:

$$\text{Data roof} = \text{Peak throughput}$$

$$\text{DRAM Bandwidth} \times \text{RP} = \text{Peak throughput}$$


$$\text{RP} = \frac{\text{Peak throughput}}{\text{DRAM Bandwidth}}$$

$$\text{RP} = \frac{35.6\,\mathrm{TFLOP/s}}{935.8\,\mathrm{GB/s}} \approx 38.0 \text{ FLOP/s}$$

Roofline Model

Roofline Model


For a given system, we can predict a the **upper bound** of throughput of a kernel given its AI.



Roofline Model

Roofline Model


For a given system, we can predict a the **upper bound** of throughput of a kernel given its AI. Up to the **ridge point**, we are **memory bound**, increasing AI will raise the upper bound of throughput.



Roofline Model

Roofline Model

For a given system, we can predict a the **upper bound** of throughput of a kernel given its AI. Up to the **ridge point**, we are **memory bound**, increasing AI will raise the upper bound of throughput. Past that, we are **compute bound**, increasing AI will not raise the upper bound of throughput.



Roofline Model of our RTX 3090

