

Todo list

■ A justification for why we decided to do this should be added	1
■ OG Alalfi et al., 2010	3
■ OG Artzi et al., 2008	3
■ OG PMBOK	6
■ find original source for SouzaEtAl2017 technique examples: Mathur (2012)	9
■ OG IEEE 2013	11
■ OG ISO/IEC 2014	11
■ Find examples?	11
■ OG [19]	12
■ OG [3, 4, 5, 8]	14
■ OG Black, 2009	14
■ add acronym?	16
■ is this punctuation right?	16
■ more in Umar2000	17
■ OG Hetzel88	18
■ find source	18
■ OG Hass, 2008	21
■ OG IEEE 2013	23
■ OG Fewster and Graham	23
■ van Vliet (2000, p. 399) may list these as synonyms; investigate	23
■ OG PMBOK 5th ed.	24
■ find more academic sources	25
■ OG ISO1984	29
■ OG Beizer	33
■ OG Myers 1976	33
■ OG ISO/IEC 2014	34
■ OG?	34
■ OG ISO 26262	35
■ This should probably be explained after “test adequacy criterion” is defined	36
■ Q #1: Bring up!	37
■ Expand on reliability testing (make own section?)	37
■ see ISO 29119-11	38
■ Investigate	39
■ OG [11, 6]	39
■ OG Halfond and Orso, 2007	39
■ OG Artzi et al., 2008	39

Describe anyway	39
Investigate this source more!	43
OG ISO 25010?	44
Originally used a <i>very</i> vague definition from (Peters and Pedrycz, 2000, p. 447); re-investigate!	44
Investigate	45
Q #2: Is this true?	45
Do this!	45
This shouldn't really be at the same level as Reviews, but I didn't want to fight with more subsections yet	47
This shouldn't really be at the same level as Reviews, but I didn't want to fight with more subsections yet	47
Does symbolic execution belong here? Investigate from textbooks	49
OG Miller et al., 1994	50
OG Miller et al., 1994	50
OG Miller et al., 1994	50
OG Miller et al., 1994	50
Q #3: How do we decide on our definition?	50
OG Miller et al., 1994	51
OG Beizer, 1990	52
Is this sufficient?	52
Q #4: How is All-DU-Paths coverage stronger than All-Uses coverage according to (van Vliet, 2000, p. 433)?	52
OG KA85	53
Investigate!	54
Investigate these	54
Add paragraph/section number?	56
Add example	56
Add source(s)?	56
OG IEEE 2013	62

Contents

Todo list	1
Contents	3
List of Figures	5
List of Tables	6
List of Source Codes	7
1 List of Abbreviations and Symbols	8
2 Software Testing Research	1
2.1 Scope	1
2.1.1 Static Testing	3
2.2 Methodology	4
2.2.1 Sources	4
2.2.2 Procedure	4
2.2.3 Undefined Terms	6
2.3 Observations	7
2.3.1 Categories of Testing Approaches	7
2.3.2 Derived Test Approaches	10
2.3.3 Orthogonally Derived Test Approaches	12
2.3.4 Categorizations	13
2.3.5 Existing Taxonomies, Ontologies, and the State of Practice .	15
2.4 Discrepancies and Ambiguities	17
2.4.1 Synonyms	17
2.4.2 Parent Relations	20
2.4.3 Categories of Testing Approaches	22
2.4.4 Functional Testing	23
2.4.5 Operational (Acceptance) Testing	25
2.4.6 Recovery Testing	26
2.4.7 Scalability Testing	27
2.4.8 Other Discrepancies	27
2.5 Definitions	33
2.5.1 Documentation	35
2.6 General Testing Notes	35

2.6.1	Steps to Testing	36
2.6.2	Testing Stages	36
2.6.3	Test Oracles	37
2.6.4	Generating Test Cases	38
2.7	Static Black-Box (Specification) Testing	39
2.7.1	Coverage-Based Testing of Specification	40
2.8	Dynamic Black-Box (Behavioural) Testing	40
2.8.1	Exploratory Testing	40
2.8.2	Equivalence Partitioning/Classing	41
2.8.3	Data Testing	41
2.8.4	State Testing	43
2.8.5	Other Black-Box Testing	45
2.9	Static White-Box Testing (Structural Analysis)	45
2.9.1	Reviews	46
2.9.2	Coding Standards and Guidelines	47
2.9.3	Generic Code Review Checklist	47
2.9.4	Correctness Proofs	49
2.10	Dynamic White-Box (Structural) Testing	49
2.10.1	Code Coverage or Control-Flow Coverage	49
2.10.2	Data Coverage	51
2.10.3	Fault Seeding	53
2.10.4	Mutation Testing	53
2.11	Gray-Box Testing	53
2.12	Regression Testing	53
2.13	Metamorphic Testing (MT)	54
2.13.1	Benefits of MT	54
2.13.2	Examples of MT	55
2.14	Roadblocks to Testing	55
2.14.1	Roadblocks to Testing Scientific Software	56
2.15	Recommendations	56
2.15.1	Recovery Testing	57
2.15.2	Scalability Testing	59
2.15.3	Performance(-related) Testing	60
	Bibliography	63
	Appendix	72

List of Figures

2.1	Current relations between “recovery testing” terms.	57
2.2	Proposed relations between rationalized “recovery testing” terms. .	57
2.3	Current relations between “scalability testing” terms.	60
2.4	Proposed relations between rationalized “scalability testing” terms.	60
2.5	Proposed relations between rationalized “performance-related test- ing” terms.	61

List of Tables

2.1	IEEE Testing Terminology	8
2.2	Other Testing Terminology	9
2.3	Breakdown of Discrepancies Found	17
2.4	Types of Data Flow Coverage	52

List of Source Codes

A.1	Tests for main with an invalid input file	72
A.2	Projectile’s choice for constraint violation behaviour in code	73
A.3	Projectile’s manually created input verification requirement	73
A.4	“MultiDefinitions” (MultiDefn) Definition	73
A.5	Pseudocode: Broken QuantityDict Chunk Retriever	73

Chapter 1

List of Abbreviations and Symbols

DAC	Differential Assertion Checking
DOM	Document Object Model
EMSEC	EManations SECurity
GOOL	Generic Object-Oriented Language
ISTQB	International Software Testing Qualifications Board
ML	Machine Learning
MR	Metamorphic Relation
MT	Metamorphic Testing
OAT	Orthogonal Array Testing
QAI	Quality Assurance Institute
RAC	Runtime Assertion Checking
SUT	System Under Test
SV	Software Verification
TOAT	Taguchi's Orthogonal Array Testing
C-use	Computational Use
P-use	Predicate Use
Projectile	Projectile
SWEBOK Guide	Guide to the SoftWare Engineering Body Of Knowledge
V&V	Verification and Validation

Chapter 2

Software Testing Research

It was realized early on in the process that it would be beneficial to understand the different kinds of testing (including what they test, what artifacts are needed to perform them, etc.). This section provides some results of this research, as well as some information on why and how it was performed.

A justification for why we decided to do this should be added

2.1 Scope

Since our motivation is restricted to testing of code, only the “testing” component of Verification and Validation (V&V) is considered (see #22). For example, design reviews and documentation reviews (see ISO/IEC and IEEE, 2017, pp. 132, 144, respectively) are out of scope, as they focus on the V&V of design and documentation, respectively. Likewise, ergonomics testing and proximity-based testing (see Hamburg and Mogyorodi, 2024) are out of scope as they fundamentally involve hardware. Similarly removed is EManations SECurity (EMSEC) testing (ISO, 2021; Zhou et al., 2012, p. 95), which deals with the “security risk” of “information leakage via electromagnetic emanation” (Zhou et al., 2012, p. 95). Security audits that focus on “an organization’s ... processes and infrastructure” (Hamburg and Mogyorodi, 2024), are also out of scope, but security audits that “aim to ensure that all of the products installed on a site are secure when checked against the known vulnerabilities for those products” (Gerrard, 2000b, p. 28) are not. While Orthogonal Array Testing (OAT) can be used when testing software (Mandl, 1985), it can also be used for hardware (Valcheva, 2013, pp. 471-472), such as “processors ... made from pre-built and pre-tested hardware components” (p. 471). A subset of OAT called “Taguchi’s Orthogonal Array Testing (TOAT)” is used for “experimental design problems in manufacturing” (Yu et al., 2011, p. 1573) or “product and manufacturing process design” (Tsui, 2007, p. 44) and is thus out of scope.

Sometimes, wider decisions must be made on whether a whole category of testing is in scope or not. For example, while all the examples of domain-specific testing given by Firesmith (2015, p. 26) are focused on hardware, this might not be representative of all types (e.g., Machine Learning (ML) model testing seems domain-specific). Conversely, the examples of environmental tolerance testing (p. 56) do not seem to apply to software. For example, radiation tolerance

testing seems to focus on hardware, such as motors (Mukhin et al., 2022), robots (Zhang et al., 2020), or “nanolayered carbide and nitride materials” (Tunes et al., 2022, p. 1). Acceleration tolerance testing seems to focus on astronauts (Morgun et al., 1999, p. 11), aviators (Howe and Johnson, 1995, pp. 27, 42), or catalysts (Liu et al., 2023, p. 1463) and acoustic tolerance testing on rats (Holley et al., 1996), which are even less related! Since these all seem to focus on environment-specific factors that would not impact the code, this category of testing is also out of scope.

It is also interesting to note that different test approaches seem to be more specific to certain domains. For example, the terms “software qualification testing” and “system qualification testing” show up throughout (Knüvener Mackert GmbH, 2022), which was written for the automotive industry, and the more general idea of “qualification testing” seems to refer to the process of making a hardware component, such as an electronic component (Ahsan et al., 2020), gas generator (Parate et al., 2021) or photovoltaic device, “into a reliable and marketable product” (Suhir et al., 2013, p. 1).

Furthermore, only some aspects of some testing approaches are relevant. This mainly manifests as a testing approach that applies to both the V&V itself and to the code. For example:

1. *Error seeding* is the “process of intentionally adding known faults to those already in a computer program”, done to both “monitor[] the rate of detection and removal”, which is a part of V&V of the V&V itself (out of scope), “and estimat[e] the number of faults remaining” (ISO/IEC and IEEE, 2017, p. 165), which helps verify the actual code (in scope).
2. *Fault injection testing*, where “faults are artificially introduced into the SUT [System Under Test]”, can be used to evaluate the effectiveness of a test suite (Washizaki, 2024, p. 5-18), which is a part of V&V of the V&V itself (out of scope), or “to test the robustness of the system in the event of internal and external failures” (ISO/IEC and IEEE, 2022, p. 42), which helps verify the actual code (in scope).
3. “*Mutation [t]esting* was originally conceived as a technique to evaluate test suites in which a mutant is a slightly modified version of the SUT” (Washizaki, 2024, p. 5-15), which is in the realm of V&V of the V&V itself (out of scope). However, it “can also be categorized as a structure-based technique” and can be used to assist fuzz and metamorphic testing (Washizaki, 2024, p. 5-15) (in scope).
4. Even though *reliability testing* and *maintainability testing* can start *without* code by “measur[ing] structural attributes of representations of the software” (Fenton and Pfleeger, 1997, p. 18), only reliability and maintainability testing done *on* code is in scope.
5. Since control systems often have a software *and* hardware component (ISO, 2015; Preuße et al., 2012; Forsyth et al., 2004), only the software component

is in scope. In some cases, it is unclear whether the “loops”¹ being tested are implemented by software or hardware, such as those in wide-area damping controllers (Pierre et al., 2017; Trudnowski et al., 2017).

- A related note: “path coverage” or “path testing” seems to be able to refer to either paths through code (as a subset of control-flow testing) (Washizaki, 2024, p. 5-13) or through a model, such as a finite-state machine (as a subset of model-based testing) (Doğan et al., 2014, p. 184).

Specific programming languages are sometimes used to define “kinds” of testing. These will not be included (see #63); if the reliance on a specific programming language is intentional, then this really implies an underlying test approach that may be generalized to other languages. Some examples:

- “They implemented an approach ... for JavaScript testing (referred to as Randomized)” (Doğan et al., 2014, p. 192) - this really refers to random testing used within JavaScript
- “SQL statement coverage” is really just statement coverage used specifically for SQL statements (Doğan et al., 2014, Tab. 13)
- “Faults specific to PHP” is just a subcategory of fault-based testing, since “execution failures ... caused by missing an included file, wrong MySQL quer[ies] and uncaught exceptions” are not exclusive to PHP (Doğan et al., 2014, Tab. 27)
- While “HTML testing” is listed or implied by Gerrard (2000a, Tab. 2; 2000b, Tab. 1, p. 3) and Patton (2006, p. 220), it seems to be a combination of syntax testing, functionality testing, hyperlink testing/link checking, cross-browser compatibility testing, performance testing, and content checking (Gerrard, 2000b, p. 3)

OG Alalfi et al.,
2010

OG Artzi et al.,
2008

2.1.1 Static Testing

Sometimes, the term “testing” excludes static testing (Ammann and Offutt, 2017, p. 222; Firesmith, 2015, p. 13), restricting it to “dynamic validation” (Washizaki, 2024, p. 5-1) or “dynamic verification” “in which a system or component is executed” (ISO/IEC and IEEE, 2017, p. 427). Since “terminology is not uniform among different communities, and some use the term *testing* to refer to static techniques² as well” (Washizaki, 2024, p. 5-2), the scope of “testing” for the purpose of this project will include both “static testing” and “dynamic testing”, as done by ISO/IEC and IEEE (2022, p. 17), Gerrard (2000a, pp. 8-9), and even a source that explicitly excluded static testing (ISO/IEC and IEEE, 2017, p. 440)!

¹Humorously, the testing of loops in chemical systems (Dominguez-Pumar et al., 2020) and copper loops (Goralski, 1999) are out of scope.

²Not formally defined, but distinct from the notion of “test technique” described in IEEE Testing Terminology.

Static testing seems to be somewhat more ad hoc which makes it less relevant for own goals (automatic generation of tests). In particular, some techniques generate false positives which require human intervention. Nevertheless, understanding the breadth of testing approaches provides a more complete picture of how software can be tested, how the various approaches are related to one another, and potentially how even parts of these “out-of-scope” approaches may be generated in the future! For the current purpose of this work, we keep these in-scope at this stage of the analysis.

2.2 Methodology

2.2.1 Sources

As there is no single authoritative source on software testing terminology, we need to look at many. Unfortunately, this brings to light a variety of discrepancies. Starting from some set of sources, we then use “snowballing” to gather further sources (see [Section 2.2.3](#)). Groups of sources with information that shows up in a relevant graph are given a unique colour to better visualize them; see [Figures 2.1 to 2.5](#).

0. Trusted textbooks ([Patton, 2006](#); [Peters and Pedrycz, 2000](#); [van Vliet, 2000](#))
 - Ad hoc and arbitrary; not systematic
1. Established standards, such as IEEE, ISO/IEC, and the Guide to the Software Engineering Body Of Knowledge (SWEBOK Guide)
 - Standards organizations ([ISO/IEC and IEEE, 2022](#); [2017](#); [2013](#); [ISO/IEC, 2023b](#); [IEEE, 2012](#); [ISO/IEC, 2023a](#); [ISO/IEC and IEEE, 2021](#); [ISO/IEC, 2018](#); [ISO, 2021](#); [2015](#)) colored green
 - “Meta-level” commentaries or collections of terminology (often based on these standards) ([Washizaki, 2024](#); [Bourque and Fairley, 2014](#); [Hamburg and Mogyorodi, 2024](#); [Firesmith, 2015](#)) colored blue,
2. Other resources: less-formal classifications of terminology (e.g., [Kuļešovs et al., 2013](#)), sources investigated to “fill in” missing definitions (see [Section 2.2.3](#)), and testing-related resources that emerged for unrelated reasons
 - Colored black, along with any “surface-level” analysis that followed straightforwardly.

2.2.2 Procedure

To track terminology used in the literature, we build a glossary of test approaches, including the term itself, its definition, and any synonyms or parents. Many test approaches are multi-faceted and can be “specialized” into others, such as [Performance\(-related\) Testing](#). These “specializations” will be referred to as “children”

or “sub-approaches³” of the multi-faceted “parent”. Any additional notes, such as questions or sources to investigate further, are also recorded. Approach categorizations, such as those found in Table 2.1 and some outliers (e.g., “artifact”), are tracked for future investigation.

All sources are analyzed in their entirety to systematically extract terminology. (Some sources given in Section 2.2.3 were only partially investigated to focus on the area of interest or since the test approach was determined to be out-of-scope.) Heuristics are used to guide this process, by investigating:

- glossaries and lists of terms,
- testing-related terms (e.g., terms containing “test(ing)”, “review(s)”, “audit(s)”, “validation”, or “verification”),
- terms that had emerged as part of already-discovered testing approaches, *especially* those that were ambiguous or prompted further discussion (e.g., terms containing “performance”, “recovery”, “component”, “bottom-up”, “boundary”, or “configuration”), and
- terms that implied testing approaches⁴ (see Section 2.3.2).

When terms have multiple definitions, either the clearest and most concise version is kept, or they are merged to paint a more complete picture. If any discrepancies or ambiguities arise, they are reasonably investigated and always documented. If a testing approach is mentioned but not defined, it is added to the glossary to indicate it should be investigated further (see Section 2.2.3). A similar methodology is used for tracking software qualities, albeit in a separate document (see Section 2.3.2).

During the first pass of data collection, all software-testing-focused terms are included. Some of them are less applicable to test case automation (such as Section 2.1.1, #39) or too broad (such as Section 2.3.2, #55), so they will be omitted over the course of analysis.

During this investigation, some terms came up that seemed to be relevant to testing but were so vague, they didn’t provide any new information. These were decided to be not worth tracking (see #39, #44, #28) and are listed below:

- **Evaluation:** the “systematic determination of the extent to which an entity meets its specified criteria” (ISO/IEC and IEEE, 2017, p. 167)
- **Product Analysis:** the “process of evaluating a product by manual or automated means to determine if the product has certain characteristics” (ISO/IEC and IEEE, 2017, p. 343)

³This nomenclature extends to other categories of approaches from Table 2.1, such as “sub-type”.

⁴Since these methods for deriving test approaches only arose as research progressed, some examples would have been missed during the first pass(es) of resources investigated earlier in the process. While reiterating over them would be ideal, this may not be possible due to time constraints.

- **Quality Audit:** “a structured, independent process to determine if project activities comply with organizational and project policies, processes, and procedures” (ISO/IEC and IEEE, 2017, p. 361)
- **Software Product Evaluation:** a “technical operation that consists of producing an assessment of one or more characteristics of a software product according to a specified procedure” (ISO/IEC and IEEE, 2017, p. 424)

2.2.3 Undefined Terms

The search process led to some testing approaches being mentioned without definition; (ISO/IEC and IEEE, 2022) and (Firesmith, 2015) in particular introduced many. Once “standard” sources had been exhausted, we devised a strategy to look for sources that explicitly defined these terms, consistent with our snowballing approach. This uncovered new approaches, both in and out of scope (such as EM-anations SEcURITY (EMSEC) testing, HTML testing, and aspects of loop testing and orthogonal array testing (see Section 2.1)).

The following terms (and their respective related terms) were explored in the following sources, bringing the number of testing approaches from 432 to 515 and the number of *undefined* terms from 153 to 171 (the assumption can be made that about 78% of added terms also included a definition):

- **Assertion Checking:** Lahiri et al. (2013); Chalin et al. (2006); Berdine et al. (2006)
- **Loop Testing**⁵: Dhok and Ramanathan (2016); Godefroid and Luchaup (2011); Preuße et al. (2012); Forsyth et al. (2004)
- **EMSEC Testing:** Zhou et al. (2012); ISO (2021)
- **Asynchronous Testing:** Jard et al. (1999)
- **Performance(-related) Testing:** Moghadam (2019)
- **Web Application Testing:** Doğan et al. (2014); Kam (2008)
 - **HTML Testing:** Choudhary et al. (2010); Sneed and Göschl (2000); Gerrard (2000b)
 - **Document Object Model (DOM) Testing:** Bajammal and Mesbah (2018)
- **Sandwich Testing:** Sharma et al. (2021); Sangwan and LaPlante (2006)
- **Orthogonal Array Testing**⁶: Mandl (1985); Valcheva (2013)

⁵(ISO, 2015) and (ISO, 2022) were used as reference for terms but not fully investigated, (Trudnowski et al., 2017) and (Pierre et al., 2017) were added as potentially in scope, and (Goralski, 1999) and (Dominguez-Pumar et al., 2020) were added as out-of-scope examples.

⁶(Yu et al., 2011) and (Tsui, 2007) were added as out-of-scope examples.

- **Backup Testing**⁷: Bas (2024)

We then develop a tool to automatically generate graphs of the relations between test approaches. All child-parent relations are graphed, as well as synonym relations where either:

1. both terms are present in the glossary, or
2. one term is synonyms with more than one term that is present in the glossary (see [Section 2.4.1](#)).

[Figures 2.1](#) and [2.3](#) are modified versions of these graphs generated based on the existing literature, focused on specific subsets of testing terminology. This tool was also expanded to be able to make changes to these generated graphs based on our [Recommendations](#). [Figures 2.2](#), [2.4](#) and [2.5](#) are modified versions of these proposed graphs.

2.3 Observations

2.3.1 Categories of Testing Approaches

⁷See [Section 2.4.6](#).

Table 2.1: IEEE Testing Terminology

Term	Definition	Examples
Approach	A “high-level test implementation choice, typically made as part of the test strategy design activity” that includes “test level, test type, test technique, test practice and the form of static testing to be used” (ISO/IEC and IEEE, 2022, p. 10); described by a <i>test strategy</i> (2017, p. 472) and is also used to “pick the particular test case values” (2017, p. 465)	black or white box, minimum and maximum boundary value testing (ISO/IEC and IEEE, 2017, p. 465)
(Design) ^a Technique	A “defined” and “systematic” (ISO/IEC and IEEE, 2017, p. 464) “procedure used to create or select a test model, identify test coverage items, and derive corresponding test cases” (2022, p. 11; similar in 2017, p. 467) “that ... generate evidence that test item requirements have been met or that defects are present in a test item” (2021, p. vii); “a variety ... is typically required to suitably cover any system” (2022, p. 33) and is “often selected based on team skills and familiarity, on the format of the test basis”, and on expectations (2022, p. 23)	equivalence partitioning, boundary value analysis, branch testing (ISO/IEC and IEEE, 2022, p. 11)
Level ^b (sometimes “Phase” ^c or “Stage” ^d)	A stage of testing “typically associated with the achievement of particular objectives and used to treat particular risks”, each performed in sequence (ISO/IEC and IEEE, 2022, p. 12; 2021, p. 6) with their “own documentation and resources” (2017, p. 469); more generally, “designat[es] ... the coverage and detail” (2017, p. 249)	unit/component testing, integration testing, system testing (ISO/IEC and IEEE, 2022, p. 12; 2021, p. 6; 2017, p. 467)
Practice	A “conceptual framework that can be applied to ... [a] test process to facilitate testing” (ISO/IEC and IEEE, 2022, p. 14; 2017, p. 471; OG IEEE 2013); more generally, a “specific type of activity that contributes to the execution of a process” (2017, p. 331)	scripted testing, exploratory testing, automated testing (ISO/IEC and IEEE, 2022, p. 20)
Type	“Testing that is focused on specific quality characteristics” (ISO/IEC and IEEE, 2022, p. 15; 2021, p. 7; 2017, p. 473; OG IEEE 2013)	security testing, usability testing, performance testing (ISO/IEC and IEEE, 2022, p. 15; 2017, p. 473)

^a“Design technique” is sometimes abbreviated to “technique” (ISO/IEC and IEEE, 2022, p. 11; Hamburg and Mogyorodi, 2024).

^b“Test level” can also refer to the scope of a test process; for example, “across the whole organization” or only “to specific projects” (ISO/IEC and IEEE, 2022, p. 24).

^c“Test phase” can be a synonym for “test level” (ISO/IEC and IEEE, 2017, p. 469; 2013, p. 9) but can also refer to the “period of time in the software life cycle” when testing occurs (2017, p. 470), usually after the implementation phase (2017, pp. 420, 509; Perry, 2006, p. 56).

^dUsed by (Washizaki, 2024, pp. 5-6 to 5-7; Hamburg and Mogyorodi, 2024; Gerrard, 2000a, pp. 9, 13).

Table 2.2: Other Testing Terminology

Term	Definition	Examples	IEEE Equiv.
Guidance	none given (Barbosa et al., 2006, p. 3)	none given	Technique?
Level	“distinguished based on the object of testing, the <i>target</i> , or on the purpose or <i>objective</i> ” (Washizaki, 2024, p. 5-6); these are “orthogonal” and “determine how the test suite is identified ... regarding its consistency ... and its composition” (Washizaki, 2024, p. 5-2)	Target: unit, integration, system (Washizaki, 2024, pp. 5-6 to 5-7; Souza et al., 2017, p. 3), acceptance testing (Washizaki, 2024, p. 5-7) Objective: conformance, installation, regression, performance, reliability, security (Washizaki, 2024, pp. 5-7 to 5-9)	Target: Level Obj.: Mainly type
Method	none given (Barbosa et al., 2006, p. 3)	none given	Practice?
Phase	none given (Perry, 2006, p. 221; Barbosa et al., 2006, p. 3)	unit, integration, system, regression testing (Perry, 2006, p. 221; Barbosa et al., 2006, p. 3)	Level
Procedure	The basis for how testing is performed that guides the process (Barbosa et al., 2006, p. 3); categorized in[to] testing methods, testing guidances and testing techniques (Barbosa et al., 2006, p. 3)	none given generally; see examples of “Technique”	Approach
Process	“A sequence of testing steps” (Barbosa et al., 2006, p. 2) that is “based on a development technology and ... paradigm, as well as on a testing procedure” (Barbosa et al., 2006, p. 3)	none given	Practice
Stage	An alternative to the “traditional ... test stages” that is based on “clear technical groupings” (Gerrard, 2000a, p. 13); see “Level” in IEEE Testing Terminology	desktop development testing, infrastructure testing, system testing, large scale integration, and post-deployment monitoring (Gerrard, 2000a, p. 13)	Level
Technique	“systematic procedures and approaches for generating or selecting the most suitable test suites” (Washizaki, 2024, p. 5-10) “on a sound theoretical basis” (Barbosa et al., 2006, p. 3)	specification-, structure-, experience-, fault-, usage-based testing (Washizaki, 2024, pp. 5-10, 5-13 to 5-15); black-box, white-box, defect/fault-based, model-based testing (Souza et al., 2017, p. 3); functional, structural, error-based, state-based testing (Barbosa et al., 2006, p. 3)	Technique

find original source for S
EtAl2017 te
nique exam
Mathur (20

Different sources categorize software testing approaches in different ways; while it is useful to record and think about these categorizations (see [Section 2.3.4](#)), following one (or more) during the research stage could lead to bias and a prescriptive categorization, instead of letting one emerge descriptively during the analysis stage. Since these categorizations are not mutually exclusive, it also means that more than one could be useful (both in general and to this specific project). [ISO/IEC and IEEE \(2022\)](#) provide a classification for different kinds of tests (see [Table 2.1](#)). A deeper rationale for a proposed classification will be given during the analysis stage.

However, other sources ([Barbosa et al., 2006](#); [Souza et al., 2017](#)) provide alternate categories (see [Table 2.2](#)) which may be beneficial to investigate to determine if this categorization is sufficient. A “metric” categorization was considered at one point, but was decided to be out of the scope of this project (see [Section 2.1](#)), [#21](#), and [#22](#). Related testing approaches may be grouped into a “class” or “family” to group those with “commonalities and well-identified variabilities that can be instantiated”, where “the commonalities are large and the variabilities smaller” (see [#64](#)). Examples of these are the classes of combinatorial ([ISO/IEC and IEEE, 2021](#), p. 15) and data flow testing (p. 3) and the family of performance-related testing ([Moghadam, 2019](#), p. 1187)⁸, and may also be implied for security testing, a test type that consists of “a number of techniques⁹” ([ISO/IEC and IEEE, 2021](#), p. 40).

It also seems that these categories are orthogonal. For example, “a test type can be performed at a single test level or across several test levels” ([ISO/IEC and IEEE, 2022](#), p. 15; [2021](#), p. 7). Due to this, a specific test approach can be derived by combining test approaches from different categories; see [Section 2.3.3](#) for some examples of this.

2.3.2 Derived Test Approaches

Since the field of software is ever-evolving, being able to adapt to new developments, as well as being able to talk about and understand them, is crucial. In addition to methods of categorizing test approaches, the literature also provides the following methods of deriving new ones.

Coverage-driven Techniques

Test techniques are able to “identify test coverage items ... and derive corresponding test cases” ([ISO/IEC and IEEE, 2022](#), p. 11; similar in [2017](#), p. 467) in a “systematic” way ([2017](#), p. 464). This allows for “the coverage achieved by a specific test design technique” to be calculated as “the number of test coverage items covered by executed test cases” divided by “the total number of test coverage items identi-

⁸The original source describes “performance testing ... as a family of performance-related testing techniques”, but it makes more sense to consider “performance-related testing” as the “family” with “performance testing” being one of the variabilities (see [Section 2.15.3](#)).

⁹This may or may not be distinct from the notion of “test technique” described in [IEEE Testing Terminology](#).

fied” (2021, p. 30). “Coverage levels can range from 0% to 100%” and may or may not include “infeasible” test coverage items, which are “not ... executable or [are] impossible to be covered by a test case” (p. 30). Perhaps more interestingly, the further implication is that a given coverage metric implies a test approach aimed to maximize it; for example, “path testing” is testing that “aims to execute all entry-to-exit control flow paths in a SUT’s control flow graph” (Washizaki, 2024, p. 5013), thus maximizing the path coverage (see also #63, (Sharma et al., 2021, Fig. 1)).

Quality-driven Types

Since test types are “focused on specific quality characteristics” (ISO/IEC and IEEE, 2022, p. 15; 2021, p. 7; 2017, p. 473), they can be derived from software qualities: “capabilit[ies] of software product[s] to satisfy stated and implied needs when used under specified conditions” (ISO/IEC and IEEE, 2017, p. 424). This is supported by reliability and performance testing, which are both examples of test types (ISO/IEC and IEEE, 2022; 2021) that are based on their underlying qualities (Fenton and Pfleeger, 1997, p. 18). For quantifying quality-driven testing, measurements should include an entity to be measured, a specific attribute to measure, and the actual measure (i.e., units, starting state, ending state, what to include) (1997, p. 36) where attributes must be defined before they can be measured (p. 38).

Given the importance of software qualities to defining test types, the definitions of 75 software qualities are also tracked in this current work (see #21, #23, and #27). This was done by capturing their definitions, any precedent for the existence of an associated test type, and any additional notes in a glossary. Over time, software qualities were “upgraded” to test types when mentioned (or implied) by a source.

Requirements-driven Approaches

While not as universally applicable, some types of requirements have associated types of testing (e.g., functional, non-functional, security). This may mean that categories of requirements *also* imply related testing approaches (such as “technical testing”). Even assuming this is the case, some types of requirements do not apply to the code itself, and as such are out of scope (see #43), such as:

- **Nontechnical Requirement:** a “requirement affecting product and service acquisition or development that is not a property of the product or service” (ISO/IEC and IEEE, 2017, p. 293)
- **Physical Requirement:** a “requirement that specifies a physical characteristic that a system or system component must possess” (ISO/IEC and IEEE, 2017, p. 322)

Attacks

Since attacks are given as a test practice (ISO/IEC and IEEE, 2022, p. 34), different kinds of software attacks, such as code injection and password cracking, can also be used as test approaches.

2.3.3 Orthogonally Derived Test Approaches

Some test approaches appear to be combinations of other (seemingly orthogonal) approaches. We indicate the combination for the first item, but omit them (for space) otherwise as the name makes it clear what the combination is. Some examples:

- Black box conformance testing (Jard et al., 1999, p. 25) (combining black box and conformance testing)
- Black-box integration testing (Sakamoto et al., 2013, p. 345-346)
- Checklist-based reviews (Hamburg and Mogyorodi, 2024)
- Closed-loop HiL verification (Preuße et al., 2012, p. 6)
- Closed-loop protection system testing (Forsyth et al., 2004, p. 331)
- Endurance stability testing (Firesmith, 2015, p. 55)
- End-to-end functionality testing (ISO/IEC and IEEE, 2021, p. 20; Gerrard, 2000a, Tab. 2)
- Formal reviews (Hamburg and Mogyorodi, 2024)
- Gray-box integration testing (Sakamoto et al., 2013, p. 344)
- Incremental integration testing (Sharma et al., 2021, p. 601)
- Informal reviews (Hamburg and Mogyorodi, 2024)
- Infrastructure compatibility testing (Firesmith, 2015, p. 53)
- Invariant-based automatic testing (Doğan et al., 2014, pp. 184-185, Tab. 21), including for “AJAX user interfaces” (p. 191)
- Legacy system integration (testing) (Gerrard, 2000a, Tab. 2)
- Machine learning-assisted performance testing? (Moghadam, 2019)
- Manual procedure testing (Firesmith, 2015, p. 47)
- Manual security audits (Gerrard, 2000b, p. 28)
- Model-based GUI testing (Doğan et al., 2014, Tab. 1; implied by Sakamoto et al., 2013, p. 356)

- Model-based web application testing (implied by [Sakamoto et al., 2013](#), p. 356)
- Non-functional search-based testing ([Doğan et al., 2014](#), Tab. 1)
- Offline MBT ([Hamburg and Mogyorodi, 2024](#))
- Online MBT ([Hamburg and Mogyorodi, 2024](#))
- Role-based reviews ([Hamburg and Mogyorodi, 2024](#))
- Scenario walkthroughs ([Gerrard, 2000a](#), Fig. 4)
- Scenario-based reviews ([Hamburg and Mogyorodi, 2024](#))
- Security attacks ([Hamburg and Mogyorodi, 2024](#))
- Statistical web testing ([Doğan et al., 2014](#), p. 185)
- Usability test script(ing) ([Hamburg and Mogyorodi, 2024](#))
- Web application regression testing ([Doğan et al., 2014](#), Tab. 21)
- White-box unit testing ([Sakamoto et al., 2013](#), pp. 345-346)

Some classes seem to be closely associated, such as remote testing with asynchronous testing, and local with synchronous ([Jard et al., 1999](#)), possibly implying a parent-child relation rather than a combination.

2.3.4 Categorizations

Software testing approaches can be divided into the following categories. Note that “there is a lot of overlap between different classes of testing” ([Firesmith, 2015](#), p. 8), meaning that “one category [of test techniques] might deal with combining two or more techniques” ([Washizaki, 2024](#), p. 5-10). For example, “performance, load and stress testing might considerably overlap in many areas” ([Moghadam, 2019](#), p. 1187). A side effect of this is that it is difficult to “untangle” these classes; for example, take the following sentence: “whitebox fuzzing extends dynamic test generation based on symbolic execution and constraint solving from unit testing to whole-application security testing” ([Godefroid and Luchaup, 2011](#), p. 23)!

Despite its challenges, it is useful to understand the differences between testing classes because tests from multiple subsets within the same category, such as functional and structural, “use different sources of information and have been shown to highlight different problems” ([Washizaki, 2024](#), p. 5-16). However, some subsets, such as deterministic and random, may have “conditions that make one approach more effective than the other” ([Washizaki, 2024](#), p. 5-16).

- Visibility of code: black-, white-, or grey-box (specificational/functional, structural, or a mix of the two) ([ISO/IEC and IEEE, 2021](#), p. 8; [Washizaki, 2024](#), pp. 5-10, 5-16; [Sharma et al., 2021](#), p. 601, called “testing approaches”

- OG [3, 4, 5, 8] and (stepwise) code reading replaced “grey-box testing”; [Ammann and Offutt, 2017](#), pp. 57-58; [Kuřšovs et al., 2013](#), p. 213; [Patton, 2006](#), pp. 53, 218; [Perry, 2006](#), p. 69; [Kam, 2008](#), pp. 4-5, called “testing methods”)
- OG Black, 2009
- Level/stage¹⁰ of testing: unit, integration, system, or acceptance ([Washizaki, 2024](#), pp. 5-6 to 5-7; [Hamburg and Mogyorođi, 2024](#); [Kuřšovs et al., 2013](#), p. 218; [Patton, 2006](#); [Perry, 2006](#); [Peters and Pedrycz, 2000](#); [Gerrard, 2000a](#), pp. 9, 13) (sometimes includes installation ([van Vliet, 2000](#), p. 439) or regression ([Barbosa et al., 2006](#), p. 3))
 - Source of information for design: specification, structure, or experience ([ISO/IEC and IEEE, 2021](#), p. 8)
 - Source of test data: specification-, implementation-, or error-oriented ([Peters and Pedrycz, 2000](#), p. 440)
 - Test case selection process: deterministic or random ([Washizaki, 2024](#), p. 5-16)
 - Coverage criteria: input space partitioning, graph coverage, logic coverage, or syntax-based testing ([Ammann and Offutt, 2017](#), pp. 18-19)
 - Question: what-, when-, where-, who-, why-, how-, and how-well-based testing; these are then divided into a total of “16 categories of testing types”¹¹ ([Firesmith, 2015](#), p. 17)
 - Execution of code: static or dynamic ([Kuřšovs et al., 2013](#), p. 214; [Gerrard, 2000a](#), p. 12; [Patton, 2006](#), p. 53)
 - Goal of testing: verification or validation ([Kuřšovs et al., 2013](#), p. 214; [Perry, 2006](#), pp. 69-70)
 - Property of code ([Kuřšovs et al., 2013](#), p. 213) or test target ([Kam, 2008](#), pp. 4-5): functional or non-functional
 - Human involvement: manual or automated ([Kuřšovs et al., 2013](#), p. 214)
 - Structuredness: scripted or exploratory ([Kuřšovs et al., 2013](#), p. 214)
 - Coverage requirement: data or control flow ([Kam, 2008](#), pp. 4-5)
 - Adequacy criterion: coverage-, fault-, or error-based (“based on knowledge of the typical errors that people make”) ([van Vliet, 2000](#), pp. 398-399)
 - Priority¹²: smoke, usability, performance, or functionality testing ([Gerrard, 2000a](#), p. 12)

¹⁰See [Table 2.1](#).

¹¹Not formally defined, but distinct from the notion of “test type” described in [IEEE Testing Terminology](#).

¹²In the context of testing e-business projects.

- Category of test “type”¹³: static testing, test browsing, functional testing, non-functional testing, or large scale integration (testing) (Gerrard, 2000a, p. 12)
- Purpose: correctness, performance, reliability, or security (Pan, 1999)

Tests can also be tailored to “test factors” (also called “quality factors” or “quality attributes”): “attributes of the software that, if they are wanted, pose a risk to the success of the software” (Perry, 2006, p. 40). These include correctness, file integrity, authorization, audit trail, continuity of processing, service levels (e.g., response time), access control, compliance, reliability, ease of use, maintainability, portability, coupling (e.g., with other applications in a given environment), performance, and ease of operation (e.g., documentation, training) (Perry, 2006, pp. 40-41). *These may overlap with Derived Test Approaches and/or the “Results of Testing (Area of Confidence)” column in the summary spreadsheet.*

Engström “investigated classifications of research” (Engström and Petersen, 2015, p. 1) on the following four testing techniques. *These four categories seem like comparing apples to oranges to me.*

- **Combinatorial testing:** how the system under test is modelled, “which combination strategies are used to generate test suites and how test cases are prioritized” (Engström and Petersen, 2015, pp. 1-2)
- **Model-based testing:** the information represented and described by the test model (Engström and Petersen, 2015, p. 2)
- **Search-based testing:** “how techniques ¹⁴ had been empirically evaluated (i.e. objective and context)” (Engström and Petersen, 2015, p. 2)
- **Unit testing:** “source of information (e.g. code, specifications or testers intuition)” (Engström and Petersen, 2015, p. 2)

2.3.5 Existing Taxonomies, Ontologies, and the State of Practice

One thing we may want to consider when building a taxonomy/ontology is the semantic difference between related terms. For example, one ontology found that the term “‘IntegrationTest’ is a kind of Context (with semantic of stage, but not a kind of Activity)” while “‘IntegrationTesting’ has semantic of Level-based Testing that is a kind of Testing Activity [or] ... of Test strategy” (Tebes et al., 2019, p. 157).

A note on testing artifacts is that they are “produced and used throughout the testing process” and include test plans, test procedures, test cases, and test results

¹³“Each type of test addresses a different risk area” (Gerrard, 2000a, p. 12), which is distinct from the notion of “test type” described in IEEE Testing Terminology.

¹⁴Not formally defined, but distinct from the notion of “test technique” described in IEEE Testing Terminology.

(Souza et al., 2017, p. 3). The role of testing artifacts is not specified in (Barbosa et al., 2006); requirements, drivers, and source code are all treated the same with no distinction (Barbosa et al., 2006, p. 3).

In (Souza et al., 2017), the ontology (ROoST) is made to answer a series of questions, including “What is the test level of a testing activity?” and “What are the artifacts used by a testing activity?” (Souza et al., 2017, pp. 8-9). The question “How do testing artifacts relate to each other?” (Souza et al., 2017, p. 8) is later broken down into multiple questions, such as “What are the test case inputs of a given test case?” and “What are the expected results of a given test case?” (Souza et al., 2017, p. 21). *These questions seem to overlap with the questions we were trying to ask about different testing techniques.*

Most ontologies I can find seem to focus on the high-level testing process rather than the testing approaches themselves. For example, the terms and definitions (Teves et al., 2020b) from TestTDO (Teves et al., 2020a) provide *some* definitions of testing approaches, but mainly focus on parts of the testing process (e.g., test goal, test plan, testing role, testable entity) and how they relate to one another. Teves et al. (2019, pp. 152-153) may provide some sources for software testing terminology and definitions (this seems to include **the ones suggested by Dr. Carette**) in addition to a list of ontologies (some of which have been investigated).

One software testing model developed by the Quality Assurance Institute (QAI) includes the test environment (“conditions ...that both enable and constrain how testing is performed”, including mission, goals, strategy, “management support, resources, work processes, tools, motivation”), test process (testing “standards and procedures”), and tester competency (“skill sets needed to test software in a test environment”) (Perry, 2006, pp. 5-6).

Unterkalmsteiner et al. (2014) provide a foundation to allow one “to classify and characterize alignment research and solutions that focus on the boundary between [requirements engineering and software testing]” but “do[] not aim at providing a systematic and exhaustive state-of-the-art survey of [either domain]” (p. A:2).

Another source introduced the notion of an “intervention”: “an act performed (e.g. use of a technique¹⁵ or a process change) to adapt testing to a specific context, to solve a test issue, to diagnose testing or to improve testing” (Engström and Petersen, 2015, p. 1) and noted that “academia tend[s] to focus on characteristics of the intervention [while] industrial standards categorize the area from a process perspective” (Engström and Petersen, 2015, p. 2). It provides a structure to “capture both a problem perspective and a solution perspective with respect to software testing” (Engström and Petersen, 2015, pp. 3-4), but this seems to focus more on test interventions and challenges rather than approaches (Engström and Petersen, 2015, Fig. 5).

¹⁵Not formally defined, but distinct from the notion of “test technique” described in **IEEE Testing Terminology**.

add acronym?
is this punctuation right?

2.4 Discrepancies and Ambiguities

After gathering all this data¹⁶, we found many discrepancies and ambiguities. A summary of the number of different kinds of discrepancies is shown in [Table 2.3](#), where a given row corresponds to the number of discrepancies either within/between one or more sources within that category and/or between a source of that category and one of a “more trusted” source (i.e., a source from a category higher up in the table). Issues with [Synonyms](#), [Parent Relations](#), and [Categories of Testing Approaches](#) are (Exp)licit or (Imp)lied. Issues with the following test approaches are also given: [\(Func\)ctional Testing](#), [Orthogonal Array Testing \(OAT\)](#), [\(Rec\)overy Testing](#), and [\(Scal\)ability Testing](#). [Other Discrepancies](#) are grouped into degrees of severity as follows. (Note that only select discrepancies are listed for brevity.)

- High: Semantic differences between test approaches
- (Med)ium: Differences in supporting information about test approaches
- Low: Typos, redundant information, or referencing issues

Table 2.3: Breakdown of Discrepancies Found

Source Category	Synonyms		Parents		Categories		Standalone			
	Exp	Imp	Exp	Imp	Exp	Imp	Func	OAT	Rec	Sc
Established Standards	0	0	2	1	7	2	2	1	4	1
“Meta-level” Collections	2	1	1	5	2	6	5	1	1	1
Trusted Textbooks	2	0	1	0	1	0	0	0	0	0
Other	6	6	6	6	3	0	3	1	1	1
Total	10	7	10	12	13	8	10	3	6	3

2.4.1 Synonyms

The same approach often has many names. For example, *specification-based testing* is also called:

1. Black-Box Testing ([ISO/IEC and IEEE, 2022](#), p. 9; [2021](#), p. 8; [2017](#), p. 431; [Washizaki, 2024](#), p. 5-10; [Hamburg and Mogyorodi, 2024](#); [Firesmith, 2015](#), p. 46 (without hyphen); [Sakamoto et al., 2013](#), p. 344; [van Vliet, 2000](#), p. 399)
2. Closed-Box Testing ([ISO/IEC and IEEE, 2022](#), p. 9; [2017](#), p. 431)

¹⁶Available in `ApproachGlossary.csv` and `QualityGlossary.csv` at [Repository link suppressed].

more in
Umar2000

3. Functional Testing¹⁷ (2017, p. 196; Kam, 2008, p. 44; van Vliet, 2000, p. 399; implied by 2021, p. 129; 2017, p. 431)
4. Domain Testing (Washizaki, 2024, p. 5-10)
5. Input Domain-Based Testing (implied by (Bourque and Fairley, 2014, p. 4-8))

While some of these synonyms may express mild variations, their core meaning is nevertheless the same. Here we use the terms “specification-based” and “structure-based testing” as they articulate the source of the information for designing test cases, but a team or project also using gray-box testing may prefer the terms “black-box” and “white-box testing” for consistency. Thus, synonyms do not inherently signify a discrepancy. Unfortunately, there are many instances of incorrect or ambiguous synonyms, such as the following:

1. Sneed and Göschl give “white-”, “grey-”, and “black-box testing” as synonyms for “module”, “integration”, and “system testing”, respectively (2000, p. 18), but this mapping is incorrect; black-box testing can be performed on a module, for example. This makes the claim that “red-box testing” is a synonym for “acceptance testing” (p. 18) lose credibility.
2. “Program testing” is given as a synonym of “component testing” (Kam, 2008, p. 46), although it probably should be a synonym of “system testing” instead.
3. Kam seems to imply that “mutation testing” is a synonym of “back-to-back testing” (2008, p. 46), but these are two quite distinct techniques.
4. “Conformance testing” is implied to be a synonym of “compliance testing” by Kam, which only makes sense because of the vague definition of “compliance testing”: “testing to determine the compliance of the component or system” (2008, p. 43).

There are also cases in which a term is given a synonym to two (or more) disjoint, unrelated terms, which would be a source of ambiguity to teams using these terms. Ten of these cases were identified through automatic analysis of the generated graphs, listed below (synonyms in *italics* have at least one of their synonyms implied):

1. Invalid Testing:

- Error Tolerance Testing (Kam, 2008, p. 45)
- Negative Testing (Hamburg and Mogyorodi, 2024; implied by ISO/IEC and IEEE, 2021, p. 10)

2. Soak Testing:

¹⁷This may be an outlier; see Section 2.4.4.

- Endurance Testing (ISO/IEC and IEEE, 2021, p. 39)
- Reliability Testing (Gerrard, 2000a, Tab. 2; 2000b, Tab. 1, p. 26)

3. **User Scenario Testing:**

- Scenario Testing (Hamburg and Mogyorodi, 2024)
- Use Case Testing (Kam, 2008, p. 48; although “an actor can be a user or another system” (ISO/IEC and IEEE, 2021, p. 20))

4. **(Multiple) Condition Testing:**

- Branch Condition Combination Testing (Hamburg and Mogyorodi, 2024; Patton, 2006, p. 120)
- Branch Condition Testing (Patton, 2006, p. 120)

5. **Extended Branch Coverage:**

- Branch Condition Combination Testing (van Vliet, 2000, p. 422)
- Branch Condition Testing (van Vliet, 2000, p. 422)

6. **Link Testing:**

- Branch Testing (implied by ISO/IEC and IEEE, 2021, p. 24)
- Component Integration Testing (Kam, 2008, p. 45)
- Integration Testing (implied by Gerrard, 2000a, p. 13)

7. **State-based Testing:**

- State Transition Testing (Firesmith, 2015, p. 47)
- State-based Web Browser Testing (Doğan et al., 2014, p. 193)

8. **Static Verification:**

- Static Assertion Checking (Chalin et al., 2006, p. 343)
- Static Testing (implied by Chalin et al., 2006, p. 343)

9. **Production Acceptance Testing:**

- Operational Testing (Hamburg and Mogyorodi, 2024)
- Production Verification Testing

10. **Operational Testing:**

- Field Testing
- Qualification Testing

Some interesting notes about these synonyms:

- The terms are not synonyms, although endurance testing is given as a kind of reliability testing by Firesmith (2015, p. 55).
- “Scenario testing” and “use case testing” are given as synonyms by Hamburg and Mogyorodi (2024) and Kam (2008, pp. 47-49), but listed separately by ISO/IEC and IEEE (2022, p. 22), who also give “use case testing” as a “common form of scenario testing” (2021, p. 20).
- Chalin et al. list Runtime Assertion Checking (RAC) and Software Verification (SV) as “two complementary forms of assertion checking” (2006, p. 343); based on how the term “static assertion checking” is used by Lahiri et al. (2013, p. 345), it seems like this should be the complement to RAC instead.
- “Operational” and “production acceptance testing” are treated as synonyms by Hamburg and Mogyorodi (2024), but listed separately by Firesmith (2015, p. 30).
- “Production acceptance testing” (Firesmith, 2015, p. 30) seems to be the same as “production verification testing” (ISO/IEC and IEEE, 2022, p. 22), but neither are defined.

2.4.2 Parent Relations

Parent relations are not immune to difficulties, including self-referential definitions, which were identified through automatic analysis of the generated graphs.

1. Performance Testing (Gerrard, 2000a, Tab. 2; 2000b, Tab. 1)
2. Usability Testing (Gerrard, 2000a, Tab. 2; 2000b, Tab. 1)

Performance testing is *not* described as a sub-approach of usability testing by (Gerrard, 2000a;b), which would have been more meaningful information to capture.

There are also pairs of synonyms where one is described as a sub-approach of the other, abusing the meaning of “synonym” and causing confusion. In the next list, lack of source implies the relationship is inferrable from the terms’ definitions.

1. “**All transitions testing**” is called a sub-approach of “**state transition testing**” in (ISO/IEC and IEEE, 2021, p. 19), but the two are called synonyms in (Kam, 2008, p. 15).
2. “**Co-existence testing**” is called a sub-approach of “**compatibility testing**” in (ISO/IEC, 2023a; ISO/IEC and IEEE, 2022, p. 3; 2021, Tab. A.1), but the two are called synonyms in (ISO/IEC and IEEE, 2021, p. 37).
3. “**Fault tolerance testing**” is called a sub-approach of “**robustness testing**” in (Firesmith, 2015, p. 56), but the two are called synonyms in (Hamburg and Mogyorodi, 2024).

4. “**Functional testing**” is called a sub-approach of “**specification-based testing**” in (ISO/IEC and IEEE, 2021, p. 38), but the two are called synonyms in (ISO/IEC and IEEE, 2017, p. 196; Kam, 2008, p. 44; van Vliet, 2000, p. 399; implied by ISO/IEC and IEEE, 2021, p. 129; 2017, p. 431).
5. “**Orthogonal array testing**” is called a sub-approach of “**pairwise testing**” in (Mandl, 1985, p. 1055), but the two are called synonyms in (Washizaki, 2024, p. 5-11; Valcheva, 2013, p. 473).
6. “**Performance testing**” is called a sub-approach of “**performance-related testing**” in (ISO/IEC and IEEE, 2022, p. 22; 2021, p. 38), but the two are called synonyms in (Moghadam, 2019, p. 1187).
7. “**Use case testing**” is called a sub-approach of “**scenario testing**” in (ISO/IEC and IEEE, 2021, p. 20), but the two are called synonyms in (Hamburg and Mogyorodi, 2024; Kam, 2008, pp. 47-49).
8. “**Condition testing**” is implied to be a sub-approach of “**decision testing**” in (Hamburg and Mogyorodi, 2024), but the two are called synonyms in (Washizaki, 2024, p. 5-13).
9. “**Dynamic analysis**” is implied by its static counterpart to be a sub-approach of “**dynamic testing**” in (ISO/IEC and IEEE, 2022, pp. 9, 17, 25, 28; Hamburg and Mogyorodi, 2024), but the two are called synonyms in (ISO/IEC and IEEE, 2017, p. 149).
10. “**Beta testing**” is implied to be a sub-approach of “**user testing**” in (Firesmith, 2015, p. 39), but the two are implied to be synonyms in (Firesmith, 2015, p. 39).
11. “**Functionality testing**” may be a sub-approach of “**functional suitability testing**”, but the two are called synonyms in (Hamburg and Mogyorodi, 2024).
12. “**Programmer testing**” is called a sub-approach of “**developer testing**” in (Firesmith, 2015, p. 39), but the two may be synonyms.
13. “**Structured walkthroughs**” may be a sub-approach of “**walkthroughs**”, but the two are called synonyms in (Hamburg and Mogyorodi, 2024).
14. “**Functionality testing**” may be a sub-approach of “**functional suitability testing**”, but the two are implied to be synonyms in (Hamburg and Mogyorodi, 2024).

The relationships between the following pairs of approaches aren’t given in any investigated sources and are also ambiguous, based on their definitions. In each pair, the first may be a sub-approach of the second, or they may be synonyms.

- Field testing and operational testing

OG Hass, 2008

- Organization-based testing and role-based testing
- System qualification testing and system testing

Finally, it is worth pointing out that

- Fault tolerance testing may also be a sub-approach of reliability testing (ISO/IEC and IEEE, 2017, p. 375; Washizaki, 2024, p. 7-10), which is distinct from robustness testing (Firesmith, 2015, p. 53).
- The distinction between organization- and role-based testing in (Firesmith, 2015, pp. 17, 37, 39) seems arbitrary, but further investigation may prove it to be meaningful (see #59).

2.4.3 Categories of Testing Approaches

While the IEEE categorization of testing approaches is useful, it is not without its faults. The boundaries between items within a category may be unclear: “although each technique is defined independently of all others, in practice [sic] some can be used in combination with other techniques” (ISO/IEC and IEEE, 2021, p. 8). For example, “the test coverage items derived by applying equivalence partitioning can be used to identify the input parameters of test cases derived for scenario testing” (p. 8). Even the categories themselves are not consistently defined, and some approaches are categorized differently by different sources:

1. ISO/IEC and IEEE categorize experience-based testing as both a test design technique and a test practice on the same page—twice (2022, Fig. 2, p. 34)!
 - These authors previously say “experience-based testing practices like exploratory testing ... are not ... techniques for designing test cases”, although they “can use ... test techniques” (2021, p. viii). This implies that “experience-based test design techniques” are techniques used by the *practice* of experience-based testing, not that experience-based testing is *itself* a test technique. If this is the case, it is not always clearly articulated (ISO/IEC and IEEE, 2022, pp. 4, 22; 2021, p. 4; Washizaki, 2024, p. 5-13; Hamburg and Mogyorodi, 2024) and is sometimes contradicted (Firesmith, 2015, p. 46). However, this conflates the distinction between “practice” and “technique”, making these terms less useful, so this may just be a mistake (see #64).
 - This also causes confusion about its children, such as error guessing and exploratory testing; again, on the same page, ISO/IEC and IEEE say error guessing is an “experience-based test design technique” and “experience-based test practices include ... exploratory testing, tours, attacks, and checklist-based testing” (2022, p. 34). Other sources also do not agree whether error guessing is a technique (pp. 20, 22; 2021, p. viii) or a practice (Washizaki, 2024, p. 5-14).

2. The following test approaches are categorized as test techniques by (ISO/IEC and IEEE, 2021, p. 38) and as test types by the sources provided:
 - (a) Capacity testing (ISO/IEC and IEEE, 2022, p. 22; 2013, p. 2; implied by its quality (ISO/IEC, 2023a; ISO/IEC and IEEE, 2021, Tab. A.1) and by (Firesmith, 2015, p. 53)),
 - (b) Endurance testing (ISO/IEC and IEEE, 2013, p. 2; implied by (Firesmith, 2015, p. 55)),
 - (c) Load testing (ISO/IEC and IEEE, 2022, pp. 5, 20, 22; 2017, p. 253; Hamburg and Mogyorodi, 2024; implied by (Firesmith, 2015, p. 54)),
 - (d) Performance testing (ISO/IEC and IEEE, 2022, pp. 7, 22, 26-27; 2021, p. 7; implied by (Firesmith, 2015, p. 53)), and
 - (e) Stress testing (ISO/IEC and IEEE, 2022, pp. 9, 22; 2017, p. 442; implied by (Firesmith, 2015, p. 54)).
3. “Installability testing” is given as a test type (ISO/IEC and IEEE, 2022, p. 22; 2021, p. 38) but is sometimes called a test level as “installation testing” (Peters and Pedrycz, 2000, p. 445).
4. Model-based testing is categorized as both a test practice (ISO/IEC and IEEE, 2022, p. 22; 2021, p. viii) and a test technique (Kam, 2008, p. 4; implied by ISO/IEC and IEEE, 2021, p. 7; 2017, p. 469).
5. Data-driven testing is categorized as both a test practice (ISO/IEC and IEEE, 2022, p. 22) and a test technique (Kam, 2008, p. 43).
6. Although ad hoc testing is sometimes classified as a “technique” (Washizaki, 2024, p. 5-14), it is one in which “no recognized test design technique is used” (Kam, 2008, p. 42).

There are also instances of inconsistencies between parent and child test approach categorizations. This may indicate they aren’t necessarily the same, or that more thought must be given to this method of classification.

2.4.4 Functional Testing

“Functional testing” is described alongside many other, likely related, terms. This leads to confusion about what distinguishes these terms, as shown by the following five:

Specification-based Testing

This is defined as “testing in which the principal test basis is the external inputs and outputs of the test item” (ISO/IEC and IEEE, 2022, p. 9). This agrees with a definition of “functional testing”: “testing that ... focuses solely on the outputs generated in response to selected inputs and execution conditions” (ISO/IEC and IEEE, 2017, p. 196). Notably, ISO/IEC and IEEE (2017) lists both as synonyms

OG IEEE 2013

OG Fewster and Graham

van Vliet (2000, p. 399) may list these as synonyms; investigate

of “black-box testing” (pp. 431, 196, respectively), despite them sometimes being defined separately. For example, the International Software Testing Qualifications Board (ISTQB) defines “specification-based testing” as “testing based on an analysis of the specification of the component or system” (and gives “black-box testing” as a synonym) and “functional testing” as “testing performed to evaluate if a component or system satisfies functional requirements” (specifying no synonyms) (Hamburg and Mogyorodi, 2024); the latter references ISO/IEC and IEEE (2017, p. 196) (“testing conducted to evaluate the compliance of a system or component with specified functional requirements”) which *has* “black-box testing” as a synonym, and mirrors ISO/IEC and IEEE (2022, p. 21) (testing “used to check the implementation of functional requirements”). Overall, specification-based testing (ISO/IEC and IEEE, 2022, pp. 2-4, 6-9, 22) and black-box testing (Washizaki, 2024, p. 5-10; Souza et al., 2017, p. 3) are test design techniques used to “derive corresponding test cases” (ISO/IEC and IEEE, 2022, p. 11) from “selected inputs and execution conditions” (ISO/IEC and IEEE, 2017, p. 196).

Correctness Testing

Washizaki says “test cases can be designed to check that the functional specifications are correctly implemented, which is variously referred to in the literature as conformance testing, correctness testing or functional testing” (2024, p. 5-7); this mirrors previous definitions of “functional testing” (ISO/IEC and IEEE, 2022, p. 21; 2017, p. 196) but groups it with “correctness testing”. Since “correctness” is a software quality (ISO/IEC and IEEE, 2017, p. 104; Washizaki, 2024, p. 3-13) which is what defines a “test type” (ISO/IEC and IEEE, 2022, p. 15) (see Section 2.3.2), it seems consistent to label “functional testing” as a “test type” (ISO/IEC and IEEE, 2022, pp. 15, 20, 22); this conflicts with its categorization as a “technique” if considered a synonym of Specification-based Testing. “Correctness testing” is listed separately from “functionality testing” by Firesmith (2015, p. 53).

Conformance Testing

Testing that ensures “that the functional specifications are correctly implemented”, and can be called “conformance testing” or “functional testing” (Washizaki, 2024, p. 5-7). “Conformance testing” is later defined as testing used “to verify that the SUT conforms to standards, rules, specifications, requirements, design, processes, or practices” (Washizaki, 2024, p. 5-7). This definition seems to be a superset of testing methods mentioned earlier as the latter includes “standards, rules, requirements, design, processes, ... [and]” practices in *addition* to specifications!

A complicating factor is that “compliance testing” is also (plausibly) given as a synonym of “conformance testing” (Kam, 2008, p. 43). However, “conformance testing” can also be defined as testing that evaluates the degree to which “results ... fall within the limits that define acceptable variation for a quality requirement” (ISO/IEC and IEEE, 2017, p. 93), which seems to describe something different.

Functional Suitability Testing

Procedure testing is called a “type of functional suitability testing” (ISO/IEC and IEEE, 2022, p. 7), but no definition of that term is given. “Functional suitability” is the “capability of a product to provide functions that meet stated and implied needs of intended users when it is used under specified conditions”, including meeting “the functional specification” (ISO/IEC, 2023a). This seems to align with the definition of “functional testing” as related to “black-box/specification-based testing”. “Functional suitability” has three child terms: “functional completeness” (the “capability of a product to provide a set of functions that covers all the specified tasks and intended users’ objectives”), “functional correctness” (the “capability of a product to provide accurate results when used by intended users”), and “functional appropriateness” (the “capability of a product to provide functions that facilitate the accomplishment of specified tasks and objectives”) (ISO/IEC, 2023a). Notably, “functional correctness”, which includes precision and accuracy (ISO/IEC, 2023a; Hamburg and Mogyorodi, 2024), seems to align with the quality/ies that would be tested by “correctness” testing.

Functionality Testing

“Functionality” is defined as the “capabilities of the various ... features provided by a product” (ISO/IEC and IEEE, 2017, p. 196) and is said to be a synonym of “functional suitability” (Hamburg and Mogyorodi, 2024), although it seems like it should really be its “parent”. Its associated test type is implied to be a sub-approach of build verification testing (Hamburg and Mogyorodi, 2024) and made distinct from “functional testing”; interestingly, security is described as a sub-approach of both non-functional and functionality testing (Gerrard, 2000a, Tab. 2). “Functionality testing” is listed separately from “correctness testing” by Firesmith (2015, p. 53).

2.4.5 Operational (Acceptance) Testing

Some sources refer to “operational acceptance testing” (ISO/IEC and IEEE, 2022, p. 22; Hamburg and Mogyorodi, 2024) while some refer to “operational testing” (Washizaki, 2024, p. 6-9, in the context of software engineering operations; ISO/IEC, 2018; ISO/IEC and IEEE, 2017, p. 303; Bourque and Fairley, 2014, pp. 4-6, 4-9). A distinction is sometimes made (Firesmith, 2015, p. 30) but without accompanying definitions, it is hard to evaluate its merit. Since this terminology is not standardized, I propose that the two terms are treated as synonyms (as done by other sources (LambdaTest, 2024; Bocchino and Hamilton, 1996)) as a type of acceptance testing (ISO/IEC and IEEE, 2022, p. 22; Hamburg and Mogyorodi, 2024) that focuses on “non-functional” attributes of the system (LambdaTest, 2024).

A summary of definitions of “operational (acceptance) testing” is that it is “test[ing] to determine the correct installation, configuration and operation of a module and that it operates securely in the operational environment” (ISO/IEC, 2018) or “evaluate a system or component in its operational environment” (ISO/IEC

and IEEE, 2017, p. 303), particularly “to determine if operations and/or systems administration staff can accept [it]” (Hamburg and Mogyorodi, 2024).

2.4.6 Recovery Testing

“Recovery testing” is “testing ... aimed at verifying software restart capabilities after a system crash or other disaster” (Washizaki, 2024, p. 5-9) including “recover[ing] the data directly affected and re-establish[ing] the desired state of the system” (ISO/IEC, 2023a; similar in Washizaki, 2024, p. 7-10) so that the system “can perform required functions” (ISO/IEC and IEEE, 2017, p. 370). It is also called “recoverability testing” (Kam, 2008, p. 47) and potentially “restart & recovery (testing)” (Gerrard, 2000a, Fig. 5). The following terms, along with “recovery testing” itself (ISO/IEC and IEEE, 2022, p. 22) are all classified as test types, and the relations between them can be found in Figure 2.1.

- **Recoverability Testing:** Testing “how well a system or software can recover data during an interruption or failure” (Washizaki, 2024, p. 7-10; similar in ISO/IEC, 2023a) and “re-establish the desired state of the system” (ISO/IEC, 2023a). Synonym for “recovery testing” in Kam (2008, p. 47).
- **Disaster/Recovery Testing** serves to evaluate if a system can “return to normal operation after a hardware or software failure” (ISO/IEC and IEEE, 2017, p. 140) or if “operation of the test item can be transferred to a different operating site and ... be transferred back again once the failure has been resolved” (2021, p. 37). These two definitions seem to describe different aspects of the system, where the first is intrinsic to the hardware/software and the second might not be.
- **Backup and Recovery Testing** “measures the degree to which system state can be restored from backup within specified parameters of time, cost, completeness, and accuracy in the event of failure” (ISO/IEC and IEEE, 2013, p. 2). This may be what is meant by “recovery testing” in the context of performance-related testing and seems to correspond to the definition of “disaster/recovery testing” in (2017, p. 140).
- **Backup/Recovery Testing:** Testing that determines the ability “to restor[e] from back-up memory in the event of failure, without transfer[ing] to a different operating site or back-up system” (ISO/IEC and IEEE, 2021, p. 37). This seems to correspond to the definition of “disaster/recovery testing” in (2021, p. 37). It is also given as a sub-type of “disaster/recovery testing”, even though that tests if “operation of the test item can be transferred to a different operating site” (p. 37).
- **Failover/Recovery Testing:** Testing that determines the ability “to mov[e] to a back-up system in the event of failure, without transfer[ing] to a different operating site” (ISO/IEC and IEEE, 2021, p. 37). This is given as a sub-type of “disaster/recovery testing”, even though that tests if “operation of the test item can be transferred to a different operating site” (p. 37).

- **Failover Testing:** Testing that “validates the SUT’s ability to manage heavy loads or unexpected failure to continue typical operations” (Washizaki, 2024, p. 5-9) by entering a “backup operational mode in which [these responsibilities] ... are assumed by a secondary system” (Hamburg and Mogyorodi, 2024). While not *explicitly* related to recovery, “failover/recovery testing” also describes the idea of “failover”, and Firesmith uses the term “failover and recovery testing” (2015, p. 56), which could be a synonym of both of these terms.

2.4.7 Scalability Testing

There were three ambiguities around the term “scalability testing”, listed below. The relations between these test approaches (and other relevant ones) are shown in Figure 2.3.

1. ISO/IEC and IEEE give “scalability testing” as a synonym of “capacity testing” (2021, p. 39) while other sources differentiate between the two (Firesmith, 2015, p. 53; Bas, 2024, pp. 22-23)
2. ISO/IEC and IEEE give the external modification of the system as part of “scalability” (2021, p. 39), while ISO/IEC implies that it is limited to the system itself (2023a)
3. The SWEBOK Guide V4’s definition of “scalability testing” (Washizaki, 2024, p. 5-9) is really a definition of usability testing!

2.4.8 Other Discrepancies

We now outline discrepancies/ambiguities found in the literature that were not “large” enough to merit their own sections, grouped by the “categories” of sources outlined in Section 2.2.1.

Other Discrepancies from Standards

- “Compatibility testing” is defined as “testing that measures the degree to which a test item can function satisfactorily alongside other independent products in a shared environment (co-existence), and where necessary, exchanges information with other systems or components (interoperability)” (ISO/IEC and IEEE, 2022, p. 3). This definition is nonatomic as it combines the ideas of “co-existence” and “interoperability”. The term “interoperability testing” is not defined, but is used three times (ISO/IEC and IEEE, 2022, pp. 22, 43) (although the third usage seems like it should be “portability testing”). This implies that “co-existence testing” and “interoperability testing” should be defined as their own terms, which is supported by definitions of “co-existence” and “interoperability” often being separate (Hamburg and Mogyorodi, 2024; ISO/IEC and IEEE, 2017, pp. 73, 237), the definition of “interoperability testing” from ISO/IEC and IEEE (2017,

p. 238), and the decomposition of “compatibility” into “co-existence” and “interoperability” by ISO/IEC (2023a)!

- The “interoperability” element of “compatibility testing” is explicitly excluded by ISO/IEC and IEEE (2021, p. 37), (incorrectly) implying that “compatibility testing” and “co-existence testing” are synonyms.
 - The definition of “compatibility testing” in (Kam, 2008, p. 43) unhelpfully says “See *interoperability testing*”, adding another layer of confusion to the direction of their relationship.
- “Fuzz testing” is “tagged” (?) as “artificial intelligence” (ISO/IEC and IEEE, 2022, p. 5).
 - Integration, system, and system integration testing are all listed as “common test levels” (ISO/IEC and IEEE, 2022, p. 12; 2021, p. 6), but no definitions are given for the latter two, making it unclear what “system integration testing” is; it is a combination of the two? somewhere on the spectrum between them? It is listed as a child of integration testing by Hamburg and Mogyorodi (2024) and of system testing by Firesmith (2015, p. 23).
 - Similarly, component, integration, and component integration testing are all listed in (ISO/IEC and IEEE, 2017), but “component integration testing” is only defined as “testing of groups of related components” (ISO/IEC and IEEE, 2017, p. 82); it is a combination of the two? somewhere on the spectrum between them? Likewise, it is listed as a child of integration testing by Hamburg and Mogyorodi (2024).
 - Retesting and regression testing seem to be separated from the rest of the testing approaches (ISO/IEC and IEEE, 2022, p. 23), but it is not clearly detailed why; Barbosa et al. (2006, p. 3) consider regression testing to be a test level.
 - A component is an “entity with discrete structure ... within a system considered at a particular level of analysis” (ISO/IEC, 2023b) and “the terms module, component, and unit [sic] are often used interchangeably or defined to be subelements of one another in different ways depending upon the context” with no standardized relationship (ISO/IEC and IEEE, 2017, p. 82). This means unit/component/module testing can refer to the testing of both a module and a specific function in a module (see #14). However, “component” is sometimes defined differently than “module”: “components differ from classical modules for being re-used in different contexts independently of their development” (Baresi and Pezzè, 2006, p. 107), so distinguishing the two may be necessary.
 - A typo in (ISO/IEC and IEEE, 2021, Fig. 2) means that “specification-based techniques” is listed twice, when the latter should be “structure-based techniques”.

- **ISO/IEC and IEEE** define an “extended entry (decision) table” both as a decision table where the “conditions consist of multiple values rather than simple Booleans” (2021, p. 18) and one where “the conditions and actions are generally described but are incomplete” (2017, p. 175).
- **ISO/IEC and IEEE** provide a definition for “inspections and audits” (2017, p. 228), despite also giving definitions for “inspection” (p. 227) and “audit” (p. 36); while the first term *could* be considered a superset of the latter two, this distinction doesn’t seem useful.
- **ISO/IEC and IEEE** say that “test level” and “test phase” are synonyms, both meaning a “specific instantiation of [a] test sub-process” (2017, pp. 469, 470; 2013, p. 9), but there are also alternative definitions for them. “Test level” can also refer to the scope of a test process; for example, “across the whole organization” or only “to specific projects” (2022, p. 24), while “test phase” can also refer to the “period of time in the software life cycle” when testing occurs (2017, p. 470), usually after the implementation phase (2017, pp. 420, 509; Perry, 2006, p. 56).
- **ISO/IEC and IEEE** use the same definition for “partial correctness” (2017, p. 314) and “total correctness” (p. 480).

Also of note: (**ISO/IEC and IEEE, 2022**) and (2021), from the ISO/IEC/IEEE 29119 family of standards, mention the following 23 test approaches without defining them. This means that out of the 114 test approaches they mention, about 20% have no associated definition!

However, the previous version of this standard, (2013), generally explained two, provided references for two, and explicitly defined one of these terms, for a total of five definitions that could (should) have been included in (2022)! These terms have been underlined, *italicized*, and **bolded**, respectively. Additionally, entries marked with an asterisk* were defined (at least partially) in (2017), which would have been available when creating this family of standards. These terms bring the total count of terms that could (should) have been defined to nine; almost 40% of undefined test approaches could have been defined!

- Acceptance Testing*
- Alpha Testing*
- Beta Testing*
- Capture-Replay Driven Testing
- Data-driven Testing
- Error-based Testing
- Factory Acceptance Testing
- Fault Injection Testing

- Functional Suitability Testing (also mentioned but not defined in (ISO/IEC and IEEE, 2017))
- Integration Testing*
- Model Verification
- Operational Acceptance Testing
- Orthogonal Array Testing
- Production Verification Testing
- Recovery Testing* (Failover/Recovery Testing, Back-up/Recovery Testing, **Backup and Recovery Testing***, Recovery*; see Section 2.4.6)
- Response-Time Testing
- *Reviews* (ISO/IEC 20246) (Code Reviews*)
- Scalability Testing (defined as a synonym of “capacity testing”; see Section 2.4.7)
- Statistical Testing
- System Integration Testing (System Integration*)
- System Testing* (also mentioned but not defined in (ISO/IEC and IEEE, 2013))
- *Unit Testing** (IEEE Std 1008-1987, IEEE Standard for Software Unit Testing implicitly listed in the bibliography!)
- User Acceptance Testing

Other Discrepancies from “Meta-Level” Sources

- The SWEBOK Guide V4 defines “privacy testing” as testing that “assess[es] the security and privacy of users’ personal data to prevent local attacks” (Washizaki, 2024, p. 5-10); this seems to overlap (both in scope and name) with the definition of “security testing” in (ISO/IEC and IEEE, 2022): testing “conducted to evaluate the degree to which a test item, [sic] and associated data and information, are protected so that” only “authorized persons or systems” can use them as intended.
- Various sources say that alpha testing is performed by different people, including “only by users within the organization developing the software” (ISO/IEC and IEEE, 2017, p. 17), by “a small, selected group of potential users” (Washizaki, 2024, p. 5-8), or “in the developer’s test environment by roles outside the development organization” (Hamburg and Mogyorodi, 2024).

- While correct, ISTQB’s definition of “specification-based testing” is not helpful: “testing based on an analysis of the specification of the component or system” ([Hamburg and Mogyorodi, 2024](#)).
- “Machine Learning (ML) model testing” and “ML functional performance” are defined in terms of “ML functional performance criteria”, which is defined in terms of “ML functional performance metrics”, which is defined as “a set of measures that relate to the functional correctness of an ML system” ([Hamburg and Mogyorodi, 2024](#)). The use of “performance” (or “correctness”) in these definitions is at best ambiguous and at worst incorrect.
- While ergonomics testing is out of scope (as it tests hardware, not software), its definition of “testing to determine whether a component or system and its input devices are being used properly with correct posture” ([Hamburg and Mogyorodi, 2024](#)) seems to focus on how the system is *used* as opposed to the system *itself*.
- The definition of “math testing” given by [Hamburg and Mogyorodi \(2024\)](#) is too specific to be useful, likely taken from an example instead of a general definition: “testing to determine the correctness of the pay table implementation, the random number generator results, and the return to player computations”.
- A similar issue exists with multiplayer testing, where its definition specifies “the casino game world” ([Hamburg and Mogyorodi, 2024](#)).
- Thirdly, “par sheet testing” from ([Hamburg and Mogyorodi, 2024](#)) seems to refer to this specific example and does not seem more widely applicable, since a “PAR sheet” is “a list of all the symbols on each reel of a slot machine” ([Bluejay, 2024](#)).
- [Hamburg and Mogyorodi \(2024\)](#) describe the term “software in the loop” as a kind of testing, while the source it references seems to describe “Software-in-the-Loop-Simulation” as a “simulation environment” that may support software integration testing ([Knüvener Mackert GmbH, 2022](#), p. 153); is this a testing approach or a tool that supports testing?
- The source cited for the definition of “test type” from ([Hamburg and Mogyorodi, 2024](#)) does not seem to provide a definition itself.
- The same is true for “visual testing”.
- The same is true for “security attack”.
- There is disagreement on the structure of tests; they can either be quite general ([ISO/IEC and IEEE, 2022](#), p. 34) or “organized around a special focus” ([Hamburg and Mogyorodi, 2024](#)).

- While model testing is said to test the object under test, it seems to describe testing the models themselves [Firesmith \(2015, p. 20\)](#); using the models to test the object under test seems to be called “driver-based testing” (p. 33).
- “System testing” is listed as a subtype of “system testing” by [Firesmith \(2015, p. 23\)](#).
- “Hardware-” and “human-in-the-loop testing” have the same acronym: “HIL”¹⁸ ([Firesmith, 2015, p. 23](#)).
- The same is true for “customer” and “contract(ual) acceptance testing” (“CAT”) ([Firesmith, 2015, p. 30](#)).
- The acronym “SoS” is used but not defined by [Firesmith \(2015, p. 23\)](#).
- It is ambiguous whether “tool/environment testing” refers to testing the tools/environment *themselves* or *using* them to test the object under test; the latter is implied, but the wording of its subtypes ([Firesmith, 2015, p. 25](#)) seems to imply the former.
- Performance and security testing are given as subtypes of reliability testing by ([ISO/IEC, 2023a](#)) but these are all listed separately by [Firesmith \(2015, p. 53\)](#).
- The terms “acceleration” and “acoustic tolerance testing” seem to only refer to software testing in ([Firesmith, 2015, p. 56](#)); elsewhere, they seem to refer to testing the acoustic tolerance of rats ([Holley et al., 1996](#)) or the acceleration tolerance of astronauts ([Morgun et al., 1999, p. 11](#)), aviators ([Howe and Johnson, 1995, pp. 27, 42](#)), or catalysts ([Liu et al., 2023, p. 1463](#)), which don’t exactly seem relevant...
- The distinctions between development testing ([ISO/IEC and IEEE, 2017, p. 136](#)), developmental testing ([Firesmith, 2015, p. 30](#)), and developer testing ([Firesmith, 2015, p. 39](#); [Gerrard, 2000a, p. 11](#)) are unclear and seem miniscule.

Other Discrepancies from Textbooks

- “Load testing” is defined as using loads “usually between anticipated conditions of low, typical, and peak usage” ([ISO/IEC and IEEE, 2022, p. 5](#)), while [Patton](#) says the loads should as large as possible ([2006, p. 86](#)).

Other Discrepancies from Other Sources

- [Bas](#) lists “three [backup] location categories: local, offsite and cloud based [sic]” ([2024, p. 16](#)), but does not define or discuss “offsite backups” (pp. 16-17).

¹⁸“HiL” is used for the former by [Preuße et al. \(2012, p. 2\)](#).

- Doğan et al. claim that (Sakamoto et al., 2013) defines “prime path coverage” (2014, p. 184), but it doesn’t.
- “State-based” is misspelled by Kam as “state-base” (2008, pp. 13, 15) and “stated-base” (Tab. 1).
- Kam’s definition of “boundary value testing” says “See *boundary value analysis*,” but this definition is not present (2008).
- Kam also says that the goal of negative testing is “showing that a component or system does not work” (2008, p. 46) which is not true; if robustness is an important quality for the system, then testing the system “in a way for which it was not intended to be used” (Hamburg and Mogyorodi, 2024) (i.e., negative testing) is one way to help test this!
- Availability testing isn’t assigned to a test priority (Gerrard, 2000a, Tab. 2), despite the claim that “the test types¹⁹ have been allocated a slot against the four test priorities” (p. 13); I think usability and/or performance would have made sense.
- “Visual browser validation” is described as both static *and* dynamic in the same table (Gerrard, 2000a, Tab. 2), even though they are implied to be orthogonal classifications: “test types can be static *or* dynamic” (p. 12, emphasis added).
- Gerrard makes a distinction between “transaction verification” and “transaction testing” (2000a, Tab. 2) and uses the phrase “transaction flows” (Fig. 5), but doesn’t explain them.
- The phrase “continuous automated testing” (Gerrard, 2000a, p. 11) is redundant since continuous testing is a sub-category of automated testing (ISO/IEC and IEEE, 2022, p. 35, Hamburg and Mogyorodi, 2024).
- End-to-end functionality testing is *not* indicated to be functionality testing (Gerrard, 2000a, Tab. 2).
- Gerrard’s definition for “security audits” seems too specific, only applying to “the products installed on a site” and “the known vulnerabilities for those products” (2000b, p. 28).

2.5 Definitions

- Software testing: “the process of executing a program with the intent of finding errors” (Peters and Pedrycz, 2000, p. 438) . “Testing can reveal failures, but the faults causing them are what can and must be removed” (Washizaki,

¹⁹“Each type of test addresses a different risk area” (Gerrard, 2000a, p. 12), which is distinct from the notion of “test type” described in IEEE Testing Terminology.

OG Beizer

OG Myers 1976

2024, p. 5-3); it can also include certification, quality assurance, and quality improvement (Washizaki, 2024, p. 5-4). Involves “specific preconditions [and] ... stimuli so that its actual behavior can be compared with its expected or required behavior”, including control flows, data flows, and postconditions (Firesmith, 2015, p. 11), and “an evaluation ... of some aspect of the system or component” based on “results [that] are observed or recorded” (ISO/IEC and IEEE, 2022, p. 10; 2021, p. 6; 2017, p. 465)

OG ISO/IEC
2014

- Test case: “the specification of all the entities that are essential for the execution, such as input values, execution and timing conditions, testing procedure, and the expected outcomes” (Washizaki, 2024, pp. 5-1 to 5-2)
- Defect: “an observable difference between what the software is intended to do and what it does” (Washizaki, 2024, p. 1-1); “can be used to refer to either a fault or a failure, [sic] when the distinction is not important” (Bourque and Fairley, 2014, p. 4-3)

OG?

- Error: “a human action that produces an incorrect result” (van Vliet, 2000, p. 399)
- Fault: “the manifestation of an error” in the software itself (van Vliet, 2000, p. 400); “the *cause* of a malfunction” (Washizaki, 2024, p. 5-3)
- Failure: incorrect output or behaviour resulting from encountering a fault; can be defined as not meeting specifications or expectations and “is a relative notion” (van Vliet, 2000, p. 400); “an undesired effect observed in the system’s delivered service” (Washizaki, 2024, p. 5-3)
- Verification: “the process of evaluating a system or component to determine whether the products of a given development phase satisfy the conditions imposed at the start of that phase” (van Vliet, 2000, p. 400)
- Validation: “the process of evaluating a system or component during or at the end of the development process to determine whether it satisfies specified requirements” (van Vliet, 2000, p. 400)
- Test Suite Reduction: the process of reducing the size of a test suite while maintaining the same coverage (Barr et al., 2015, p. 519); can be accomplished through **Mutation Testing**
- Test Case Reduction: the process of “removing side-effect free functions” from an individual test case to “reduc[e] test oracle costs” (Barr et al., 2015, p. 519)
- Probe: “a statement inserted into a program” for the purpose of dynamic testing (Peters and Pedrycz, 2000, p. 438)

2.5.1 Documentation

- Verification and Validation (V&V) Plan: a document for the “planning of test activities” described by IEEE Standard 1012 (van Vliet, 2000, p. 411)
- Test Plan: “a document describing the scope, approach, resources, and schedule of intended test activities” in more detail than the V&V Plan (van Vliet, 2000, pp. 412-413); should also outline entry and exit conditions for the testing activities as well as any risk sources and levels (Peters and Pedrycz, 2000, p. 445)
- Test Design documentation: “specifies ... the details of the test approach and identifies the associated tests” (van Vliet, 2000, p. 413)
- Test Case documentation: “specifies inputs, predicted outputs and execution conditions for each test item” (van Vliet, 2000, p. 413)
- Test Procedure documentation: “specifies the sequence of actions for the execution of each test” (van Vliet, 2000, p. 413)
- Test Report documentation: “provides information on the results of testing tasks”, addressing software verification and validation reporting (van Vliet, 2000, p. 413)

2.6 General Testing Notes

- The scope of testing is very dependent on what type of software is being tested, as this informs what information/artifacts are available, which approaches are relevant, and which tacit knowledge is present (see #54). For example, a method table is a tool for tracking the “test approaches, testing techniques and test types that are required depending ... on the context of the test object” (Hamburg and Mogyorodi, 2024), although this is more specific to the automotive domain
- “Proving the correctness of software ... applies only in circumstances where software requirements are stated formally” and assumes “these formal requirements are themselves correct” (van Vliet, 2000, p. 398)
- If faults exist in programs, they “must be considered faulty, even if we cannot devise test cases that reveal the faults” (van Vliet, 2000, p. 401)
- Black-box test cases should be created based on the specification *before* creating white-box test cases to avoid being “biased into creating test cases based on how the module works” (Patton, 2006, p. 113)
- Simple, normal test cases (test-to-pass) should always be developed and run before more complicated, unusual test cases (test-to-fail) (Patton, 2006, p. 66)

- “There is no established consensus on which techniques ... are the most effective. The only consensus is that the selection will vary as it should be dependent on a number of factors” (ISO/IEC and IEEE, 2021, p. 128; similar in van Vliet, 2000, p. 440), and it is advised to use many techniques when testing (p. 440). This supports the principle of *independence of testing*: the “separation of responsibilities, which encourages the accomplishment of objective testing” (Hamburg and Mogyorodi, 2024)
- When comparing adequacy criteria, “criterion X is stronger than criterion Y if, for all programs P and all test sets T, X-adequacy implies Y-adequacy” (the “stronger than” relation is also called the “subsumes” relation) (van Vliet, 2000, p. 432); this relation only “compares the thoroughness of test techniques, not their ability to detect faults” (van Vliet, 2000, p. 434)

This should probably be explained after “test adequacy criterion” is defined

2.6.1 Steps to Testing (Peters and Pedrycz, 2000, p. 443)

1. Identify the goal(s) of the test
2. Decide on an approach
3. Develop the tests
4. Determine the expected results
5. Run the tests
6. Compare the expected results to the actual results

2.6.2 Testing Stages

- Unit testing: “testing the individual modules [of a program]” (van Vliet, 2000, p. 438); also called “module testing” (Patton, 2006, p. 109) or “component testing” (Peters and Pedrycz, 2000, p. 444), although Baresi and Pezzè (2006, p. 107) say “components differ from classical modules for being re-used in different contexts independently of their development.” Note that since a *component* is “a part of a system that can be tested in isolation” (Hamburg and Mogyorodi, 2024), this seems like it could apply to the testing of both modules *and* specific functions
- Integration testing: “testing the composition of modules”; done incrementally using *bottom-up* and/or *top-down* testing (van Vliet, 2000, pp. 438-439), although other paradigms for design, such as *big bang* and *sandwich* exist (Peters and Pedrycz, 2000, p. 489). See also (Patton, 2006, p. 109).
 - Bottom-up testing: uses *test drivers*: “tool[s] that generate[] the test environment for a component to be tested” (van Vliet, 2000, p. 410) by “sending test-case data to the modules under test, read[ing] back the results, and verify[ing] that they’re correct” (Patton, 2006, p. 109)

- Top-down testing: uses *test stubs*: tools that “simulate[] the function of a component not yet available” (van Vliet, 2000, p. 410) by providing “fake” values to a given module to be tested (Patton, 2006, p. 110)
- Big bang testing: the process of “integrat[ing] all modules in a single step and test[ing] the resulting system[]” (Peters and Pedrycz, 2000, p. 489). *Although this is “quite challenging and risky” (Peters and Pedrycz, 2000, p. 489), it may be made less so through the ease of generation, and may be more practical as a testing process for Drasil, although the introduction of the test cases themselves may be introduced, at least initially, in a more structured manner; also of note is its relative ease “to test paths” and “to plan and control” (Peters and Pedrycz, 2000, p. 490)*

Q #1: Bring up!

- Sandwich testing: “combines the ideas of bottom-up and top-down testing by defining a certain target layer in the hierarchy of the modules” and working towards it from either end using the relevant testing approach (Peters and Pedrycz, 2000, p. 491)

- System testing: “test[ing] the whole system against the user documentation and requirements specification after integration testing has finished” (van Vliet, 2000, p. 439) ((Patton, 2006, p. 109) says this can also be done on “at least a major portion” of the product); often uses random, but representative, input to test reliability (van Vliet, 2000, p. 439)

Expand on reliability testing (make own section?)

- Acceptance testing: Similar to system testing that is “often performed under supervision of the user organization”, focusing on usability (van Vliet, 2000, p. 439) and the needs of the customer(s) (Peters and Pedrycz, 2000, p. 492)
- Installation testing: Focuses on the portability of the product, especially “in an environment different from the one in which it has been developed” (van Vliet, 2000, p. 439); not one of the four levels of testing identified by the IEEE standard (Peters and Pedrycz, 2000, p. 445)

2.6.3 Test Oracles

A test oracle is a “source of information for determining whether a test has passed or failed” (ISO/IEC and IEEE, 2022, p. 13) or that “the SUT behaved correctly ... and according to the expected outcomes” and can be “human or mechanical” (Washizaki, 2024, p. 5-5). Oracles provide either “a ‘pass’ or ‘fail’ verdict”; otherwise, “the test output is classified as inconclusive” (Washizaki, 2024, p. 5-5). This process can be “deterministic” (returning a Boolean value) or “probabilistic” (returning “a real number in the closed interval [0, 1]”) (Barr et al., 2015, p. 509). Probabilistic test oracles can be used to reduce the computation cost (since test oracles are “typically computationally expensive”) (Barr et al., 2015, p. 509) or in “situations where some degree of imprecision can be tolerated” since they “offer a probability that [a given] test case is acceptable” (Barr et al., 2015, p. 510). The SWEBOK Guide V4 lists “unambiguous requirements specifications, behavioral

models, and code annotations” as examples (Washizaki, 2024, p. 5-5), and Barr et al. provides four categories (2015, p. 510):

- Specified test oracle: “judge[s] all behavioural aspects of a system with respect to a given formal specification” (Barr et al., 2015, p. 510)
- Derived test oracle: any “artefact[] from which a test oracle may be derived—for instance, a previous version of the system” or “program documentation”; this includes Regression Testing, Metamorphic Testing (MT) (Barr et al., 2015, p. 510), and invariant detection (either known in advance or “learned from the program”) (Barr et al., 2015, p. 516)
 - This seems to prove “relative correctness” as opposed to “absolute correctness” (Lahiri et al., 2013, p. 345) since this derived oracle may be wrong!
 - “Two versions can be checked for semantic equivalence to ensure the correctness of [a] transformation” in a process that can be done “incrementally” (Lahiri et al., 2013, p. 345)
 - Note that the term “invariant” may be used in different ways (see (Chalin et al., 2006, p. 348))
- Pseudo-oracle: a type of derived test oracle that is “an alternative version of the program produced independently” (by a different team, in a different language, etc.) (Barr et al., 2015, p. 515). *We could potentially use the programs generated in other languages as pseudo-oracles!*
- Implicit test oracles: detect “‘obvious’ faults such as a program crash” (potentially due to a null pointer, deadlock, memory leak, etc.) (Barr et al., 2015, p. 510)
- “Lack of an automated test oracle”: for example; a human oracle generating sample data that is “realistic” and “valid”, (Barr et al., 2015, pp. 510-511), crowdsourcing (Barr et al., 2015, p. 520), or a “Wideband Delphi”: “an expert-based test estimation technique that ... uses the collective wisdom of the team members” (Hamburg and Mogyorodi, 2024)

see ISO 29119-11

2.6.4 Generating Test Cases

- “Impl[ies] a reduction in human effort and cost, with the potential to impact the test coverage positively”, and a given “policy could be reused in analogous situations which leads to even more efficiency in terms of required efforts” (Moghadam, 2019, p. 1187)
- “A **test adequacy criterion** ... specifies requirements for testing ... and can be used ... as a test case generator. ... [For example, i]f a 100% statement coverage has not been achieved yet, an additional test case is selected that covers one or more statements yet untested” (van Vliet, 2000, p. 402)

- “Test data generators” are mentioned on ([van Vliet, 2000](#), p. 410) but not described

- “Dynamic test generation consists of running a program while simultaneously executing the program symbolically in order to gather constraints on inputs from conditional statements encountered along the execution ([Godefroid and Luchaup, 2011](#), p. 23)

- “Generating tests to detect [loop inefficiencies]” is difficult due to “virtual call resolution”, reachability conditions, and order-sensitivity ([Dhok and Ramanathan, 2016](#), p. 896)
- Can be facilitated by “testing frameworks such as JUnit [that] automate the testing process by writing test code” ([Sakamoto et al., 2013](#), p. 344)
- Assertion checking requires “auxiliary invariants”, and while “many ... can be synthesized automatically by invariant generation methods, the undecidable nature (or the high practical complexity) of assertion checking precludes complete automation for a general class of user-supplied assertions” ([Lahiri et al., 2013](#), p. 345)
 - Differential Assertion Checking (DAC) can be supported by “automatic invariant generation” ([Lahiri et al., 2013](#), p. 345)

- *Automated interface discovery* can be used “for test-case generation for web applications” ([Doğan et al., 2014](#), p. 184)

- “Concrete and symbolic execution” can be used in “a dynamic test generation technique ... for PHP applications” ([Doğan et al., 2014](#), p. 192)

- COBRA is a tool that “generates test cases automatically and applies them to the simulated industrial control system in a SiL Test” ([Preuße et al., 2012](#), p. 2)
- Test case generation is useful for instances where one kind of testing is difficult, but can be generated from a different, simpler kind (e.g., asynchronous testing from synchronous testing ([Jard et al., 1999](#)))

2.7 Static Black-Box (Specification) Testing ([Patton, 2006](#), pp. 56-62)

Most of this section is irrelevant to generating test cases, as they require human involvement (e.g., Pretend to Be the Customer ([Patton, 2006](#), pp. 57-58), Research Existing Standards and Guidelines ([Patton, 2006](#), pp. 58-59)). However, it provides a “Specification Terminology Checklist” ([Patton, 2006](#), p. 61) that includes some keywords that, if found, could trigger an applicable warning to the user (similar to the idea behind the correctness/consistency checks project). In general, each requirement should be unambiguous, testable, binding, and “acceptable

to all stakeholders”, and the “overall collection” should be complete, consistent, and feasible (Washizaki, 2024, p. 1-8):

- **Potentially unrealistic:** always, every, all, none, every, certainly, therefore, clearly, obviously, evidently
- **Potentially vague:** some, sometimes, often, usually, ordinarily, customarily, most, mostly, good, high-quality, fast, quickly, cheap, inexpensive, efficient, small, stable
- **Potentially incomplete:** etc., and so forth, and so on, such as, handled, processed, rejected, skipped, eliminated, if ... then ... (without “else” or “otherwise”), to be determined (van Vliet, 2000, p. 408)

2.7.1 Coverage-Based Testing of Specification (van Vliet, 2000, pp. 425-426)

Requirements can be “depicted as a graph, where the nodes denote elementary requirements and the edges denote relations between [them]” from which test cases can be derived (van Vliet, 2000, p. 425). However, it can be difficult to assess whether a set of equivalence classes are truly equivalent, since the specific data available in each node is not apparent (van Vliet, 2000, p. 426).

2.8 Dynamic Black-Box (Behavioural) Testing (Patton, 2006, pp. 64-65)

This is the process of “entering inputs, receiving outputs, and checking the results” (Patton, 2006, p. 64). (van Vliet, 2000, p. 399) also calls this “functional testing”.

Requirements

- Requirements documentation (definition of what the software does) (Patton, 2006, p. 64); relevant information could be:
 - Requirements: Input-Values and Output-Values
 - Input/output data constraints

2.8.1 Exploratory Testing (Patton, 2006, p. 65)

An alternative to dynamic black-box testing when a specification is not available (Patton, 2006, p. 65). The software is explored to determine its features, and these features are then tested (Patton, 2006, p. 65). Finding any bugs using this method is a positive thing (Patton, 2006, p. 65), since despite not knowing what the software *should* do, you were able to determine that something is wrong.

This is not applicable to Drasil, because not only does it already generate a specification, making this type of testing unnecessary, there is also a lot of human-based trial and error required for this kind of testing (Smith and Carette, 2023).

2.8.2 Equivalence Partitioning/Classing (Patton, 2006, pp. 67-69)

The process of dividing the infinite set of test cases into a finite set that is just as effective (i.e., that reveals the same bugs) (Patton, 2006, p. 67). The opposite of this, testing every combination of inputs, is called “exhaustive testing” and is “probably not feasible” (Washizaki, 2024, p. 5-5; ISO/IEC and IEEE, 2022, p. 4; van Vliet, 2000, p. 421; Peters and Pedrycz, 2000, pp. 439, 461).

Requirements

- Ranges of possible values (Patton, 2006, p. 67); could be obtained through:
 - Input/output data constraints
 - Case statements

2.8.3 Data Testing (Patton, 2006, pp. 70-79)

The process of “checking that information the user inputs [and] results”, both final and intermediate, “are handled correctly” (Patton, 2006, p. 70). This type of testing can also occur at the white-box level, such as the implementation of boundaries (van Vliet, 2000, p. 431) or intermediate values within components.

Boundary Conditions (Patton, 2006, pp. 70-74)

“[S]ituations at the edge of the planned operational limits of the software” (Patton, 2006, p. 72). Often affects types of data (e.g., numeric, speed, character, location, position, size, quantity (Patton, 2006, p. 72)) each with its own set of (e.g., first/last, min/max, start/finish, over/under, empty/full, shortest/longest, slowest/fastest, soonest/latest, largest/smallest, highest/lowest, next-to/farthest-from (Patton, 2006, pp. 72-73)). Data at these boundaries should be included in an equivalence partition, but so should data in between them (Patton, 2006, p. 73). Boundary conditions should be tested using “the valid data just inside the boundary, ... the last possible valid data, and ... the invalid data just outside the boundary” (Patton, 2006, p. 73), and values at the boundaries themselves should still be tested even if they occur “with zero probability”, in case there actually *is* a case where it can occur; this process of testing may reveal it (Peters and Pedrycz, 2000, p. 460).

Requirements

- Ranges of possible values (Patton, 2006, p. 67, 73); could be obtained through:
 - Case statements
 - Input/output data constraints (e.g., inputs that would lead to a boundary output)

Buffer Overruns ([Patton, 2006](#), pp. 201-205) *Buffer overruns* are “the number one cause of software security issues” ([Patton, 2006](#), p. 75). They occur when the size of the destination for some data is smaller than the data itself, causing existing data (including code) to be overwritten and malicious code to potentially be injected ([Patton, 2006](#), p. 202, 204-205). They often arise from bad programming practices in “languages [sic] such as C and C++, that lack safe string handling functions” ([Patton, 2006](#), p. 201). Any unsafe versions of these functions that are used should be replaced with the corresponding safe versions ([Patton, 2006](#), pp. 203-204).

Sub-Boundary Conditions ([Patton, 2006](#), pp. 75-77)

Boundary conditions “that are internal to the software [but] aren’t necessarily apparent to an end user” ([Patton, 2006](#), p. 75). These include powers of two ([Patton, 2006](#), pp. 75-76) and ASCII and Unicode tables ([Patton, 2006](#), pp. 76-77).

While this is of interest to the domain of scientific computing, this is too involved for Drasil right now, and the existing software constraints limit much of the potential errors from over/underflow ([Smith and Carette, 2023](#)). Additionally, strings are not really used as inputs to Drasil and only occur in output with predefined values, so testing these values are unlikely to be fruitful.

There also exist sub-boundary conditions that arise from “complex” requirements, where behaviour depends on multiple conditions ([van Vliet, 2000](#), p. 430). These “error prone” points around these boundaries should be tested ([van Vliet, 2000](#), p. 430) as before: “the valid data just inside the boundary, ... the last possible valid data, and ... the invalid data just outside the boundary” ([Patton, 2006](#), p. 73). In this type of testing, the second type of data is called an “ON point”, the first type is an “OFF point” for the domain on the *other* side of the boundary, and the third type is an “OFF point” for the domain on the *same* side of the boundary ([van Vliet, 2000](#), p. 430).

Requirements

- Increased knowledge of data type structures (e.g., monoids, rings, etc. ([Smith and Carette, 2023](#))); this would capture these sub-boundaries, as well as other information like relevant tests cases, along with our notion of these data types ([Space](#))

Default, Empty, Blank, Null, Zero, and None ([Patton, 2006](#), pp. 77-78)

These should be their own equivalence class, since “the software usually handles them differently” than “the valid cases or ... invalid cases” ([Patton, 2006](#), p. 78).

Since these values may not always be applicable to a given scenario (e.g., a test case for zero doesn’t make sense if there is a constraint that the value in question cannot be zero), the user should likely be able to select categories of tests to generate instead of Drasil just generating all possible test cases based on the inputs ([Smith and Carette, 2023](#)).

Requirements

- Knowledge of an “empty” value for each **Space** (stored alongside each type in **Space**?)
- Knowledge of how input data could be omitted from an input (e.g., a missing command line argument, an empty line in a file); could be obtained from:
 - User responsibilities
- Knowledge of how a programming language deals with **Null** values and how these can be passed as arguments

Invalid, Wrong, Incorrect, and Garbage Data (Patton, 2006, pp. 78-79)

This is testing-to-fail (Patton, 2006, p. 77).

Requirements This seems to be the most open-ended category of testing.

- Specification of correct inputs that can be ignored; could be obtained through:
 - Input/output data constraints (e.g., inputs that would lead to a violated output constraint)
 - Type information for each input (e.g., passing a string instead of a number)

Syntax-Driven Testing (Peters and Pedrycz, 2000, pp. 448-449)

If the inputs to the system “are described by a certain grammar” (Peters and Pedrycz, 2000, p. 448), “test cases ... [can] be designed according to the syntax or constraint of input domains defined in requirement specification” (Intana et al., 2020, p. 260).

Investigate this source more!

Decision Table-Based Testing (Peters and Pedrycz, 2000, pp. 448, 450-453)

“When the original software requirements have been formulated in the format of ‘if-then’ statements,” a decision table can be created with a column for each test situation (Peters and Pedrycz, 2000, p. 448). “The upper part of the column contains conditions that must be satisfied. The lower portion of a decision table specifies the action that results from the satisfaction of conditions in a rule” (from the specification) (Peters and Pedrycz, 2000, p. 450).

2.8.4 State Testing (Patton, 2006, pp. 79-87)

The process of testing “the program’s logic flow through its various states” (Patton, 2006, p. 79) by checking that state variables are correct after different transitions (p. 83). This is usually done by creating a state transition diagram that includes:

- Every possible unique state
- The condition(s) that take(s) the program between states
- The condition(s) and output(s) when a state is entered or exited

to map out the logic flow from the user's perspective (Patton, 2006, pp. 81-82). Next, these states should be partitioned using one (or more) of the following methods:

1. Test each state once
2. Test the most common state transitions
3. Test the least common state transitions
4. Test all error states and error return transitions
5. Test random state transitions (Patton, 2006, pp. 82-83)

For all of these tests, the values of the state variables should be verified (Patton, 2006, p. 83).

Requirements

- Knowledge of the different states of the program (Patton, 2006, p. 82); could be obtained through:
 - The program's modules and/or functions
 - The program's exceptions
- Knowledge about the different state transitions (Patton, 2006, p. 82); could be obtained through:
 - Testing the state transitions near the beginning of a workflow more?

Performance Testing

Testing to determine how efficiently software uses resources (including time and capacity) "when accomplishing its designated functions" (Hamburg and Mogyorodi, 2024).

OG ISO 25010?

Originally used a very vague definition from (Peters and Pedrycz, 2000, p. 447); re-investigate!

Testing States to Fail (Patton, 2006, pp. 84-87)

The goal here is to try and put the program in a fail state by doing things that are out of the ordinary. These include:

- Race Conditions and Bad Timing (Patton, 2006, pp. 85-86) (Is this relevant to our examples?)

- Repetition Testing: “doing the same operation over and over”, potentially up to “thousands of attempts” (Patton, 2006, p. 86)
- Stress Testing: “running the software under less-than-ideal conditions” to see how it functions (Patton, 2006, p. 86)
- Load testing: running the software with as large of a load as possible (e.g., large inputs, many peripherals) (Patton, 2006, p. 86)

Requirements

- Repetition Testing: The types of operations that are likely to lead to errors when repeated (e.g., overwriting files?)
- Stress testing: can these be automated with pytest or are they outside our scope?
- Load testing: Knowledge about the types of inputs that could overload the system (e.g., upper bounds on values of certain types)

Investigate

2.8.5 Other Black-Box Testing (Patton, 2006, pp. 87-89)

- Act like an inexperienced user (*likely out of scope*)
- Look for bugs where they’ve already been found (*keep track of previous failed test cases? This could pair well with Metamorphic Testing (MT)!*)
- Think like a hacker (*likely out of scope*)
- Follow experience (*implicitly done by using Drasil*)

2.9 Static White-Box Testing (Structural Analysis) (Patton, 2006, pp. 91-104)

White-box testing is also called “glass box testing” (Peters and Pedrycz, 2000, p. 439). (Peters and Pedrycz, 2000, p. 447) claims that “structural testing subsumes white box testing”, but I am unsure if this is a meaningful statement; they seem to describe the same thing to me, especially since it says “structure tests are aimed at exercising the internal logic of a software system” and “in white box testing ..., using detailed knowledge of code, one creates a battery of tests in such a way that they exercise all components of the code (say, statements, branches, paths)” on the same page!

Q #2: Is this true?

There are also some more specific categories of this, such as Scenario-Based Evaluation (van Vliet, 2000, pp. 417-418) and Stepwise Abstraction (van Vliet, 2000, pp. 419-420), that could be investigated further.

Do this!

- “The process of carefully and methodically reviewing the software design, architecture, or code for bugs without executing it” (Patton, 2006, p. 92)

- Less common than black-box testing, but often used for “military, financial, factory automation, or medical software, ... in a highly disciplined development model” or when “testing software for security issues” (Patton, 2006, p. 91); often avoided because of “the misconception that it’s too time-consuming, too costly, or not productive” (Patton, 2006, p. 92)
- Especially effective early on in the development process (Patton, 2006, p. 92)
- Can “find bugs that would be difficult to uncover or isolate with dynamic black-box testing” and “gives the team’s black-box testers ideas for test cases to apply” (Patton, 2006, p. 92)
- Largely “done by the language compiler” or by separate tools (van Vliet, 2000, pp. 413-414)

2.9.1 Reviews (Patton, 2006, pp. 92-95), (van Vliet, 2000, pp. 415-417), (Peters and Pedrycz, 2000, pp. 482-485)

- “The process under which static white-box testing is performed” (Patton, 2006, p. 92); consists of four main parts:
 1. Identify Problems: Find what is wrong or missing
 2. Follow Rules: There should be a structure to the review, such as “the amount of code to be reviewed ..., how much time will be spent ..., what can be commented on, and so on”, to set expectations; “if a process is run in an ad-hoc fashion, bugs will be missed and the participants will likely feel that the effort was a waste of time”
 3. Prepare: Based on the participants’ roles, they should know what they will be contributing during the actual review; “most of the problems found through the review process are found during preparation”
 4. Write a Report: A summary should be created and provided to the rest of the development team so that they know what problems exist, where they are, etc. (Patton, 2006, p. 93)
- Reviews improve communication, learning, and camaraderie, as well as the quality of code *even before the review*: if a developer “knows that his work is being carefully reviewed by his peers, he might make an extra effort to ... make sure that it’s right” (Patton, 2006, pp. 93-94)
- Many forms:
 - Peer Review: Also called “buddy review” (Patton, 2006, p. 94). The most informal review at the smallest scale (Patton, 2006, p. 94). One variation is where a group of two or three people go through code that one of them wrote (Patton, 2006, p. 94). Another is to have each

person in a larger group submit “a ‘best’ program and one of lesser quality”, randomly distribute all programs to be assessed by two people in the group, and return all feedback anonymously to the appropriate developer (van Vliet, 2000, p. 414)

- Walkthrough: The author of the code presents it line by line to a small group that “question anything that looks suspicious” (Patton, 2006, p. 95); this is done by using test data to “walk through” the execution of the program (van Vliet, 2000, p. 416). A more structured walkthrough may have specific roles (presenter, coordinator, secretary, maintenance oracle, standards bearer, and user representative) (Peters and Pedrycz, 2000, p. 484)
- Inspection: Someone who is *not* the author of the code presents it to a small group of people (Patton, 2006, p. 95); the author should be “a largely silent observer” who “may be consulted by the inspectors” (van Vliet, 2000, p. 415). Each member has a role, which may be tied to a different perspective (e.g., designer, implementer, tester, (Peters and Pedrycz, 2000, p. 439) user, or product support person) (Patton, 2006, p. 95). Changes are made based on issues identified *after* the inspection (van Vliet, 2000, p. 415), and a reinspection may take place (Patton, 2006, p. 95); one guideline is to reinspect 100% of the code “[i]f more than 5% of the material inspected has been reworked” (Peters and Pedrycz, 2000, p. 483).
- Can use various tools (see Section 2.9.2) and Generic Code Review Checklist
- *Could be used to evaluate Drasil and/or generated code, but couldn't be automated due to the human element*

2.9.2 Coding Standards and Guidelines (Patton, 2006, pp. 96-99)

- Code may work but still be incorrect if it doesn't meet certain criteria, since these affect its reliability, readability, maintainability, and/or portability; e.g., the `goto`, `while`, and `if-else` commands in C can cause bugs if used incorrectly (Patton, 2006, p. 96)
- These guidelines can range in strictness and formality, as long as they are agreed upon and followed (Patton, 2006, p. 96)
- This could be checked using linters

2.9.3 Generic Code Review Checklist (Patton, 2006, pp. 99-103)

This shouldn't really be at the same level as **Reviews**, but I didn't want to fight with more subsections yet

This shouldn't really be at the same level as **Reviews**, but I didn't want to fight with more subsections yet

- Data reference errors: “bugs caused by using a variable, constant, ... [etc.] that hasn’t been properly declared or initialized” for its context (Patton, 2006, p. 99)
- Data declaration errors: bugs “caused by improperly declaring or using variables or constants” (Patton, 2006, p. 100)
- Computation errors: “essentially bad math”; e.g., type mismatches, over/underflow, zero division, out of meaningful range (Patton, 2006, p. 101)
- Comparison errors: “very susceptible to boundary condition problems”; e.g., correct inclusion, floating point comparisons (Patton, 2006, p. 101)
- Control flow errors: bugs caused by “loops and other control constructs in the language not behaving as expected” (Patton, 2006, p. 102)
- Subroutine parameter errors: bugs “due to incorrect passing of data to and from software subroutines” (Patton, 2006, p. 102) (could also be called “interface errors” (van Vliet, 2000, p. 416))
- Input/output errors: e.g., how are errors handled? (Patton, 2006, pp. 102-103)
- ASCII character handling, portability, compilation warnings (Patton, 2006, p. 103)

Requirements

- Data reference errors: know what operations are allowed for each type and check that values are only used for those operations
- Data declaration errors: I think this will mainly be covered by checking for data reference errors and by our generator (e.g., no typos in type names)
- Computation errors: partially tested dynamically by system tests, but could also more formally check for things like type mismatches (does GOOL do this already?) or if divisors can ever be zero
- Comparison errors: I think this would mainly have to be done manually (maybe except for checking for (in)equality between values where it can never occur), but we may be able to generate a summary of all comparisons for manual verification
- Control flow errors: mostly irrelevant since we don’t implement loops yet; would this include system tests?
- Subroutine parameter errors: we could check the types of values returned by a subroutine with the expected type (at least for languages like Python)
- Input/output errors: knowledge of (and more formal specification of) requirements would be needed here

- ASCII character handling, portability, compilation warnings: we could automatically check that the compiler (for languages that meaningfully have a compile stage) doesn't output any warnings (e.g., by saving output to a file and checking it is what is expected from a normal compilation); do we have any string inputs?

2.9.4 Correctness Proofs (van Vliet, 2000, pp. 418-419)

Requires a formal specification (van Vliet, 2000, p. 418) and uses “highly formal methods of logic” (Peters and Pedrycz, 2000, p. 438) to prove the existence of “an equivalence between the program and its specification” (p. 485). It is not often used and its value is “sometimes disputed” (van Vliet, 2000, p. 418). *Could be useful for Drasil down the road if we can specify requirements formally, and may overlap with others' interests in the areas of logic and proof-checking.*

Does symbolic execution belong here? Investigate from textbooks

2.10 Dynamic White-Box (Structural) Testing (Patton, 2006, pp. 105-121)

“Using information you gain from seeing what the code does and how it works to determine what to test, what not to test, and how to approach the testing” (Patton, 2006, p. 106).

2.10.1 Code Coverage (Patton, 2006, pp. 117-121) or Control-Flow Coverage (van Vliet, 2000, pp. 421-424)

“[T]est[ing] the program's states and the program's flow among them” (Patton, 2006, p. 117); allows for redundant and/or missing test cases to be identified (Patton, 2006, p. 118). Coverage-based testing is often based “on the notion of a control graph ... [where] nodes denote actions, ... (directed) edges connect actions with subsequent actions (in time) ... [and a] path is a sequence of nodes connected by edges. The graph may contain cycles ... [which] correspond to loops ...” (van Vliet, 2000, pp. 420-421). “A cycle is called *simple* if its inner nodes are distinct and do not include [the node at the beginning/end of the cycle]” (van Vliet, 2000, p. 421, emphasis added). If there are multiple actions represented as nodes that occur one after another, they may be collapsed into a single node (van Vliet, 2000, p. 421).

We discussed that generating infrastructure for reporting coverage may be a worthwhile goal, and that it can be known how to increase certain types of coverage (since we know the structure of the generated code, to some extent, beforehand), but I'm not sure if all of these are feasible/worthwhile to get to 100% (e.g., path coverage (van Vliet, 2000, p. 421)).

- Statement/line coverage: attempting to “execute every statement in the program at least once” (Patton, 2006, p. 119)

OG Miller et al.,
1994

– Weaker than (van Vliet, 2000, p. 421) and “only about 50% as effective as branch coverage” (Peters and Pedrycz, 2000, p. 481)

OG Miller et al.,
1994

– Requires 100% coverage to be effective (Peters and Pedrycz, 2000, p. 481)

OG Miller et al.,
1994

– “[C]an be used at the module level with less than 5000 lines of code”²⁰ (Peters and Pedrycz, 2000, p. 481)

– Doesn’t guarantee correctness (van Vliet, 2000, p. 421)

- Branch coverage: attempting to, “at each branching node in the control graph, ... [choose] all possible branches ... at least once” (van Vliet, 2000, p. 421)

– Weaker than path coverage (van Vliet, 2000, p. 433), although (Patton, 2006, p. 119) says it is “the simplest form of path testing” (*I don’t think this is true*)

– Requires at least 85% coverage to be effective and is “most effective ... at the module level” (Peters and Pedrycz, 2000, p. 481)

OG Miller et al.,
1994

– Cyclomatic-number criterion: an adequacy criterion that requires that “all linearly-independent paths are covered” (van Vliet, 2000, p. 423); results in complete branch coverage

– Doesn’t guarantee correctness (van Vliet, 2000, p. 421)

- Path coverage: “[a]ttempting to cover all the paths in the software” (Patton, 2006, p. 119); I always thought the “path” in “path coverage” was a path from program start to program end, but van Vliet seems to use the more general definition (which is, albeit, sometimes valid, like in “du-path”) of being any subset of a program’s execution (see (van Vliet, 2000, p. 420))

Q #3: How do
we decide on our
definition?

– The number of paths to test can be bounded based on its structure and can be approached by dividing the system into subgraphs and computing the bounds of each individually (Peters and Pedrycz, 2000, pp. 471-473); this is less feasible if a loop is present (Peters and Pedrycz, 2000, pp. 473-476) since “a loop often results in an infinite number of possible paths” (van Vliet, 2000, p. 421)

– van Vliet claims that if this is done completely, it “is equivalent to exhaustively testing the program” (van Vliet, 2000, p. 421); however, this overlooks the effect of inputs on behaviour as pointed out in (Peters and Pedrycz, 2000, pp. 466-467). Exhaustive testing requires both full path coverage *and* every input to be checked

– Generally “not possible” to achieve completely due to the complexity of loops, branches, and potentially unreachable code (van Vliet, 2000,

²⁰The US Software Engineering Institute has a checklist for determining which types of lines of code are included when counting (Fenton and Pfleeger, 1997, pp. 30-31).

p. 421); even infeasible paths (“control flow paths that cannot be exercised by any input data” (Washizaki, 2024, p. 5-5)) must be checked for full path coverage to be achieved (Peters and Pedrycz, 2000, p. 439), presenting “a “significant problem in path-based testing” (Washizaki, 2024, p. 5-5)!

- Usually “limited to a few functions with life criticality features (medical systems, real-time controllers)” (Peters and Pedrycz, 2000, p. 481)

- (Multiple) condition coverage: “takes the extra conditions on the branch statements into account” (e.g., all possible inputs to a Boolean expression) (Patton, 2006, p. 120)
 - “Also known as **extended branch coverage**” (van Vliet, 2000, p. 422)
 - Does not subsume and is not subsumed by path coverage (van Vliet, 2000, p. 433)
 - “May be quite challenging” since “if each subcondition is viewed as a single input, then this ... is analogous to exhaustive testing”; however, there is usually a manageable number of subconditions (Peters and Pedrycz, 2000, p. 464)

2.10.2 Data Coverage (Patton, 2006, pp. 114-116)

In addition to **Data Flow Coverage**, there are also some minor forms of data coverage:

- Sub-boundaries: mentioned previously in 2.8.3
- Formulas and equations: related to **computation errors**
- Error forcing: setting variables to specific values to see how errors are handled; any error forced must have a chance of occurring in the real world, even if it is unlikely, and as such, must be double-checked for validity (Patton, 2006, p. 116)

Data Flow Coverage (Patton, 2006, p. 114), (van Vliet, 2000, pp. 424-425)

“[T]racking a piece of data completely through the software” (or a part of it), usually using debugger tools to check the values of variables (Patton, 2006, p. 114).

- “A variable is *defined* in a certain statement if it is assigned a (new) value because of the execution of that statement” (van Vliet, 2000, p. 424)
- “A definition in statement X is *alive* in statement Y if there exists a path from X to Y in which that variable does not get assigned a new value at some intermediate node” (van Vliet, 2000, p. 424)

- A path from a variable's definition to a statement where it is still alive is called **definition-clear** (with respect to this variable) (van Vliet, 2000, p. 424)
- Basic block: “[a] consecutive part[] of code that execute[s] together without any branching” (Peters and Pedrycz, 2000, p. 477)
- Predicate Use (P-use): e.g., the use of a variable in a conditional (van Vliet, 2000, p. 424)
- Computational Use (C-use): e.g., the use of a variable in a computation or I/O statement (van Vliet, 2000, p. 424)
- All-use: either a P-use or a C-use (Peters and Pedrycz, 2000, p. 478)
- DU-path: “a path from a variable definition to [one of] its use[s] that contains no redefinition of the variable” (Peters and Pedrycz, 2000, pp. 478-479)
- The three possible actions on data are defining, killing, and using; “there are a number of anomalies associated with these actions” (Peters and Pedrycz, 2000, pp. 478, 480) (see **Data reference errors**)

Table 2.4 contains different types of data flow coverage criteria, approximately from weakest to strongest, as well as their requirements; all information is adapted from (van Vliet, 2000, pp. 424-425) .

Table 2.4: Types of Data Flow Coverage

Criteria	Requirements
All-defs coverage	Each definition to be used at least once
All-P-uses coverage	A definition-clear path from each definition to each P-use
All-P-uses/Some-C-uses coverage	Same as All-P-uses coverage, but if a definition is only used in computations, at least one definition-clear path to a C-use must be included
All-C-uses/Some-P-uses coverage	A definition-clear path from each definition to each C-use; if a definition is only used in predicates, at least one definition-clear path to a P-use must be included
All-Uses coverage	A definition-clear path between each variable definition to each of its uses and each of these uses' successors
All-DU-Paths coverage	Same as All-Uses coverage, but each path must be cycle-free or a simple cycle

OG Beizer, 1990

Is this sufficient?

Q #4: How is All-DU-Paths coverage stronger than All-Uses coverage according to (van Vliet, 2000, p. 433)?

2.10.3 Fault Seeding (van Vliet, 2000, pp. 427-428)

The introduction of faults to estimate the number of undiscovered faults in the system based on the ratio between the number of new faults and the number of introduced faults that were discovered (which will ideally be small) (van Vliet, 2000, p. 427). Makes many assumptions, including “that both real and seeded faults have the same distribution” and requires careful consideration as to which faults are introduced and how (van Vliet, 2000, p. 427).

2.10.4 Mutation Testing (van Vliet, 2000, pp. 428-429)

“A (large) number of variants of a program is generated”, each differing from the original “slightly” (e.g., by deleting a statement or replacing an operator with another) (van Vliet, 2000, p. 428). These *mutants* are then tested; if set of tests fails to expose a difference in behaviour between the original and many mutants, “then that test set is of low quality” (van Vliet, 2000, pp. 428-429). The goal is to maximize the number of mutants identified by a given test set (van Vliet, 2000, p. 429). **Strong mutation testing** works at the program level while **weak mutation testing** works at the component level (and “is often easier to establish”) (van Vliet, 2000, p. 429).

There is an unexpected byproduct of this form of testing. In some cases of one experiment, “the original program failed, while the modified program [mutant] yielded the right result” (van Vliet, 2000, p. 432)! In addition to revealing shortcomings of a test set, mutation testing can also point the developer(s) in the direction of a better solution!

2.11 Gray-Box Testing (Patton, 2006, pp. 218-220)

A type of testing where “you still test the software as a black-box, but you supplement the work by taking a peek (not a full look, as in white-box testing) at what makes the software work” (Patton, 2006, p. 218). An example of this is looking at HTML code and checking the tags used since “HTML doesn’t execute or run, it just determines how text and graphics appear onscreen” (Patton, 2006, p. 220).

2.12 Regression Testing

Repeating “tests previously executed ... at a later point in development and maintenance” (Peters and Pedrycz, 2000, p. 446) “to make sure there are no unwanted changes [to the software’s behaviour]” (p. 481) (although allowing “some unwanted differences to pass through” is sometimes desired, if tedious (p. 482)). See also (Patton, 2006, p. 232).

- Should be done automatically (Peters and Pedrycz, 2000, p. 481); “[t]est suite augmentation techniques specialise in identifying and generating” new tests

Investigate!

based on changes “that add new features”, but they could be extended to also augment “the expected output” and “the existing *oracles*” (Barr et al., 2015, p. 516)

- Its “effectiveness ... is expressed in terms of”:
 1. difficulty of test suite construction and maintenance
 2. reliability of the testing system (Peters and Pedrycz, 2000, pp. 481-482)
- Various levels:
 - Retest-all: “all tests are rerun”; “this may consume a lot of time and effort” (van Vliet, 2000, p. 411) (*shouldn’t take too much effort, since it will be automated, but may lead to longer CI runtimes depending on the scope of generated tests*)
 - Selective retest: “only some of the tests are rerun” after being selected by a *regression test selection technique*; “[v]arious strategies have been proposed for doing so; few of them have been implemented yet” (van Vliet, 2000, p. 411)

Investigate these

2.13 Metamorphic Testing (MT)

The use of Metamorphic Relations (MRs) “to determine whether a test case has passed or failed” (Kanewala and Yueh Chen, 2019, p. 67). “A[n] MR specifies how the output of the program is expected to change when a specified change is made to the input” (Kanewala and Yueh Chen, 2019, p. 67); this is commonly done by creating an initial test case, then transforming it into a new one by applying the MR (both the initial and the resultant test cases are executed and should both pass) (Kanewala and Yueh Chen, 2019, p. 68). “MT is one of the most appropriate and cost-effective testing techniques for scientists and engineers” (Kanewala and Yueh Chen, 2019, p. 72).

2.13.1 Benefits of MT

- Easier for domain experts; not only do they understand the domain (and its relevant MRs) (Kanewala and Yueh Chen, 2019, p. 70), they also may not have an understanding of testing principles (Kanewala and Yueh Chen, 2019, p. 69). *This majorly overlaps with Drasil!*
- Easy to implement via scripts (Kanewala and Yueh Chen, 2019, p. 69). *Again, Drasil*
- Helps negate the test oracle (Kanewala and Yueh Chen, 2019, p. 69) and output validation (Kanewala and Yueh Chen, 2019, p. 70) problems from **Roadblocks to Testing Scientific Software** (*i.e., the two that are relevant for Drasil*)

- Can extend a limited number of test cases (e.g., from an experiment that was only able to be conducted a few times) (Kanewala and Yueh Chen, 2019, pp. 70-72)
- Domain experts are sometimes unable to identify faults in a program based on its output (Kanewala and Yueh Chen, 2019, p. 71)

2.13.2 Examples of MT

- The distance between two points should be the same regardless of which one is the “start” point (ISO/IEC and IEEE, 2021, p. 22)
- “If a person smokes more cigarettes, then their expected age of death will probably decrease (and not increase)” (ISO/IEC and IEEE, 2021, p. 22)
- “For a function that translates speech into text[,] ... the same speech at different input volume levels ... [should result in] the same text” (ISO/IEC and IEEE, 2021, p. 22)
- The average of a list of numbers should be equal (within floating-point errors) regardless of the list’s order (Kanewala and Yueh Chen, 2019, p. 67)
- For matrices, if $B = B_1 + B_2$, then $A \times B = A \times B_1 + A \times B_2$ (Kanewala and Yueh Chen, 2019, pp. 68-69)
- Symmetry of trigonometric functions; for example, $\sin(x) = \sin(-x)$ and $\sin(x) = \sin(x + 360^\circ)$ (Kanewala and Yueh Chen, 2019, p. 70)
- Modifying input parameters to observe expected changes to a model’s output (e.g., testing epidemiological models calibrated with “data from the 1918 Influenza outbreak”); by “making changes to various model parameters ... authors identified an error in the output method of the agent based epidemiological model” (Kanewala and Yueh Chen, 2019, p. 70)
- Using machine learning to predict likely MRs to identify faults in mutated versions of a program (about 90% in this case) (Kanewala and Yueh Chen, 2019, p. 71)

2.14 Roadblocks to Testing

- Intractability: it is generally impossible to test a program exhaustively (Washizaki, 2024, p. 5-5; ISO/IEC and IEEE, 2022, p. 4; van Vliet, 2000, p. 421; Peters and Pedrycz, 2000, pp. 439, 461)
- Adequacy: to counter the issue of intractability, it is desirable “to reduce the cardinality of the test suites while keeping the same effectiveness in terms of coverage or fault detection rate” (Washizaki, 2024, p. 5-4) which is difficult to do objectively; see also “minimization”, the process of “removing redundant test cases” (Washizaki, 2024, p. 5-4)

- Undecidability (Peters and Pedrycz, 2000, p. 439): it is impossible to know certain properties about a program, such as if it will halt (i.e., the Halting Problem (Gurfinkel, 2017, p. 4)), so “automatic testing can’t be guaranteed to always work” for all properties (Nelson, 1999)

Add paragraph/section number?

2.14.1 Roadblocks to Testing Scientific Software (Kanewala and Yueh Chen, 2019, p. 67)

- “Correct answers are often unknown”: if the results were already known, there would be no need to develop software to model them (Kanewala and Yueh Chen, 2019, p. 67); in other words, complete test oracles don’t exist “in all but the most trivial cases” (Barr et al., 2015, p. 510), and even if they are, the “automation of mechanized oracles can be difficult and expensive” (Washizaki, 2024, p. 5.5)
- “Practically difficult to validate the computed output”: complex calculations and outputs are difficult to verify (Kanewala and Yueh Chen, 2019, p. 67)
- “Inherent uncertainties”: since scientific software models scenarios that occur in a chaotic and imperfect world, not every factor can be accounted for (Kanewala and Yueh Chen, 2019, p. 67)
- “Choosing suitable tolerances”: difficult to decide what tolerance(s) to use when dealing with floating-point numbers (Kanewala and Yueh Chen, 2019, p. 67)
- “Incompatible testing tools”: while scientific software is often written in languages like FORTRAN, testing tools are often written in languages like Java or C++ (Kanewala and Yueh Chen, 2019, p. 67)

Out of this list, only the first two apply. The scenarios modelled by Drasil are idealized and ignore uncertainties like air resistance, wind direction, and gravitational fluctuations. There are not any instances where special consideration for floating-point arithmetic must be taken; the default tolerance used for relevant testing frameworks has been used and is likely sufficient for future testing. On a related note, the scientific software we are trying to test is already generated in languages with widely-used testing frameworks.

Add example

Add source(s)?

2.15 Recommendations

We provide different recommendations for resolving various discrepancies (see Section 2.4). This was done with the goal of organizing them more logically and making them:

1. Atomic (e.g., disaster/recovery testing seems to have two disjoint definitions)




Figure 2.1: Current relations between “recovery testing” terms.




Figure 2.2: Proposed relations between rationalized “recovery testing” terms.

2. Straightforward (e.g., backup and recovery testing’s definition implies the idea of performance, but its name does not; failover/recovery testing, failover and recovery testing, and failover testing are all given separately)
3. Consistent (e.g., backup/recovery testing and failover/recovery testing explicitly exclude an aspect included in its parent disaster/recovery testing)

The following are our recommendations for the areas of **Recovery**, **Scalability**, and **Performance(-related) Testing**, along with graphs of these subsets.

2.15.1 Recovery Testing

The following terms should be used in place of the current terminology to more clearly distinguish between different recovery-related test approaches. The result of the proposed terminology, along with their relations, is demonstrated in **Figures 2.1** and **2.2**.

- **Recoverability Testing:** “Testing ... aimed at verifying software restart capabilities after a system crash or other disaster” (Washizaki, 2024, p. 5-9) including “recover[ing] the data directly affected and re-establish[ing] the desired state of the system” (ISO/IEC, 2023a; similar in Washizaki, 2024, p. 7-10) so that the system “can perform required functions” (ISO/IEC and IEEE, 2017, p. 370). “Recovery testing” will be a synonym, as in (Kam, 2008, p. 47), since it is the more prevalent term throughout various sources, although “recoverability testing” is preferred to indicate that this explicitly focuses on the *ability* to recover, not the *performance* of recovering.
- **Failover Testing:** Testing that “validates the SUT’s ability to manage heavy loads or unexpected failure to continue typical operations” (Washizaki, 2024, p. 5-9) by entering a “backup operational mode in which [these responsibilities] ... are assumed by a secondary system” (Hamburg and Mogyorodi, 2024). This will replace “failover/recovery testing”, since it is more clear, and since this is one way that a system can recover from failure, it will be a subset of “recovery testing”.
- **Transfer Recovery Testing:** Testing to evaluate if, in the case of a failure, “operation of the test item can be transferred to a different operating site and ... be transferred back again once the failure has been resolved” (2021, p. 37). This replaces the second definition of “disaster/recovery testing”, since the first is just a description of “recovery testing”, and could potentially be considered as a kind of failover testing. This may not be intrinsic to the hardware/software (e.g., may be the responsibility of humans/processes).
- **Backup Recovery Testing:** Testing that determines the ability “to restor[e] from back-up memory in the event of failure” (ISO/IEC and IEEE, 2021, p. 37). The qualification that this occurs “without transfer[ing] to a different operating site or back-up system” (p. 37) *could* be made explicit, but this is implied since it is separate from transfer recovery testing and failover testing, respectively.
- **Recovery Performance Testing:** Testing “how well a system or software can recover ... [from] an interruption or failure” (Washizaki, 2024, p. 7-10; similar in ISO/IEC, 2023a) “within specified parameters of time, cost, completeness, and accuracy” (ISO/IEC and IEEE, 2013, p. 2). The distinction between the performance-related elements of recovery testing seemed to be meaningful (see #40), but was not captured consistently by the literature. This will be a subset of “performance-related testing” (see Section 2.15.3) as “recovery testing” is in (ISO/IEC and IEEE, 2022, p. 22). This could also be extended into testing the performance of specific elements of recovery (e.g., failover performance testing), but this be too fine-grained and may better be captured as an **orthogonally derived test approach**.

2.15.2 Scalability Testing

The ambiguity around scalability testing found in the literature is resolved and/or explained by other sources! [ISO/IEC and IEEE](#) give “scalability testing” as a synonym of “capacity testing”, defined as the testing of a system’s ability to “perform under conditions that may need to be supported in the future”, which “may include assessing what level of additional resources (e.g. memory, disk capacity, network bandwidth) will be required to support anticipated future loads” ([2021](#), p. 39). This focus on “the future” is supported by [Hamburg and Mogyorodi](#), who define “scalability” as “the degree to which a component or system can be adjusted for changing capacity” ([2024](#)); the original source they reference agrees, defining it as “the measure of a system’s ability to be upgraded to accommodate increased loads” ([Gerrard and Thompson, 2002](#), p. 381). In contrast, capacity testing focuses on the system’s present state, evaluating the “capability of a product to meet requirements for the maximum limits of a product parameter”, such as the number of concurrent users, transaction throughput, or database size ([ISO/IEC, 2023a](#)). Because of this nuance, it makes more sense to consider these terms separate and *not* synonyms, as done by [Firesmith \(2015, p. 53\)](#) and [Bas \(2024, pp. 22-23\)](#).

Unfortunately, only focusing on future capacity requirements still leaves room for ambiguity. While the previous definition of “scalability testing” includes the external modification of the system, [ISO/IEC](#) describes it as testing the “capability of a product to handle growing or shrinking workloads or to adapt its capacity to handle variability” ([2023a](#)), implying that this is done by the system itself. The potential reason for this is implied by the SWEBOK Guide V4’s claim that one objective of elasticity testing is “to evaluate scalability” ([Washizaki, 2024](#), p. 5-9): [ISO/IEC](#)’s notion of “scalability” likely refers more accurately to “elasticity”! This also makes sense in the context of other definitions provided by the SWEBOK Guide V4:

- **Scalability:** “the software’s ability to increase and scale up on its nonfunctional requirements, such as load, number of transactions, and volume of data” ([Washizaki, 2024](#), p. 5-5). Based on this definition, scalability testing is then a subtype of load testing and volume testing, as well as potentially transaction flow testing.
- **Elasticity Testing²¹:** testing that “assesses the ability of the SUT ... to rapidly expand or shrink compute, memory, and storage resources without compromising the capacity to meet peak utilization” ([Washizaki, 2024](#), p. 5-9). Based on this definition, elasticity testing is then a subtype of memory management testing (with both being a subtype of resource utilization testing) and stress testing.

This distinction is also consistent with how the terms are used in industry: [Pandey](#) says that scalability is the ability to “increase ... performance or efficiency as demand increases over time”, while elasticity allows a system to “tackle changes in the workload [that] occur for a short period” ([2023](#); see [#35](#)).

²¹While this definition seems correct, it only cites a single source **that doesn’t contain the**




Figure 2.3: Current relations between “scalability testing” terms.




Figure 2.4: Proposed relations between rationalized “scalability testing” terms.

To make things even more confusing, the SWEBOK Guide V4 says “scalability testing evaluates the capability to use and learn the system and the user documentation” and “focuses on the system’s effectiveness in supporting user tasks and the ability to recover from user errors” (Washizaki, 2024, p. 5-9). This seems to define “usability testing” with elements of functional and recovery testing, which is completely separate from the definitions of “scalability”, “capacity”, and “elasticity testing”! This definition should simply be disregarded, since it is inconsistent with the rest of the literature. The removal of the previous two synonym relations is demonstrated in Figures 2.3 and 2.4.

2.15.3 Performance(-related) Testing

“Performance testing” is defined as testing “conducted to evaluate the degree to which a test item accomplishes its designated functions” (ISO/IEC and IEEE, 2022, p. 7; 2017, p. 320; similar in 2021, pp. 38-39; Moghadam, 2019, p. 1187). It does this by “measuring the performance metrics” (Moghadam, 2019, p. 1187; similar in Hamburg and Mogyorodi, 2024) (such as the “system’s capacity for

words “elasticity” or “elastic”!




Figure 2.5: Proposed relations between rationalized “performance-related testing” terms.

growth” (Gerrard, 2000b, p. 23)), “detecting the functional problems appearing under certain execution conditions” (Moghadam, 2019, p. 1187), and “detecting violations of non-functional requirements under expected and stress conditions” (Moghadam, 2019, p. 1187; similar in (Washizaki, 2024, p. 5-9)). It is performed either ...

1. ... “within given constraints of time and other resources” (ISO/IEC and IEEE, 2022, p. 7; 2017, p. 320; similar in Moghadam, 2019, p. 1187), or
2. ... “under a ‘typical’ load” (ISO/IEC and IEEE, 2021, p. 39).

It is listed as a subset of performance-related testing, which is defined as testing “to determine whether a test item performs as required when it is placed under various types and sizes of ‘load’ ” (2021, p. 38), along with other approaches like load and capacity testing (ISO/IEC and IEEE, 2022, p. 22). In contrast, Washizaki (2024, p. 5-9) gives “capacity and response time” as examples of “performance characteristics” that performance testing would seek to “assess”, which seems to imply that these are sub-approaches to performance testing instead. This is consistent with how some sources treat “performance testing” and “performance-related testing” as synonyms (Washizaki, 2024, p. 5-9; Moghadam, 2019, p. 1187), as noted in Section 2.4.1. This makes sense because of how general the concept of “performance” is; most definitions of “performance testing” seem to treat it as a category of tests.

However, it seems more consistent to infer that the definition of “performance-related testing” is the more general one often assigned to “performance testing” performed “within given constraints of time and other resources” (ISO/IEC and IEEE, 2022, p. 7; 2017, p. 320; similar in Moghadam, 2019, p. 1187), and “performance testing” is a sub-approach of this performed “under a ‘typical’ load” (ISO/IEC and IEEE, 2021, p. 39). This has other implications for relations between these types of testing; for example, “load testing” usually occurs “between anticipated conditions of low, typical, and peak usage” (ISO/IEC and IEEE, 2022, p. 5; 2021, p. 39; 2017, p. 253; Hamburg and Mogyorodi, 2024), so it is a child of “performance-related testing” and a parent of “performance testing”.

Finally, the “self-loops” mentioned in Section 2.4.2 provide no new information and can be removed. These changes (along with those from Sections 2.15.1 and 2.15.2 made implicitly) result in the relations shown in Figure 2.5.

Bibliography

- Mominul Ahsan, Stoyan Stoyanov, Chris Bailey, and Alhussein Albarbar. Developing Computational Intelligence for Smart Qualification Testing of Electronic Products. *IEEE Access*, 8:16922–16933, January 2020. ISSN 2169-3536. doi: 10.1109/ACCESS.2020.2967858. URL <https://www.webofscience.com/api/gateway?GWVersion=2&SrcAuth=DynamicDOIArticle&SrcApp=WOS&KeyAID=10.1109%2FACCESS.2020.2967858&DestApp=DOI&SrcAppSID=USW2EC0CB9ABcVz5BcZ70BCfllmtJ&SrcJTitle=IEEE+ACCESS&DestDOIRegistrantName=Institute+of+Electrical+and+Electronics+Engineers>. Place: Piscataway.
- Paul Ammann and Jeff Offutt. *Introduction to Software Testing*. Cambridge University Press, Cambridge, United Kingdom, 2nd edition, 2017. ISBN 978-1-107-17201-2. URL <https://eopcw.com/find/downloadFiles/11>.
- Mohammad Bajammal and Ali Mesbah. Web Canvas Testing Through Visual Inference. In *2018 IEEE 11th International Conference on Software Testing, Verification and Validation (ICST)*, pages 193–203, Västerås, Sweden, 2018. IEEE. ISBN 978-1-5386-5012-7. doi: 10.1109/ICST.2018.00028. URL <https://ieeexplore.ieee.org/stamp/stamp.jsp?tp=&arnumber=8367048>.
- Ellen Francine Barbosa, Elisa Yumi Nakagawa, and José Carlos Maldonado. Towards the Establishment of an Ontology of Software Testing. volume 6, pages 522–525, San Francisco, CA, USA, January 2006.
- Luciano Baresi and Mauro Pezzè. An Introduction to Software Testing. *Electronic Notes in Theoretical Computer Science*, 148(1):89–111, February 2006. ISSN 1571-0661. doi: 10.1016/j.entcs.2005.12.014. URL <https://www.sciencedirect.com/science/article/pii/S1571066106000442>.
- Earl T. Barr, Mark Harman, Phil McMinn, Muzammil Shahbaz, and Shin Yoo. The Oracle Problem in Software Testing: A Survey. *IEEE Transactions on Software Engineering*, 41(5):507–525, 2015. doi: 10.1109/TSE.2014.2372785.
- Mykola Bas. *Data Backup and Archiving*. Bachelor thesis, Czech University of Life Sciences Prague, Praha-Suchdol, Czechia, March 2024. URL https://thes.cz/id/60licg/zaverecna_prace_Archive.pdf.
- Josh Berdine, Cristiano Calcagno, and Peter W. O’Hearn. Smallfoot: Modular Automatic Assertion Checking with Separation Logic. In Frank S. de Boer,

- Marcello M. Bonsangue, Susanne Graf, and Willem-Paul de Roever, editors, *Formal Methods for Components and Objects*, pages 115–137, Berlin, Heidelberg, 2006. Springer. ISBN 978-3-540-36750-5. doi: 10.1007/11804192_6.
- Michael Bluejay. Slot Machine PAR Sheets, May 2024. URL <https://easy.vegas/games/slots/par-sheets>.
- Chris Bocchino and William Hamilton. Eastern Range Titan IV/Centaur-TDRSS Operational Compatibility Testing. In *International Telemetering Conference Proceedings*, San Diego, CA, USA, October 1996. International Foundation for Telemetering. ISBN 978-0-608-04247-3. URL https://repository.arizona.edu/bitstream/handle/10150/607608/ITC_1996_96-01-4.pdf?sequence=1&isAllowed=y.
- Pierre Bourque and Richard E. Fairley, editors. *Guide to the Software Engineering Body of Knowledge, Version 3.0*. IEEE Computer Society Press, Washington, DC, USA, 2014. ISBN 0-7695-5166-1. URL www.swebok.org.
- Patrice Chalin, Joseph R. Kiniry, Gary T. Leavens, and Erik Poll. Beyond Assertions: Advanced Specification and Verification with JML and ESC/Java2. In Frank S. de Boer, Marcello M. Bonsangue, Susanne Graf, and Willem-Paul de Roever, editors, *Formal Methods for Components and Objects*, pages 342–363, Berlin, Heidelberg, 2006. Springer. ISBN 978-3-540-36750-5. doi: 10.1007/11804192_16.
- Shauvik Roy Choudhary, Husayn Versee, and Alessandro Orso. A Cross-browser Web Application Testing Tool. In *2010 IEEE International Conference on Software Maintenance*, pages 1–6, Timisoara, Romania, September 2010. IEEE. ISBN 978-1-4244-8629-8. doi: 10.1109/ICSM.2010.5609728. URL <https://ieeexplore.ieee.org/abstract/document/5609728>. ISSN: 1063-6773.
- Monika Dhok and Murali Krishna Ramanathan. Directed Test Generation to Detect Loop Inefficiencies. In *Proceedings of the 2016 24th ACM SIGSOFT International Symposium on Foundations of Software Engineering, FSE 2016*, pages 895–907, New York, NY, USA, November 2016. Association for Computing Machinery. ISBN 978-1-4503-4218-6. doi: 10.1145/2950290.2950360. URL <https://dl.acm.org/doi/10.1145/2950290.2950360>.
- M. Dominguez-Pumar, J. M. Olm, L. Kowalski, and V. Jimenez. Open loop testing for optimizing the closed loop operation of chemical systems. *Computers & Chemical Engineering*, 135:106737, 2020. ISSN 0098-1354. doi: <https://doi.org/10.1016/j.compchemeng.2020.106737>. URL <https://www.sciencedirect.com/science/article/pii/S0098135419312736>.
- Serdar Doğan, Aysu Betin-Can, and Vahid Garousi. Web application testing: A systematic literature review. *Journal of Systems and Software*, 91:174–201, 2014. ISSN 0164-1212. doi: <https://doi.org/10.1016/j.jss.2014.01.010>. URL <https://www.sciencedirect.com/science/article/pii/S0164121214000223>.

- Emelie Engström and Kai Petersen. Mapping software testing practice with software testing research — serp-test taxonomy. In *2015 IEEE Eighth International Conference on Software Testing, Verification and Validation Workshops (ICSTW)*, pages 1–4, 2015. doi: 10.1109/ICSTW.2015.7107470.
- Norman E. Fenton and Shari Lawrence Pfleeger. *Software Metrics: A Rigorous & Practical Approach*. PWS Publishing Company, Boston, MA, USA, 2nd edition, 1997. ISBN 0-534-95425-1.
- Donald G. Firesmith. A Taxonomy of Testing Types, 2015. URL <https://apps.dtic.mil/sti/pdfs/AD1147163.pdf>.
- P. Forsyth, T. Maguire, and R. Kuffel. Real Time Digital Simulation for Control and Protection System Testing. In *2004 IEEE 35th Annual Power Electronics Specialists Conference (IEEE Cat. No.04CH37551)*, volume 1, pages 329–335, Aachen, Germany, 2004. IEEE. ISBN 0-7803-8399-0. doi: 10.1109/PESC.2004.1355765.
- Paul Gerrard. Risk-based E-business Testing - Part 1: Risks and Test Strategy. Technical report, Systeme Evolutif, London, UK, 2000a. URL https://www.agileconnection.com/sites/default/files/article/file/2013/XUS129342file1_0.pdf.
- Paul Gerrard. Risk-based E-business Testing - Part 2: Test Techniques and Tools. Technical report, Systeme Evolutif, London, UK, 2000b. URL wenku.uml.com.cn/document/test/EBTestingPart2.pdf.
- Paul Gerrard and Neil Thompson. *Risk-based E-business Testing*. Artech House computing library. Artech House, Norwood, MA, USA, 2002. ISBN 978-1-58053-570-0. URL <https://books.google.ca/books?id=54UKereAdJ4C>.
- Patrice Godefroid and Daniel Luchaup. Automatic Partial Loop Summarization in Dynamic Test Generation. In *Proceedings of the 2011 International Symposium on Software Testing and Analysis, ISSTA '11*, pages 23–33, New York, NY, USA, July 2011. Association for Computing Machinery. ISBN 978-1-4503-0562-4. doi: 10.1145/2001420.2001424. URL <https://dl.acm.org/doi/10.1145/2001420.2001424>.
- W. Goralski. xDSL loop qualification and testing. *IEEE Communications Magazine*, 37(5):79–83, 1999. doi: 10.1109/35.762860.
- Arie Gurfinkel. Testing: Coverage and Structural Coverage, 2017. URL <https://ece.uwaterloo.ca/~agurfink/ece653w17/assets/pdf/W03-Coverage.pdf>.
- Matthias Hamburg and Gary Mogyorodi. ISTQB Glossary, v4.3, 2024. URL https://glossary.istqb.org/en_US/search.
- Matthias Hamburg and Gary Mogyorodi, editors. ISTQB Glossary, v4.3, 2024. URL https://glossary.istqb.org/en_US/search.

- Daniel C Holley, Gary D Mele, and Sujata Naidu. NASA Rat Acoustic Tolerance Test 1994-1995: 8 kHz, 16 kHz, 32 kHz Experiments. Technical Report NASA-CR-202117, San Jose State University, San Jose, CA, USA, January 1996. URL <https://ntrs.nasa.gov/api/citations/19960047530/downloads/19960047530.pdf>.
- R. Brian Howe and Robert Johnson. Research Protocol for the Evaluation of Medical Waiver Requirements for the Use of Lisinopril in USAF Aircrew. Interim Technical Report AL/AO-TR-1995-0116, Air Force Materiel Command, Brooks Air Force Base, TX, USA, November 1995. URL <https://apps.dtic.mil/sti/tr/pdf/ADA303379.pdf>.
- IEEE. IEEE Standard for System and Software Verification and Validation. *IEEE Std 1012-2012 (Revision of IEEE Std 1012-2004)*, 2012. doi: 10.1109/IEEESTD.2012.6204026.
- Adisak Intana, Monchanok Thongthep, Phatcharee Thepnimit, Phaplak Saethapan, and Tanawat Monpipat. SYNTest: Prototype of Syntax Test Case Generation Tool. In *5th International Conference on Information Technology (InCIT)*, pages 259–264. IEEE, 2020. ISBN 978-1-72819-321-2. doi: 10.1109/InCIT50588.2020.9310968.
- ISO. ISO 13849-1:2015 - Safety of machinery –Safety-related parts of control systems –Part 1: General principles for design. *ISO 13849-1:2015*, December 2015. URL <https://www.iso.org/obp/ui#iso:std:iso:13849:-1:ed-3:v1:en>.
- ISO. ISO 21384-2:2021 - Unmanned aircraft systems –Part 2: UAS components. *ISO 21384-2:2021*, December 2021. URL <https://www.iso.org/obp/ui#iso:std:iso:21384:-2:ed-1:v1:en>.
- ISO. ISO 28881:2022 - Machine tools –Safety –Electrical discharge machines. *ISO 28881:2022*, April 2022. URL <https://www.iso.org/obp/ui#iso:std:iso:28881:ed-2:v1:en>.
- ISO/IEC. ISO/IEC TS 20540:2018 - Information technology – Security techniques –Testing cryptographic modules in their operational environment. *ISO/IEC TS 20540:2018*, May 2018. URL <https://www.iso.org/obp/ui#iso:std:iso-iec:ts:20540:ed-1:v1:en>.
- ISO/IEC. ISO/IEC 25010:2023 - Systems and software engineering –Systems and software Quality Requirements and Evaluation (SQuaRE) –Product quality model. *ISO/IEC 25010:2023*, November 2023a. URL <https://www.iso.org/obp/ui/#iso:std:iso-iec:25010:ed-2:v1:en>.
- ISO/IEC. ISO/IEC 25019:2023 - Systems and software engineering –Systems and software Quality Requirements and Evaluation (SQuaRE) –Quality-in-use model. *ISO/IEC 25019:2023*, November 2023b. URL <https://www.iso.org/obp/ui/en/#iso:std:iso-iec:25019:ed-1:v1:en>.

- ISO/IEC and IEEE. ISO/IEC/IEEE International Standard - Systems and software engineering –Software testing –Part 1: General concepts. *ISO/IEC/IEEE 29119-1:2013*, September 2013. doi: 10.1109/IEEESTD.2013.6588537.
- ISO/IEC and IEEE. ISO/IEC/IEEE International Standard - Systems and software engineering–Vocabulary. *ISO/IEC/IEEE 24765:2017(E)*, September 2017. doi: 10.1109/IEEESTD.2017.8016712.
- ISO/IEC and IEEE. ISO/IEC/IEEE International Standard - Software and systems engineering –Software testing –Part 4: Test techniques. *ISO/IEC/IEEE 29119-4:2021(E)*, October 2021. doi: 10.1109/IEEESTD.2021.9591574.
- ISO/IEC and IEEE. ISO/IEC/IEEE International Standard - Systems and software engineering –Software testing –Part 1: General concepts. *ISO/IEC/IEEE 29119-1:2022(E)*, January 2022. doi: 10.1109/IEEESTD.2022.9698145.
- Claude Jard, Thierry Jérón, Lénäïck Tanguy, and César Viho. Remote testing can be as powerful as local testing. In Jianping Wu, Samuel T. Chanson, and Qiang Gao, editors, *Formal Methods for Protocol Engineering and Distributed Systems: Forte XII / PSTV XIX'99*, volume 28 of *IFIP Advances in Information and Communication Technology*, pages 25–40, Beijing, China, October 1999. Springer. ISBN 978-0-387-35578-8. doi: 10.1007/978-0-387-35578-8_2. URL https://doi.org/10.1007/978-0-387-35578-8_2.
- Ben Kam. Web Applications Testing. Technical Report 2008-550, Queen’s University, Kingston, ON, Canada, October 2008. URL <https://research.cs.queensu.ca/TechReports/Reports/2008-550.pdf>.
- Upulee Kanewala and Tsong Yueh Chen. Metamorphic testing: A simple yet effective approach for testing scientific software. *Computing in Science & Engineering*, 21(1):66–72, 2019. doi: 10.1109/MCSE.2018.2875368.
- Knüvener Mackert GmbH. *Knüvener Mackert SPICE Guide*. Knüvener Mackert GmbH, Reutlingen, Germany, 7th edition, 2022. ISBN 978-3-00-061926-7. URL <https://knuevenermackert.com/wp-content/uploads/2021/06/SPICE-BOOKLET-2022-05.pdf>.
- Ivans Kuļešovs, Vineta Arnīcane, Guntis Arnīcans, and Juris Borzovs. Inventory of Testing Ideas and Structuring of Testing Terms. 1:210–227, January 2013.
- Shuvendu K. Lahiri, Kenneth L. McMillan, Rahul Sharma, and Chris Hawblitzel. Differential Assertion Checking. In *Proceedings of the 2013 9th Joint Meeting on Foundations of Software Engineering*, ESEC/FSE 2013, pages 345–355, New York, NY, USA, August 2013. Association for Computing Machinery. ISBN 978-1-4503-2237-9. doi: 10.1145/2491411.2491452. URL <https://dl.acm.org/doi/10.1145/2491411.2491452>.
- LambdaTest. What is Operational Testing: Quick Guide With Examples, 2024. URL <https://www.lambdatest.com/learning-hub/operational-testing>.

- Danye Liu, Shaonan Tian, Yu Zhang, Chaoquan Hu, Hui Liu, Dong Chen, Lin Xu, and Jun Yang. Ultrafine SnPd nanoalloys promise high-efficiency electrocatalysis for ethanol oxidation and oxygen reduction. *ACS Applied Energy Materials*, 6(3):1459–1466, January 2023. doi: <https://doi.org/10.1021/acsaem.2c03355>. URL https://pubs.acs.org/doi/pdf/10.1021/acsaem.2c03355?casa_token=ItHfKxeQNbsAAAAA:8zEdU5hi2HfHsSony3ku-lbH902jkHpA-JZw8jIeODzUvFtSdQRdbYhmVq47aX22igR52o2S22mnC88Mxw. Publisher: ACS Publications.
- Robert Mandl. Orthogonal Latin squares: an application of experiment design to compiler testing. *Communications of the ACM*, 28(10):1054–1058, October 1985. ISSN 0001-0782. doi: [10.1145/4372.4375](https://doi.org/10.1145/4372.4375). URL <https://doi.org/10.1145/4372.4375>.
- Mahshid Helali Moghadam. Machine Learning-Assisted Performance Testing. In *Proceedings of the 2019 27th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering, ESEC/FSE 2019*, pages 1187–1189, New York, NY, USA, 2019. Association for Computing Machinery. ISBN 978-1-4503-5572-8. doi: [10.1145/3338906.3342484](https://doi.org/10.1145/3338906.3342484). URL <https://doi.org/10.1145/3338906.3342484>.
- V. V. Morgun, L. I. Voronin, R. R. Kaspransky, S. L. Pool, M. R. Barratt, and O. L. Novinkov. The Russian-US Experience with Development Joint Medical Support Procedures for Before and After Long-Duration Space Flights. Technical report, NASA, Houston, TX, USA, 1999. URL <https://ntrs.nasa.gov/api/citations/2000085877/downloads/2000085877.pdf>.
- E. E. Mukhin, V. M. Nelyubov, V. A. Yukish, E. P. Smirnova, V. A. Solovei, N. K. Kalinina, V. G. Nagaitsev, M. F. Valishin, A. R. Belozeroval, S. A. Enin, A. A. Borisov, N. A. Deryabina, V. I. Khripunov, D. V. Portnov, N. A. Babinov, D. V. Dokhtarenko, I. A. Khodunov, V. N. Klimov, A. G. Razdobarin, S. E. Alexandrov, D. I. Elets, A. N. Bazhenov, I. M. Bukreev, An P. Chernakov, A. M. Dmitriev, Y. G. Ibragimova, A. N. Koval, G. S. Kurskiev, A. E. Litvinov, K. O. Nikolaenko, D. S. Samsonov, V. A. Senichenkov, R. S. Smirnov, S. Yu Tolstyakov, I. B. Tereschenko, L. A. Varshavchik, N. S. Zhiltsov, A. N. Mokeev, P. V. Chernakov, P. Andrew, and M. Kempnaars. Radiation tolerance testing of piezoelectric motors for ITER (first results). *Fusion Engineering and Design*, 176(article 113017), 2022. ISSN 0920-3796. doi: <https://doi.org/10.1016/j.fuseengdes.2022.113017>. URL <https://www.sciencedirect.com/science/article/pii/S0920379622000175>.
- Randal C. Nelson. Formal Computational Models and Computability, January 1999. URL https://www.cs.rochester.edu/u/nelson/courses/csc_173/computability/undecidable.html.
- Jiantao Pan. Software Testing, 1999. URL http://users.ece.cmu.edu/~koopman/des_s99/sw_testing/.
- Pranav Pandey. Scalability vs Elasticity, February 2023. URL <https://www.linkedin.com/pulse/scalability-vs-elasticity-pranav-pandey/>.

- Bhupesh A. Parate, K.D. Deodhar, and V.K. Dixit. Qualification Testing, Evaluation and Test Methods of Gas Generator for IEDs Applications. *Defence Science Journal*, 71(4):462–469, July 2021. doi: 10.14429/dsj.71.16601. URL <https://publications.drdo.gov.in/ojs/index.php/dsj/article/view/16601>.
- Ron Patton. *Software Testing*. Sams Publishing, Indianapolis, IN, USA, 2nd edition, 2006. ISBN 0-672-32798-8.
- William E. Perry. *Effective Methods for Software Testing*. Wiley Publishing, Inc., Indianapolis, IN, USA, 3rd edition, 2006. ISBN 978-0-7645-9837-1.
- J.F. Peters and W. Pedrycz. *Software Engineering: An Engineering Approach*. Worldwide series in computer science. John Wiley & Sons, Ltd., 2000. ISBN 978-0-471-18964-0.
- Brian J. Pierre, Felipe Wilches-Bernal, David A. Schoenwald, Ryan T. Elliott, Jason C. Neely, Raymond H. Byrne, and Daniel J. Trudnowski. Open-loop testing results for the pacific DC intertie wide area damping controller. In *2017 IEEE Manchester PowerTech*, pages 1–6, 2017. doi: 10.1109/PTC.2017.7980834.
- Sebastian Preuße, Hans-Christian Lapp, and Hans-Michael Hanisch. Closed-loop System Modeling, Validation, and Verification. In *Proceedings of 2012 IEEE 17th International Conference on Emerging Technologies & Factory Automation (ETFA 2012)*, pages 1–8, Krakow, Poland, 2012. IEEE. ISBN 978-1-4673-4736-5. doi: 10.1109/ETFA.2012.6489679. URL <https://ieeexplore.ieee.org/abstract/document/6489679>.
- Kazunori Sakamoto, Kaizu Tomohiro, Daigo Hamura, Hironori Washizaki, and Yoshiaki Fukazawa. POGen: A Test Code Generator Based on Template Variable Coverage in Gray-Box Integration Testing for Web Applications. In Vittorio Cortellessa and Dániel Varró, editors, *Fundamental Approaches to Software Engineering*, pages 343–358, Berlin, Heidelberg, March 2013. Springer Berlin Heidelberg. ISBN 978-3-642-37057-1. URL https://link.springer.com/chapter/10.1007/978-3-642-37057-1_25.
- Raghvinder S. Sangwan and Phillip A. LaPlante. Test-Driven Development in Large Projects. *IT Professional*, 8(5):25–29, October 2006. ISSN 1941-045X. doi: 10.1109/MITP.2006.122. URL <https://ieeexplore.ieee.org/stamp/stamp.jsp?tp=&arnumber=1717338>.
- Sheetal Sharma, Kartika Panwar, and Rakesh Garg. Decision Making Approach for Ranking of Software Testing Techniques Using Euclidean Distance Based Approach. *International Journal of Advanced Research in Engineering and Technology*, 12(2):599–608, February 2021. ISSN 0976-6499. doi: 10.34218/IJARET.12.2.2021.059. URL <https://iaeme.com/Home/issue/IJARET?Volume=12&Issue=2>.
- Spencer Smith and Jacques Carette. Private Communication, July 2023.

- Harry Sneed and Siegfried Göschl. A Case Study of Testing a Distributed Internet-System. *Software Focus*, 1:15–22, September 2000. doi: 10.1002/1529-7950(20009)1:13.3.CO;2-#. URL https://www.researchgate.net/publication/220116945_Testing_software_for_Internet_application.
- Erica Souza, Ricardo Falbo, and Nandamudi Vijaykumar. ROoST: Reference Ontology on Software Testing. *Applied Ontology*, 12:1–32, March 2017. doi: 10.3233/AO-170177.
- Ephraim Suhir, Laurent Bechou, Alain Bensoussan, and Johann Nicolics. Photovoltaic reliability engineering: quantification testing and probabilistic-design-reliability concept. In *Reliability of Photovoltaic Cells, Modules, Components, and Systems VI*, volume 8825, pages 125–138. SPIE, September 2013. doi: 10.1117/12.2030377. URL <https://www.spiedigitallibrary.org/conference-proceedings-of-spie/8825/88250K/Photovoltaic-reliability-engineering--quantification-testing-and-probabilistic-design-reliability/10.1117/12.2030377.full>.
- Guido Tebes, Denis Peppino, Pablo Becker, Gerardo Matturro, Martín Solari, and Luis Olsina. A Systematic Review on Software Testing Ontologies. pages 144–160. August 2019. ISBN 978-3-030-29237-9. doi: 10.1007/978-3-030-29238-6_11.
- Guido Tebes, Luis Olsina, Denis Peppino, and Pablo Becker. TestTDO: A Top-Domain Software Testing Ontology. pages 364–377, Curitiba, Brazil, May 2020a. ISBN 978-1-71381-853-3.
- Guido Tebes, Luis Olsina, Denis Peppino, and Pablo Becker. TestTDO_terms_definitions_vfinal.pdf, February 2020b. URL <https://drive.google.com/file/d/19TWHd50HF04K6PPyVixQzR6c7HjW2kED/view>.
- Daniel Trudnowski, Brian Pierre, Felipe Wilches-Bernal, David Schoenwald, Ryan Elliott, Jason Neely, Raymond Byrne, and Dmitry Kosterev. Initial closed-loop testing results for the pacific DC intertie wide area damping controller. In *2017 IEEE Power & Energy Society General Meeting*, pages 1–5, 2017. doi: 10.1109/PESGM.2017.8274724.
- Kwok-Leung Tsui. An Overview of Taguchi Method and Newly Developed Statistical Methods for Robust Design. *IIE Transactions*, 24(5):44–57, May 2007. doi: 10.1080/07408179208964244. URL <https://doi.org/10.1080/07408179208964244>. Publisher: Taylor & Francis.
- Matheus A. Tunes, Sean M. Drewry, Jose D. Arregui-Mena, Sezer Picak, Graeme Greaves, Luigi B. Cattini, Stefan Pogatscher, James A. Valdez, Saryu Fensin, Osman El-Atwani, Stephen E. Donnelly, Tarik A. Saleh, and Philip D. Edmondson. Accelerated radiation tolerance testing of Ti-based MAX phases. *Materials Today Energy*, 30(article 101186), October 2022. ISSN 2468-6069. doi: <https://doi.org/10.1016/j.mtener.2022.101186>. URL <https://www.sciencedirect.com/science/article/pii/S2468606922002441>.

- Michael Unterkalmsteiner, Robert Feldt, and Tony Gorschek. A Taxonomy for Requirements Engineering and Software Test Alignment. *ACM Transactions on Software Engineering and Methodology*, 23(2):1–38, March 2014. ISSN 1049-331X, 1557-7392. doi: 10.1145/2523088. URL <http://arxiv.org/abs/2307.12477>. arXiv:2307.12477 [cs].
- Petya Valcheva. Orthogonal Arrays and Software Testing. In Dimiter G. Velev, editor, *3rd International Conference on Application of Information and Communication Technology and Statistics in Economy and Education*, volume 200, pages 467–473, Sofia, Bulgaria, December 2013. University of National and World Economy. ISBN 978-954-644-586-5. URL <https://icaictsee-2013.unwe.bg/proceedings/ICAICTSEE-2013.pdf>.
- Hans van Vliet. *Software Engineering: Principles and Practice*. John Wiley & Sons, Ltd., Chichester, England, 2nd edition, 2000. ISBN 0-471-97508-7.
- Hironori Washizaki, editor. *Guide to the Software Engineering Body of Knowledge, Version 4.0*. January 2024. URL <https://waseda.app.box.com/v/SWEBOK4-book>.
- Han Yu, C. Y. Chung, and K. P. Wong. Robust Transmission Network Expansion Planning Method With Taguchi’s Orthogonal Array Testing. *IEEE Transactions on Power Systems*, 26(3):1573–1580, August 2011. ISSN 0885-8950. doi: 10.1109/TPWRS.2010.2082576. URL <https://ieeexplore.ieee.org/stamp/stamp.jsp?tp=&arnumber=5620950>.
- Kaiqiang Zhang, Chris Hutson, James Knighton, Guido Herrmann, and Tom Scott. Radiation Tolerance Testing Methodology of Robotic Manipulator Prior to Nuclear Waste Handling. *Frontiers in Robotics and AI*, 7(article 6), February 2020. ISSN 2296-9144. doi: 10.3389/frobt.2020.00006. URL <https://www.frontiersin.org/articles/10.3389/frobt.2020.00006>.
- Changlin Zhou, Qun Yu, and Litao Wang. Investigation of the Risk of Electromagnetic Security on Computer Systems. *International Journal of Computer and Electrical Engineering*, 4(1):92, February 2012. URL <http://ijcee.org/papers/457-JE504.pdf>. Publisher: IACSIT Press.

Appendix

Source Code A.1: Tests for main with an invalid input file

```
# from
↳ https://stackoverflow.com/questions/54071312/how-to-pass-command-line-arg
## \brief Tests main with invalid input file
# \par Types of Testing:
# Dynamic Black-Box (Behavioural) Testing
# Boundary Conditions
# Default, Empty, Blank, Null, Zero, and None
# Invalid, Wrong, Incorrect, and Garbage Data
# Logic Flow Testing
@mark.parametrize("filename", invalid_value_input_files)
@mark.xfail
def test_main_invalid(monkeypatch, filename):
    # from
    ↳ https://stackoverflow.com/questions/10840533/most-pythonic-way-to-delete-file
    try:
        remove(output_filename)
    except OSError as e: # this would be "except OSError, e:"
        ↳ before Python 2.6
        if e.errno != ENOENT: # no such file or directory
            raise # re-raise exception if a different error
                ↳ occurred

    assert not path.exists(output_filename)

    with monkeypatch.context() as m:
        m.setattr(sys, 'argv', ['Control.py',
            ↳ str(Path("test/test_input") / f"{filename}.txt")])
        Control.main()

    assert not path.exists(output_filename)
```

Source Code A.2: Projectile's choice for constraint violation behaviour in code

```
srsConstraints = makeConstraints Warning Warning,
```

Source Code A.3: Projectile's manually created input verification requirement

```
verifyParamsDesc = foldlSent [S "Check the entered", plural
  → inValue,
  S "to ensure that they do not exceed the" +:+. namedRef (datCon
    → [] []) (plural datumConstraint),
  S "If any of the", plural inValue, S "are out of bounds" `sC`
  S "an", phrase errMsg, S "is displayed" `S.andThe` plural
    → calculation, S "stop"]
```

Source Code A.4: “MultiDefinitions” (MultiDefn) Definition

```
-- | 'MultiDefn's are QDefinition factories, used for showing one
  → or more ways
-- we can define a QDefinition.
data MultiDefn e = MultiDefn{
  -- | UID
  _rUId :: UID,
  -- | Underlying quantity it defines.
  _qd :: QuantityDict,
  -- | Explanation of the different ways we can define a quantity.
  _rDesc :: Sentence,
  -- | All possible ways we can define the related quantity.
  _rvs :: NE.NonEmpty (DefiningExpr e)
}
```

Source Code A.5: Pseudocode: Broken QuantityDict Chunk Retriever

```
retrieveQD :: UID -> ChunkDB -> Maybe QuantityDict
retrieveQD u cdb = do
  (Chunk expectedQd) <- lookup u cdb
  pure expectedQd
```
