

```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/And.hdl
```

```
/**
```

```
 * And gate:
```

```
 * out = 1 if (a == 1 and b == 1)
```

```
 *      0 otherwise
```

```
 */
```

```
CHIP And {
```

```
    IN a, b;
```


```
    OUT out;
```

```
    PARTS:
```

```
    Nand( a = a, b = b, out = w1);
```

```
    Not( in = w1, out = out );
```

```
}
```




```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Not.hdl
```

```
/**
 * Not gate:
 * out = not in
 */
```

```
CHIP Not {
    IN in;
    OUT out;

    PARTS:
    Nand( a = in, b = in, out = out);
}
```




```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Or.hdl
```

```
/**
 * Or gate:
 * out = 1 if (a == 1 or b == 1)
 *      0 otherwise
 */
```

```
CHIP Or {
    IN a, b;
    OUT out;

    PARTS:
        Not( in = a, out = nota);
        Not( in = b, out = notb);
        Nand( a = nota, b = notb, out = out);
}
```




```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Xor.hdl
```

```
/**
 * Exclusive-or gate:
 * out = not (a == b)
 */
```

```
CHIP Xor {
    IN a, b;
    OUT out;

    PARTS:
        Not( in = a, out = nota);
        Not( in = b, out = notb);
        And( a = a, b = notb, out = w1);
        And( a = nota, b = b, out = w2);
        Or( a = w1, b = w2, out = out);
}
```




```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/And16.hdl
```

```
/**
 * 16-bit bitwise And:
 * for i = 0..15: out[i] = (a[i] and b[i])
 */

CHIP And16 {
    IN a[16], b[16];
    OUT out[16];

    PARTS:
    And( a = a[0], b = b[0], out = out[0]);
    And( a = a[1], b = b[1], out = out[1]);
    And( a = a[2], b = b[2], out = out[2]);
    And( a = a[3], b = b[3], out = out[3]);
    And( a = a[4], b = b[4], out = out[4]);
    And( a = a[5], b = b[5], out = out[5]);
    And( a = a[6], b = b[6], out = out[6]);
    And( a = a[7], b = b[7], out = out[7]);
    And( a = a[8], b = b[8], out = out[8]);
    And( a = a[9], b = b[9], out = out[9]);
    And( a = a[10], b = b[10], out = out[10]);
    And( a = a[11], b = b[11], out = out[11]);
    And( a = a[12], b = b[12], out = out[12]);
    And( a = a[13], b = b[13], out = out[13]);
    And( a = a[14], b = b[14], out = out[14]);
    And( a = a[15], b = b[15], out = out[15]);
}
```

And 16




```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Or16.hdl
```

```
/**
 * 16-bit bitwise Or:
 * for i = 0..15 out[i] = (a[i] or b[i])
 */
```

```
CHIP Or16 {
    IN a[16], b[16];
    OUT out[16];

    PARTS:
    Or( a = a[0], b = b[0], out = out[0]);
    Or( a = a[1], b = b[1], out = out[1]);
    Or( a = a[2], b = b[2], out = out[2]);
    Or( a = a[3], b = b[3], out = out[3]);
    Or( a = a[4], b = b[4], out = out[4]);
    Or( a = a[5], b = b[5], out = out[5]);
    Or( a = a[6], b = b[6], out = out[6]);
    Or( a = a[7], b = b[7], out = out[7]);
    Or( a = a[8], b = b[8], out = out[8]);
    Or( a = a[9], b = b[9], out = out[9]);
    Or( a = a[10], b = b[10], out = out[10]);
    Or( a = a[11], b = b[11], out = out[11]);
    Or( a = a[12], b = b[12], out = out[12]);
    Or( a = a[13], b = b[13], out = out[13]);
    Or( a = a[14], b = b[14], out = out[14]);
    Or( a = a[15], b = b[15], out = out[15]);
}
```




```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Or8Way.hdl
```

```
/**
 * 8-way Or:
 * out = (in[0] or in[1] or ... or in[7])
 */
```

```
CHIP Or8Way {
    IN in[8];
    OUT out;

    PARTS:
    Or( a = in[0], b = in[1], out = w1);
    Or( a = w1, b = in[2], out = w2);
    Or( a = w2, b = in[3], out = w3);
    Or( a = w3, b = in[4], out = w4);
    Or( a = w4, b = in[5], out = w5);
    Or( a = w5, b = in[6], out = w6);
    Or( a = w6, b = in[7], out = out);
}
```



```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Not16.hdl
```

```
/**
```

```
 * 16-bit Not:
```

```
 * for i=0..15: out[i] = not in[i]
```

```
 */
```

```
CHIP Not16 {
```

```
    IN in[16];
```

```
    OUT out[16];
```

```
    PARTS:
```

```
    Not( in = in[0], out = out[0]);
```

```
    Not( in = in[1], out = out[1]);
```

```
    Not( in = in[2], out = out[2]);
```

```
    Not( in = in[3], out = out[3]);
```

```
    Not( in = in[4], out = out[4]);
```

```
    Not( in = in[5], out = out[5]);
```

```
    Not( in = in[6], out = out[6]);
```

```
    Not( in = in[7], out = out[7]);
```

```
    Not( in = in[8], out = out[8]);
```

```
    Not( in = in[9], out = out[9]);
```

```
    Not( in = in[10], out = out[10]);
```

```
    Not( in = in[11], out = out[11]);
```


```
    Not( in = in[12], out = out[12]);
```

```
    Not( in = in[13], out = out[13]);
```

```
    Not( in = in[14], out = out[14]);
```

```
    Not( in = in[15], out = out[15]);
```

```
}
```




```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Mux.hdl
```

```
/**
```

```
 * Multiplexor:
```

```
 * out = a if sel == 0
```

```
 *     b otherwise
```

```
 */
```

```
CHIP Mux {
```

```
    IN a, b, sel;
```

```
    OUT out;
```

```
    PARTS:
```


```
    Not( in = sel, out = notsel);
```

```
    And( a = a, b = notsel, out = w1);
```

```
    And( a = b, b = sel, out = w2);
```

```
    Or( a = w1, b = w2, out = out);
```

```
}
```




```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Mux16.hdl
```

```
/**
 * 16-bit multiplexor:
 * for i = 0..15 out[i] = a[i] if sel == 0
 *                      b[i] if sel == 1
 */

CHIP Mux16 {
    IN a[16], b[16], sel;
    OUT out[16];

    PARTS:
    Mux( a = a[0], b = b[0], sel = sel, out = out[0]);
    Mux( a = a[1], b = b[1], sel = sel, out = out[1]);
    Mux( a = a[2], b = b[2], sel = sel, out = out[2]);
    Mux( a = a[3], b = b[3], sel = sel, out = out[3]);
    Mux( a = a[4], b = b[4], sel = sel, out = out[4]);
    Mux( a = a[5], b = b[5], sel = sel, out = out[5]);
    Mux( a = a[6], b = b[6], sel = sel, out = out[6]);
    Mux( a = a[7], b = b[7], sel = sel, out = out[7]);
    Mux( a = a[8], b = b[8], sel = sel, out = out[8]);
    Mux( a = a[9], b = b[9], sel = sel, out = out[9]);
    Mux( a = a[10], b = b[10], sel = sel, out = out[10]);
    Mux( a = a[11], b = b[11], sel = sel, out = out[11]);
    Mux( a = a[12], b = b[12], sel = sel, out = out[12]);
    Mux( a = a[13], b = b[13], sel = sel, out = out[13]);
    Mux( a = a[14], b = b[14], sel = sel, out = out[14]);
    Mux( a = a[15], b = b[15], sel = sel, out = out[15]);
}
```



```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Mux4Way16.hdl
```

```
/**
```

```
 * 4-way 16-bit multiplexor:
```

```
 * out = a if sel == 00
```

```
 *      b if sel == 01
```

```
 *      c if sel == 10
```

```
 *      d if sel == 11
```

```
 */
```

```
CHIP Mux4Way16 {
    IN a[16], b[16], c[16], d[16], sel[2];
    OUT out[16];
```

```
    PARTS:
```


```
    Mux16( a = a, b = b, sel = sel[0], out = w1);
```

```
    Mux16( a = c, b = d, sel = sel[0], out = w2);
```

```
    Mux16( a = w1, b = w2, sel = sel[1], out = out);
```

```
}
```

mux 4 way 16



**these are all
mux16 gates*

```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/Mux8Way16.hdl
```


```
/**
 * 8-way 16-bit multiplexor:
 * out = a if sel == 000
 *      b if sel == 001
 *      etc.
 *      h if sel == 111
 */
```

```
CHIP Mux8Way16 {
    IN a[16], b[16], c[16], d[16],
       e[16], f[16], g[16], h[16],
       sel[3];
    OUT out[16];
```

PARTS:

```
Mux4Way16( a = a, b = b, c = c, d = d, sel = sel[0..1], out = w1);
Mux4Way16( a = e, b = f, c = g, d = h, sel = sel[0..1], out = w2);
Mux16( a = w1, b = w2, sel = sel[2], out = out);
```

```
}
```



```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/DMux.hdl
```

```
/**
```

```
 * Demultiplexor:
```

```
 * {a, b} = {in, 0} if sel == 0
```

```
 *      {0, in} if sel == 1
```

```
 */
```

```
CHIP DMux {
```

```
    IN in, sel;
```

```
    OUT a, b;
```

```
    PARTS:
```


```
    Not( in = sel, out = notsel);
```

```
    And( a = in, b = notsel, out = a);
```

```
    And( a = in, b = sel, out = b);
```

```
}
```

dmux




```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/DMux4Way.hdl
```

```
/**
 * 4-way demultiplexor:
 * {a, b, c, d} = {in, 0, 0, 0} if sel == 00
 *                {0, in, 0, 0} if sel == 01
 *                {0, 0, in, 0} if sel == 10
 *                {0, 0, 0, in} if sel == 11
 */
```

```
CHIP DMux4Way {
    IN in, sel[2];
    OUT a, b, c, d;

    PARTS:
    DMux( in = in, sel = sel[1], a = w1, b = w2);
    DMux( in = w1, sel = sel[0], a = a, b = b);
    DMux( in = w2, sel = sel[0], a = c, b = d);
}
```

dmux 4 way



```
// This file is part of www.nand2tetris.org
// and the book "The Elements of Computing Systems"
// by Nisan and Schocken, MIT Press.
// File name: projects/01/DMux8Way.hdl
```

```
/**
 * 8-way demultiplexor:
 * {a, b, c, d, e, f, g, h} = {in, 0, 0, 0, 0, 0, 0, 0} if sel == 000
 *                               {0, in, 0, 0, 0, 0, 0, 0} if sel == 001
 *                               etc.
 *                               {0, 0, 0, 0, 0, 0, 0, in} if sel == 111
 */
```

```
CHIP DMux8Way {
    IN in, sel[3];
    OUT a, b, c, d, e, f, g, h;

    PARTS:
    DMux4Way( in = in, sel = sel[0..1], a = w1, b = w2, c = w3, d = w4);
    DMux( in = w1, sel = sel[2], a = a, b = e);
    DMux( in = w2, sel = sel[2], a = b, b = f);
    DMux( in = w3, sel = sel[2], a = c, b = g);
    DMux( in = w4, sel = sel[2], a = d, b = h);
}
```

