# 2-4 Trees

2 rules


#### 2 rules

Every node is either a 2, 3, or 4-Node

#### 2 rules


Every node is either a 2, 3, or 4-Node

#### 2-Node




#### 2 rules

• Every node is either a 2, 3, or 4-Node




#### 2 rules


Every node is either a 2, 3, or 4-Node





#### 2 rules

- Every node is either a 2, 3, or 4-Node
- All NULL nodes are on the same level of the tree









All NULL children have certain rules in both tree structures

All NULL children have certain rules in both tree structures

We can turn a R-B tree into a 2-4 and vice versa

All NULL children have certain rules in both tree structures

We can turn a R-B tree into a 2-4 and vice versa

2-4 to R-B

All NULL children have certain rules in both tree structures

We can turn a R-B tree into a 2-4 and vice versa

2-4 to R-B

All 2 nodes become a black node.

All NULL children have certain rules in both tree structures

We can turn a R-B tree into a 2-4 and vice versa

#### 2-4 to R-B

- All 2 nodes become a black node.
- All 3 nodes have one value become a black node and the other a red child of the black node.

All NULL children have certain rules in both tree structures

We can turn a R-B tree into a 2-4 and vice versa

#### 2-4 to R-B

- All 2 nodes become a black node.
- All 3 nodes have one value become a black node and the other a red child of the black node.
- All 4 nodes have the middle value become a black node and the other two a red child of the black node.

All NULL children have certain rules in both tree structures

We can turn a R-B tree into a 2-4 and vice versa

#### 2-4 to R-B

- All 2 nodes become a black node.
- All 3 nodes have one value become a black node and the other a red child of the black node.
- All 4 nodes have the middle value become a black node and the other two a red child of the black node.

In all cases the parent of the node points to the black node.

Insert()

#### Insert()

Find the lowest (non-NULL) node in which the value belongs

#### Insert()

- Find the lowest (non-NULL) node in which the value belongs
- Emplace the node

#### Insert()

- Find the lowest (non-NULL) node in which the value belongs
- Emplace the node
- Fix if the node is a 5-Node

### **Eviction**

Nodes that have too many values can move a value out.

#### **Eviction**

Nodes that have too many values can move a value out.


The problems start at the bottom of the tree, so we propagate the "errors" up.


#### **Eviction**


Nodes that have too many values can move a value out.


The problems start at the bottom of the tree, so we propagate the "errors" up.

One of the middle values can be moved up into the parent.









We could create another 5-node so this is repeated until...

We could create another 5-node so this is repeated until...

• A non-5-node is made

We could create another 5-node so this is repeated until...

- A non-5-node is made
- A new root is made

### Removal

Could be described as a case heavy nightmare

#### Removal

Could be described as a case heavy nightmare

If I have time at the end of the course (not lecture), I will go over 2-4 Removal

#### Removal

Could be described as a case heavy nightmare

If I have time at the end of the course (not lecture), I will go over 2-4 Removal

2-4 Removal won't be tested on in the first exam